



TEST REPORT

No. 2008TAR046

for

AMOI Mobile Co., LTD

Dual mode gsm wcdma mobile phone with bluetooth

Type: WMA8710

with

Hardware Version: V3.0

Software Version: WP3.0_V1.5_HK

Issued Date: Aug 25th, 2008



No. DAT-P-114/01-01

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of TMC Beijing.

Test Laboratory:

TMC Beijing, Telecommunication Metrology Center of Ministry of Information Industry

No. 52, Huayuan Bei Road, Haidian District, Beijing, P. R. China 100083.

Tel:+86(0)10-62303288-2105, Fax:+86(0)10-62304793 Email:welcome@emcite.com. www.emcite.com

©Copyright. All rights reserved by TMC Beijing.

CONTENTS

1. TEST LABORATORY.....	3
1.1. TESTING LOCATION.....	3
1.2. TESTING ENVIRONMENT.....	3
1.3. PROJECT DATA.....	3
1.4. SIGNATURE	3
2. CLIENT INFORMATION.....	4
2.1. APPLICANT INFORMATION.....	4
2.2. MANUFACTURER INFORMATION.....	4
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE)	5
3.1. ABOUT EUT	5
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST	5
3.3. INTERNAL IDENTIFICATION OF AE USED DURING THE TEST.....	5
3.4. GENERAL DESCRIPTION	6
4. REFERENCE DOCUMENTS	6
4.1. REFERENCE DOCUMENTS FOR TESTING.....	6
5. LABORATORY ENVIRONMENT	6
6. SUMMARY OF TEST RESULTS.....	7
7. TEST EQUIPMENTS UTILIZED.....	7
ANNEX A: EUT PHOTOGRAPH.....	9
ANNEX B: MEASUREMENT RESULTS	14
B.1 OUTPUT POWER (§22.913(A)/§24.232(B))	14
B.2 EMISSION LIMT (§2.1051/§24.238).....	16
B.3 CONDUCTED EMISSION.....	23
B.4 FREQUENCY STABILITY (§2.1055/§24.235).....	26
B.5 OCCUPIED BANDWIDTH (§2.1049(H)(I))	28
B.6 EMISSION BANDWIDTH (§22.917(B)/§24.238(B))	34
B.7 BAND EDGE COMPLIANCE.....	40
B.8 CONDUCTED SPURIOUS EMISSION (§2.1057/§22.917/§24.238).....	43
ANNEX C: TEST LAYOUT.....	48

1. Test Laboratory

1.1. Testing Location

Company Name: TMC Beijing, Telecommunication Metrology Center of MII
Address: No 52, Huayuan beilu, Haidian District, Beijing, P.R.China
Postal Code: 100083
Telephone: 00861062303288
Fax: 00861062304793


1.2. Testing Environment

Normal Temperature: 15-35°C
Relative Humidity: 20-75%


1.3. Project data

Testing Start Date: Aug 6,2008
Testing End Date: Aug 21,2008

1.4. Signature



Zi Xiaogang
(Prepared this test report)



Sun Xiangqian
(Reviewed this test report)



Lu Bingsong
Deputy Director of the laboratory
(Approved this test report)

2. Client Information

2.1. Applicant Information

Company Name: AMOI Mobile Co., LTD
Address /Post: 102 Xiaguang Road,Haicang district,Xiamen City,Fujian
Province ,P.R.China
City: Xiamen
Postal Code: 361022
Country: China
Telephone: 0086-592-6516777-3316
Fax: 0086-592-6516007

2.2. Manufacturer Information

Company Name: AMOI Mobile Co., LTD
Address /Post: 102 Xiaguang Road,Haicang district,Xiamen City,Fujian
Province ,P.R.China
City: Xiamen
Postal Code: 361022
Country: China
Telephone: 0086-592-6516777-3316
Fax: 0086-592-6516007

3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description	Dual mode gsm wcdma mobile phone with bluetooth
Model	WMA8710
FCC ID	WGL-WMA8710
Frequency	PCS 1900 MHz
Antenna	Internal
Power supply	Battery or Charger (AC Adaptor)
Output power	23.44 dBm maximum EIRP measured for PCS1900
Extreme vol. Limits	3.5VDC to 4.2VDC (nominal: 3.7 VDC)
Extreme temp. Tolerance	-30°C to +50°C

Note: Photographs of EUT are shown in ANNEX A of this test report. Components list, please refer to documents of the manufacturer; it is also included in the original test record of Telecommunication Metrology Center of MII of People's Republic of China.

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
N13	354541020002841	V3.0	WP3.0_V1.5_HK

*EUT ID: is used to identify the test sample in the lab internally.

3.3. Internal Identification of AE used during the test

AE ID*	Description	SN
AE1	Battery	080506101846
AE2	Travel Adapter	/
AE3	Headset	/

AE1

Model	AH-01
Manufacturer	BYD Co., Ltd
Capacitance	1150mAh
Nominal Voltage	3.7V

AE2

Model	TM350-EU-10PIN
Manufacturer	i.Tech Dynamic Limited
Length of DC line	175cm

AE3

Model	HSE769LR-1
Manufacturer	lianchuang
Length	125cm

*AE ID: is used to identify the test sample in the lab internally.

3.4. General Description

The Equipment Under Test (EUT) is a model of dual mode gsm wcdma mobile phone with integrated antenna. It has Bluetooth, Camera and MP3 function. It consists of Hand Telephone Set and normal options: lithium battery, charger and Headset.

Manual and specifications of the EUT were provided to fulfil the test.

Samples undergoing test were selected by the Client.

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part 24	PERSONAL COMMUNICATIONS SERVICES	V 10.1.06
ANSI/TIA-603-C	Land Mobile FM or PM Communications Equipment Measurement and Performance Standards	2004
ANSI C63.4	Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz	2003

5. LABORATORY ENVIRONMENT

Semi-anechoic chamber (23 meters × 17 meters × 10 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	< ±3.2 dB, 10 m distance, from 30 to 1000 MHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 2000 MHz

Control room did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 35 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω

Conducted chamber did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω

Fully-anechoic chamber (6.8 meters × 3.08 meters × 3.53 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
Uniformity of field strength	Between 0 and 6 dB, from 80 to 2000 MHz

6. SUMMARY OF TEST RESULTS

Items	List	Clause in FCC rules	Verdict
1	Output Power	22.913(a)/24.232(b)	P
2	Emission Limit	2.1051/22.917/24.238	P
3	Conducted Emission	15.107/207	P
4	Frequency Stability	2.1055/24.235	P
5	Occupied Bandwidth	2.1049(h)(i)	P
6	Emission Bandwidth	22.917(b)/24.238(b)	P
7	Band Edge Compliance	22.917(b)/24.238(b)	P
8	Conducted Spurious Emission	2.1057/22.917/24.238	P


7. Test Equipments Utilized


NO.	NAME	TYPE	SERIES NUMBER	PRODUCER	CAL DUE DATE
1	Test Receiver	ESS	847151/015	R&S	2008-10-30
2	Test Receiver	ESI40	831564/002	R&S	2009-2-11
3	BiLog Antenna	3142B	9908-1403	EMCO	2009-1-16
4	BiLog Antenna	3142B	9908-1405	EMCO	2009-9-19
5	Signal Generator	SMT06	831285/005	R&S	2008-12-26
6	Signal Generator	SMP04	100070	R&S	2009-4-20
7	LISN	ESH2-Z5	829991/012	R&S	2008-8
8	Spectrum Analyzer	FSU26	200030	R&S	2009-6-18

9	Universal Radio Communication Tester	CMU200	100680	R&S	2009-8-23
10	Dual-Ridge Waveguide Horn Antenna	3115	9906-5827	EMCO	2009-3
11	Dual-Ridge Waveguide Horn Antenna	3116	2663	EMCO	2009-3
12	Dual-Ridge Waveguide Horn Antenna	3116	2661	EMCO	2009-3
13	Climatic chamber	PL-2G	343074	ESPEC	2009-5-15

ANNEX A: EUT photograph**External Photo****Mobile Phone****Mobile Phone**

**Mobile Phone****Battery**

**Battery****Internal Photo****Mobile phone Disassembly**

**Mobile phone Disassembly****Mobile phone Disassembly**



Mobile phone Disassembly

ANNEX B: MEASUREMENT RESULTS

B.1 OUTPUT POWER (§22.913(a)/§24.232(b))

B.1.1 Summary

During the process of testing, the EUT was controlled via Rhode & Schwarz Digital Radio Communication tester (CMU-200) to ensure max power transmission and proper modulation. This result contains peak output power and EIRP measurements for the EUT.

In all cases, output power is within the specified limits.

B.1.2 Conducted

B.1.2.1 Method of Measurements

The EUT was set up for the max output power with pseudo random data modulation.

The power was measured with Rhode & Schwarz Spectrum Analyzer FSU (peak)

These measurements were done at 3 frequencies, 1850.2 MHz, 1880.0 MHz and 1909.8 MHz for PCS1900 band (bottom, middle and top of operational frequency range).

PCS1900

Limit

Power step	Nominal Peak output power (dBm)	Tolerance (dB)
0	30dBm(1W)*	± 2

*GSM Specification – ETSI EN 300 910 V8.5.1 (2000-11) Section 4.1

Measurement result

GSM

Frequency(MHz)	Conducted Output Power(dBm)
1850.2	28.76
1880.0	28.75
1909.8	28.65

GPRS

Frequency(MHz)	Conducted Output Power(dBm)
1850.2	28.88
1880.0	29.01
1909.8	28.88

EGPRS

Frequency(MHz)	Conducted Output Power(dBm)
1850.2	27.98
1880.0	28.03
1909.8	28.40

B.1.3 Radiated**B.1.3.1 Description**

This is the test for the maximum radiated power from the EUT.

Rule Part 24.232(b) specifies, "Mobile/portable stations are limited to 2 watts e.i.r.p. Peak power" and 24.232(c) specifies that "Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage." Rule Part 22.913(a) specifies "Maximum ERP. The effective radiated power (ERP) of base transmitters and cellular repeaters must not exceed 500 Watts. The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts."

B.1.3.2 Method of Measurement

1. In an anechoic antenna test chamber, a half-wave dipole antenna for the frequency band of interest is placed at the reference centre of the chamber. An RF Signal source for the frequency band of interest is connected to the dipole with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A known (measured) power (P_{in}) is applied to the input of the dipole, and the power received (P_r) at the chamber's probe antenna is recorded.
2. A "reference path loss" is established as $P_{in} + 2.15 - P_r$.
3. The EUT is substituted for the dipole at the reference centre of the chamber and a scan is performed to obtain the radiation pattern.
4. From the radiation pattern, the co-ordinates where the maximum antenna gain occurs are identified.
5. The EUT is then put into pulse mode at its maximum power level (Power Step 0 for PCS1900).
6. "Gated mode" power measurements are performed with the receiving antenna placed at the coordinates determined in Step 3 to determine the output power as defined in Rule 24.232 (b) and (c). The "reference path loss" from Step1 is added to this result.
7. This value is EIRP since the measurement is calibrated using a half-wave dipole antenna of known gain (2.15 dBi) and known input power (P_{in}).
8. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dBi}$.

PCS1900-EIRP 24.232(b)**Limits**

Power Step	Burst Peak EIRP (dBm)
0	$\leq 33\text{dBm}$ (2W)

Measurement result**GSM**

Frequency(MHz)	Peak EIRP(dBm)
1850.2	23.42
1880.0	22.97
1909.8	21.92

GPRS

Frequency(MHz)	Peak EIRP(dBm)
1850.2	23.44
1880.0	22.97
1909.8	22.21

EGPRS

Frequency(MHz)	Peak EIRP(dBm)
1850.2	22.89
1880.0	22.69
1909.8	21.71

ANALYZER SETTINGS: RBW = VBW = 3MHz

B.2 EMISSION LIMIT (§2.1051/§24.238)

B.2.1 Measurement Method

The measurements procedures in TIA-603C-2004 are used.

The spectrum was scanned from 30 MHz to the 10th harmonic of the highest frequency generated within the equipment, which is the transmitted carrier that can be as high as 1910 MHz. The resolution bandwidth is set 1MHz as outlined in Part 24.238. The spectrum was scanned with the mobile station transmitting at carrier frequencies that pertain to low, mid and high channels of the PCS1900 band.


The procedure of radiated spurious emissions is as follows:

a) Pre-calibration

With pre-calibration method, the Radiated Spurious Emissions(RSE) is calculated as,

$$RSE = Rx \text{ (dBuV)} + CL \text{ (dB)} + SA \text{ (dB)} + Gain \text{ (dBi)} - 107 \text{ (dBuV to dBm)}$$


The SA is calibrated using following setup.



b) EUT test

EUT was placed on a 1.5 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the test item for emission measurements. The height of receiving antenna is 1.5m. The test setup refers to figure below. Detected emissions were maximized at each frequency by rotating the test item and

adjusting the receiving antenna polarization. The radiated emission measurements of all non-harmonic and harmonics of the transmit frequency through the 10th harmonic were measured with peak detector and 1MHz bandwidth.



B.2.2 Measurement Limit



Sec. 24.238 Emission Limits.



(a) On any frequency outside a licensee's frequency block (e.g. A, D, B, etc.) within the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least $43 + 10\log(P)$ dB. The specification that emissions shall be attenuated below the transmitter power (P) by at least $43 + 10 \log (P)$ dB, translates in the relevant power range (1 to 0.001 W) to -13 dBm. At 1 W the specified minimum attenuation becomes 43 dB and relative to a 30 dBm (1 W) carrier becomes a limit of -13 dBm. At 0.001 W (0 dBm) the minimum attenuation is 13 dB, which again yields a limit of -13 dBm. In this way a translation of the specification from relative to absolute terms is carried out.



B.2.3 Measurement Results

Radiated emissions measurements were made only at the upper, middle, and lower carrier frequencies of the PCS band (1850.2 MHz, 1880 MHz and 1909.8 MHz). It was decided that measurements at these three carrier frequencies would be sufficient to demonstrate compliance with emissions limits because it was seen that all the significant spurs occur well outside the band and no radiation was seen from a carrier in one block of the PCS1900 into any of the other blocks. The equipment must still, however, meet emissions requirements with the carrier at all frequencies over which it is capable of operating and it is the manufacturer's responsibility to verify this.

NOTE: The spurious emissions were done with different settings, using the relevant pre-amplifiers for the relevant frequency ranges. This is the reason that the graphs show different noise levels.



PCS 1900**B.2.3.1 RADIATED SPURIOUS EMISSIONS-Channel 512: 30MHz – 2GHz****NOTE: peak above the limit line is the Carrier frequency @ ch-512****B.2.3.2 RADIATED SPURIOUS EMISSIONS-Channel 661: 30MHz – 2GHz****NOTE: peak above the limit line is the Carrier frequency @ ch-661**


B.2.3.3 RADIATED SPURIOUS EMISSIONS-Channel 810: 30MHz – 2GHz**NOTE: peak above the limit line is the Carrier frequency @ ch-810****B.2.3.4 RADIATED SPURIOUS EMISSIONS-Channel 512: 2GHz – 18GHz**

B.2.3.5 RADIATED SPURIOUS EMISSIONS-Channel 661: 2GHz – 18GHz**B.2.3.6 RADIATED SPURIOUS EMISSIONS-Channel 810: 2GHz – 18GHz**


B.2.3.7 Radiated spurious emission (18GHz-20GHz)

Note: This plot is valid for low, mid & high channels. It is same as the floor noise.


B.2.3.8 RADIATED SPURIOUS EMISSIONS-EUT in Idle Mode: 30MHz – 2GHz


B.2.3.9 RADIATED SPURIOUS EMISSIONS-EUT in Idle Mode: 2GHz – 18GHz**B.2.3.10 RADIATED SPURIOUS EMISSIONS-EUT in Idle Mode: 18GHz – 20GHz**

Note: It is same as the floor noise.



B.3 CONDUCTED EMISSION (§15.107§15.207)

The measurement procedure in ANSI C63.4-1003 is used. Conducted Emission is measured with travel charger.

B.3.1 Limit

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi -Peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50


* Decreases with logarithm of the frequency

B.3.2 Test Condition

Voltage (V)	Frequency (Hz)
110	60



B.3.3 Measurement result


PCS 1900MHz



MEASUREMENT RESULT: "8TA611_5PC_fin QP"

Frequency MHz	Level dB μ V	Transd dB	Limit dB μ V	Margin dB	Line	PE
0.520000	34.00	10.1	56	22.0	N	GND
0.680000	37.20	10.1	56	18.8	L1	FLO

MP3**Camera**

Bluetooth

B.4 FREQUENCY STABILITY (§2.1055/§24.235)

B.4.1 Method of Measurement

In order to measure the carrier frequency under the condition of AFC lock, it is necessary to make measurements with the EUT in a "call mode". This is accomplished with the use of R&S CMU200 DIGITAL RADIO COMMUNICATION TESTER.

1. Measure the carrier frequency at room temperature.
2. Subject the EUT to overnight soak at -30°C.
3. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on channel 661 for PCS 1900, measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
4. Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
5. Remeasure carrier frequency at room temperature with nominal voltage. Vary supply voltage from minimum voltage to maximum voltage, in 0.1Volt increments remeasuring carrier frequency at each voltage. Pause at nominal voltage for 1 1/2 hours unpowered, to allow any self-heating to stabilize, before continuing.
6. Subject the EUT to overnight soak at +50°C.
7. With the EUT, powered via nominal voltage, connected to the CMU200 and in a simulated call on channel 661 (centre channel), measure the carrier frequency. These measurements should be made within 2 minutes of Powering up the EUT, to prevent significant self-warming.
8. Repeat the above measurements at 10 C increments from +50°C to -30°C. Allow at least 1 1/2 hours at each temperature, unpowered, before making measurements.
9. At all temperature levels hold the temperature to +/- 0.5°C during the measurement procedure.

B.4.2 Measurement Limit

B.4.2.1 For Hand carried battery powered equipment

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. As this transceiver is considered "Hand carried, battery powered equipment" Section 2.1055(d)(2) applies. This requires that the lower voltage for frequency stability testing be specified by the manufacturer. This transceiver is specified to operate with an input voltage of between 3.5VDC and 4.2VDC, with a nominal voltage of 3.7VDC. Operation above or below these voltage limits is prohibited by transceiver software in order to prevent improper operation as well as to protect components from overstress. These voltages represent a tolerance of -10 % and +12.5 %. For the purposes of measuring frequency stability these voltage limits are to be used.

B.4.2.2 For equipment powered by primary supply voltage

According to the JTC standard the frequency stability of the carrier shall be accurate to within 0.1 ppm of the received frequency from the base station. This accuracy is sufficient to meet Sec. 24.235, Frequency Stability. The frequency stability shall be sufficient to ensure that the

fundamental emission stays within the authorized frequency block. For this EUT section 2.1055(d)(1) applies. This requires varying primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

B.4.3 Measurement results

PCS 1900

Frequency Error vs Voltage

Voltage(V)	Frequency error(Hz)	Frequency error(ppm)
3.5	87	0.046
3.7	85	0.045
4.2	81	0.043

Frequency Error vs Temperature


temperature(°C)	Frequency error(Hz)	Frequency error(ppm)
-30	90	0.048
-20	87	0.046
-10	85	0.045
0	84	0.045
10	80	0.043
20	81	0.043
30	82	0.044
40	85	0.045
50	88	0.047

B.5 OCCUPIED BANDWIDTH (§2.1049(h)(i))**B.5.1 Occupied Bandwidth Results**


Similar to conducted emissions; occupied bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of the USPCS frequency band. The table below lists the measured -20dBc BW (99%). Spectrum analyzer plots are included on the following pages.

PCS 1900(99%)

Frequency(MHz)	Occupied Bandwidth (99%)(kHz)
1850.2	246.795
1880.0	248.397
1909.8	245.192


ANALYZER SETTINGS: RBW=VBW=3kHz**PCS 1900****Channel 512-Occupied Bandwidth (99%)**

Channel 661-Occupied Bandwidth (99%)



Date: 7.AUG.2008 02:44:25


Channel 810-Occupied Bandwidth (99%)



Date: 7.AUG.2008 02:45:08


GPRS

Frequency(MHz)	Occupied Bandwidth (99%)(kHz)
1850.2	245.192
1880.0	245.102
1909.8	243.589

ANALYZER SETTINGS: RBW=VBW=3kHz
GPRS
Channel 512-Occupied Bandwidth (99%)



Date: 7.AUG.2008 03:27:19

Channel 661-Occupied Bandwidth (99%)



Date: 7.AUG.2008 03:28:00


Channel 810-Occupied Bandwidth (99%)



Date: 7.AUG.2008 03:29:35


EGPRS

Frequency(MHz)	Occupied Bandwidth (99%)(kHz)
1850.2	240.384
1880.0	245.192
1909.8	246.795

ANALYZER SETTINGS: RBW=VBW=3kHz
EGPRS
Channel 512-Occupied Bandwidth (99%)



Date: 7.AUG.2008 03:32:43

Channel 661-Occupied Bandwidth (99%)



Date: 7.AUG.2008 03:33:19

Channel 810-Occupied Bandwidth (99%)



Date: 7.AUG.2008 03:33:19

B.6 EMISSION BANDWIDTH (§22.917(b)/§24.238(b))

B.6.1 Emission Bandwidth Results

Similar to conducted emissions; Emission bandwidth measurements are only provided for selected frequencies in order to reduce the amount of submitted data. Data were taken at the extreme and mid frequencies of the PCS1900 band. Table below lists the measured -26dBc BW. Spectrum analyzer plots are included on the following pages.


PCS 1900(-26dBc)

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)(kHz)
1850.2	307.692
1880.0	307.692
1909.8	306.090

ANALYZER SETTINGS: RBW=VBW=3kHz;


PCS 1900

Channel 512-Occupied Bandwidth (-26dBc BW)




Date: 7.AUG.2008 02:47:03

Channel 661-Occupied Bandwidth (-26dBc BW)



Date: 7.AUG.2008 02:46:25

Channel 810-Occupied Bandwidth (-26dBc BW)



Date: 7.AUG.2008 02:45:51


GPRS

Frequency(MHz)	Occupied Bandwidth (–26dBc BW)(kHz)
1850.2	304.487
1880.0	309.295
1909.8	309.295


ANALYZER SETTINGS: RBW=VBW=3kHz;

GPRS


Channel 512-Occupied Bandwidth (-26dBc BW)



Date: 7.AUG.2008 03:31:27

Channel 661-Occupied Bandwidth (-26dBc BW)



Date: 7.AUG.2008 03:30:50

Channel 810-Occupied Bandwidth (-26dBc BW)


Date: 7.AUG.2008 03:30:14


EGPRS

Frequency(MHz)	Occupied Bandwidth (-26dBc BW)(kHz)
1850.2	302.885
1880.0	301.282
1909.8	302.885

ANALYZER SETTINGS: RBW=VBW=3kHz;
EGPRS
Channel 512-Occupied Bandwidth (-26dBc BW)



Date: 7.AUG.2008 03:36:24

Channel 661-Occupied Bandwidth (-26dBc BW)



Date: 7.AUG.2008 03:35:27

Channel 810-Occupied Bandwidth (-26dBc BW)




Date: 7.AUG.2008 03:34:59

B.7 BAND EDGE COMPLIANCE (§22.917(b)/§24.238(b))


PCS 1900

LOW BAND EDGE BLOCK-A (PCS-1900)-Channel 512




Date: 7.AUG.2008 03:12:38


HIGH BAND EDGE BLOCK-C (PCS-1900) –Channel 810




Date: 7.AUG.2008 03:13:51

GPRS
LOW BAND EDGE BLOCK-A (PCS-1900)-Channel 512



Date: 7.AUG.2008 03:51:48

HIGH BAND EDGE BLOCK-C (PCS-1900) –Channel 810


Date: 7.AUG.2008 03:52:32

EGPRS
LOW BAND EDGE BLOCK-A (PCS-1900)-Channel 512


Date: 7.AUG.2008 03:53:32

HIGH BAND EDGE BLOCK-C (PCS-1900) –Channel 810


Date: 7.AUG.2008 03:54:15

B.8 CONDUCTED SPURIOUS EMISSION **(§2.1057/§22.917/§24.238)****B.8.1 Measurement Method**

The following steps outline the procedure used to measure the conducted emissions from the EUT.

1. Determine frequency range for measurements: From CFR 2.1057 the spectrum should be investigated from the lowest radio frequency generated in the equipment up to at least the 10th harmonic of the carrier frequency. For the equipment of PCS1900 band, this equates to a frequency range of 30 MHz to 19.1 GHz, data taken from 30 MHz to 20 GHz.
2. Determine EUT transmit frequencies: below outlines the band edge frequencies pertinent to conducted emissions testing.

PCS1900 Transmitter

Channel	Frequency (MHz)
512	1850.2
661	1880.0
810	1909.8

B. 8.2 Measurement Limit

Sec. 24.238 Emission Limits.

(a) On any frequency outside frequency band of the USPCS spectrum, the power of any emission shall be attenuated below the transmitter power (P, in Watts) by at least $43+10\log(P)$ dB. For all power levels +30 dBm to 0 dBm, this becomes a constant specification limit of -13 dBm.

B. 8.3 Measurement result**PCS1900**


Harmonic	Tx ch. 512 Freq. (MHz)	Level (dBm)	Tx ch. 661 Freq. (MHz)	Level (dBm)	Tx ch. 810 Freq. (MHz)	Level (dBm)
2	3700.4	nf	3760	nf	3819.6	nf
3	5550.6	nf	5640	nf	5729.4	nf
4	7400.8	nf	7520	nf	7639.2	nf
5	9251.0	nf	9400	nf	9549.0	nf
6	11101.2	nf	11280	nf	11458.8	nf
7	12951.4	nf	13160	nf	13368.6	nf
8	14801.6	nf	15040	nf	15278.4	nf
9	16651.8	nf	16920	nf	17188.2	nf
10	18502.0	nf	18800	nf	19098.0	nf

nf: Noise floor

B. 8.3.1 Channel 512: 30MHz – 4GHz

Spurious emission limit –13dBm.


NOTE: peak above the limit line is the carrier frequency.



Date: 7.AUG.2008 03:05:29

B. 8.3.2 Channel 512: 4GHz – 20GHz

Spurious emission limit –13dBm.




Date: 7.AUG.2008 03:06:20

B. 8.3.3 Channel 661: 30MHz – 4GHz

Spurious emission limit –13dBm


NOTE: peak above the limit line is the carrier frequency.



Date: 7.AUG.2008 03:07:46

B. 8.3.4 Channel 661: 4GHz –20GHz


Spurious emission limit –13dBm



Date: 7.AUG.2008 03:07:01

B. 8.3.5 Channel 810: 30MHz – 4GHz


Spurious emission limit –13dBm.

NOTE: peak above the limit line is the carrier frequency.


Date: 7.AUG.2008 03:08:27

B. 8.3.6 Channel 810: 4GHz – 20GHz


Spurious emission limit –13dBm.



Date: 7.AUG.2008 03:09:13

B. 8.3.7 Idle mode: 30MHz – 4GHz


Spurious emission limit –13dBm.



Date: 7.AUG.2008 03:10:06

B. 8.3.8 Idle mode: 4GHz – 20GHz

Spurious emission limit -13dBm.



Date: 7.AUG.2008 03:10:32

ANNEX C: TEST LAYOUT**Pic C-1 Conducted Emission****Pic C-2 Radiated Spurious Emission*******END OF REPORT*****