

TEST REPORT

No. 2008TAR047

for

AMOI Mobile Co., LTD

Dual mode gsm wcdma mobile phone with bluetooth

Type: WMA8710

with

Hardware Version: V3.0

Software Version: WP3.0_V1.5_HK

Issued Date: Aug 25th, 2008



No. DAT-P-114/01-01

Note:

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of TMC Beijing.

Test Laboratory:

TMC Beijing, Telecommunication Metrology Center of Ministry of Information Industry

No. 52, Huayuan Bei Road, Haidian District, Beijing, P. R. China 100083.

Tel:+86(0)10-62303288-2105, Fax:+86(0)10-62304793 Email:welcome@emcite.com. www.emcite.com

©Copyright. All rights reserved by TMC Beijing.



CONTENTS

1. TEST LABORATORY	3
1.1. TESTING LOCATION	3
1.2. TESTING ENVIRONMENT	3
1.3. PROJECT DATA	3
1.4. SIGNATURE	3
2. CLIENT INFORMATION	4
2.1. APPLICANT INFORMATION	4
2.2. MANUFACTURER INFORMATION	4
3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (A	۸E)5
3.1. ABOUT EUT	5
3.2. INTERNAL IDENTIFICATION OF EUT USED DURING THE TEST.	5
4. REFERENCE DOCUMENTS	5
4.1. REFERENCE DOCUMENTS FOR TESTING	5
5. LABORATORY ENVIRONMENT	6
6. SUMMARY OF TEST RESULTS	7
7. TEST EQUIPMENTS UTILIZED	7
ANNEX A: EUT PHOTOGRAPH	8
ANNEX B: MEASUREMENT RESULTS	13
ANNEY C. TEST I AVOLIT	17



1. Test Laboratory

1.1. Testing Location

Company Name: TMC Beijing, Telecommunication Metrology Center of MII Address: No 52, Huayuan beilu, Haidian District, Beijing, P.R.China

Postal Code: 100083

Telephone: 00861062303288 Fax: 00861062304793

1.2. <u>Testing Environment</u>

Normal Temperature: $15-35^{\circ}$ C Relative Humidity: 20-75%

1.3. Project data

Testing Start Date: Aug 18th, 2008
Testing End Date: Aug 22th, 2008

1.4. Signature

登晚刚

Zi Xiaogang

(Prepared this test report)

Sun Xiangqian

(Reviewed this test report)

Lu Bingsong

附城市

Deputy Director of the laboratory

(Approved this test report)



2. Client Information

2.1. Applicant Information

Company Name: AMOI Mobile Co., LTD

Address /Post: 102 Xiaguang Road, Haicang district, Xiamen City, Fujian

Province ,P.R.China

City: Xiamen
Postal Code: 361022
Country: China

Telephone: +86-592-6516777-3316

Fax: +86-592-6516007

2.2. Manufacturer Information

Company Name: AMOI Mobile Co., LTD

Address /Post: 102 Xiaguang Road, Haicang district, Xiamen City, Fujian

Province ,P.R.China

City: Xiamen
Postal Code: 361022
Country: China

Telephone: +86-592-6516777-3316

Fax: +86-592-6516007



3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

3.1. About EUT

Description Dual mode gsm wcdma mobile phone with bluetooth

Model WMA8710

FCC ID WGL-WMA8710

Hardware status V3.0

Software status WP3.0_V1.5_HK

Power supply Battery or Charger (AC Adaptor)

Note: Photographs of EUT are shown in ANNEX A of this test report. Components list, please refer to documents of the manufacturer; it is also included in the original test record of Telecommunication Metrology Center of MII of People's Republic of China.

3.2. Internal Identification of EUT used during the test

EUT ID*	SN or IMEI	HW Version	SW Version
EUT1	354541020002841	V3.0	WP3.0_V1.5_HK

^{*}EUT ID: is used to identify the test sample in the lab internally.

4. Reference Documents

4.1. Reference Documents for testing

The following documents listed in this section are referred for testing.

ReferenceTitleVersionFCC Part 15, Subpart BRadio frequency devicesV 10.1.07ANSI C63.4Methods of Measurement of Radio-Noise Emissions2003

from Low-Voltage Electrical and Electronic Equipment in

the Range of 9 kHz to 40 GHz



5. LABORATORY ENVIRONMENT

Semi-anechoic chamber (23 meters \times 17meters \times 10meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
Normalised site attenuation (NSA)	< ±3.2 dB, 10 m distance, from 30 to 1000 MHz
Uniformity of field strength	Between 0 and 6 dB, from 80 to 2000 MHz

Control room did not exceed following limits along the EMC testing:

Temperature	Min. = 15 $^{\circ}$ C, Max. = 35 $^{\circ}$ C
Relative humidity	Min. =30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω

Conducted chamber did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω

Fully-anechoic chamber (6.8 meters × 3.08 meters × 3.53 meters) did not exceed following limits along the EMC testing:

Temperature	Min. = 15 °C, Max. = 30 °C
Relative humidity	Min. = 30 %, Max. = 60 %
Shielding effectiveness	> 110 dB
Electrical insulation	> 10 kΩ
Ground system resistance	< 0.5 Ω
Uniformity of field strength	Between 0 and 6 dB, from 80 to 2000 MHz



6. SUMMARY OF TEST RESULTS

Abbreviations used in this clause:	
Р	Pass
NA	Not applicable
F	Fail

Clause	List	Clause in FCC rules	Verdict
1	Radiated Emission	15.109(a)	Р
2	Conducted Emission	15.107(a)	Р

7. Test Equipments Utilized

NO.	Description	TYPE	SERIES	MANUFACTUR	CAL DUE
NO.	Description	ITPE	NUMBER	E	DATE
1	Test Receiver	ESS	847151/015	R&S	2008-10-30
2	Test Receiver	ESI40	831564/002	R&S	2009-2-11
3	BiLog Antenna	3142B	9908-1403	EMCO	2009-1-16
4	BiLog Antenna	VUL9163	9163 175	Schwarzbeck	2009-9-19
5	Signal Generator	SMT06	831285/005	R&S	2008-12-26
6	Signal Generator	SMP04	100070	R&S	2009-4-20
7	LISN	ESH2-Z5	829991/012	R&S	2008-9-13
8	Spectrum Analyzer	FSU26	200030	R&S	2009-6-18
	Universal Radio				
9	Communication	CMU200	100680	R&S	2009-8-23
	Tester				
	Dual-Ridge				2009-3
10	Waveguide Horn	3115	9906-5827	EMCO	
	Antenna				
	Dual-Ridge				2009-3
11	Waveguide Horn	3116	2663	EMCO	
	Antenna				
	Dual-Ridge				2009-3
12	Waveguide Horn	3116	2661	EMCO	
	Antenna				
13	Climatic chamber	SH-241	92003546	ESPEC	2009-5-15



ANNEX A: EUT photograph

External Photo



Mobile Phone



Mobile Phone





Mobile Phone



Battery AE1





Battery AE1



Internal Photo




Mobile phone Disassembly



Mobile phone Disassembly





Mobile phone Disassembly



Mobile phone Disassembly



ANNEX B: MEASUREMENT RESULTS

B.1 Radiated Emission (§15.109(a))

B.1.1 Method of measurement

The field strength of radiated emissions from the unintentional radiator (USB mode of MS) at a distance of 3 meters is tested. Tested in accordance with the procedures of ANSI C63.4 - 2003, section 8.3. The test set-up please refers to Annex C.1.

B.1.2 EUT Operating Mode:

The MS is operating in the USB mode. During the test MS is connected to a laptop via a USB cable. The model of the laptop is IBM T42 2373-M6C, and the serial number of the laptop is 99-FV6P2. The software is used to let the laptop keep on copying data to MS, reading and erasing the data after copy action was finished.

B.1.3 Measurement Limit

Frequency of emission (MHz)	Field strength (microvolts/meter)
30-88	100
88-216	150
216-960	200
Above 960	500



B.1.4 Measurement Results

MEB BTA611_1RE_pre PK LM FCC Pari 158 Class A

Figure B.1 Radiated Emission from 30MHz to 1GHz

Frequency (Hz)

211

3111

5000




Figure B.2 Radiated Emission from 1GHz to 4GHz



B.2 Conducted Emission (§15.107(a))

B.2.1 Method of measurement

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150kHz to 30MHz shall not exceed the limits. Tested in accordance with the procedures of ANSI C63.4 – 2003, section 7.2. The test set-up please refers to Annex C.2.

B.2.2 EUT Operating Mode:

The MS is operating in the USB mode. During the test MS is connected to a laptop via a USB cable. The model of the laptop is IBM T42 2373-M6C, and the serial number of the laptop is 99-FV6P2. The software is used to let the laptop keep on copying data to MS, reading and erasing the data after copy action was finished. During the charging mode, Conducted Emission is measured with travel charger.

B.2.3 Measurement Limit


Frequency of emission (MHz)	Conducted limit (dBµV)		
	Quasi-peak	Average	
0.15-0.5	66 to 56*	56 to 46*	
0.5-5	56	46	
5-30 60 50			
*Decreases with the logarithm of the frequency			

B.2.4 Test Condition

Voltage (V)	Frequency (Hz)
110	60



B.2.4 Measurement ResultsWith Laptop



MEASUREMENT RESULT: "8TA611_15B_fin QP"

Frequency	Level	Transd	Limit	Margin	Line	PE
MHz	dΒμV	dB	dΒμV	dB		
0.180000	56.90	10.1	65	7.5	L1	GND
0.485000	47.90	10.1	56	8.4	L1	GND
2.707262	39.50	10.1	56	16.5	N	GND
3.149781	40.50	10.1	56	15.5	L1	GND
3.937089	40.70	10.1	56	15.3	L1	GND
4.508211	43.10	10.2	56	12.9	N	GND

MEASUREMENT RESULT: "8TA611_15B_fin AV"

Frequency	Level	Transd	Limit	Margin	Line	PE
MHz	dΒμV	dB	dΒμV	dB		
2.364292	34.40	10.1	46	11.6	L1	GND
2.480072	37.40	10.1	46	8.6	L1	GND
6.987689	43.40	10.2	50	6.6	N	GND
7.099939	41.60	10.2	50	8.4	L1	FLO
7.213992	43.50	10.2	50	6.5	L1	FLO
8.001337	41.50	10.2	50	8.5	N	GND



ANNEX C: TEST LAYOUT



Pic C-1 Conducted Emission



Pic C-2 Radiated Spurious Emission

END OF REPORT