

# RF Exposure Evaluation declaration

Product Name: IEEE802.11b/g Wireless LAN Mini-PCI Card

Model No. : EW-7358MG

FCC ID : WHD-DS-42-WG

Applicant: ORing Industrial Networking Corp.

Address: 4F., No.3, Lane 235, Baociao Rd., Sindian City, Taipei

County, Taiwan (R.O.C.)

Date of Receipt : July. 07, 2008

Date of Declaration: July. 15, 2008

Report No. : 087153R-RFUSP05V01

The declaration results relate only to the samples calculated.

The declaration shall not be reproduced except in full without the written approval of QuieTek Corporation. This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

Page: 1 of 3 Version: 1.0



# 1. RF Exposure Evaluation

#### 1.1. Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b) LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

		` _				
Frequency Range	Electric Field	Magnetic Field	Power Density	Average Time		
(MHz)	Strength (V/m)	Strength (A/m)	$(mW/cm^2)$	(Minutes)		
(A) Limits for Occupational/ Control Exposures						
300-1500			F/300	6		
1500-100,000			5	6		
(B) Limits for General Population/ Uncontrolled Exposures						
300-1500			F/1500	6		
1500-100,000			1	30		

F= Frequency in MHz

Friis Formula

Friis transmission formula:  $Pd = (Pout*G)/(4*pi*r^2)$ 

Where

 $Pd = power density in mW/cm^2$ 

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

Pd id the limit of MPE,  $1 \text{ mW/cm}^2$ . If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

#### 1.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

Page: 2 of 3 Version: 1.0



# 1.3. Test Result of RF Exposure Evaluation

Product : IEEE802.11b/g Wireless LAN Mini-PCI Card

Test Item : RF Exposure Evaluation

Test Site : CTR1

#### **Antenna Gain**

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 2.09dBi in logarithm scale.

# 802.11b (2412~2462MHz)

# Output Power Into Antenna & RF Exposure Evaluation Distance (2.09dBi):

Channel	Frequency (MHz)	Output Power to Antenna (mW)	Power Density at $R = 20 \text{ cm}$ (mW/cm2)
1	2412.00	63.8263	0.020546
6	2437.00	64.1210	0.020641
11	2462.00	64.8634	0.020880

The distance r ( $4^{th}$  column) calculated from the Fries transmission formula is far shorter than 20 cm separation requirement.

## 802.11g (2412~2462MHz)

## Output Power Into Antenna & RF Exposure Evaluation Distance (2.09dBi):

<u> </u>		,		
Channel	Frequency (MHz)	Output Power to Antenna (mW)	Power Density at $R = 20 \text{ cm}$ (mW/cm2)	
1	2412.00	57.2796	0.018439	
6	2437.00	55.8470	0.017978	
11	2462.00	59.0201	0.018999	

The distance r ( $4^{th}$  column) calculated from the Fries transmission formula is far shorter than 20 cm separation requirement.

Page: 3 of 3 Version: 1.0