



Statement of compliance to Maximum Permissible Exposure (MPE) No. 170402017SHA-002

Applicant : Canton Elektronik GmbH + Co. KG

Neugasse 21-23, 61276 Weilrod / Niederlauken, Germany

Manufacturing site : Porsche Lizenz- und Handelsgesellschaft mbH & Co. KG

Groenerstrasse 5, 71636 Ludwigsburg, Germany

Product Name : Portable active speaker

Type/Model: 911 SPEAKER

According to §2.1091, §2.1093 and §1.1307(b), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Date of issue: July 7, 2017

Prepared by:

Wade zhang

Wade Zhang (Project engineer)

Daniel Zhao (Reviewer)



FCC ID: WHZ-911SP

Power density (S) is calculated according to the formula:

 $S = PG / (4\pi R^2)$

Where $S = power density in mW/cm^2$

P = transmit power in mW

G = numeric gain of transmit antenna (numeric gain=Log-1(dB antenna gain/10))

R = distance (cm)

The calculations in the table below use the highest gain of antenna for client EUT. These calculations represent worst case in terms of the exposure levels.

Frequency band	Power		Antenna Gain		R	S	Limits
(MHz)	dBm	mW	dBi	(Numeric)	(cm)	(mW/cm ²)	(mW/cm ²)
2402 - 2480	8.618	7.27	2.0	1.58	20	0.002	1

Note: 1 mW/cm² from 1.310 Table 1



Appendix I

Definition below must be outlined in the User Manual:

To satisfy FCC RF exposure requirements, a separation distance of **20** cm or more should be maintained between the antenna of this device and persons during device operation. To ensure compliance, operations at closer than this distance is not recommended.