

FCC CERTIFICATION
On Behalf of
Eric Beare Associates Limited

Wireless Mouse Calculator
Model No.: BD10102

FCC ID: WIK10102

Prepared for : Eric Beare Associates Limited
Address : Unit 1202-1204, New Kowloon Plaza, 38 Tai Kok Tsui
Road, Kowloon, Hong Kong

Prepared by : ACCURATE TECHNOLOGY CO. LTD
Address : F1, Bldg. A, Changyuan New Material Port, Keyuan Rd.
Science & Industry Park, Nanshan, Shenzhen, Guangdong
P.R. China

Tel: (0755) 26503290
Fax: (0755) 26503396

Report Number : ATE20081291
Date of Test : July 9, 2008
Date of Report : July 9, 2008

TABLE OF CONTENTS

	Description	Page
Test Report Certification		
1. GENERAL INFORMATION	4	
1.1. Description of Device (EUT).....	4	
1.2. Description of Test Facility	4	
1.3. Measurement Uncertainty.....	4	
2. MEASURING DEVICE AND TEST EQUIPMENT	5	
3. SUMMARY OF TEST RESULTS.....	6	
4. RADIATED EMISSION FOR FCC PART 15 SECTION 15.227(B).....	7	
4.1. Block Diagram of Test Setup.....	7	
4.2. The Field Strength of Radiation Emission Measurement Limits.....	8	
4.3. Configuration of EUT on Measurement	8	
4.4. Operating Condition of EUT	8	
4.5. Test Procedure	9	
4.6. The Field Strength of Radiation Emission Measurement Results	10	
5. FUNDAMENTAL RADIATED EMISSION FOR FCC PART 15 SECTION 15.227(A) ...	11	
5.1. Block Diagram of Test Setup.....	11	
5.2. The Emission Limit For Section 15.227(a)	11	
5.3. EUT Configuration on Measurement	12	
5.4. Operating Condition of EUT	12	
5.5. Test Procedure	12	
5.6. The Emission Measurement Result	13	
6. BAND EDGES	14	
6.1. The Requirement	14	
6.2. EUT Configuration on Measurement	14	
6.3. Operating Condition of EUT	14	
6.4. Test Procedure	14	
6.5. The Measurement Result	15	

APPENDIX I (TEST CURVES) (3 pages)

Test Report Certification

Applicant : Eric Beare Associates Limited
 Manufacturer : Eric Beare Associates Limited
 EUT Description : Wireless Mouse Calculator
 (A) MODEL NO.: BD10102
 (B) SERIAL NO.: N/A
 (C) POWER SUPPLY: 3.0V DC ("AAA" batteries 2×)

Measurement Procedure Used:


FCC Rules and Regulations Part 15 Subpart C Section 15.227: 2007 & ANSI C63.4:2003

The device described above is tested by ACCURATE TECHNOLOGY CO. LTD to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C Section 15.227 limits. The measurement results are contained in this test report and ACCURATE TECHNOLOGY CO. LTD is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of ACCURATE TECHNOLOGY CO. LTD.


Date of Test : July 9, 2008

Prepared by :



(Engineer)

Approved & Authorized Signer :



(Manager)

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT : Wireless Mouse Calculator
 (Note: This sample contains an independent and detachable calculator which is taken other test for Part 15 Subpart B.)

 Model Number : BD10102

 Power Supply : 3.0V DC ("AAA" batteries 2×)

 Applicant : Eric Beare Associates Limited
 Address : Unit 1202-1204, New Kowloon Plaza, 38 Tai Kok Tsui Road, Kowloon, Hong Kong

 Manufacturer : Eric Beare Associates Limited
 Address : Unit 1202-1204, New Kowloon Plaza, 38 Tai Kok Tsui Road, Kowloon, Hong Kong

 Date of sample received : July 8, 2008
 Date of Test : July 9, 2008

1.2. Description of Test Facility

EMC Lab : Accredited by TUV Rheinland Shenzhen

 Listed by FCC
 The Registration Number is 752051

 Listed by Industry Canada
 The Registration Number is 5077A-2

 Accredited by China National Accreditation Committee for Laboratories
 The Certificate Registration Number is L3193

 Name of Firm : ACCURATE TECHNOLOGY CO. LTD
 Site Location : F1, Bldg. A, Changyuan New Material Port, Keyuan Rd. Science & Industry Park, Nanshan, Shenzhen, Guangdong P.R. China

1.3. Measurement Uncertainty

Conducted emission expanded uncertainty = 2.23dB, k=2

 Radiated emission expanded uncertainty = 4.12dB, k=2

2. MEASURING DEVICE AND TEST EQUIPMENT

Table 1: List of Test and Measurement Equipment

Kind of equipment	Manufacturer	Type	S/N	Calibrated until
EMI Test Receiver	Rohde&Schwarz	ESCS30	100307	03.29.2009
EMI Test Receiver	Rohde&Schwarz	ESPI3	101526/003	03.29.2009
Spectrum Analyzer	Agilent	E7405A	MY45115511	03.29.2009
Pre-Amplifier	Rohde&Schwarz	CBLU118354 0-01	3791	03.31.2009
Loop Antenna	Schwarzbeck	FMZB1516	1516131	03.28.2009
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	03.29.2009
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	12.20.2008
Horn Antenna	Schwarzbeck	BBHA9170	9170-359	10.10.2008
LISN	Rohde&Schwarz	ESH3-Z5	100305	03.29.2009
LISN	Schwarzbeck	NLSK8126	8126431	03.29.2009

3. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
Section 15.207	Conducted Emission	N/A
Section 15.209 Section 15.227(b)	Radiated Emission	Compliant
Section 15.227(a)	Fundamental Radiated Emission	Compliant
Section 15.227	Band Edge	Compliant

4. RADIATED EMISSION FOR FCC PART 15 SECTION 15.227(B)


4.1. Block Diagram of Test Setup

4.1.1. Block diagram of connection between the EUT and simulators



(EUT: Wireless Mouse Calculator)

4.1.2. Anechoic Chamber Test Setup Diagram



4.2.The Field Strength of Radiation Emission Measurement Limits

4.2.1.The field strength of any emissions which appear outside of this band shall not exceed the general radiated emission limits in section 15.209

Radiation Emission Measurement Limits According to Section 15.209(a)

Frequency (MHz)	Limit,		
	Field Strength of Quasi-peak Value (microvolts/m)	Field Strength of Quasi-peak Value (dB μ V/m)	The final measurement in band 9-90kHz, 110-490kHz and above 1000MHz is performed with Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	

4.3.Configuration of EUT on Measurement

The following equipment are installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

4.3.1. Wireless Mouse Calculator (EUT)

Model Number : BD10102
 Serial Number : N/A
 Manufacturer : Eric Beare Associates Limited

4.4.Operating Condition of EUT

4.4.1.Setup the EUT and simulator as shown as Section 4.1.

4.4.2.Turn on the power of all equipment.

4.4.3.Let the EUT work in TX modes and measure it.

4.5. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C 63.4: 2003 on radiated emission measurement.

The bandwidth of test receiver (R&S ESCS30) is set at 120KHz in 30-1000MHz. The frequency range from 30MHz to 1000MHz is checked.

The final measurement in band 9-90kHz, 110-490kHz and above 1000MHz is performed with Average detector. Except those frequency bands mention above, the final measurement for frequencies below 1000MHz is performed with Quasi Peak detector.

4.6.The Field Strength of Radiation Emission Measurement Results PASS.

The frequency range 30MHz to 1000MHz is investigated.

Date of Test:	July 9, 2008	Temperature:	25°C
EUT:	Wireless Mouse Calculator	Humidity:	52%
Model No.:	BD10102	Power Supply:	3.0V DC (“AAA” battery 2×)
Test Mode:	TX	Test Engineer:	Feng

Polarization	Frequency (MHz)	Reading(dB μ V/m) QP	Factor Corr.(dB)	Result(dB μ V/m) QP	Limits(dB μ V/m) QP	Margin(dB) QP
Horizontal	54.1031	7.01	11.59	18.60	40.00	-21.40
Vertical	54.0890	12.70	11.60	24.30	40.00	-15.70
Vertical	540.9495	9.89	25.01	34.90	46.00	-11.10

Note:

1. The spectral diagrams in appendix 1 display the measurement of peak values with corrected factors counted.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$

Where Corrected Factor = Antenna Factor + Cable Loss + High Pass Filter Loss – Amplifier Gain

5. FUNDAMENTAL RADIATED EMISSION FOR FCC PART 15

SECTION 15.227(A)


5.1. Block Diagram of Test Setup

5.1.1. Block diagram of connection between the EUT and simulators



(EUT: Wireless Mouse Calculator)

5.1.2. Anechoic Chamber Test Setup Diagram



(EUT: Wireless Mouse Calculator)

5.2. The Emission Limit For Section 15.227(a)

5.2.1. The field strength of any emission within this band shall not exceed 10,000 microvolts/meter at 3 meters. The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in Section 15.35 for limiting peak emission apply.

5.3.EUT Configuration on Measurement

The following equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

5.3.1.Wireless Mouse Calculator (EUT)

Model Number	:	BD10102
Serial Number	:	N/A
Manufacturer	:	Eric Beare Associates Limited

5.4.Operating Condition of EUT

5.4.1.Setup the EUT and simulator as shown as Section 5.1.

5.4.2.Turn on the power of all equipment.

5.4.3.Let the EUT work in TX mode and measure it.

5.5.Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. A calibrated Loop antenna is used as receiving antenna. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C 63.4: 2003 on radiated emission measurement.

The bandwidth of test receiver (R&S ESCS30) is set at 9kHz in 9kHz-30MHz.

5.6.The Emission Measurement Result

PASS.

Date of Test:	July 9, 2008	Temperature:	25°C
EUT:	Wireless Mouse Calculator	Humidity:	52%
Model No.:	BD10102	Power Supply:	3.0V DC ("AAA" battery
Test Mode:	TX	Test Engineer:	Feng

Fundamental Radiated Emissions

Test conditions		Fundamental Frequency		
		27.045MHz		
T _{nom} (25°C)	V _{nom} (3.0V DC)	(dB μ V/m)/(μ V/m)	(dB μ V/m)/(μ V/m)	
		PEAK	AV	
		47.10/226.46	44.30/164.06	
Limit		100/100,000	80/10,000	

Note: Measurement was performed with modulated signal with average detector and peak detector.

6. BAND EDGES

6.1. The Requirement

6.1.1. The wanted emission within the band 26.96-27.28MHz.

6.2. EUT Configuration on Measurement

The following equipment are installed on the emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

6.2.1. Wireless Mouse Calculator (EUT)

Model Number	:	BD10102
Serial Number	:	N/A
Manufacturer	:	Eric Beare Associates Limited

6.3. Operating Condition of EUT

6.3.1. Setup the EUT and simulator as shown as Section 5.1.

6.3.2. Turn on the power of all equipment.

6.3.3. Let the EUT work in TX mode and measure it.

6.4. Test Procedure

The transmitter output was fed into the spectrum analyzer and photo was taken. The vertical scale is set to 10dB per division; the horizontal scale is set to 32kHz per division. Start frequency are 26.96MHz, stop frequency are 27.28MHz. RBW are 3kHz, VBW are 10kHz, Sweep time are 50ms.

6.5.The Measurement Result

The EUT does meet the requirement.

The spectral diagrams attached in appendix 1.


APPENDIX I (Test Curves)



ACCURATE TECHNOLOGY CO., LTD.
 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Tel:+86-0755-26503290
 Fax:+86-0755-26503396
<http://www.atc-lab.com>

Job No.:	RTTE #171	Polarization:	Horizontal
Standard:	FCC Class B 3M Radiated	Power Source:	DC 3V
Test item:	Radiation Test	Date:	08/07/09/
Temp. (°C)/Hum. (%RH):	25(°C)/52%RH	Time:	9/41/58
EUT:	Wireless Mouse Calculator	Test By:	feng
Mode:	TX	Distance:	3m
Model:	BD10102		
Manufacturer:	Eric Beare Associates Limited		
Note:	Sample No.:082584	Report No.:ATE20081291	



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	54.1031	7.01	11.59	18.60	40.00	-21.40	QP




ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg.A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,PR.China

Tel:+86-0755-26503290
Fax:+86-0755-26503396
<http://www.atc-lab.com>

Job No.:	RTTE #170	Polarization:	Vertical
Standard:	FCC Class B 3M Radiated	Power Source:	DC 3V
Test item:	Radiation Test	Date:	08/07/09/
Temp. (°C)/Hum.(%RH):	25(°C)/52%RH	Time:	9/35/10
EUT:	Wireless Mouse Calculator	Test By:	feng
Mode:	TX	Distance:	3m
Model:	BD10102		
Manufacturer:	Eric Beare Associates Limited		
Note:	Sample No.:082584	Report No.:ATE20081291	



No.	Frequency (MHz)	Reading (dBuV/m)	Correct Factor(dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	54.0890	12.70	11.60	24.30	40.00	-15.70	QP
2	540.9495	9.89	25.01	34.90	46.00	-11.10	QP



Date: 9.JUL.2008 10:15:41