



## MEASUREMENT REPORT

---

**FCC ID** : WIYS1F4B001  
**IC** : 27350-S1F4B001  
**APPLICANT** : CASTLES TECHNOLOGY CO., LTD.

**Application Type** : Certification

**Product** : POS Cradle

**Model No.** : S1F4B

**Trademark** :  CASTLES  
TECHNOLOGY

**FCC Classification** : (DTS) Digital Transmission System

**FCC Rule Part(s)** : Part 15.247

**ISED Standard** : RSS-247 Issue 3

**Test Procedure(s)** : ANSI C63.10-2013

**Received Date** : February 24, 2025

**Test Date** : March 6, 2025~ March 11, 2025

**Tested By** : *Fran Chen*  
( Fran Chen )



**Reviewed By** : *Paddy Chen*  
( Paddy Chen )



**Approved By** : *Chenz Ker*  
( Chenz Ker )

The test results only relate to the tested samples.

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10 Test results reported herein relate only to the item(s) tested.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Taiwan) Co., Ltd.

## Revision History

Report No.	Version	Description	Issue Date	Note
2502TW8702-U2	1.0	Original Report	2025-03-19	

## CONTENTS

Description	Page
<b>1. INTRODUCTION .....</b>	<b>6</b>
1.1. Scope.....	6
1.2. MRT Test Location.....	6
<b>2. PRODUCT INFORMATION .....</b>	<b>7</b>
2.1. Equipment Description .....	7
2.2. Working Frequencies for this Report .....	8
2.3. Test Mode .....	10
2.4. Test Software .....	10
2.5. Test Configuration.....	11
2.6. Test System Details .....	11
2.7. EMI Suppression Device(s)/Modifications .....	11
2.8. Labeling Requirements .....	12
<b>3. DESCRIPTION of TEST.....</b>	<b>13</b>
3.1. Evaluation Procedure.....	13
3.2. AC Line Conducted Emissions .....	13
3.3. Radiated Emissions .....	14
<b>4. ANTENNA REQUIREMENTS.....</b>	<b>15</b>
<b>5. TEST EQUIPMENT CALIBRATION DATE.....</b>	<b>16</b>
<b>6. MEASUREMENT UNCERTAINTY.....</b>	<b>17</b>
<b>7. TEST RESULT .....</b>	<b>18</b>
7.1. Summary.....	18
7.2. 6dB Bandwidth Measurement .....	19
7.2.1. Test Limit.....	19
7.2.2. Test Procedure used .....	19
7.2.3. Test Setting .....	19
7.2.4. Test Setup .....	19
7.2.5. Test Result .....	20
7.3. Output Power Measurement.....	25
7.3.1. Test Limit.....	25
7.3.2. Test Procedure Used.....	25
7.3.3. Test Setting .....	25
7.3.4. Test Setup .....	25
7.3.5. Test Result of Output Power.....	26
7.4. Power Spectral Density Measurement .....	28
7.4.1. Test Limit.....	28
7.4.2. Test Procedure Used.....	28
7.4.3. Test Setting .....	28
7.4.4. Test Setup .....	28
7.4.5. Test Result .....	29
7.5. Out-of-Band Spurious Emissions Measurement.....	33
7.5.1. Test Limit.....	33

---

7.5.2. Test Procedure Used.....	33
7.5.3. Test Setting .....	33
7.5.4. Test Setup .....	33
7.5.5. Test Result .....	34
7.6. Radiated Spurious Emission Measurement.....	41
7.6.1. Test Limit.....	41
7.6.2. Test Procedure Used.....	41
7.6.3. Test Setting .....	41
7.6.4. Test Setup .....	43
7.6.5. Test Result .....	45
7.7. Radiated Restricted Band Edge Measurement.....	75
7.7.1. Test Limit.....	75
7.7.2. Test Procedure Used.....	75
7.7.3. Test Setting .....	75
7.7.4. Test Setup .....	77
7.7.5. Test Result .....	78
7.8. AC Conducted Emissions Measurement.....	110
7.8.1. Test Limit.....	110
7.8.2. Test Setup .....	110
7.8.3. Test Result .....	111
<b>8. CONCLUSION .....</b>	<b>113</b>
<b>Appendix A : Test Photograph.....</b>	<b>114</b>
<b>Appendix B : EUT Photograph.....</b>	<b>114</b>
<b>Appendix C : Internal Photograph.....</b>	<b>114</b>

## General Information

<b>Applicant</b>	CASTLES TECHNOLOGY CO., LTD.
<b>Applicant Address</b>	6F, NO. 207-5, SEC. 3, BEIXIN RD., XINDIAN DISTRICT, NEW TAIPEI CITY 231030, TAIWAN (R.O.C.)
<b>Manufacturer</b>	CASTLES TECHNOLOGY CO., LTD.
<b>Manufacturer Address</b>	6F, NO. 207-5, SEC. 3, BEIXIN RD., XINDIAN DISTRICT, NEW TAIPEI CITY 231030, TAIWAN (R.O.C.)
<b>Test Site</b>	MRT Technology (Taiwan) Co., Ltd
<b>Test Site Address</b>	No. 38, Fuxing Second Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C)
<b>MRT FCC Registration No.</b>	291082
<b>MRT IC Registration No.</b>	21723
<b>Test Device Serial No.:</b>	#1-1 <input type="checkbox"/> Production <input checked="" type="checkbox"/> Pre-Production <input type="checkbox"/> Engineering

## Test Facility / Accreditations

1. MRT facility is a FCC registered (Reg. No. 291082) test facility with the site description report on file and is designated by the FCC as an Accredited Test Firm.
2. MRT facility is an IC registered (MRT Reg. No. 21723) test laboratory with the site description on file at Industry Canada.
3. MRT Lab is accredited to ISO 17025 by the Taiwan Accreditation Foundation (TAF Cert. No. 3261) in EMC, Telecommunications and Radio testing for FCC (Designation Number: TW3261), Industry Canada, EU and TELEC Rules.


## 1. INTRODUCTION

## 1.1. Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

## 1.2. MRT Test Location

The map below shows the location of the MRT LABORATORY, its proximity to the Taoyuan City. These measurement tests were conducted at the MRT Technology (Taiwan) Co., Ltd. Facility located at No.38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 33377, Taiwan (R.O.C).



## 2. PRODUCT INFORMATION

### 2.1. Equipment Description

Product Name	POS Cradle
Trademark	 CASTLES TECHNOLOGY
Model No.	S1F4B
Test Sample Number	#1
Wi-Fi Specification	802.11 b/g/n (2TX / 2RX)
Frequency Range	<u>2.4GHz:</u> For 802.11b/g/n-20M: 2412 ~ 2462 MHz For 802.11n-40M: 2422 ~ 2452 MHz
Type of Modulation	802.11b: DSSS, DBPSK, DQPSK, CCK 802.11g/n-20M/n-40M: OFDM, BPSK, QPSK, 16QAM, 64QAM
Accessory	
Power Adapter	Brand Name:  CASTLES TECHNOLOGY Model: PW04-945A Input: AC 100-240V~1A max, 50/60Hz Output: DC 9.0V--4.5A 40.5W DC Cable Out Non-Shielding, 1.5m

## 2.2. Working Frequencies for this Report

802.11b/g/n-HT20

Channel	Frequency	Channel	Frequency	Channel	Frequency
01	2412 MHz	02	2417 MHz	03	2422 MHz
04	2427 MHz	05	2432 MHz	06	2437 MHz
07	2442 MHz	08	2447 MHz	09	2452 MHz
10	2457 MHz	11	2462 MHz	--	--

802.11n-HT40

Channel	Frequency	Channel	Frequency	Channel	Frequency
03	2422 MHz	04	2427 MHz	05	2432 MHz
06	2437 MHz	07	2442 MHz	08	2447 MHz
09	2452 MHz	--	--	--	--

## Duty Cycle

Test Mode	Duty Cycle
802.11b	96.22%
802.11g	80.25%
802.11 n-HT20	66.03%
802.11 n-HT40	49.80%



## 2.3. Test Mode

Test Mode	Mode 1: Transmit by 802.11b with Ant 0
	Mode 2: Transmit by 802.11g with Ant 0
	Mode 3: Transmit by 802.11n-20M with Ant 0+1
	Mode 4: Transmit by 802.11n-40M with Ant 0+1
	Mode 5: Receiver by 802.11n-20M with Ant 0+1

Note:

1. Regarding to the operation frequency, the lowest, middle and highest frequency are selected to perform the test.


## 2.4. Test Software

The test utility software used during testing was “Tera Term”.

## 2.5. Test Configuration

This device was tested per the guidance of ANSI C63.10-2013. ANSI C63.10-2013 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing.

Connection Diagram



Signal Cable Type		Signal Cable Description
A	Type B to A Cable	Shielded 1.2m
B	USB Keyboard Cable	Shielded, 1.5m
C	USB Mouse Cable	Shielded, 1.8m

## 2.6. Test System Details

The types for all equipment, and descriptions of all cables used in the tested system (including inserted cards) are:

No.	Product	Manufacturer	Model No.	Serial No.	Power Cord
1	Notebook PC	DELL	P65F	N/A	Non-shielded, 0.8m
2	USB Keyboard	Logitech	K120	N/A	N/A
3	USB Mouse	Logitech	M90	N/A	N/A

## 2.7. EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

## 2.8. Labeling Requirements

Per 2.1074 & 15.19; Docket 95-19

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the FCC ID must be displayed on the device per Section 15.19(a)(5). Please see attachment for FCC ID label and label location.

### 3. DESCRIPTION of TEST

#### 3.1. Evaluation Procedure

The measurement procedures described in the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2013), and the guidance provided in KDB 558074 D01v05 were used in the measurement of the device.

**Deviation from measurement procedure.....** **None**

#### 3.2. AC Line Conducted Emissions

The line-conducted facility is located inside an 9'x4'x3' shielded enclosure. A 1m x 2m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50uH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference ground-plane. Power cables for support equipment were routed down to the second LISN while ensuring that that cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the receiver and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The receiver was scanned from 150kHz to 30MHz. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 9kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Each emission was also maximized by varying: power lines, the mode of operation or data exchange speed, or support equipment which determined the worst-case emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions are used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

An extension cord was used to connect to a single LISN which powered by EUT. The extension cord was calibrated with LISN, the impedance and insertion loss are compliance with the requirements as stated in ANSI C63.10-2013.

Line conducted emissions test results are shown in Section 7.8.

### 3.3. Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. For measurements above 1GHz absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections. For measurements below 1GHz, the absorbers are removed. A MF Model 210SS turntable is used for radiated measurement. It is a continuously rotatable, remote controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm high PVC support structure is placed on top of the turntable. For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33(b)(1) depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up for frequencies below 1GHz was placed on top of the 0.8 meter high, 1 x 1.5 meter table; and test set-up for frequencies 1-40GHz was placed on top of the 1.5 meter high, 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, clock speed, mode of operation or video resolution, if applicable, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, which produced the worst-case emissions. According to 3dB Beam-Width of horn antenna, the horn antenna should be always directed to the EUT when rising height.

Radiated emissions test results are shown in Section 7.6 & 7.7 .

## 4. ANTENNA REQUIREMENTS

### Excerpt from §15.203 of the FCC Rules/Regulations:

"An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section."

- The antenna of the **POS Cradle**, is permanently attached.
- There are no provisions for connection to an external antenna.

### **Conclusion:**

The EUT unit complies with the requirement of §15.203.

### **Antenna List**

Antenna Type	Frequency Band (MHz)	Tx Paths	Number of spatial streams	Max Antenna Gain (dBi)	Directional Gain (dBi)	CDD Directional Gain (dBi)	
						For Power	For PSD
<b>Wi-Fi Antenna</b>							
Dipole	2412 ~ 2462	2	1	3.28	6.29	3.28	6.29
	5150 ~ 5250	2	1	4.49	7.50	4.49	7.50
	5725 ~ 5850	2	1	4.06	7.07	4.06	7.07

### Remark:

1. The EUT supports Cyclic Delay Diversity (CDD) mode, and CDD signals are correlated.

If all antennas have the same gain,  $G_{ANT}$ , Directional gain =  $G_{ANT} + \text{Array Gain}$ , where Array Gain is as follows.

- For power spectral density (PSD) measurements on all devices,

$$\text{Array Gain} = 10 \log (N_{ANT}/ N_{SS}) \text{ dB};$$

- For power measurements on IEEE 802.11 devices,

$$\text{Array Gain} = 0 \text{ dB for } N_{ANT} \leq 2;$$

2. All messages of antenna were declared by manufacturer.

## 5. TEST EQUIPMENT CALIBRATION DATE

### Conducted Emissions – SR2

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Two-Line V-Network	R&S	ENV216	MRTTWA00019	1 year	2026/3/5
Cable	Rosnol	N1C50-RG400-B1C50-500CM	MRTTWE00013	1 year	2025/6/14
EMI Test Receiver	R&S	ESR3	MRTTWA00009	1 year	2026/3/4

### Radiated Emissions – AC1

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
Active Loop Antenna	SCHWARZBECK	FMZB 1519B	MRTTWA00002	1 year	2025/5/7
Broadband TRILOG Antenna	SCHWARZBECK	VULB 9162	MRTTWA00086	1 year	2025/11/5
Broadband Hornantenna	SCHWARZBECK	BBHA 9120D	MRTTWA00003	1 year	2026/2/11
Broadband Preamplifier	SCHWARZBECK	BBV 9718	MRTTWA00005	1 year	2026/2/11
Breitband Hornantenna	SCHWARZBECK	BBHA 9170	MRTTWA00004	1 year	2025/3/26
Broadband Amplifier	SCHWARZBECK	BBV 9721	MRTTWA00006	1 year	2025/3/21
EMI Test Receiver	R&S	ESR3	MRTTWA00009	1 year	2026/3/4
Signal Analyzer	R&S	FSV40	MRTTWA00007	1 year	2025/3/14
Antenna Cable	HUBERSUHNER	SF106	MRTTWE00010	1 year	2025/6/14
Cable	Rosnol	K1K50-UP0264-K1K50-4M	MRTTWE00012	1 year	2025/6/14
Temperature/Humidity Meter	TFA	35.1083	MRTTWA00050	1 year	2025/6/2

### Conducted Test Equipment – SR7

Instrument	Manufacturer	Type No.	Asset No.	Cali. Interval	Cali. Due Date
EXA Signal Analyzer	KEYSIGHT	N9010A	MRTTWA00012	1 year	2025/9/24
EXA Signal Analyzer	KEYSIGHT	N9010B	MRTTWA00074	1 year	2025/8/12
USB Wideband Power Sensor	KEYSIGHT	U2021XA	MRTTWA00015	1 year	2025/3/12

### Test Software

Software	Version	Function
e3	9.160520a	EMI Test Software
EMI	V3	EMI Test Software

## 6. MEASUREMENT UNCERTAINTY

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of  $k = 2$ .

Conducted Emission- Power Line
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2U_{c(y)}$ ): 0.15MHz~30MHz: $\pm 2.53\text{dB}$
Radiated Spurious Emission
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2U_{c(y)}$ ): 9kHz~30MHz: $\pm 3.92\text{dB}$ 30MHz~1GHz: $\pm 4.25\text{dB}$ 1GHz~18GHz: $\pm 4.40\text{dB}$ 18GHz~40GHz: $\pm 4.45\text{dB}$
Frequency Error
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2U_{c(y)}$ ): $\pm 78.4\text{Hz}$
Conducted Power
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2U_{c(y)}$ ): $\pm 0.84\text{dB}$
Conducted Spurious Emission
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2U_{c(y)}$ ): $\pm 2.65\text{ dB}$
Occupied Bandwidth
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2U_{c(y)}$ ): $\pm 3.3\%$
Temp. / Humidity
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2U_{c(y)}$ ): $\pm 0.82^\circ\text{C} / \pm 3\%$
DC Voltage
Measuring Uncertainty for a Level of Confidence of 95% ( $U=2U_{c(y)}$ ): $\pm 0.3\%$

## 7. TEST RESULT

### 7.1. Summary

**Product Name:** POS Cradle

**FCC Classification:** (DTS) Digital Transmission System

FCC Part Section(s)	IC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.247(a)(2)	RSS-247 5.2 (a)	6dB Bandwidth	$\geq 500\text{kHz}$	Conducted	Pass	Section 7.2
15.247(b)(3)	RSS-247 5.4 (d)	Output Power	$\leq 30.00\text{dBm}$		Pass	Section 7.3
15.247(e)	RSS-247 5.2 (b)	Power Spectral Density	$\leq 8.00\text{dBm/3kHz}$		Pass	Section 7.4
15.247(d)	RSS-247 5.5	Out-of-Band Emissions	Conducted $\geq 20\text{dBc}$		Pass	Section 7.5
15.205 15.209	RSS-247 5.5	Spurious Emission	$< \text{FCC 15.209 limits}$	Radiated	Pass	Section 7.6
15.205 15.209	RSS-247 5.5	Band Edge Measurement	$\leq 74\text{dBuV/m(Peak)}$ $\leq 54\text{dBuV/m(Average)}$		Pass	Section 7.7
15.207	RSS-Gen 8.8	AC Conducted Emissions 150kHz - 30MHz	$< \text{FCC 15.207 limits}$	Line Conducted	Pass	Section 7.8

#### Notes:

- 1) Determining compliance is based on the test results met the regulation limits or requirements declared by clients, and the test results don't take into account the value of measurement uncertainty.
- 2) All modes of operation and data rates were investigated. For radiated emission test, every axis (X, Y, Z) was also verified. The test results shown in the following sections represent the worst case emissions.
- 3) The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
- 4) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.

## 7.2. 6dB Bandwidth Measurement

### 7.2.1. Test Limit

The minimum 6dB bandwidth shall be at least 500 kHz.


### 7.2.2. Test Procedure used

ANSI C63.10 - 2013 Section 11.8

### 7.2.3. Test Setting

1. The Spectrum's automatic bandwidth measurement capability was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to X = 6. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. Set RBW = 100 kHz
3. VBW  $\geq 3 \times$  RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. Allow the trace was allowed to stabilize

### 7.2.4. Test Setup



### 7.2.5. Test Result

Product	POS Cradle	Temperature	25°C
Test Engineer	Fran	Relative Humidity	54%
Test Site	SR7	Test Date	2025/3/11

Test Mode	Data Rate / MCS	Channel No.	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	99 % Bandwidth (MHz)	Result
Ant 0							
802.11b	1Mbps	01	2412	10.09	≥ 0.5	14.791	Pass
802.11b	1Mbps	06	2437	10.07	≥ 0.5	14.749	Pass
802.11b	1Mbps	11	2462	10.11	≥ 0.5	14.790	Pass
802.11g	6Mbps	01	2412	15.90	≥ 0.5	16.415	Pass
802.11g	6Mbps	06	2437	15.92	≥ 0.5	16.419	Pass
802.11g	6Mbps	11	2462	15.96	≥ 0.5	16.425	Pass
802.11n-HT20	MCS0	01	2412	16.43	≥ 0.5	17.589	Pass
802.11n-HT20	MCS0	06	2437	16.52	≥ 0.5	17.570	Pass
802.11n-HT20	MCS0	11	2462	15.79	≥ 0.5	17.579	Pass
802.11n-HT40	MCS0	03	2422	35.49	≥ 0.5	36.003	Pass
802.11n-HT40	MCS0	06	2437	35.18	≥ 0.5	36.145	Pass
802.11n-HT40	MCS0	09	2452	35.50	≥ 0.5	36.075	Pass

## 6dB bandwidth

### 802.11 b CH01 (2412MHz)




### 802.11 b CH06 (2437MHz)




### 802.11 b CH11 (2462MHz)




### 802.11 g CH01 (2412MHz)




### 802.11 g CH06 (2437MHz)




### 802.11 g CH11 (2462MHz)




### 802.11 n-20M CH01 (2412MHz)




### 802.11 n-20M CH06 (2437MHz)




### 802.11 n-20M CH11 (2462MHz)




### 802.11 n-40M CH03 (2422MHz)



### 802.11 n-40M CH06 (2437MHz)



### 802.11 n-40M CH09 (2452MHz)



## 99% bandwidth

### 802.11 b CH01 (2412MHz)



### 802.11 b CH06 (2437MHz)




### 802.11 b CH11 (2462MHz)




### 802.11 g CH01 (2412MHz)




### 802.11 g CH06 (2437MHz)



### 802.11 g CH11 (2462MHz)





## 7.3. Output Power Measurement

### 7.3.1. Test Limit

The maximum out power shall be less 1 Watt (30dBm).

### 7.3.2. Test Procedure Used

ANSI C63.10 - 2013 Section 11.9.2.3.2

### 7.3.3. Test Setting


#### Peak Power Measurement

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

#### Average Power Measurement

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power.

### 7.3.4. Test Setup



### 7.3.5. Test Result of Output Power

Product	POS Cradle			Temperature	25°C			
Test Engineer	Fran			Relative Humidity	54%			
Test Site	SR7			Test Date	2025/3/11			

Test Mode	Data Rate/ MCS	Channel No.	Freq. (MHz)	Ant 0 Peak Power (dBm)	Ant 1 Peak Power (dBm)	Total Peak Power (dBm)	Limit (dBm)	Result
<b>CDD Mode</b>								
802.11b	1Mbps	01	2412	22.23	--	--	≤ 30.00	Pass
802.11b	1Mbps	06	2437	22.11	--	--	≤ 30.00	Pass
802.11b	1Mbps	11	2462	22.04	--	--	≤ 30.00	Pass
802.11g	6Mbps	01	2412	26.77	--	--	≤ 30.00	Pass
802.11g	6Mbps	06	2437	26.58	--	--	≤ 30.00	Pass
802.11g	6Mbps	11	2462	26.52	--	--	≤ 30.00	Pass
802.11n-HT20	MCS0	01	2412	24.87	25.14	28.02	≤ 30.00	Pass
802.11n-HT20	MCS0	06	2437	25.52	25.20	28.37	≤ 30.00	Pass
802.11n-HT20	MCS0	11	2462	25.51	25.16	28.35	≤ 30.00	Pass
802.11n-HT40	MCS0	03	2422	26.06	25.39	28.75	≤ 30.00	Pass
802.11n-HT40	MCS0	06	2437	25.98	25.63	28.82	≤ 30.00	Pass
802.11n-HT40	MCS0	09	2452	25.71	25.35	28.54	≤ 30.00	Pass

Note: Total Peak Power (dBm) =  $10 \times \log \{10^{(\text{Ant 0 Power /10})} + 10^{(\text{Ant 1 Power /10})}\}$

Test Mode	Data Rate/ MCS	Channel No.	Freq. (MHz)	Ant 0 Average Power (dBm) [Report only]	Ant 1 Average Power (dBm) [Report only]	Total Average Power (dBm) [Report only]	Limit (dBm)	Result
<b>CDD Mode</b>								
802.11b	1Mbps	01	2412	20.31	--	--	$\leq$ 30.00	Pass
802.11b	1Mbps	06	2437	20.18	--	--	$\leq$ 30.00	Pass
802.11b	1Mbps	11	2462	20.10	--	--	$\leq$ 30.00	Pass
802.11g	6Mbps	01	2412	18.30	--	--	$\leq$ 30.00	Pass
802.11g	6Mbps	06	2437	18.00	--	--	$\leq$ 30.00	Pass
802.11g	6Mbps	11	2462	17.78	--	--	$\leq$ 30.00	Pass
802.11n-HT20	MCS0	01	2412	17.08	17.02	20.06	$\leq$ 30.00	Pass
802.11n-HT20	MCS0	06	2437	17.14	17.18	20.17	$\leq$ 30.00	Pass
802.11n-HT20	MCS0	11	2462	17.03	17.09	20.07	$\leq$ 30.00	Pass
802.11n-HT40	MCS0	03	2422	15.09	14.84	17.98	$\leq$ 30.00	Pass
802.11n-HT40	MCS0	06	2437	14.88	15.06	17.98	$\leq$ 30.00	Pass
802.11n-HT40	MCS0	09	2452	14.64	14.83	17.75	$\leq$ 30.00	Pass

Note: Total Peak Power (dBm) =  $10 \times \log \{10^{(\text{Ant 0 Power /10})} + 10^{(\text{Ant 1 Power /10})}\}$

## 7.4. Power Spectral Density Measurement

### 7.4.1. Test Limit

The maximum permissible power spectral density is 8dBm in any 3 kHz band.

### 7.4.2. Test Procedure Used


ANSI C63.10 - 2013 Section 11.10.5

### 7.4.3. Test Setting

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance, and is optional if the maximum conducted (average) output power was used to demonstrate compliance.

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to: 3 kHz.
- d) Set the VBW  $\geq 3^* \text{ RBW}$ .
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.

### 7.4.4. Test Setup



#### 7.4.5. Test Result

Product	POS Cradle			Temperature	25°C		
Test Engineer	Fran			Relative Humidity	54%		
Test Site	SR7			Test Date	2025/3/11		

Test Mode	Data Rate/ MCS	Channel No.	Freq. (MHz)	Ant 0 Peak PSD (dBm/ 3kHz)	Ant 1 Peak PSD (dBm/ 3kHz)	Total Peak PSD (dBm/ 3kHz)	Limit (dBm/ 3kHz)	Result
802.11b	1Mbps	01	2412	-2.944	--	--	≤ 7.71	Pass
802.11b	1Mbps	06	2437	-3.919	--	--	≤ 7.71	Pass
802.11b	1Mbps	11	2462	-4.265	--	--	≤ 7.71	Pass
802.11g	6Mbps	01	2412	-7.372	--	--	≤ 7.71	Pass
802.11g	6Mbps	06	2437	-8.037	--	--	≤ 7.71	Pass
802.11g	6Mbps	11	2462	-8.909	--	--	≤ 7.71	Pass
802.11n-HT20	MCS0	01	2412	-9.149	-8.554	-5.831	≤ 7.71	Pass
802.11n-HT20	MCS0	06	2437	-9.215	-8.256	-5.699	≤ 7.71	Pass
802.11n-HT20	MCS0	11	2462	-9.204	-8.310	-5.724	≤ 7.71	Pass
802.11n-HT40	MCS0	03	2422	-13.787	-14.465	-11.102	≤ 7.71	Pass
802.11n-HT40	MCS0	06	2437	-9.626	-11.946	-7.623	≤ 7.71	Pass
802.11n-HT40	MCS0	09	2452	-13.265	-14.709	-10.917	≤ 7.71	Pass

Note: Total Peak PSD (dBm/kHz) =  $10 \times \log \{10^{(\text{Ant 0 PSD /10})} + 10^{(\text{Ant 1 PSD/10})}\}$

## Antenna 0


### 802.11 b CH01 (2412MHz)




### 802.11 b CH06 (2437MHz)




### 802.11 b CH11 (2462MHz)




### 802.11 g CH01 (2412MHz)




### 802.11 g CH06 (2437MHz)




### 802.11 g CH11 (2462MHz)






## Antenna 1


### 802.11 n-20M CH01 (2412MHz)




### 802.11 n-20M CH06 (2437MHz)




### 802.11 n-20M CH11 (2462MHz)




### 802.11 n-40M CH03 (2422MHz)



### 802.11 n-40M CH06 (2437MHz)



### 802.11 n-40M CH09 (2452MHz)



## 7.5. Out-of-Band Spurious Emissions Measurement

### 7.5.1. Test Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 Db below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on RF conducted measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.


### 7.5.2. Test Procedure Used

ANSI C63.10 - 2013 Section 11.11

### 7.5.3. Test Setting

- (a) Set instrument center frequency to DTS channel center frequency
- (b) Set the span to  $\geq 1.5$  times the DTS bandwidth
- (c) Set the RBW = 100 kHz
- (d) Set the VBW  $\geq 3 \times$  RBW
- (e) Detector = peak
- (f) Sweep time = auto couple
- (g) Trace mode = max hold
- (h) Allow trace to fully stabilize






### 7.5.4. Test Setup



### 7.5.5. Test Result

Product	POS Cradle	Temperature	25°C
Test Engineer	Fran	Relative Humidity	54%
Test Site	SR7	Test Date	2025/3/11

Test Mode	Data Rate / MCS	Channel No.	Frequency (MHz)	Limit (dBc)	Result
802.11b	1Mbps	01	2412	20	Pass
802.11b	1Mbps	06	2437	20	Pass
802.11b	1Mbps	11	2462	20	Pass
802.11g	6Mbps	01	2412	20	Pass
802.11g	6Mbps	06	2437	20	Pass
802.11g	6Mbps	11	2462	20	Pass
802.11n-HT20	MCS0	01	2412	20	Pass
802.11n-HT20	MCS0	06	2437	20	Pass
802.11n-HT20	MCS0	11	2462	20	Pass
802.11n-HT40	MCS0	03	2422	20	Pass
802.11n-HT40	MCS0	06	2437	20	Pass
802.11n-HT40	MCS0	09	2452	20	Pass

**Ant 0**
**802.11 b CH01 (2412MHz)**

**802.11 b CH01 (2412MHz)**

**802.11 b CH06 (2437MHz)**

**802.11 b CH06 (2437MHz)**

**802.11 b CH11 (2462MHz)**

**802.11 b CH11 (2462MHz)**
