

FCC Test Report

Report No.: RF180802C04-3

FCC ID: WIYVEGA3000-LTE

Test Model: VEGA3000

Received Date: Aug. 02, 2018

Test Date: Aug. 17, 2018 ~ Sep. 12, 2018

Issued Date: Sep. 14, 2018

Applicant: CASTLES TECHNOLOGY CO., LTD.

Address: 6F, NO. 207-5, SEC. 3, BEIXIN RD., XINDIAN DISTRICT, NEW TAIPEI

CITY 23143, TAIWAN (R. O. C.)

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

(R.O.C)

Test Location (1): No.19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City

33383, Taiwan, R.O.C.

Test Location (2): No.215, Sec. 3, Beixin Rd., Xindian Dist., New Taipei City 231, Taiwan,

R.O.C

FCC Registration /

427177 / TW0011

Designation Number:





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Report No.: RF180802C04-3 Page No. 1 / 48 Report Format Version: 6.1.1



Table of Contents

Re	leas	e Control Record	4
1	Cer	tificate of Conformity	5
2	Sun	nmary of Test Results	6
		Measurement Uncertainty	
		Modification Record	
3		neral Information	
		General Description of EUT	
	3.2	Description of Test Modes	
	3 3	Duty Cycle of Test Signal	
		Description of Support Units	
	.	3.4.1 Configuration of System under Test	
	3.5	General Description of Applied Standards	
4	Tes	t Types and Results	12
	4.1	Radiated Emission and Bandedge Measurement	12
		4.1.1 Limits of Radiated Emission and Bandedge Measurement	
		4.1.2 Test Instruments	
		4.1.3 Test Procedures	
		4.1.4 Deviation from Test Standard	
		4.1.6 EUT Operating Conditions	
		4.1.7 Test Results	
	4.2	Conducted Emission Measurement	
		4.2.1 Limits of Conducted Emission Measurement	
		4.2.2 Test Instruments	
		4.2.3 Test Procedures	
		4.2.4 Deviation from Test Standard	
		4.2.5 Test Setup	
		4.2.7 Test Results	
	4.3	Number of Hopping Frequency Used	
		4.3.1 Limits of Hopping Frequency Used Measurement	
		4.3.2 Test Setup	
		4.3.3 Test Instruments	
		4.3.4 Test Procedure	
		4.3.5 Deviation from Test Standard	
	11	4.3.6 Test Results Dwell Time on Each Channel	
	4.4	4.4.1 Limits of Dwell Time on Each Channel Measurement	
		4.4.2 Test Setup	
		4.4.3 Test Instruments	
		4.4.4 Test Procedures	
		4.4.5 Deviation from Test Standard	
	4 =	4.4.6 Test Results	
	4.5	Channel Bandwidth	
		4.5.1 Limits of Channel Bandwidth Measurement	
		4.5.3 Test Instruments	
		4.5.4 Test Procedure	
		4.5.5 Deviation from Test Standard	
		4.5.6 EUT Operating Condition	34
		4.5.7 Test Results	
	4.6	Occupied Bandwidth Measurement	36



		404 T +0+	~~
		4.6.1 Test Setup	
		4.6.2 Test Instruments	
		4.6.3 Test Procedure	
		4.6.4 Deviation from Test Standard	
		4.6.5 EUT Operating Conditions	
		4.6.6 Test Results	
	4.7	Hopping Channel Separation	
		4.7.1 Limits of Hopping Channel Separation Measurement	
		4.7.2 Test Setup	
		4.7.4 Test Procedure	
		4.7.5 Deviation from Test Standard	
		4.7.6 Test Results	
	/ Q	Maximum Output Power	
	4.0	4.8.1 Limits of Maximum Output Power Measurement	
		4.8.2 Test Setup	
		4.8.3 Test Instruments	
		4.8.4 Test Procedure	
		4.8.5 Deviation from Test Standard	
		4.8.6 EUT Operating Condition	
		4.8.7 Test Results	
	4.9	Conducted Out of Band Emission Measurement	
		4.9.1 Limits Of Conducted Out of Band Emission Measurement	
		4.9.2 Test Instruments	
		4.9.3 Test Procedure	
		4.9.4 Deviation from Test Standard	42
		4.9.5 EUT Operating Condition	
		4.9.6 Test Results	
5	Pict	tures of Test Arrangements	47
		dix – Information on the Testing Laboratories	
7	יויטקי	aix iniviniudon on the leading Laboratories	70



Release Control Record

Issue No.	Description	Date Issued
RF180802C04-3	Original Release	Sep. 14, 2018

Report No.: RF180802C04-3 Page No. 4 / 48 Report Format Version: 6.1.1



1 Certificate of Conformity

Product: POS Terminal

Brand: CASTLES TECHNOLOGY

Test Model: VEGA3000

Sample Status: Identical Prototype

Applicant: CASTLES TECHNOLOGY CO., LTD.

Test Date: Aug. 17, 2018 ~ Sep. 12, 2018

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.247)

ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Gina Liu / Specialist

Dylan Chiou / Project Engineer



2 Summary of Test Results

	47 CFR FCC Part 15, Subpart C (Section 15.247)							
FCC Clause	Test Item	Result	Remarks					
15.207	AC Power Conducted Emission	Pass	Meet the requirement of limit. Minimum passing margin is -0.33 dB at 0.65734 MHz.					
15.247(a)(1) (iii)	Number of Hopping Frequency Used	Pass	Meet the requirement of limit.					
15.247(a)(1) (iii)	Dwell Time on Each Channel	Pass	Meet the requirement of limit.					
15.247(a)(1)	Hopping Channel Separation Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	Pass	Meet the requirement of limit.					
15.247(b)	Maximum Peak Output Power	Pass	Meet the requirement of limit.					
	Occupied Bandwidth Measurement	Pass	Reference only					
15.205 & 209	Radiated Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -6.81 dB at 2493 MHz.					
15.247(d) Band Edge Measurement		Pass	Meet the requirement of limit.					
15.247(d)	Antenna Port Emission	Pass	Meet the requirement of limit.					
15.203	Antenna Requirement	Pass	No antenna connector is used.					

Note: If The Frequency Hopping System operating in 2400-2483.5 MHz band and the output power less than 125 mW. The hopping channel carrier frequencies separated by a minimum of 25 kHz or two-thirds of the 20 dB bandwidth of hopping channel whichever is greater.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expended Uncertainty (k=2) (±)
Conducted Emissions at mains ports	150 kHz ~ 30 MHz	2.44 dB
Radiated Emissions up to 1 GHz	30 MHz ~ 200 MHz	2.0153 dB
Radiated Effissions up to 1 GHZ	200 MHz ~ 1000 MHz	2.0224 dB
Radiated Emissions above 1 GHz	1 GHz ~ 18 GHz	1.0121 dB
Radiated Emissions above 1 GHZ	18 GHz ~ 40 GHz	1.1508 dB

2.2 Modification Record

There were no modifications required for compliance.

Report No.: RF180802C04-3 Page No. 6 / 48 Report Format Version: 6.1.1



3 General Information

3.1 General Description of EUT

Product	POS Terminal
Brand	CASTLES TECHNOLOGY
Test Model	VEGA3000
Status of EUT	Identical Prototype
Dawer Cumply Bating	5.0 Vdc (adapter or host equipment)
Power Supply Rating	3.7 Vdc (battery)
Modulation Type	GFSK, π/4-DQPSK, 8DPSK
Transfer Rate	1/2/3 Mbps
Operating Frequency	2402 ~ 2480 MHz
Number of Channel	79
Output Power	10.209 mW
Antenna Type	Dipole antenna with 1.17 dBi gain
Antenna Connector	N/A
Accessory Device	Refer to Note as below
Data Cable Supplied	Refer to Note as below

Note:

1. The EUT contains following accessory devices.

Product	Brand	Model	Description
USB Cable	CHANG YANG ELECTRON CO., LTD.	CY-AS-HK0059	1 m

2. The above EUT information is declared by manufacturer and for more detailed features description, please refers to the manufacturer's specifications or User's Manual.

Report No.: RF180802C04-3 Page No. 7 / 48 Report Format Version: 6.1.1



3.2 Description of Test Modes

79 channels are provided to this EUT:

Channel	Freq. (MHz)						
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		



Test Mode Applicability and Tested Channel Detail 3.2.1

EUT Configure		Applica	able To		Description
Mode	RE≥1G	RE<1G	PLC	APCM	Description
-	V	V	√	√	-

Where

RE≥1G: Radiated Emission above 1 GHz

RE<1G: Radiated Emission below 1 GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

Note:

- 1. For Radiated emission test, pre-tested GFSK, $\pi/4$ -DQPSK, 8DPSK modulation type and found GFSK was the worse, therefore chosen for the final test and presented in the test report.
- 2. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on Z-plane.
- 3. "-" means no effect.

Radiated Emission Test (Above 1 GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
-	0 to 78	0, 39, 78	FHSS	GFSK	DH5
-	0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

Radiated Emission Test (Below 1 GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture). Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Modulation **Available Channel Tested Channel Modulation Type Packet Type** Mode Technology **FHSS GFSK** DH5 0 to 78 78

Power Line Conducted Emission Test:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Available Channel	Tested Channel	Modulation Technology	Modulation Type	Packet Type
-	0 to 78	78	FHSS	GFSK	DH5

Report No.: RF180802C04-3 Page No. 9 / 48 Report Format Version: 6.1.1



Antenna Port Conducted Measurement:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.


EUT Configure Mode	Available Channel		Modulation Technology	Modulation Type	Packet Type
-	0 to 78	0, 39, 78	FHSS	GFSK	DH5
-	0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

Test Condition:

Applicable To	Environmental Conditions	Input Power	Tested by
RE≥1G	25 deg. C, 65 % RH	120 Vac, 60 Hz	Charles Hsiao
RE<1G	25 deg. C, 65 % RH	120 Vac, 60 Hz	Harry Hsueh
PLC	25 deg. C, 65 % RH	120 Vac, 60 Hz	Jisyong Wang
APCM	25 deg. C, 65 % RH	3.7 Vdc	Wayne Lin

3.3 Duty Cycle of Test Signal

Duty cycle = 2.885/3.747 = 0.77, Duty factor = $10 * \log(1/0.77) = 1.135$



Report No.: RF180802C04-3 Page No. 10 / 48 Report Format Version: 6.1.1



3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


No.	Product	Brand	Model No.	Serial No.	FCC ID
1.	Adapter	LUCENT	1A52-UB52A	N/A	N/A

No.	Signal Cable Description Of The Above Support Units
1.	N/A

Note:

- 1. All power cords of the above support units are non-shielded (1.8m).
- 2. Item 1 was provided by client.

3.4.1 Configuration of System under Test



3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247) KDB 558074 D01 15.247 Meas Guidance v05

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

Report No.: RF180802C04-3 Page No. 11 / 48 Report Format Version: 6.1.1



4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F (kHz)	300
0.490 ~ 1.705	24000/F (kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Note:

- a. The lower limit shall apply at the transition frequencies.
- b. Emission level $(dBuV/m) = 20 \log Emission level (uV/m)$.
- c. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

Report No.: RF180802C04-3 Page No. 12 / 48 Report Format Version: 6.1.1



4.1.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver Agilent Technologies	N9038A	MY52260177	Aug. 20, 2018	Aug. 19, 2019
Spectrum Analyzer ROHDE & SCHWARZ	FSU43	101261	Jan. 11, 2018	Jan. 10, 2019
BILOG Antenna SCHWARZBECK	VULB 9168	9168-616	Dec. 14, 2017	Dec. 13, 2018
HORN Antenna ETS-Lindgren	3117	00143293	Dec. 13, 2017	Dec. 12, 2018
HORN Antenna SCHWARZBECK	BBHA 9170	9170-480	Dec. 01, 2017	Nov. 30, 2018
Fixed Attenuator Mini-Circuits	MDCS18N-10	MDCS18N-10-01	Apr. 16, 2018	Apr. 15, 2019
Bluetooth Tester	СВТ	100980	Jun. 28, 2017	Jun. 27, 2019
Loop Antenna EMCI	LPA600	270	Aug. 11,2017	Aug. 10,2019
Preamplifier Agilent	310N	187226	Jun. 19, 2018	Jun. 18, 2019
Preamplifier Agilent	83017A	MY39501357	Jun. 19, 2018	Jun. 18, 2019
Power Meter Anritsu	ML2495A	1012010	Sep. 05, 2018	Sep. 04, 2019
Power Sensor Anritsu	MA2411B	1315050	Sep. 04, 2018	Sep. 03, 2019
RF signal cable ETS-LINDGREN	5D-FB	Cable-CH1-01(RFC -SMS-100-SMS-12 0+RFC-SMS-100-S MS-400)	Jun. 19, 2018	Jun. 18, 2019
RF signal cable ETS-LINDGREN	8D-FB	Cable-CH1-02(RFC -SMS-100-SMS-24)	Jun. 19, 2018	Jun. 18, 2019
Software BV ADT	E3 8.130425b	NA	NA	NA
Antenna Tower MF	NA	NA	NA	NA
Turn Table MF	NA	NA	NA	NA
Antenna Tower &Turn Table Controller MF	MF-7802	NA	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 / 24 months and the calibrations are traceable to NML/ROC and NIST/USA.

- 2. The test was performed in HsinTien Chamber 1.
- 3. The horn antenna and preamplifier (model: 83017A) are used only for the measurement of emission frequency above 1 GHz if tested.
- 4. The IC Site Registration No. is IC7450I-1.



4.1.3 Test Procedures

For Radiated Emission below 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Both Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz at frequency below 30 MHz.

For Radiated Emission above 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30 MHz ~ 1 GHz) / 1.5 meters (for above 1 GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detected function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:

- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1 GHz.
- 3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is ≥ 1/T (Duty cycle < 98 %) or 10 Hz (Duty cycle ≥ 98 %) for Average detection (AV) at frequency above 1 GHz. (RBW = 1 MHz, VBW = 1 kHz)
- 4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard


No deviation.

Report No.: RF180802C04-3 Page No. 14 / 48 Report Format Version: 6.1.1




4.1.5 Test Set Up

<Radiated Emission below 30 MHz>




<Radiated Emission 30 MHz to 1 GHz>





<Radiated Emission above 1 GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

Set the EUT under transmission condition continuously at specific channel frequency.



4.1.7 Test Results

Above 1 GHz Data:

GFSK

EUT Test Condition		Measurement Detail		
Channel	Channel 0	Frequency Range	1 GHz ~ 25 GHz	
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)	
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Charles Hsiao	

	Antenna Polarity & Test Distance: Horizontal at 3 m									
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2388.93	44.82	43.11	54	-9.18	31.8	5.4	35.49	100	250	Average
2388.93	51.65	49.94	74	-22.35	31.8	5.4	35.49	100	250	Peak
2402	100.2	98.47			31.8	5.4	35.47	100	151	Average
2402	103.79	102.06			31.8	5.4	35.47	100	151	Peak
7206	45.9	35.32	54	-8.1	35.56	9.94	34.92	100	90	Average
7206	50.4	39.82	74	-23.6	35.56	9.94	34.92	100	90	Peak
		Δ	ntenna P	olarity &	Test Dista	ance: Vert	ical at 3 r	n		
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2389.02	40.16	38.45	54	-13.84	31.8	5.4	35.49	100	279	Average
2389.02	50.35	48.64	74	-23.65	31.8	5.4	35.49	100	279	Peak
2402	97.32	95.59			31.8	5.4	35.47	100	279	Average
2402	100.19	98.46			31.8	5.4	35.47	100	279	Peak
4804	36.88	28.79	54	-17.12	33.96	8.25	34.12	110	3	Average
4804	44.87	36.78	74	-29.13	33.96	8.25	34.12	110	3	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss Preamp Factor Margin value = Emission level – Limit value
- 2. 2402 MHz: Fundamental frequency.
- 3. The emission levels of other frequencies were very low against the limit.

Report No.: RF180802C04-3 Page No. 17 / 48 Report Format Version: 6.1.1



EUT Test Condition		Measurement Detail		
Channel	Channel 39	Frequency Range	1 GHz ~ 25 GHz	
Input Power	120 Vac, 60 Hz		Peak (PK) Average (AV)	
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Charles Hsiao	

	Antenna Polarity & Test Distance: Horizontal at 3 m									
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2374.17	37.23	35.57	54	-16.77	31.78	5.37	35.49	100	206	Average
2374.17	50.11	48.45	74	-23.89	31.78	5.37	35.49	100	206	Peak
2441	100.66	98.79			31.85	5.46	35.44	100	206	Average
2441	103.19	101.32			31.85	5.46	35.44	100	206	Peak
2488.68	37.74	35.73	54	-16.26	31.9	5.53	35.42	100	206	Average
2488.68	50.27	48.26	74	-23.73	31.9	5.53	35.42	100	206	Peak
7323	46.77	36.31	54	-7.23	35.53	9.95	35.02	100	80	Average
7323	52.65	42.19	74	-21.35	35.53	9.95	35.02	100	80	Peak
		Δ	ntenna P	olarity &	Test Dista	ance: Vert	ical at 3 r	n		
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2368.59	37.22	35.56	54	-16.78	31.78	5.37	35.49	100	268	Average
2368.59	49.42	47.76	74	-24.58	31.78	5.37	35.49	100	268	Peak
2441	97.63	95.76			31.85	5.46	35.44	100	268	Average
2441	100.84	98.97			31.85	5.46	35.44	100	268	Peak
2485.48	37.59	35.6	54	-16.41	31.88	5.53	35.42	100	268	Average
2485.48	50.71	48.72	74	-23.29	31.88	5.53	35.42	100	268	Peak
4882	37.17	28.98	54	-16.83	33.98	8.27	34.06	102	222	Average
4882	44.86	36.67	74	-29.14	33.98	8.27	34.06	102	222	Peak

Remarks:

- Emission Level = Read Level + Antenna Factor + Cable Loss Preamp Factor Margin value = Emission level – Limit value
- 2. 2441 MHz: Fundamental frequency.
- 3. The emission levels of other frequencies were very low against the limit.

Report No.: RF180802C04-3 Page No. 18 / 48 Report Format Version: 6.1.1



EUT Test Condition		Measurement Detail		
Channel	Channel 78	Frequency Range	1 GHz ~ 25 GHz	
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)	
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Charles Hsiao	

	Antenna Polarity & Test Distance: Horizontal at 3 m									
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2480	100.22	98.26			31.88	5.5	35.42	100	206	Average
2480	103.03	101.07			31.88	5.5	35.42	100	206	Peak
2493	47.19	45.17	54	-6.81	31.9	5.53	35.41	100	0	Average
2493	53.27	51.25	74	-20.73	31.9	5.53	35.41	100	0	Peak
7440	47.36	37	54	-6.64	35.51	9.96	35.11	126	77	Average
7440	52.17	41.81	74	-21.83	35.51	9.96	35.11	126	77	Peak
		A	ntenna P	olarity &	Test Dista	ance: Vert	ical at 3 r	n		
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2480	97.55	95.59			31.88	5.5	35.42	100	279	Average
2480	100.4	98.44			31.88	5.5	35.42	100	279	Peak
2493.12	40.23	38.21	54	-13.77	31.9	5.53	35.41	100	279	Average
2493.12	50.26	48.24	74	-23.74	31.9	5.53	35.41	100	279	Peak
4960	37.31	29.04	54	-16.69	33.99	8.29	34.01	100	325	Average
4960	44.11	35.84	74	-29.89	33.99	8.29	34.01	100	325	Peak

- Emission Level = Read Level + Antenna Factor + Cable Loss Preamp Factor Margin value = Emission level – Limit value
- 2. 2480 MHz: Fundamental frequency.
- 3. The emission levels of other frequencies were very low against the limit.



8DPSK

EUT Test Condition		Measurement Detail			
Channel	Channel 0	Frequency Range	1 GHz ~ 25 GHz		
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)		
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Charles Hsiao		

	Antenna Polarity & Test Distance: Horizontal at 3 m									
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2389.02	44.58	42.87	54	-9.42	31.8	5.4	35.49	100	250	Average
2389.02	52.84	51.13	74	-21.16	31.8	5.4	35.49	100	250	Peak
2402	97.14	95.41			31.8	5.4	35.47	100	206	Average
2402	102.93	101.2			31.8	5.4	35.47	100	206	Peak
7206	42.58	32	54	-11.42	35.56	9.94	34.92	100	90	Average
7206	48.72	38.14	74	-25.28	35.56	9.94	34.92	100	90	Peak
		Δ	ntenna P	olarity &	Test Dista	ance: Vert	ical at 3 r	n		
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2389.02	40.12	38.41	54	-13.88	31.8	5.4	35.49	100	279	Average
2389.02	49.85	48.14	74	-24.15	31.8	5.4	35.49	100	279	Peak
2402	94.85	93.12			31.8	5.4	35.47	100	279	Average
2402	99.26	97.53			31.8	5.4	35.47	100	279	Peak
4804	36.56	28.47	54	-17.44	33.96	8.25	34.12	123	30	Average
4804	44.71	36.62	74	-29.29	33.96	8.25	34.12	123	30	Peak

- Emission Level = Read Level + Antenna Factor + Cable Loss Preamp Factor Margin value = Emission level – Limit value
- 2. 2402 MHz: Fundamental frequency.
- 3. The emission levels of other frequencies were very low against the limit.



EUT Test Condition		Measurement Detail			
Channel	Channel 39	Frequency Range	1 GHz ~ 25 GHz		
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)		
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Charles Hsiao		

	Antenna Polarity & Test Distance: Horizontal at 3 m									
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2344.74	37.18	35.61	54	-16.82	31.74	5.33	35.5	100	206	Average
2344.74	49.64	48.07	74	-24.36	31.74	5.33	35.5	100	206	Peak
2441	98.24	96.37			31.85	5.46	35.44	100	206	Average
2441	103.14	101.27			31.85	5.46	35.44	100	206	Peak
2488.8	37.59	35.58	54	-16.41	31.9	5.53	35.42	100	206	Average
2488.8	50.91	48.9	74	-23.09	31.9	5.53	35.42	100	206	Peak
7323	45.27	34.81	54	-8.73	35.53	9.95	35.02	100	80	Average
7323	51.09	40.63	74	-22.91	35.53	9.95	35.02	100	80	Peak
		Δ	ntenna P	olarity &	Test Dista	ance: Vert	ical at 3 r	n		
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2386.86	37.23	35.52	54	-16.77	31.8	5.4	35.49	100	268	Average
2386.86	49.76	48.05	74	-24.24	31.8	5.4	35.49	100	268	Peak
2441	94.57	92.7			31.85	5.46	35.44	100	268	Average
2441	99.81	97.94			31.85	5.46	35.44	100	268	Peak
2498.96	37.72	35.7	54	-16.28	31.9	5.53	35.41	100	268	Average
2498.96	50.63	48.61	74	-23.37	31.9	5.53	35.41	100	268	Peak
4882	36.68	28.49	54	-17.32	33.98	8.27	34.06	132	275	Average
4882	46.03	37.84	74	-27.97	33.98	8.27	34.06	132	275	Peak

- Emission Level = Read Level + Antenna Factor + Cable Loss Preamp Factor Margin value = Emission level – Limit value
- 2. 2441 MHz: Fundamental frequency.
- 3. The emission levels of other frequencies were very low against the limit.



EUT Test Condition		Measurement Detail			
Channel	Channel 78	Frequency Range	1 GHz ~ 25 GHz		
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Average (AV)		
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Charles Hsiao		

	Antenna Polarity & Test Distance: Horizontal at 3 m									
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2480	99.49	97.53			31.88	5.5	35.42	100	206	Average
2480	102.02	100.06			31.88	5.5	35.42	100	206	Peak
2493.04	46.92	44.9	54	-7.08	31.9	5.53	35.41	100	0	Average
2493.04	52.3	50.28	74	-21.7	31.9	5.53	35.41	100	0	Peak
7440	43.28	32.92	54	-10.72	35.51	9.96	35.11	126	77	Average
7440	50.14	39.78	74	-23.86	35.51	9.96	35.11	126	77	Peak
		Α	ntenna P	olarity &	Test Dista	ance: Vert	ical at 3 r	n		
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
2480	94.44	92.48			31.88	5.5	35.42	100	279	Average
2480	99.49	97.53			31.88	5.5	35.42	100	279	Peak
2493	40.31	38.29	54	-13.69	31.9	5.53	35.41	100	279	Average
2493	50.84	48.82	74	-23.16	31.9	5.53	35.41	100	279	Peak
4960	36.87	28.6	54	-17.13	33.99	8.29	34.01	104	12	Average
4960	45.22	36.95	74	-28.78	33.99	8.29	34.01	104	12	Peak

- Emission Level = Read Level + Antenna Factor + Cable Loss Preamp Factor Margin value = Emission level – Limit value
- 2. 2480 MHz: Fundamental frequency.
- 3. The emission levels of other frequencies were very low against the limit.




9 kHz ~ 30 MHz Data:

The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.


30 MHz ~ 1 GHz Worst-Case Data:

EUT Test Condition		Measurement Detail			
Channel	Channel 78	Frequency Range	30 MHz ~ 1 GHz		
Input Power	120 Vac, 60 Hz	Detector Function	Peak (PK) Quasi-peak (QP)		
Environmental Conditions	25 deg. C, 65 % RH	Tested By	Harry Hsueh		

Horizontal



Vertical





	Antenna Polarity & Test Distance: Horizontal at 3 m									
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
61.32	15.73	33.95	40	-24.27	13.11	0.9	32.23	141	152	Peak
89.67	22.02	42.16	43.5	-21.48	10.46	1.11	31.71	136	251	Peak
179.58	21.8	42.75	43.5	-21.7	9.68	1.61	32.24	107	158	Peak
395.9	26.9	41.86	46	-19.1	14.91	2.34	32.21	115	184	Peak
647.9	30.06	40.81	46	-15.94	18.41	2.99	32.15	107	142	Peak
749.4	24.61	33.73	46	-21.39	19.81	3.22	32.15	169	185	Peak
		Δ	ntenna P	olarity &	Test Dista	ance: Vert	ical at 3 r	n		
Frequency (MHz)	Emission Level (dBuV/m)	Read Level (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Antenna Height (cm)	Table Angle (Degree)	Remark
58.35	23.27	40.92	40	-16.73	13.68	0.9	32.23	112	136	Peak
119.91	8.94	29.75	43.5	-34.56	10.16	1.28	32.25	157	184	Peak
204.42	10.87	30.38	43.5	-32.63	11.12	1.65	32.28	105	126	Peak
384	19.85	35.02	46	-26.15	14.67	2.34	32.18	125	162	Peak
624.1	21.63	32.71	46	-24.37	18.16	2.93	32.17	112	132	Peak
737.5	21.92	31.21	46	-24.08	19.68	3.16	32.13	148	195	Peak

- Emission Level = Read Level + Antenna Factor + Cable Loss Preamp Factor Margin value = Emission level – Limit value
- 2. The emission levels of other frequencies were very low against the limit.



4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Evenuency (MU=)	Conducted Limit (dBuV)					
Frequency (MHz)	Quasi-Peak	Average				
0.15 - 0.5	66 - 56	56 - 46				
0.50 - 5.0	56	46				
5.0 - 30.0	60	50				

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

4.2.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Date of Calibration	Due Date of Calibration
Test Receiver ROHDE & SCHWARZ	ESCI	100613	Nov. 23, 2017	Nov. 22, 2018
RF signal cable Woken	5D-FB	Cable-cond1-01	Sep. 05, 2018	Sep. 04, 2019
LISN/AMN ROHDE & SCHWARZ (EUT)	ENV216	101826	Feb. 26, 2018	Feb. 25, 2019
LISN/AMN ROHDE & SCHWARZ (Peripheral)	ENV216	101196	Apr. 24, 2018	Apr. 23, 2019
Software ADT	BV ADT_Cond_ V7.3.7.3	NA	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

- 2. The test was performed in HwaYa Shielded Room 1.
- 3. The VCCI Site Registration No. is C-2040.



4.2.3 Test Procedures


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50 uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit 20 dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz - 30 MHz.

4.2.4 Deviation from Test Standard

No deviation.

4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Condition

Set the EUT under transmission condition continuously at specific channel frequency.

Report No.: RF180802C04-3 Page No. 26 / 48 Report Format Version: 6.1.1




4.2.7 Test Results

CONDUCTED WORST-CASE DATA: GFSK

Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25℃, 65%RH
Tested by	Jisyong Wang	Test Date	2018/8/21

	Phase Of Power : Line (L)									
	Frequency	Correction	Readin	g Value	Emissio	n Level	Lir	nit	Mai	rgin
No		Factor	(dB	uV)	(dB	uV)	(dB	uV)	(d	B)
	(MHz)	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.16173	9.67	35.48	20.01	45.15	29.68	65.37	55.37	-20.22	-25.69
2	0.21736	9.67	31.94	17.87	41.61	27.54	62.92	52.92	-21.31	-25.38
3	0.32614	9.67	31.23	17.71	40.90	27.38	59.55	49.55	-18.65	-22.17
4	0.43924	9.67	33.14	20.27	42.81	29.94	57.08	47.08	-14.27	-17.14
5	0.66221	9.68	40.36	25.07	50.04	34.75	56.00	46.00	-5.96	-11.25
6	3.61817	9.75	30.32	15.72	40.07	25.47	56.00	46.00	-15.93	-20.53

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value






Frequency Range	150kHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9kHz
Input Power	120Vac, 60Hz	Environmental Conditions	25℃, 65%RH
Tested by	Jisyong Wang	Test Date	2018/8/21

Phase Of Power : Neutral (N)										
	Frequency	Correction	Reading Value		Emission Level		Limit		Margin	
No		Factor	(dBuV)		(dBuV)		(dBuV)		(dB)	
	(MHz)	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.21621	9.68	31.43	18.17	41.11	27.85	62.96	52.96	-21.85	-25.11
2	0.27120	9.68	29.45	15.24	39.13	24.92	61.08	51.08	-21.95	-26.16
3	0.38099	9.68	31.80	18.47	41.48	28.15	58.26	48.26	-16.78	-20.11
4	0.43543	9.68	28.77	7.73	38.45	17.41	57.15	47.15	-18.70	-29.74
5	0.65734	9.68	40.20	35.99	49.88	45.67	56.00	46.00	-6.12	-0.33
6	1.69445	9.71	30.84	18.26	40.55	27.97	56.00	46.00	-15.45	-18.03

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value






4.3 Number of Hopping Frequency Used

4.3.1 Limits of Hopping Frequency Used Measurement

At least 15 channels frequencies, and should be equally spaced.

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedure

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
- d. Set the SA on View mode and then plot the result on SA screen.
- e. Repeat above procedures until all frequencies measured were complete.

4.3.5 Deviation from Test Standard


No deviation.




4.3.6 Test Results

There are 79 hopping frequencies in the hopping mode. Please refer to next page for the test result. On the plots, it shows that the hopping frequencies are equally spaced.

<GFSK>



<8DPSK>






4.4 Dwell Time on Each Channel

4.4.1 Limits of Dwell Time on Each Channel Measurement

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

4.4.2 Test Setup



4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.4 Test Procedures

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
- d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
- e. Repeat above procedures until all different time-slot modes have been completed.

4.4.5 Deviation from Test Standard

No deviation.

Report No.: RF180802C04-3 Page No. 31 / 48 Report Format Version: 6.1.1




4.4.6 Test Results

GFSK

Mode	Number of Transmission in a 31.6 (79 Hopping*0.4)	Length of Transmission Time (msec)	Result (msec)	Limit (sec)
DH1	50 (times / 5 sec) * 6.32 = 316 times	0.474	149.78	0.4
DH3	26 (times / 5 sec) * 6.32 = 164.32 times	1.85	303.99	0.4
DH5	16 (times / 5 sec) * 6.32 = 101.12 times	3.02	305.38	0.4

Note: Test plots of the transmitting time slot are shown as below.





8DPSK

Mode	Number of Transmission in a 31.6 (79 Hopping*0.4)	Length of Transmission Time (msec)	Result (msec)	Limit (sec)
3DH1	50 (times / 5 sec) * 6.32 = 316 times	0.468	147.89	0.4
3DH3	27 (times / 5 sec) * 6.32 = 170.64 times	1.73	295.21	0.4
3DH5	17 (times / 5 sec) * 6.32 = 107.44 times	3.01	323.39	0.4

Note: Test plots of the transmitting time slot are shown as below.






4.5 Channel Bandwidth

4.5.1 Limits of Channel Bandwidth Measurement

For frequency hopping system operating in the 2400-2483.5 MHz, if the 20 dB bandwidth of hopping channel is greater than 25 kHz, two-thirds 20 dB bandwidth of hopping channel shell be a minimum limit for the hopping channel separation.

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.5.4 Test Procedure

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth.
- d. Repeat above procedures until all frequencies measured were complete.

4.5.5 Deviation from Test Standard

No deviation.

4.5.6 EUT Operating Condition


The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

Report No.: RF180802C04-3 Page No. 34 / 48 Report Format Version: 6.1.1



4.5.7 Test Results


Channel	Frequency	20 dB Bandwidth (MHz)			
Channel	(MHz)	GFSK	8DPSK		
0	2402	1.02	1.29		
39	2441	1.01	1.30		
78	2480	1.04	1.30		





4.6 Occupied Bandwidth Measurement

4.6.1 Test Setup



4.6.2 Test Instruments

Refer to section 4.1.2 to get information of above instrument

4.6.3 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with resolution bandwidth in the range of 1 % to 5 % of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth and set the detector to PEAK. The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 % of the total mean power of a given emission.

4.6.4 Deviation from Test Standard

No deviation.

4.6.5 EUT Operating Conditions


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

Report No.: RF180802C04-3 Page No. 36 / 48 Report Format Version: 6.1.1



4.6.6 Test Results

Channal	Frequency	Occupied Bandwidth (MHz)			
Channel	(MHz)	GFSK	8DPSK		
0	2402	0.89	1.16		
39	2441	0.91	1.16		
78	2480	0.91	1.17		






4.7 Hopping Channel Separation

4.7.1 Limits of Hopping Channel Separation Measurement

At least 25 kHz or two-third of 20 dB hopping channel bandwidth (whichever is greater).

4.7.2 Test Setup



4.7.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.7.4 Test Procedure

Measurement Procedure REF

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
- c. By using the MaxHold function record the separation of two adjacent channels.
- d. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
- e. Repeat above procedures until all frequencies measured were complete.

4.7.5 Deviation from Test Standard

No deviation.




4.7.6 Test Results

Channel	Freq. (MHz)	Sepai	ration I		dB lth (MHz)	Minimum Limit (MHz)		Pass / Fail
		GFSK	8DPSK	GFSK	8DPSK	GFSK	8DPSK	
0	2402	1.00	1.00	1.02	1.29	0.68	0.86	Pass
39	2441	1.00	1.00	1.01	1.30	0.68	0.87	Pass
78	2480	1.00	1.00	1.04	1.30	0.70	0.87	Pass

Note:

1. The minimum limit is two-third 20 dB bandwidth.






4.8 Maximum Output Power

4.8.1 Limits of Maximum Output Power Measurement

The Maximum Output Power Measurement is 125 mW.

4.8.2 Test Setup



4.8.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.8.4 Test Procedure

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. The center frequency of the spectrum analyzer is set to the fundamental frequency and using 3 MHz RBW and 10 MHz VBW.
- d. Measure the captured power within the band and recording the plot.
- e. Repeat above procedures until all frequencies required were complete.

4.8.5 Deviation from Test Standard

No deviation.

4.8.6 EUT Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

Report No.: RF180802C04-3 Page No. 40 / 48 Report Format Version: 6.1.1




4.8.7 Test Results

<GFSK>

Channel	Freq. (MHz)	Output Power (mW)	Output Power (dBm)	Power Limit (mW)	Pass / Fail
0	2402	7.145	8.54	125	Pass
39	2441	7.852	8.95	125	Pass
78	2480	8.166	9.12	125	Pass

<8DPSK>

Channel	Freq. (MHz)	Output Power (mW)	Output Power (dBm)	Power Limit (mW)	Pass / Fail
0	2402	8.954	9.52	125	Pass
39	2441	9.931	9.97	125	Pass
78	2480	10.209	10.09	125	Pass





4.9 Conducted Out of Band Emission Measurement

4.9.1 Limits Of Conducted Out of Band Emission Measurement

Below –20 dB of the highest emission level of operating band (in 100 kHz RBW).

4.9.2 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.9.3 Test Procedure

The transmitter output was connected to the spectrum analyzer via a low lose cable. Set both RBW and VBW of spectrum analyzer to 100 kHz and 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. The band edges was measured and recorded.

4.9.4 Deviation from Test Standard

No deviation.

4.9.5 EUT Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

4.9.6 Test Results


The spectrum plots are attached on the following images. D1 line indicates the highest level, D2 line indicates the 20 dB offset below D1. It shows compliance with the requirement.

Report No.: RF180802C04-3 Page No. 42 / 48 Report Format Version: 6.1.1





















5 Pictures of Test Arrangements						
Please refer to the attached file (Test Setup Photo).						

Report No.: RF180802C04-3 Page No. 47 / 48 Report Format Version: 6.1.1



Appendix - Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-2-26052180 Fax: 886-2-26051924 Tel: 886-3-6668565 Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety

Tel: 886-3-3183232 Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com
Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---

Report No.: RF180802C04-3 Page No. 48 / 48 Report Format Version: 6.1.1