



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640

Fax: +86-755-26648637

Website: www.cqa-cert.com

Report Template Version: V04

Report Template Revision Date: 2018-07-06

RF Exposure Evaluation Report

Report No.: CQASZ20200901059E-02
Applicant: Avantronics Limited
Address of Applicant: The 4th Floor, Yuepeng Building, No.1019 Jiabin Rd, Luohu District, Shenzhen
Equipment Under Test (EUT):
EUT Name: Avantree Ensemble
Model No.: BTTC-5150
Brand Name: Avantree
FCC ID: WJ5-BTTC-5150
Standards: 47 CFR Part 1.1307
47 CFR Part 1.1310
KDB447498D01 General RF Exposure Guidance v06
Date of Receipt: 2020-09-17
Date of Test: 2020-09-17 to 2020-10-09
Date of Issue: 2020-10-09
Test Result: PASS*

*In the configuration tested, the EUT complied with the standards specified above

Tested By: Martin Lee
(Martin Lee)

Reviewed By: Sheek Luo
(Sheek Luo)

Approved By: Jack Ai
(Jack Ai)



1 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ20200901059E-02	Rev.01	Initial report	2020-10-09

2 Contents

	Page
1 VERSION	2
2 CONTENTS	3
3 GENERAL INFORMATION	4
3.1 CLIENT INFORMATION	4
3.2 GENERAL DESCRIPTION OF EUT	4
4 RF EXPOSURE EVALUATION.....	5
4.1 RF EXPOSURE COMPLIANCE REQUIREMENT.....	5
4.1.1 Limits	5
4.1.2 Test Procedure.....	5
4.2 1.1.3 EUT RF EXPOSURE EVALUATION.....	6

3 General Information

3.1 Client Information

Applicant:	Avantronics Limited
Address of Applicant:	The 4th Floor, Yuepeng Building, No.1019 Jiabin Rd, Luohu District, Shenzhen
Manufacturer:	Avantronics Limited
Address of Manufacturer:	The 4th Floor, Yuepeng Building, No.1019 Jiabin Rd, Luohu District, Shenzhen

3.2 General Description of EUT

Product Name:	Avantree Ensemble
Model No.:	BTTC-5150
Trade Mark:	Avantree
Hardware Version:	V03
Software Version:	V028
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V5.0
Modulation Technique:	Frequency Hopping Spread Spectrum(FHSS)
Modulation Type:	GFSK, $\pi/4$ DQPSK, 8DPSK
Transfer Rate:	1Mbps/2Mbps/3Mbps
Number of Channel:	79
Hopping Channel Type:	Adaptive Frequency Hopping systems
Product Type:	☐ Mobile ☐ Portable ☒ Fix Location
Test Software of EUT:	Blue test 3 (manufacturer declare)
Antenna Type:	PCB antenna
Antenna Gain:	1.8dBi
Power Supply:	DC5V

4 RF Exposure Evaluation

4.1 RF Exposure Compliance Requirement

4.1.1 Limits

According to FCC Part1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in part1.1307(b)

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500			f/300	6
1500–100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500			f/1500	30
1500–100,000			1.0	30

F= Frequency in MHz

Friis Formula

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

4.1.2 Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

4.2 1.1.3 EUT RF Exposure Evaluation

1) For BT

Antenna Gain: 1.8dBi

Antenna Gain: The maximum Gain measured in fully anechoic chamber is 1.51 in linear scale.

Output Power Into Antenna & RF Exposure Evaluation Distance:

Measurement Data

GFSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	-1.680	-2.5±1	-1.5	0.708
Middle(2441MHz)	1.850	1.0±1	2.0	1.585
Highest(2480MHz)	2.440	1.5±1	2.5	1.778
π/4DQPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	-6.000	-6.5±1	-5.5	0.282
Middle(2441MHz)	-2.190	-3.0±1	-2.0	0.631
Highest(2480MHz)	-1.610	-2.5±1	-1.5	0.708
8DPSK mode				
Test channel	Peak Output Power (dBm)	Tune up tolerance (dBm)	Maximum tune-up Power	
			(dBm)	(mW)
Lowest(2402MHz)	-4.930	-5.5±1	-4.5	0.355
Middle(2441MHz)	-1.100	-2.0±1	-1.0	0.794
Highest(2480MHz)	-0.510	-1.5±1	-0.5	0.891

The worst case:

Maximum tune-up Power (mW)	Antenna Gain (dBi)	Power Density at R = 20 cm (mW/cm ²)	Limit	Result
1.778	1.8	0.0005	1.0	PASS

Note: 1) Refer to report No. CQASZ20200901059E-01 for EUT test Max Conducted Peak Output Power value.

$$2) P_d = (P_{out} * G) / (4 * \pi * R^2) = (1.778 * 1.51) / (4 * 3.1416 * 20^2) = 0.0005$$