

RF EXPOSURE REPORT

OF

Applicant: MARS TOHKEN SOLUTION CO.LTD
1-10-7 Shinjuku, Shinjuku-ku, Tokyo 160-0022, Japan

Product Name: UHF RFID READER/WRITER MODULE

Brand Name: MARS

Model No.: FRU-4100Q

Model Difference: N/A

Report Number: E2/2020/50002

FCC ID: WK4FRU4100Q

FCC Rule Part Part 2.1091

Issue Date: May 22, 2020

We hereby certify that:

The above equipment was verified by SGS Taiwan Ltd. The evaluation in this report is in compliance with the above rule(s).

The results of this report relate only to the sample identified in this report.

Approved By: _____

Yeh John / Asst. Manager

John Teh



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Revision History

Report Number	Revision	Description	Issue Date	Remark
E2/2020/50002	Rev.00	Original.	May 22, 2020	Revised By: Yuri Tsai

Note:**Disclaimer:**

Antenna information is provided by the applicant, test results of this report are applicable to the sample EUT received.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Table of Contents

1	DESCRIPTION OF EQUIPMENT UNDER TEST (EUT).....	4
2	FCC MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	5

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

1 DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)

1.1 General:

Product Name:	UHF RFID READER/WRITER
Brand Name:	MaRS
Model No. of Host:	MRU-F5100US
Model Difference:	N/A
Hardware Version:	N/A
Software Version:	N/A
Model No. of RFID Module:	FRU-4100Q
Module FCC ID:	WK4FRU4100Q
Scope:	The test report covers the radiated emissions requirements of the standards referenced in the report to allow system level approval of the module in this specific host.
Class II Permissive change:	UHF RFID READER/WRITER MODULE INSTALLED IN UHF RFID READER/WRITER
Power Supply:	DC 12V / 24V

Radio Technology:	RFID
Frequency Range:	902.75 – 927.25MHz
Channel number:	50 channels
Modulation type:	PR-ASK, ASK
Transmit Power:	28.99dBm (Peak)
Dwell Time:	<= 0.4s
Operating Mode:	Point-to-Point
Antenna Designation:	1. Patch Antenna , Gain: 4.75dBi, Model No.: UAT-002 2. Patch Antenna , Gain: -1.5dBi, Model No.: UAT-006 3. Patch Antenna , Gain: 4.12dBi, Model No.: A6034_70809 4. Patch Antenna , Gain: 5.7dBi, Model No.: RAF2031

1.2 Maximum Output power

The Max. output power value is derived from test report.

RFID	Report Number:	E2/2020/40028
	Test Lab:	SGS Taiwan Ltd.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

2 FCC MAXIMUM PERMISSIBLE EXPOSURE (MPE)

2.1 FCC Standard Applicable

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

This is a Mobile device, the MPE is required.

According to §1.1310 and §2.1091 RF exposure is calculated.

Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-15000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equipment power density

Prediction of MPE limit at a given distance

$$S = PG / 4\pi R^2$$

Where: S = Power density

P = Power input to antenna

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

2.2 Power Density Calculation (Worst Case)

RFID					
CH	Freq. (MHz)	Peak Output Power (dBm)	Peak Output Power (mW)	Limit	RESULT
1	902.75	28.90	776.25	1 Watt = 30.00 dBm	PASS
25	914.75	28.99	792.50	1 Watt = 30.00 dBm	PASS
50	927.25	28.85	767.36	1 Watt = 30.00 dBm	PASS
RFID					
CH	Freq. (MHz)	Avg. Output Power (dBm)	Avg. Output Power (mW)	Limit	RESULT
1	902.75	26.91	490.91	1 Watt = 30.00 dBm	PASS
25	914.75	26.93	493.17	1 Watt = 30.00 dBm	PASS
50	927.25	26.86	485.29	1 Watt = 30.00 dBm	PASS

FCC Standalone MPE

Operation Mode	Evaluation Frequency (MHz)	Operation Distance (cm)	Max. output Power (dBm)	Antenna Gain (dBi)	Max. output Power EIRP (mW)	Power Density (PD) (mW/cm ²)	Limit (mW/cm ²)	Pass / Fail	Power Density / Limit
RFID	914.75	20	26.93	5.70	1832.31	0.365	0.610	Pass	0.598

Note: For conservativeness, the lowest uplink frequency of each band is used to determine the MPE limit of that band.

~ End of Report ~

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.