



Maximum Permissible Exposure Evaluation

FCC ID: WKA-SDM802

Report No.	:	TBR-C-202503-0183-8	
Applicant	:	MAXELL CORPORATION OF AMERICA	
Equipment Under Test (EUT)			
EUT Name	:	Voice Amplifier	
Model No.	:	VC-AMP	
Series Model No.	:	M802	
Brand Name	:	----	
Sample ID	:	HC-C-202503-0183-01-1#&HC-C-202503-0183-01-2#	
Receipt Date	:	2025-03-20	
Test Date	:	2025-03-20 to 2025-04-09	
Issue Date	:	2025-04-09	
Standards	:	FCC Part 2.1093	
Test Method	:	KDB 447498 D01 General RF Exposure Guidance v06	
Conclusions	:	PASS	
		In the configuration tested, the EUT complied with the standards specified above.	
Test By	:	Lily.zhang	Lily Zhang
Reviewed By	:	Emily	Emily Tang
Approved By	:	Ivan Su	Ivan Su

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.

CONTENTS

CONTENTS.....	2
1. GENERAL INFORMATION ABOUT EUT.....	4
1.1 Client Information.....	4
1.2 General Description of EUT (Equipment Under Test)	4
2. TEST FACILITY.....	5
3. SAR TEST EXCLUSION CALCULATIONS.....	6



Revision History



1. General Information about EUT

1.1 Client Information

Applicant	:	MAXELL CORPORATION OF AMERICA
Address	:	3 Garret Mountain Plaza, Woodland Park, New Jersey, 07424 United States
Manufacturer	:	SHENZHEN SHIDU DIGITAL CO., LTD
Address	:	Building A8, Zone 2, Xinhe Xinxing Industrial Park, Fuhai Street, Baoan District, Shenzhen, China

1.2 General Description of EUT (Equipment Under Test)

EUT Name	:	Voice Amplifier	
Models No.	:	VC-AMP, M802	
Model Different	:	All these models are identical in the same PCB, layout and electrical circuit, The only difference is appearance.	
Product Description	Operation Frequency:	Bluetooth V5.0 (BR+EDR): 2402MHz~2480MHz	
	Modulation Type:	Bluetooth: GFSK, Pi/4-DQPSK, 8DPSK	
	Antenna Gain:	0dBi PCB Antenna	
Power Rating	:	Input: DC 5V, 1A	
Li-ion Polymer Battery	:	3.7V by 2000mAh Rechargeable Li-ion battery	
Software Version	:	V1	
Hardware Version	:	V1	

Remark: The above antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.



2. Test Facility

The testing report were performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at 1/F., Building 6, Rundongsheng Industrial Zone, Longzhu, Xixiang, Bao'an District, Shenzhen, Guangdong, China. At the time of testing, the following bodies accredited the Laboratory:

CNAS (L5813)

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

A2LA Certificate No.: 4750.01

The laboratory has been accredited by American Association for Laboratory Accreditation(A2LA) to ISO/IEC 17025: 2017 General Requirements for the Competence of Testing and Calibration Laboratories for the technical competence in the field of Electrical Testing. And the A2LA Certificate No.: 4750.01.FCC Accredited Test Site Number: 854351. Designation Number: CN1223.

IC Registration No.: (11950A)

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A. CAB identifier: CN0056.



3. SAR Test Exclusion Calculations

4.1 FCC: According to KDB 447498 D01 v06 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v06.

(1) Clause 4.3: General SAR test reduction and exclusion guidance

Sub clause 4.31: Standalone SAR test exclusion considerations

- 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6GHz at test separation distance ≤ 5 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] * [\sqrt{f_{(\text{GHz})}}] \leq 3.0 \text{ for 1-g SAR}$

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] * [\sqrt{f_{(\text{GHz})}}] \leq 7.5.0 \text{ for 10-g SAR}$

4.2 Summary simultaneous transmission for SAR Exclusion

The SAR exemption limits outlined in clause 4.3.2(b) of KDB 447498 have been derived based on an approximate SAR value of 0.4 W/kg using half-wave dipole antennas Footnote 1. As such, when simultaneous transmitter SAR evaluations include transmitters that have been exempt from routine SAR evaluation, the SAR must be estimated based on the ratio between the maximum tune-up tolerance limit of the transmitter that has been exempt and the exemption limit at the specific distance and frequency for that transmitter. This ratio must be multiplied by 0.4 W/kg (2.0 W/kg for controlled use and 1.0 W/kg for limb worn devices) in order to calculate the estimated SAR level.

The estimated SAR value is calculated based on the following equation:

(maximum power level including tune-up tolerance for transmitter A / maximum power level of exemption at the same frequency and distance) * 0.4W/kg

- 1) $[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] * [\sqrt{f_{(\text{GHz})}}/x] \text{ W/kg, for test separation distances} \leq 50 \text{ mm};$
where $x = 7.5$ for 1-g SAR and $x = 18.75$ for 10-g SAR.
- 2) 0.4 W/kg for 1-g SAR and 1.0 W/kg for 10-g SAR, when the test separation distance is > 50 mm.³⁷

The $[\sum \text{ of (the highest measured or estimated SAR for each standalone antenna configuration, adjusted for maximum tune-up tolerance) / 1.6 W/kg} + [\sum \text{ of MPE ratios}]] \leq 1.0$.

The SAR to peak location separation ratios of all simultaneously transmitting antenna pairs operating in portable device exposure conditions are all ≤ 0.04 , and the $[\sum \text{ of MPE ratios}] \leq 1.0$.



4.3 Calculation:

Test separation: 5mm						
Bluetooth Mode (GFSK)						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	2.044	2±1	3	1.995	0.618	3.0
2.441	1.787	2±1	3	1.995	0.623	3.0
2.480	3.052	3±1	4	2.512	0.791	3.0
Bluetooth Mode (Pi/4-DQPSK)						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	3.967	4±1	5	3.162	0.980	3.0
2.441	3.706	4±1	5	3.162	0.988	3.0
2.480	2.902	3±1	4	2.512	0.791	3.0
Bluetooth Mode (8-DPSK)						
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (dBm)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	4.385	4±1	5	3.162	0.980	3.0
2.441	3.913	4±1	5	3.162	0.988	3.0
2.480	3.306	3±1	4	2.512	0.791	3.0

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 D01 v06.

-----END OF THE REPORT-----

