



# PCTEST ENGINEERING LABORATORY, INC.

6660-B Dobbin Road, Columbia, MD 21045 USA

Tel. 410.290.6652 / Fax 410.290.6554

<http://www.pctestlab.com>



## RF EXPOSURE EVALUATION (MAXIMUM PERMISSIBLE EXPOSURE)

**Applicant Name:**

NextWave Broadband, Inc.  
3611 Valley Centre Drive  
San Diego, CA 92130  
United States

**Date of Testing:**

August 12 - 14, 2008

**Test Site/Location:**

PCTEST Lab, Columbia, MD, USA

**Test Report Serial No.:**

0808141129.WKH

**FCC ID:** WKH-BMX-SPT**APPLICANT:** NextWave Broadband, Inc.**EUT Type:** WiMAX Module**FCC Rule Part(s):** FCC Part 1 (§1.1310) and Part 2 (§2.1091)**FCC Classification:** Licensed Non-Broadcast Transmitter (TNB)**Operating Frequency:** 2489.25MHz**Test Procedure:** OET Bulletin 65

**Note:** This report is prepared based on FCC Order FCC-08-98A1 regarding the GlobalStar ATC waiver request.

The device bearing the FCC Identifier specified above has been shown to comply with the applicable technical standards as indicated in the measurement report and has been tested in accordance with the measurement procedures specified in FCC OET Bulletin 65 (See Test Report). These measurements were performed with no deviation from the standards.

I authorize and attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

*PCTEST certifies that no party to this application has been denied the FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.*

  
\_\_\_\_\_  
Randy Ortanez  
President

FCC ID: WKH-BMX-SPT	MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT		Reviewed by: Quality Manager
Test Report S/N: 0808141129.WKH	Test Dates: August 12 - 14, 2008	EUT Type: WiMAX Module	Page 1 of 6

## T A B L E   O F   C O N T E N T S

---

1.0	RF EXPOSURE EVALUATION – MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	3
1.1	INTRODUCTION .....	3
1.2	EUT DESCRIPTION.....	3
1.3	MPE REQUIREMENTS OVERVIEW.....	4
1.4	PROCEDURE.....	5
1.5	SUMMARY OF RESULTS.....	5
2.0	CONCLUSION.....	6

FCC ID: WKH-BMX-SPT	 PCTEST ENGINEERING LABORATORY, INC.	MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT	 NextWave WIRELESS	Reviewed by: Quality Manager
Test Report S/N: 0808141129.WKH	Test Dates: August 12 - 14, 2008	EUT Type: WiMAX Module		Page 2 of 6

## 1.0 RF EXPOSURE EVALUATION – MAXIMUM PERMISSIBLE EXPOSURE (MPE)

### 1.1 Introduction

This document is prepared on behalf of NextWave Broadband, Inc. to show compliance with the RF Exposure requirements as required in §1.1310 of the FCC Rules and Regulations and RSS-102 of Industry Canada.

The limit for Maximum Permissible Exposure (MPE), specified in FCC §1.1310, is listed in Table 1-1. According to FCC §1.1310 and RSS-102: the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b).

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Average Time (Minutes)
(A) Limits For Occupational / Control Exposures (f = frequency)				
30-300	61.4	0.163	1.0	6
300-1500	...	...	f/300	6
1500-100,000	...	...	5.0	6
(B) Limits For General Population / Uncontrolled Exposure (f = frequency)				
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

**Table 1-1. Limits for Maximum Permissible Exposure (MPE)**

### 1.2 EUT Description

The NextWave FCC ID: WKH-BMX-SPT is a WiMAX module integrated into a Spot Satellite Personal Tracker, previously certified under FCC ID: L2V-PT1. The Spot transmitter is a satellite locating system (GlobalStar) operating in the 1.6GHz band and the WiMAX transmitter operates at 2489.25MHz. Only one of the two transmitters can operate at any given time while the other transmitter is shutdown through internal software. The WiMAX transmitter operation is completely controlled through software installed on a laptop that communicates via USB connection with the EUT. The WiMAX transmitter is only operable when connected to a PC via the provided USB cable and uses a permanently attached antenna. The Spot transmitter is used in a portable condition. Please refer to separate SAR test report for RF exposure information for the Spot transmitter.

**EUT:**

Grantee: NextWave Broadband, Inc.  
 FCC ID: WKH-BMX-SPT (WiMAX Module)  
                   L2V-PT1 (Previously certified Spot transmitter)  
 WiMAX Operating Frequency: 2489.25MHz

FCC ID: WKH-BMX-SPT	MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT			Reviewed by: Quality Manager
Test Report S/N: 0808141129.WKH	Test Dates: August 12 - 14, 2008	EUT Type: WiMAX Module		Page 3 of 6

### 1.3 MPE Requirements Overview

Three different categories of transmitters are defined by the FCC in OET Bulletin 65. These categories are fixed installation, mobile, and portable and are defined as follows:

- **Fixed Installations:** fixed location means that the device, including its antenna, is physically secured at a permanent location and is not able to be easily moved to another location. Additionally, distance to humans from the antenna is maintained to at least 2 meters.
- **Mobile Devices:** a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to be generally used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structures and the body of the user or nearby persons. Transmitters designed to be used by consumers or workers that can be easily re-located, such as a wireless modem operating in a laptop computer, are considered mobile devices if they meet the 20 centimeter separation requirement. The FCC rules for evaluating mobile devices for RF compliance are found in 47 CFR §2.1091.
- **Portable Devices:** a portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user. Portable device requirements are found in Section 2.1093 of the FCC's Rules (47 CFR§2.1093).

The FCC also categorizes the use of the device as based upon the user's awareness and ability to exercise control over his or her exposure. The two categories defined are Occupational/ Controlled Exposure and General Population/Uncontrolled Exposure. These two categories are defined as follows:

- **Occupational/Controlled Exposure:** In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means. Awareness of the potential for RF exposure in a workplace or similar environment can be provided through specific training as part of a RF safety program. If appropriate, warning signs and labels can also be used to establish such awareness by providing prominent information on the risk of potential exposure and instructions on methods to minimize such exposure risks.
- **General Population/Uncontrolled Exposure:** The general population / uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

The NextWave WiMAX Module FCC ID: WKH-BMX-SPT is evaluated to the Mobile Device requirements and is considered a device to be used by the General Population/Uncontrolled Exposure.

FCC ID: WKH-BMX-SPT	PCTEST <sup>®</sup> Engineering Laboratory, Inc.		MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT	Reviewed by: Quality Manager
Test Report S/N: 0808141129.WKH	Test Dates: August 12 - 14, 2008	EUT Type: WiMAX Module		Page 4 of 6
© 2008 PCTEST Engineering Laboratory, Inc.				

## 1.4 Procedure

The procedure used to determine the RF power density was based upon a calculation for determining compliance with the MPE requirements.

The maximum peak EIRP generated by the WiMAX transmitter used in this product was measured with a spectrum analyzer and the power was recorded. Through use of the Friis transmission formula, the power density level is calculated at a distance of 20cm.

### Friis Transmission Formula

Friis transmission formula:  $P_d = \text{EIRP} / (4\pi r^2)$

Where,

$$\text{EIRP} = P_{\text{out}} * G$$

$$\pi = 3.1416$$

$P_{\text{out}}$  = output power to antenna (mW)

$r$  = distance between observation point and center of the radiator (cm)

$G$  = gain of antenna in linear scale

### Calculated MPE

The power density limit for General Population/Uncontrolled Exposure at each frequency is determined based on the information in Table 1-1.

Since only one transmitter can operate at any given time, there is no co-location between the electric fields of the two transmitters in this device, therefore the following power density is calculated only for the WiMAX transmitter at 20cm spacing:

Frequency Limit	2489.25 MHz
Distance (cm), R =	1.000 mW/cm <sup>2</sup>
EIRP (dBm), PG =	20 cm
Power Density (S) =	16.141 dBm
Minimum Distance =	41.12 mW
	<b>0.008</b> mW/cm <sup>2</sup> (at 20cm)
	<b>1.8</b> cm

Table 1-2. Calculated MPE Data for Cellular Band

## 1.5 Summary of Results

Operating Frequency [MHz]	Maximum Peak EIRP [dBm]	MPE @ 20cm (mW/cm <sup>2</sup> )	Test Result
2489.25	16.141	0.008	PASS

Table 1-3. Maximum Permissible Exposure Summary Table

FCC ID: WKH-BMX-SPT	MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT			Reviewed by: Quality Manager
Test Report S/N: 0808141129.WKH	Test Dates: August 12 - 14, 2008	EUT Type: WiMAX Module		Page 5 of 6

## 2.0 CONCLUSION

The device meets the mobile RF exposure limit at a 20cm separation distance as specified in §2.1091 of the FCC Rules and Regulations and Health Canada Safety Code 6. An appropriate RF exposure compliance statement will be placed in the user's manual.

FCC ID: WKH-BMX-SPT	 PCTEST ENGINEERING LABORATORY, INC.	MAXIMUM PERMISSIBLE EXPOSURE (MPE) DATA REPORT	 NextWave WIRELESS	Reviewed by: Quality Manager
Test Report S/N: 0808141129.WKH	Test Dates: August 12 - 14, 2008	EUT Type: WiMAX Module		Page 6 of 6