



# FCC Test Report

**Equipment** : Tablet PC  
**Brand Name** : ECS ELITEGROUP  
**Model No.** : TA80CA1, TA80CA2, TA80CA5, TA80CAx  
(x=0~9, A~Z or blank or "-")  
**FCC ID** : WL6-TABC8CA1  
**Standard** : 47 CFR FCC Part 15.247  
**Operating Band** : 2400 MHz – 2483.5 MHz  
**Equipment Class** : DTS  
**Applicant** : ELITEGROUP COMPUTER SYSTEM CO., LTD  
No.239, Sec. 2, Ti Ding Blvd., Taipei, Taiwan  
**Manufacturer** : Golden Elite Technology (SHENZHEN) Co., Ltd.  
No.1 , Nan-Huan Rd., Shajing, BaoAn, Shen zhen, China  
**WiFi/BT Module** : Broadcom / BCM4330

The product sample received on Dec. 09, 2013 and completely tested on Dec. 17, 2013. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2009 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:

  
\_\_\_\_\_  
Wayne Hsu / Assistant Manager





## Table of Contents

<b>1</b>	<b>GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1	Information.....	5
1.2	Accessories .....	7
1.3	Support Equipment .....	7
1.4	Testing Applied Standards .....	7
1.5	Testing Location Information .....	7
1.6	Measurement Uncertainty .....	8
<b>2</b>	<b>TEST CONFIGURATION OF EUT .....</b>	<b>9</b>
2.1	The Worst Case Modulation Configuration .....	9
2.2	The Worst Case Power Setting Parameter .....	9
2.3	The Worst Case Measurement Configuration .....	10
2.4	Test Setup Diagram .....	11
<b>3</b>	<b>TRANSMITTER TEST RESULT .....</b>	<b>13</b>
3.1	AC Power-line Conducted Emissions .....	13
3.2	6dB Bandwidth.....	16
3.3	RF Output Power .....	18
3.4	Power Spectral Density .....	22
3.5	Transmitter Bandedge Emissions.....	24
3.6	Transmitter Unwanted Emissions .....	27
<b>4</b>	<b>TEST EQUIPMENT AND CALIBRATION DATA.....</b>	<b>50</b>

### APPENDIX A. TEST PHOTOS

### APPENDIX B. PHOTOGRAPHS OF EUT



## Summary of Test Result

Conformance Test Specifications					
Report Clause	Ref. Std. Clause	Description	Measured	Limit	Result
1.1.2	15.203	Antenna Requirement	Antenna connector mechanism complied	FCC 15.203	Complied
3.1	15.207	AC Power-line Conducted Emissions	[dBuV]: 0.1863950MHz 49.92 (Margin 14.28dB) - QP 39.34 (Margin 14.86dB) - AV	FCC 15.207	Complied
3.2	15.247(a)	Bandwidth	6dB Bandwidth Unit [MHz]: 6.57	$\geq$ 500kHz	Complied
3.3	15.247(b)	RF Output Power (Maximum Peak Conducted Output Power)	Power [dBm]:18.80	Power [dBm]:30	Complied
3.4	15.247(d)	Power Spectral Density	PSD [dBm/100kHz]:-7.90	PSD [dBm/3kHz]:8	Complied
3.5	15.247(c)	Transmitter Radiated Bandedge Emissions	Non-Restricted Bands: 2510.70MHz: 29.71dB Restricted Bands [dBuV/m at 3m]: 2390.00MHz 69.54 (Margin 4.46dB) - PK 49.39 (Margin 4.61dB) - AV	Non-Restricted Bands: > 20 dBc Restricted Bands: FCC 15.209	Complied
3.6	15.247(c)	Transmitter Radiated Unwanted Emissions	[dBuV/m at 3m]: 4874.000MHz 55.87 (Margin 18.13dB) - PK 51.96 (Margin 2.04dB) - AV	Non-Restricted Bands: > 20 dBc Restricted Bands: FCC 15.209	Complied



## Revision History



## 1 General Description

### 1.1 Information

#### 1.1.1 RF General Information

RF General Information						
Frequency Range (MHz)	IEEE Std. 802.11	Ch. Freq. (MHz)	Channel Number	Transmit Chains (N <sub>TX</sub> )	RF Output Power (dBm)	Co-location
2400-2483.5	b	2412-2462	1-11 [11]	1	18.80	N/A
2400-2483.5	g	2412-2462	1-11 [11]	1	16.25	N/A
2400-2483.5	n (HT20)	2412-2462	1-11 [11]	1	16.19	N/A

Note 1: RF output power specifies that Maximum Peak Conducted Output Power.  
Note 2: 802.11b uses a combination of DSSS-DBPSK, DQPSK, CCK modulation.  
Note 3: 802.11g/n uses a combination of OFDM-BPSK, QPSK, 16QAM, 64QAM modulation.  
Note 4: Co-location, Co-location is generally defined as simultaneously transmitting (co-transmitting) antennas within 20 cm of each other. (i.e., EUT has simultaneously co-transmitting that operating 2.4GHz and 5GHz.)

#### 1.1.2 Antenna Information

Antenna Category	
<input checked="" type="checkbox"/>	Integral antenna (antenna permanently attached)
<input checked="" type="checkbox"/>	Temporary RF connector provided
<input type="checkbox"/>	No temporary RF connector provided Transmit chains bypass antenna and soldered temporary RF connector provided for connected measurement. In case of conducted measurements the transmitter shall be connected to the measuring equipment via a suitable attenuator and correct for all losses in the RF path.

Antenna General Information			
No.	Ant. Cat.	Ant. Type	Gain (dBi)
1	Integral	PIFA	3.10



### 1.1.3 Type of EUT

Identify EUT	
EUT Serial Number	N/A
Presentation of Equipment	<input checked="" type="checkbox"/> Production ; <input type="checkbox"/> Pre-Production ; <input type="checkbox"/> Prototype
Type of EUT	
<input checked="" type="checkbox"/> Stand-alone	
<input type="checkbox"/> Combined (EUT where the radio part is fully integrated within another device) Combined Equipment - Brand Name / Model No.:	
<input type="checkbox"/> Plug-in radio (EUT intended for a variety of host systems) Host System - Brand Name / Model No.:	
<input type="checkbox"/> Other:	

### 1.1.4 Test Signal Duty Cycle

Operated Mode for Worst Duty Cycle	
<input type="checkbox"/> Operated normally mode for worst duty cycle	
<input checked="" type="checkbox"/> Operated test mode for worst duty cycle	
Test Signal Duty Cycle (x)	Power Duty Factor [dB] – (10 log 1/x)
<input checked="" type="checkbox"/> 100% - IEEE 802.11b	0
<input checked="" type="checkbox"/> 100% - IEEE 802.11g	0
<input checked="" type="checkbox"/> 100% - IEEE 802.11n (HT20)	0

### 1.1.5 EUT Operational Condition

Supply Voltage	<input checked="" type="checkbox"/> AC mains	<input type="checkbox"/> DC	<input type="checkbox"/> System
Type of DC Source	<input type="checkbox"/> Internal DC supply	<input checked="" type="checkbox"/> External DC adapter	<input checked="" type="checkbox"/> Battery



## 1.2 Accessories

Accessories Information				
AC Adapter	Brand Name	Chicony	Model Name	W12-010N3F
	Power Rating	I/P: 100-240V~ 50/60Hz 0.3A	O/P: 5V	--- 2A

Reminder: Regarding to more detail and other information, please refer to user manual.

## 1.3 Support Equipment

Support Equipment					
No.	Equipment	Brand Name	Model Name	FCC ID	Test Condition
1	Notebook	DELL	PP25L	DoC	AC Conduction
2	Notebook	DELL	E5530	DoC	Radiated Emission

## 1.4 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 15
- ♦ ANSI C63.10-2009
- ♦ FCC KDB 558074
- ♦ FCC KDB 662911

## 1.5 Testing Location Information

Testing Location			
<input checked="" type="checkbox"/>	HWA YA	ADD :	No. 52, Hwa Ya 1 <sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.
	TEL :	886-3-327-3456	FAX : 886-3-327-0973
Test Condition	Test Site No.	Test Engineer	Test Environment
AC Conduction	CO04-HY	Zeus	24°C / 51%
RF Conducted	TH01-HY	Ian	22.1°C / 61%
Radiated Emission	03CH03-HY	Leo	26.2°C / 53%



## 1.6 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)

Measurement Uncertainty		
Test Item	Uncertainty	
AC power-line conducted emissions	$\pm 2.26$ dB	
Emission bandwidth, 6dB bandwidth	$\pm 1.42$ %	
RF output power, conducted	$\pm 0.63$ dB	
Power density, conducted	$\pm 0.81$ dB	
Unwanted emissions, conducted	9 – 150 kHz	$\pm 0.38$ dB
	0.15 – 30 MHz	$\pm 0.42$ dB
	30 – 1000 MHz	$\pm 0.51$ dB
	1 – 18 GHz	$\pm 0.67$ dB
	18 – 40 GHz	$\pm 0.83$ dB
	40 – 200 GHz	N/A
All emissions, radiated	9 – 150 kHz	$\pm 2.49$ dB
	0.15 – 30 MHz	$\pm 2.28$ dB
	30 – 1000 MHz	$\pm 2.56$ dB
	1 – 18 GHz	$\pm 3.59$ dB
	18 – 40 GHz	$\pm 3.82$ dB
	40 – 200 GHz	N/A
Temperature	$\pm 0.8$ °C	
Humidity	$\pm 3$ %	
DC and low frequency voltages	$\pm 3$ %	
Time	$\pm 1.42$ %	
Duty Cycle	$\pm 1.42$ %	



## 2 Test Configuration of EUT

### 2.1 The Worst Case Modulation Configuration

Worst Modulation Used for Conformance Testing			
Modulation Mode	Transmit Chains (N <sub>TX</sub> )	Data Rate / MCS	Worst Data Rate / MCS
11b,1-11Mbps	1	1-11 Mbps	1 Mbps
11g,6-54Mbps	1	6-54 Mbps	6 Mbps
HT20,M0-7	1	M0-7	MCS 0

### 2.2 The Worst Case Power Setting Parameter

The Worst Case Power Setting Parameter (2400-2483.5MHz band)					
Test Software Version	Dos				
Modulation Mode	N <sub>TX</sub>	Test Frequency (MHz)			
		NCB: 20MHz			
		2412	2437	2462	
11b,1-11Mbps	1	16	16	16	
11g,6-54Mbps	1	11	11	11	
HT20,M0-7	1	11	11	11	



## 2.3 The Worst Case Measurement Configuration

The Worst Case Mode for Following Conformance Tests	
<b>Tests Item</b>	AC power-line conducted emissions
<b>Condition</b>	AC power-line conducted measurement for line and neutral Test Voltage: 120Vac / 60Hz
<b>Operating Mode</b>	Operating Mode Description
1	AC Power & Radio link (WLAN) (Transmission)
2	USB Power & Radio link (WLAN) (Transmission)


For operating mode 2 is the worst case and it was record in this test report.



The Worst Case Mode for Following Conformance Tests	
<b>Tests Item</b>	RF Output Power, Power Spectral Density, 6 dB Bandwidth
<b>Test Condition</b>	Conducted measurement at transmit chains
<b>Modulation Mode</b>	11b, 11g, HT20

The Worst Case Mode for Following Conformance Tests							
<b>Tests Item</b>	Transmitter Radiated Unwanted Emissions Transmitter Radiated Bandedge Emissions						
<b>Test Condition</b>	Radiated measurement If EUT consist of multiple antenna assembly (multiple antenna are used in EUT regardless of spatial multiplexing MIMO configuration), the radiated test should be performed with highest antenna gain of each antenna type.						
<b>User Position</b>	<input type="checkbox"/> EUT will be placed in fixed position. <input checked="" type="checkbox"/> EUT will be placed in mobile position and operating multiple positions. EUT shall be performed three orthogonal planes. The worst planes is X. <input type="checkbox"/> EUT will be a hand-held or body-worn battery-powered devices and operating multiple positions. EUT shall be performed two or three orthogonal planes.						
<b>Operating Mode &lt; 1GHz</b>	<input checked="" type="checkbox"/> 1. AC Power & Radio link (WLAN) (Transmission) <input checked="" type="checkbox"/> 2. USB Power & Radio link (WLAN) (Transmission) For operating mode 2 is the worst case and it was record in this test report.						
<b>Operating Mode &gt; 1GHz</b>	<input checked="" type="checkbox"/> 2. USB Power & Radio link (WLAN) (Transmission)						
<b>Modulation Mode</b>	11b, 11g, HT20						
<b>Orthogonal Planes of EUT</b>	<table border="1"> <thead> <tr> <th>X Plane</th> <th>Y Plane</th> <th>Z Plane</th> </tr> </thead> <tbody> <tr> <td></td> <td></td> <td></td> </tr> </tbody> </table>	X Plane	Y Plane	Z Plane			
X Plane	Y Plane	Z Plane					

## 2.4 Test Setup Diagram

Test Setup Diagram – AC Line Conducted Emission Test (Mode 2 is the worst case)



**Test Setup Diagram - Radiated Test (Below 1GHz) (Mode 2 is the worst case)****Test Setup Diagram - Radiated Test (Above 1GHz) (Mode 2)**

### 3 Transmitter Test Result

#### 3.1 AC Power-line Conducted Emissions

##### 3.1.1 AC Power-line Conducted Emissions Limit

AC Power-line Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: \* Decreases with the logarithm of the frequency.


##### 3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

##### 3.1.3 Test Procedures


Test Method
<input checked="" type="checkbox"/> Refer as ANSI C63.10-2009, clause 6.2 for AC power-line conducted emissions.

##### 3.1.4 Test Setup






## 3.1.5 Test Result of AC Power-line Conducted Emissions

AC Power-line Conducted Emissions Result							
Operating Mode	2	Power Phase	Neutral				
Operating Function	USB Power & Radio link (WLAN) (Transmission)						
Date: 2013-12-17							
							
Emissions Data Table							
Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.1863950	49.92	-14.28	64.20	49.55	0.23	0.14 QP
2	0.1863950	39.34	-14.86	54.20	38.97	0.23	0.14 Average
3	0.2729650	44.70	-16.33	61.03	44.37	0.23	0.10 QP
4	0.2729650	33.93	-17.10	51.03	33.60	0.23	0.10 Average
5	0.3132810	40.95	-18.93	59.88	40.63	0.22	0.10 QP
6	0.3132810	30.14	-19.74	49.88	29.82	0.22	0.10 Average
7	0.5020260	38.46	-17.54	56.00	38.12	0.22	0.12 QP
8	0.5020260	25.90	-20.10	46.00	25.56	0.22	0.12 Average
9	0.7009560	22.73	-23.27	46.00	22.34	0.23	0.16 Average
10	0.7009560	37.67	-18.33	56.00	37.28	0.23	0.16 QP
11	1.590	26.75	-19.25	46.00	26.24	0.24	0.27 Average
12	1.590	39.13	-16.87	56.00	38.62	0.24	0.27 QP
13	26.700	37.40	-22.60	60.00	36.68	0.68	0.04 QP
14	26.700	29.46	-20.54	50.00	28.74	0.68	0.04 Average

Note 1: ">20dB" means emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found emissions (No emissions were detected.)



## 3.2 6dB Bandwidth

### 3.2.1 6dB Bandwidth Limit

6dB Bandwidth Limit
<b>Systems using digital modulation techniques:</b>
<input checked="" type="checkbox"/> 6 dB bandwidth $\geq$ 500 kHz.


### 3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

### 3.2.3 Test Procedures

Test Method
<input checked="" type="checkbox"/> For the emission bandwidth shall be measured using one of the options below:
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 8.1 Option 1 for 6 dB bandwidth measurement.
<input type="checkbox"/> Refer as FCC KDB 558074, clause 8.2 Option 2 for 6 dB bandwidth measurement.
<input type="checkbox"/> Refer as ANSI C63.10, clause 6.9.1 for occupied bandwidth testing.
<input checked="" type="checkbox"/> For conducted measurement.
<input checked="" type="checkbox"/> The EUT supports single transmit chain and measurements performed on this transmit chain.
<input type="checkbox"/> The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.
<input type="checkbox"/> The EUT supports multiple transmit chains using options given below:
<input type="checkbox"/> Option 1: Multiple transmit chains measurements need to be performed on one of the active transmit chains (antenna outputs). All measurement had be performed on transmit chains 1.
<input type="checkbox"/> Option 2: Multiple transmit chains measurements need to be performed on each transmit chains individually (antenna outputs). All measurement had be performed on all transmit chains.


### 3.2.4 Test Setup





## 3.2.5 Test Result of Emission Bandwidth

Emission Bandwidth Result					
Condition			Emission Bandwidth (MHz)		
Modulation Mode	N <sub>TX</sub>	Freq. (MHz)	99% Bandwidth	6dB Bandwidth	
11b	1	2412	12.12	6.57	
11b	1	2437	12.00	7.59	
11b	1	2462	12.11	8.02	
11g	1	2412	16.32	16.03	
11g	1	2437	16.32	16.30	
11g	1	2462	16.29	16.02	
HT20	1	2412	17.52	17.58	
HT20	1	2437	17.51	17.56	
HT20	1	2462	17.52	17.56	
Limit			N/A	≥500 kHz	
Result			Complied		

Note 1: N<sub>TX</sub> = Number of Transmit Chains



### 3.3 RF Output Power

#### 3.3.1 RF Output Power Limit

RF Output Power Limit	
<b>Maximum Peak Conducted Output Power or Maximum Conducted Output Power Limit and e.i.r.p.</b>	
<input checked="" type="checkbox"/> 2400-2483.5 MHz Band:	
<input checked="" type="checkbox"/>	Point-to-multipoint systems (P2M): $P_{out} \leq 30 \text{ dBm}$ (1 W); $P_{eirp} \leq 36 \text{ dBm}$ (4 W)
<input type="checkbox"/>	Point-to-point systems (P2P): If $P_{eirp} > 36 \text{ dBm}$ , $G_{TX} \leq P_{out}$
<input type="checkbox"/>	Smart antenna system (SAS): If $P_{eirp} > 36 \text{ dBm}$ , $G_{TX} \leq P_{out}$
	<input type="checkbox"/> Single beam: follow P2M, P2P limits
	<input type="checkbox"/> Overlap beam: follow P2M limit
	<input type="checkbox"/> Aggregate power on all beams: follow P2M limit + 8dB
$P_{out}$ = maximum peak conducted output power or maximum conducted output power in dBm, $G_{TX}$ = the maximum transmitting antenna directional gain in dBi. $P_{eirp}$ = e.i.r.p. Power in dBm.	

#### 3.3.2 Measuring Instruments


Refer a test equipment and calibration data table in this test report.

#### 3.3.3 Test Procedures

Test Method	
<input checked="" type="checkbox"/> Maximum Peak Conducted Output Power	
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 8.1.1 Option 1 (RBW $\geq$ EBW method).
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 8.1.2 Option 2 (integrated band power method).
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 8.1.3 Option 2 (peak power meter for VBW $\geq$ DTS BW)
<input checked="" type="checkbox"/> Maximum Conducted (Average) Output Power	
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 8.2.1 Option 1 (spectral trace averaging).
<input checked="" type="checkbox"/>	Refer as FCC KDB 558074, clause 8.2.2 Option 2 (slow sweep speed).
<input type="checkbox"/>	Refer as FCC KDB 558074, clause 8.2.3 Option 3 (average power meter).
<input checked="" type="checkbox"/> For conducted measurement.	
<input checked="" type="checkbox"/>	The EUT supports single transmit chain and measurements performed on this transmit chain.
<input type="checkbox"/>	The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.
<input type="checkbox"/>	The EUT supports multiple transmit chains using options given below: Refer as FCC KDB 662911, In-band power measurements. Using the measure-and-sum approach, measured all transmit ports individually. Sum the power (in linear power units e.g., mW) of all ports for each individual sample and save them.
<input type="checkbox"/>	If multiple transmit chains, EIRP calculation could be following as methods: $P_{total} = P_1 + P_2 + \dots + P_n$ (calculated in linear unit [mW] and transfer to log unit [dBm]) $EIRP_{total} = P_{total} + DG$



### 3.3.4 Test Setup






### 3.3.5 Test Result of Maximum Peak Conducted Output Power

Maximum Peak Conducted Output Power Result						
Condition			RF Output Power (dBm)			
Modulation Mode	N <sub>TX</sub>	Freq. (MHz)	Output Power	Power Limit	EIRP Power	EIRP Limit
11b	1	2412	18.37	30	21.47	36
11b	1	2437	18.34	30	21.44	36
11b	1	2462	18.80	30	21.90	36
11g	1	2412	15.52	30	18.62	36
11g	1	2437	15.61	30	18.71	36
11g	1	2462	16.25	30	19.35	36
HT20	1	2412	15.40	30	18.50	36
HT20	1	2437	15.62	30	18.72	36
HT20	1	2462	16.19	30	19.29	36
Result			Complied			

### 3.3.6 Test Result of Maximum Conducted Output Power

Maximum Conducted Output Power						
Condition			RF Output Power (dBm)			
Modulation Mode	N <sub>TX</sub>	Freq. (MHz)	Output Power	Power Limit	EIRP Power	EIRP Limit
11b	1	2412	15.44	30	18.54	36
11b	1	2437	15.60	30	18.70	36
11b	1	2462	15.90	30	19.00	36
11g	1	2412	9.96	30	13.06	36
11g	1	2437	10.01	30	13.11	36
11g	1	2462	10.80	30	13.90	36
HT20	1	2412	9.43	30	12.53	36
HT20	1	2437	9.84	30	12.94	36
HT20	1	2462	10.87	30	13.97	36
Result			Complied			





## 3.4 Power Spectral Density

### 3.4.1 Power Spectral Density Limit

Power Spectral Density Limit
<input checked="" type="checkbox"/> Power Spectral Density (PSD) $\leq 8 \text{ dBm/3kHz}$


### 3.4.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

### 3.4.3 Test Procedures


Test Method
<input checked="" type="checkbox"/> Peak power spectral density procedures that the same method as used to determine the conducted output power. If maximum peak conducted output power was measured to demonstrate compliance to the output power limit, then the peak PSD procedure below (Method PKPSD) shall be used. If maximum conducted output power was measured to demonstrate compliance to the output power limit, then one of the average PSD procedures shall be used, as applicable based on the following criteria (the peak PSD procedure is also an acceptable option).
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 10.2 Method PKPSD (RBW=3-100kHz;detector=peak).. [duty cycle $\geq 98\%$ or external video / power trigger]
<input type="checkbox"/> Refer as FCC KDB 558074, clause 10.3 Method AVGPSD-1 (spectral trace averaging).
<input type="checkbox"/> Refer as FCC KDB 558074, clause 10.4 Method AVGPSD-1 Alt. (slow sweep speed)
duty cycle $< 98\%$ and average over on/off periods with duty factor
<input type="checkbox"/> Refer as FCC KDB 558074, clause 10.5 Method AVGPSD-2 (spectral trace averaging).
<input type="checkbox"/> Refer as FCC KDB 558074, clause 10.6 Method AVGPSD-2 Alt. (slow sweep speed)
<input checked="" type="checkbox"/> For conducted measurement.
<input checked="" type="checkbox"/> The EUT supports single transmit chain and measurements performed on this transmit chain.
<input type="checkbox"/> The EUT supports diversity transmitting and the results on transmit chain port 1 is the worst case.
<input type="checkbox"/> The EUT supports multiple transmit chains using options given below:
<input type="checkbox"/> Option 1: Measure and sum the spectra across the outputs. Refer as FCC KDB 662911, In-band power spectral density (PSD). Sample all transmit ports simultaneously using a spectrum analyzer for each transmit port. Where the trace bin-by-bin of each transmit port summing can be performed. (i.e., in the first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3, and so on up to the $N_{TX}$ output to obtain the value for the first frequency bin of the summed spectrum.). Add up the amplitude (power) values for the different transmit chains and use this as the new data trace.
<input type="checkbox"/> Option 2: Measure and add $10 \log(N)$ dB, where $N$ is the number of transmit chains. Refer as FCC KDB 662911, In-band power spectral density (PSD). Performed at each transmit chains and each transmit chains shall be compared with the limit have been reduced with $10 \log(N)$ . Or each transmit chains shall be add $10 \log(N)$ to compared with the limit.

### 3.4.4 Test Setup




### 3.4.5 Test Result of Power Spectral Density

Power Spectral Density Result				
Modulation Mode	N <sub>TX</sub>	Freq. (MHz)	Power Spectral Density (dBm/100kHz)	Power Limit (dBm/3kHz)
11b	1	2412	-9.14	8
11b	1	2437	-10.06	8
11b	1	2462	-7.90	8
11g	1	2412	-18.53	8
11g	1	2437	-18.45	8
11g	1	2462	-16.54	8
HT20	1	2412	-18.88	8
HT20	1	2437	-17.86	8
HT20	1	2462	-17.97	8
Result		Complied		



## 3.5 Transmitter Bandedge Emissions

### 3.5.1 Transmitter Radiated Bandedge Emissions Limit




### 3.5.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

### 3.5.3 Test Procedures

<b>Test Method</b>
<input checked="" type="checkbox"/> The average emission levels shall be measured in [duty cycle $\geq$ 98 or duty factor].
<input checked="" type="checkbox"/> Refer as ANSI C63.10, clause 6.9.2.2 bandedge testing shall be performed at the lowest frequency channel and highest frequency channel within the allowed operating band.
<input checked="" type="checkbox"/> For the transmitter unwanted emissions shall be measured using following options below:
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 11 for unwanted emissions into non-restricted bands.
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 12 for unwanted emissions into restricted bands.
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 12.2.5.1 Option 1 (trace averaging for duty cycle $\geq 98\%$ )
<input type="checkbox"/> Refer as FCC KDB 558074, clause 12.2.5.2 Option 2 (trace averaging + duty factor).
<input type="checkbox"/> Refer as FCC KDB 558074, clause 12.2.5.3 Option 3 (Reduced VBW $\geq 1/T$ ).
<input type="checkbox"/> Refer as ANSI C63.10, clause 4.2.3.2.3 (Reduced VBW). VBW $\geq 1/T$ , where T is pulse time.
<input type="checkbox"/> Refer as ANSI C63.10, clause 4.2.3.2.4 average value of pulsed emissions.
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 11.3 and 12.2.4 measurement procedure peak limit.
<input checked="" type="checkbox"/> For the transmitter bandedge emissions shall be measured using following options below:
<input type="checkbox"/> Refer as FCC KDB 558074, clause 13.3 for narrower resolution bandwidth (100kHz) using the band power and summing the spectral levels (i.e., 1 MHz).
<input checked="" type="checkbox"/> Refer as ANSI C63.10, clause 6.9.2 for band-edge testing.
<input type="checkbox"/> Refer as ANSI C63.10, clause 6.9.3 for marker-delta method for band-edge measurements.
<input checked="" type="checkbox"/> For radiated measurement, refer as FCC KDB 558074, clause 12.2.7 and ANSI C63.10, clause 6.6. Test distance is 3m.

### 3.5.4 Test Setup

<b>Transmitter Radiated Bandedge Emissions</b>
 <p>Electric field tests shall be performed in transmitter bandedge emissions using a calibrated horn antenna.</p>



### 3.5.5 Transmitter Radiated Bandedge Emissions

2400-2483.5MHz Transmitter Radiated Bandedge Emissions (Non-restricted Band)								
Modulation	N <sub>TX</sub>	Test Freq. (MHz)	In-band PSD [i] (dBuV/100kHz)	Freq. (MHz)	Out-band PSD [o] (dBuV/100kHz)	[i] – [o] (dB)	Limit (dB)	Pol.
11b	1	2412	105.56	2398.59	63.09	42.47	20	V
11b	1	2462	100.84	2520.30	62.32	38.52	20	V
11g	1	2412	97.74	2396.69	62.60	35.14	20	V
11g	1	2462	92.33	2584.30	62.39	29.94	20	V
HT20	1	2412	97.75	2399.94	62.73	35.02	20	V
HT20	1	2462	92.41	2510.70	62.70	29.71	20	V

Note 1: Measurement worst emissions of receive antenna polarization

2400-2483.5MHz Transmitter Radiated Bandedge Emissions (Restricted Band)										
Modulation Mode	N <sub>TX</sub>	Freq. (MHz)	Measure Distance (m)	Freq. (MHz) PK	Level (dBuV/m) PK	Limit (dBuV/m) PK	Freq. (MHz) AV	Level (dBuV/m) AV	Limit (dBuV/m) AV	Pol.
11b	1	2412	3	2388.74	60.97	74	2390.00	48.09	54	V
11b	1	2462	3	2485.80	61.03	74	2484.70	48.68	54	V
11g	1	2412	3	2390.00	68.54	74	2390.00	48.64	54	V
11g	1	2462	3	2483.80	70.45	74	2483.50	47.80	54	V
HT20	1	2412	3	2389.18	69.54	74	2390.00	49.39	54	V
HT20	1	2462	3	2483.50	71.28	74	2483.50	48.37	54	V

Note 1: Measurement worst emissions of receive antenna polarization.



## 3.6 Transmitter Unwanted Emissions

### 3.6.1 Transmitter Radiated Unwanted Emissions Limit

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Un-restricted Band Emissions Limit	
RF output power procedure	Limit (dB)
Peak output power procedure	20
Average output power procedure	30

Note 1: If the peak output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the peak conducted output power measured within any 100 kHz outside the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum measured in-band peak PSD level.

Note 2: If the average output power procedure is used to measure the fundamental emission power to demonstrate compliance to requirements, then the power in any 100 kHz outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum measured in-band average PSD level.

### 3.6.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.




### 3.6.3 Test Procedures

Test Method
<input checked="" type="checkbox"/> Measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).
<input checked="" type="checkbox"/> The average emission levels shall be measured in [duty cycle $\geq$ 98 or duty factor].
<input checked="" type="checkbox"/> For the transmitter unwanted emissions shall be measured using following options below:
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 11 for unwanted emissions into non-restricted bands.
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 12 for unwanted emissions into restricted bands.
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 12.2.5.1 Option 1 (trace averaging for duty cycle $\geq 98\%$ )
<input type="checkbox"/> Refer as FCC KDB 558074, clause 12.2.5.2 Option 2 (trace averaging + duty factor).
<input type="checkbox"/> Refer as FCC KDB 558074, clause 12.2.5.3 Option 3 (Reduced $VBW \geq 1/T$ ).
<input type="checkbox"/> Refer as ANSI C63.10, clause 4.2.3.2.3 (Reduced $VBW$ ). $VBW \geq 1/T$ , where $T$ is pulse time.
<input type="checkbox"/> Refer as ANSI C63.10, clause 4.2.3.2.4 average value of pulsed emissions.
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 11.3 and 12.2.4 measurement procedure peak limit.
<input checked="" type="checkbox"/> Refer as FCC KDB 558074, clause 12.2.3 measurement procedure Quasi-Peak limit.
<input checked="" type="checkbox"/> For radiated measurement, refer as FCC KDB 558074, clause 12.2.7.
<input checked="" type="checkbox"/> Refer as ANSI C63.10, clause 6.4 for radiated emissions below 30 MHz and test distance is 3m.
<input checked="" type="checkbox"/> Refer as ANSI C63.10, clause 6.5 for radiated emissions 30 MHz to 1 GHz and test distance is 3m.
<input checked="" type="checkbox"/> Refer as ANSI C63.10, clause 6.6 for radiated emissions above 1 GHz and test distance is 3m.
<input checked="" type="checkbox"/> The any unwanted emissions level shall not exceed the fundamental emission level.
<input checked="" type="checkbox"/> All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.

### 3.6.4 Test Setup

#### Transmitter Radiated Unwanted Emissions




Magnetic field tests shall be performed in the frequency range of 9 kHz to 30 MHz using a calibrated loop antenna. Electric field tests shall be performed in the frequency range of 30 MHz to 1000 MHz using a calibrated bi-log antenna and the frequency range of 1 GHz to 40 GHz using a calibrated horn antenna.

### 3.6.5 Transmitter Radiated Unwanted Emissions (Below 30MHz)

All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.




## 3.6.6 Transmitter Radiated Unwanted Emissions (Below 1GHz)





## Transmitter Radiated Unwanted Emissions (Below 1GHz)

<b>Operating Mode</b>	2	<b>Polarization</b>	H
<b>Operating Function</b>	USB Power & Radio link (WLAN) (Transmission)		



Freq	Level	Over Limit		ReadAntenna		Cable Preamp		Remark	Ant Pos	Table Pos
		Limit	Line	Level	Factor	Loss	Factor			
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 @ 62.980	36.28	-3.72	40.00	55.83	6.70	1.28	27.53	Peak	---	---
2 @ 164.830	37.42	-6.08	43.50	52.51	9.92	2.12	27.13	Peak	---	---
3 @ 230.790	37.77	-8.23	46.00	51.57	10.60	2.50	26.90	Peak	---	---
4 @ 319.060	38.09	-7.91	46.00	48.23	13.66	2.98	26.78	Peak	---	---
5 @ 358.930	36.83	-9.17	46.00	46.05	14.67	3.16	27.05	Peak	---	---
6 @ 479.110	29.60	-16.40	46.00	36.64	17.06	3.66	27.76	Peak	---	---

Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical).

Note 4: No level of unwanted emissions exceeds the level of the fundamental emission.



### 3.6.7 Transmitter Radiated Unwanted Emissions (Above 1GHz)

**Transmitter Radiated Unwanted Emissions (Above 1GHz)**

Modulation Mode	11b	Test Freq. (MHz)	2412
N <sub>TX</sub>	1	Polarization	V

Level (dBuV/m)

Date: 2013-12-14


Frequency (MHz)

Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Remark	Ant	Table
		Limit	Line	Level	Factor	Loss	Factor			
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 4824.000	52.61	-21.39	74.00	46.24	33.09	5.71	32.43	Peak	---	---
2 4824.000	50.38	-3.62	54.00	44.01	33.09	5.71	32.43	Average	---	---
3 7236.000	53.29			42.83	35.88	7.23	32.65	Peak	---	---
4 9648.000	57.26			43.23	38.34	8.79	33.10	Peak	---	---



## Transmitter Radiated Unwanted Emissions (Above 1GHz)

<b>Modulation Mode</b>	11b	<b>Test Freq. (MHz)</b>	2412
<b>N<sub>TX</sub></b>	1	<b>Polarization</b>	H



Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table
		Limit	Line	Level	Factor	Loss	Factor		
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
4824.000	55.59	-18.41	74.00	49.22	33.09	5.71	32.43	Peak	---
4824.000	51.63	-2.37	54.00	45.26	33.09	5.71	32.43	Average	---
7236.000	53.07			42.61	35.88	7.23	32.65	Peak	---
9648.000	56.56			42.53	38.34	8.79	33.10	Peak	---

Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.


Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (109.37 dB<sub>UV</sub>/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.



## Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11b	Test Freq. (MHz)	2437
N <sub>TX</sub>	1	Polarization	V



Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant Pos	Table Pos
		Line	Limit	Antenna	Level	Level	Factor		
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	4874.000	53.22	-20.78	74.00	46.74	33.18	5.72	32.42	Peak
2	4874.000	47.24	-6.76	54.00	40.76	33.18	5.72	32.42	Average
3	7311.000	52.43	-21.57	74.00	41.77	36.04	7.28	32.66	Peak
4	7311.000	39.87	-14.13	54.00	29.21	36.04	7.28	32.66	Average
5	9748.000	57.23			42.97	38.57	8.77	33.08	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.


Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (106.62 dBuV/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.



## Transmitter Radiated Unwanted Emissions (Above 1GHz)

<b>Modulation Mode</b>	11b	<b>Test Freq. (MHz)</b>	2437
<b>N<sub>TX</sub></b>	1	<b>Polarization</b>	H



Freq	Level	Over	Limit	Read	Antenna	Cable Preamp		Remark	Ant Pos	Table Pos
		Line	Level	Factor	Loss	Factor				
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB		cm	deg
1 4874.000	55.87	-18.13	74.00	49.39	33.18	5.72	32.42	Peak	---	---
2 @ 4874.000	51.96	-2.04	54.00	45.48	33.18	5.72	32.42	Average	---	---
3 7311.000	52.86	-21.14	74.00	42.20	36.04	7.28	32.66	Peak	---	---
4 7311.000	39.60	-14.40	54.00	28.94	36.04	7.28	32.66	Average	---	---
5 9748.000	57.33			43.07	38.57	8.77	33.08	Peak	---	---

Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.


Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (106.62 dB<sub>UV</sub>/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.



## Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11b	Test Freq. (MHz)	2462
N <sub>TX</sub>	1	Polarization	V



Freq	Level	Over Limit	Line	Read		Ant	Table		
				Antenna	Cable				
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1 4924.000	53.93	-20.07	74.00	47.32	33.28	5.74	32.41	Peak	---
2 4924.000	48.45	-5.55	54.00	41.84	33.28	5.74	32.41	Average	---
3 7386.000	52.51	-21.49	74.00	41.61	36.25	7.34	32.69	Peak	---
4 7386.000	40.25	-13.75	54.00	29.35	36.25	7.34	32.69	Average	---
5 9848.000	57.07			42.65	38.76	8.74	33.08	Peak	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.


Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (104.35 dBuV/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.



## Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11b	Test Freq. (MHz)	2462
N <sub>TX</sub>	1	Polarization	H



Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant Pos	Table Pos
		Line	Level	Factor		Loss	Factor		
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1 4924.000	54.24	-19.76	74.00	47.63	33.28	5.74	32.41	Peak	---
2 @ 4924.000	49.60	-4.40	54.00	42.99	33.28	5.74	32.41	Average	---
3 7386.000	53.46	-20.54	74.00	42.56	36.25	7.34	32.69	Peak	---
4 7386.000	39.87	-14.13	54.00	28.97	36.25	7.34	32.69	Average	---
5 9848.000	56.94			42.52	38.76	8.74	33.08	Peak	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.


Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (104.35 dBuV/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.



## Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11g	Test Freq. (MHz)	2412
N <sub>TX</sub>	1	Polarization	V



Freq	Level	Over Limit	Limit	Read	Antenna	Cable Preamp			Ant Pos	Table Pos
						Line	Level Factor	Loss Factor		
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m				cm	deg
1 4824.000	48.43	-25.57	74.00	42.06	33.09	5.71	32.43	Peak	---	---
2 4824.000	36.79	-17.21	54.00	30.42	33.09	5.71	32.43	Average	---	---
3 7236.000	51.86			41.40	35.88	7.23	32.65	Peak	---	---
4 9648.000	56.72			42.69	38.34	8.79	33.10	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.


Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (108.90 dBuV/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.



## Transmitter Radiated Unwanted Emissions (Above 1GHz)

<b>Modulation Mode</b>	11g	<b>Test Freq. (MHz)</b>	2412
<b>N<sub>TX</sub></b>	1	<b>Polarization</b>	H



Freq	Level	Over Limit		ReadAntenna		Cable Preamp		Ant Pos	Table Pos
		Line	Level Factor	dB	dB/uV	dB	dB/m		
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1 4824.000	48.99	-25.01	74.00	42.62	33.09	5.71	32.43	Peak	---
2 4824.000	37.32	-16.68	54.00	30.95	33.09	5.71	32.43	Average	---
3 7236.000	52.24			41.78	35.88	7.23	32.65	Peak	---
4 9648.000	56.38			42.35	38.34	8.79	33.10	Peak	---

Note 1: “>20dB” means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected).

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.


Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (108.90 dB<sub>UV</sub>/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.



## Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11g	Test Freq. (MHz)	2437
N <sub>TX</sub>	1	Polarization	V



Freq	Level	Over Limit	Line	Read		Ant	Table		
				Antenna	Cable				
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1 4874.000	48.48	-25.52	74.00	42.00	33.18	5.72	32.42	Peak	---
2 4874.000	36.28	-17.72	54.00	29.80	33.18	5.72	32.42	Average	---
3 7311.000	51.70	-22.30	74.00	41.04	36.04	7.28	32.66	Peak	---
4 7311.000	39.38	-14.62	54.00	28.72	36.04	7.28	32.66	Average	---
5 9748.000	56.95			42.69	38.57	8.77	33.08	Peak	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.


Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (106.50 dBuV/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.



## Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11g	Test Freq. (MHz)	2437
N <sub>TX</sub>	1	Polarization	H



Freq	Level	Over Limit	Line	Read		Ant	Table		
				Antenna	Cable			Pos	Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1 4874.000	49.21	-24.79	74.00	42.73	33.18	5.72	32.42	Peak	---
2 4874.000	36.43	-17.57	54.00	29.95	33.18	5.72	32.42	Average	---
3 7311.000	52.46	-21.54	74.00	41.80	36.04	7.28	32.66	Peak	---
4 7311.000	39.30	-14.70	54.00	28.64	36.04	7.28	32.66	Average	---
5 9748.000	57.26			43.00	38.57	8.77	33.08	Peak	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (106.50 dBuV/m).


Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.





## Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	11g	Test Freq. (MHz)	2462
N <sub>TX</sub>	1	Polarization	H



Freq	Level	Over Limit	Line	ReadAntenna		Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
				MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB
1	4924.000	48.35	-25.65	74.00	41.74	33.28	5.74	32.41	Peak	---
2	4924.000	37.09	-16.91	54.00	30.48	33.28	5.74	32.41	Average	---
3	7386.000	53.02	-20.98	74.00	42.12	36.25	7.34	32.69	Peak	---
4	7386.000	40.40	-13.60	54.00	29.50	36.25	7.34	32.69	Average	---
5	9848.000	57.74			43.32	38.76	8.74	33.08	Peak	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.


Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (103.43 dBuV/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.



## Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (MHz)	2412
N <sub>TX</sub>	1	Polarization	V



Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant Pos	Table Pos
		Line	Limit	Antenna	Level	Factor	Loss		
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1 4824.000	48.26	-25.74	74.00	41.89	33.09	5.71	32.43	Peak	---
2 4824.000	35.83	-18.17	54.00	29.46	33.09	5.71	32.43	Average	---
3 7236.000	51.94			41.48	35.88	7.23	32.65	Peak	---
4 9648.000	56.19			42.16	38.34	8.79	33.10	Peak	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.


Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (108.06 dBuV/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.



## Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (MHz)	2412
N <sub>TX</sub>	1	Polarization	H



Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table		
		MHz	dBuV/m	dB	dBuV/m	Level	Factor			Pos	Pos
										cm	deg
1	4824.000	49.03	-24.97	74.00	42.66	33.09	5.71	32.43	Peak	---	---
2	4824.000	36.91	-17.09	54.00	30.54	33.09	5.71	32.43	Average	---	---
3	7236.000	51.74			41.28	35.88	7.23	32.65	Peak	---	---
4	9648.000	57.49			43.46	38.34	8.79	33.10	Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.


Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (108.06 dBuV/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.



## Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (MHz)	2437
N <sub>TX</sub>	1	Polarization	V



Freq	Level	Over Limit	Line	Read		Ant	Table		
				Antenna	Cable			Pos	Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1 4874.000	48.31	-25.69	74.00	41.83	33.18	5.72	32.42	Peak	---
2 4874.000	36.27	-17.73	54.00	29.79	33.18	5.72	32.42	Average	---
3 7311.000	52.20	-21.80	74.00	41.54	36.04	7.28	32.66	Peak	---
4 7311.000	39.21	-14.79	54.00	28.55	36.04	7.28	32.66	Average	---
5 9748.000	56.96			42.70	38.57	8.77	33.08	Peak	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.


Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (105.50 dBuV/m).


Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.





## Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (MHz)	2462
N <sub>TX</sub>	1	Polarization	V



Freq	Level	Over Limit	Line	ReadAntenna		Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
				Level	Factor					
MHz	dBuV/m		dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	4924.000	49.66	-24.34	74.00	43.05	33.28	5.74	32.41 Peak	---	---
2	4924.000	36.77	-17.23	54.00	30.16	33.28	5.74	32.41 Average	---	---
3	7386.000	53.44	-20.56	74.00	42.54	36.25	7.34	32.69 Peak	---	---
4	7386.000	39.83	-14.17	54.00	28.93	36.25	7.34	32.69 Average	---	---
5	9848.000	57.42			43.00	38.76	8.74	33.08 Peak	---	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.


Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (102.74 dBuV/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.



## Transmitter Radiated Unwanted Emissions (Above 1GHz)

Modulation Mode	HT20	Test Freq. (MHz)	2462
N <sub>TX</sub>	1	Polarization	H



Freq	Level	Over Limit	Limit	Read		Ant	Table		
				Line	Antenna			Pos	Pos
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1 4924.000	48.90	-25.10	74.00	42.29	33.28	5.74	32.41	Peak	---
2 4924.000	36.41	-17.59	54.00	29.80	33.28	5.74	32.41	Average	---
3 7386.000	52.83	-21.17	74.00	41.93	36.25	7.34	32.69	Peak	---
4 7386.000	39.99	-14.01	54.00	29.09	36.25	7.34	32.69	Average	---
5 9848.000	57.63			43.21	38.76	8.74	33.08	Peak	---

Note 1: ">20dB" means spurious emission levels that exceed the level of 20 dB below the applicable limit.

Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)

Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical)

Note 4: For restricted bands, the peak measurement is fully sufficient, as the max field strength as measured with the Peak-Detector meets the AV-Limit so that the AV level does not need to be reported in addition.

Note 5: For un-restricted bands, unwanted emissions shall be attenuated by at least 20 dB relative to the maximum measured in-band level (102.74 dBuV/m).

Note 6: No level of unwanted emissions exceeds the level of the fundamental emission.



## 4 Test Equipment and Calibration Data

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMC Receiver	R&S	ESCS 30	100174	9kHz ~ 2.75GHz	Mar. 26, 2013	Conduction (CO04-HY)
LISN	SCHWARZBECK MESS-ELEKTRONIK	NSLK 8127	8127-477	9kHz ~ 30MHz	Jan. 21, 2013	Conduction (CO04-HY)
RF Cable-CON	HUBER+SUHNER	RG213/U	7.61183201e+012	9kHz ~ 30MHz	Oct. 30, 2013	Conduction (CO04-HY)
EMC Receiver	R&S	ESCS 30	100174	9kHz ~ 2.75GHz	Mar. 26, 2013	Conduction (CO04-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	R&S	FSV 40	101013	9KHz~40GHz	Jan. 29, 2013	Conducted (TH01-HY)
Signal Generator	R&S	SMR40	100116	10MHz ~ 40GHz	Jun. 27, 2013	Conducted (TH01-HY)
RF Cable-0.5m	HUBER+SUHNER	SUCOFLEX_104	SN MY10714/4	30MHz ~ 26.5GHz	Dec. 02, 2013	Conducted (TH01-HY)

Note: Calibration Interval of instruments listed above is one year.



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30MHz ~ 1GHz 3m	Nov. 30, 2013	Radiation (03CH03-HY)
Amplifier	HP	8447D	2944A08033	10kHz ~ 1.3GHz	May. 03, 2013	Radiation (03CH03-HY)
Amplifier	Agilent	8449B	3008A02120	1GHz ~ 26.5GHz	Aug. 20, 2013	Radiation (03CH03-HY)
Horn Antenna	EMCO	3115	6741	1GHz ~ 18GHz	May 31, 2013	Radiation (03CH03-HY)
Horn Antenna	SCHWARZBECK	BBHA9170	BBHA9170154	15GHz ~ 40GHz	Jan. 08, 2013	Radiation (03CH03-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	9kHz ~ 1GHz	Jan. 17, 2013	Radiation (03CH03-HY)
RF Cable-high	SUHNER	SUCOFLEX 106	03CH03-HY	1GHz ~ 40GHz	Jan. 17, 2013	Radiation (03CH03-HY)
Bilog Antenna	SCHAFFNER	CBL 6112D	22237	30MHz ~ 1GHz	Sep. 21, 2013	Radiation (03CH03-HY)
Turn Table	Chaintek Instruments	3000	MF7802058	0~ 360 degree	N/A	Radiation (03CH03-HY)
Antenna Mast	MF	MF7802	MF780208205	1 ~ 4 m	N/A	Radiation (03CH03-HY)
Spectrum Analyzer	R&S	FSP30	100023	9kHz ~ 30GHz	Jul. 20, 2013	Radiation (03CH03-HY)

Note: Calibration Interval of instruments listed above is one year.

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Loop Antenna	TESEQ	HLA 6120	31244	9kHz ~ 30MHz	Dec. 02, 2012	Radiation (03CH03-HY)

Note: Calibration Interval of instruments listed above is two year.