



Test Report No.: RF171129N008-3



TEST REPORT



Applicant	DEI Sales, Inc., dba Polk Audio
Address	1 Viper Way Vista, California 92801, USA

Manufacturer or Supplier	DEI Sales, Inc., dba Polk Audio
Address	1 Viper Way Vista, California 92801, USA
Product	Smart Speaker
Brand Name	Polk
Model	ASSIST
Additional Model & Model Difference	N/A
Date of tests	Nov. 29, 2017 ~ Mar. 15, 2018

The tests have been carried out according to the requirements of the following standard:

FCC Part 15, Subpart C, Section 15.247

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Andy Zhu Project Engineer / EMC Department	Approved by Glyn He Supervisor / EMC Department
	 Date: Apr. 04, 2018

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



TABLE OF CONTENTS

RELEASE CONTROL RECORD4

1 SUMMARY OF TEST RESULTS5

2 MEASUREMENT UNCERTAINTY5

3 GENERAL INFORMATION.....6

3.1 GENERAL DESCRIPTION OF EUT.....6

3.2 DESCRIPTION OF TEST MODES.....7

3.2.1 CONFIGURATION OF SYSTEM UNDER TEST8

3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL8

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS 11

3.4 DESCRIPTION OF SUPPORT UNITS 11

4 TEST TYPES AND RESULTS12

4.1 CONDUCTED EMISSION MEASUREMENT12

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT12

4.1.2 TEST INSTRUMENTS12

4.1.3 TEST PROCEDURES.....13

4.1.4 DEVIATION FROM TEST STANDARD13

4.1.5 TEST SETUP.....14

4.1.6 EUT OPERATING CONDITIONS14

4.1.7 TEST RESULTS.....15

4.2 RADIATED EMISSION MEASUREMENT17

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT17

4.2.2 TEST INSTRUMENTS18

4.2.3 TEST PROCEDURES.....19

4.2.4 DEVIATION FROM TEST STANDARD20

4.2.5 TEST SETUP.....20

4.2.6 EUT OPERATING CONDITIONS21

4.2.7 TEST RESULTS.....22

4.3 6DB BANDWIDTH MEASUREMENT36

4.3.1 LIMITS OF 6DB BANDWIDTH MEASUREMENT36

4.3.2 TEST INSTRUMENTS36

4.3.3 TEST PROCEDURE36

4.3.4 DEVIATION FROM TEST STANDARD37

4.3.5 TEST SETUP.....37

4.3.6 EUT OPERATING CONDITIONS37

4.3.7 TEST RESULTS.....38



4.4	CONDUCTED OUTPUT POWER.....	40
4.4.1	LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT.....	40
4.4.2	TEST SETUP.....	40
4.4.3	TEST INSTRUMENTS	40
4.4.4	TEST PROCEDURES.....	41
4.4.5	DEVIATION FROM TEST STANDARD.....	41
4.4.6	EUT OPERATING CONDITIONS	41
4.4.7	TEST RESULTS.....	42
4.5	POWER SPECTRAL DENSITY MEASUREMENT	43
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	43
4.5.2	TEST SETUP.....	43
4.5.3	TEST INSTRUMENTS	43
4.5.4	TEST PROCEDURE	43
4.5.5	DEVIATION FROM TEST STANDARD.....	43
4.5.6	EUT OPERATING CONDITION.....	44
4.5.7	TEST RESULTS.....	44
4.6	OUT OF BAND EMISSION MEASUREMENT	46
4.6.1	LIMITS OF OUT OF BAND EMISSION MEASUREMENT.....	46
4.6.2	TEST SETUP.....	46
4.6.3	TEST INSTRUMENTS	46
4.6.4	TEST PROCEDURE	46
4.6.5	DEVIATION FROM TEST STANDARD.....	47
4.6.6	EUT OPERATING CONDITION.....	47
4.6.7	TEST RESULTS.....	48
5	PHOTOGRAPHS OF THE TEST CONFIGURATION.....	54
6	APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB.....	55



Test Report No.: RF171129N008-3

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF171129N008-3	Original release	Apr. 04, 2018

1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit.
15.247(d) 15.209	Radiated Emissions	PASS	Meet the requirement of limit.
15.247(d)	Band Edge Measurement	PASS	Meet the requirement of limit.
15.247(a)(2)	6dB bandwidth	PASS	Meet the requirement of limit.
15.247(b)	Conducted Output power	PASS	Meet the requirement of limit.
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used

2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.70dB
Radiated emissions	9KHz ~ 30MHz	2.16dB
	30MHz ~ 1GMHz	3.83dB
	1GHz ~ 18GHz	4.93dB
	18GHz ~ 40GHz	4.80dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Smart Speaker
MODEL NO.	ASSIST
ADDITIONAL NO.	N/A
FCC ID	WLQAM9305
NOMINAL VOLTAGE	DC 22V 1.8A From Adapter Input AC 100-240V 50/60Hz 1.0A
MODULATION TYPE	CCK, DQPSK, DBPSK for DSSS 64QAM, 16QAM, QPSK, BPSK for OFDM
MODULATION TECHNOLOGY	DSSS, OFDM
OPERATING FREQUENCY RANG	2412-2462MHz for 11b/g/n(HT20) 2422-2452MHz for 11n(HT40)
AVERAGE POWER	13.94dBm(Maximum)
ANTENNA TYPE	FPC Antenna, 3.03dBi Gain
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	N/A

NOTE:

1. The EUT provides completed transmitters and receivers:

MODULATION MODE	FUNCTION
802.11b	1TX/1RX
802.11g	1TX/1RX
802.11n (HT20)	1TX/1RX
802.11n (HT40)	1TX/1RX

2. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
3. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
4. Please refer to the EUT photo document (Reference No.: 171129N008) for detailed product photo.
5. The EUT can be powered by adapter as list as attach.

ADAPTER	
BRAND:	Polk
MODEL:	MU036A220180
INPUT:	AC 100-240V, 50/60Hz, 1.0A
OUTPUT:	DC 22V 1.8A
CABLE:	Unshielded, Non-detachable 2.5m

3.2 DESCRIPTION OF TEST MODES

11 channels are provided for 802.11b, 802.11g and 802.11n(HT20):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

9 channels are provided for 802.11n(HT40):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
3	2422 MHz	7	2442 MHz
4	2427 MHz	8	2447 MHz
5	2432 MHz	9	2452 MHz
6	2437 MHz		

3.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photographs of the test configuration for reference.

3.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case was found when positioned on X axis for radiated emission. Following test modes were selected for the final test, and the final worst case is marked in boldface and recorded in the report:

EUT CONFIGURE MODE	APPLICABLE TO				MODE
	RE<1G	RE≥1G	PLC	APCM	
A	√	√	√	√	Powered by adaptor

Where **RE<1G**: Radiated Emission below 1GHz **RE≥1G**: Radiated Emission above 1GHz
PLC: Power Line Conducted Emission **APCM**: Antenna Port Conducted Measurement

POWER LINE CONDUCTED EMISSION TEST:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	TESTED CONDITION
A	WIFI (2.4G) Link

RADIATED EMISSION TEST (BELOW 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A	802.11b	1 to 11	1	OFDM	DBPSK	1.0

RADIATED EMISSION TEST (ABOVE 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
A	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
A	802.11n HT20	1 to 11	1, 6, 11	OFDM	BPSK	6.5
A	802.11n HT40	3 to 9	3, 6, 9	OFDM	BPSK	6.5

BANDEDGE MEASUREMENT:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A	802.11b	1 to 11	1, 11	DSSS	DBPSK	1.0
A	802.11g	1 to 11	1, 11	OFDM	BPSK	6.0
A	802.11n HT20	1 to 11	1, 11	OFDM	BPSK	6.5
A	802.11n HT40	3 to 9	3, 9	OFDM	BPSK	6.5

ANTENNA PORT CONDUCTED MEASUREMENT:

This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	DATA RATE (Mbps)
A	802.11b	1 to 11	1, 6, 11	DSSS	DBPSK	1.0
A	802.11g	1 to 11	1, 6, 11	OFDM	BPSK	6.0
A	802.11n HT20	1 to 11	1, 6, 11	OFDM	BPSK	6.5
A	802.11n HT40	3 to 9	3, 6, 9	OFDM	BPSK	6.5



Test Report No.: RF171129N008-3

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE	TESTED BY
RE<1G	25deg. C, 55%RH	AC 120V/60Hz	Arnold
RE≥1G	25deg. C, 55%RH	AC 120V/60Hz	Arnold
PLC	25deg. C, 55%RH	AC 120V/60Hz	Xue Wang
APCM	25deg. C, 55%RH	AC 120V/60Hz	Robert Cheng



Test Report No.: RF171129N008-3

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C, Section 15.247

KDB 558074 D01 DTS Meas Guidance v04

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together without any other necessary accessories or support units.

4 TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR7	101494	Apr. 05,17	Apr. 04,18
Artificial Mains Network	Rohde&Schwarz	ENV216	101173	Mar. 03,18	Mar. 02,19
Artificial Mains Network	Rohde&Schwarz	ESH3-Z5	100317	Apr. 05,17	Apr. 04,18
Voltage probe	SCHWARZBECK	TK 9421	TK 9421-176	Jan. 17,18	Jan. 16,19
Test software	ADT	ADT_Cond_V7.3.7	N/A	N/A	N/A

- NOTE:**
1. The test was performed in shielded room 553.
 2. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

4.1.3 TEST PROCEDURES


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation.

4.1.5 TEST SETUP



- Note: 1.Support units were connected to second LISN.**
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.


4.1.7 TEST RESULTS

CONDUCTED WORST-CASE DATA: WIFI Link

PHASE	Line	6dB BANDWIDTH	9kHz
-------	------	---------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15924	10.22	32.94	15.09	43.16	25.31	65.50	55.50	-22.34	-30.19
2	0.19500	10.22	27.80	10.60	38.02	20.82	63.82	53.82	-25.80	-33.00
3	0.20356	10.22	28.37	12.19	38.59	22.41	63.46	53.46	-24.87	-31.05
4	0.26647	10.22	22.38	9.07	32.60	19.29	61.23	51.23	-28.63	-31.94
5	0.32100	10.22	17.07	5.41	27.29	15.63	59.68	49.68	-32.39	-34.05
6	0.45664	10.23	27.55	22.10	37.78	32.33	56.75	46.75	-18.97	-14.42


- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



PHASE	Neutral	6dB BANDWIDTH	9kHz
--------------	---------	----------------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	10.01	36.89	17.76	46.90	27.77	66.00	56.00	-19.10	-28.23
2	0.18825	10.01	27.06	10.77	37.07	20.78	64.11	54.11	-27.04	-33.33
3	0.20625	10.01	26.46	11.37	36.47	21.38	63.35	53.35	-26.88	-31.97
4	0.24000	10.01	24.06	10.69	34.07	20.70	62.10	52.10	-28.03	-31.40
5	0.25800	10.01	22.44	11.23	32.45	21.24	61.50	51.50	-29.05	-30.26
6	0.45424	10.03	27.73	25.04	37.76	35.07	56.80	46.80	-19.04	-11.73

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.



4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESU40	100449	Mar. 11,18	Mar. 10,19
Signal and Spectrum Analyzer	Rohde&Schwarz	FSV7	102331	Nov. 04,17	Nov. 03,18
Active Loop Antenna (9KHz -30MHz)	SCHWARZBECK	FMZB 1519B	1519B-045	May 31,17	May 30,18
Amplifier (9KHz -1GHz)	Burgeon	BPA-530	100210	Apr. 05,17	Apr. 04,18
Bilog Antenna (20MHz -2GHz)	Teseq	CBL 6111D	30643	Jul. 28, 17	Jul. 27, 18
Horn Antenna (1GHz -18GHz)	ETS -Lindgren	3117	00062558	May 19,17	May 18,18
Horn Antenna (18GHz -40GHz)	SCHWARZBECK	BBHA 9170	BBHA9170242	Mar. 10,18	Mar. 14,19
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	NSEMC003	Feb. 10,18	Feb. 09,19
Test Software	ADT	ADT_Radiated_V7.6.15.9.2	N/A	N/A	N/A
Broadband Preamplifier (1GHz~18GHz)	SCHWARZBECK	BBV9718	305	Mar. 21,17	Mar. 20,18
Pre-Amplifier (18GHz-40GHz)	EMCI	EMC 184045	980102	Nov. 08,17	Nov. 07,18
Test Software	ADT	ADT_Radiated_V7.6.15.9.2	N/A	N/A	N/A
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	Aug. 10,17	Aug. 09,18

NOTE:

1. The test was performed in 966 Chamber.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
3. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 749762.

4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 1.5 meters (above 1GHz) and 0.8 meters (below 1GHz) above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. For below 30MHz, a loop antenna with its vertical plane is place 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1m above the ground.
- g. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

NOTE:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz(Duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.
5. The testing of the EUT was performed on all 3 orthogonal axes, the worst-case test configuration was reported on the file test setup photo.

4.2.4 DEVIATION FROM TEST STANDARD


No deviation.

4.2.5 TEST SETUP

Below 30MHz test setup




Below 1GHz test setup



Note: For the actual test configuration, please refer to the attached file (Test Setup Photo).

Above 1GHz test setup



Note: For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT OPERATING CONDITIONS

- Placed the EUT on a testing table.
- Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.

4.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA:


802.11b

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9KHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	30.00	34.81 QP	40.00	-5.19	1.00 H	90	40.28	-5.47
2	54.87	29.65 QP	40.00	-10.35	1.00 H	230	47.14	-17.49
3	253.85	36.29 QP	46.00	-9.71	1.00 H	69	44.22	-7.93
4	284.94	36.69 QP	46.00	-9.31	1.00 H	53	44.47	-7.78
5	398.41	33.96 QP	46.00	-12.04	1.00 H	168	36.49	-2.53
6	880.30	40.33 QP	46.00	-5.67	1.00 H	320	34.87	5.46

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.




CHANNEL	TX Channel 1	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9KHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	30.00	37.01 QP	40.00	-2.99	2.00 V	33	42.48	-5.47
2	54.87	36.89 QP	40.00	-3.11	2.00 V	180	54.38	-17.49
3	253.85	29.64 QP	46.00	-16.36	2.00 V	98	37.57	-7.93
4	284.94	30.65 QP	46.00	-15.35	2.00 V	250	38.43	-7.78
5	399.97	32.48 QP	46.00	-13.52	2.00 V	43	34.80	-2.32
6	880.30	38.76 QP	46.00	-7.24	2.00 V	156	33.30	5.46

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.



ABOVE 1GHz DATA

802.11b

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	56.35 PK	74.00	-17.65	1.02 H	89	53.25	3.10
2	2390.00	48.37 AV	54.00	-5.63	1.02 H	89	45.27	3.10
3	*2412.00	110.33 PK			1.35 H	90	107.16	3.17
4	*2412.00	106.06 AV			1.35 H	90	102.89	3.17
5	4824.00	51.24 PK	74.00	-22.76	1.30 H	249	45.14	6.10
6	4824.00	38.69 AV	54.00	-15.31	1.30 H	249	32.59	6.10
7	#7236.00	56.69 PK	74.00	-17.31	1.58 H	247	45.18	11.51
8	#7236.00	43.26 AV	54.00	-10.74	1.58 H	247	31.75	11.51
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	49.68 PK	74.00	-24.32	1.32 V	219	46.58	3.10
2	2390.00	45.26 AV	54.00	-8.74	1.32 V	219	42.16	3.10
3	*2412.00	103.23 PK			1.54 V	245	100.06	3.17
4	*2412.00	100.19 AV			1.54 V	245	97.02	3.17
5	4824.00	51.36 PK	74.00	-22.64	1.30 V	219	45.26	6.10
6	4824.00	41.27 AV	54.00	-12.73	1.30 V	219	35.17	6.10
7	#7236.00	55.58 PK	74.00	-18.42	1.30 V	149	44.07	11.51
8	#7236.00	42.01 AV	54.00	-11.99	1.30 V	149	30.50	11.51

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	110.40 PK			1.58 H	86	107.13	3.27
2	*2437.00	106.26 AV			1.58 H	86	102.99	3.27
3	4874.00	49.69 PK	74.00	-24.31	1.02 H	146	43.49	6.20
4	4874.00	38.98 AV	54.00	-15.02	1.02 H	146	32.78	6.20
5	7311.00	54.35 PK	74.00	-19.65	1.30 H	202	42.63	11.72
6	7311.00	42.01 AV	54.00	-11.99	1.30 H	202	30.29	11.72
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	104.98 PK			1.20 V	140	101.71	3.27
2	*2437.00	101.40 AV			1.20 V	140	98.13	3.27
3	4874.00	50.27 PK	74.00	-23.73	1.35 V	248	44.07	6.20
4	4874.00	38.85 AV	54.00	-15.15	1.35 V	248	32.65	6.20
5	7311.00	55.24 PK	74.00	-18.76	1.35 V	248	43.52	11.72
6	7311.00	42.39 AV	54.00	-11.61	1.35 V	248	30.67	11.72

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	109.60 PK			1.35 H	219	106.24	3.36
2	*2462.00	105.26 AV			1.35 H	219	101.90	3.36
3	2483.50	52.01 PK	74.00	-21.99	1.35 H	249	48.57	3.44
4	2483.50	38.98 AV	54.00	-15.02	1.35 H	249	35.54	3.44
5	4924.00	50.24 PK	74.00	-23.76	1.35 H	246	43.93	6.31
6	4924.00	38.65 AV	54.00	-15.35	1.35 H	246	32.34	6.31
7	7386.00	54.57 PK	74.00	-19.43	1.48 H	259	42.64	11.93
8	7386.00	42.39 AV	54.00	-11.61	1.48 H	259	30.46	11.93

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	108.69 PK			1.24 V	158	105.33	3.36
2	*2462.00	102.58 AV			1.24 V	158	99.22	3.36
3	2483.50	50.29 PK	74.00	-23.71	1.25 V	149	46.85	3.44
4	2483.50	36.98 AV	54.00	-17.02	1.25 V	149	33.54	3.44
5	4924.00	50.37 PK	74.00	-23.63	1.24 V	147	44.06	6.31
6	4924.00	38.37 AV	54.00	-15.63	1.24 V	147	32.06	6.31
7	7386.00	55.27 PK	74.00	-18.73	1.87 V	85	43.34	11.93
8	7386.00	42.38 AV	54.00	-11.62	1.87 V	85	30.45	11.93

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

802.11g

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	72.26 PK	74.00	-1.74	1.15 H	84	69.16	3.10
2	2390.00	53.64 AV	54.00	-0.36	1.15 H	84	50.54	3.10
3	*2412.00	113.68 PK			1.35 H	249	110.51	3.17
4	*2412.00	101.46 AV			1.35 H	249	98.29	3.17
5	4824.00	51.26 PK	74.00	-22.74	1.02 H	210	45.16	6.10
6	4824.00	38.95 AV	54.00	-15.05	1.02 H	210	32.85	6.10
7	#7236.00	54.89 PK	74.00	-19.11	1.69 H	301	43.38	11.51
8	#7236.00	42.18 AV	54.00	-11.82	1.69 H	301	30.67	11.51
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	65.11 PK	74.00	-8.89	1.20 V	149	62.01	3.10
2	2390.00	48.21 AV	54.00	-5.79	1.20 V	149	45.11	3.10
3	*2412.00	106.98 PK			1.00 V	56	103.81	3.17
4	*2412.00	94.85 AV			1.00 V	56	91.68	3.17
5	4824.00	50.68 PK	74.00	-23.32	1.30 V	291	44.58	6.10
6	4824.00	40.01 AV	54.00	-13.99	1.30 V	291	33.91	6.10
7	#7236.00	55.62 PK	74.00	-18.38	1.54 V	216	44.11	11.51
8	#7236.00	43.03 AV	54.00	-10.97	1.54 V	216	31.52	11.51

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	110.68 PK			1.02 H	80	107.41	3.27
2	*2437.00	100.78 AV			1.02 H	80	97.51	3.27
3	4874.00	52.38 PK	74.00	-21.62	1.02 H	147	46.18	6.20
4	4874.00	40.68 AV	54.00	-13.32	1.02 H	147	34.48	6.20
5	7311.00	55.89 PK	74.00	-18.11	1.32 H	258	44.17	11.72
6	7311.00	43.69 AV	54.00	-10.31	1.32 H	258	31.97	11.72
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	106.85 PK			1.05 V	70	103.58	3.27
2	*2437.00	96.31 AV			1.05 V	70	93.04	3.27
3	4874.00	49.68 PK	74.00	-24.32	1.20 V	140	43.48	6.20
4	4874.00	40.38 AV	54.00	-13.62	1.20 V	140	34.18	6.20
5	7311.00	53.28 PK	74.00	-20.72	1.02 V	198	41.56	11.72
6	7311.00	42.31 AV	54.00	-11.69	1.02 V	198	30.59	11.72

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	109.68 PK			1.30 H	298	106.32	3.36
2	*2462.00	100.46 AV			1.30 H	298	97.10	3.36
3	2483.50	70.61 PK	74.00	-3.39	1.69 H	321	67.17	3.44
4	2483.50	52.57 AV	54.00	-1.43	1.69 H	321	49.13	3.44
5	4924.00	51.27 PK	74.00	-22.73	1.52 H	214	44.96	6.31
6	4924.00	39.69 AV	54.00	-14.31	1.52 H	214	33.38	6.31
7	7386.00	55.98 PK	74.00	-18.02	1.30 H	216	44.05	11.93
8	7386.00	42.07 AV	54.00	-11.93	1.30 H	216	30.14	11.93

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	106.45 PK			1.09 V	67	103.09	3.36
2	*2462.00	96.81 AV			1.09 V	67	93.45	3.36
3	2483.50	72.26 PK	74.00	-1.74	1.00 V	63	68.82	3.44
4	2483.50	53.28 AV	54.00	-0.72	1.00 V	63	49.84	3.44
5	4924.00	49.68 PK	74.00	-24.32	1.02 V	135	43.37	6.31
6	4924.00	38.65 AV	54.00	-15.35	1.02 V	135	32.34	6.31
7	7386.00	55.35 PK	74.00	-18.65	1.20 V	187	43.42	11.93
8	7386.00	41.27 AV	54.00	-12.73	1.20 V	187	29.34	11.93

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

802.11n HT20

CHANNEL	TX Channel 1	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	72.03 PK	74.00	-1.97	1.36 H	254	68.93	3.10
2	2390.00	51.98 AV	54.00	-2.02	1.36 H	254	48.88	3.10
3	*2412.00	112.35 PK			1.30 H	215	109.18	3.17
4	*2412.00	100.04 AV			1.30 H	215	96.87	3.17
5	4824.00	50.23 PK	74.00	-23.77	1.30 H	219	44.13	6.10
6	4824.00	40.01 AV	54.00	-13.99	1.30 H	219	33.91	6.10
7	#7236.00	55.23 PK	74.00	-18.77	1.30 H	260	43.72	11.51
8	#7236.00	41.27 AV	54.00	-12.73	1.30 H	260	29.76	11.51

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	68.98 PK	74.00	-5.02	1.30 V	216	65.88	3.10
2	2390.00	49.68 AV	54.00	-4.32	1.30 V	216	46.58	3.10
3	*2412.00	105.27 PK			1.35 V	249	102.10	3.17
4	*2412.00	96.68 AV			1.35 V	249	93.51	3.17
5	4824.00	50.39 PK	74.00	-23.61	1.20 V	140	44.29	6.10
6	4824.00	38.98 AV	54.00	-15.02	1.20 V	140	32.88	6.10
7	#7236.00	55.51 PK	74.00	-18.49	1.25 V	169	44.00	11.51
8	#7236.00	42.69 AV	54.00	-11.31	1.25 V	169	31.18	11.51

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	109.96 PK			1.35 H	89	106.69	3.27
2	*2437.00	100.26 AV			1.35 H	89	96.99	3.27
3	4874.00	50.68 PK	74.00	-23.32	1.02 H	70	44.48	6.20
4	4874.00	38.98 AV	54.00	-15.02	1.02 H	70	32.78	6.20
5	7311.00	54.78 PK	74.00	-19.22	1.69 H	320	43.06	11.72
6	7311.00	41.69 AV	54.00	-12.31	1.69 H	320	29.97	11.72
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	103.21 PK			1.02 V	140	99.94	3.27
2	*2437.00	94.68 AV			1.02 V	140	91.41	3.27
3	4874.00	50.47 PK	74.00	-23.53	1.05 V	135	44.27	6.20
4	4874.00	39.68 AV	54.00	-14.32	1.05 V	135	33.48	6.20
5	7311.00	55.02 PK	74.00	-18.98	1.36 V	201	43.30	11.72
6	7311.00	43.69 AV	54.00	-10.31	1.36 V	201	31.97	11.72

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 11	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	109.32 PK			1.35 H	86	105.96	3.36
2	*2462.00	99.59 AV			1.35 H	86	96.23	3.36
3	2483.50	72.73 PK	74.00	-1.27	1.35 H	249	69.29	3.44
4	2483.50	53.93 AV	54.00	-0.07	1.35 H	249	50.49	3.44
5	4924.00	50.32 PK	74.00	-23.68	1.30 H	89	44.01	6.31
6	4924.00	38.54 AV	54.00	-15.46	1.30 H	89	32.23	6.31
7	7386.00	54.57 PK	74.00	-19.43	1.20 H	90	42.64	11.93
8	7386.00	42.37 AV	54.00	-11.63	1.20 H	90	30.44	11.93
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2462.00	103.21 PK			1.02 V	88	99.85	3.36
2	*2462.00	93.68 AV			1.02 V	88	90.32	3.36
3	2483.50	62.32 PK	74.00	-11.68	1.35 V	249	58.88	3.44
4	2483.50	45.36 AV	54.00	-8.64	1.35 V	249	41.92	3.44
5	4924.00	50.39 PK	74.00	-23.61	1.02 V	70	44.08	6.31
6	4924.00	38.67 AV	54.00	-15.33	1.02 V	70	32.36	6.31
7	7386.00	55.24 PK	74.00	-18.76	1.35 V	68	43.31	11.93
8	7386.00	43.21 AV	54.00	-10.79	1.35 V	68	31.28	11.93

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

802.11n (HT40)

CHANNEL	TX Channel 3	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	73.14 PK	74.00	-0.86	1.30 H	90	70.04	3.10
2	2390.00	48.96 AV	54.00	-5.04	1.30 H	90	45.86	3.10
3	*2422.00	107.00 PK			1.35 H	249	103.79	3.21
4	*2422.00	97.05 AV			1.35 H	249	93.84	3.21
5	4844.00	50.01 PK	74.00	-23.99	1.30 H	149	43.87	6.14
6	4844.00	40.69 AV	54.00	-13.31	1.30 H	149	34.55	6.14
7	7266.00	54.24 PK	74.00	-19.76	1.54 H	90	42.65	11.59
8	7266.00	41.89 AV	54.00	-12.11	1.54 H	90	30.30	11.59
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	72.38 PK	74.00	-1.62	1.35 V	248	69.28	3.10
2	2390.00	53.50 AV	54.00	-0.50	1.35 V	248	50.40	3.10
3	*2422.00	100.36 PK			1.02 V	59	97.15	3.21
4	*2422.00	92.01 AV			1.02 V	59	88.80	3.21
5	4844.00	49.68 PK	74.00	-24.32	1.35 V	249	43.54	6.14
6	4844.00	38.65 AV	54.00	-15.35	1.35 V	249	32.51	6.14
7	7266.00	55.27 PK	74.00	-18.73	1.02 V	89	43.68	11.59
8	7266.00	42.81 AV	54.00	-11.19	1.02 V	89	31.22	11.59

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.
5. " * " : Fundamental frequency.

CHANNEL	TX Channel 6	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	106.10 PK			1.21 H	86	102.83	3.27
2	*2437.00	96.78 AV			1.21 H	86	93.51	3.27
3	4874.00	49.64 PK	74.00	-24.36	1.30 H	85	43.44	6.20
4	4874.00	37.89 AV	54.00	-16.11	1.30 H	85	31.69	6.20
5	7311.00	54.87 PK	74.00	-19.13	1.30 H	80	43.15	11.72
6	7311.00	42.31 AV	54.00	-11.69	1.30 H	80	30.59	11.72
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2437.00	98.87 PK			1.25 V	50	95.60	3.27
2	*2437.00	92.36 AV			1.25 V	50	89.09	3.27
3	4874.00	50.08 PK	74.00	-23.92	1.30 V	87	43.88	6.20
4	4874.00	40.39 AV	54.00	-13.61	1.30 V	87	34.19	6.20
5	7311.00	55.01 PK	74.00	-18.99	1.36 V	95	43.29	11.72
6	7311.00	40.12 AV	54.00	-13.88	1.36 V	95	28.40	11.72

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.

CHANNEL	TX Channel 9	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	107.20 PK			1.30 H	98	103.88	3.32
2	*2452.00	96.95 AV			1.30 H	98	93.63	3.32
3	2483.50	73.30 PK	74.00	-0.70	1.35 H	249	69.86	3.44
4	2483.50	49.65 AV	54.00	-4.35	1.35 H	249	46.21	3.44
5	4904.00	50.32 PK	74.00	-23.68	1.35 H	87	44.05	6.27
6	4904.00	38.98 AV	54.00	-15.02	1.35 H	87	32.71	6.27
7	7356.00	55.24 PK	74.00	-18.76	1.30 H	86	43.40	11.84
8	7356.00	42.03 AV	54.00	-11.97	1.30 H	86	30.19	11.84

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2452.00	94.00 PK			1.35 V	88	90.68	3.32
2	*2452.00	84.60 AV			1.35 V	88	81.28	3.32
3	2483.50	61.78 PK	74.00	-12.22	1.21 V	90	58.34	3.44
4	2483.50	38.21 AV	54.00	-15.79	1.21 V	90	34.77	3.44
5	4904.00	49.69 PK	74.00	-24.31	1.36 V	90	43.42	6.27
6	4904.00	41.03 AV	54.00	-12.97	1.36 V	90	34.76	6.27
7	7356.00	56.69 PK	74.00	-17.31	1.02 V	249	44.85	11.84
8	7356.00	43.27 AV	54.00	-10.73	1.02 V	249	31.43	11.84

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The emission levels of other frequencies were less than 20dB margin against the limit.
4. Margin value = Emission level – Limit value.
5. " * " : Fundamental frequency.

4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Power Sensor	Keysight	U2021XA	MY55060016	May 19,17	May 18,18
Power Sensor	Keysight	U2021XA	MY55060018	May 19,17	May 18,18
Power Meter	Anritsu	ML2495A	1139001	Nov. 04,17	Nov. 03,18
Digital Multimeter	FLUKE	15B	A1220010DG	Oct. 21, 17	Oct. 20, 18
Humid & Temp Programmable Tester	Haida	HD-2257	110807201	Sep.05,17	Sep. 04,18
Oscilloscope	Agilent	DSO9254A	MY51260160	Nov. 08,17	Nov. 07,18
Signal Analyzer	Rohde & Schwarz	FSV7	102331	Nov. 04,17	Nov. 03,18
Signal Generator	Agilent	N5183A	MY50140980	Jan. 02,18	Jan. 01,19
Agile Signal Generator	Agilent	8645A	Agilent	Sep.01, 17	Aug.31, 18
Spectrum Analyzer	Keysight	N9020A	MY55400499	Apr. 10,17	Apr. 09,18
MXG-B RF Vector Signal Generator	Keysight	N5182B	MY56200288	Jan. 02,18	Jan. 01,19
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	Aug.10, 17	Aug.09, 18
Attenuator	MINI	BW-S10W2+	S130129FGE2	N/A	N/A
DC Source	Keysight	E3642A	MY56146098	N/A	N/A

NOTE:

1. The test was performed in RF Oven room.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.


4.3.3 TEST PROCEDURE

1. Set resolution bandwidth (RBW) = 100KHz
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
3. Trace mode = max hold.
4. Sweep = auto couple.
5. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

4.3.4 DEVIATION FROM TEST STANDARD

No deviation.

4.3.5 TEST SETUP



4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 TEST RESULTS

802.11b

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	9.07	0.5	PASS
6	2437	8.60	0.5	PASS
11	2462	9.09	0.5	PASS

802.11g


CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	15.76	0.5	PASS
6	2437	15.46	0.5	PASS
11	2462	15.78	0.5	PASS

802.11n HT20

CHANNEL	CHANNEL FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2412	16.10	0.5	PASS
6	2437	16.79	0.5	PASS
11	2462	16.02	0.5	PASS

802.11n HT40

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
3	2422	35.22	0.5	PASS
6	2437	35.21	0.5	PASS
9	2452	35.25	0.5	PASS




4.4 CONDUCTED OUTPUT POWER

4.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation in the 2400–2483.5 MHz band: 1 Watt (30dBm).

4.4.2 TEST SETUP



4.4.3 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Power Sensor	Keysight	U2021XA	MY55060016	May 19,17	May 18,18
Power Sensor	Keysight	U2021XA	MY55060018	May 19,17	May 18,18
Power Meter	Anritsu	ML2495A	1139001	Nov. 04,17	Nov. 03,18
Digital Multimeter	FLUKE	15B	A1220010DG	Oct. 21, 17	Oct.20, 18
Humid & Temp Programmable Tester	Haida	HD-2257	110807201	Sep.05,17	Sep. 04,18
Oscilloscope	Agilent	DSO9254A	MY51260160	Nov. 08,17	Nov. 07,18
Signal Analyzer	Rohde & Schwarz	FSV7	102331	Nov. 04,17	Nov. 03,18
Signal Generator	Agilent	N5183A	MY50140980	Jan. 02,18	Jan. 01,19
Agile Signal Generator	Agilent	8645A	Agilent	Sep.01, 17	Aug.31, 18
Spectrum Analyzer	Keysight	N9020A	MY55400499	Apr. 10,17	Apr. 09,18
MXG-B RF Vector Signal Generator	Keysight	N5182B	MY56200288	Jan. 02,18	Jan. 01,19
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	Aug.10, 17	Aug.09, 18
Attenuator	MINI	BW-S10W2+	S130129FGE2	N/A	N/A
DC Source	Keysight	E3642A	MY56146098	N/A	N/A

NOTE:

1. The test was performed in RF Oven room.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



4.4.4 TEST PROCEDURES

Average power sensor was used on the output port of the EUT. Average power meter was used to read the response of the average power sensor. Record the average power level.

4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

4.4.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.4.7 TEST RESULTS

AVERAGE OUTPUT POWER

The average power sensor was used on the output port of the EUT. A power meter was used to read the response of the power sensor. Record the power level.

802.11b

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVG. POWER (mW)	POWER LIMIT (W)	PASS / FAIL
1	2412	13.39	21.827	1	PASS
6	2437	13.94	24.774	1	PASS
11	2462	13.25	21.135	1	PASS

802.11g

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVG. POWER (mW)	POWER LIMIT (W)	PASS / FAIL
1	2412	12.06	16.069	1	PASS
6	2437	12.53	17.906	1	PASS
11	2462	11.96	15.704	1	PASS

802.11n HT20

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVG. POWER (mW)	POWER LIMIT (W)	PASS / FAIL
1	2412	12.12	16.293	1	PASS
6	2437	12.49	17.742	1	PASS
11	2462	11.93	15.596	1	PASS

802.11n HT40


CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVG. POWER (mW)	POWER LIMIT (W)	PASS / FAIL
3	2422	11.15	13.032	1	PASS
6	2437	12.33	17.100	1	PASS
9	2452	10.23	10.544	1	PASS

4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm/3KHz.

4.5.2 TEST SETUP



4.5.3 TEST INSTRUMENTS

Refer to section 4.3.2 to get information of above instrument.

4.5.4 TEST PROCEDURE

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set span to 1.5 times the DTS bandwidth
- c) Set RBW to: 3KHz
- d) Set VBW $\geq 3 \times$ RBW.
- e) Detector = peak
- f) Ensure that the number of measurement points in the sweep $\geq 2 \times$ span/RBW.
- g) Sweep time = auto couple.
- h) Use the peak marker function to determine the maximum amplitude level.

4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

4.5.6 EUT OPERATING CONDITION

Same as item 4.3.6.

4.5.7 TEST RESULTS

802.11b

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-12.87	8.00	PASS
6	2437	-12.15	8.00	PASS
11	2462	-12.23	8.00	PASS

802.11g


Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-13.52	8.00	PASS
6	2437	-14.17	8.00	PASS
11	2462	-13.91	8.00	PASS

802.11n HT20

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2412	-14.44	8.00	PASS
6	2437	-12.92	8.00	PASS
11	2462	-13.97	8.00	PASS

802.11n HT40

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
3	2422	-16.41	8.00	PASS
6	2437	-17.39	8.00	PASS
9	2452	-19.05	8.00	PASS




4.6 OUT OF BAND EMISSION MEASUREMENT

4.6.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below -30dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST SETUP



4.6.3 TEST INSTRUMENTS

Refer to section 4.3.2 to get information of above instrument.

4.6.4 TEST PROCEDURE

Measurement Procedure - Reference Level

1. Set the RBW = 100 kHz.
2. Set the VBW \geq 300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.



Test Report No.: RF171129N008-3

Measurement Procedure –Unwanted Emission Level

1. Set RBW = 100 kHz.
2. Set VBW \geq 300 kHz.
3. Set span to encompass the spectrum to be examined
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.

4.6.5 DEVIATION FROM TEST STANDARD

No deviation.


4.6.6 EUT OPERATING CONDITION

Same as item 4.3.6


4.6.7 TEST RESULTS

802.11b


CH 1



CH 6




CH 11




802.11g


CH 1



CH 6





CH 11





802.11n HT20



CH 1



CH 6



CH 11







BUREAU VERITAS



Test Report No.: RF171129N008-3

802.11n HT40



CH 3




CH 6




CH 9




802.11b



802.11g



802.11n HT20






BUREAU VERITAS


Test Report No.: RF171129N008-3

802.11n HT40

CH 3 Band edge



CH 9 Band edge



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com



Test Report No.: RF171129N008-3

5 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



Test Report No.: RF171129N008-3

6 APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---