



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

No. 1 Workshop, M-10, Middle section, Science & Technology Park, Nanshan
District, Shenzhen, Guangdong, China 518057

Telephone: +86 (0) 755 2601 2053
Fax: +86 (0) 755 2671 0594
Email: ee.shenzhen@sgs.com

Report No.: SZEM150700437302
Page: 1 of 143

FCC REPORT

Application No:	SZEM1507004373CR
Applicant:	Polk Audio
Manufacturer:	Polk Audio
Factory:	Zhao Yang Electronic (ShenZhen) Co., Ltd.
Product Name:	wireless all-in-one speaker system
Model No.(EUT):	OMNI S6
Trade Mark:	POLK
FCC ID:	WLQOMNIS6L
Standards:	47 CFR Part 15, Subpart C (2014)
Date of Receipt:	2015-07-25
Date of Test:	2015-08-18 to 2015-08-24
Date of Issue:	2015-09-02

Test Result:	PASS *
---------------------	---------------

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Jack Zhang
EMC Laboratory Manager


The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of SGS International Electrical Approvals or testing done by SGS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by SGS International Electrical Approvals in writing.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

2 Version

Revision Record				
Version	Chapter	Date	Modifier	Remark
00		2015-09-02		Original

Authorized for issue by:			
			2015-08-24
Tested By		(Owen Zhou) /Project Engineer	Date
			2015-09-02
Prepared By		(Joyce Shi) /Clerk	Date
			2015-09-02
Checked By		(Eric Fu) /Reviewer	Date

3 Test Summary

Test Item	Test Requirement	Test method	Result
Antenna Requirement	47 CFR Part 15, Subpart C Section 15.203/15.247 (c)	ANSI C63.10 2013	PASS
AC Power Line Conducted Emission	47 CFR Part 15, Subpart C Section 15.207	ANSI C63.10 2013	PASS
Conducted Peak Output Power	47 CFR Part 15, Subpart C Section 15.247 (b)(3)	ANSI C63.10 2013	PASS
6dB Occupied Bandwidth	47 CFR Part 15, Subpart C Section 15.247 (a)(2)	ANSI C63.10 2013	PASS
Power Spectral Density	47 CFR Part 15, Subpart C Section 15.247 (e)	ANSI C63.10 2013	PASS
Band-edge for RF Conducted Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2013	PASS
RF Conducted Spurious Emissions	47 CFR Part 15, Subpart C Section 15.247(d)	ANSI C63.10 2013	PASS
Radiated Spurious Emissions	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2013	PASS
Restricted bands around fundamental frequency (Radiated Emission)	47 CFR Part 15, Subpart C Section 15.205/15.209	ANSI C63.10 2013	PASS

4 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 TEST SUMMARY	3
4 CONTENTS	4
5 GENERAL INFORMATION.....	5
5.1 CLIENT INFORMATION	5
5.2 GENERAL DESCRIPTION OF EUT	5
5.3 TEST ENVIRONMENT AND MODE.....	7
5.4 DESCRIPTION OF SUPPORT UNITS.....	7
5.5 TEST LOCATION.....	7
5.6 TEST FACILITY.....	8
5.7 DEVIATION FROM STANDARDS	8
5.8 ABNORMALITIES FROM STANDARD CONDITIONS.....	8
5.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER.....	8
5.10 EQUIPMENT LIST	9
6 TEST RESULTS AND MEASUREMENT DATA.....	12
6.1 ANTENNA REQUIREMENT	12
6.2 CONDUCTED EMISSIONS.....	13
6.3 CONDUCTED PEAK OUTPUT POWER	17
6.4 6dB OCCUPY BANDWIDTH.....	32
6.5 POWER SPECTRAL DENSITY.....	40
6.6 BAND-EDGE FOR RF CONDUCTED EMISSIONS.....	54
6.7 RF CONDUCTED SPURIOUS EMISSIONS.....	59
TEST PLOT AS FOLLOWS:.....	60
6.8 RADIATED SPURIOUS EMISSIONS.....	96
6.8.1 Radiated emission below 1GHz.....	99
6.8.2 Transmitter emission above 1GHz.....	101
6.9 RESTRICTED BANDS AROUND FUNDAMENTAL FREQUENCY.....	108
7 PHOTOGRAPHS - EUT TEST SETUP.....	142
7.1 CONDUCTED EMISSION.....	142
7.2 RADIATED SPURIOUS EMISSION.....	142
8 PHOTOGRAPHS - EUT CONSTRUCTIONAL DETAILS	143

5 General Information

5.1 Client Information

Applicant:	Polk Audio
Address of Applicant:	5601 Metro Drive Baltimore, Maryland, 21215, USA
Manufacturer:	Polk Audio
Address of Manufacturer:	5601 Metro Drive Baltimore, Maryland, 21215, USA
Factory:	Zhao Yang Electronic (ShenZhen) Co., Ltd.
Address of Factory:	Section A, 4th Floor, Building 1 & Building 2, De Yong Jia Industrial Park, Guang Qiao Road, Yu Lv Community, Gong Ming Street, Guang Ming New District, Shenzhen, Guangdong, P.R.C

5.2 General Description of EUT

Product Name:	wireless all-in-one speaker system
Model No.:	OMNI S6
Trade Mark:	POLK
Operation Frequency:	IEEE 802.11b/g/n(HT20): 2412MHz to 2462MHz IEEE 802.11n(HT40): 2422MHz to 2452MHz
Channel Numbers:	IEEE 802.11b/g, IEEE 802.11n(HT20): 11 Channels IEEE 802.11n(HT40): 7 Channels
Channel Separation:	5MHz
Type of Modulation:	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE802.11n(HT20 and HT40): OFDM (64QAM, 16QAM, QPSK, BPSK)
Sample Type:	Fixed production
Test Power Grade:	802.11b :15dBm@11Mbps; 802.11g:14dBm@ 54Mbps; 802.11n20(2.4G):13 dBm@MCS7; 802.11n40(2.4G) :10 dBm@MCS7
Test Software of EUT:	teraterm.exe (manufacturer declare)
Antenna Type:	Integral
Antenna Gain:	2.28dBi
Antenna Delivery:	1TX+1RX Remark: The antennas can not transmit simultaneously.
Power Supply:	AC 100-240V 50/60Hz
Test Voltage:	AC 120V 60Hz

Operation Frequency each of channel(802.11b/g/n HT20)							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Operation Frequency each of channel(802.11n HT40)					
Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2422MHz	4	2437MHz	7	2452MHz
2	2427MHz	5	2442MHz		
3	2432MHz	6	2447MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

For 802.11b/g/n (HT20):

Channel	Frequency
The Lowest channel	2412MHz
The Middle channel	2437MHz
The Highest channel	2462MHz

For 802.11n (HT40)

Channel	Frequency
The Lowest channel	2422MHz
The Middle channel	2437MHz
The Highest channel	2452MHz

5.3 Test Environment and Mode

Operating Environment:	
Temperature:	24.0 °C
Humidity:	52 % RH
Atmospheric Pressure:	1005 mbar
Test mode:	
Transmitting mode	Keep the EUT in transmitting mode with all kind of modulation and all kind of data rate.

5.4 Description of Support Units

The EUT has been tested independent unit.

5.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch E&E Lab,

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China.
518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS (No. CNAS L2929)**

CNAS has accredited SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch EMC Lab to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration Laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **VCCI**

The 10m Semi-anechoic chamber and Shielded Room (7.5m x 4.0m x 3.0m) of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-823, R-4188, T-1153 and C-2383 respectively.

- **FCC – Registration No.: 556682**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 556682.

- **Industry Canada (IC)**

Two 3m Semi-anechoic chambers of SGS-CSTC Standards Technical Services Co., Ltd. have been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 4620C-2.

5.7 Deviation from Standards

None.

5.8 Abnormalities from Standard Conditions

None.

5.9 Other Information Requested by the Customer

None.

5.10 Equipment List

Conducted Emission					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	Shielding Room	ZhongYu Electron	GB-88	SEL0042	2016-05-13
2	LISN	Rohde & Schwarz	ENV216	SEL0152	2015-10-24
3	LISN	ETS-LINDGREN	3816/2	SEL0021	2016-05-13
4	8 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T8-02	SEL0162	2015-08-30
5	4 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T4-02	SEL0163	2015-08-30
6	2 Line ISN	Fischer Custom Communications Inc.	FCC-TLISN-T2-02	SEL0164	2015-08-30
7	EMI Test Receiver	Rohde & Schwarz	ESCI	SEL0022	2016-05-13
8	Coaxial Cable	SGS	N/A	SEL0025	2016-05-13
9	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2015-10-24
10	Humidity/ Temperature Indicator	Shanghai Qixiang	ZJ1-2B	SEL0103	2015-10-24
11	Barometer	Chang Chun	DYM3	SEL0088	2016-05-13





SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

Report No.: SZEM150700437302

Page: 10 of 143

RE in Chamber					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	3m Semi-Anechoic Chamber	ETS-LINDGREN	N/A	SEL0017	2016-05-13
2	Spectrum Analyzer	Rohde & Schwarz	FSU43	SEL0270	2016-04-25
3	EMI Test software	AUDIX	E3	SEL0050	N/A
4	BiConiLog Antenna (26-3000MHz)	ETS-LINDGREN	3142C	SEL0015	2015-10-24
5	Double-ridged horn (1-18GHz)	ETS-LINDGREN	3117	SEL0006	2015-10-24
6	Horn Antenna (18-26GHz)	ETS-LINDGREN	3160	SEL0076	2015-10-24
7	Horn Antenna(26GHz-40 GHz)	A.H.Systems, inc.	SAS-573	SEL0349	2016-03-20
8	Pre-amplifier (0.1-1300MHz)	Agilent Technologies	8447D	SEL0053	2016-05-16
9	Pre-Amplifier (0.1-26.5GHz)	Compliance Directions Systems Inc.	PAP-0126	SEL0168	2015-10-24
10	Pre-amplifier(26GHz -40GHz)	Compliance Directions Systems Inc.	PAP-2640-50	SEL0350	2016-03-20
11	Coaxial cable	SGS	N/A	SEL0027	2016-05-29
12	Coaxial cable	SGS	N/A	SEL0189	2016-05-29
13	Coaxial cable	SGS	N/A	SEL0121	2016-05-29
14	Coaxial cable	SGS	N/A	SEL0178	2016-05-29
16	Barometer	Chang Chun	DYM3	SEL0088	2016-05-13
17	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2015-10-24
18	Humidity/ Temperature Indicator	Shanghai Qixiang	ZJ1-2B	SEL0103	2015-10-24
19	Signal Generator (10M-27GHz)	Rohde & Schwarz	SMR27	SEL0067	2016-05-16
20	Signal Generator	Rohde & Schwarz	SMY01	SEL0155	2015-10-24
21	Loop Antenna	Beijing Daze	ZN30401	SEL0203	2016-05-13

*This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

RF connected test					
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Due date (yyyy-mm-dd)
1	DC Power Supply	Zhao Xin	RXN-305D	SEL0117	2015-10-24
2	Humidity/ Temperature Indicator	HYGRO	ZJ1-2B	SEL0033	2015-10-24
3	Spectrum Analyzer	Rohde & Schwarz	FSP	SEL0154	2015-10-24
4	Coaxial cable	SGS	N/A	SEL0178	2016-05-13
5	Coaxial cable	SGS	N/A	SEL0179	2016-05-13
6	Barometer	ChangChun	DYM3	SEL0088	2016-05-13
7	Signal Generator	Rohde & Schwarz	SML03	SEL0068	2016-04-25
8	Band filter	amideon	82346	SEL0094	2016-05-13
9	POWER METER	R & S	NRVS	SEL0144	2015-10-24
10	Attenuator	Beijin feihang taida	TST-2-6dB	SEL0205	2016-04-25
11	Power Divider(splitter)	Agilent Technologies	11636B	SEL0130	2015-10-24

6 Test results and Measurement Data

6.1 Antenna Requirement

Standard requirement:	47 CFR Part 15C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	15.247(b) (4) requirement: The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.
EUT Antenna:	
	The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 2.28dBi. It support operations in 1X1 diversity , 1 X1 SISO configurations and Single-stream legacy modes.

6.2 Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.207					
Test Method:	ANSI C63.10: 2013					
Test Frequency Range:	150kHz to 30MHz					
Limit:	Frequency range (MHz)		Limit (dBuV)			
			Quasi-peak	Average		
	0.15-0.5	66 to 56*		56 to 46*		
	0.5-5	56		46		
5-30		60		50		
* Decreases with the logarithm of the frequency.						
Test Procedure:	<ol style="list-style-type: none">1) The mains terminal disturbance voltage test was conducted in a shielded room.2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a $50\Omega/50\mu\text{H} + 5\Omega$ linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane.4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10: 2013 on conducted measurement.					


Test Setup:	
Exploratory Test Mode:	<p>Transmitting with all kind of modulations, data rates at lowest, middle and highest channel.</p> <p>Transmitting mode.</p>
Final Test Mode:	<p>Through Pre-scan, find the 1Mbps of rate of 802.11b at lowest channel is the worst case.</p> <p>Transmitting mode.</p> <p>Only the worst case is recorded in the report.</p> <p>Pre-scan was performed at Antenna 0 and Antenna 1, no worst case was found. Only the test data of Antenna 0 was shown in this report.</p>
Instruments Used:	Refer to section 5.10 for details.
Test Results:	Pass

Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.


Live Line:



Site : Shielding Room
Condition : 47 CFR PART15C AV CE LINE
Job No. : 4373CR
Test Mode : TX

	Freq	Cable	LISN	Read	Limit	Over	Remark
		Loss	Factor	Level	Level	Line	
	MHz	dB	dB	dBuV	dBuV	dB	
1	0.15321	0.02	9.82	41.15	51.00	55.82	-4.83 Peak
2	0.19550	0.02	9.83	35.80	45.64	53.80	-8.15 Peak
3	0.28782	0.01	9.84	26.87	36.73	50.59	-13.86 Peak
4	2.854	0.02	10.02	25.81	35.84	46.00	-10.16 Peak
5	4.269	0.01	10.09	27.30	37.41	46.00	-8.59 Peak
6	9.502	0.01	10.15	32.66	42.82	50.00	-7.18 Peak

Neutral Line:




Site : Shielding Room
Condition : 47 CFR PART15C AV CE NEUTRAL
Job No. : 4373CR
Test Mode : TX

	Freq	Cable	LISN	Read	Limit	Over	Remark
		Loss	Factor	Level			
	MHz	dB	dB	dBuV	dBuV	dBuV	dB
1	0.15160	0.02	9.78	37.81	47.61	55.91	-8.30 Peak
2	0.23533	0.02	9.86	30.37	40.24	52.26	-12.01 Peak
3	1.426	0.02	10.07	20.99	31.09	46.00	-14.91 Peak
4	2.884	0.02	10.12	25.83	35.98	46.00	-10.02 Peak
5	4.269	0.01	10.13	26.96	37.11	46.00	-8.89 Peak
6	11.438	0.01	10.16	29.82	39.99	50.00	-10.01 Peak

Notes:

1. The following Quasi-Peak and Average measurements were performed on the EUT:
2. Final Test Level = Receiver Reading + LISN Factor + Cable Loss.

6.3 Conducted Peak Output Power

Test Requirement:	47 CFR Part 15C Section 15.247 (b)(3)
Test Method:	ANSI C63.10 2013
Test Setup:	 <p>Spectrum Analyzer E.U.T Non-Conducted Table Ground Reference Plane</p>
	<p><i>Remark:</i> <i>Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.</i></p>
Test Instruments:	Refer to section 5.10 for details.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates.
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40).
Limit:	30dBm
Test Results:	Pass

Pre-scan under all rate at lowest channel of Antenna 0								
Mode	802.11b							
Data Rate	1Mbps	2Mbps	5.5Mbps	11Mbps				
Power (dBm)	16.43	16.33	16.25	16.03				
Mode	802.11g							
Data Rate	6Mbps	9Mbps	12Mbps	18Mbps	24Mbps	36Mbps	48Mbps	54Mbps
Power (dBm)	20.99	20.81	20.74	20.65	20.52	20.41	20.32	20.11
Mode	802.11n(HT20)							
Data Rate	6.5Mbps	13Mbps	19.5Mbps	26Mbps	39Mbps	52Mbps	58.5Mbps	65Mbps
Power (dBm)	19.86	19.79	19.65	19.54	19.33	19.21	19.05	18.86
Mode	802.11n(HT40)							
Data Rate	13.5Mbps	27Mbps	40.5Mbps	54Mbps	81Mbps	108Mbps	121.5Mbps	135Mbps
Power (dBm)	16.19	16.03	15.92	15.86	15.72	15.54	15.38	15.26

Through Pre-scan, 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40).



Measurement Data

802.11b mode				
Test channel	Peak Output Power (dBm)		Limit (dBm)	Result
	Antenna 0	Antenna 1		
Lowest	16.43	15.36	30.00	Pass
Middle	17.36	15.77	30.00	Pass
Highest	18.01	16.51	30.00	Pass
802.11g mode				
Test channel	Peak Output Power (dBm)		Limit (dBm)	Result
	Antenna 0	Antenna 1		
Lowest	20.99	19.40	30.00	Pass
Middle	21.31	19.65	30.00	Pass
Highest	20.92	19.40	30.00	Pass
802.11n(HT20) mode				
Test channel	Peak Output Power (dBm)		Limit (dBm)	Result
	Antenna 0	Antenna 1		
Lowest	19.86	18.27	30.00	Pass
Middle	19.88	18.94	30.00	Pass
Highest	19.82	18.71	30.00	Pass
802.11n(HT40) mode				
Test channel	Peak Output Power (dBm)		Limit (dBm)	Result
	Antenna 0	Antenna 1		
Lowest	16.19	15.04	30.00	Pass
Middle	16.14	15.03	30.00	Pass
Highest	16.07	15.02	30.00	Pass




Test plot as follows:

Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------

Antenna 0

Antenna 1


Test mode:	802.11b	Test channel:	Middle
------------	---------	---------------	--------

Antenna 0


Antenna 1


Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------



Antenna 0



Antenna 1




Test mode:	802.11g	Test channel:	Lowest
------------	---------	---------------	--------


Antenna 0

Antenna 1


Test mode:	802.11g	Test channel:	Middle
------------	---------	---------------	--------

Antenna 0




Antenna 1



Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------

Antenna 0



Antenna 1



Test mode:	802.11n(HT20)	Test channel:	Lowest
------------	---------------	---------------	--------

Antenna 0



Antenna 1




Test mode:	802.11n(HT20)	Test channel:	Middle
------------	---------------	---------------	--------



Antenna 0

Antenna 1




Test mode:	802.11n(HT20)	Test channel:	Highest
------------	---------------	---------------	---------

Antenna 0

Antenna 1


Test mode:	802.11n(HT40)	Test channel:	Lowest
------------	---------------	---------------	--------


Antenna 0

Antenna 1


Test mode:	802.11n(HT40)	Test channel:	Middle
------------	---------------	---------------	--------


Antenna 0

Antenna 1


Test mode:	802.11n(HT40)	Test channel:	Highest
------------	---------------	---------------	---------


Antenna 0



Antenna 1



6.4 6dB Occupy Bandwidth

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(2)
Test Method:	ANSI C63.10 2013
Test Setup:	
Instruments Used:	Refer to section 5.10 for details.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates.
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40). Pre-scan was performed at Antenna 0 and Antenna 1, no worst case was found. Only the test data of Antenna 0 was shown in this report.
Limit:	≥ 500 kHz
Test Results:	Pass

Measurement Data

802.11b mode			
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result
Lowest	10.144	≥500	Pass
Middle	10.144	≥500	Pass
Highest	10.144	≥500	Pass


802.11g mode			
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result
Lowest	16.490	≥500	Pass
Middle	16.490	≥500	Pass
Highest	16.683	≥500	Pass

802.11n(HT20) mode			
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result
Lowest	17.740	≥500	Pass
Middle	17.740	≥500	Pass
Highest	17.740	≥500	Pass


802.11n(HT40) mode			
Test channel	6dB Occupy Bandwidth (MHz)	Limit (kHz)	Result
Lowest	36.699	≥500	Pass
Middle	36.699	≥500	Pass
Highest	36.522	≥500	Pass

Test plot as follows:


Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------




Test mode:	802.11b	Test channel:	Middle
------------	---------	---------------	--------




Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------




Test mode:	802.11g	Test channel:	Lowest
------------	---------	---------------	--------




Test mode:	802.11g	Test channel:	Middle
------------	---------	---------------	--------




Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------




Test mode:	802.11n(HT20)	Test channel:	Lowest
------------	---------------	---------------	--------




Test mode:	802.11n(HT20)	Test channel:	Middle
------------	---------------	---------------	--------




Test mode:	802.11n(HT20)	Test channel:	Highest
------------	---------------	---------------	---------




Test mode:	802.11n(HT40)	Test channel:	Lowest
------------	---------------	---------------	--------




Test mode:	802.11n(HT40)	Test channel:	Middle
------------	---------------	---------------	--------



Test mode:	802.11n(HT40)	Test channel:	Highest
------------	---------------	---------------	---------



6.5 Power Spectral Density

Test Requirement:	47 CFR Part 15C Section 15.247 (e)
Test Method:	ANSI C63.10 2013
Test Setup:	 <p>Spectrum Analyzer E.U.T Non-Conducted Table Ground Reference Plane</p> <p><i>Remark:</i> <i>Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.</i></p>
Test Instruments:	Refer to section 5.10 for details.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates.
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40).
Limit:	≤8.00dBm/3kHz
Test Results:	Pass


Measurement Data

802.11b mode				
Test channel	Power Spectral Density (dBm/3kHz)		Limit (dBm/3kHz)	Result
	Antenna 0	Antenna 1		
Lowest	-15.51	-17.30	≤8.00	Pass
Middle	-15.09	-16.85	≤8.00	Pass
Highest	-14.77	-15.94	≤8.00	Pass
802.11g mode				
Test channel	Power Spectral Density (dBm/3kHz)		Limit (dBm/3kHz)	Result
	Antenna 0	Antenna 1		
Lowest	-15.96	-17.17	≤8.00	Pass
Middle	-15.66	-17.50	≤8.00	Pass
Highest	-15.37	-17.63	≤8.00	Pass
802.11n (HT20) mode				
Test channel	Power Spectral Density (dBm/3kHz)		Limit (dBm/3kHz)	Result
	Antenna 0	Antenna 1		
Lowest	-16.62	-17.66	≤8.00	Pass
Middle	-15.89	-17.92	≤8.00	Pass
Highest	-16.46	-17.46	≤8.00	Pass
802.11n(HT40) mode				
Test channel	Power Spectral Density (dBm/3kHz)		Limit (dBm/3kHz)	Result
	Antenna 0	Antenna 1		
Lowest	-23.33	-23.16	≤8.00	Pass
Middle	-23.53	-22.23	≤8.00	Pass
Highest	-22.90	-23.08	≤8.00	Pass


Test plot as follows:

Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------

Antenna 0




Antenna 1




Test mode:	802.11b	Test channel:	Middle
------------	---------	---------------	--------

Antenna 0




Antenna 1




Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------

Antenna 0




Antenna 1




Test mode:	802.11g	Test channel:	Lowest
------------	---------	---------------	--------

Antenna 0




Antenna 1




Test mode:	802.11g	Test channel:	Middle
------------	---------	---------------	--------

Antenna 0




Antenna 1




Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------

Antenna 0




Antenna 1




Test mode:	802.11n (HT20)	Test channel:	Lowest
------------	----------------	---------------	--------

Antenna 0




Antenna 1




Test mode:	802.11n (HT20)	Test channel:	Middle
------------	----------------	---------------	--------

Antenna 0




Antenna 1




Test mode:	802.11n (HT20)	Test channel:	Highest
------------	----------------	---------------	---------

Antenna 0




Antenna 1




Test mode:	802.11n (HT40)	Test channel:	Lowest
------------	----------------	---------------	--------

Antenna 0




Antenna 1




Test mode:	802.11n (HT40)	Test channel:	Middle
------------	----------------	---------------	--------

Antenna 0




Antenna 1




Test mode:	802.11n (HT40)	Test channel:	Highest
------------	----------------	---------------	---------


Antenna 0



Antenna 1




6.6 Band-edge for RF Conducted Emissions


Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10 2013
Test Setup:	 <p>Spectrum Analyzer E.U.T Non-Conducted Table Ground Reference Plane</p> <p><i>Remark:</i> <i>Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.</i></p>
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates.
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40). Pre-scan was performed at Antenna 0 and Antenna 1, no worst case was found. Only the test data of Antenna 0 was shown in this report.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Instruments Used:	Refer to section 5.10 for details.
Test Results:	Pass

Test plot as follows:


Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------




Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------




Test mode:	802.11g	Test channel:	Lowest
------------	---------	---------------	--------




Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------




Test mode:	802.11n (HT20)	Test channel:	Lowest
------------	----------------	---------------	--------




Test mode:	802.11n (HT20)	Test channel:	Highest
------------	----------------	---------------	---------




Test mode:	802.11n (HT40)	Test channel:	Lowest
------------	----------------	---------------	--------



Test mode:	802.11n (HT40)	Test channel:	Highest
------------	----------------	---------------	---------





6.7 RF Conducted Spurious Emissions



Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10 2013
Test Setup:	 <p>Remark: <i>Offset the High-Frequency cable loss 1.5dB in the spectrum analyzer.</i></p>
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates.
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40). Pre-scan was performed at Antenna 0 and Antenna 1, no worst case was found. Only the test data of Antenna 0 was shown in this report.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Instruments Used:	Refer to section 5.10 for details.
Test Results:	Pass





Test plot as follows:



Test mode:	802.11b	Test channel:	Lowest
------------	---------	---------------	--------













Test mode:	802.11b	Test channel:	Middle
------------	---------	---------------	--------













Test mode:	802.11b	Test channel:	Highest
------------	---------	---------------	---------











Test mode:	802.11g	Test channel:	Lowest
------------	---------	---------------	--------







"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms_and_conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms_e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."









Test mode:	802.11g	Test channel:	Middle
------------	---------	---------------	--------













Test mode:	802.11g	Test channel:	Highest
------------	---------	---------------	---------













Test mode:	802.11n (HT20)	Test channel:	Lowest
------------	----------------	---------------	--------













Test mode:	802.11n (HT20)	Test channel:	Middle
------------	----------------	---------------	--------













Test mode:	802.11n (HT20)	Test channel:	Highest
------------	----------------	---------------	---------













Test mode:	802.11n (HT40)	Test channel:	Lowest
------------	----------------	---------------	--------













Test mode:	802.11n (HT40)	Test channel:	Middle
------------	----------------	---------------	--------











Test mode:	802.11n (HT40)	Test channel:	Highest
------------	----------------	---------------	---------






Remark:

Pretest 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o) ,The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.

6.8 Radiated Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10 2013				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.					

Test Setup:	

Figure 1. Below 30MHz

Figure 2. 30MHz to 1GHz

Figure 3. Above 1 GHz


Test Procedure:

- For below 1GHz test, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz test, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to height 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

	<ul style="list-style-type: none">g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.h. Test the EUT in the lowest channel, the middle channel, the Highest channel.i. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates. Transmitting mode
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40). For below 1GHz, through Pre-scan, find the 1Mbps of rate of 802.11b at lowest channel is the worst case. Only the worst case is recorded in the report. Pre-scan was performed at Antenna 0 and Antenna 1, no worst case was found. Only the test data of Antenna 0 was shown in this report.
Instruments Used:	Refer to section 5.10 for details.
Test Results:	Pass

6.8.1 Radiated emission below 1GHz

30MHz~1GHz (QP)		
Test mode:	Transmitting mode	Vertical



Condition: 47 CFR PART 15.209 3m 3142C Vertical


Job No. : 4373CR

Test mode: TX

	Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dB
1	41.59	0.63	12.40	27.31	43.44	29.16	40.00 -10.84
2	70.75	0.83	6.96	27.25	49.77	30.31	40.00 -9.69
3	177.27	1.37	9.79	26.78	51.98	36.36	43.50 -7.14
4	271.94	1.78	12.74	26.47	47.31	35.36	46.00 -10.64
5	465.99	2.47	17.48	27.54	42.73	35.14	46.00 -10.86
6	637.60	2.78	20.55	27.49	41.90	37.74	46.00 -8.26



Test mode:	Transmitting mode	Horizontal
------------	-------------------	------------



Condition: 47 CFR PART 15.209 3m 3142C Horizontal

Job No. : 4373CR

Test mode: TX

Freq	Cable	Ant	Preamp	Read	Limit	Over	Over	
	Loss	Factor	Factor	Level				
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	34.72	0.60	16.06	27.34	33.47	22.79	40.00	-17.21
2	81.40	1.10	7.84	27.23	45.53	27.24	40.00	-12.76
3	162.85	1.34	9.57	26.85	49.44	33.50	43.50	-10.00
4	247.07	1.66	12.21	26.54	48.44	35.77	46.00	-10.23
5	507.25	2.61	18.00	27.69	43.15	36.07	46.00	-9.93
6	637.60	2.78	20.55	27.49	43.72	39.56	46.00	-6.44

6.8.2 Transmitter emission above 1GHz

Test mode:		802.11b	Test channel:		Lowest	Remark:	Peak	
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3449.984	7.06	32.84	38.72	46.94	48.12	74	-25.88	Vertical
4824.000	6.46	34.72	39.24	46.22	48.16	74	-25.84	Vertical
5980.114	8.05	36.26	39.19	48.49	53.61	74	-20.39	Vertical
7236.000	8.96	35.60	39.06	46.08	51.58	74	-22.42	Vertical
9648.000	9.97	37.45	37.91	43.05	52.56	74	-21.44	Vertical
11877.950	10.56	38.58	38.64	42.02	52.52	74	-21.48	Vertical
3437.643	7.09	32.82	38.71	47.25	48.45	74	-25.55	Horizontal
4824.000	6.46	34.72	39.24	47.74	49.68	74	-24.32	Horizontal
6001.583	8.08	36.30	39.18	47.10	52.30	74	-21.70	Horizontal
7236.000	8.96	35.60	39.06	47.50	53.00	74	-21.00	Horizontal
9648.000	9.97	37.45	37.91	42.43	51.94	74	-22.06	Horizontal
11116.030	10.31	38.11	38.28	41.38	51.52	74	-22.48	Horizontal

Test mode:		802.11b	Test channel:		Middle	Remark:	Peak	
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
3292.950	7.37	32.50	38.65	45.78	47.00	74	-27.00	Vertical
4874.000	6.57	34.77	39.26	47.01	49.09	74	-24.91	Vertical
5958.723	8.02	36.22	39.19	46.53	51.58	74	-22.42	Vertical
7311.000	9.06	35.52	39.06	47.18	52.70	74	-21.30	Vertical
9748.000	9.91	37.76	37.85	41.24	51.06	74	-22.94	Vertical
11116.030	10.31	38.11	38.28	41.38	51.52	74	-22.48	Vertical
3413.093	7.13	32.79	38.70	45.27	46.49	74	-27.51	Horizontal
4874.000	6.57	34.77	39.26	45.63	47.71	74	-26.29	Horizontal
6001.583	8.08	36.30	39.18	47.52	52.72	74	-21.28	Horizontal
7311.000	9.06	35.52	39.06	46.30	51.82	74	-22.18	Horizontal
9748.000	9.91	37.76	37.85	42.26	52.08	74	-21.92	Horizontal
11604.470	10.44	38.30	38.52	40.96	51.18	74	-22.82	Horizontal

Test mode:		802.11b		Test channel:		Highest	Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	
3413.093	7.13	32.79	38.70	45.27	46.49	74	-27.51	Vertical	
4924.000	6.68	34.82	39.28	45.49	47.71	74	-26.29	Vertical	
6001.583	8.08	36.30	39.18	47.52	52.72	74	-21.28	Vertical	
7386.000	9.16	35.44	39.05	45.50	51.05	74	-22.95	Vertical	
9848.000	9.85	38.06	37.79	42.31	52.43	74	-21.57	Vertical	
11877.950	10.56	38.58	38.64	42.36	52.86	74	-21.14	Vertical	
3388.719	7.18	32.75	38.69	46.59	47.83	74	-26.17	Horizontal	
4924.000	6.68	34.82	39.28	46.55	48.77	74	-25.23	Horizontal	
5980.114	8.05	36.26	39.19	46.49	51.61	74	-22.39	Horizontal	
7386.000	9.16	35.44	39.05	46.48	52.03	74	-21.97	Horizontal	
9848.000	9.85	38.06	37.79	42.86	52.98	74	-21.02	Horizontal	
11899.250	10.57	38.60	38.65	41.99	52.51	74	-21.49	Horizontal	

Test mode:		802.11g		Test channel:		Lowest	Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	
3425.346	7.11	32.81	38.71	46.91	48.12	74	-25.88	Vertical	
4824.000	6.46	34.72	39.24	46.44	48.38	74	-25.62	Vertical	
5916.169	7.95	36.14	39.19	48.44	53.34	74	-20.66	Vertical	
7236.000	8.96	35.60	39.06	47.03	52.53	74	-21.47	Vertical	
9648.000	9.97	37.45	37.91	42.67	52.18	74	-21.82	Vertical	
11772.010	10.51	38.47	38.59	41.33	51.72	74	-22.28	Vertical	
3437.643	7.09	32.82	38.71	47.25	48.45	74	-25.55	Horizontal	
4824.000	6.46	34.72	39.24	47.74	49.68	74	-24.32	Horizontal	
5958.723	8.02	36.22	39.19	46.53	51.58	74	-22.42	Horizontal	
7236.000	8.96	35.60	39.06	45.77	51.27	74	-22.73	Horizontal	
9648.000	9.97	37.45	37.91	41.55	51.06	74	-22.94	Horizontal	
11116.030	10.31	38.11	38.28	41.38	51.52	74	-22.48	Horizontal	

Test mode:		802.11g		Test channel:		Middle	Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	
3400.884	7.16	32.78	38.70	46.76	48.00	74	-26.00	Vertical	
4874.000	6.57	34.77	39.26	47.60	49.68	74	-24.32	Vertical	
5852.908	7.85	36.01	39.20	48.43	53.09	74	-20.91	Vertical	
7311.000	9.06	35.52	39.06	47.48	53.00	74	-21.00	Vertical	
9748.000	9.91	37.76	37.85	42.17	51.99	74	-22.01	Vertical	
11096.130	10.30	38.11	38.27	42.32	52.46	74	-21.54	Vertical	
3462.369	7.04	32.85	38.72	45.68	46.85	74	-27.15	Horizontal	
4874.000	6.57	34.77	39.26	45.63	47.71	74	-26.29	Horizontal	
5895.006	7.92	36.10	39.19	46.56	51.39	74	-22.61	Horizontal	
7311.000	9.06	35.52	39.06	46.14	51.66	74	-22.34	Horizontal	
9748.000	9.91	37.76	37.85	41.90	51.72	74	-22.28	Horizontal	
11877.950	10.56	38.58	38.64	42.36	52.86	74	-21.14	Horizontal	

Test mode:		802.11g		Test channel:		Highest	Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	
3388.719	7.18	32.75	38.69	45.17	46.41	74	-27.59	Vertical	
4924.000	6.68	34.82	39.28	45.95	48.17	74	-25.83	Vertical	
6287.786	8.02	35.97	39.15	47.94	52.78	74	-21.22	Vertical	
7386.000	9.16	35.44	39.05	44.48	50.03	74	-23.97	Vertical	
9848.000	9.85	38.06	37.79	40.66	50.78	74	-23.22	Vertical	
11750.940	10.50	38.45	38.58	41.87	52.24	74	-21.76	Vertical	
3449.984	7.06	32.84	38.72	46.94	48.12	74	-25.88	Horizontal	
4924.000	6.68	34.82	39.28	46.47	48.69	74	-25.31	Horizontal	
5916.169	7.95	36.14	39.19	47.44	52.34	74	-21.66	Horizontal	
7386.000	9.16	35.44	39.05	46.48	52.03	74	-21.97	Horizontal	
9848.000	9.85	38.06	37.79	41.06	51.18	74	-22.82	Horizontal	
11877.950	10.56	38.58	38.64	42.02	52.52	74	-21.48	Horizontal	

Test mode:		802.11n(HT20)		Test channel:		Lowest	Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	
3425.346	7.11	32.81	38.71	46.91	48.12	74	-25.88	Vertical	
4824.000	6.46	34.72	39.24	46.22	48.16	74	-25.84	Vertical	
5916.169	7.95	36.14	39.19	48.44	53.34	74	-20.66	Vertical	
7236.000	8.96	35.60	39.06	46.80	52.30	74	-21.70	Vertical	
9648.000	9.97	37.45	37.91	43.47	52.98	74	-21.02	Vertical	
11877.950	10.56	38.58	38.64	42.02	52.52	74	-21.48	Vertical	
3437.643	7.09	32.82	38.71	47.25	48.45	74	-25.55	Horizontal	
4824.000	6.46	34.72	39.24	47.74	49.68	74	-24.32	Horizontal	
5916.169	7.95	36.14	39.19	48.18	53.08	74	-20.92	Horizontal	
7236.000	8.96	35.60	39.06	47.50	53.00	74	-21.00	Horizontal	
9648.000	9.97	37.45	37.91	43.48	52.99	74	-21.01	Horizontal	
11116.030	10.31	38.11	38.28	43.38	53.52	74	-20.48	Horizontal	

Test mode:		802.11n(HT20)		Test channel:		Middle	Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	
3474.799	7.02	32.86	38.73	47.44	48.59	74	-25.41	Vertical	
4874.000	6.57	34.77	39.26	47.35	49.43	74	-24.57	Vertical	
5958.723	8.02	36.22	39.19	48.53	53.58	74	-20.42	Vertical	
7311.000	9.06	35.52	39.06	46.37	51.89	74	-22.11	Vertical	
9748.000	9.91	37.76	37.85	43.17	52.99	74	-21.01	Vertical	
11116.030	10.31	38.11	38.28	43.38	53.52	74	-20.48	Vertical	
3425.346	7.11	32.81	38.71	45.62	46.83	74	-27.17	Horizontal	
4874.000	6.57	34.77	39.26	45.63	47.71	74	-26.29	Horizontal	
5958.723	8.02	36.22	39.19	47.31	52.36	74	-21.64	Horizontal	
7311.000	9.06	35.52	39.06	45.24	50.76	74	-23.24	Horizontal	
9748.000	9.91	37.76	37.85	40.43	50.25	74	-23.75	Horizontal	
11877.950	10.56	38.58	38.64	42.36	52.86	74	-21.14	Horizontal	

Test mode:		802.11n(HT20)		Test channel:		Highest	Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	
3425.346	7.11	32.81	38.71	45.62	46.83	74	-27.17	Vertical	
4924.000	6.68	34.82	39.28	45.95	48.17	74	-25.83	Vertical	
6001.583	8.08	36.30	39.18	47.52	52.72	74	-21.28	Vertical	
7386.000	9.16	35.44	39.05	45.21	50.76	74	-23.24	Vertical	
9848.000	9.85	38.06	37.79	42.31	52.43	74	-21.57	Vertical	
11877.950	10.56	38.58	38.64	42.36	52.86	74	-21.14	Vertical	
3449.984	7.06	32.84	38.72	46.94	48.12	74	-25.88	Horizontal	
4924.000	6.68	34.82	39.28	45.94	48.16	74	-25.84	Horizontal	
5916.169	7.95	36.14	39.19	48.44	53.34	74	-20.66	Horizontal	
7386.000	9.16	35.44	39.05	46.50	52.05	74	-21.95	Horizontal	
9848.000	9.85	38.06	37.79	42.44	52.56	74	-21.44	Horizontal	
11877.950	10.56	38.58	38.64	42.02	52.52	74	-21.48	Horizontal	

Test mode:		802.11n(HT40)		Test channel:		Lowest	Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	
3425.346	7.11	32.81	38.71	46.91	48.12	74	-25.88	Vertical	
4844.000	6.51	34.74	39.25	46.16	48.16	74	-25.84	Vertical	
5916.169	7.95	36.14	39.19	48.44	53.34	74	-20.66	Vertical	
7266.000	9.00	35.57	39.06	46.54	52.05	74	-21.95	Vertical	
9688.000	9.94	37.57	37.88	42.93	52.56	74	-21.44	Vertical	
12071.040	10.72	38.79	38.76	41.97	52.72	74	-21.28	Vertical	
3400.884	7.16	32.78	38.70	46.76	48.00	74	-26.00	Horizontal	
4844.000	6.51	34.74	39.25	47.40	49.40	74	-24.60	Horizontal	
5948.056	8.00	36.20	39.19	47.32	52.33	74	-21.67	Horizontal	
7266.000	9.00	35.57	39.06	46.76	52.27	74	-21.73	Horizontal	
9688.000	9.94	37.57	37.88	43.36	52.99	74	-21.01	Horizontal	
11296.740	10.35	38.13	38.37	42.81	52.92	74	-21.08	Horizontal	

Test mode:		802.11n(HT40)		Test channel:		Middle	Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	
3376.597	7.21	32.72	38.69	46.30	47.54	74	-26.46	Vertical	
4874.000	6.57	34.77	39.26	47.60	49.68	74	-24.32	Vertical	
5990.839	8.07	36.28	39.18	47.72	52.89	74	-21.11	Vertical	
7311.000	9.06	35.52	39.06	46.75	52.27	74	-21.73	Vertical	
9748.000	9.91	37.76	37.85	42.17	51.99	74	-22.01	Vertical	
11276.520	10.34	38.13	38.36	42.21	52.32	74	-21.68	Vertical	
3425.346	7.11	32.81	38.71	45.62	46.83	74	-27.17	Horizontal	
4874.000	6.57	34.77	39.26	46.09	48.17	74	-25.83	Horizontal	
5948.056	8.00	36.20	39.19	46.81	51.82	74	-22.18	Horizontal	
7311.000	9.06	35.52	39.06	45.55	51.07	74	-22.93	Horizontal	
9748.000	9.91	37.76	37.85	41.79	51.61	74	-22.39	Horizontal	
11877.950	10.56	38.58	38.64	42.36	52.86	74	-21.14	Horizontal	

Test mode:		802.11n(HT40)		Test channel:		Highest	Remark:		Peak
Frequency (MHz)	Cable Loss (dB)	Antenna Factor (dB/m)	Preamp Factor (dB)	Read Level (dBuV)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization	
3425.346	7.11	32.81	38.71	45.62	46.83	74	-27.17	Vertical	
4908.000	6.64	34.81	39.27	45.53	47.71	74	-26.29	Vertical	
6001.583	8.08	36.30	39.18	47.52	52.72	74	-21.28	Vertical	
7356.000	9.12	35.47	39.05	44.86	50.40	74	-23.60	Vertical	
9808.000	9.88	37.94	37.81	41.60	51.61	74	-22.39	Vertical	
12049.430	10.69	38.76	38.74	42.34	53.05	74	-20.95	Vertical	
3425.346	7.11	32.81	38.71	46.91	48.12	74	-25.88	Horizontal	
4904.000	6.64	34.81	39.27	47.55	49.73	74	-24.27	Horizontal	
5916.169	7.95	36.14	39.19	48.44	53.34	74	-20.66	Horizontal	
7356.000	9.12	35.47	39.05	46.99	52.53	74	-21.47	Horizontal	
9808.000	9.88	37.94	37.81	42.55	52.56	74	-21.44	Horizontal	
11793.120	10.52	38.49	38.60	41.79	52.20	74	-21.80	Horizontal	

Remark:

- 1) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 2) Scan from 9kHz to 25GHz, The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported .
- 3) As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

6.9 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205		
Test Method:	ANSI C63.10 2013		
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)		
Limit:	Frequency	Limit (dBuV/m @3m)	Remark
	30MHz-88MHz	40.0	Quasi-peak Value
	88MHz-216MHz	43.5	Quasi-peak Value
	216MHz-960MHz	46.0	Quasi-peak Value
	960MHz-1GHz	54.0	Quasi-peak Value
	Above 1GHz	54.0	Average Value
		74.0	Peak Value
Test Setup:			

Figure 1. 30MHz to 1GHz


Figure 2. Above 1 GHz

Test Procedure:	<ol style="list-style-type: none"> a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel g. Test the EUT in the lowest channel , the Highest channel h. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates. Transmitting mode
Final Test Mode:	Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40). Only the worst case is recorded in the report. Pre-scan was performed at Antenna 0 and Antenna 1, no worst case was found. Only the test data of Antenna 0 was shown in this report.
Instruments Used:	Refer to section 5.10 for details.
Test Results:	Pass



Test plot as follows:

Test mode:	802.11b	Test channel:	Lowest	Remark:	Peak	Vertical
------------	---------	---------------	--------	---------	------	----------




Site : chamber
Condition: FCC PART C 247 PK 3m Vertical
Job No: : 4373CR
Mode: : 2412 B Band edge

		Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit	
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1		2390.00	4.90	32.35	38.46	48.84	47.63	74.00	-26.37
2 pp		2413.37	4.93	32.41	38.46	99.01	97.89	74.00	23.89

Test mode:	802.11b	Test channel:	Lowest	Remark:	Peak	Horizontal
------------	---------	---------------	--------	---------	------	------------

Data: 923



Site : chamber

Condition: FCC PART C 247 PK 3m Horizontal


Job No: : 4373CR

Mode: : 2412 B Band edge

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.00	4.90	32.35	38.46	58.65	57.44	74.00	-16.56
2 pp	2413.14	4.93	32.41	38.46	109.53	108.41	74.00	34.41

Test mode:	802.11b	Test channel:	Lowest	Remark:	Average	Vertical
------------	---------	---------------	--------	---------	---------	----------

Data: 926



Site : chamber

Condition: FCC PART C 247 AV 3m Vertical


Job No: : 4373CR

Mode: : 2412 B Band edge

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.00	4.90	32.35	38.46	34.66	33.45	54.00	-20.55
2 pp	2413.26	4.93	32.41	38.46	90.03	88.91	54.00	34.91

Test mode:	802.11b	Test channel:	Lowest	Remark:	Average	Horizontal
------------	---------	---------------	--------	---------	---------	------------

Data: 924



Site : chamber

Condition: FCC PART C 247 AV 3m Horizontal


Job No: : 4373CR

Mode: : 2412 B Band edge

		Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dB
1	pp	2390.00	4.90	32.35	38.46	40.19	38.98	54.00 -15.02
2	pp	2413.26	4.93	32.41	38.46	98.16	97.04	54.00 43.04

Test mode:	802.11b	Test channel:	Highest	Remark:	Peak	Vertical
------------	---------	---------------	---------	---------	------	----------


Data: 927



Site : chamber
Condition: FCC PART C 247 PK 3m Vertical
Job No: : 4373CR
Mode: : 2462 B Band edge

		Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dB
1 pp	2463.31	5.00	32.43	38.46	98.24	97.21	74.00	23.21
2	2483.50	5.03	32.44	38.47	48.39	47.39	74.00	-26.61

Test mode:	802.11b	Test channel:	Highest	Remark:	Peak	Horizontal
------------	---------	---------------	---------	---------	------	------------



Site : chamber

Condition: FCC PART C 247 PK 3m Horizontal


Job No: : 4373CR

Mode: : 2462 B Band edge

		Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dB
1	pp	2463.31	5.00	32.43	38.46	109.70	108.67	74.00 34.67
2		2483.50	5.03	32.44	38.47	59.12	58.12	74.00 -15.88

Test mode:	802.11b	Test channel:	Highest	Remark:	Average	Vertical
------------	---------	---------------	---------	---------	---------	----------

Data: 928



Site : chamber

Condition: FCC PART C 247 AV 3m Vertical


Job No: : 4373CR

Mode: : 2462 B Band edge

		Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Line Level	Over Limit
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dB
1	pp	2463.22	5.00	32.43	38.46	89.30	88.27	54.00
2		2483.50	5.03	32.44	38.47	34.29	33.29	54.00

1 pp 2463.22 5.00 32.43 38.46 89.30 88.27 54.00 34.27
2 2483.50 5.03 32.44 38.47 34.29 33.29 54.00 -20.71

Test mode:	802.11b	Test channel:	Highest	Remark:	Average	Horizontal
------------	---------	---------------	---------	---------	---------	------------



Site : chamber

Condition: FCC PART C 247 AV 3m Horizontal


Job No: : 4373CR

Mode: : 2462 B Band edge

		Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dB
1	pp	2463.22	5.00	32.43	38.46	100.49	99.46	54.00 45.46
2		2483.50	5.03	32.44	38.47	43.57	42.57	54.00 -11.43

Test mode:	802.11g	Test channel:	Lowest	Remark:	Peak	Vertical
------------	---------	---------------	--------	---------	------	----------

Data: 931




Site : chamber
Condition: FCC PART C 247 PK 3m Vertical
Job No: : 4373CR
Mode: : 2422 G Band edge

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.00	4.90	32.35	38.46	57.24	56.03	74.00	-17.97
2 pp	2413.83	4.93	32.42	38.46	98.11	97.00	74.00	23.00

Test mode:	802.11g	Test channel:	Lowest	Remark:	Peak	Horizontal
------------	---------	---------------	--------	---------	------	------------

Data: 933



Site : chamber

Condition: FCC PART C 247 PK 3m Horizontal

Job No: : 4373CR


Mode: : 2422 G Band edge

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
	MHz	dB	dB/m		dBuV	dBuV/m	dBuV/m	dB
1	2390.00	4.90	32.35	38.46	64.70	63.49	74.00	-10.51
2 pp	2413.83	4.93	32.42	38.46	103.42	102.31	74.00	28.31



Test mode:	802.11g	Test channel:	Lowest	Remark:	Average	Vertical
------------	---------	---------------	--------	---------	---------	----------

Data: 932



Site : chamber

Condition: FCC PART C 247 AV 3m Vertical


Job No: : 4373CR

Mode: : 2422 G Band edge

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.00	4.90	32.35	38.46	41.73	40.52	54.00	-13.48
2 pp	2414.89	4.94	32.42	38.46	86.73	85.63	54.00	31.63

Test mode:	802.11g	Test channel:	Lowest	Remark:	Average	Horizontal
------------	---------	---------------	--------	---------	---------	------------

Data: 934



Site : chamber

Condition: FCC PART C 247 AV 3m Horizontal


Job No: : 4373CR

Mode: : 2422 G Band edge

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.00	4.90	32.35	38.46	48.18	46.97	54.00	-7.03
2 pp	2418.65	4.94	32.42	38.46	92.07	90.97	54.00	36.97

Test mode:	802.11g	Test channel:	Highest	Remark:	Peak	Vertical
------------	---------	---------------	---------	---------	------	----------

Data: 945



Site : chamber

Condition: FCC PART C 247 PK 3m Vertical


Job No: : 4373CR

Mode: : 2462 G Band edge

		Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dB
1	pp	2463.85	5.00	32.43	38.46	94.11	93.08	74.00 19.08
2		2483.50	5.03	32.44	38.47	52.44	51.44	74.00 -22.56

Test mode:	802.11g	Test channel:	Highest	Remark:	Peak	Horizontal
------------	---------	---------------	---------	---------	------	------------

Data: 943



Site : chamber

Condition: FCC PART C 247 PK 3m Horizontal


Job No: : 4373CR

Mode: : 2462 G Band edge

		Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dB
1 pp		2463.80	5.00	32.43	38.46	103.17	102.14	74.00 28.14
2		2483.50	5.03	32.44	38.47	61.97	60.97	74.00 -13.03

Test mode:	802.11g	Test channel:	Highest	Remark:	Average	Vertical
------------	---------	---------------	---------	---------	---------	----------

Data: 946



Site : chamber

Condition: FCC PART C 247 AV 3m Vertical


Job No: : 4373CR

Mode: : 2462 G Band edge

		Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dB
1	pp	2468.48	5.01	32.43	38.46	83.00	81.98	54.00 27.98
2		2483.50	5.03	32.44	38.47	37.70	36.70	54.00 -17.30

Test mode:	802.11g	Test channel:	Highest	Remark:	Average	Horizontal
------------	---------	---------------	---------	---------	---------	------------

Data: 944



Site : chamber

Condition: FCC PART C 247 AV 3m Horizontal


Job No: : 4373CR

Mode: : 2462 G Band edge

		Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dB
1 pp	2457.19	4.99	32.43	38.46	91.98	90.94	54.00	36.94
2	2483.50	5.03	32.44	38.47	47.44	46.44	54.00	-7.56

Test mode:	802.11n(HT20)	Test channel:	Lowest	Remark:	Peak	Vertical
------------	---------------	---------------	--------	---------	------	----------

Data: 937




Site : chamber
Condition: FCC PART C 247 PK 3m Vertical
Job No: : 4373CR
Mode: : 2412 N20 Band edge

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.00	4.90	32.35	38.46	56.37	55.16	74.00	-18.84
2 pp	2415.36	4.94	32.42	38.46	94.12	93.02	74.00	19.02

Test mode:	802.11n(HT20)	Test channel:	Lowest	Remark:	Peak	Horizontal
------------	---------------	---------------	--------	---------	------	------------

Data: 935



Site : chamber

Condition: FCC PART C 247 PK 3m Horizontal


Job No: : 4373CR

Mode: : 2412 N20 Band edge

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.00	4.90	32.35	38.46	66.41	65.20	74.00	-8.80
2 pp	2415.36	4.94	32.42	38.46	100.40	99.30	74.00	25.30

Test mode:	802.11n(HT20)	Test channel:	Lowest	Remark:	Average	Vertical
------------	---------------	---------------	--------	---------	---------	----------

Data: 938



Site : chamber

Condition: FCC PART C 247 AV 3m Vertical


Job No: : 4373CR

Mode: : 2412 N20 Band edge

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.00	4.90	32.35	38.46	40.85	39.64	54.00	-14.36
2 pp	2415.12	4.94	32.42	38.46	84.33	83.23	54.00	29.23

Test mode:	802.11n(HT20)	Test channel:	Lowest	Remark:	Average	Horizontal
------------	---------------	---------------	--------	---------	---------	------------

Data: 936



Site : chamber

Condition: FCC PART C 247 AV 3m Horizontal


Job No: : 4373CR

Mode: : 2412 N20 Band edge

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.00	4.90	32.35	38.46	48.30	47.09	54.00	-6.91
2 pp	2414.89	4.94	32.42	38.46	90.44	89.34	54.00	35.34



Test mode:	802.11n(HT20)	Test channel:	Highest	Remark:	Peak	Vertical
------------	---------------	---------------	---------	---------	------	----------




Site : chamber
Condition: FCC PART C 247 PK 3m Vertical
Job No: : 4373CR
Mode: : 2462 N20 Band edge

	Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dB
1 pp	2456.64	4.99	32.43	38.46	91.37	90.33	74.00 16.33
2	2483.50	5.03	32.44	38.47	57.04	56.04	74.00 -17.96

Test mode:	802.11n(HT20)	Test channel:	Highest	Remark:	Peak	Horizontal
------------	---------------	---------------	---------	---------	------	------------

Data: 942



Site : chamber

Condition: FCC PART C 247 PK 3m Horizontal


Job No: : 4373CR

Mode: : 2462 N20 Band edge

		Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit	
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	pp	2456.64	4.99	32.43	38.46	99.87	98.83	74.00	24.83
2		2483.50	5.03	32.44	38.47	62.53	61.53	74.00	-12.47

Test mode:	802.11n(HT20)	Test channel:	Highest	Remark:	Average	Vertical
------------	---------------	---------------	---------	---------	---------	----------

Data: 940




Site : chamber
Condition: FCC PART C 247 AV 3m Vertical
Job No: : 4373CR
Mode: : 2462 N20 Band edge

		Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Line dBuV/m	Over Limit
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dB
1 pp	2456.10	4.99	32.43	38.46	81.68	80.64	54.00	26.64
2	2483.50	5.03	32.44	38.47	37.87	36.87	54.00	-17.13

Test mode:	802.11n(HT20)	Test channel:	Highest	Remark:	Average	Horizontal
------------	---------------	---------------	---------	---------	---------	------------

Data: 941



Site : chamber


Condition: FCC PART C 247 AV 3m Horizontal

Job No: : 4373CR

Mode: : 2462 N20 Band edge

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 pp	2456.69	4.99	32.43	38.46	90.03	88.99	54.00	34.99
2	2483.50	5.03	32.44	38.47	46.59	45.59	54.00	-8.41

Test mode:	802.11n(HT40)	Test channel:	Lowest	Remark:	Peak	Vertical
------------	---------------	---------------	--------	---------	------	----------




Site : chamber
Condition: FCC PART C 247 PK 3m Vertical
Job No: : 4373CR
Mode: : 2422 N40 Band edge

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.00	4.90	32.35	38.46	57.87	56.66	74.00	-17.34
2 pp	2415.79	4.94	32.42	38.46	90.33	89.23	74.00	15.23

Test mode:	802.11n(HT40)	Test channel:	Lowest	Remark:	Peak	Horizontal
------------	---------------	---------------	--------	---------	------	------------

Data: 983



Site : chamber

Condition: FCC PART C 247 PK 3m Horizontal


Job No: : 4373CR

Mode: : 2422 N40 Band edge

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.00	4.90	32.35	38.46	66.22	65.01	74.00	-8.99
2 pp	2415.79	4.94	32.42	38.46	96.51	95.41	74.00	21.41

Test mode:	802.11n(HT40)	Test channel:	Lowest	Remark:	Average	Vertical
------------	---------------	---------------	--------	---------	---------	----------

Data: 986




Site : chamber
Condition: FCC PART C 247 AV 3m Vertical
Job No: : 4373CR
Mode: : 2422 N40 Band edge

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Limit Line	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2390.00	4.90	32.35	38.46	42.47	41.26	54.00	-12.74
2 pp	2415.79	4.94	32.42	38.46	81.17	80.07	54.00	26.07

Test mode:	802.11n(HT40)	Test channel:	Lowest	Remark:	Average	Horizontal
------------	---------------	---------------	--------	---------	---------	------------

Data: 984



Site : chamber

Condition: FCC PART C 247 AV 3m Horizontal


Job No: : 4373CR

Mode: : 2422 N40 Band edge

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	2388.93	4.90	32.34	38.46	49.37	48.15	54.00	-5.85
2	2390.00	4.90	32.35	38.46	47.87	46.66	54.00	-7.34
3 pp	2423.19	4.95	32.42	38.46	87.50	86.41	54.00	32.41

Test mode:	802.11n(HT40)	Test channel:	Highest	Remark:	Peak	Vertical
------------	---------------	---------------	---------	---------	------	----------

Data: 979



Site : chamber

Condition: FCC PART C 247 PK 3m Vertical


Job No: : 4373CR

Mode: : 2452 N40 Band edge

		Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Line Level	Over Limit
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dB
1	pp	2447.48	4.98	32.43	38.46	85.77	84.72	74.00 10.72
2		2483.50	5.03	32.44	38.47	61.47	60.47	74.00 -13.53

Test mode:	802.11n(HT40)	Test channel:	Highest	Remark:	Peak	Horizontal
------------	---------------	---------------	---------	---------	------	------------

Data: 981



Site : chamber

Condition: FCC PART C 247 PK 3m Horizontal

Job No: : 4373CR


Mode: : 2452 N40 Band edge

		Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Line Level	Line Level	Over Limit
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	pp	2476.97	5.02	32.44	38.47	94.32	93.31	74.00	19.31
2		2483.50	5.03	32.44	38.47	71.70	70.70	74.00	-3.30



Test mode:	802.11n(HT40)	Test channel:	Highest	Remark:	Average	Vertical
------------	---------------	---------------	---------	---------	---------	----------

Data: 980




Site : chamber
Condition: FCC PART C 247 AV 3m Vertical
Job No: : 4373CR
Mode: : 2452 N40 Band edge

		Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Line dBuV/m	Over Limit
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dB
1 pp		2455.70	4.99	32.43	38.46	80.43	79.39	54.00 25.39
2		2483.50	5.03	32.44	38.47	49.28	48.28	54.00 -5.72

Test mode:	802.11n(HT40)	Test channel:	Highest	Remark:	Average	Horizontal
------------	---------------	---------------	---------	---------	---------	------------

Data: 982



Site : chamber

Condition: FCC PART C 247 AV 3m Horizontal

Job No: : 4373CR

Mode: : 2452 N40 Band edge

		Cable Freq	Ant Loss	Preamp Factor	Read Level	Limit Level	Line Limit	Over Limit
		MHz	dB	dB/m	dB	dBuV	dBuV/m	dB
1	pp	2455.70	4.99	32.43	38.46	88.29	87.25	54.00
2		2483.50	5.03	32.44	38.47	51.24	50.24	54.00

33.25
-3.76

Note:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor


7 Photographs - EUT Test Setup


Test model No.: OMNI S6

7.1 Conducted Emission



7.2 Radiated Spurious Emission





8 Photographs - EUT Constructional Details

Refer to Appendix A - Photographs of EUT Constructional Details for SZEM1507004373CR.