

RF Exposure Report

Report No.: SA140729D01A-2

FCC ID: WLQOMNISB1PLUSTX

Test Model: Omni SB1 Plus Soundbar

Received Date: Dec. 10, 2015

Test Date: Dec. 14 ~ 21, 2015

Issued Date: Dec. 22, 2015

Applicant: Polk Audio

Address: 5601 Metro Drive Baltimore Maryland 21215 United States

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

(R.O.C.)





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Report No.: SA140729D01A-2 Page No. 1 / 6 Report Format Version: 6.1.1

Reference No.: 140729D01, 151210D10



Table of Contents

R	≀elea	se Control Record	. 3
1		Certificate of Conformity	. 4
2	2	RF Exposure	. 5
	2.2	Limits For Maximum Permissible Exposure (MPE)	. 5
3	}	Calculation Result Of Maximum Conducted Power	. 6



Release Control Record

Issue No.	Description	Date Issued
SA140729D01A-2	Original release.	Dec. 22, 2015

Report No.: SA140729D01A-2 Page No. 3 / 6 Report Format Version: 6.1.1

Report No.: SA140729D01A-2 Reference No.: 140729D01, 151210D10



1 Certificate of Conformity

Product: Soundbar

Brand:



Test Model: Omni SB1 Plus Soundbar

Sample Status: Engineering sample

Applicant: Polk Audio

Test Date: Dec. 14 ~ 21, 2015

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D03 KDB 447498 D01

IEEE C95.1

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by: Annie Chang, Date: Dec. 22, 2015

Annie Chang / Senior Specialist

Approved by: , Date: Dec. 22, 2015

Rex Lai / Assistant Manager

Report No.: SA140729D01A-2 Reference No.: 140729D01, 151210D10



2 RF Exposure

2.1 Limits For Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)	
Limits For General Population / Uncontrolled Exposure					
300-1500			F/1500	30	
1500-100,000			1.0	30	

F = Frequency in MHz

2.2 MPE Calculation Formula

 $Pd = (Pout*G) / (4*pi*r^2)$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

Report No.: SA140729D01A-2 Reference No.: 140729D01, 151210D10



3 Calculation Result Of Maximum Conducted Power

Function	Frequency Band (MHz)	Max Power (dBm)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm²)
Audio WIFI	2403.5~ 2477.3	5.54	1.82	20	0.0011	1
	2412 ~ 2462	22.45	2.43	20	0.0612	1
	5180 ~ 5240	13.42	2.04	20	0.0070	1
WLAN	5260 ~ 5320	13.09	2.04	20	0.0065	1
	5500 ~ 5700	13.04	2.04	20	0.0064	1
	5745 ~ 5825	13.18	2.04	20	0.0066	1

CONCULSION:

Both of the modules can transmit simultaneously, the formula of calculated the MPE is:

CPD1 / LPD1 + CPD2 / LPD2 +etc. < 1

CPD = Calculation power density

LPD = Limit of power density

1. Audio WIFI + WLAN = 0.0011 / 1 + 0.0612 / 1 = 0.0623

FREQUENCY BAND (MHz)	MAX POWER (dBm)			TOTAL POWER	POWER LIMIT (dBm)
	Audio WIFI	WIFI (5.0G)	WIFI (2.4G)	(dBm)	(3.2)
2400 ~ 2483.5	5.54	•	22.45	22.54	30
5180 ~ 5240	ı	13.42	-	13.42	24
5260 ~ 5320	ı	13.09	-	13.09	24
5500 ~ 5700	-	13.04	-	13.04	24
5745 ~ 5825	-	13.18	-	13.18	30

--- END ---