

FCC TEST REPORT

REPORT NO.: RF140729D01-1

MODEL NO.: OMNI SB1 SOUNDBAR

FCC ID: WLQPKOMNISB1IHTTX

RECEIVED: Jul. 29, 2014

TESTED: Aug. 14 ~ Sep. 11, 2014

ISSUED: Sep. 25, 2014

APPLICANT: Polk Audio

ADDRESS: 5601 Metro Drive Baltimore Maryland 21215 United

States

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.)

Ltd., Taoyuan Branch

LAB ADDRESS: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New

Taipei City, Taiwan (R.O.C.)

This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.





This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.



TABLE OF CONTENTS

RELE	ASE CONTROL RECORD	4
1.	CERTIFICATION	
2.	SUMMARY OF TEST RESULTS	6
2.1	MEASUREMENT UNCERTAINTY	6
3.	GENERAL INFORMATION	7
3.1	GENERAL DESCRIPTION OF EUT	7
3.2	DESCRIPTION OF TEST MODES	8
3.2.1	TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL	9
3.3	DESCRIPTION OF SUPPORT UNITS	11
3.3.1	CONFIGURATION OF SYSTEM UNDER TEST	11
3.4	GENERAL DESCRIPTION OF APPLIED STANDARDS	12
4.	TEST TYPES AND RESULTS	13
4.1	RADIATED EMISSION AND BANDEDGE MEASUREMENT	13
4.1.1	LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT	13
4.1.2	TEST INSTRUMENTS	14
4.1.3	TEST PROCEDURES	15
4.1.4	DEVIATION FROM TEST STANDARD	15
4.1.5	TEST SETUP	16
4.1.6	EUT OPERATING CONDITIONS	
4.1.7	TEST RESULTS	17
4.2	CONDUCTED EMISSION MEASUREMENT	21
4.2.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	21
4.2.2	TEST INSTRUMENTS	21
4.2.3	TEST PROCEDURES	22
4.2.4	DEVIATION FROM TEST STANDARD	22
4.2.5	TEST SETUP	22
4.2.6	EUT OPERATING CONDITIONS	22
4.2.7	TEST RESULTS	23
4.3	6DB BANDWIDTH MEASUREMENT	25
4.3.1	LIMITS OF 6DB BANDWIDTH MEASUREMENT	25
4.3.2	TEST SETUP	25
4.3.3	TEST INSTRUMENTS	25
4.3.4	TEST PROCEDURE	25
4.3.5	DEVIATION FROM TEST STANDARD	25
4.3.6	EUT OPERATING CONDITIONS	25
4.3.7	TEST RESULTS	26
4.4	CONDUCTED OUTPUT POWER	27



4.4.1	LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT	.27
4.4.2	TEST SETUP	.27
4.4.3	TEST INSTRUMENTS	.27
4.4.4	TEST PROCEDURES	.27
4.4.5	DEVIATION FROM TEST STANDARD	.27
4.4.6	EUT OPERATING CONDITIONS	.27
4.4.7	TEST RESULTS	.28
4.5	POWER SPECTRAL DENSITY MEASUREMENT	.29
4.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	.29
4.5.2	TEST SETUP	.29
4.5.3	TEST INSTRUMENTS	.29
4.5.4	TEST PROCEDURE	.29
4.5.5	DEVIATION FROM TEST STANDARD	.29
4.5.6	EUT OPERATING CONDITION	.29
4.5.7	TEST RESULTS	.30
4.6	CONDUCTED OUT OF BAND EMISSION MEASUREMENT	.31
4.6.1	LIMITS OF CONDUCTED OUT OF BAND EMISSION MEASUREMENT	.31
4.6.2	TEST SETUP	.31
4.6.3	TEST INSTRUMENTS	.31
4.6.4	TEST PROCEDURE	.31
4.6.5	DEVIATION FROM TEST STANDARD	.32
4.6.6	EUT OPERATING CONDITION	.32
4.6.7	TEST RESULTS	.32
5.	PHOTOGRAPHS OF THE TEST CONFIGURATION	.34
6.	INFORMATION ON THE TESTING LABORATORIES	.35
7.	APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES	3
	TO THE EUT BY THE LAB	.36



RELEASE CONTROL RECORD

ISSUE NO.	O. REASON FOR CHANGE	
RF140729D01-1	Original release	Sep. 25, 2014

Report No.: RF140729D01-1 4 of 36 Report Format Version 5.2.0



1. CERTIFICATION

PRODUCT: Soundbar

BRAND NAME:



MODEL NO.: OMNI SB1 SOUNDBAR

APPLICANT: Polk Audio

TESTED: Aug. 14 ~ Sep. 11, 2014

TEST SAMPLE: ENGINEERING SAMPLE

STANDARDS: FCC Part 15, Subpart C (Section 15.247)

ANSI C63.10-2009

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch,** and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY: , DATE: Sep. 25, 2014

(Jessica Cheng / Senior Specialist)

APPROVED BY: , **DATE**: Sep. 25, 2014

(Rex Lai / Assistant Manager)



2. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)						
STANDARD SECTION TEST TYPE		RESULT	REMARK			
15.207	15.207 AC Power Conducted Emission Page 15.207		Meet the requirement of limit. Minimum passing margin is -24.16dB at 0.15000MHz.			
15.205 & Radiated Emissions		PASS	Meet the requirement of limit. Minimum passing margin is -3.1dB at 7431.90MHz.			
15.247(d)	15.247(d) Band Edge Measurement		Meet the requirement of limit. Minimum passing margin is -10.2dB at 2400.0MHz.			
15.247(d)	15.247(d) Antenna Port Emission		Meet the requirement of limit.			
15.247(a)(2) 6dB bandwidth		PASS	Meet the requirement of limit.			
15.247(b)	Conducted power	PASS	Meet the requirement of limit.			
15.247(e)	Power Spectral Density	PASS	Meet the requirement of limit.			
15.203 Antenna Requirement		PASS	No antenna connector is used.			

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Uncertainty
Conducted emissions	150kHz~30MHz	3.43 dB
Radiated emissions	30MHz ~ 1GHz	4.00 dB
	Above 1GHz	3.36 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k = 2.



3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

EUT	Soundbar	
MODEL NO.	OMNI SB1 SOUNDBAR	
POWER SUPPLY	24Vdc from AC Adapter	
MODULATION TYPE	FSK	
TRANSFER RATE	2Mbps	
OPERATING FREQUENCY	2403.5~ 2477.3MHz	
NUMBER OF CHANNEL	49	
OUTPUT POWER	3.6mW	
ANTENNA TYPE	Printed antenna with 1.82dBi gain	
ANTENNA CONNECTOR	N/A	
DATA CABLE	Refer to user's manual	
I/O PORTS	Refer to user's manual	
ACCESSORY DEVICES	Refer to note as below	

NOTE:

- 1. The EUT is a Soundbar.
- 2. The EUT consumes power from an AC adapter as follows:

Brand	Model No.	Spec.
		AC I/P: 100-240Vac, 50/60Hz, 1.5A Max.
polk	DYS602-240250W	DC O/P: 24Vdc, 2.5A
рок		Non-shielded AC cable (1.8m) 2 Pin
		Non-shielded DC cable with one core (1.8m)

3. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.



3.2 DESCRIPTION OF TEST MODES

49 channels are provided to this EUT:

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2403.5 MHz	26	2442.0 MHz
2	2405.1 MHz	27	2443.5 MHz
3	2406.6 MHz	28	2445.0 MHz
4	2408.1 MHz	29	2446.6 MHz
5	2409.7 MHz	30	2448.1 MHz
6	2411.2 MHz	31	2449.6 MHz
7	2412.8 MHz	32	2451.2 MHz
8	2414.3 MHz	33	2452.7 MHz
9	2415.8 MHz	34	2454.3 MHz
10	2417.4 MHz	35	2455.8 MHz
11	2418.9 MHz	36	2457.3 MHz
12	2420.4 MHz	37	2458.9 MHz
13	2422.0 MHz	38	2460.4 MHz
14	2423.5 MHz	39	2461.9 MHz
15	2425.1 MHz	40	2463.5 MHz
16	2426.6 MHz	41	2465.0 MHz
17	2428.1 MHz	42	2466.6 MHz
18	2429.7 MHz	43	2468.1 MHz
19	2431.2 MHz	44	2469.6 MHz
20	2432.7 MHz	45	2471.2 MHz
21	2434.3 MHz	46	2472.7 MHz
22	2435.8 MHz	47	2474.2 MHz
23	2437.4 MHz	48	2475.8 MHz
24	2438.9 MHz	49	2477.3 MHz
25	2440.4 MHz		



3.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE		APPLICA	ABLE TO	DESCRIPTION	
MODE	RE ³ 1G	RE<1G	PLC	APCM	DESCRIPTION
-	V	\checkmark	\checkmark	\checkmark	-

Where **RE**³**1G**: Radiated Emission above 1GHz

RE<1G: Radiated Emission below 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

RADIATED EMISSION TEST (ABOVE 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE AVAILABLE MODE CHANNEL		TESTED CHANNEL	MODULATION TYPE
-	1 to 49	1, 25, 49	FSK

RADIATED EMISSION TEST (BELOW 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE AVAILABLE MODE CHANNEL		TESTED CHANNEL	MODULATION TYPE
-	1 to 49	25	FSK

POWER LINE CONDUCTED EMISSION TEST:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE AVAILABLE		TESTED	MODULATION
MODE CHANNEL		CHANNEL	TYPE
-	1 to 49	25	FSK



BANDEDGE MEASUREMENT:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	EUT CONFIGURE AVAILABLE MODE CHANNEL		MODULATION TYPE	
-	1 to 49	1, 49	FSK	

ANTENNA PORT CONDUCTED MEASUREMENT:

This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE			MODULATION TYPE	
-	1 to 49	1,25, 49	FSK	


TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE ³ 1G	27deg. C, 69% RH	120Vac / 60Hz	Aaron You
RE<1G	27deg. C, 69% RH	120Vac / 60Hz	Aaron You
PLC	25deg. C, 73% RH	120Vac / 60Hz	Dalen Dai
APCM	20deg. C, 70%RH	120Vac / 60Hz	Saxon Lee



3.3 DUTY CYCLE OF TEST SIGNAL


Duty cycle of test signal is 100 %



3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together without other necessary accessories or support units.

3.4.1 CONFIGURATION OF SYSTEM UNDER TEST





3.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.247) 558074 D01 DTS Meas Guidance v03r02

ANSI C63.10-2009

All test items have been performed and recorded as per the above standards.



4. TEST TYPES AND RESULTS

4.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT

4.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

- 1. The lower limit shall apply at the transition frequencies.
- 2. Emission level $(dBuV/m) = 20 \log Emission level (uV/m)$.
- 3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
HP Preamplifier	8447D	2432A03504	Feb. 26, 2014	Feb. 25, 2015
HP Preamplifier	8449B	3008A01201	Feb. 26, 2014	Feb. 25, 2015
Agilent TEST RECEIVER	N9038A	MY51210129	Jan. 18, 2014	Jan. 17, 2015
Schwarzbeck Antenna	VULB 9168	139	Feb. 24, 2014	Feb. 23, 2015
Schwarzbeck Antenna	VHBA 9123	480	May 29, 2013	May 28, 2015
ADT. Turn Table	TT100	0306	NA	NA
ADT. Tower	AT100	0306	NA	NA
Software	ADT_Radiated_V 7.6.15.9.4	NA	NA	NA
SUHNER RF cable	SF104	CABLE-CH6	Aug. 15, 2014	Aug. 14, 2015
EMCO Horn Antenna	3115	00028257	Sep. 27, 2013	Sep. 26, 2014
Highpass filter Wainwright Instruments	WHK 3.1/18G-10SS	SN 8	NA	NA
ROHDE & SCHWARZ Spectrum Analyzer	FSP 40	100036	May 17, 2014	May 16, 2015
Anritsu Power Sensor	MA2411B	0738404	Apr. 21, 2014	Apr. 20, 2015
Anritsu Power Meter	ML2495A	0842014	Apr. 21, 2014	Apr. 20, 2015

NOTE: 1. The calibration interval of the above test instruments is 12/24 months. And the calibrations are traceable to NML/ROC and NIST/USA.

- 2. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
- 3. The test was performed in Chamber No. 6.
- 4. The Industry Canada Reference No. IC 7450E-6.
- 5. The FCC Site Registration No. is 447212.



4.1.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meters semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE:


- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
- 3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is ≥ 1/T(Duty cycle < 98%) or 10Hz(Duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.
- 4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 DEVIATION FROM TEST STANDARD


No deviation.



4.1.5 TEST SETUP



Frequency range above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

- a. Turn on the power of all equipment.
- b. Set the EUT under transmitting condition.



4.1.7 TEST RESULTS

ABOVE 1GHz DATA

CHANNEL	TX Channel 1	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz	FUNCTION	Average (AV)

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M							
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	52.0 PK	74.0	-22.0	1.10 H	185	55.62	-3.58
2	2390.00	39.1 AV	54.0	-14.9	1.10 H	185	42.65	-3.58
3	2400.00	52.7 PK	74.0	-21.3	1.10 H	185	56.23	-3.54
4	2400.00	43.3 AV	54.0	-10.7	1.10 H	185	46.88	-3.54
5	*2403.50	84.5 PK			1.10 H	185	88.03	-3.53
6	*2403.50	83.3 AV			1.10 H	185	86.83	-3.53
7	4807.00	51.9 PK	74.0	-22.1	1.00 H	146	47.97	3.93
8	4807.00	44.5 AV	54.0	-9.5	1.00 H	146	40.53	3.93
9	7210.50	53.0 PK	74.0	-21.0	1.46 H	134	44.04	8.93
10	7210.50	41.1 AV	54.0	-13.0	1.46 H	134	32.12	8.93
11	9614.00	58.6 PK	74.0	-15.4	1.36 H	192	46.58	12.01
12	9614.00	47.7 AV	54.0	-6.3	1.36 H	192	35.73	12.01
		ANTENNA	A POLARITY	/ & TEST DI	STANCE: V	ERTICAL A	T 3 M	
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	52.9 PK	74.0	-21.2	1.06 V	275	56.43	-3.58
2	2390.00	39.3 AV	54.0	-14.7	1.06 V	275	42.89	-3.58
3	2400.00	54.8 PK	74.0	-19.2	1.06 V	275	58.31	-3.54
4	2400.00	43.8 AV	54.0	-10.2	1.06 V	275	47.32	-3.54
5	*2403.50	88.1 PK			1.06 V	275	91.58	-3.53
6	*2403.50	86.8 AV			1.06 V	275	90.31	-3.53
7	4807.00	53.1 PK	74.0	-20.9	1.11 V	206	49.16	3.93
8	4807.00	45.5 AV	54.0	-8.5	1.11 V	206	41.59	3.93
9	7210.50	53.1 PK	74.0	-21.0	1.29 V	230	44.12	8.93
10	7210.50	41.3 AV	54.0	-12.7	1.29 V	230	32.39	8.93
11	9614.00	58.7 PK	74.0	-15.3	1.26 V	78	46.68	12.01
12	9614.00	47.9 AV	54.0	-6.1	1.26 V	78	35.91	12.01

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) Pre-Amplifier Factor(dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission Level Limit value
- 5. " * ": Fundamental frequency.



CHANNEL	TX Channel 25	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz	FUNCTION	Average (AV)

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)	
1	*2440.40	86.6 PK			1.08 H	185	90.06	-3.42	
2	*2440.40	85.4 AV			1.08 H	185	88.84	-3.42	
3	4880.80	56.5 PK	74.0	-17.5	1.00 H	145	52.17	4.30	
4	4880.80	49.6 AV	54.0	-4.4	1.00 H	145	45.30	4.30	
5	7321.20	56.8 PK	74.0	-17.2	1.36 H	136	47.38	9.46	
6	7321.20	47.3 AV	54.0	-6.7	1.36 H	136	37.87	9.46	
7	9761.60	59.9 PK	74.0	-14.1	1.30 H	190	47.72	12.16	
8	9761.60	50.3 AV	54.0	-3.7	1.30 H	190	38.14	12.16	
		ANTENNA	A POLARITY	/ & TEST DI	STANCE: V	ERTICAL A	T 3 M		
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)	
1	*2440.40	87.9 PK			1.03 V	278	91.27	-3.42	
2	*2440.40	87.5 AV			1.03 V	278	90.96	-3.42	
3	4880.80	56.9 PK	74.0	-17.1	1.03 V	168	52.58	4.30	
4	4880.80	50.7 AV	54.0	-3.3	1.03 V	168	46.36	4.30	
5	7321.20	59.6 PK	74.0	-14.4	1.33 V	148	50.12	9.46	
6	7321.20	50.1 AV	54.0	-3.9	1.33 V	148	40.63	9.46	
7	9761.60	59.9 PK	74.0	-14.1	1.31 V	80	47.78	12.16	
8	9761.60	50.4 AV	54.0	-3.6	1.31 V	80	38.26	12.16	

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) Pre-Amplifier Factor(dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission Level Limit value
- 5. " * ": Fundamental frequency.



CHANNEL	TX Channel 49	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz	FUNCTION	Average (AV)

	ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)	
1	*2477.30	85.5 PK			1.06 H	186	88.85	-3.31	
2	*2477.30	84.4 AV			1.06 H	186	87.68	-3.31	
3	2483.50	52.3 PK	74.0	-21.7	1.06 H	186	55.63	-3.30	
4	2483.50	38.7 AV	54.0	-15.4	1.06 H	186	41.95	-3.30	
5	4954.60	54.1 PK	74.0	-19.9	1.00 H	147	49.59	4.52	
6	4954.60	47.4 AV	54.0	-6.6	1.00 H	147	42.91	4.52	
7	7431.90	59.1 PK	74.0	-14.9	1.51 H	134	49.64	9.46	
8	7431.90	50.4 AV	54.0	-3.6	1.51 H	134	40.98	9.46	
9	9909.20	60.4 PK	74.0	-13.7	1.33 H	188	48.31	12.04	
10	9909.20	50.3 AV	54.0	-3.7	1.33 H	188	38.29	12.04	
	ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
		AN I CINNA	A PULAKII	A IESI DI	STANCE: V	ERTICAL A	1 3 IVI		
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)	
NO .		EMISSION LEVEL	LIMIT	MARGIN	ANTENNA HEIGHT	TABLE ANGLE	RAW VALUE	FACTOR	
	(MHz)	EMISSION LEVEL (dBuV/m)	LIMIT	MARGIN	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	FACTOR (dB/m)	
1	(MHz) *2477.30	EMISSION LEVEL (dBuV/m) 87.3 PK	LIMIT	MARGIN	ANTENNA HEIGHT (m) 1.02 V	TABLE ANGLE (Degree)	RAW VALUE (dBuV) 90.56	FACTOR (dB/m) -3.31	
1 2	(MHz) *2477.30 *2477.30	EMISSION LEVEL (dBuV/m) 87.3 PK 86.0 AV	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m) 1.02 V 1.02 V	TABLE ANGLE (Degree) 278 278	RAW VALUE (dBuV) 90.56 89.31	FACTOR (dB/m) -3.31 -3.31	
1 2 3	*2477.30 *2477.30 2483.50	EMISSION LEVEL (dBuV/m) 87.3 PK 86.0 AV 52.9 PK	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m) 1.02 V 1.02 V 1.02 V	TABLE ANGLE (Degree) 278 278 278	RAW VALUE (dBuV) 90.56 89.31 56.19	FACTOR (dB/m) -3.31 -3.31 -3.30	
1 2 3 4	*2477.30 *2477.30 2483.50 2483.50	EMISSION LEVEL (dBuV/m) 87.3 PK 86.0 AV 52.9 PK 39.1 AV	LIMIT (dBuV/m) 74.0 54.0	MARGIN (dB) -21.1 -14.9	ANTENNA HEIGHT (m) 1.02 V 1.02 V 1.02 V	TABLE ANGLE (Degree) 278 278 278 278	RAW VALUE (dBuV) 90.56 89.31 56.19 42.41	FACTOR (dB/m) -3.31 -3.31 -3.30 -3.30	
1 2 3 4 5	*2477.30 *2477.30 2483.50 2483.50 4954.60	EMISSION LEVEL (dBuV/m) 87.3 PK 86.0 AV 52.9 PK 39.1 AV 55.1 PK	LIMIT (dBuV/m) 74.0 54.0 74.0	-21.1 -14.9 -18.9	ANTENNA HEIGHT (m) 1.02 V 1.02 V 1.02 V 1.02 V 1.28 V	TABLE ANGLE (Degree) 278 278 278 278 278	RAW VALUE (dBuV) 90.56 89.31 56.19 42.41 50.57	FACTOR (dB/m) -3.31 -3.31 -3.30 -3.30 4.52	
1 2 3 4 5 6	*2477.30 *2477.30 2483.50 2483.50 4954.60 4954.60	EMISSION LEVEL (dBuV/m) 87.3 PK 86.0 AV 52.9 PK 39.1 AV 55.1 PK 48.2 AV	LIMIT (dBuV/m) 74.0 54.0 74.0 54.0 54.0	-21.1 -14.9 -18.9 -5.8	ANTENNA HEIGHT (m) 1.02 V 1.02 V 1.02 V 1.02 V 1.28 V	TABLE ANGLE (Degree) 278 278 278 278 168	RAW VALUE (dBuV) 90.56 89.31 56.19 42.41 50.57 43.72	FACTOR (dB/m) -3.31 -3.31 -3.30 -3.30 -3.30 4.52 4.52	
1 2 3 4 5 6 7	*2477.30 *2477.30 2483.50 2483.50 4954.60 4954.60 7431.90	EMISSION LEVEL (dBuV/m) 87.3 PK 86.0 AV 52.9 PK 39.1 AV 55.1 PK 48.2 AV 59.6 PK	74.0 54.0 74.0 54.0 74.0	-21.1 -14.9 -18.9 -5.8 -14.4	ANTENNA HEIGHT (m) 1.02 V 1.02 V 1.02 V 1.02 V 1.28 V 1.28 V	TABLE ANGLE (Degree) 278 278 278 278 168 168	RAW VALUE (dBuV) 90.56 89.31 56.19 42.41 50.57 43.72 50.17	FACTOR (dB/m) -3.31 -3.31 -3.30 -3.30 4.52 4.52 9.46	

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) Pre-Amplifier Factor(dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission Level Limit value
- 5. " * ": Fundamental frequency.



BELOW 1GHz WORST-CASE

CHANNEL	TX Channel 25	DETECTOR	Oversi Bask (OD)
FREQUENCY RANGE	30MHz ~ 1GHz	FUNCTION	Quasi-Peak (QP)

		ANTENNA	POLARITY	& TEST DIS	TANCE: HO	RIZONTAL	AT 3 M	
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	101.39	34.5 QP	43.5	-9.0	2.21 H	3	52.42	-17.88
2	144.42	39.3 QP	43.5	-4.2	2.00 H	195	53.09	-13.81
3	213.97	38.9 QP	43.5	-4.6	1.50 H	218	54.81	-15.94
4	294.91	36.9 QP	46.0	-9.1	1.37 H	230	49.10	-12.24
5	478.23	36.0 QP	46.0	-10.0	2.03 H	182	44.79	-8.76
6	638.04	40.9 QP	46.0	-5.2	1.15 H	352	46.50	-5.65
7	717.78	41.1 QP	46.0	-4.9	1.00 H	144	45.75	-4.63
		ANTENNA	A POLARITY	/ & TEST DI	STANCE: V	ERTICAL A	T 3 M	
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	41.59	33.5 QP	40.0	-6.5	1.32 V	360	47.73	-14.26
2	142.08	36.3 QP	43.5	-7.2	1.00 V	298	50.34	-14.08
3	209.31	35.6 QP	43.5	-7.9	1.00 V	107	51.59	-16.02
4	238.56	33.7 QP	46.0	-12.3	1.24 V	283	48.44	-14.71
5	380.22	32.1 QP	46.0	-13.9	1.69 V	126	42.63	-10.53
6	498.36	33.2 QP	46.0	-12.8	2.24 V	273	41.52	-8.36
7	682.23	34.6 QP	46.0	-11.4	2.73 V	236	39.64	-5.08
8	761.87	33.6 QP	46.0	-12.4	1.97 V	74	37.10	-3.46

- 1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- 2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) Pre-Amplifier Factor(dB)
- 3. The other emission levels were very low against the limit.
- 4. Margin value = Emission Level Limit value



4.2 CONDUCTED EMISSION MEASUREMENT

4.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBµV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

NOTE: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2.2 TEST INSTRUMENTS

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
ROHDE & SCHWARZ TEST RECEIVER	ESCS 30	100292	Dec. 16, 2013	Dec. 15, 2014
ROHDE & SCHWARZ Artificial Mains Network (for EUT)	ESH2-Z5	100104	Dec. 06, 2013	Dec. 05, 2014
LISN With Adapter (for EUT)	AD10	C09Ada-001	Dec. 06, 2013	Dec. 05, 2014
ROHDE & SCHWARZ Artificial Mains Network (for peripherals)	ESH3-Z5	847265/023	Oct. 28, 2013	Oct. 27, 2014
SCHWARZBECK Artificial Mains Network (For EUT)	NNLK8129	8129229	May 08, 2014	May 07, 2015
Software	ADT_Cond_V7.3.7	NA	NA	NA
RF cable (JYEBAO)	5D-FB	Cable-C09.01	Feb. 20, 2014	Feb. 19, 2015
SUHNER Terminator (For ROHDE & SCHWARZ LISN)	65BNC-5001	E1-010789	May 20, 2014	May 19, 2015

Notes: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

- 2. The test was performed in Shielded Room No. 9.
- 3. The VCCI Site Registration No. C-1312.



4.2.3 TEST PROCEDURES


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit 20dB) was not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

4.2.5 TEST SETUP



Note: Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT OPERATING CONDITIONS

Same as item 4.1.6



4.2.7 TEST RESULTS


CONDUCTED WORST-CASE DATA:

PHASE Line 1	6dB BANDWIDTH 9kHz
--------------	--------------------

No	Frequency	Correction Factor	Readin (dB	_		on Level suV)		nit uV)		gin B)
	(MHz)	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	0.16	41.68	22.03	41.84	22.19	66.00	56.00	-24.16	-33.81
2	0.33359	0.20	27.92	20.42	28.12	20.62	59.36	49.36	-31.24	-28.74
3	0.79063	0.26	17.76	11.41	18.02	11.67	56.00	46.00	-37.98	-34.33
4	1.92051	0.34	18.52	14.29	18.86	14.63	56.00	46.00	-37.14	-31.37
5	4.22522	0.43	22.03	20.16	22.46	20.59	56.00	46.00	-33.54	-25.41
6	13.44199	0.77	26.13	21.88	26.90	22.65	60.00	50.00	-33.10	-27.35

Remarks:

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value






PHASE Line 2 6d	dB BANDWIDTH	9kHz
-----------------	--------------	------

No	Frequency	Correction Factor		g Value uV)		n Level uV)		nit uV)		gin B)
	(MHz)	(dB)	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15391	0.29	40.41	23.45	40.70	23.74	65.79	55.79	-25.08	-32.04
2	0.33750	0.35	30.75	23.12	31.10	23.47	59.26	49.26	-28.16	-25.79
3	0.81016	0.41	17.52	10.32	17.93	10.73	56.00	46.00	-38.07	-35.27
4	1.92188	0.48	17.71	13.84	18.19	14.32	56.00	46.00	-37.81	-31.68
5	4.22521	0.52	23.14	20.58	23.66	21.10	56.00	46.00	-32.34	-24.90
6	13.44141	0.62	26.56	22.27	27.18	22.89	60.00	50.00	-32.82	-27.11

Remarks:

- 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
- 2. The emission levels of other frequencies were very low against the limit.
- 3. Margin value = Emission level Limit value
- 4. Correction factor = Insertion loss + Cable loss
- 5. Emission Level = Correction Factor + Reading Value






4.3 6dB BANDWIDTH MEASUREMENT

4.3.1 LIMITS OF 6dB BANDWIDTH MEASUREMENT

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

4.3.2 TEST SETUP



4.3.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.3.4 TEST PROCEDURE

- a. Set resolution bandwidth (RBW) = 100kHz
- b. Set the video bandwidth (VBW) \geq 3 x RBW, Detector = Peak.
- c. Trace mode = max hold.
- d. Sweep = auto couple.
- e. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.3.5 DEVIATION FROM TEST STANDARD

No deviation.


4.3.6 EUT OPERATING CONDITIONS

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



4.3.7 TEST RESULTS

CHANNEL	FREQUENCY (MHz)	6dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
1	2403.5	1.14	0.5	PASS
25	2440.4	1.15	0.5	PASS
49	2477.3	1.13	0.5	PASS






4.4 CONDUCTED OUTPUT POWER

4.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT

For systems using digital modulation: 1 Watt (30dBm)

.

4.4.2 TEST SETUP



4.4.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.4.4 TEST PROCEDURES

A peak / average power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak / average power sensor. Record the peak power level.

4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

4.4.6 EUT OPERATING CONDITIONS

Same as Item 4.3.6.



4.4.7 TEST RESULTS

FOR PEAK POWER

CHANNEL	FREQUENCY (MHz)	PEAK POWER (dBm)	PEAK POWER (mW)	LIMIT (dBm)	PASS/FAIL
1	2403.5	5.50	3.5	30	PASS
25	2440.4	5.54	3.6	30	PASS
49	2477.3	5.37	3.4	30	PASS

FOR AVERAGE POWER

CHANNEL	FREQUENCY (MHz)	AVERAGE POWER (dBm)
1	2403.5	5.41
25	2440.4	5.44
49	2477.3	5.28



4.5 POWER SPECTRAL DENSITY MEASUREMENT

4.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT

The Maximum of Power Spectral Density Measurement is 8dBm.

4.5.2 TEST SETUP



4.5.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.5.4 TEST PROCEDURE

- a. Set the RBW = 3 kHz, VBW =10 kHz, Detector = peak.
- b. Sweep time = auto couple, Trace mode = max hold, allow trace to fully stabilize.
- c. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

4.5.5 DEVIATION FROM TEST STANDARD

No deviation.


4.5.6 EUT OPERATING CONDITION

Same as Item 4.3.6



4.5.7 TEST RESULTS

Channel	FREQ. (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)	PASS /FAIL
1	2403.5	-3.77	8	PASS
25	2440.4	-3.30	8	PASS
49	2477.3	-3.83	8	PASS






4.6 CONDUCTED OUT OF BAND EMISSION MEASUREMENT

4.6.1 LIMITS OF CONDUCTED OUT OF BAND EMISSION MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

4.6.2 TEST SETUP



4.6.3 TEST INSTRUMENTS

Refer to section 4.1.2 to get information of above instrument.

4.6.4 TEST PROCEDURE

MEASUREMENT PROCEDURE REF

- 1. Set the RBW = 100 kHz.
- 2. Set the VBW ≥ 300 kHz.
- 3. Detector = peak.
- 4. Sweep time = auto couple.
- 5. Trace mode = max hold.
- 6. Allow trace to fully stabilize.
- 7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.



MEASUREMENT PROCEDURE OOBE

- 1. Set RBW = 100 kHz.
- 2. Set VBW ≥ 300 kHz.
- 3. Detector = peak.
- 4. Sweep = auto couple.
- 5. Trace Mode = max hold.
- 6. Allow trace to fully stabilize.
- 7. Use the peak marker function to determine the maximum amplitude level.

4.6.5 DEVIATION FROM TEST STANDARD

No deviation.


4.6.6 EUT OPERATING CONDITION

Same as Item 4.3.6

4.6.7 TEST RESULTS

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 20dB offset below D1. It shows compliance with the requirement.







	7828 A D T
5. PHOTOGRAPHS OF THE TEST CONFIGURATION	
Please refer to the attached file (Test Setup Photo).	



6. INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

Hsin Chu EMC/RF/Telecom Lab

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180 Tel: 886-3-5935343 Fax: 886-2-26051924 Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232 Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com
Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.



7. APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB
No modifications were made to the EUT by the lab during the test.
END