





ISO/IEC17025Accredited Lab.

Report No: FCC 1104050 File reference No: 2011-04-09

Applicant: Shenzhen HAC Telecom Technology Co., Ltd.

Product: Zigbee module

Model No: HAC-UBee

Trademark: N/A

Test Standards: FCC Part 15 Subpart C, Paragraph 15.247

Test result:

It is herewith confirmed and found to comply with the

requirements set up by ANSI C63.4FCC Part 15 Subpart C, Paragraph 15.247 regulations for the evaluation of

electromagnetic compatibility

Approved By

Jack Chung

Jack Chung Manager

Dated: April 09, 2011

Results appearing herein relate only to the sample tested

The technical reports is issued errors and omissions exempt and is subject to withdrawal at

SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO LTD

5/F,Block 4, Anhua Industrial Zone.,No.8 TaiRan Rd.CheGongMiao,FuTian District, Shenzhen,CHINA.

Tel (755) 83448688 Fax (755) 83442996

Report No: 1104050 Page 2 of 61

Date: 2011-04-09



Special Statement:

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19.

The testing quality system of our laboratory meet with ISO/IEC-17025 requirements, which is approved by CNAL. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

CNAL-LAB Code: L2292

The EMC Laboratory has been assessed and in compliance with CNAL/AC01:2002 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:1999 General Requirements) for the Competence of testing Laboratories.

FCC-Registration No.: 899988

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files. Registration No.: 899988.

IC- Registration No.: IC5205A-01

The EMC Laboratory has been registered and fully described in a report filed with the (IC) Industry Canada. The acceptance letter from the IC is maintained in our files. Registration IC No.: 5205A-01.

Page 3 of 61

Report No: 1104050 Date: 2011-04-09



Test Report Conclusion Content

1.0	General Details	4
1.1	Test Lab Details.	4
1.2	Applicant Details	4
1.3	Description of EUT	4
1.4	Submitted Sample	5
1.5	Test Duration.	5
1.6	Test Uncertainty.	5
1.7	Test By	5
2.0	List of Measurement Equipment	5
3.0	Technical Details	6
3.1	Summary of Test Results.	7
3.2	Test Standards.	7
4.0	EUT Modification.	7
5.0	Power Line Conducted Emission Test.	8
5.1	Schematics of the Test.	8
5.2	Test Method and Test Procedure.	8
5.3	Configuration of the EUT.	8
5.4	EUT Operating Condition.	9
5.5	Conducted Emission Limit.	9
5.6	Test Result.	9
6.0	Radiated Emission test.	12
6.1	Test Method and Test Procedure.	12
6.2	Configuration of the EUT	12
6.3	EUT Operation Condition.	12
6.4	Radiated Emission Limit.	13
7.0	6dB Bandwidth Measurement.	28
8.0	Maximum Peak Output Power.	33
9.0	Power Spectral Density Measurement.	37
10.0	Out of Band Measurement.	41
11.0	Antenna Requirement.	52
12.0	RF Exposure.	53
13.0	FCC ID Label	54
14.0	Photo of Test Setup and EUT View.	55

Report No: 1104050 Page 4 of 61

Date: 2011-04-09



1.0 General Details

1.1 Test Lab Details

Name: SHENZHEN TIMEWAY TECHNOLOGY CONSULTING CO LTD

Address: 5/F,Block 4, Anhua Industrial Zone.,No.8 TaiRan Rd.CheGongMiao,FuTian District,

Shenzhen, CHINA.

Telephone: (755) 83448688 Fax: (755) 83442996

Site on File with the Federal Communications Commission – United Sates

Registration Number: 899988

For 3m & 10 m OATS

Site Listed with Industry Canada of Ottawa, Canada

Registration Number: IC: 5205A-01

For 3m & 10 m OATS

1.2 Applicant Details

Applicant: Shenzhen HAC Telecom Technology Co., Ltd.

Address: 1903, Tower A of Haisong Bldg, 9th Tairan Road, Chegongmiao, Futian, Shenzhen, China.

Telephone: 86-755-23981078 Fax: 86-755-23981070

1.3 Description of EUT

Product: Zigbee module

Manufacturer: Shenzhen HAC Telecom Technology Co., Ltd.

Model Number: HAC-UBee

Type of Modulation QPSK

Frequency range 2405-2480MHz

Channel Spacing 5MHz
Frequency Selection By software
Channel Number 16 Channels

1.4 Submitted Sample: 1 Sample

1.5 Test Duration:

2011-04-02 to 2011-04-09

1.6 Test Uncertainty

Conducted Emissions Uncertainty = 3.6dB Radiated Emissions Uncertainty = 4.7dB

The report refers only to the sample tested and does not apply to the bulk.

Page 5 of 61

Report No: 1104050 Date: 2011-04-09



1.7 Test Engineer

The sample tested by

Terry Tang

Print Name: Terry Tang

2.0		Test Equip	ments		
Instrument Type	Manufacturer	Model	Serial No.	Date of Cal.	Due Date
ESPI Test Receiver	ROHDE&SCHWARZ	ESPI 3	100379	2011-12-03	2012-12-02
TWO Line-V-NETW	ROHDE&SCHWARZ	EZH3-Z5	100294	2011-12-03	2012-12-02
TWO Line-V-NETW	ROHDE&SCHWARZ	EZH3-Z5	100253	2011-12-03	2012-12-02
Ultra Broadband ANT	ROHDE&SCHWARZ	HL562	100157	2011-12-03	2012-12-02
ESDV Test Receiver	ROHDE&SCHWARZ	ESDV	100008	2011-03-03	2012-03-03
Impuls-Begrenzer	ROHDE&SCHWARZ	ESH3-Z2	100281	2011-03-03	2012-03-03
System Controller	CT	SC100	-	2011-03-03	2012-03-03
Power Supply	LW	APS1502	-	-	-
Bilog Antenna	Chase	CBL6111C	2576	2011-03-03	2012-03-03
Loop Antenna	EMCO	6502	00042960	2011-03-03	2012-03-03
ESPI Test Receiver	ROHDE&SCHWARZ	ESI26	838786/013	2011-03-03	2012-03-03
3m OATS			N/A	2011-03-03	2012-03-03
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170265	2010-08-13	2011-08-12
Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-631	2010-07-03	2011-07-02
Power meter	Anritsu	ML2487A	6K00003613	2011-03-03	2012-03-03
Power sensor	Anritsu	MA2491A	32263	2011-03-03	2012-03-03
Bilog Antenna	Schwarebeck	VULB9163	9163/340	2010-05-14	2011-05-13
LISN	AFJ	LS16C	10010947251	2010-04-26	2011-04-25
LISN (Three Phase)	Schwarebeck	NSLK 8126	8126453	2010-04-26	2011-04-25
9*6*6 Anechoic			N/A	2010-04-26	2011-04-25
EMI Test Receiver	RS	ESCS30	100139	2010-04-26	2011-04-25
LISN	AFJ	LS16C	10010947251	2010-04-26	2011-04-25
LISN (Three Phase)	Schwarebeck	NSLK 8126	8126453	2010-04-26	2011-04-25

Report No: 1104050 Page 6 of 61

Date: 2011-04-09



3. DESCRIPTION OF TEST MODES

IEEE 802.15.4

The EUT had been tested under operating condition. There are three channels have been tested as following:

Channel	Frequency (MHz)
Low	2405
Middle	2445
High	2480

Page 7 of 61

Report No: 1104050 Date: 2011-04-09



3.0 Technical Details

3.1 Summary of test results

The EUT has been	ı tested accordin	g to the following	specifications:
		A	, 50000

Standard	Test Type	Result	Notes
FCC Part 15, Paragraph 15.107	Conducted Emission Test	PASS	Complies
& 15.207			
	Spectrum bandwidth of a		Complies
FCC Part 15 Subpart C	Orthogonal Frequency		
Paragraph 15.247(a)(2) Limit	Division Multiplex System	PASS	
r aragraph 13.247(a)(2) Linnt	Limit: 6dB		
	bandwidth>500kHz		
FCC Part 15, Paragraph	Maximum peak output		
15.247(b)	power	PASS	Complies
13.247(0)	Limit: max. 30dBm		
FCC Part 15, Paragraph	Transmitter Radiated	PASS	Complies
15.109,15.205 & 15.209	Emission		
	Limit: Table 15.209		
FCC Part 15, Paragraph	Power Spectral Density	PASS	Complies
15.247(d)	Limit: max. 8dBm		
FCC Part 15, Paragraph	Out of Band Emission and	PASS	Complies
15.247(c)	Restricted Band		
	Radiation		
	Limit: 20dB less than		
	peak value of fundamental		
	frequency		
	Restricted band limit:		
	Table 15.209		

3.2 Test Standards

FCC Part 15 Subpart & Subpart C, Paragraph 15.247

4.0 EUT Modification


No modification by Shenzhen Timeway Technology Consulting Co.,Ltd

Report No: 1104050 Date: 2011-04-09



5. Power Line Conducted Emission Tes

5.1 Schematics of the test




EUT: Equipment Under Test

5.2 Test Method and test Procedure

The EUT was tested according to ANSI C63.4-2009. The Frequency spectrum From 0.15MHz to 30MHz was investigated. The LISN used was 50ohm/50uH as specified by section 5.1 of ANSI C63.4 –2003.

Block diagram of Test setup



5.3 Configuration of The EUT

The EUT was configured according to ANSI C63.4-2009. All interface ports were connected to the appropriate peripherals. All peripherals and cables are listed below.

A. EUT

Device	Manufacturer	Model	FCC ID
Zigbee module	Shenzhen HAC Telecom Technology Co., Ltd.	HAC-UBee	WMUHAC-UBEEV3X

B. Internal Device

Device	Manufacturer	Model	FCC ID/DOC
N/A			

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: 1104050 Page 9 of 61

Date: 2011-04-09

C. Peripherals

Device	Manufacturer	Model	FCC ID/DOC	Cable
Power	MoSo	AB41-060A-100T	-	1m of length DC output cable
Supply				without shielding

5.4 EUT Operating Condition

Operating condition is according to ANSI C63.4 -2003.

- A Setup the EUT and simulators as shown on follow
- B Enable AF signal and confirm EUT active to normal condition

5.5 Power line conducted Emission Limit according to Paragraph 15.207 and 15.107

_						
	Frequency	Class A Lim	its (dB µ V)	Class B Limits (dB µ V)		
	(MHz)	Quasi-peak Level	Average Level	Quasi-peak Level	Average Level	
	$0.15 \sim 0.50$	79.0	66.0	66.0~56.0*	56.0~46.0*	
	$0.50 \sim 5.00$	73.0	60.0	56.0	46.0	
	5.00 ~ 30.00	73.0	60.0	60.0	50.0	

Notes:

- 1. *Decreasing linearly with logarithm of frequency.
- 2. The tighter limit shall apply at the transition frequencies

5.6 Test Results

The frequency spectrum from 0.15MHz to 30MHz was investigated. All reading are quasi-peak values with a resolution bandwidth of 9kHz.

Note: the worse cases was selected to conducted the test


Report No: 1104050 Date: 2011-04-09

A Conducted Emission on Line Terminal of the power line (150kHz to 30MHz)

EUT set Condition: Keep Transmitting

Results: Pass

Please refer to following diagram for individual



Eraguancy	Reading(dB µ V)				Limi	t
Frequency (MHz)	Line	;	Neutr	Neutral		V)
(MHZ)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.3219	32.07	16.79			59.66	49.66
0.2047	29.14	25.81			63.41	53.41
1.1187	27.29	7.20			56.00	46.00
5.5586	25.11	9.56			60.00	50.00
8.0586	23.22	4.45			60.00	50.00
0.1695	27.08	19.38			64.98	54.98


Report No: 1104050 Date: 2011-04-09

A Conducted Emission on Neutral Terminal of the power line (150kHz to 30MHz)

EUT set Condition: Keep Transmitting

Results: Pass

Please refer to following diagram for individual



Fraguanay	Reading(dB µ V)				Limi	t
Frequency (MHz)	Line		Neutral		$(dB \mu V)$	
(WITIZ)	Quasi-peak	Average	Quasi-peak	Average	Quasi-peak	Average
0.3219			37.64	23.71	59.66	59.66
1.1305			27.80	10.79	56.00	56.00
5.5078			28.31	10.92	60.00	60.00
7.8398			25.38	7.20	60.00	60.00
0.2047			30.75	26.04	63.41	63.41
1.1968			30.89	14.65	56.00	56.00

Report No: 1104050 Page 12 of 61


Date: 2011-04-09



6 Radiated Emission Test

- 6.1 Test Method and test Procedure:
- (1) The EUT was tested according to ANSI C63.4 –2009. The radiated test was performed at Timeway Laboratory. This site is on file with the FCC laboratory division, Registration No.899988
- (2) The EUT, peripherals were put on the turntable which table size is 1m x 1.5 m, table high 0.8 m. All set up is according to ANSI C63.4-2009.
- (3) The frequency spectrum from 30 MHz to 25 GHz was investigated. All readings from 30 MHz to 1 GHz are Quasi-peak values with a resolution bandwidth of 120 kHz. For measurement above 1GHz, peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=10Hz and PK detector. Measurements were made at 3 meters.
- (4) The antenna high is varied from 1 m to 4 m high to find the maximum emission for each frequency.
- (5) Maximizing procedure was performed on the six (6) highest emissions to ensure EUT compliance is with all installation combinations. All data was recorded in the peak detection mode. Quasi-peak readings was performed only when an emission was found to be marginal (within -4 dB of specification limit), and are distinguished with a "QP" in the data table.
- (6) The antenna polarization: Vertical polarization and Horizontal polarization.

Block diagram of Test setup



- 6.2 Configuration of The EUT

 Same as section 5.3 of this report
- 6.3 EUT Operating Condition
 Same as section 5.4 of this report.

Report No: 1104050 Page 13 of 61

Date: 2011-04-09



6.4 Radiated Emission Limit

All emission from a digital device, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strength specified below:

Frequencies in restricted band are complied to limit on Paragraph 15.209 and 15.109

		~ <u>-</u>
Frequency Range (MHz)	Distance (m)	Field strength (dB µ V/m)
30-88	3	40.0
88-216	3	43.5
216-960	3	46.0
Above 960	3	54.0

Note:

- 1. RF Voltage (dBuV) = 20 log RF Voltage (uV)
- 2. In the Above Table, the higher limit applies at the band edges.
- 3. Distance refers to the distance in meters between the measuring instrument antenna and the EUT

Report No: 1104050 Page 14 of 61

Date: 2011-04-09



Test result

General Radiated Emission Data and Harmonics Radiated Emission Data

Radiated Emission In Horizontal (30MHz----1000MHz)

EUT set Condition: Keep Transmitting (Low channel)

Results: Pass


Antenna: Inverted F PCB Antenna


Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \u03b4 V/m)	
151.250 30.61		Н	43.50	
151.250 22.66		V	43.50	

Report No: 1104050 Date: 2011-04-09



Test Figure:





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

Report No: 1104050 Page 16 of 61

Date: 2011-04-09



Test result

General Radiated Emission Data and Harmonics Radiated Emission Data

Radiated Emission In Horizontal (30MHz----1000MHz)

EUT set Condition: Keep Transmitting (Low channel)

Results: Pass

Antenna: Dipole Antenna


Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \u03b4 V/m)	
141.550	35.04	V	43.50	
165.800	165.800 24.96		43.50	
156.100 20.92		Н	43.50	

Page 17 of 61

Report No: 1104050 Date: 2011-04-09



Test Figure:



The report refers only to the sample tested and does not apply to the bulk.

30.000

40

50

60 70

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

(MHz)

300

400

500

600 700

1000.000

Report No: 1104050 Page 18 of 61

Date: 2011-04-09

Operation Mode: Keep Transmitting (ECT with Inverted F PCB Antenna)						
Frequency (MHz)	Level@3m (dB \mu V/m)	Antenna Polarity	Limit@3m (dB \u03b4 V/m)			
2405	79.25 (PK)	Н	Fundamental Frequency			
2405	80.15 (PK)	V	Fundamental Frequency			
4810		Н	74(Peak)/ 54(AV)			
7215		Н	74(Peak)/ 54(AV)			
9620		H/V	74(Peak)/ 54(AV)			
12025		H/V	74(Peak)/ 54(AV)			
14430		H/V	74(Peak)/ 54(AV)			
16835		H/V	74(Peak)/ 54(AV)			
19240		H/V	74(Peak)/ 54(AV)			
21645		H/V	74(Peak)/ 54(AV)			
24050		H/V	74(Peak)/ 54(AV)			

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

^{2.} Remark "---" means that the emissions level is too low to be measured

Report No: 1104050 Page 19 of 61

Date: 2011-04-09

Operation Mode: Keep Transmitting (EUT with Inverted F PCB Antenna)

	1		
Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)
2445	78.15 (PK)	Н	Fundamental Frequency
2445	80.41 (PK)	V	Fundamental Frequency
4890	-	Н	74(Peak)/ 54(AV)
7335	-	V	74(Peak)/ 54(AV)
9780	-	H/V	74(Peak)/ 54(AV)
12225		H/V	74(Peak)/ 54(AV)
14670	1	H/V	74(Peak)/ 54(AV)
17115	-	H/V	74(Peak)/ 54(AV)
19560		H/V	74(Peak)/ 54(AV)
22005		H/V	74(Peak)/ 54(AV)
24450		H/V	74(Peak)/ 54(AV)

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

2. Remark "---" means that the emissions level is too low to be measured

Operation Mode: Keep Transmitting (EUT with Inverted F PCB Antenna)

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \u03b4 V/m)	
2480	78.69 (PK)	Н	Fundamental Frequency	
2480	82.39 (PK)	V	Fundamental Frequency	
4960	-	Н	74(Peak)/ 54(AV)	
7440	-	V	74(Peak)/ 54(AV)	
9920	1	H/V	74(Peak)/ 54(AV)	
12400	1	H/V	74(Peak)/ 54(AV)	
14880	1	H/V	74(Peak)/ 54(AV)	
17360		H/V	74(Peak)/ 54(AV)	
19840		H/V	74(Peak)/ 54(AV)	
22320	22320		74(Peak)/ 54(AV)	
24800		H/V	74(Peak)/ 54(AV)	

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit


2. Remark "---" means that the emissions level is too low to be measured

Report No: 1104050 Date: 2011-04-09




Please refer to the following test plots for details

Low CH: Horizontal



Low CH: Vertical



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Page 21 of 61


Report No: 1104050 Date: 2011-04-09



Middle CH: Horizontal



Middle CH: Vertical



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Page 22 of 61

Report No: 1104050 Date: 2011-04-09



High CH: Horizontal



High CH: Vertical



Note: For the radiated emissions from 18GHz-25GHz, it is the floor noise that meets the requirement of FCC rule.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Report No: 1104050 Page 23 of 61

Operation Mode: Keep Transmitting (EUT with Dipole antenna)

Date: 2011-04-09

operation (2000 2000)						
Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \(\mu \)V/m)			
2405	79.64 (PK)	Н	Fundamental Fraguency			
2405	80.78 (PK)	V	Fundamental Frequency			
4810		Н	74(Peak)/ 54(AV)			
7215		V	74(Peak)/ 54(AV)			
9620		H/V	74(Peak)/ 54(AV)			
12025		H/V	74(Peak)/ 54(AV)			
14430		H/V	74(Peak)/ 54(AV)			
16835		H/V	74(Peak)/ 54(AV)			
19240		H/V	74(Peak)/ 54(AV)			
21645		H/V	74(Peak)/ 54(AV)			
24050		H/V	74(Peak)/ 54(AV)			

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

2. Remark "---" means that the emissions level is too low to be measured

Operation Mode: Keep Transmitting (EUT with Dipole antenna)

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB \mu V/m)	
2445	79.69 (PK)	Н	Fundamental Frequency	
2445	80.15(PK)	V	Fundamental Frequency	
4890	ı	Н	74(Peak)/ 54(AV)	
7335	1	V	74(Peak)/ 54(AV)	
9780	-	H/V	74(Peak)/ 54(AV)	
12225	1	H/V	74(Peak)/ 54(AV)	
14670	ı	H/V	74(Peak)/ 54(AV)	
17115	1	H/V	74(Peak)/ 54(AV)	
19560	1	H/V	74(Peak)/ 54(AV)	
22005	22005		74(Peak)/ 54(AV)	
24450	24450		74(Peak)/ 54(AV)	

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit

2. Remark "---" means that the emissions level is too low to be measured

Report No: 1104050 Page 24 of 61

Operation Mode: Keep Transmitting (EUT with Dipole antenna)

Date: 2011-04-09

Frequency (MHz)	Level@3m (dB \u03b4 V/m)	Antenna Polarity	Limit@3m (dB μ V/m)	
2480	79.23(PK)	Н	Fundamental Frequency	
2480	82.36(PK)	V	Fundamental Frequency	
4960		Н	74(Peak)/ 54(AV)	
7440		V	74(Peak)/ 54(AV)	
9920		H/V	74(Peak)/ 54(AV)	
12400		H/V	74(Peak)/ 54(AV)	
14880		H/V	74(Peak)/ 54(AV)	
17360		H/V	74(Peak)/ 54(AV)	
19840		H/V	74(Peak)/ 54(AV)	
22320		H/V	74(Peak)/ 54(AV)	
24800		H/V	74(Peak)/ 54(AV)	

Note: 1. Level = Reading + AF + Cable - Preamp + Filter - Dist, Margin = Level - Limit


^{2.} Remark "---" means that the emissions level is too low to be measured

Report No: 1104050 Date: 2011-04-09




Please refer to the following test plots for details

Low CH: Horizontal



Low CH: Vertical



The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Page 26 of 61


Report No: 1104050 Date: 2011-04-09



Middle CH: Horizontal



Middle CH: Vertical



The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

Page 27 of 61


Report No: 1104050 Date: 2011-04-09



High CH: Horizontal



High CH: Vertical



Note: For the radiated emissions from 18GHz-25GHz, it is the floor noise that meet the requirement of FCC rule.

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.


Report No: 1104050 Page 28 of 61

Date: 2011-04-09



7.0 6dB Bandwidth Measurement

7.1 Test Setup



7.2 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is >500kHz

7.3 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator.

The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 kHz RBW and 100 kHz VBW; The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

7.4 Test Result

Page 29 of 61


Report No: 1104050 Date: 2011-04-09

			\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	/		ı	
EUT		Zigb	ee module	Model		HAC-UBee	
Mode		Keep	Transmitting	Input Vol	tage	ge DC4.8	
Temperat	ure	24	4 deg. C,	Humidity	56% RH		RH
Channel		el Frequency (MHz)	6 dB Bandwi (MHz)	dth		mum Limit MHz)	Pass/ Fail
Low		2405	1.619			0.5	Pass
Middle		2445	1.623			0.5	Pass
High		2480	1.623			0.5	Pass

Report No: 1104050 Page 30 of 61

Date: 2011-04-09

1. Low Channel



Date: 02.APR.2011 16:05:14

Report No: 1104050 Page 31 of 61

Date: 2011-04-09

2. Middle Channel



Date: 02.APR.2011 16:28:25

Report No: 1104050 Page 32 of 61

Date: 2011-04-09

3. High Channel



Date: 02.APR.2011 16:12:07


Page 33 of 61

Report No: 1104050 Date: 2011-04-09



8. Maximum Peak Output Power

8.1 Test Setup



8.2 Limits of Maximum Peak Output Power

The Maximum Peak Output Power Measurement is 30dBm.

8.3 Test Procedure

The RF power output was measured with a spectrum connected to the RF Antenna connector (conducted measurement) while EUT was operating in transmit mode at the appropriate centre frequency.

Note: the peak power was measured

8.4Test Results

EUT		Zigbee n	module Model HAC		Model		.C-UBee					
Mode		Keep Tran	smitting	Input Voltage		Input Voltage		Input Voltage		mitting Input Voltage D		C4.8V
Temperature	e	24 deg	eg. C, Humidity 56%		g. C, Humidity 56% RH		nidity		5% RH			
Channel	Cha	annel Frequency (MHz)	Peak Power (dBm)	Peak P Lim (dB)		nit	Pass/ Fail					
Low		2405	4.27		30		Pass					
Middle		2445	4.08		30)	Pass					
High		2480	4.01		30)	Pass					

Note: The result basic equation calculation as follow:


Peak Power Output = Peak Power Reading + Cable loss + Attenuator

Page 34 of 61

Report No: 1104050 Date: 2011-04-09



Test Figure: Low Channel:




Page 35 of 61

Report No: 1104050 Date: 2011-04-09



Middle Channel:




Date: 02.APR.2011 16:32:56

Page 36 of 61

Report No: 1104050 Date: 2011-04-09



High Channel:




Date: 02.APR.2011 16:13:20

Report No: 1104050 Page 37 of 61

Date: 2011-04-09



9.1 Test Setup



9.2 Limits of Power Spectral Density Measurement

The Maximum Power Spectral Density Measurement is 8dBm.

9.3 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3KHz RBW and 10kHz VBW, set sweep time=100s, **PK detector.**

The power spectral density was measured and recorded.

The sweep time is allowed to be longer than span / 3KHz for a full response of the mixer in the spectrum analyzer.


9.4Test Result

EUT		Zigbee module		Model		HAC-UBee	
Mode		Keep Transmitting		Input Voltage		DC4.8V	
Temperature		24 deg. C,		Humidity		56% RH	
Channel	Ch	annel Frequency (MHz)	Final RF Power Level in 3kHz BW (dBm)		Maximum Limit (dBm)		Pass/ Fail
Low		2405	-9.73		8		Pass
Middle		2445	-9.49		8		Pass
High		2480	-10.20		8		Pass

Date: 2011-04-09

9.5 Photo of Power Spectral Density Measurement

1. Low Channel




Date: 02.APR.2011 16:03:31

Report No: 1104050 Date: 2011-04-09



2. Middle Channel




Date: 02.APR.2011 16:27:06

Date: 2011-04-09

Report No: 1104050



3. High Channel




Date: 02.APR.2011 16:19:55

Report No: 1104050 Page 41 of 61

Date: 2011-04-09



10 Out of Band Measurement 10.1 Test Setup for band edge



The restricted band requirement based on radiated emission test; please see the clause 6 for the test setup

10.2 Limits of Out of Band Emissions Measurement

- 1. Below –20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).
- 2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.

10.3 Test Procedure

For signals in the restricted bands above and below the 2.4-2.483GHz allocated band a measurement was made of radiated emission test.(Peak values with RBW=VBW=1MHz and PK detector. AV value with RBW=1MHz, VBW=10Hz and PK detector)

For bandage test, the spectrum set as follows: RBW=VBW=100 kHz. A conducted measurement used

10.4 Test Result

Please see next pages

Page 42 of 61

Report No: 1104050 Date: 2011-04-09




Low Channel

10.4 Band edge Measurement

EUT	Zigbee module	Model	HAC-UBee
Mode	Keep Transmitting	Input Voltage	DC4.8V
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure:



Date: 02.APR.2011 16:07:36

Page 43 of 61

Report No: 1104050 Date: 2011-04-09




High Channel

10.4 Band edge Measurement

EUT	Zigbee module	Model	HAC-UBee
Mode	Keep Transmitting	Input Voltage	DC4.8V
Temperature	24 deg. C,	Humidity	56% RH
Test Result:	Pass	Detector	PK

Test Figure:



Date: 02.APR.2011 16:15:58

Report No: 1104050 Page 44 of 61

Date: 2011-04-09



Low Channel: (For Dipole Antenna)

Restricted band Measurement 10.4

EUT	Zigbee module		Model	HAC-UBee
Mode	Keep Transmitting		Input Voltage	DC4.8V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:	Pass		Detector	PK
The Max. FS in	PK ($dB\mu V/m$)	28.05(V) /28.07(H)		$74(dB\mu V/m)$
Restrict Band 2390MHz	AV (dBμV/m)		Limit	54(dBμV/m)

Test Figure:


Page 45 of 61

Report No: 1104050 Date: 2011-04-09




Horizontal





Vertical





The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No: 1104050 Page 46 of 61

Date: 2011-04-09



High Channel: (For Dipole Antenna)

10.4 Restricted band Measurement

EUT	Zigbee module		Model	HAC-UBee
Mode	Keep Transmitting		Input Voltage	DC4.8V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:		Pass	Detector	PK
The Max. FS in	PK (dBμV/m)	44.55(V)/41.45(H)		$74(dB\mu V/m)$
Restrict Band 2483.5MHz	AV (dBμV/m)		Limit	$54(dB\mu V/m)$

Test Figure:


Page 47 of 61

Report No: 1104050 Date: 2011-04-09




Horizontal:





Vertical:



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No: 1104050 Page 48 of 61

Date: 2011-04-09

Low Channel: (For Inverted F PCB Antenna)

Restricted band Measurement 10.4

EUT	Zigbee module		Model	HAC-UBee
Mode	Keep Transmitting		Input Voltage	DC4.8V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:		Pass	Detector	PK
The Max. FS in	PK (dBμV/m)	28.05(H)/30.70(V)		$74(dB\mu V/m)$
Restrict Band 2483.5MHz	AV (dBμV/m)		Limit	$54(dB\mu V/m)$


Test Figure:

Page 49 of 61


Report No: 1104050 Date: 2011-04-09



Horizontal:



Vertical:



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No: 1104050 Page 50 of 61

Date: 2011-04-09

High Channel: (For Inverted F PCB Antenna)

Restricted band Measurement 10.4

EUT	Zigbee module		Model	HAC-UBee
Mode	Keep Transmitting		Input Voltage	DC4.8V
Temperature	24 deg. C,		Humidity	56% RH
Test Result:		Pass	Detector	PK
The Max. FS in	PK (dBμV/m)	47.91(V)/41.99(H)		$74(dB\mu V/m)$
Restrict Band 2483.5MHz	AV (dBμV/m)		Limit	54(dBμV/m)


Test Figure:

Page 51 of 61


Report No: 1104050 Date: 2011-04-09



Horizontal:



Vertical:



The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No: 1104050 Page 52 of 61

Date: 2011-04-09



11.0 Antenna Requirement 11.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitter antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the mount in dB that the directional gain of the antenna exceeds 6 dBi.

11.2 Antenna Connected construction

The EUT can employ two types of antenna. The gain of Inverted F PCB antenna is 1.1dBi The gain of Dipole antenna is 2.15dBi

If using E1 PCB antenna, the E2 External dipole antenna is unconnected;

If using E2 External antenna, the capacitor C38 should be removed. And the capacitor C38 must be soldered.

Please see photos and schematics for details.

Report No: 1104050 Page 53 of 61

Date: 2011-04-09



12.0 RF Exposure

Applicable Standard

According to §1.1307(b)(5), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline. This modular can be used in a Portable device. **KDB616217 was used as the guidance.**According to §1.1310 and §2.1093 RF exposure is calculated.

Measurement Result

This is a Zigbee Module and the conducted output power is 4.27dBm (2.673mW).

For EUT with Inverted F PCB Antenna:

so the EIRP is 2.673*1.288=3.443mW which is lower than low threshold 60/fGHz mW (60/2.480GHz=24.19mW), and the antenna is 1.1dBi which is less than 6dBi.

For EUT with Dipole Antenna:

so the EIRP is 2.673*1.641=4.386mW which is lower than low threshold 60/fGHz mW (60/2.480GHz=24.19mW), and the antenna is 2.15dBi which is less than 6dBi.

The SAR measurement is not necessary.

Report No: 1104050 Page 54 of 61

Date: 2011-04-09




13.0 FCC ID Label

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label must not be a stick-on paper label. The label on these products must be permanently affixed to the product and readily visible at the time of purchase and must last the expected lifetime of the equipment not be readily detachable.

Mark Location:



Page 55 of 61

Report No: 1104050 Date: 2011-04-09




14.0 Photo of testing



Report No: 1104050 Date: 2011-04-09







The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion

of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No: 1104050 Date: 2011-04-09



14.3 Photo for the EUT





EUT With Dipole Antenna

The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co., Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it . or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co .,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.

Page 58 of 61

Report No: 1104050 Date: 2011-04-09






EUT With Dipole Antenna

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd vill not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Report No: 1104050 Date: 2011-04-09



EUT With Inverted F PCB Antenna

The report refers only to the sample tested and does not apply to the bulk.

This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co., Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co .,Ltd reserves the rights to withdraw it and to

adopt any other remedies which may be appropriate.

Page 60 of 61

Report No: 1104050 Date: 2011-04-09





EUT With Inverted F PCB Antenna

The report refers only to the sample tested and does not apply to the bulk.


This report is issued in confidence to the client and it will be strictly treated as such by the Shenzhen Timeway Technology Consulting Co.,Ltd. It may not be reproduced rather in its entirety or in part and it may not be used for adverting. The client to whom the report is issued may, however, show or send it. or a certified copy there of prepared by the Shenzhen Timeway Technology Consulting co.,Ltd to his customer. Supplier or others persons directly concerned. Shenzhen Timeway Technology Consulting co.,Ltd will not, without the consent of the client enter into any discussion of correspondence with any third party concerning the contents of the report.

In the event of the improper use of the report. The Shenzhen Timeway Technology Consulting co.,Ltd reserves the rights to withdraw it and to adopt any other remedies which may be appropriate.

Page 61 of 61

Report No: 1104050 Date: 2011-04-09





End of the report