

深圳创维数字技术有限公司

SZ SKYWORTH DIGITAL TECHNOLOGY CO.,LTD

ENGINEERING EVALUATION REPORT

(COMPONENTS)

REPORT NO.	EDED2302223	DATE OF APPLICATION	2023-02-17
MODEL	TEN22	APPLICATION NO.	NASP2023020020-1
DESCRIPTIONS	ANTENNA WIFI 50 OHM 189mm/145mm*1.13mm IPEX1 2.4G/5dB Wihte RF-link 扁体 RoHS		
SUPPLIER'S PART NO.	U00T01S069N02809		
SKYWORTH'S PART NO.	53XD-080025-A087		
MANUFACTURER	Jiangxi RF Link Electronic Co., Ltd. Address: Shangli Industrial Park, Chishan Town, Shangli County, Pingxiang City, Jiangxi Province		
SAFETY CERTIFICATION REQUIREMENTS	不需要		
ENVIRONMENTAL PROTECTION REQUIREMENTS	ROHS2.0		
REMARKS:			
COMMENTS:	IF THERE IS ANY QUALITY PROBLEM,PLEASE FOLLOW THE AGREEMENT OF BOTH		
FICTION:		APPROVAL:	
同敬		刘十培	

Product picture



Basic specification

Parameter attribute	Parameter name	要求值 Required value	Manufacturer specification value
specification	Glue stick	白色 189.1mm white	189.1mm 色号 RF006W
	PCB	FR-4	FR-4
	馈线 feeder	灰色 1.13 线, 145mm gray	灰色 1.13 线, 145mm gray
	馈线末端 Feeder emd	IPEX 1 代	IPEX 1 代
	配件 attachment	/	/

PCB Gerber 图



产品主要技术参数








Main technical specifications

主要技术指标		Main technical specifications	
频率范围 (MHZ)	2400-2500	Frequency Range (MHZ)	2400-2500
中心频率 特性阻抗(Ω)	50 ± 10	Impedance(Ω)	50 ± 10
增益(dBi)	5.62	Gain(dBi)	5.62
反射损耗	≤ -10	Return Loss(dB)	≤ -10
输出电压 驻波比	≤ 1.92	VSWR	≤ 1.92
极化方式	垂直极化	Polarization	Linear, Vertical
方向性	全向性	Radiation	Omni-directional
连接方式	端子	Connector Type	端子
物理性能		Physical Properties	
天线本体材料	ABS	Antenna Base	ABS
工作温度	$-20^{\circ}\text{C} \sim +60^{\circ}\text{C}$	Operating Temp	$-20^{\circ}\text{C} \sim +60^{\circ}\text{C}$
保存温度	$-20^{\circ}\text{C} \sim +70^{\circ}\text{C}$	Storage Temp	$-20^{\circ}\text{C} \sim +70^{\circ}\text{C}$

Electrical property

Parameter attribute	Parameter name	Required value	Manufacturer specification value	Manufacturer's typical value
Electrical property (Key parameter)	gain	5.62dBi	5.62dBi	5.62dBi
	efficiency	$\geq 70\%$	$\geq 70\%$	$\geq 70\%$
Electrical property (Ordinary parameter)	Frequency range	2400-2500MHz	2400-2500MHz	2400-2500MHz
	Characteristic impedan	50 Ω	50 Ω	50 Ω
	S11	$\leq -10\text{dB}$	$\leq -10\text{dB}$	$\leq -10\text{dB}$

测试报告



Frequency / MHz	Gain/ dBi	Efficiency / %
2400	3.37	65.23
2410	3.86	64.52
2420	4.1	64.57
2430	4.32	67.14
2440	4.63	71.29
2450	4.91	75.16
2460	5.15	77.45
2470	5.25	76.56
2480	5.31	76.56
2490	5.54	75.51
2500	5.62	73.96