

SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR220700026806

Page: 1 of 14

# RF EXPOSURE EVALUATION REPORT

Application No.: FYCR2207000268AT

Applicant: Shenzhen Skyworth Digital Technology Co.,LTD

Address of Applicant: Unit A14/F.Skyworth Bldg.,Gaoxin Ave.1s., Nanshan District,

Shenzhen, China

Manufacturer: STRONG Ges.m.b.H.

Address of Manufacturer: Teinfaltstraße 8/4. Stock. A-1010 Vienna. Austria.

Factory: Shenzhen Skyworth Digital Technology Co.,LTD. Baoan Branch Factory

Address of Factory: 2-5F,Integration Multi-Storied Building,Skyworth Science and Technology

Industrial Park, Tangtou Industrial Zone, Shiyan Street, Baoan

District, Shenzhen city, China

**Equipment Under Test (EUT):** 

**EUT Name:** Smart TV stick

Model No.: HP4619, HP46D, HP4619-BR, HP4619-ES, HP4619-CL, HP4619-AR,

HP4619-CO, HP4619-PE ♣

Please refer to section 3.2 of this report which indicates which model was

actually tested and which were electrically identical.

Trade Mark: Strong, Skyworth FCC ID: WNA-HP4619

Standard(s): FCC Rules 47 CFR §2.1091

KDB 447498 D04 interim General RF Exposure Guidance v01

**Date of Receipt:** 2022-07-11

**Date of Evaluation:** 2022-07-15 to 2022-08-03

**Date of Issue:** 2022-08-31

Evaluation Result: Pass\*

Winkey Wang EMC Technical Manager

WinkeyWang



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx.and">http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Documents</a>, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx.">http://www.sgs.com/en/Terms-en-Document.aspx.</a></a>
Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or faisification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) lested and such sample(s) are retained for 30 days only.

\*\*Attention:\*\* To check the authenticity of testing rinspection report & certificate, please contact us at telephone: (86-755) 8307 1443.

\*\*Attention:\*\*To check the authenticity of testing rinspection report & certificate, please contact us at telephone: (86-755) 8307 1443.

Fuyong lab. Xinlong TechnoPark, Fenglang Road, Fuyong Subdishird, Bao'an, Shenzhen, China 518103 t (86-755) 88663988 f (86-755) 26710594 www.sgsgroup.com.cn 中国·深圳·宝安区福永街道凤塘大道鑫龙科技园福永实验室 邮编: 518103 t (86-755) 88663988 f (86-755) 26710594 sgs.china@sgs.com

<sup>\*</sup> In the configuration evaluated, the EUT complied with the standards specified above.



SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR220700026806

Page: 2 of 14

	Revision Record								
Version	Chapter	Date	Modifier	Remark					
01		2022-08-31		Original					

Authorized for issue by:		
	Tree Zhan	
	Tree Zhan/Project Engineer	
	WinkeyWarg	
	Winkey Wang/Reviewer	





SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR220700026806

Page: 3 of 14

## 2 Contents

			Page
1	Cov	er Page	1
2	Con	tents	3
3	Gen	eral Informationeral	4
	3.1 3.2 3.3 3.4 3.5 3.6 3.7	General Description of E.U.T.  Details of E.U.T.  Separation Distance.  Test Location.  Test Facility.  Deviation from Standards.  Abnormalities from Standard Conditions	4 6 6
4	FCC	Radiofrequency radiation exposure limits	7
4	4.1 4.2 4.3	Blanket 1 mW Blanket Exemption  MPE-based Exemption  SAR-based Exemption	7
5	Mea	surement and Calculation	11
•	5.1 5.2	Maximum transmit power	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions.aspx</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="https://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx">https://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx</a>. Attention is drawn to the limitation of liability, indemnification insues defined therein. Any holder of his document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, \*\*Certificate, Please contact us at telephone: (86-755) 8307 1443, \*\*Certificate, Please contact us at telephone: (86-755) 8307 1443, \*\*Certificate, Please contact us at telephone: (86-755) 8307 1443, \*\*Certificate, Please contact us at telephone: (86-755) 8307 1443, \*\*Certificate, Please contact us at telephone: (86-755) 8307 1443, \*\*Certificate, Please contact us at telephone: (86-755) 8307 1443, \*\*Certificate, Please contact us at telephone: (86-755) 8307 1443, \*\*C

Fuyong lab. Xinlong TechnoPark, Fengtang Road, Fuyong Subdistrict, Barian, Sherazhen, Chira 518103 t (86-755) 88663988 f (86-755) 26710594 www.sgsgroup.com.cn 中国・深圳・宝安区福永街道凤塘大道鑫龙科技园福永实验室 邮编: 518103 t (86-755) 88663988 f (86-755) 26710594 sgs.china@sgs.com



SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR220700026806

Page: 4 of 14

## 3 General Information

3.1 General Description of E.U.T.

	☐ Portable device			
Product Type:	☐Mobile device			

### 3.2 Details of E.U.T.

Adapter:				
Model: F05L5-050100SPAU-U				
Input: AC 100-240V 50/60Hz 0.2A				
Output: DC 5.0V 1.0A 5.0W				
3.0V DC (1.5V x 2 "AAA" Size Batteries) for remote controller				
USB cable: 97cm unshielded				
HDMI cable: 7cm shielded				
2402MHz to 2480MHz				
V5.0 Dual mode				
GFSK, pi/4DQPSK, 8DPSK				
79				
1MHz				
Frequency Hopping Spread Spectrum(FHSS)				
PCB Antenna				
4.83dBi				
2402MHz to 2480MHz				
V5.0 Dual mode				
GFSK				
40				
2MHz				
1Mbit/s and 2Mbit/s				
PCB Antenna				
4.83dBi				



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions.aspx</a> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx">http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's Instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or semile CSP Doccheck@ses.com.

Fuyong lab. Xinlong TechnoPark, Fengtang Road, Fuyong Subdistrict, Barian, Sherazhen, Chira 518103 t (86-755) 88663988 f (86-755) 26710594 www.sgsgroup.com.cn 中国・深圳・宝安区福永街道凤塘大道鑫龙科技园福永实验室 邮编: 518103 t (86-755) 88663988 f (86-755) 26710594 sgs.china@sgs.com



SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR220700026806

Page: 5 of 14

For 2.4G WIFI:	
Operation Frequency:	802.11b/g/n(HT20): 2412MHz to 2462MHz;802.11n(HT40): 2422MHz to 2452MHz
Modulation Type:	802.11b: DSSS (CCK, DQPSK, DBPSK);802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Number of Channels:	802.11b/g/n(HT20):11;802.11n(HT40):7
Channel Spacing:	5MHz
Antenna Type:	PCB Antenna
Antenna Gain:	Antenna 1:2.03dBi Antenna 2:4.83dBi
For 5G WIFI:	
Operation Frequency (20MHz):	U-NII-1: 5180-5240MHz; U-NII-2A: 5260-5320MHz; U-NII-2C: 5500-5700MHz; U-NII-3: 5745-5825MHz
Operation Frequency (40MHz):	U-NII-1: 5190-5230MHz; U-NII-2A: 5270-5310MHz; U-NII-2C: 5510- 5670MHz; U-NII-3: 5755-5795MHz
Operation Frequency (80MHz):	U-NII-1: 5210MHz; U-NII-2A: 5290MHz; U-NII-2C: 5530-5610MHz; U-NII-3: 5775MHz
Moudulation Type:	802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK); 802.11n: OFDM (BPSK, QPSK, 16QAM, 64QAM); 802.11ac: OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)
Channel Spacing:	802.11a/n(HT20)/ac(HT20): 20MHz; 802.11n(HT40)/ac(HT40): 40MHz; 802.11ac(HT80): 80MHz
DFS Function:	Slave without Radar detection
TPC Function:	Without TPC function
Antenna Type:	PCB Antenna
Antenna Gain:	Antenna 1:5.81dBi Antenna 2:4.38dBi

### **Declaration of EUT Family Grouping:**

Model No.: HP4619, HP46D, HP4619-BR, HP4619-ES, HP4619-CL, HP4619-AR, HP4619-CO, HP4619-PE

Only the model HP4619 was tested, since according to the declaration from the applicant, the electrical circuit design, PCB layout, components used, internal wiring and functions were identical for all the above models, with only difference on model No. and trade mark.

### 3.3 Separation Distance

Minimum test separation distance: 20cm

Remark: This minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx.and">http://www.sgs.com/en/Terms-and-Conditions.for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions-and-Conditions-and-Cond

Fuyong lab. Xinlong TechnoPark, Fenglang Road, Fuyong Subdishrid, Bad'an, Shenzhen, China 518103 t (86-755) 88663988 f (86-755) 26710594 www.sgsgroup.com.cn 中国·深圳·宝安区福永街道风塘大道鑫龙科技园福永实验室 邮编: 518103 t (86-755) 88663988 f (86-755) 26710594 sgs.china@sgs.com



SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR220700026806

Page: 6 of 14

### 3.4 Test Location

All tests were performed at:

Compliance Certification Services (Kunshan) Inc. Shenzhen branch.

Fuyong lab. Xinlong TechnoPark, Fengtang Road, Fuyong Subdistrict, Bao'an, Shenzhen, China Tel: +86 755 8866 3988 Fax: +86 755 2671 0594

No tests were sub-contracted.

### 3.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

A2LA (Certificate No. 6606.01)

Compliance Certification Services (Kunshan) Inc. Shenzhen branch is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 6606.01.

FCC –Designation Number: CN1322

Compliance Certification Services (Kunshan) Inc. Shenzhen branch has been recognized as an accredited testing laboratory.

Designation Number: CN1322. Test Firm Registration Number: 718073

Innovation, Science and Economic Development Canada

Compliance Certification Services (Kunshan) Inc. Shenzhen branch has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0129.

IC#: 28189.

### 3.6 Deviation from Standards

None

### 3.7 Abnormalities from Standard Conditions

None



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx.and">http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx.and</a>, for electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx.">http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx.</a></a>
Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest extend of the law Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

\*\*Attention: To check the authenticity of testing finspection report & certificate, please contact us at telephone: (86-755) 8307 1443, \*\*Attention: To check the authenticity of testing finspection report & certificate, please contact us at telephone: (86-755) 8307 1443, \*\*Termination of the content or appearance of this document is unlawfully and offenders and the prosecuted to the discussion of the content or appearance or the sample of the sample



SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR220700026806

Page: 7 of 14

# 4 FCC Radiofrequency radiation exposure limits

Test exemptions apply for devices used in general population/uncontrolled exposure environments, according to the SAR-based, or MPE-based exemption thresholds.

### 4.1 Blanket 1 mW Blanket Exemption

The 1 mW Blanket Exemption of §1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

The 1-mW blanket exemption applies at separation distances less than 0.5 cm, including where there is no separation. This exemption shall not be used in conjunction with other exemption criteria other than those for multiple RF sources in paragraph §1.1307(b)(3)(ii)(A).

The 1-mW exemption is independent of service type and covers the full range of 100 kHz to 100 GHz, but it shall not be used in conjunction with other exemption criteria or in devices with higher-power transmitters operating in the same time-averaging period. Exposure from such higher-power transmitters would invalidate the underlying assumption that exposure from the lower-power transmitter is the only contributor to SAR in the relevant volume of tissue.

## 4.2 MPE-based Exemption

General frequency and separation-distance dependent MPE-based effective radiated power (ERP) thresholds are in Table B.1 [Table 1 of §1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table B.1—Thresholds For Single RF Sources Subject to Routine Environmental Evaluation

RF Source Frequency			Minimum Distance			Threshold ERP
f∟ MHz		f <sub>H</sub> MHz	λ∟ / 2π		λн / 2π	W
0.3	_	1.34	159 m	_	35.6 m	1,920 R <sup>2</sup>
1.34	_	30	35.6 m	_	1.6 m	3,450 R <sup>2</sup> /f <sup>2</sup>
30	_	300	1.6 m	_	159 mm	3.83 R <sup>2</sup>
300	_	1,500	159 mm	_	31.8 mm	0.0128 R <sup>2</sup> f
1,500	_	100,000	31.8 mm	_	0.5 mm	19.2R <sup>2</sup>

Subscripts L and H are low and high; λ is wavelength.

From §1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns.

The table applies to any RF source (i.e. single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits. These criteria apply at separation distances from any part of the radiating structure of at least  $\lambda/2\pi$ . The thresholds are





SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR220700026806

Page: 8 of 14

based on the general population MPE limits with a single perfect reflection, outside of the reactive near-field, and in the main beam of the radiator.

For mobile devices that are not exempt per Table B.1 [Table 1 of §1.1307(b)(1)(i)(C)] at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in §1.1310 is necessary if the ERP of the device is greater than *ERP*<sub>20cm</sub> in Formula (B.1) [repeated from §2.1091(c)(1); also in §1.1307(b)(1)(i)(B)].

$$P_{\rm th} \ ({\rm mW}) = ERP_{\rm 20 \ cm} \ ({\rm mW}) = \begin{cases} 2040f & 0.3 \ {\rm GHz} \le f < 1.5 \ {\rm GHz} \\ \\ 3060 & 1.5 \ {\rm GHz} \le f \le 6 \ {\rm GHz} \end{cases} \eqno(B.1)$$

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of  $\lambda/4$  or if the antenna gain is less than that of a half-wave dipole.

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

Limit calculation							
Frequency range	Frequency(MHz)	R(λ/2π)(m)	Threshold ERP(W)				
300~1500MHz	915	0.0522	0.032				
1500~100000MHz	2480	0.0193	0.007				

### 4.3 SAR-based Exemption

SAR-based thresholds are derived based on frequency, power, and separation distance of the RF source. The formula defines the thresholds in general for either available maximum time-averaged power or maximum time-averaged ERP, whichever is greater.

If the ERP of a device is not easily determined, such as for a portable device with a small form factor, the applicant may use the available maximum time-averaged power exclusively if the device antenna or radiating structure does not exceed an electrical length of  $\lambda/4$ .

As for devices with antennas of length greater than  $\lambda/4$  where the gain is not well defined, but always less than that of a half-wave dipole (length  $\lambda/2$ ), the available maximum time-averaged power generated by the device may be used in place of the maximum time-averaged ERP, where that value is not known.

The separation distance is the smallest distance from any part of the antenna or radiating structure for all persons, during operation at the applicable ERP. In the case of mobile or portable devices, the separation distance is from the outer housing of the device where it is closest to the antenna.





SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR220700026806

Page: 9 of 14

The SAR-based exemption formula of  $\S1.1307(b)(3)(i)(B)$ , repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold  $P_{th}$  (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive).  $P_{th}$  is given by Formula (B.2).

$$P_{\text{th}} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \le 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \le 40 \text{ cm} \end{cases}$$
(B. 2)

where

$$x = -\log_{10}\left(\frac{60}{ERP_{20}\operatorname{cm}\sqrt{f}}\right)$$

and f is in GHz, d is the separation distance (cm), and  $ERP_{20cm}$  is per Formula (B.1).





SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR220700026806

Page: 10 of 14

Example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

								<u>,                                      </u>		
Frequency	Distance(mm)									
(MHz)	5	10	15	20	25	30	35	40	45	50
300	39	65	88	110	129	148	166	184	201	217
450	22	44	67	89	112	135	158	180	203	226
835	9	25	44	66	90	116	145	175	207	240
1900	3	12	26	44	66	92	122	157	195	236
2450	3	10	22	38	59	83	111	143	179	219
3600	2	8	18	32	49	71	96	125	158	195
5800	1	6	14	25	40	58	80	106	136	169

Limit calculation						
Frequency range(GHz)	Frequency(GHz)	Χ	Distance(cm)	Pth (mW)		
0.3~1.5	0.915	1.474	0.5	8.133		
1.5~6	2.48	1.905	0.5	2.717		



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx.and">http://www.sgs.com/en/Terms-and-Conditions.aspx.and</a>, for electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions-and-Conditions-and



SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR220700026806

Page: 11 of 14

## 5 Measurement and Calculation

## 5.1 Maximum transmit power

### For BT:

The Power Data is based on the RF Test Report FYCR220700026802.

Antenna Gain: 4.83dBi

Output Power Into Antenna & RF Exposure Evaluation Distance:

Frequency	EIRP [dBm]	EIRP (mW)
2402	10.26	10.62

### For BLE:

The Power Data is based on the RF Test Report FYCR220700026803.

Antenna Gain: 4.83dBi

Output Power Into Antenna & RF Exposure Evaluation Distance:

Frequency	EIRP [dBm]	EIRP (mW)
2402	7.5	5.62

#### For 2.4G WIFI:

The Power Data is based on the RF Test Report FYCR220700026804.

Antenna Gain: Antenna 1:2.03dBi Antenna 2:4.83dBi Directional gain: 6.55dBi.

Output Power Into Antenna & RF Exposure Evaluation Distance:

### For MIMO:

Frequency	EIRP [dBm]	EIRP (mW)
2412	20.29	106.91





SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR220700026806

Page: 12 of 14

### For 5G WIFI:

The Power Data is based on the RF Test Report FYCR220700026805.

Antenna Gain: Antenna 1:5.81dBi Antenna 2:4.38dBi Directional gain: 8.13dBi.

Output Power Into Antenna & RF Exposure Evaluation Distance:

#### For MIMO:

Frequency	EIRP [dBm]	EIRP (mW)
5825	25.03	318.42

Note: Refer to report No. FYCR220700026805 for EUT test Max Power Value.

The distance r (4th column) calculated from the Fries transmission formula is far greater than 20 cm separation requirement.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx">http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Document.aspx</a>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction document. This document cannot be reproduced except in full, without prior written approval of the Company, Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are tested for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, \*\*Certificate, Please contact us at telephone: (86-755) 8307 1443, \*\*Certificate, Please contact us at telephone: (86-755) 8307 1443, \*\*Certificate, Please contact us at telephone: (86-755) 8307 1443, \*\*Certificate, Please contact us at telephone: (86-755) 8307 1443, \*\*Certificate, Please contact us at telephone: (86-755) 8307 1443, \*\*Certificate, Please contact us at telephone: (86-755) 8307 1443, \*\*Certificate, Please contact us at telephone: (86-755) 8307 1443, \*\*Certificate, Please contact us at telephone: (86-755) 8307 1443, \*\*Certificate, Please contact us at telephone: (86-755) 8307 1443, \*\*Certificate, Please contact us at telephone: (86-755) 8307 1443, \*\*Certificate, P



SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR220700026806

Page: 13 of 14

### 5.2 RF Exposure Calculation

**Remark**: we used the maximum power between the conducted power and ERP/EIRP to perform RF exposure exemption evaluation.

#### For BT:

The Max EIRP is 10.62mW. The best case gain of the antenna is 4.83dBi.

	Evaluation method	Exempt Limit(mW)	Verdict
	Blanket 1 mW Blanket Exemption	1mW	N/A
	MPE-based Exemption(ERP)	7mW(ERP)	N/A
$\boxtimes$	SAR-based Exemption( $P_{ ext{th}}$ )	3060	Yes

### For BLE:

The Max EIRP is 5.62mW. The best case gain of the antenna is 4.83dBi.

	Evaluation method	Exempt Limit(mW)	Verdict
	Blanket 1 mW Blanket Exemption	1mW	N/A
	MPE-based Exemption(ERP)	7mW(ERP)	N/A
$\boxtimes$	SAR-based Exemption( $P_{ ext{th}}$ )	3060	Yes

#### For 2.4 WIFI transmitter:

The Max EIRP is 106.91mW. The best case gain Antenna 1:2.03dBi Antenna 2:4.83dBi Directional gain: 6.55dBi.

	Evaluation method	Exempt Limit(mW)	Verdict
	Blanket 1 mW Blanket Exemption	1mW	N/A
	MPE-based Exemption(ERP)	7mW(ERP)	N/A
$\boxtimes$	SAR-based Exemption( $P_{th}$ )	3060	Yes

#### For 5G WIFI transmitter:

The Max EIRP is 318.42mW. The best case gain Antenna 1:5.81dBi Antenna 2:4.38dBi Directional gain: 8.13dBi.

Evaluation method	Exempt Limit(mW)	Verdict
Blanket 1 mW Blanket Exemption	1mW	N/A
MPE-based Exemption(ERP)	7mW(ERP)	N/A
SAR-based Exemption( $P_{ m th}$ )	3060	Yes

So, the device is to qualify for SAR test exemption, the exemption report is in lieu of the SAR report.





SZCCS-TRF-01 Rev. A/0 Aug01,2022

Report No.: FYCR220700026806

Page: 14 of 14

### Exposure condition for simultaneous transmission operations

Either SAR-based or MPE-based exemption may be considered for test exemption for fixed, mobile, or portable device exposure conditions; therefore, the contributions from each exemption in conjunction with the measured SAR (Evaluatedk term) shall be used to determine exemption for simultaneous transmission according to Formula (C.1) [repeated from § 1.1307(b)(3)(ii)(B)].

$$\sum_{i=1}^{a} \frac{P_i}{P_{\text{th},i}} + \sum_{j=1}^{b} \frac{ERP_j}{ERP_{\text{th},j}} + \sum_{k=1}^{c} \frac{Evaluated_k}{Exposure\ Limit_k} \le 1$$
 (C. 1)

#### Remark:

- a -number of fixed, mobile, or portable RF sources claiming exemption using the §1.1307(b)(3)(i)(B) formula for Pth, including existing exempt transmitters and those being added.
- b -number of fixed, mobile, or portable RF sources claiming exemption using the applicable § 1.1307(b)(3)(i)(C) Table 1 formula for Threshold ERP, including existing exempt transmitters and those being added.
- c -number of existing fixed, mobile, or portable RF sources with known evaluation for the specified minimum distance.
- Pi -the available maximum time-averaged power or the ERP, whichever is greater, for fixed, mobile, or portable RF source i at a distance between 0.5 cm and 40 cm (inclusive).
- Pth,i -the exemption threshold power (Pth) according to the § 1.1307(b)(3)(i)(B) formula for fixed, mobile, or portable RF source i.

ERPj -the available maximum time-averaged power or the ERP, whichever is greater, of fixed, mobile, or portable RF source j. ERPth,j -exemption threshold ERP for fixed, mobile, or portable RF source j, at a distance of at least  $\lambda/2\pi$ , according to the applicable § 1.1307(b)(3)(i)(C) Table 1 formula at the location in question.

Evaluated<sub>k</sub> -the maximum reported SAR or MPE of fixed, mobile, or portable RF source k either in the device or at the transmitter site from an existing evaluation.

Exposure Limit<sub>k</sub> -either the general population/uncontrolled maximum permissible exposure (MPE) or specific absorption rate (SAR) limit for each fixed, mobile, or portable sources, as applicable

Because Wi-Fi power is greater than BT/BLE transmitting power, so the maximum simultaneous transmitting is two antennas transmitting Wi-Fi signal at the same time.

The sum of the ratios = 318.42/3060=0.104<1

Therefore, the device is to qualify for simultaneous transmission SAR test exemption, the exemption report is in lieu of the SAR report.

### -- End of the Report--



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <a href="http://www.sgs.com/en/Terms-and-Conditions.aspx.and">http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Documents</a>, subject to Terms and Conditions for Electronic Documents at <a href="http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx.">http://www.sgs.com/en/Terms-and-Conditions/Terms-en-Document.aspx.</a>
Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Cilent's instructions, if any. The Company's sole responsibility is to its Cilent and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawfull and offenders may be prosecuted to the fullest extend of the law Luless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

\*\*Attention:\*\*To check the authenticity of testing (inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, \*\*Attention:\*\*To check the authenticity of testing (inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, \*\*To check the authenticity of testing (inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, \*\*To check the authenticity of testing (inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, \*\*To check the authenticity of testing (inspection report & certificate, please