



Hermon Laboratories Ltd. Harakevet Industrial Zone, Binyamina 30500, Israel

Tel. +972-4-6288001 Fax. +972-4-6288277

E-mail: mail@hermonlabs.com

TEST REPORT

ACCORDING TO: FCC 47CFR part 15 subpart C § 15.247 (DTS) and subpart B, RSS-247 issue 1, RSS-Gen issue 4, ICES-003 Issue 5:2012

FOR:

Visonic Ltd.
Wireless PIR Detector

Model: MP-840

FCC ID:WP3MP840

IC:1467C-MP840

This report is in conformity with ISO/ IEC 17025. The "A2LA Accredited" symbol endorsement applies only to the tests and calibrations that are listed in the scope of Hermon Laboratories accreditation. The test results relate only to the items tested. This test report shall not be reproduced in any form except in full with the written approval of Hermon Laboratories Ltd.

Report ID: VISRAD_FCC.27985.docx

Date of Issue: 20-Apr-16



Table of contents

1	Applicant information	3
2	Equipment under test attributes	3
3	Manufacturer information	3
4	Test details	3
5	Tests summary	4
6	EUT description	5
6.1	General information	5
6.2	Test configuration	5
6.3	Changes made in the EUT	5
6.4	Transmitter characteristics	6
7	Transmitter tests according to 47CFR part 15 subpart C and RSS-247 requirements	7
7.1	Minimum 6 dB bandwidth	7
7.2	Peak output power	11
7.3	Field strength of spurious emissions	16
7.4	Band edge radiated emissions	44
7.5	Peak spectral power density	49
7.6	Antenna requirements	54
8	Unintentional emissions	55
8.1	Radiated emission measurements	55
9	APPENDIX A Test equipment and ancillaries used for tests	60
10	APPENDIX B Measurement uncertainties	61
11	APPENDIX C Test laboratory description	62
12	APPENDIX D Specification references	62
13	APPENDIX E Test equipment correction factors	63
14	APPENDIX F Abbreviations and acronyms	72





1 Applicant information

Client name: Visonic Ltd.

Address: 24 Habarzel street, Tel Aviv 69710, Israel

 Telephone:
 +972 3645 6832

 Fax:
 +972 3645 6788

 E-mail:
 zurir@tycoint.com

 Contact name:
 Mr. Zuri Rubin

2 Equipment under test attributes

Product name: Wireless PIR Detector

Product type: Transceiver
Model(s): MP-840
Serial number: 0916582224
Hardware version: 90-208026
Software release: JS-703129
Receipt date 02-Feb-16

3 Manufacturer information

Manufacturer name: Visonic Ltd.

Address: 24 Habarzel street, Tel Aviv 69710, Israel

 Telephone:
 +972 3645 6832

 Fax:
 +972 3645 6788

 E-Mail:
 zurir@tycoint.com

 Contact name:
 Mr. Zuri Rubin

4 Test details


Project ID: 27985

Location: Hermon Laboratories Ltd. Harakevet Industrial Zone, Binyamina 30500, Israel

Test started: 02-Feb-16 **Test completed:** 08-Mar-16

Test specification(s): FCC 47CFR part 15 subpart C § 15.247 (DTS);

RSS-247 issue 1, RSS-Gen issue 4





5 Tests summary

Test	Status
Transmitter characteristics	
FCC section 15.247(a)2 / RSS-247 section 5.2(1), 6 dB bandwidth	Pass
FCC section 15.247(b)3/ RSS-247 section 5.4(4), Peak output power	Pass
FCC section 15.247(i) / RSS-102 section 2.5.2, RF exposure	Pass, the exhibit to the application of certification is provided
FCC section 15.247(d) / RSS-247 section 5.5, Radiated spurious emissions	Pass
FCC section 15.247(d)/ RSS-247 section 5.5, Emissions at band edges	Pass
FCC section 15.247(e) / RSS-247 section 5.2(2), Peak power density	Pass
FCC section 15.203 / RSS-Gen section 8.3, Antenna requirement	Pass
FCC section 15.207(a) / RSS-Gen section 8.8, Conducted emission	Not required
Unintentional emissions	
FCC section 15.107/ ICES-003, Section 6.1, Class B, Conducted emission at AC power port	Not required
FCC section 15.109/ RSS-Gen section 7.1.2 /ICES-003, Section 6.2, Class B, Radiated emission	Pass

Testing was completed against all relevant requirements of the test standard. The results obtained indicate that the product under test complies in full with the requirements tested.

The test results relate only to the items tested. Pass/ fail decision was based on nominal values.

	Name and Title	Date	Signature
Tested by:	Mrs. E. Pitt, test engineer	March 8, 2016	H
Reviewed by:	Mrs. M. Cherniavsky, certification engineer	March 17, 2016	Chu
Approved by:	Mr. M. Nikishin, EMC and Radio group manager	April 19, 2016	ff




6 EUT description

6.1 General information

The EUT, MP-840, is a wireless PIR detector with RF module operating@2.4 GHz.

6.2 Test configuration



6.3 Changes made in the EUT

No changes were implemented in the EUT during the testing.





6.4 Transmitter characteristics

Type of equipment							
	Stand-alone (Equipment with or without its own control provisions)						
	Combined equipment (Equipment where the radio part is fully integrated within another type of equipment)						
Plug-in card (Equipment intended for a variety of host systems)							
ntended use Condition of use							
fixed Always at a d	istance more tha	n 2 m from all people					
X mobile Always at a d	istance more tha	n 20 cm from all people					
portable May operate a	at a distance clos	ser than 20 cm to huma	n body				
Assigned frequency ranges	2400 -2483.5 N	ЛНz					
Operating frequencies	2405-2480 MH	Z					
Maximum rated output navor	At transmitter 5	$50~\Omega$ RF output connect	or	dBm			
Maximum rated output power	Peak output po	ower		16.28 dBm			
	X No						
		continuous	variable				
s transmitter output power variable?	V	stepped va	ariable with stepsize	dB			
	Yes	minimum RF power		dBm			
		maximum RF power		dBm			
Antenna connection							
unique coupling		V internal	with temporary RF	connector			
unique coupling star	ndard connector	X integral	X without temporary	ary RF connector			
Antenna/s technical characteristics							
Type Manufac	cturer	Model number	Gain				
Integral Visonic		Printed	3 dBi				
Transmitter aggregate data rate							
Type of modulation	00	QPSK					
Transmitter power source							
X Battery Nominal rated vol	tage 3	VDC Battery	type Lithium CR123				
DC Nominal rated voltage							
AC mains Nominal rated vol	tage	Freque	ncy				



Test specification:	FCC section 15.247(a)(2), RSS-247 section 5.2(1), 6 dB bandwidth					
Test procedure:	ANSI C63.10 section 11.8.1					
Test mode:	Compliance	Verdict: PASS				
Date(s):	02-Feb-16	verdict:	PASS			
Temperature: 23 °C	Air Pressure: 1021 hPa	Relative Humidity: 54 %	Power Supply: Battery			
Remarks:		-	-			

7 Transmitter tests according to 47CFR part 15 subpart C and RSS-247 requirements

7.1 Minimum 6 dB bandwidth

7.1.1 General

This test was performed to measure the 6 dB bandwidth of the EUT carrier frequency. Specification test limits are given in Table 7.1.1, Table 7.1.2.

Table 7.1.1 The 6 dB bandwidth limits

Assigned frequency, MHz	Modulation envelope reference points*, dBc	Minimum bandwidth, kHz
902.0 - 928.0		
2400.0 - 2483.5	6.0	>500.0
5725.0 - 5850.0		

^{* -} Modulation envelope reference points provided in terms of attenuation below the peak of modulated carrier.

Table 7.1.2 The 99% bandwidth limits

Assigned frequency, MHz	Modulation envelope reference points	Limit, kHz
902.0 - 928.0		
2400.0 – 2483.5	99%	>500.0
5725.0 – 5850.0		

7.1.2 Test procedure

- **7.1.2.1** The EUT was set up as shown in Figure 7.1.1, energized and its proper operation was checked.
- **7.1.2.2** The EUT was set to transmit modulated carrier.
- **7.1.2.3** The transmitter minimum 6 dB bandwidth was measured with spectrum analyzer as frequency delta between reference points on modulation envelope and provided in Table 7.1.3 and the associated plots.
- **7.1.2.4** The 99% bandwidth results are provided in Table 7.1.4 and the associated plots.

Figure 7.1.1 The 6 dB bandwidth test setup





Test specification: FCC section 15.247(a)(2), RSS-247 section 5.2(1), 6 dB bandwidth

Test procedure: ANSI C63.10 section 11.8.1

Test mode: Compliance Verdict: PASS

Date(s): 02-Feb-16

Temperature: 23 °C Air Pressure: 1021 hPa Relative Humidity: 54 % Power Supply: Battery

Remarks:

Table 7.1.3 The 6 dB bandwidth test results

ASSIGNED FREQUENCY BAND: 2400-2483.5 MHz

DETECTOR USED:

SWEEP MODE:

Max hold

SWEEP TIME:

RESOLUTION BANDWIDTH:

VIDEO BANDWIDTH:

MODULATION:

BIT RATE:

Peak

Max hold

Auto

100 kHz

VIDEO BANDWIDTH:

3 RBW

OQPSK

BIT RATE:

250 kbps

Carrier frequency, MHz	6 dB bandwidth, kHz	Limit, kHz	Margin, kHz	Verdict
2405	1592	500	1092	Pass
2445	1594	500	1094	Pass
2475	1593	500	1093	Pass
2480	1548	500	1048	Pass

Table 7.1.4 The 99% bandwidth test results

ASSIGNED FREQUENCY BAND: 2400-2483.5 MHz

DETECTOR USED: Peak
SWEEP MODE: Max hold
SWEEP TIME: Auto
RESOLUTION BANDWIDTH: 100 kHz
VIDEO BANDWIDTH: 3 RBW
MODULATION: OQPSK
BIT RATE: 250 kbps

Carrier frequency, MHz	99% bandwidth, kHz	Limit, kHz	Margin, kHz	Verdict
2405	2442	500	1942	Pass
2445	2442	500	1942	Pass
2475	2447	500	1947	Pass
2480	2429	500	1929	Pass

Reference numbers of test equipment used


HL 521	HL 1984	HL 4353	HL 4278			

Full description is given in Appendix A.




Test specification:	FCC section 15.247(a)(2), RSS-247 section 5.2(1), 6 dB bandwidth					
Test procedure:	ANSI C63.10 section 11.8.1					
Test mode:	Compliance	Verdict: PASS				
Date(s):	02-Feb-16					
Temperature: 23 °C	Air Pressure: 1021 hPa	Relative Humidity: 54 %	Power Supply: Battery			
Remarks:		-	•			

Plot 7.1.1 The occupied bandwidth test result at low frequency ch.11




Plot 7.1.2 The occupied bandwidth test result at mid frequency ch.19






Test specification:	FCC section 15.247(a)(2), RSS-247 section 5.2(1), 6 dB bandwidth					
Test procedure:	ANSI C63.10 section 11.8.1					
Test mode:	Compliance	Verdict: PASS				
Date(s):	02-Feb-16					
Temperature: 23 °C	Air Pressure: 1021 hPa	Relative Humidity: 54 %	Power Supply: Battery			
Remarks:		-	-			

Plot 7.1.3 The occupied bandwidth test result at high frequency ch.25



Plot 7.1.4 The occupied bandwidth test result at high frequency ch.26





Report ID: VISRAD_FCC.27985.docx

Date of Issue: 20-Apr-16

Test specification:	FCC section 15.247(b)(3), RSS-247 section 5.4(4), Peak output power (radiated)					
Test procedure:	ANSI C63.10 section 11.9					
Test mode:	Compliance	Verdict:	PASS			
Date(s):	02-Feb-16	verdict.	PASS			
Temperature: 23 °C	Air Pressure: 1021 hPa	Relative Humidity: 54 %	Power Supply: Battery			
Remarks:						

7.2 Peak output power

7.2.1 General

This test was performed to measure the maximum peak output power radiated by transmitter. Specification test limits are given in Table 7.2.1.

Table 7.2.1 Peak output power limits

Assigned frequency	Maximum antenna	Peak output power*		Equivalent field strength
range, MHz	gain, dBi	W	dBm	limit @ 3m, dB(μV/m)**
902.0 - 928.0				
2400.0 - 2483.5	6.0	1.0	30.0	131.2
5725.0 - 5850.0				

^{*-} The limit is provided in terms of conducted RF power at the antenna connector. If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power limit shall be reduced below the stated value as follows:

by 1 dB for every 3 dB that the directional gain of antenna exceeds 6 dBi for fixed point-to-point transmitters operate in 2400-2483.5 MHz band;

without any corresponding reduction for fixed point-to-point transmitters operate in 5725-5850 MHz band; by the amount in dB that the directional gain of antenna exceeds 6 dBi for the rest of transmitters.

7.2.2 Test procedure

- **7.2.2.1** The EUT was set up as shown in Figure 7.2.1, energized and its proper operation was checked.
- **7.2.2.2** The EUT was adjusted to produce maximum available to end user RF output power.
- **7.2.2.3** The resolution bandwidth of spectrum analyzer was set wider than 6 dB bandwidth of the EUT and the field strength of the EUT carrier frequency was measured with antenna connected to spectrum analyzer/ EMI receiver. To find maximum radiation the turntable was rotated 360⁰ and the measuring antenna height was swept in both vertical and horizontal polarizations.
- **7.2.2.4** The maximum field strength of the EUT carrier frequency was measured as provided in Table 7.2.2 and associated plots.
- **7.2.2.5** The maximum peak output power was calculated from the field strength of carrier as follows:

$$P = (E \times d)^2 / (30 \times G),$$

where P is the peak output power in W, E is the field strength in V/m, d is the test distance and G is the transmitter numeric antenna gain over an isotropic radiator.

The above equation was converted in logarithmic units for 3 m test distance:

Peak output power in dBm = Field strength in dB(μ V/m) - Transmitter antenna gain in dBi – 95.2 dB


7.2.2.6 The worst test results (the lowest margins) were recorded in Table 7.2.2.

^{**-} Equivalent field strength limit was calculated from the peak output power as follows: E=sqrt(30×P×G)/r, where P is peak output power in Watts, r is antenna to EUT distance in meters and G is transmitter antenna gain in dBi.



Test specification:	FCC section 15.247(b)(3), RSS-247 section 5.4(4), Peak output power (radiated)					
Test procedure:	ANSI C63.10 section 11.9					
Test mode:	Compliance	Verdict:	PASS			
Date(s):	02-Feb-16	verdict.	FASS			
Temperature: 23 °C	Air Pressure: 1021 hPa	Relative Humidity: 54 %	Power Supply: Battery			
Remarks:						

Figure 7.2.1 Setup for carrier field strength measurements





Report ID: VISRAD_FCC.27985.docx

Date of Issue: 20-Apr-16

Test specification:	FCC section 15.247(b)(3), RSS-247 section 5.4(4), Peak output power (radiated)					
Test procedure:	ANSI C63.10 section 11.9					
Test mode:	Compliance	Verdict:	PASS			
Date(s):	02-Feb-16	verdict.	FASS			
Temperature: 23 °C	Air Pressure: 1021 hPa	Relative Humidity: 54 %	Power Supply: Battery			
Remarks:						

Table 7.2.2 Peak output power test results

ASSIGNED FREQUENCY: 2400-2483.5 MHz

TEST DISTANCE: 3 m

TEST SITE: Semi anechoic chamber

EUT HEIGHT: 1.5 m DETECTOR USED: Peak

TEST ANTENNA TYPE: Biconilog (30 MHz – 1000 MHz)

Double ridged guide (above 1000 MHz)

MODULATION:
BIT RATE:
250 kbps
TRANSMITTER OUTPUT POWER SETTINGS:
Maximum
DETECTOR USED:
EUT 6 dB BANDWIDTH:
RESOLUTION BANDWIDTH:
VIDEO BANDWIDTH:
3 MHz
VIDEO BANDWIDTH:
3 MHz

Frequency, MHz	Field strength, dB(μV/m)	Antenna polarization	Antenna height, m	Azimuth, degrees*	EUT antenna gain, dBi	Peak output power, dBm**	Limit, dBm	Margin, dB***	Verdict
2405	113.93	Horizontal	1.8	0	3	15.73	30	-14.27	Pass
2445	113.48	Horizontal	1.3	0	3	15.28	30	-14.72	Pass
2475	114.48	Horizontal	1.3	0	3	16.28	30	-13.72	Pass
2480	105.36	Horizontal	1.8	0	3	7.16	30	-22.84	Pass

^{*-} EUT front panel refer to 0 degrees position of turntable.

Reference numbers of test equipment used

_			= =			
	HL 0521	HL 1984	HL 4278	HL 4353		

Full description is given in Appendix A.

^{**-} Peak output power was calculated from the field strength of carrier as follows: $P = (E \times d)^2/(30 \times G)$, where P is the peak output power in W, E is the field strength in V/m, d is the test distance in meters and G is the transmitter numeric antenna gain over an isotropic radiator. The above equation was converted in logarithmic units for 3 m test distance: Peak output power in dBm = Field strength in dB(μ V/m) - Transmitter antenna gain in dBi – 95.2 dB

^{***-} Margin = Peak output power – specification limit.







Test specification: FCC section 15.247(b)(3), RSS-247 section 5.4(4), Peak output power (radiated) ANSI C63.10 section 11.9 Test procedure: Compliance Test mode: **PASS** Verdict: 02-Feb-16 Date(s): Temperature: 23 °C Air Pressure: 1021 hPa Relative Humidity: 54 % Power Supply: Battery Remarks:

Plot 7.2.1 Field strength of carrier at low frequency ch.11

ANTENNA POLARIZATION: Vertical ANTENNA POLARIZATION: Horizontal



Plot 7.2.2 Field strength of carrier at mid frequency ch.19








Test specification: FCC section 15.247(b)(3), RSS-247 section 5.4(4), Peak output power (radiated) ANSI C63.10 section 11.9 Test procedure: Compliance Test mode: **PASS** Verdict: 02-Feb-16 Date(s): Temperature: 23 °C Air Pressure: 1021 hPa Relative Humidity: 54 % Power Supply: Battery Remarks:


Plot 7.2.3 Field strength of carrier at high frequency ch.25


ANTENNA POLARIZATION: Vertical ANTENNA POLARIZATION: Horizontal



Plot 7.2.4 Field strength of carrier at high frequency ch.26









Test specification:	FCC section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions						
Test procedure:	ANSI C63.10 section 11.12.1						
Test mode:	Compliance	Verdict:	PASS				
Date(s):	02-Feb-16 - 08-Mar-16	verdict:	PASS				
Temperature: 23 °C	Air Pressure: 1021 hPa	Relative Humidity: 54 %	Power Supply: Battery				
Remarks:			-				

7.3 Field strength of spurious emissions

7.3.1 General

This test was performed to measure field strength of spurious emissions from the EUT. Specification test limits are given in Table 7.3.1.

Table 7.3.1 Radiated spurious emissions limits

Frequency, MHz	Field streng	th at 3 m within res dB(μV/m)*	Attenuation of field strength of spurious versus	
r requerioy, mile	Peak	Quasi Peak	Average	carrier outside restricted bands, dBc***
0.009 - 0.090	148.5 – 128.5	NA	128.5 – 108.5**	
0.090 - 0.110	NA	108.5 – 106.8**	NA	
0.110 - 0.490	126.8 – 113.8	NA	106.8 - 93.8**	
0.490 - 1.705		73.8 – 63.0**		
1.705 – 30.0*		69.5		20.0
30 – 88	NA	40.0	NA	20.0
88 – 216	INA	43.5	INA	
216 – 960		46.0		
960 - 1000		54.0		
1000 – 10 th harmonic	74.0	NA	54.0	

^{*-} The limit for 3 m test distance was calculated using the inverse square distance extrapolation factor as follows: $\lim_{S_2} = \lim_{S_1} + 40 \log (S_1/S_2)$,

where S_1 and S_2 – standard defined and test distance respectively in meters.

7.3.2 Test procedure for spurious emission field strength measurements in 9 kHz to 30 MHz band

- 7.3.2.1 The EUT was set up as shown in Figure 7.3.1, energized and the performance check was conducted.
- **7.3.2.2** The specified frequency range was investigated with antenna connected to spectrum analyzer/ EMI receiver. To find maximum radiation the turntable was rotated 360⁰ and the measuring antenna was rotated around its vertical axis.
- 7.3.2.3 The worst test results (the lowest margins) were recorded and shown in the associated plots.

7.3.3 Test procedure for spurious emission field strength measurements above 30 MHz

- 7.3.3.1 The EUT was set up as shown in Figure 7.3.2, energized and the performance check was conducted.
- **7.3.3.2** The specified frequency range was investigated with antenna connected to spectrum analyzer/ EMI receiver. To find maximum radiation the turntable was rotated 360⁰, the measuring antenna height was changed from 1 to 4 m, its polarization was switched from vertical to horizontal.
- **7.3.3.3** The worst test results (the lowest margins) were recorded and shown in the associated plots.

^{**-} The limit decreases linearly with the logarithm of frequency.

^{*** -} The field strength limits applied from the lowest radio frequency generated in the device, without going below 9 kHz up to the tenth harmonic of the highest fundamental frequency.



Test specification:	FCC section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions					
Test procedure:	ANSI C63.10 section 11.12.1					
Test mode:	Compliance	Verdict:	PASS			
Date(s):	02-Feb-16 - 08-Mar-16	verdict:	PASS			
Temperature: 23 °C	Air Pressure: 1021 hPa	Relative Humidity: 54 %	Power Supply: Battery			
Remarks:						

Figure 7.3.1 Setup for spurious emission field strength measurements below 30 MHz





Figure 7.3.2 Setup for spurious emission field strength measurements above 30 MHz







Test specification:	FCC section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions					
Test procedure:	ANSI C63.10 section 11.12.1					
Test mode:	Compliance	Verdict:	PASS			
Date(s):	02-Feb-16 - 08-Mar-16	verdict:	PASS			
Temperature: 23 °C	Air Pressure: 1021 hPa	Relative Humidity: 54 %	Power Supply: Battery			
Remarks:		-	-			

Table 7.3.2 Field strength of emissions outside restricted bands

INVESTIGATED FREQUENCY RANGE: 0.009 -25000 MHz

TEST DISTANCE: 3 m MODULATION: OQPSK BIT RATE: 250 kbps **DUTY CYCLE**: 100 % TRANSMITTER OUTPUT POWER SETTINGS: Maximum **DETECTOR USED:** Peak **RESOLUTION BANDWIDTH:** 100 kHz VIDEO BANDWIDTH: 300 kHz

TIDEO BANDWIDTH. 300 KHZ									
Frequency, MHz	Field strength of spurious, dB(μV/m)	Antenna polarization	Antenna height, m	Azimuth, degrees*	Field strength of carrier, dB(μV/m)	Attenuation below carrier, dBc	Limit, dBc	Margin, dB**	Verdict
Low carrier	frequency, char	nnel 11							
9620	54.86	Horizontal	1.3	20	109.95	55.09	20.0	35.09	Pass
19240	47.57	Horizontal	1.4	70	109.95	62.38	20.0	42.38	Fa55
Mid carrier f	Mid carrier frequency, channel 19								
9780	57.65	Horizontal	1.3	20	109.59	51.94	20.0	31.94	Pass
19560	51.61	Horizontal	1.4	70	109.59	57.98	20.0	37.98	Pass
High carrier	High carrier frequency, channel 25								
9900	55.91	Horizontal	1.3	30	440.50	54.65	20.0	34.65	D
19800	48.54	Horizontal	1.4	70	110.56	62.02	20.0	42.02	Pass
High carrier	High carrier frequency, channel 26								
	No emissions were found								Pass

^{*-} EUT front panel refers to 0 degrees position of turntable.

^{**-} Margin = Attenuation below carrier – specification limit.



Report ID: VISRAD_FCC.27985.docx

Date of Issue: 20-Apr-16

Test specification:	FCC section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions					
Test procedure:	ANSI C63.10 section 11.12.1					
Test mode:	Compliance	Verdict:	PASS			
Date(s):	02-Feb-16 - 08-Mar-16	verdict:	PASS			
Temperature: 23 °C	Air Pressure: 1021 hPa	Relative Humidity: 54 %	Power Supply: Battery			
Remarks:						

Table 7.3.3 Field strength of spurious emissions above 1 GHz within restricted bands

INVESTIGATED FREQUENCY RANGE: 1000 – 25000 MHz

TEST DISTANCE:

MODULATION:
OQPSK
BIT RATE:
250 kbps
DUTY CYCLE:
100 %
TRANSMITTER OUTPUT POWER SETTINGS:
Maximum
DETECTOR USED:
Peak
RESOLUTION BANDWIDTH:
1000 kHz

REGOLOTION BANDWIDTH:											
F	Anteni	na	A =: 4 l-	Peak field s	strength(VB	SW=3 MHz)	Average	e field stren	gth(VBW=1	0 Hz)	
Frequency, MHz		Height,	Azimuth, degrees*	Measured,	Limit,	Margin,	Measured,	Calculated,	Limit,	Margin,	Verdict
IVITIZ	Polarization	m	uegrees	dB(μV/m)	dB(μV/m)	dB**	dB(μV/m)	dB(μV/m)	$dB(\mu V/m)$	dB***	
Low carrie	r frequency, o	channel [•]	11								
4810	Horizontal	1.2	0	47.12	74	-26.88	36.39	23.82	54	-30.18	Pass
12025	Horizontal	1.4	80	66.83	74	-7.17	57.74	45.17	54	-8.83	rass
Mid carrier	frequency, c	hannel 1	9								
4890	Horizontal	1.2	0	48.21	74	-25.79	38.17	25.60	54	-28.40	Pass
12225	Horizontal	1.4	80	67.77	74	-6.23	58.02	45.45	54	-8.55	F a 5 5
High carrie	r frequency,	channel	25								
4950	Horizontal	1.2	0	49.17	74	-24.83	39.98	27.41	54	-26.59	Pass
12380	Horizontal	14	80	66.58	74	-7.42	57.50	44.93	54	-9.07	rass
High carrie	High carrier frequency, channel 26										
No emissions were found						Pass					

^{*-} EUT front panel refers to 0 degrees position of turntable.

where Calculated field strength = Measured field strength + average factor.

Table 7.3.4 Average factor calculation

Transmission pulse Transmission burst		Transmission train	Average feeter		
Duration, ms	Number of pulses during 100 msec	Duration, ms	Period, ms duration, ms		Average factor, dB
1.96	12	NA	NA	NA	-12.57

^{*-} Average factor was calculated as follows Average factor =20 log (1.96 x 12/100) = -12.57

^{**-} Margin = Measured field strength - specification limit.

^{***-} Margin = Calculated field strength - specification limit,



Test specification: FCC section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions

Test procedure: ANSI C63.10 section 11.12.1

Test mode: Compliance Verdict: PASS

Date(s): 02-Feb-16 - 08-Mar-16

Temperature: 23 °C Air Pressure: 1021 hPa Relative Humidity: 54 % Power Supply: Battery

Remarks:

Table 7.3.5 Field strength of spurious emissions below 1 GHz within restricted bands

ASSIGNED FREQUENCY: 2400-2483.5 MHz INVESTIGATED FREQUENCY RANGE: 0.009 – 1000 MHz

TEST DISTANCE: 3 m

MODULATION: OQPSK

MODULATING SIGNAL: PRBS

BIT RATE: 250 kbps

DUTY CYCLE: 100 %

TRANSMITTER OUTPUT POWER SETTINGS: Maximum

RESOLUTION BANDWIDTH: 0.2 kHz (9 kHz – 150 kHz)

9.0 kHz (150 kHz – 30 MHz) 120 kHz (30 MHz – 1000 MHz)

VIDEO BANDWIDTH: > Resolution bandwidth
TEST ANTENNA TYPE: Active loop (9 kHz – 30 MHz)
Biconilog (30 MHz – 1000 MHz)

Frequency, MHz	Peak emission, dB(μV/m)	Quas Measured emission, dB(μV/m)	i-peak Limit, dB(μV/m)	Margin, dB*	Antenna polariz.	Antenna height, m	Turn-table position**, degrees	Verdict
	No signals were found							Pass

^{*-} Margin = Measured emission - specification limit.

Reference numbers of test equipment used

HL 0446	HL 0604	HL 1984	HL 2780	HL 3347	HL 3818	HL 3901	HL 4278
HL 4338	HL 4353	HL 4932	HL 4933	HL 4956			

Full description is given in Appendix A.

^{**-} EUT front panel refer to 0 degrees position of turntable.



Test specification:	FCC section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions				
Test procedure:	ANSI C63.10 section 11.12.1				
Test mode:	Compliance	- Verdict: PASS			
Date(s):	02-Feb-16 - 08-Mar-16	Verdict:	PASS		
Temperature: 23 °C	Air Pressure: 1021 hPa	Relative Humidity: 54 %	Power Supply: Battery		
Remarks:		-	-		

Table 7.3.6 Restricted bands according to FCC section 15.205

MHz	MHz	MHz	MHz	MHz	GHz
0.09 - 0.11	8.37625 - 8.38675	73 - 74.6	399.9 - 410	2690 - 2900	10.6 - 12.7
0.495 - 0.505	8.41425 - 8.41475	74.8 - 75.2	608 - 614	3260 - 3267	13.25 - 13.4
2.1735 - 2.1905	12.29 - 12.293	108 - 121.94	960 - 1240	3332 - 3339	14.47 - 14.5
4.125 - 4.128	12.51975 - 12.52025	123 - 138	1300 - 1427	3345.8 - 3358	15.35 - 16.2
4.17725 - 4.17775	12.57675 - 12.57725	149.9 - 150.05	1435 - 1626.5	3600 - 4400	17.7 - 21.4
4.20725 - 4.20775	13.36 - 13.41	156.52475 - 156.52525	1645.5 - 1646.5	4500 - 5150	22.01 - 23.12
6.215 - 6.218	16.42 - 16.423	156.7 - 156.9	1660 - 1710	5350 - 5460	23.6 - 24
6.26775 - 6.26825	16.69475 - 16.69525	162.0125 - 167.17	1718.8 - 1722.2	7250 - 7750	31.2 - 31.8
6.31175 - 6.31225	16.80425 - 16.80475	167.72 - 173.2	2200 - 2300	8025 - 8500	36.43 - 36.5
8.291 - 8.294	25.5 - 25.67	240 - 285	2310 - 2390	9000 - 9200	Above 38.6
8.362 - 8.366	37.5 - 38.25	322 - 335.4	2483.5 - 2500	9300 - 9500	ADOVE 36.6

Table 7.3.7 Restricted bands according to RSS-Gen

MHz	MHz	MHz	MHz	MHz	GHz
0.09 - 0.11	8.291 - 8.294	16.80425 - 16.80475	399.9 - 410	3260 - 3267	10.6 - 12.7
2.1735 - 2.1905	8.362 - 8.366	25.5 - 25.67	608 - 614	3332 – 3339	13.25 - 13.4
3.020 - 3.026	8.37625 - 8.38675	37.5 - 38.25	960 – 1427	3345.8 - 3358	14.47 – 14.5
4.125 – 4.128	8.41425 - 8.41475	73 - 74.6	1435 – 1626.5	3500 - 4400	15.35 – 16.2
4.17725 – 4.17775	12.29 – 12.293	74.8 - 75.2	1645.5 - 1646.5	4500 - 5150	17.7 – 21.4
4.20725 – 4.20775	12.51975 – 12.52025	108 – 138	1660 - 1710	5350 - 5460	22.01 - 23.12
5.677 – 5.683	12.57675 – 12.57725	156.52475 – 156.52525	1718.8 - 1722.2	7250 - 7750	23.6 - 24
6.215 - 6.218	13.36 – 13.41	156.7 - 156.9	2200 - 2300	8025 - 8500	31.2 - 31.8
6.26775 - 6.26825	16.42 - 16.423	240 - 285	2310 - 2390	9000 - 9200	36.43 - 36.5
6.31175 - 6.31225	16.69475 - 16.69525	322 - 335.4	2655 - 2900	9300 - 9500	Above 38.6



Test specification:	FCC section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions				
Test procedure:	ANSI C63.10 section 11.12.1				
Test mode:	Compliance	Verdict: PASS			
Date(s):	02-Feb-16 - 08-Mar-16	verdict.	FASS		
Temperature: 23 °C	Air Pressure: 1021 hPa	Relative Humidity: 54 %	Power Supply: Battery		
Remarks:					


Plot 7.3.1 Radiated emission measurements at the low carrier frequency ch.11

TEST SITE: Semi anechoic chamber

TEST DISTANCE: 3 m

ANTENNA POLARIZATION: Vertical & Horizontal






Plot 7.3.2 Radiated emission measurements at the mid carrier frequency ch.19

TEST SITE: Semi anechoic chamber

TEST DISTANCE: 3 m







Test specification:	FCC section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions				
Test procedure:	ANSI C63.10 section 11.12.1				
Test mode:	Compliance	Verdict: PASS			
Date(s):	02-Feb-16 - 08-Mar-16	verdict:	PASS		
Temperature: 23 °C	Air Pressure: 1021 hPa	Relative Humidity: 54 %	Power Supply: Battery		
Remarks:					

Plot 7.3.3 Radiated emission measurements at the high carrier frequency ch.25

TEST SITE: Semi anechoic chamber

TEST DISTANCE: 3 m

ANTENNA POLARIZATION: Vertical & Horizontal








Plot 7.3.4 Radiated emission measurements at the high carrier frequency ch.26

TEST SITE: Semi anechoic chamber

TEST DISTANCE: 3 m








Test specification:	FCC section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions				
Test procedure:	ANSI C63.10 section 11.12.1				
Test mode:	Compliance	Verdict: PASS			
Date(s):	02-Feb-16 - 08-Mar-16	verdict.	FASS		
Temperature: 23 °C	Air Pressure: 1021 hPa	Relative Humidity: 54 %	Power Supply: Battery		
Remarks:					

Plot 7.3.5 Radiated emission measurements from 9 to 150 kHz at the low, mod, high carrier frequency

TEST SITE: Semi anechoic chamber

TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical






Plot 7.3.6 Radiated emission measurements from 0.15 to 30 MHz at the low, mid, high carrier frequency

TEST SITE: Semi anechoic chamber

TEST DISTANCE: 3 m
ANTENNA POLARIZATION: Vertical







Test specification:	FCC section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions				
Test procedure:	ANSI C63.10 section 11.12.1				
Test mode:	Compliance	Verdict: PASS			
Date(s):	02-Feb-16 - 08-Mar-16	verdict.	FASS		
Temperature: 23 °C	Air Pressure: 1021 hPa	Relative Humidity: 54 %	Power Supply: Battery		
Remarks:					

Plot 7.3.7 Radiated emission measurements from 30 to 1000 MHz at the low, mid, high carrier frequency


TEST SITE: Semi anechoic chamber

TEST DISTANCE: 3 m

ANTENNA POLARIZATION: Vertical and Horizontal

(A)

ACTV DET: PEAK MEAS DET: PEAK OP AVG MKR 971.4 MHz 33.58 dBμV/m







Test specification: FCC section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions

Test procedure: ANSI C63.10 section 11.12.1

Test mode: Compliance Verdict: PASS

Date(s): 02-Feb-16 - 08-Mar-16


Temperature: 23 °C Air Pressure: 1021 hPa Relative Humidity: 54 % Power Supply: Battery


Remarks:

Plot 7.3.8 Radiated emission measurements from 1000 to 2900 MHz at the low carrier frequency ch.11

TEST SITE: Semi anechoic chamber

TEST DISTANCE: 3 m









Test specification: FCC section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions

Test procedure: ANSI C63.10 section 11.12.1

Test mode: Compliance Verdict: PASS

Date(s): 02-Feb-16 - 08-Mar-16


Temperature: 23 °C Air Pressure: 1021 hPa Relative Humidity: 54 % Power Supply: Battery


Remarks:

Plot 7.3.9 Radiated emission measurements from 1000 to 2900 MHz at the mid carrier frequency ch.19

TEST SITE: Semi anechoic chamber

TEST DISTANCE: 3 m









(B)

START 1.000 GHz

RL #1F BW 1.0 MHz


Test specification: FCC section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions Test procedure: ANSI C63.10 section 11.12.1 Test mode: Compliance **PASS** Verdict: 02-Feb-16 - 08-Mar-16 Date(s): Relative Humidity: 54 % Temperature: 23 °C Air Pressure: 1021 hPa Power Supply: Battery Remarks:

Plot 7.3.10 Radiated emission measurements from 1000 to 2900 MHz at the high carrier frequency ch.25

TEST SITE: Semi anechoic chamber

TEST DISTANCE: 3 m

ANTENNA POLARIZATION: Vertical and Horizontal





ACTV DET: PEAK MEAS DET: PEAK OP AVG MKR 2.225 GHz 46.88 dBµV/m


STOP 2.310 OHz SWP 393 msec

BL #1F BW 1.0 MHz


ACTU DET: PEAK MEAS DET: PEAK OP AVG MKR 2.8950 GHz 49.93 dBμV/m







#AVG BW 10 kHz



#AVO BW 10 kHz





Test specification: FCC section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions Test procedure: ANSI C63.10 section 11.12.1 Test mode: Compliance **PASS** Verdict: 02-Feb-16 - 08-Mar-16 Date(s): Relative Humidity: 54 % Temperature: 23 °C Air Pressure: 1021 hPa Power Supply: Battery Remarks:

Plot 7.3.11 Radiated emission measurements from 1000 to 2900 MHz at the high carrier frequency ch.26

(B)

TEST SITE: Semi anechoic chamber


TEST DISTANCE: 3 m


ANTENNA POLARIZATION: Vertical and Horizontal




ACTV DET: PEAK MEAS DET: PEAK OP AVG MKR 2.025 GHz 44.26 dBµV/m

ACTU DET: PEAK MEAS DET: PEAK OP AVG MKR 2.8290 GHz 50.29 dBμV/m



















Test specification: FCC section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions

Test procedure: ANSI C63.10 section 11.12.1

Test mode: Compliance Verdict: PASS

Date(s): 02-Feb-16 - 08-Mar-16

Temperature: 23 °C Air Pressure: 1021 hPa Relative Humidity: 54 % Power Supply: Battery


Remarks:

Plot 7.3.12 Radiated emission measurements from 2900 to 6500 MHz at the low carrier frequency ch.11

TEST SITE: Semi anechoic chamber

TEST DISTANCE: 3 m


ANTENNA POLARIZATION: Vertical and Horizontal



Plot 7.3.13 Radiated emission measurements from 2900 to 6500 MHz at the mid carrier frequency ch.19

TEST SITE: Semi anechoic chamber

TEST DISTANCE: 3 m





Test specification: FCC section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions

Test procedure: ANSI C63.10 section 11.12.1

Test mode: Compliance Verdict: PASS

Date(s): 02-Feb-16 - 08-Mar-16


Temperature: 23 °C Air Pressure: 1021 hPa Relative Humidity: 54 % Power Supply: Battery

Remarks:

Plot 7.3.14 Radiated emission measurements from 2900 to 6500 MHz at the high carrier frequency ch.25


TEST SITE: Semi anechoic chamber TEST DISTANCE: 3 m

ANTENNA POLARIZATION: Vertical and Horizontal



Plot 7.3.15 Radiated emission measurements from 2900 to 6500 MHz at the high carrier frequency ch.26

TEST SITE: Semi anechoic chamber TEST DISTANCE: 3 m






Test specification:	FCC section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions				
Test procedure:	ANSI C63.10 section 11.12.1				
Test mode:	Compliance	Vardiet. DACC			
Date(s):	02-Feb-16 - 08-Mar-16	Verdict: PASS			
Temperature: 23 °C	Air Pressure: 1021 hPa	Relative Humidity: 54 %	Power Supply: Battery		
Remarks:					

Plot 7.3.16 Radiated emission measurements from 6500 to 18000 MHz at the low carrier frequency ch.11

TEST SITE: Semi anechoic chamber

TEST DISTANCE: 3 m


ANTENNA POLARIZATION: Vertical and Horizontal



Plot 7.3.17 Radiated emission measurements from 6500 to 18000 MHz at the mid carrier frequency ch.19

TEST SITE: Semi anechoic chamber

TEST DISTANCE: 3 m







Test specification: FCC section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions

Test procedure: ANSI C63.10 section 11.12.1

Test mode: Compliance Verdict: PASS

Date(s): 02-Feb-16 - 08-Mar-16

Temperature: 23 °C Air Pressure: 1021 hPa Relative Humidity: 54 % Power Supply: Battery


Remarks:

Plot 7.3.18 Radiated emission measurements from 6500 to 18000 MHz at the high carrier frequency ch.25

TEST SITE: Semi anechoic chamber

TEST DISTANCE: 3 m


ANTENNA POLARIZATION: Vertical and Horizontal



Plot 7.3.19 Radiated emission measurements from 6500 to 18000 MHz at the high carrier frequency ch.26

TEST SITE: Semi anechoic chamber

TEST DISTANCE: 3 m






Test specification:	FCC section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions		
Test procedure:	ANSI C63.10 section 11.12.1		
Test mode:	Compliance	Verdict:	PASS
Date(s):	02-Feb-16 - 08-Mar-16		
Temperature: 23 °C	Air Pressure: 1021 hPa	Relative Humidity: 54 %	Power Supply: Battery
Remarks:		-	-

Plot 7.3.20 Radiated emission measurements from 18000 to 25000 MHz at the low carrier frequency ch.11

TEST SITE: Semi anechoic chamber

TEST DISTANCE: 3 m


ANTENNA POLARIZATION: Vertical and Horizontal



Plot 7.3.21 Radiated emission measurements from 18000 to 25000 MHz at the mid carrier frequency ch.19

TEST SITE: Semi anechoic chamber

TEST DISTANCE: 3 m






Test specification:	FCC section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions		
Test procedure:	ANSI C63.10 section 11.12.1		
Test mode:	Compliance	Verdict: PASS	DACC
Date(s):	02-Feb-16 - 08-Mar-16		PASS
Temperature: 23 °C	Air Pressure: 1021 hPa	Relative Humidity: 54 %	Power Supply: Battery
Remarks:			

Plot 7.3.22 Radiated emission measurements from 18000 to 25000 MHz at the high carrier frequency ch.25

TEST SITE: Semi anechoic chamber

TEST DISTANCE: 3 m


ANTENNA POLARIZATION: Vertical and Horizontal



Plot 7.3.23 Radiated emission measurements from 18000 to 25000 MHz at the high carrier frequency ch.26

TEST SITE: Semi anechoic chamber

TEST DISTANCE: 3 m





Test specification: FCC section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions

Test procedure: ANSI C63.10 section 11.12.1

Test mode: Compliance Verdict: PASS

Date(s): 02-Feb-16 - 08-Mar-16


Temperature: 23 °C Air Pressure: 1021 hPa Relative Humidity: 54 % Power Supply: Battery

Remarks:

Plot 7.3.24 Radiated emission measurements at the second harmonic of low carrier frequency ch.11

TEST SITE: Semi anechoic chamber


TEST DISTANCE: 3 m



Plot 7.3.25 Radiated emission measurements at the second harmonic of mid carrier frequency ch.19

TEST SITE: Semi anechoic chamber

TEST DISTANCE: 3 m






Test specification:	FCC section 15.247(d), RS	FCC section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions				
Test procedure:	ANSI C63.10 section 11.12.1	ANSI C63.10 section 11.12.1				
Test mode:	Compliance	Verdict:	PASS			
Date(s):	02-Feb-16 - 08-Mar-16	verdict: PASS				
Temperature: 23 °C	Air Pressure: 1021 hPa	Relative Humidity: 54 %	Power Supply: Battery			
Remarks:						

Plot 7.3.26 Radiated emission measurements at the second harmonic of high carrier frequency ch 25

TEST SITE: Semi anechoic chamber


TEST DISTANCE: 3 m






Test specification:	FCC section 15.247(d), R	SS-247 section 5.5, Radiate	d spurious emissions		
Test procedure:	ANSI C63.10 section 11.12.1	ANSI C63.10 section 11.12.1			
Test mode:	Compliance	Verdict: PASS			
Date(s):	02-Feb-16 - 08-Mar-16	Verdict: PASS			
Temperature: 23 °C	Air Pressure: 1021 hPa	Relative Humidity: 54 %	Power Supply: Battery		
Remarks:		-	-		

Plot 7.3.27 Radiated emission measurements at the fourth harmonic of low carrier frequency ch.11



Plot 7.3.28 Radiated emission measurements at the fourth harmonic of mid carrier frequency ch.19






Test specification:	FCC section 15.247(d), RS	FCC section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions				
Test procedure:	ANSI C63.10 section 11.12.1	ANSI C63.10 section 11.12.1				
Test mode:	Compliance	Verdict:	PASS			
Date(s):	02-Feb-16 - 08-Mar-16	verdict.	FASS			
Temperature: 23 °C	Air Pressure: 1021 hPa	Relative Humidity: 54 %	Power Supply: Battery			
Remarks:						

Plot 7.3.29 Radiated emission measurements at the fourth harmonic of high carrier frequency ch.25

TEST SITE: Semi anechoic chamber


TEST DISTANCE: 3 m






Test specification:	FCC section 15.247(d), RS	FCC section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions				
Test procedure:	ANSI C63.10 section 11.12.1	ANSI C63.10 section 11.12.1				
Test mode:	Compliance	Verdict:	PASS			
Date(s):	02-Feb-16 - 08-Mar-16	verdict: PASS				
Temperature: 23 °C	Air Pressure: 1021 hPa	Relative Humidity: 54 %	Power Supply: Battery			
Remarks:						

Plot 7.3.30 Radiated emission measurements at the fifth harmonic of low carrier frequency ch.11



Plot 7.3.31 Radiated emission measurements at the fifth harmonic of mid carrier frequency ch.19






Test specification:	FCC section 15.247(d), R	FCC section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions				
Test procedure:	ANSI C63.10 section 11.12.1	ANSI C63.10 section 11.12.1				
Test mode:	Compliance	Verdict: PASS				
Date(s):	02-Feb-16 - 08-Mar-16	verdict:	PASS			
Temperature: 23 °C	Air Pressure: 1021 hPa	Relative Humidity: 54 %	Power Supply: Battery			
Remarks:			-			

Plot 7.3.32 Radiated emission measurements at the fifth harmonic of high carrier frequency ch.25

TEST SITE: Semi anechoic chamber TEST DISTANCE: 3 m # Agilent # Agilent Mkr1 12.372534 GHz Mkr1 12.377716 GHz **66.58 dB**µ∨/m Ref 80 dBμV/m **57.5 dB**µ∨/m Ref 80 dBμV/m #Atten 0 dB #Atten 0 dB Peak Peak Log Log 10 10 dB/ dB/ 54.0 dBμ\ 74.0 S3 FC S3 FC A AA A AA Center 12.38 GHz Res BW 1 MHz Span 20 MHz #Sweep 100 ms (800 pts) Span 20 MHz Center 12.38 GHz #VBW 3 MHz #Sweep 100 ms (800 pts) Res BW 1 MHz #VBW 1 kHz

Plot 7.3.33 Radiated emission measurements at the eighth harmonic of low carrier frequency ch.11


TEST SITE: Semi anechoic chamber TEST DISTANCE: 3 m






Test specification:	FCC section 15.247(d), R	FCC section 15.247(d), RSS-247 section 5.5, Radiated spurious emissions				
Test procedure:	ANSI C63.10 section 11.12.1	ANSI C63.10 section 11.12.1				
Test mode:	Compliance	Verdict: PASS				
Date(s):	02-Feb-16 - 08-Mar-16	verdict:	PASS			
Temperature: 23 °C	Air Pressure: 1021 hPa	Relative Humidity: 54 %	Power Supply: Battery			
Remarks:			-			

Plot 7.3.34 Radiated emission measurements at the eighth harmonic of mid carrier frequency ch.19



Plot 7.3.35 Radiated emission measurements at the eighth harmonic of high carrier frequency ch.25


TEST SITE: Semi anechoic chamber TEST DISTANCE: 3 m






Test specification:	FCC section 15.247(d), RS	SS-247 section 5.5, Radiate	d spurious emissions		
Test procedure:	ANSI C63.10 section 11.12.1	ANSI C63.10 section 11.12.1			
Test mode:	Compliance	Verdict: PASS			
Date(s):	02-Feb-16 - 08-Mar-16	Verdict: PASS			
Temperature: 23 °C	Air Pressure: 1021 hPa	Relative Humidity: 54 %	Power Supply: Battery		
Remarks:		-	•		

Plot 7.3.36 Transmission pulse duration



Plot 7.3.37 Transmission pulse period





Test specification:	FCC section 15.247(d), RS	FCC section 15.247(d), RSS-247 section 5.5, Band edge emissions				
Test procedure:	ANSI C63.10 section 11.12.1	ANSI C63.10 section 11.12.1				
Test mode:	Compliance	Verdict:	PASS			
Date(s):	02-Feb-16	verdict.	FASS			
Temperature: 23 °C	Air Pressure: 1021 hPa	Relative Humidity: 54 %	Power Supply: Battery			
Remarks:						

7.4 Band edge radiated emissions

7.4.1 General

This test was performed to measure emissions, radiated from the EUT at the assigned frequency band edges. Specification test limits are given in Table 7.4.1.

Table 7.4.1 Band edge emission limits

Output power	Assigned frequency, MHz	Attenuation below carrier*, dBc Field strength at 3 m within bands, dB(μV/m			
	rrequericy, winz	carrier, dbc	Peak	Average	
	902.0 - 928.0				
Peak	2400.0 - 2483.5	20.0	74.0	54.0	
	5725.0 – 5850.0				
Averaged ever a time	902.0 - 928.0				
Averaged over a time interval	2400.0 - 2483.5	30.0	74.0	54.0	
iiileivai	5725.0 - 5850.0				

^{* -} Band edge emission limit is provided in terms of attenuation below the peak of modulated carrier measured with the same resolution bandwidth.

7.4.2 Test procedure

- **7.4.2.1** The EUT was set up as shown in Figure 7.4.1, energized normally modulated at the maximum data rate and its proper operation was checked.
- **7.4.2.2** The EUT was adjusted to produce maximum available to end user RF output power at the lowest carrier frequency.
- **7.4.2.3** The spectrum analyzer span was set to capture the carrier frequency and associated modulation products. The resolution bandwidth was set wider than 1 % of the frequency span.
- **7.4.2.4** The spectrum analyzer was set in max hold mode and allowed trace to stabilize. The highest emission level within the authorized band was measured.
- **7.4.2.5** The maximum band edge emission and modulation product outside of the band were measured as provided in Table 7.4.2 and associated plots and referenced to the highest emission level measured within the authorized band.
- **7.4.2.6** The above procedure was repeated with the EUT adjusted to produce maximum RF output power at the highest carrier frequency.

Figure 7.4.1 Band edge emission test setup





Report ID: VISRAD_FCC.27985.docx

Date of Issue: 20-Apr-16

Test specification:	FCC section 15.247(d), RSS-247 section 5.5, Band edge emissions				
Test procedure:	ANSI C63.10 section 11.12.1	ANSI C63.10 section 11.12.1			
Test mode:	Compliance	Verdict: PASS			
Date(s):	02-Feb-16				
Temperature: 23 °C	Air Pressure: 1021 hPa	Relative Humidity: 54 %	Power Supply: Battery		
Remarks:		•			

Table 7.4.2 Band edge emission test results

ASSIGNED FREQUENCY RANGE: 2400-2483.5 MHz

DETECTOR USED:

MODULATION:

BIT RATE:

TRANSMITTER OUTPUT POWER

SETTINGS:

Peak

OQPSK

250 kbps

Maximum

VIDEO BANDWIDTH: ≥ RBW

Frequency, MHz	Band edge emission, peak, dBµV/m	Limit, dBµV/m	Margin, dB**	Band edge emission, average, dBµV/m	Calculated band edge emission,** dBµV/m	Limit, dBµV/m	Margin, dB**	Verdict
Ch.11 2400.0	69.17	109.82	-40.65	NA	NA	NA	NA	
Ch.25.2483.5	65.03	74.00	-8.97	54.96	42.39	54	-11.61	Pass
Ch.26 2483.5	72.65	74.00	-1.35	64.02	51.45	54	-2.55	

^{*-} Margin = Measured emission – specification limit.

Reference numbers of test equipment used

HL 0521	HL 1984	HL 4278	HL 4353		


Full description is given in Appendix A.

^{**-} Average factor (-12.57 dB) was applied.





Test specification:	FCC section 15.247(d), RSS-247 section 5.5, Band edge emissions			
Test procedure:	ANSI C63.10 section 11.12.1			
Test mode:	Compliance	Verdict:	PASS	
Date(s):	02-Feb-16	verdict.	FASS	
Temperature: 23 °C	Air Pressure: 1021 hPa	Relative Humidity: 54 %	Power Supply: Battery	
Remarks:				

Plot 7.4.1 The highest emission level within the assigned band at low carrier frequency



Plot 7.4.2 The highest emission level within the assigned band at high carrier frequency ch.26









Test specification:	FCC section 15.247(d), RSS-247 section 5.5, Band edge emissions			
Test procedure:	ANSI C63.10 section 11.12.1			
Test mode:	Compliance	Verdict:	PASS	
Date(s):	02-Feb-16	verdict.	FASS	
Temperature: 23 °C	Air Pressure: 1021 hPa	Relative Humidity: 54 %	Power Supply: Battery	
Remarks:				

Plot 7.4.3 The highest band edge emission at low carrier frequency ch.11




(B)






Test specification:	FCC section 15.247(d), RSS-247 section 5.5, Band edge emissions			
Test procedure:	ANSI C63.10 section 11.12.1			
Test mode:	Compliance	Verdict:	PASS	
Date(s):	02-Feb-16	verdict.	FASS	
Temperature: 23 °C	Air Pressure: 1021 hPa	Relative Humidity: 54 %	Power Supply: Battery	
Remarks:				

Plot 7.4.4 The highest band edge emission at high carrier frequency ch.25



Plot 7.4.5 The highest band edge emission at high carrier frequency ch.26





Report ID: VISRAD_FCC.27985.docx

Date of Issue: 20-Apr-16

Test specification:	FCC section 15.247(e), RSS-247 section 5.2(2), Peak power spectral density			
Test procedure:	ANSI C63.10 section 11.10.2			
Test mode:	Compliance	Verdict:	PASS	
Date(s):	02-Feb-16	verdict:	PASS	
Temperature: 23 °C	Air Pressure: 1021 hPa	Relative Humidity: 54 %	Power Supply: Battery	
Remarks:			•	

7.5 Peak spectral power density

7.5.1 General

This test was performed to measure the peak spectral power density radiated by the transmitter RF antenna. Specification test limits are given in Table 7.5.1.

Table 7.5.1 Peak spectral power density limits

Assigned frequency range, MHz	Measurement bandwidth, kHz	Peak spectral power density, dBm	Equivalent field strength limit @ 3m, dB(μV/m)*
902.0 - 928.0			
2400.0 - 2483.5	3.0	8.0	103.2
5725.0 – 5850.0			

^{* -} Equivalent field strength limit was calculated from the peak spectral power density as follows: E=sqrt(30×P)/r, where P is peak spectral power density and r is antenna to EUT distance in meters.


7.5.2 Test procedure for field strength measurements

- **7.5.2.1** The EUT was set up as shown in Figure 7.5.1, energized and its proper operation was checked.
- **7.5.2.2** The EUT was adjusted to produce maximum available to end user RF output power.
- **7.5.2.3** The field strength of the EUT carrier frequency was measured with antenna connected to spectrum analyzer/ EMI receiver. To find maximum radiation the turntable was rotated 360⁰ and the measuring antenna height was swept in both vertical and horizontal polarizations.
- **7.5.2.4** The frequency span of spectrum analyzer was set to capture the entire 6 dB band of the transmitter, in peak hold mode with resolution bandwidth set to 3.0 kHz, video bandwidth wider than resolution bandwidth, auto sweep time and sufficient number of sweeps was allowed for trace stabilization. The spectrum lines spacing was verified to be wider than 3 kHz. Otherwise the resolution bandwidth was reduced until individual spectrum lines were resolved and the power of individual spectrum lines was integrated over 3 kHz band.
- **7.5.2.5** The peak of emission was zoomed with span set just wide enough to capture the emission peak area and sweep time was set equal to span width divided by resolution bandwidth. Spectrum analyzer was set in peak hold mode, sufficient number of sweeps was allowed for trace stabilization and peak spectral power density was measured as provided in Table 7.5.2 and associated plots.



Test specification:	FCC section 15.247(e), RSS-247 section 5.2(2), Peak power spectral density			
Test procedure:	ANSI C63.10 section 11.10.2			
Test mode:	Compliance	Verdict:	PASS	
Date(s):	02-Feb-16	verdict:	PASS	
Temperature: 23 °C	Air Pressure: 1021 hPa	Relative Humidity: 54 %	Power Supply: Battery	
Remarks:		-	-	

Figure 7.5.1 Setup for carrier field strength measurements







Test specification: FCC section 15.247(e), RSS-247 section 5.2(2), Peak power spectral density

Test procedure: ANSI C63.10 section 11.10.2

Test mode: Compliance Verdict: PASS

Date(s): 02-Feb-16

Temperature: 23 °C Air Pressure: 1021 hPa Relative Humidity: 54 % Power Supply: Battery

Remarks:

Table 7.5.2 Field strength measurement of peak spectral power density

ASSIGNED FREQUENCY: 2400-2483.5 MHz

TEST DISTANCE: 3 m
TEST SITE: OATS
EUT HEIGHT: 1.5 m
DETECTOR USED: Peak

TEST ANTENNA TYPE: Double ridged guide (above 1000 MHz)

MODULATION: OQPSK BIT RATE: 250 kbps

Frequency, MHz	Field strength, dB(μV/m)	EUT antenna gain, dBi	Limit, dB(μV/m)	Margin, dB*	Antenna polarization	Antenna height, m	RBW kHz	Verdict
2405	98.20	3	103.2	-8.00	Horizontal	1.8	3	Pass
2445	98.55	3	103.2	-7.65	Horizontal	1.3	3	Pass
2475	98.05	3	103.2	-17.05	Horizontal	1.3	3	Pass
2480	89.15	3	103.2	-17.05	Horizontal	1.8	3	Pass

^{*-} Margin = Field strength - EUT antenna gain - calculated field strength limit.

Reference numbers of test equipment used

	,					
ĺ	HL 0521	HL 1984	HL 4278	HL 4353		


Full description is given in Appendix A.

^{**-} EUT front panel refer to 0 degrees position of turntable.




Test specification:	FCC section 15.247(e), RS	SS-247 section 5.2(2), Peak	power spectral density
Test procedure:	ANSI C63.10 section 11.10.2		
Test mode:	Compliance	Verdict:	PASS
Date(s):	02-Feb-16	verdict.	FASS
Temperature: 23 °C	Air Pressure: 1021 hPa	Relative Humidity: 54 %	Power Supply: Battery
Remarks:			

Plot 7.5.1 Peak spectral power density at low frequency zoomed at the peak, ch.11




Plot 7.5.2 Peak spectral power density at mid frequency zoomed at the peak, ch.19






Test specification:	FCC section 15.247(e), RSS-247 section 5.2(2), Peak power spectral density			
Test procedure:	ANSI C63.10 section 11.10.2			
Test mode:	Compliance	Verdict:	PASS	
Date(s):	02-Feb-16	verdict.	FASS	
Temperature: 23 °C	Air Pressure: 1021 hPa	Relative Humidity: 54 %	Power Supply: Battery	
Remarks:				

Plot 7.5.3 Peak spectral power density at high frequency zoomed at the peak, ch.25



Plot 7.5.4 Peak spectral power density at high frequency zoomed at the peak, ch.26





Test specification:	FCC section 15.203, RSS-Gen section 8.3, Antenna requirement				
Test procedure:	Visual inspection	Visual inspection			
Test mode:	Compliance	Verdict:	PASS		
Date(s):	08-Mar-16	verdict.	FASS		
Temperature: 23 °C	Air Pressure: hPa	Relative Humidity: 55 %	Power Supply: Battery		
Remarks:					

7.6 Antenna requirements


The EUT was verified for compliance with antenna requirements. A transmitter shall be designed to ensure that no antenna other than that furnished by the responsible party will be used with the device. It may be either permanently attached or employs a unique antenna connector for every antenna proposed for use with the EUT. This requirement does not apply to professionally installed transmitters.

The rationale for compliance with the above requirements was either visual inspection results or supplier declaration. The summary of results is provided in Table 7.6.1.

Table 7.6.1 Antenna requirements

Requirement	Rationale	Verdict
The transmitter antenna is permanently attached	Visual inspection	
The transmitter employs a unique antenna connector	NA	Comply
The transmitter requires professional installation	NA	

Photograph 7.6.1 Antenna assembly





Test specification:	FCC Part 15, Section 109 / RSS-Gen, Section 7.1.2 / ICES-003, Section 6.2, Radiated emission				
Test procedure:	ANSI C63.4, Sections 11.6 an	d 12.1.4			
Test mode:	Compliance	Verdict:	PASS		
Date(s):	21-Feb-16 - 22-Feb-16	verdict.	PASS		
Temperature: 22 °C	Air Pressure: 1010 hPa	Relative Humidity: 54 %	Power Supply: Battery		
Remarks:					

8 Unintentional emissions

8.1 Radiated emission measurements

8.1.1 General

This test was performed to measure radiated emissions from the EUT enclosure. Specification test limits are given in Table 8.1.1, Table 8.1.2.

Table 8.1.1 Radiated emission limits according to FCC Part 15, Section 109

Frequency,	Class B lim	it, dB(μV/m)	Class A limit, dB(μV/m)			
MHz	10 m distance	3 m distance	10 m distance	3 m distance		
30 - 88	29.5*	40.0	39.0	49.5*		
88 - 216	33.0*	43.5	43.5	54.0*		
216 - 960	35.5*	46.0	46.4	56.9*		
960 - 5 th harmonic**	43.5*	54.0	49.5	60.0*		

^{* -} The limit for test distance other than specified was calculated using the inverse linear distance extrapolation factor as follows: $Lim_{S2} = Lim_{S1} + 20 log (S_1/S_2)$,

where $S_1\, \text{and}\, S_2-\text{standard}$ defined and test distance respectively in meters.

Table 8.1.2 Radiated emission limits according to RSS-Gen, Section 7.1.2

Frequency, MHz	Field strength limit at 3 m test distance, dB(μV/m)
30 - 88	40.0
88 - 216	43.5
216 - 960	46.0
960 - 5 th harmonic**	54.0

^{** -} harmonic of the highest frequency the EUT generates, uses, operates or tunes to.


8.1.2 Test procedure

- **8.1.2.1** The EUT was set up as shown in Figure 8.1.1 and associated photographs, energized and the performance check was conducted.
- **8.1.2.2** The specified frequency range was investigated with biconilog antenna connected to EMI receiver. To find maximum radiation the turntable was rotated 360°, the measuring antenna height was changed from 1 to 4 m, its polarization was switched from vertical to horizontal and the EUT cables position was varied.
- **8.1.2.3** The worst test results (the lowest margins) were provided in the associated tables and plots.



Test specification:	FCC Part 15, Section 109 / RSS-Gen, Section 7.1.2 / ICES-003, Section 6.2, Radiated emission				
Test procedure:	ANSI C63.4, Sections 11.6 ar	nd 12.1.4			
Test mode:	Compliance	Verdict:	PASS		
Date(s):	21-Feb-16 - 22-Feb-16	verdict.	PASS		
Temperature: 22 °C	Air Pressure: 1010 hPa	Relative Humidity: 54 %	Power Supply: Battery		
Remarks:					

Figure 8.1.1 Setup for radiated emission measurements in anechoic chamber, table-top equipment



Photograph 8.1.1 Setup for radiated emission measurements







Test specification:	FCC Part 15, Section 109 / RSS-Gen, Section 7.1.2 / ICES-003, Section 6.2, Radiated emission				
Test procedure:	ANSI C63.4, Sections 11.6 an	d 12.1.4			
Test mode:	Compliance	Verdict:	PASS		
Date(s):	21-Feb-16 - 22-Feb-16	verdict.	FASS		
Temperature: 22 °C	Air Pressure: 1010 hPa	Relative Humidity: 54 %	Power Supply: Battery		
Remarks:					

Table 8.1.3 Radiated emission test results

EUT SET UP: TABLE-TOP LIMIT: Class B

EUT OPERATING MODE: Receive
TEST SITE: SEMI ANECHOIC CHAMBER

TEST DISTANCE: 3 m

FREQUENCY RANGE: 30 MHz – 1000 MHz

RESOLUTION BANDWIDTH: 120 kHz

TEGGEORIGIT BY THE TIE					· 101 12			
_ Peak			Quasi-peak			Antenna	Turn-table	
Frequency, MHz	emission, dB(μV/m)	Measured emission, dB(μV/m)	Limit, dB(μV/m)	Margin, dB*	Antenna polarization	haight	position**, degrees	Verdict
	No signals were found					Pass		

TEST SITE: SEMI ANECHOIC CHAMBER

TEST DISTANCE: 3 m

DETECTORS USED: PEAK / AVERAGE FREQUENCY RANGE: 1000 MHz – 13000 MHz

RESOLUTION BANDWIDTH: 1000 kHz

Eroguenov		Peak		Average			Antonno	Turn table		
Frequency,	Measured	Limit,	Margin,	Measured	Limit,	Margin,	Antenna		Turn-table position**,	
MHz	emission,			emission,			polarization	m	degrees	Vertice
1411 12	dB(μV/m)	dB(μV/m)	dB*	$dB(\mu V/m)$	$dB(\mu V/m)$	dB*		""	degrees	
No signals were found							Pass			

^{*-} Margin = Measured emission - specification limit.

Reference numbers of test equipment used

HL 0521	HL 0604	HL 3818	HL 4276	HL 4353	HL 4720	HL 4933	

Full description is given in Appendix A.

^{**-} EUT front panel refer to 0 degrees position of turntable.




Test specification:	FCC Part 15, Section 109 / RSS-Gen, Section 7.1.2 / ICES-003, Section 6.2, Radiated emission				
Test procedure:	ANSI C63.4, Sections 11.6 ar	ANSI C63.4, Sections 11.6 and 12.1.4			
Test mode:	Compliance	Verdict:	PASS		
Date(s):	21-Feb-16 - 22-Feb-16	verdict.	FASS		
Temperature: 22 °C	Air Pressure: 1010 hPa	Relative Humidity: 54 %	Power Supply: Battery		
Remarks:					

Plot 8.1.1 Radiated emission measurements in 30 - 1000 MHz range, vertical & horizontal antenna polarization

TEST SITE: Semi anechoic chamber

LIMIT: Class B
TEST DISTANCE: 3 m
EUT OPERATING MODE: Receive







Plot 8.1.2 Radiated emission measurements in 1-6 GHz range, vertical & horizontal antenna polarization

TEST SITE: Semi anechoic chamber LIMIT: Class B

TEST DISTANCE: 3 m
EUT OPERATING MODE: Receive









Test specification:	FCC Part 15, Section 109 / RSS-Gen, Section 7.1.2 / ICES-003, Section 6.2, Radiated emission			
Test procedure:	ANSI C63.4, Sections 11.6 an	d 12.1.4		
Test mode:	Compliance	Verdict:	PASS	
Date(s):	21-Feb-16 - 22-Feb-16	verdict.	FASS	
Temperature: 22 °C	Air Pressure: 1010 hPa	Relative Humidity: 54 %	Power Supply: Battery	
Remarks:				

Plot 8.1.3 Radiated emission measurements in 6-13 GHz range, vertical & horizontal antenna polarization

TEST SITE: Semi anechoic chamber

LIMIT: Class B
TEST DISTANCE: 3 m
EUT OPERATING MODE: Receive








9 APPENDIX A Test equipment and ancillaries used for tests

HL	Description	Manufacturer	Model	Ser. No.	Last Cal./	Due Cal./
No	·				Check	Check
0446	Antenna, Loop, Active, 10 kHz - 30 MHz	EMCO	6502	2857	18-Jan-16	18-Jan-17
0521	EMI Receiver (Spectrum Analyzer) with	Hewlett	8546A	3617A	27-Oct-15	27-Oct-16
	RF filter section 9 kHz-6.5 GHz	Packard		00319, 3448A002 53		
0604	Antenna BiconiLog Log-Periodic/T Bow-TIE, 26 - 2000 MHz	EMCO	3141	9611-1011	15-May-15	15-May-16
1984	Antenna, Double-Ridged Waveguide Horn, 1 to 18 GHz, 300 W	EMC Test Systems	3115	9911-5964	17-Apr-15	17-Apr-16
2780	EMC analyzer, 100 Hz to 26.5 GHz	Agilent Technologies	E7405A	MY451024 62	08-Sep-15	08-Sep-16
3347	High Pass Filter, 50 Ohm, 6000 to 11500 MHz.	Mini-Circuits	VHF- 5500+	NA	01-Oct-15	01-Oct-17
3818	PSA Series Spectrum Analyzer, 3 Hz- 44 GHz	Agilent Technologies	E4446A	MY482502 88	29-Apr-15	29-Apr-16
3901	Microwave Cable Assembly, 40.0 GHz, 3.5 m, SMA/SMA	Huber-Suhner	SUCOFLE X 102A	1225/2A	15-Feb-16	15-Feb-17
4278	Test Cable , DC-18 GHz, 4.6 m, N/M - N/M	Mini-Circuits	APC- 15FT- NMNM+	0755A	22-Nov-15	22-Nov-16
4338	Reject Band Filter, 50 Ohm, 0 to 2170 and 3000 to 18000 MHz, SMA-FM / SMA-M	Micro-Tronics	BRM 50702-02	023	05-May-15	05-May-16
4353	Low Loss Armored Test Cable, DC - 18 GHz, 6.2 m, N type-M/N type-M	MegaPhase	NC29- N1N1-244	12025101 003	15-Mar-15	15-Mar-16
4720	Low Loss Armored Test Cable, DC - 18 GHz, 4.5 m, N type-M/N type-M	MegaPhase	NC29- N1N1-177	51300101 002	30-Dec-15	30-Dec-16
4932	Microwave preamplifier, 500 MHz to 18 GHz, 40 dB Gain	Com-Power Corporation	PAM- 118A	551029	19-Nov-15	19-Nov-16
4933	Active Horn Antenna, 1 GHz to 18 GHz	Com-Power Corporation	AHA-118	701046	04-Sep-15	04-Sep-16
4956	Active horn antenna, 18 to 40 GHz	Com-Power Corporation	AHA-840	105004	09-Nov-15	09-Nov-16





10 APPENDIX B Measurement uncertainties


Expanded uncertainty at 95% confidence in Hermon Labs EMC measurements

Test description	Expanded uncertainty
Conducted carrier power at RF antenna connector	Below 12.4 GHz: ± 1.7 dB
	12.4 GHz to 40 GHz: ± 2.3 dB
Conducted emissions at RF antenna connector	9 kHz to 2.9 GHz: ± 2.6 dB
	2.9 GHz to 6.46 GHz: ± 3.5 dB
	6.46 GHz to 13.2 GHz: ± 4.3 dB
	13.2 GHz to 22.0 GHz: ± 5.0 dB
	22.0 GHz to 26.8 GHz: ± 5.5 dB
	26.8 GHz to 40.0 GHz: ± 4.8 dB
Occupied bandwidth	± 8.0 %
Duty cycle, timing (Tx ON / OFF) and average factor measurements	± 1.0 %
Conducted emissions with LISN	9 kHz to 150 kHz: ± 3.9 dB
	150 kHz to 30 MHz: ± 3.8 dB
Radiated emissions at 3 m measuring distance	
Horizontal polarization	Biconilog antenna: ± 5.3 dB
	Biconical antenna: ± 5.0 dB
	Log periodic antenna: ± 5.3 dB
Margarita da Cargari	Double ridged horn antenna: ± 5.3 dB
Vertical polarization	Biconilog antenna: ± 6.0 dB
	Biconical antenna: ± 5.7 dB
	Log periodic antenna: ± 6.0 dB
	Double ridged horn antenna: ± 6.0 dB

Hermon Laboratories is accredited by A2LA for calibration according to present requirements of ISO/IEC 17025 and NCSL Z540-1. The accreditation is granted to perform calibration of parameters that are listed in the Scope of Hermon Laboratories Accreditation.

Hermon Laboratories calibrates its reference and transfer standards by calibration laboratories accredited to ISO/IEC 17025 by a mutually recognized Accreditation Body or by a recognized national metrology institute. All reference and transfer standards used in the calibration system are traceable to national or international standards.

In-house calibration of all test and measurement equipment is performed on a regular basis according to Hermon Laboratories calibration procedures, manufacturer calibration/verification procedures or procedures defined in the relevant standards. The Hermon Laboratories test and measurement equipment is calibrated within the tolerances specified by the manufacturers and/or by the relevant standards.





11 APPENDIX C Test laboratory description

Tests were performed at Hermon Laboratories Ltd., which is a fully independent, private, EMC, safety, environmental and telecommunication testing facility.

Hermon Laboratories is listed by the Federal Communications Commission (USA) for all parts of Code of Federal Regulations 47 (CFR 47), Registration Numbers 90624 for OATS and 90623 for the anechoic chamber; by Industry Canada for electromagnetic emissions (file number IC 2186A-1 for OATS), certified by VCCI, Japan (the registration numbers are R-808 for OATS, R-1082 for anechoic chamber, C-845 for conducted emissions site, T-1606 for conducted emissions at telecommunication ports), has a status of a Telefication - Listed Testing Laboratory, Certificate No. L138/00. The laboratory is accredited by American Association for Laboratory Accreditation (USA) according to ISO/IEC 17025 for electromagnetic compatibility, product safety, telecommunications testing and environmental simulation (for exact scope please refer to Certificate No. 839.01). The FCC Designation Number is IL1001.


Address: P.O. Box 23, Binyamina 30500, Israel.

Telephone: +972 4628 8001 Fax: +972 4628 8277 e-mail: mail@hermonlabs.com website: www.hermonlabs.com

Person for contact: Mr. Alex Usoskin, CEO.

12 APPENDIX D Specification references

FCC 47CFR part 15: 2015 Radio Frequency Devices ANSI C63.10: 2013 American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices ANSI C63.2: 1996 American National Standard for Instrumentation-Electromagnetic Noise and Field Strength, 10 kHz to 40 GHz-Specifications ANSI C63.4: 2009 American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz RSS-247 Issue 1: 2015 Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence- Exempt Local Area Network (LE-LAN) Devices RSS-Gen Issue 4: 2014 General Requirements for Compliance of Radio Apparatus






13 APPENDIX E Test equipment correction factors

Antenna factor Active loop antenna Model 6502, S/N 2857, HL 0446

Frequency, MHz	Magnetic antenna factor, dB	Electric antenna factor, dB
0.009	-32.8	18.7
0.010	-33.8	17.7
0.020	-38.3	13.2
0.050	-41.1	10.4
0.075	-41.3	10.2
0.100	-41.6	9.9
0.150	-41.7	9.8
0.250	-41.6	9.9
0.500	-41.8	9.8
0.750	-41.9	9.7
1.000	-41.4	10.1
2.000	-41.5	10.0
3.000	-41.4	10.2
4.000	-41.4	10.1
5.000	-41.5	10.1
10.000	-41.9	9.6
15.000	-41.9	9.6
20.000	-42.2	9.3
25.000	-42.8	8.7
30.000	-44.0	7.5

Antenna factor in dB(1/m) is to be added to receiver meter reading in dB(μ V) to convert it into field strength in dB(μ V/m).






Antenna factor Biconilog antenna EMCO Model 3141 Ser.No.1011, HL 0604

Frequency, MHz	Antenna factor, dB(1/m)	Frequency, MHz	Antenna factor, dB(1/m)	Frequency, MHz	Antenna factor, dB(1/m)
26	7.8	580	20.6	1320	27.8
28	7.8	600	21.3	1340	28.3
30	7.8	620	21.5	1360	28.2
40	7.2	640	21.2	1380	27.9
60	7.1	660	21.4	1400	27.9
70	8.5	680	21.9	1420	27.9
80	9.4	700	22.2	1440	27.8
90	9.8	720	22.2	1460	27.8
100	9.7	740	22.1	1480	28.0
110	9.3	760	22.3	1500	28.5
120	8.8	780	22.6	1520	28.9
130	8.7	800	22.7	1540	29.6
140	9.2	820	22.9	1560	29.8
150	9.8	840	23.1	1580	29.6
160	10.2	860	23.4	1600	29.5
170	10.4	880	23.8	1620	29.3
180	10.4	900	24.1	1640	29.2
190	10.3	920	24.1	1660	29.4
200	10.6	940	24.0	1680	29.6
220	11.6	960	24.1	1700	29.8
240	12.4	980	24.5	1720	30.3
260	12.8	1000	24.9	1740	30.8
280	13.7	1020	25.0	1760	31.1
300	14.7	1040	25.2	1780	31.0
320	15.2	1060	25.4	1800	30.9
340	15.4	1080	25.6	1820	30.7
360	16.1	1100	25.7	1840	30.6
380	16.4	1120	26.0	1860	30.6
400	16.6	1140	26.4	1880	30.6
420	16.7	1160	27.0	1900	30.6
440	17.0	1180	27.0	1920	30.7
460	17.7	1200	26.7	1940	30.9
480	18.1	1220	26.5	1960	31.2
500	18.5	1240	26.5	1980	31.6
520	19.1	1260	26.5	2000	32.0
540	19.5	1280	26.6		
560	19.8	1300	27.0		

Antenna factor in dB(1/m) is to be added to receiver meter reading in $dB(\mu V)$ to convert it into field strength in $dB(\mu V/m)$.





Antenna factor Double-ridged wave guide horn antenna Model 3115, S/N 9911-5964, HL1984

Frequency, MHz	Antenna factor, dB(1/m)		
1000.0	24.7		
1500.0	25.7		
2000.0	27.6		
2500.0	28.9		
3000.0	31.2		
3500.0	32.0		
4000.0	32.5		
4500.0	32.7		
5000.0	33.6		
5500.0	35.1		
6000.0	35.4		
6500.0	34.9		
7000.0	36.1		
7500.0	37.8		
8000.0	38.0		
8500.0	38.1		
9000.0	39.1		
9500.0	38.3		
10000.0	38.6		
10500.0	38.2		
11000.0	38.7		
11500.0	39.5		
12000.0	40.0		
12500.0	40.4		
13000.0	40.5		
13500.0	41.1		
14000.0	41.6		
14500.0	41.7		
15000.0	38.7		
15500.0	38.2		
16000.0	38.8		
16500.0	40.5		
17000.0	42.5		
17500.0	45.9		
18000.0	49.4		

Antenna factor in dB(1/m) is to be added to receiver meter reading in dB(μ V) to convert it into field strength in dB(μ V/m).



Antenna factor, HL 4933



Active Horn Antenna Factor Calibration

1 GHz to 18 GHz

Equipment:

Model:
Serial Number:
Calibration Distance:
Polarization:

ACTIVE HORN ANTENNA
AHA-118
701046
701046
Horizontal

Calibration Date:

11/12/2014

Frequency	Preamplifier Gain	Antenna Factor with pre-amp	Frequency	Preamplifier Gain	Antenna Factor with pre-amp
(GHz)	(dB)	(dB/m)	(GHz)	(dB)	(dB/m)
1	40.96	-16.47	10	40.94	-1.97
1.5	41.21	-14-53	10.5	40.63	-1.06
2	41.44	-13.30	11	40.74	-1.50
2.5	41.71	-12.87	11.5	40.65	-0.52
3	41.96	-12.26	12	40.76	-0.15
3.5	42.14	-11.77	12.5	41.03	-0.85
4	42.13	-10.91	13	41.37	-0.81
4.5	41.79	-9.41	13.5	41.18	0.05
5	41.44	-7-54	14	40.98	0.36
5.5	40.91	-6.47	14.5	40.81	1.26
6	40.69	-5.48	15	40.65	0.25
6.5	40.64	-5-53	15.5	40.93	-1.05
7	40.76	-4.12	16	41.31	-1.44
7.5	40.94	-3.12	16.5	40.96	-0.80
8	40.68	-1.69	17	40.64	-0.02
8.5	40.08	-1.71	17.5	40.57	1.81
9	40.41	-1.86	18	40.08	3.63
9.5	41.21	-2.73	THE PARTY OF		

Calibration according to ARP 958

Antenna Factor to be added to receiver reading:

Meter Reading (dBuV) + Antenna Factor (dB/m) = Corrected Reading (dBuV/m)



28.5

43.01

Antenna factor, HL 4956



Active Horn Antenna Factor Calibration

18 GHz to 40 GHz

Equipment: ACTIVE HORN ANTENNA Model: AHA-840 Serial Number: 105004 Calibration Distance: 3 meter Polarization: Horizontal Calibration Date: 1/26/2015 Preamplifier Antenna Factor Preamplifier Antenna Factor Frequency Frequency with pre-amp with pre-amp Gain Gain (GHz) (dB) (dB/m) (GHz) (dB) (dB/m) 18 38.83 -1.06 29.5 42.47 -5.33 18.5 -2.65 -4.86 39.34 30 41.91 19 39.71 -3.88 30.5 41.60 -4.64 19.5 39.87 41.52 -4.60 -4-35 31 20 39.98 -3-97 41.56 31.5 -4.79 20.5 40.42 -3.68 41.80 -5.21 32 41.12 -4.06 42.29 21 32.5 -5.54 41.74 21.5 -5.46 33 42.79 -5.63 -6.22 42.88 22 42.14 33.5 -5.38 -6.42 22.5 42.35 42.62 -4.76 34 42.50 -6.59 42.63 -4.84 23 34.5 23.5 42.65 -6.82 35 43.15 -5.13 42.81 -7.01 -5.83 24 43.91 35.5 24.5 42.86 -7-37 36 44.59 -6.39 42.73 -7-53 36.5 45.04 -6.64 25 42.77 45.08 -6.40 25.5 -7.45 37 -7.21 26 42.85 44.82 -5.75 37.5 26.5 42.98 44.16 -4.58 -7.17 38 -2.66 27 43.14 -7.22 38.5 42.90 27.5 43.18 -1.71 -7.32 39 42.39 28 43.04 -7.10 43.76 -2.49 39.5

Calibration per ANSI C63.5: 2006
Standard Site Method, Equations 1-6 (3-antenna)


40

45.98

-6.73

Corrected Reading (dBµV/m) = Meter Reading (dBµV) + AFE(dB/m)

-5.21





Cable loss Microwave Cable Assembly, Huber-Suhner, 40 GHz, 3.5 m, SMA-SMA, S/N 1225/2A HL 3901


Frequency, MHz	Cable loss, dB	Frequency, MHz	Cable loss, dB	Frequency, MHz	Cable loss, dB
10	0.09	9500	4.29	21000	6.67
100	0.41	10000	4.40	22000	6.92
500	0.93	10500	4.52	23000	7.00
1000	1.33	11000	4.64	24000	7.18
1500	1.63	11500	4.76	25000	7.29
2000	1.90	12000	4.87	26000	7.55
2500	2.12	12500	4.99	27000	7.70
3000	2.33	13000	5.11	28000	7.88
3500	2.50	13500	5.20	29000	8.02
4000	2.67	14000	5.31	30000	8.15
4500	2.82	14500	5.42	31000	8.35
5000	2.99	15000	5.51	32000	8.40
5500	3.16	15500	5.58	33000	8.62
6000	3.32	16000	5.68	34000	8.73
6500	3.51	16500	5.78	35000	8.78
7000	3.65	17000	5.91	36000	8.94
7500	3.79	17500	5.99	37000	9.21
8000	3.92	18000	6.07	38000	9.37
8500	4.04	19000	6.36	39000	9.45
9000	4.18	20000	6.49	40000	9.52





Cable loss Test cable, Mini-Circuits, S/N 0755A, 18 GHz, 4.6 m, N/M - N/M APC-15FT-NMNM+, HL 4278


MHz Ioss, dB MHz loss, dB MHz loss, dB 10 0.24 4900 4.19 10000 6.47 15100 8.33 30 0.26 5000 4.29 10200 6.52 15300 8.37 100 0.50 5200 4.32 10300 6.57 15400 8.42 300 0.90 5400 4.41 10500 6.61 15600 8.42 300 0.90 5400 4.41 10500 6.61 15600 8.6 400 1.06 5500 4.46 10600 6.64 15800 8.50 500 1.20 5600 4.51 10700 6.64 15800 8.52 600 1.32 5700 4.56 10800 6.68 16000 8.52 600 1.54 5900 4.64 11000 6.68 1600 8.61 800 1.54 5900 4.64 11000	APC-15FT-NMNM+, HL 4278							
30	Frequency, MHz	loss,						
50 0.34 5100 4.29 10200 6.52 15300 8.37 100 0.50 5200 4.32 10300 6.59 15500 8.42 200 0.72 5300 4.38 10400 6.59 15500 8.42 300 0.90 5400 4.41 10500 6.61 15600 8.46 400 1.06 5500 4.48 10600 6.64 15700 8.50 500 1.20 5600 4.51 10700 6.64 15800 8.52 600 1.32 5700 4.56 10800 6.65 15900 8.61 700 1.44 5800 4.54 11000 6.68 16000 8.61 800 1.54 5900 4.64 11000 6.68 1600 8.61 100 1.74 6100 4.72 11200 6.70 16300 8.70 1100 1.83 6200 <td< td=""><td>10</td><td>0.24</td><td>4900</td><td>4.19</td><td>10000</td><td>6.47</td><td>15100</td><td>8.33</td></td<>	10	0.24	4900	4.19	10000	6.47	15100	8.33
100	30	0.26	5000	4.25	10100	6.50	15200	8.35
100	50	0.34	5100	4.29	10200	6.52	15300	8.37
300					10300			
300	200	0.72	5300	4.38	10400	6.59	15500	8.42
400 1.06 5500 4.46 10600 6.64 15700 8.50 500 1.20 5600 4.51 10700 6.64 15800 8.52 600 1.32 5700 4.66 10800 6.65 15900 8.56 700 1.44 5800 4.59 10900 6.68 16000 8.61 800 1.54 5900 4.64 11000 6.68 16000 8.61 800 1.64 6000 4.69 11100 6.69 16200 8.66 1000 1.74 6100 4.72 11200 6.70 16300 8.61 1100 1.83 6200 4.77 11300 6.74 16400 8.73 1200 1.92 6300 4.80 11400 6.78 16500 8.74 1300 2.01 6400 4.83 11500 6.81 16600 8.75 1400 2.93 6600	300	0.90	5400		10500	6.61	15600	
500 1.20 5600 4.51 10700 6.64 15800 8.52 600 1.32 5700 4.56 10800 6.65 15900 8.56 700 1.44 5800 4.59 10900 6.68 16000 8.61 800 1.54 5900 4.64 11000 6.68 16100 8.64 900 1.64 6000 4.69 11100 6.69 16200 8.66 1000 1.74 6100 4.72 11200 6.70 16300 8.70 1100 1.83 6200 4.77 11300 6.74 16400 8.73 1200 1.92 6300 4.80 11400 6.78 16500 8.74 1300 2.01 6400 4.83 11500 6.81 16600 8.75 1400 2.09 6500 4.89 11700 6.87 16800 8.79 1500 2.18 6600	400	1.06	5500	4.46	10600	6.64	15700	
660 1.32 5700 4.56 10800 6.65 15900 8.56 700 1.44 5800 4.59 10900 6.68 16000 8.61 800 1.54 5900 4.64 11000 6.68 16100 8.64 900 1.64 6000 4.89 11100 6.69 16200 8.66 1000 1.74 6100 4.72 11200 6.70 16300 8.70 1100 1.83 6200 4.77 11300 6.74 16400 8.73 1200 1.92 6300 4.80 11400 6.78 16500 8.74 1300 2.01 6400 4.83 11500 6.81 16600 8.75 1400 2.09 6500 4.89 11600 6.87 16800 8.79 1500 2.18 6600 4.90 11700 6.87 16800 8.79 1600 2.25 6700	500							
700 1.44 5800 4.59 10900 6.68 16000 8.61 800 1.54 5900 4.64 11000 6.68 16100 8.66 900 1.64 6000 4.69 11100 6.69 16200 8.66 1000 1.74 6100 4.72 11200 6.70 16300 8.70 1100 1.83 6200 4.77 11300 6.74 16400 8.73 1200 1.92 6300 4.80 11400 6.78 16500 8.74 1300 2.01 6400 4.83 11500 6.81 16600 8.75 1400 2.09 6500 4.89 11600 6.84 16700 8.78 1500 2.25 6700 4.95 11800 6.92 16900 8.81 1700 2.33 6800 5.01 11900 6.98 17000 8.85 1800 2.47 7000								
800 1.54 5900 4.64 11000 6.68 16100 8.64 900 1.64 6000 4.69 11100 6.69 16200 8.66 1000 1.74 6100 4.72 11200 6.70 16300 8.70 1100 1.83 6200 4.77 11300 6.74 16400 8.73 1200 1.92 6300 4.80 11400 6.78 16500 8.74 1300 2.01 6400 4.83 11500 6.81 16600 8.75 1400 2.09 6500 4.89 11600 6.84 16700 8.78 1500 2.18 6600 4.95 11800 6.84 16700 8.78 1500 2.18 6600 4.95 11800 6.92 16900 8.81 1700 2.33 6800 5.01 11900 6.98 17000 8.85 1800 2.39 6900								
900 1.64 6000 4.69 11100 6.69 16200 8.66 1000 1.74 6100 4.72 11200 6.70 16300 8.70 1100 1.83 6200 4.77 11300 6.78 16500 8.74 1300 2.01 6400 4.80 11400 6.78 16500 8.74 1300 2.01 6400 4.83 11500 6.81 16600 8.75 1400 2.09 6500 4.89 11600 6.84 16700 8.78 1500 2.18 6600 4.90 11700 6.87 16800 8.79 1600 2.25 6700 4.95 11800 6.92 16900 8.81 1700 2.33 6800 5.01 11900 6.98 17000 8.85 1800 2.25 6700 4.99 12000 7.02 17100 8.96 2000 2.53 7100								
1000								
1100 1.83 6200 4.77 11300 6.74 16400 8.73 1200 1.92 6300 4.80 11400 6.78 16500 8.74 1300 2.01 6400 4.83 11500 6.81 16600 8.75 1400 2.09 6500 4.89 11600 6.84 16700 8.78 1500 2.18 6600 4.90 11700 6.87 16800 8.79 1600 2.25 6700 4.95 11800 6.92 16900 8.81 1700 2.33 6800 5.01 11900 6.92 16900 8.81 1800 2.39 6900 4.99 12000 7.02 17100 8.90 1900 2.47 7000 5.04 12100 7.08 17200 8.95 2000 2.53 7100 5.11 12200 7.15 17300 8.99 2100 2.60 7200								
1200 1.92 6300 4.80 11400 6.78 16500 8.74 1300 2.01 6400 4.83 11500 6.81 16600 8.75 1400 2.09 6500 4.89 11600 6.84 16700 8.78 1500 2.18 6600 4.90 11700 6.87 16800 8.79 1600 2.25 6700 4.95 11800 6.92 16900 8.81 1700 2.33 6800 5.01 11900 6.98 17000 8.85 1800 2.39 6900 4.99 12000 7.02 17100 8.90 1900 2.47 7000 5.04 12100 7.08 17200 8.95 2000 2.53 7100 5.11 12200 7.15 17300 8.95 2100 2.60 7200 5.14 12300 7.26 17500 9.07 2300 2.73 7400								
1300 2.01 6400 4.83 11500 6.81 16600 8.75 1400 2.09 6500 4.89 11600 6.84 16700 8.78 1500 2.18 6600 4.90 11700 6.87 16800 8.79 1600 2.25 6700 4.95 11800 6.92 16900 8.81 1700 2.33 6800 5.01 11900 6.98 17000 8.85 1800 2.39 6900 4.99 12000 7.02 17100 8.95 2000 2.53 7100 5.04 12100 7.08 17200 8.95 2000 2.53 7100 5.11 12200 7.15 17300 8.99 2100 2.60 7200 5.14 12300 7.20 17400 9.03 2200 2.67 7300 5.21 12400 7.26 17500 9.07 2300 2.67 7500								
1400 2.09 6500 4.89 11600 6.84 16700 8.78 1500 2.18 6600 4.90 11700 6.87 16800 8.79 1600 2.25 6700 4.95 11800 6.92 16900 8.81 1700 2.33 6800 5.01 11900 6.98 17000 8.85 1800 2.39 6900 4.99 12000 7.02 17100 8.99 1900 2.47 7000 5.04 12100 7.08 17200 8.95 2000 2.53 7100 5.11 12200 7.15 17300 8.99 2100 2.60 7200 5.14 12300 7.20 17400 9.03 2200 2.67 7300 5.21 12400 7.26 17500 9.07 2300 2.73 7400 5.29 12500 7.31 17600 9.01 2400 2.880 7500 <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>								
1500 2.18 6600 4.90 11700 6.87 16800 8.79 1600 2.25 6700 4.95 11800 6.92 16900 8.81 1700 2.33 6800 5.01 11900 6.98 17000 8.85 1800 2.39 6900 4.99 12000 7.02 17100 8.90 1900 2.47 7000 5.04 12100 7.08 17200 8.95 2000 2.53 7100 5.11 12200 7.15 17300 8.99 2100 2.60 7200 5.14 12300 7.20 17400 9.03 2200 2.67 7300 5.21 12400 7.26 17500 9.07 2300 2.73 7400 5.29 12500 7.31 17600 9.11 2400 2.80 7500 5.33 12600 7.36 17700 9.15 2500 2.87 7600								
1600 2.25 6700 4.95 11800 6.92 16900 8.81 1700 2.33 6800 5.01 11900 6.98 17000 8.85 1800 2.39 6900 4.99 12000 7.02 17100 8.90 1900 2.47 7000 5.04 12100 7.08 17200 8.95 2000 2.53 7100 5.11 12200 7.15 17300 8.99 2100 2.60 7200 5.14 12300 7.20 17400 9.03 2200 2.67 7300 5.21 12400 7.26 17500 9.07 2300 2.73 7400 5.29 12500 7.31 17600 9.15 2400 2.80 7500 5.38 12700 7.41 17800 9.19 2600 2.93 7700 5.46 12800 7.46 17900 9.24 2700 3.00 7800								
1700 2.33 6800 5.01 11900 6.98 17000 8.85 1800 2.39 6900 4.99 12000 7.02 17100 8.90 1900 2.47 7000 5.04 12100 7.08 17200 8.95 2000 2.53 7100 5.11 12200 7.15 17300 8.99 2100 2.60 7200 5.14 12300 7.20 17400 9.03 2200 2.67 7300 5.21 12400 7.26 17500 9.07 2300 2.73 7400 5.29 12500 7.31 17600 9.07 2300 2.80 7500 5.33 12600 7.36 17700 9.15 2500 2.87 7600 5.38 12700 7.41 17800 9.19 2600 2.93 7700 5.46 12800 7.46 17900 9.24 2700 3.00 7800								
1800 2.39 6900 4.99 12000 7.02 17100 8.90 1900 2.47 7000 5.04 12100 7.08 17200 8.95 2000 2.53 7100 5.11 12200 7.15 17300 8.99 2100 2.60 7200 5.14 12300 7.20 17400 9.03 2200 2.67 7300 5.21 12400 7.26 17500 9.07 2300 2.73 7400 5.29 12500 7.31 17600 9.11 2400 2.80 7500 5.33 12600 7.36 17700 9.15 2500 2.87 7600 5.38 12700 7.41 17800 9.19 2600 2.93 7700 5.46 12800 7.46 17900 9.24 2700 3.00 7800 5.52 12900 7.51 18000 9.28 2800 3.06 7900								
1900 2.47 7000 5.04 12100 7.08 17200 8.95 2000 2.53 7100 5.11 12200 7.15 17300 8.99 2100 2.60 7200 5.14 12300 7.20 17400 9.03 2200 2.67 7300 5.21 12400 7.26 17500 9.07 2300 2.73 7400 5.29 12500 7.31 17600 9.11 2400 2.80 7500 5.33 12600 7.36 17700 9.15 2500 2.87 7600 5.38 12700 7.41 17800 9.19 2600 2.93 7700 5.46 12800 7.46 17900 9.24 2700 3.00 7800 5.52 12900 7.51 18000 9.28 2800 3.06 7900 5.58 13000 7.55 18000 9.28 2900 3.12 8000								
2000 2.53 7100 5.11 12200 7.15 17300 8.99 2100 2.60 7200 5.14 12300 7.20 17400 9.03 2200 2.67 7300 5.21 12400 7.26 17500 9.07 2300 2.73 7400 5.29 12500 7.31 17600 9.11 2400 2.80 7500 5.33 12600 7.36 17700 9.15 2500 2.87 7600 5.38 12700 7.41 17800 9.19 2600 2.93 7700 5.46 12800 7.46 17900 9.24 2700 3.00 7800 5.52 12900 7.51 18000 9.28 2800 3.06 7900 5.58 13000 7.55 2900 3.12 8000 5.64 13100 7.59 3100 3.24 8200 5.75 13300 7.69 3200 3.30 8300								
2100 2.60 7200 5.14 12300 7.20 17400 9.03 2200 2.67 7300 5.21 12400 7.26 17500 9.07 2300 2.73 7400 5.29 12500 7.31 17600 9.11 2400 2.80 7500 5.33 12600 7.36 17700 9.15 2500 2.87 7600 5.38 12700 7.41 17800 9.19 2600 2.93 7700 5.46 12800 7.46 17900 9.24 2700 3.00 7800 5.52 12900 7.51 18000 9.28 2800 3.06 7900 5.58 13000 7.55 18000 9.28 2900 3.12 8000 5.64 13100 7.59 300 3.18 8100 5.69 13200 7.65 3100 3.24 8200 5.75 13300 7.69 320 3.30 8300 </td <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>								
2200 2.67 7300 5.21 12400 7.26 17500 9.07 2300 2.73 7400 5.29 12500 7.31 17600 9.11 2400 2.80 7500 5.33 12600 7.36 17700 9.15 2500 2.87 7600 5.38 12700 7.41 17800 9.19 2600 2.93 7700 5.46 12800 7.46 17900 9.24 2700 3.00 7800 5.52 12900 7.51 18000 9.28 2800 3.06 7900 5.58 13000 7.55 18000 9.28 2900 3.12 8000 5.64 13100 7.59 3000 3.18 8100 5.69 13200 7.65 3100 3.24 8200 5.75 13300 7.69 3200 3.30 8300 5.80 13400 7.72 3300 3.46 8600 5.97 13700 7								
2300 2.73 7400 5.29 12500 7.31 17600 9.11 2400 2.80 7500 5.33 12600 7.36 17700 9.15 2500 2.87 7600 5.38 12700 7.41 17800 9.19 2600 2.93 7700 5.46 12800 7.46 17900 9.24 2700 3.00 7800 5.52 12900 7.51 18000 9.28 2800 3.06 7900 5.58 13000 7.55 18000 9.28 2900 3.12 8000 5.64 13100 7.59 3000 3.18 8100 5.69 13200 7.65 3100 3.24 8200 5.75 13300 7.69 3200 3.30 8300 5.84 13500 7.78 3400 3.42 8500 5.90 13600 7.82 3500 3.46 8600 5.97 13700 7.86 3600 3.52 <td< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></td<>								
2400 2.80 7500 5.33 12600 7.36 17700 9.15 2500 2.87 7600 5.38 12700 7.41 17800 9.19 2600 2.93 7700 5.46 12800 7.46 17900 9.24 2700 3.00 7800 5.52 12900 7.51 18000 9.28 2800 3.06 7900 5.58 13000 7.55 18000 9.28 2900 3.12 8000 5.64 13100 7.59 300 3.18 8100 5.69 13200 7.65 3100 3.24 8200 5.75 13300 7.69 3200 3.30 8300 5.80 13400 7.72 3300 3.42 8500 5.84 13500 7.78 3400 3.42 8500 5.90 13600 7.82 3500 3.46 8600 5.97 13700 7.86 3600 3.57 8800 6.04 13900 <								
2500 2.87 7600 5.38 12700 7.41 17800 9.19 2600 2.93 7700 5.46 12800 7.46 17900 9.24 2700 3.00 7800 5.52 12900 7.51 18000 9.28 2800 3.06 7900 5.58 13000 7.55 18000 9.28 2900 3.12 8000 5.64 13100 7.59 3000 3.18 8100 5.69 13200 7.65 3100 3.24 8200 5.75 13300 7.69 3200 3.30 8300 5.80 13400 7.72 3300 3.35 8400 5.84 13500 7.78 3400 3.42 8500 5.90 13600 7.82 3500 3.46 8600 5.97 13700 7.86 3600 3.52 8700 5.99 13800 7.91 3700 3.57 8800 6.04 13900 7.96 3800 3.61								
2600 2.93 7700 5.46 12800 7.46 17900 9.24 2700 3.00 7800 5.52 12900 7.51 18000 9.28 2800 3.06 7900 5.58 13000 7.55 18000 9.28 2900 3.12 8000 5.64 13100 7.59 3000 3.18 8100 5.69 13200 7.65 3100 3.24 8200 5.75 13300 7.69 3200 3.30 8300 5.80 13400 7.72 3300 3.35 8400 5.84 13500 7.78 3400 3.42 8500 5.90 13600 7.82 3500 3.46 8600 5.97 13700 7.86 3600 3.52 8700 5.99 13800 7.91 3700 3.57 8800 6.04 13900 7.96 3800 3.61 8900 6.10 14000 8.01 3900 3.67 9000 6.13 14100								
2700 3.00 7800 5.52 12900 7.51 18000 9.28 2800 3.06 7900 5.58 13000 7.55 1300 7.59 3000 3.12 8000 5.64 13100 7.59 3000 3.18 8100 5.69 13200 7.65 3100 3.24 8200 5.75 13300 7.69 3200 3.30 8300 5.80 13400 7.72 3300 3.35 8400 5.84 13500 7.78 3400 3.42 8500 5.90 13600 7.82 3500 3.46 8600 5.97 13700 7.86 3600 3.52 8700 5.99 13800 7.91 3700 3.57 8800 6.04 13900 7.96 3800 3.61 8900 6.10 14000 8.01 3900 3.67 9000 6.13 14100 8.06 4000 3.71 9100 6.17 14200 8.10 4100 3.83 9300								
2800 3.06 7900 5.58 13000 7.55 2900 3.12 8000 5.64 13100 7.59 3000 3.18 8100 5.69 13200 7.65 3100 3.24 8200 5.75 13300 7.69 3200 3.30 8300 5.80 13400 7.72 3300 3.35 8400 5.84 13500 7.78 3400 3.42 8500 5.90 13600 7.82 3500 3.46 8600 5.97 13700 7.86 3600 3.52 8700 5.99 13800 7.91 3700 3.57 8800 6.04 13900 7.96 3800 3.61 8900 6.10 14000 8.01 3900 3.67 9000 6.13 14100 8.06 4000 3.71 9100 6.17 14200 8.10 4100 3.83 930								
2900 3.12 8000 5.64 13100 7.59 3000 3.18 8100 5.69 13200 7.65 3100 3.24 8200 5.75 13300 7.69 3200 3.30 8300 5.80 13400 7.72 3300 3.35 8400 5.84 13500 7.78 3400 3.42 8500 5.90 13600 7.82 3500 3.46 8600 5.97 13700 7.86 3600 3.52 8700 5.99 13800 7.91 3700 3.57 8800 6.04 13900 7.96 3800 3.61 8900 6.10 14000 8.01 3900 3.67 9000 6.13 14100 8.06 4000 3.71 9100 6.17 14200 8.10 4100 3.83 9300 6.27 14400 8.16 4200 3.83 940							18000	9.28
3000 3.18 8100 5.69 13200 7.65 3100 3.24 8200 5.75 13300 7.69 3200 3.30 8300 5.80 13400 7.72 3300 3.35 8400 5.84 13500 7.78 3400 3.42 8500 5.90 13600 7.82 3500 3.46 8600 5.97 13700 7.86 3600 3.52 8700 5.99 13800 7.91 3700 3.57 8800 6.04 13900 7.96 3800 3.61 8900 6.10 14000 8.01 3900 3.67 9000 6.13 14100 8.06 4000 3.71 9100 6.17 14200 8.10 4100 3.77 9200 6.23 14300 8.13 4200 3.83 9300 6.27 14400 8.16 4300 3.94 950								
3100 3.24 8200 5.75 13300 7.69 3200 3.30 8300 5.80 13400 7.72 3300 3.35 8400 5.84 13500 7.78 3400 3.42 8500 5.90 13600 7.82 3500 3.46 8600 5.97 13700 7.86 3600 3.52 8700 5.99 13800 7.91 3700 3.57 8800 6.04 13900 7.96 3800 3.61 8900 6.10 14000 8.01 3900 3.67 9000 6.13 14100 8.06 4000 3.71 9100 6.17 14200 8.10 4100 3.77 9200 6.23 14300 8.13 4200 3.83 9300 6.27 14400 8.16 4300 3.89 9400 6.35 14600 8.21								
3200 3.30 8300 5.80 13400 7.72 3300 3.35 8400 5.84 13500 7.78 3400 3.42 8500 5.90 13600 7.82 3500 3.46 8600 5.97 13700 7.86 3600 3.52 8700 5.99 13800 7.91 3700 3.57 8800 6.04 13900 7.96 3800 3.61 8900 6.10 14000 8.01 3900 3.67 9000 6.13 14100 8.06 4000 3.71 9100 6.17 14200 8.10 4100 3.77 9200 6.23 14300 8.13 4200 3.83 9300 6.27 14400 8.16 4300 3.89 9400 6.30 14500 8.21								
3300 3.35 8400 5.84 13500 7.78 3400 3.42 8500 5.90 13600 7.82 3500 3.46 8600 5.97 13700 7.86 3600 3.52 8700 5.99 13800 7.91 3700 3.57 8800 6.04 13900 7.96 3800 3.61 8900 6.10 14000 8.01 3900 3.67 9000 6.13 14100 8.06 4000 3.71 9100 6.17 14200 8.10 4100 3.77 9200 6.23 14300 8.13 4200 3.83 9300 6.27 14400 8.16 4300 3.89 9400 6.30 14500 8.19 4400 3.94 9500 6.35 14600 8.21								
3400 3.42 8500 5.90 13600 7.82 3500 3.46 8600 5.97 13700 7.86 3600 3.52 8700 5.99 13800 7.91 3700 3.57 8800 6.04 13900 7.96 3800 3.61 8900 6.10 14000 8.01 3900 3.67 9000 6.13 14100 8.06 4000 3.71 9100 6.17 14200 8.10 4100 3.77 9200 6.23 14300 8.13 4200 3.83 9300 6.27 14400 8.16 4300 3.89 9400 6.30 14500 8.21								
3500 3.46 8600 5.97 13700 7.86 3600 3.52 8700 5.99 13800 7.91 3700 3.57 8800 6.04 13900 7.96 3800 3.61 8900 6.10 14000 8.01 3900 3.67 9000 6.13 14100 8.06 4000 3.71 9100 6.17 14200 8.10 4100 3.77 9200 6.23 14300 8.13 4200 3.83 9300 6.27 14400 8.16 4300 3.89 9400 6.30 14500 8.19 4400 3.94 9500 6.35 14600 8.21								
3600 3.52 8700 5.99 13800 7.91 3700 3.57 8800 6.04 13900 7.96 3800 3.61 8900 6.10 14000 8.01 3900 3.67 9000 6.13 14100 8.06 4000 3.71 9100 6.17 14200 8.10 4100 3.77 9200 6.23 14300 8.13 4200 3.83 9300 6.27 14400 8.16 4300 3.89 9400 6.30 14500 8.19 4400 3.94 9500 6.35 14600 8.21								
3700 3.57 8800 6.04 13900 7.96 3800 3.61 8900 6.10 14000 8.01 3900 3.67 9000 6.13 14100 8.06 4000 3.71 9100 6.17 14200 8.10 4100 3.77 9200 6.23 14300 8.13 4200 3.83 9300 6.27 14400 8.16 4300 3.89 9400 6.30 14500 8.19 4400 3.94 9500 6.35 14600 8.21								
3800 3.61 8900 6.10 14000 8.01 3900 3.67 9000 6.13 14100 8.06 4000 3.71 9100 6.17 14200 8.10 4100 3.77 9200 6.23 14300 8.13 4200 3.83 9300 6.27 14400 8.16 4300 3.89 9400 6.30 14500 8.19 4400 3.94 9500 6.35 14600 8.21								ļ
3900 3.67 9000 6.13 14100 8.06 4000 3.71 9100 6.17 14200 8.10 4100 3.77 9200 6.23 14300 8.13 4200 3.83 9300 6.27 14400 8.16 4300 3.89 9400 6.30 14500 8.19 4400 3.94 9500 6.35 14600 8.21								1
4000 3.71 9100 6.17 14200 8.10 4100 3.77 9200 6.23 14300 8.13 4200 3.83 9300 6.27 14400 8.16 4300 3.89 9400 6.30 14500 8.19 4400 3.94 9500 6.35 14600 8.21								
4100 3.77 9200 6.23 14300 8.13 4200 3.83 9300 6.27 14400 8.16 4300 3.89 9400 6.30 14500 8.19 4400 3.94 9500 6.35 14600 8.21								
4200 3.83 9300 6.27 14400 8.16 4300 3.89 9400 6.30 14500 8.19 4400 3.94 9500 6.35 14600 8.21								
4300 3.89 9400 6.30 14500 8.19 4400 3.94 9500 6.35 14600 8.21								
4400 3.94 9500 6.35 14600 8.21		3.83	9300			8.16		
	4300	3.89	9400	6.30	14500	8.19		
4500 4.00 9600 6.37 14700 8.23	4400	3.94	9500	6.35	14600	8.21		
	4500	4.00	9600	6.37	14700	8.23		
4600 4.05 9700 6.40 14800 8.26	4600	4.05	9700	6.40	14800	8.26		
4700 4.10 9800 6.44 14900 8.28	4700		9800		14900			
4800 4.16 9900 6.45 15000 8.30	4800	4.16	9900	6.45	15000	8.30		





Cable loss Low Loss Armored Test Cable, MegaPhase, 18 GHz, 6.2 m, N type-M/N type-M, NC29-N1N1-244S/N 12025101 003, HL 4353

Frequency, MHz	Cable loss, dB	Frequency, MHz	Cable loss, dB
50	0.20	9000	2.71
100	0.27	9500	2.81
300	0.47	10000	2.90
500	0.61	10500	2.97
1000	0.87	11000	3.06
1500	1.07	11500	3.13
2000	1.24	12000	3.20
2500	1.39	12500	3.26
3000	1.53	13000	3.34
3500	1.65	13500	3.39
4000	1.77	14000	3.47
4500	1.89	14500	3.54
5000	1.99	15000	3.62
5500	2.07	15500	3.69
6000	2.20	16000	3.76
6500	2.30	16500	3.83
7000	2.39	17000	3.86
7500	2.51	17500	3.94
8000	2.58	18000	4.02
8500	2.65		





Cable loss Low Loss Armored Test Cable, MegaPhase, 18 GHz, 4.5 m, N type-M/N type-M, NC29-N1N1-177, S/N 51300101 002 HL 4720

Frequency, MHz	Cable loss, dB	Frequency, MHz	Cable loss, dB
50	0.14	9000	2.10
100	0.21	9500	2.26
300	0.36	10000	2.39
500	0.46	10500	2.36
1000	0.66	11000	2.36
1500	0.81	11500	2.44
2000	0.93	12000	2.51
2500	1.05	12500	2.71
3000	1.15	13000	2.71
3500	1.25	13500	2.69
4000	1.34	14000	2.78
4500	1.42	14500	2.84
5000	1.52	15000	2.85
5500	1.60	15500	2.98
6000	1.66	16000	3.02
6500	1.78	16500	3.09
7000	1.82	17000	3.11
7500	1.86	17500	3.16
8000	1.95	18000	3.32
8500	2.01		



14 APPENDIX F Abbreviations and acronyms

A ampere

AC alternating current
AM amplitude modulation
AVRG average (detector)

cm centimeter dB decibel

 $\begin{array}{ll} \text{dBm} & \text{decibel referred to one milliwatt} \\ \text{dB}(\mu V) & \text{decibel referred to one microvolt} \end{array}$

 $dB(\mu V/m)$ decibel referred to one microvolt per meter

 $dB(\mu A) \hspace{1cm} \text{decibel referred to one microampere} \\$

DC direct current

EIRP equivalent isotropically radiated power

ERP effective radiated power EUT equipment under test

F frequency GHz gigahertz GND ground H height

HL Hermon laboratories

Hz hertz kilo kHz kilohertz LO local oscillator m meter MHz megahertz min minute millimeter mm ms millisecond microsecond μS NA not applicable

 $\begin{array}{ll} \text{OATS} & \text{open area test site} \\ \Omega & \text{Ohm} \end{array}$

NB

PM pulse modulation PS power supply

ppm part per million (10⁻⁶)

narrow band

QP quasi-peak
RE radiated emission
RF radio frequency
rms root mean square

Rx receive
s second
T temperature
Tx transmit
V volt
WB wideband

END OF DOCUMENT

Page 72 of 72