

This development tool is designed for debugging the Power G protocol, including functionality for the Sniffer, Panel Emulator, Panel Simulator on the cloud, and Manufacturing Tool.

The reference to PG DEV TOOL throughout this document includes the model PG DEV TOOL PANEL EMULATOR 915 MHz and 868 MHz, and PG DEV TOOL DEVICE EMULATOR 915 MHz and 868 MHz.

For the full installer and user manual, refer to D-309743.

#### FCC and ISED Compliance Statement

This device complies with Part 15 of the FCC Rules and with Industry Canada license-exempt RSS standard(s). Operation is subject to the following two conditions:

(1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Le présent appareil est conforme aux CNR d'Industrie Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes : (1) l'appareil ne doit pas produire de brouillage, et (2) l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.

To comply with FCC Section 1.1310 for human exposure to radio frequency electromagnetic fields and IC requirements, implement the following instruction:

A distance of at least 20cm. between the equipment and all persons should be maintained during the operation of the equipment.

Le dispositif doit être placé à une distance d'au moins 20 cm à partir de toutes les personnes au cours de son fonctionnement normal. Les antennes utilisées pour ce produit ne doivent pas être situées ou exploitées conjointement avec une autre antenne ou transmetteur.

**NOTE:** This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

This Class B digital apparatus complies with Canadian ICES-003.

Cet appareil numerique de la classe B est conforme à la norme NMB-003 du Canada

**WARNING!** Changes or modifications to this unit not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

#### Simplified EU declaration of conformity

Hereby, Visonic Ltd. declares that the radio equipment types PG DEV TOOL DEVICE OR PANEL EMULATOR 868 MHz is in compliance with Directive 2014/53/EU.

The full text of the EU declaration of conformity is available at the following internet address: <https://www.visonic.com/resources>.

Frequency band	Maximum power
868.0 MHz - 868.6 MHz	+14 dBm
868.7 MHz - 869.2 MHz	+14 dBm

European single Point of Contact: Tyco Security Products, Voltaweg 20, 6101 Xk Echt, Netherlands

UK Single point of contact: Johnson Controls / Units 1,3&4 Works Road / Letchworth / SG6 1FF / UK

#### Product Certification

PG DEV TOOL DEVICE EMULATOR AND PANEL EMULATOR complies with the following standards:

PG DEV TOOL DEVICE EMULATOR OR PANEL EMULATOR 915 MHz	FCC (912 to 919 MHz): 47CFR part 15.247 ISED Canada (912 to 919 MHz): RSS-247
PG DEV TOOL DEVICE EMULATOR OR PANEL EMULATOR 868 MHz	EN 300220, EN 301489, EN 61000-6-3, EN 62368-1

#### Safety Instructions

The PG DEV TOOL PANEL EMULATOR AND DEVICE EMULATOR is powered by USB connection only.

Input: 5V/1A DC

Temperature range: +10°C to +50°C

#### WEEE Product recycling declaration



For information regarding the recycling of this product you must contact the company from which you originally purchased it. If you are discarding this product and not returning it for repair then you must ensure that it is returned as identified by your supplier. This product is not to be thrown away with everyday waste.  
Directive 2012/19/EU Waste Electrical and Electronic Equipment.

© 2025 Johnson Controls. All rights reserved. JOHNSON CONTROLS is a registered trademark. Unauthorized use is strictly prohibited.



D-309414 PG DEV TOOL DEVICE EMULATOR OR PANEL EMULATOR Rev. 0 (02/25)



D-309414