

To whom it may concern:

Axxess Industries Inc. would like to apply for single modular FCC approval. This letter is our application for such according to FCC Part 15.212.

Modular Transmitter Requirements	Manufacturer Clarification
1. The radio elements must have the radio frequency circuitry shielded. Physical components and tuning capacitor(s) may be located external to the shield, but must be on the module assembly	A shield is provided on the module.
2. The module must have buffered modulation/data inputs to ensure that the device will comply with Part 15 requirements with any type of input signal	Signals are directly connected to the EM357 SoC which has buffered I/O ports.
3. The module must contain power supply regulation on the module	The module generates 1v8 for RF circuitry
4. The module must contain a permanently attached antenna, or contain a unique antenna connector, and be marketed and operated only with specific antenna(s), per Sections 15.203, 15.204(b), 15.204(c), 15.212(a), 2.929(b)	The module has a PCB trace antenna with no external antenna options.
5. The module must demonstrate compliance in a stand-alone configuration	The module was mounted on a bare carrier PCB for test purposes. Only power was supplied via the carrier PCB.
6. The module must be labelled with its permanently affixed FCC ID label, or use an electronic display	FCC ID number is clearly shown on module.
7. The module must comply with all specific rules applicable to the transmitter. The grantee must provide comprehensive instructions to explain compliance requirements	Module is shown to be compliant with 15.247 of the rules.
8. The module must comply with RF exposure requirements.	Module complies with RF exposure requirements. See RF exposure exhibit for details.