

# Global United Technology Services Co., Ltd.

Report No.: GTS201701000007F01

# FCC Report (Bluetooth)

Autel Intelligent Tech. Corp., Ltd. Applicant:

6th - 10th Floor, Bldg. B1, Zhiyuan, Xueyuan Rd., Xili, Nanshan **Address of Applicant:** 

Shenzhen China

Manufacturer/ Factory: Autel Intelligent Tech. Corp., Ltd.

6th - 10th Floor, Bldg. B1, Zhiyuan, Xueyuan Rd., Xili, Nanshan Address of

Shenzhen China **Manufacturer/ Factory:** 

**Equipment Under Test (EUT)** 

**Product Name:** COMPREHENSIVE TPMS TOOL

Model No.: MaxiTPMS TS608, MaxiTPMS MX808TS

Trade Mark: **AUTEL** 

FCC ID: WQ8MX808-TPMS

**Applicable standards:** FCC CFR Title 47 Part 15 Subpart C Section 15.247:2016

Date of sample receipt: January 04, 2017

Date of Test: January 05-16, 2017

Date of report issued: January 17, 2017

Test Result: PASS \*

In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Robinson Lo Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.



# 2 Version

Version No.	Date	Description
00	January 17, 2017	Original

Prepared By:	Joseph Cly	Date:	January 17, 2017
	Project Engineer		
Check By:	Andy wa	Date:	January 17, 2017

Reviewer



# 3 Contents

			Page
1	COVE	ER PAGE	1
2	VERS	SION	2
3	CONT	TENTS	3
4	TEST	SUMMARY	4
5	GENE	ERAL INFORMATION	5
	5.1	GENERAL DESCRIPTION OF EUT	5
	5.2	Test mode	7
		Test Facility	
		TEST LOCATION	
		OTHER INFORMATION REQUESTED BY THE CUSTOMER	
		DESCRIPTION OF SUPPORT UNITS	
6	TEST	INSTRUMENTS LIST	8
7	TEST	RESULTS AND MEASUREMENT DATA	9
	7.1	Antenna requirement	9
	7.2	CONDUCTED EMISSIONS	10
	7.3	CONDUCTED PEAK OUTPUT POWER	13
		20dB Emission Bandwidth	
		CARRIER FREQUENCIES SEPARATION	
		HOPPING CHANNEL NUMBER	
		DWELL TIME	
		PSEUDORANDOM FREQUENCY HOPPING SEQUENCE	
		BAND EDGE	
	7.9.1 7.9.2		
		Spurious Emission inetriod	
	7.10 3 7.10.1		
	7.10. 7.10.2		
8		SETUP PHOTO	
^	<b>-</b> 11 <b>-</b> 1	CONSTRUCTIONAL DETAILS	44



# 4 Test Summary

Test Item	Section in CFR 47	Result
Antenna Requirement	15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Peak Output Power	15.247 (b)(1)	Pass
20dB Occupied Bandwidth	15.247 (a)(1)	Pass
Carrier Frequencies Separation	15.247 (a)(1)	Pass
Hopping Channel Number	15.247 (a)(1)	Pass
Dwell Time	15.247 (a)(1)	Pass
Pseudorandom Frequency Hopping	15.247(b)(4)&TCB Exclusion List	Pass
Sequence	(7 July 2002)	Pass
Radiated Emission	15.205/15.209	Pass
Band Edge	15.247(d)	Pass

Pass: The EUT complies with the essential requirements in the standard.

Remark: Test according to ANSI C63.10:2013.

#### **Measurement Uncertainty**

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	9kHz ~ 30MHz	± 4.34dB	(1)
Radiated Emission	30MHz ~ 1000MHz	± 4.24dB	(1)
Radiated Emission	1GHz ~ 26.5GHz	± 4.68dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	± 3.45dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.



# 5 General Information

# 5.1 General Description of EUT

•			
Product Name:	COMPREHENSIVE TPMS TOOL		
Model No.:	MaxiTPMS TS608, MaxiTPMS MX808TS		
Test Model:	MaxiTPMS TS608		
	are identical in the same PCB layout, interior structure and electrical circuits is the model name for commercial purpose.		
Operation Frequency:	2402MHz~2480MHz		
Channel numbers:	79		
Channel separation:	1MHz		
Modulation type:	GFSK, Pi/4 QPSK, 8DPSK		
Antenna Type:	Integral antenna		
Antenna gain:	0.5dBi (declare by Applicant)		
Power supply:	Adapter:		
	Model:GME10C-050200FUu		
	Input: AC 100-240V, 50-60Hz, 0.28A		
	Output: DC 5V, 2A		
	DC 3.7V 5000mAh Lithium Battery		



Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
3	2404MHz	23	2424MHz	43	2444MHz	63	2464MHz
4	2405MHz	24	2425MHz	44	2445MHz	64	2465MHz
5	2406MHz	25	2426MHz	45	2446MHz	65	2466MHz
6	2407MHz	26	2427MHz	46	2447MHz	66	2467MHz
7	2408MHz	27	2428MHz	47	2448MHz	67	2468MHz
8	2409MHz	28	2429MHz	48	2449MHz	68	2469MHz
9	2410MHz	29	2430MHz	49	2450MHz	69	2470MHz
10	2411MHz	30	2431MHz	50	2451MHz	70	2471MHz
11	2412MHz	31	2432MHz	51	2452MHz	71	2472MHz
12	2413MHz	32	2433MHz	52	2453MHz	72	2473MHz
13	2414MHz	33	2434MHz	53	2454MHz	73	2474MHz
14	2415MHz	34	2435MHz	54	2455MHz	74	2475MHz
15	2416MHz	35	2436MHz	55	2456MHz	75	2476MHz
16	2417MHz	36	2437MHz	56	2457MHz	76	2477MHz
17	2418MHz	37	2438MHz	57	2458MHz	77	2478MHz
18	2419MHz	38	2439MHz	58	2459MHz	78	2479MHz
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

#### Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2402MHz
The middle channel	2441MHz
The Highest channel	2480MHz



# 5.2 Test mode

Transmitting mode Turn off the WiFi and keep the Bluetooth in continuously transmitting mode

Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.

# 5.3 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

#### • FCC —Registration No.: 600491

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fuly described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 600491, June 22, 2016.

# • Industry Canada (IC) —Registration No.: 9079A-2

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2, August 15, 2016.

# 5.4 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.

Address: No. 301-309, 3/F., Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102

Tel: 0755-27798480 Fax: 0755-27798960

# 5.5 Other Information Requested by the Customer

None.

# 5.6 Description of Support Units

None.



# 6 Test Instruments list

Rad	Radiated Emission:							
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)		
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.0(L)*6.0(W)* 6.0(H)	GTS250	July. 03 2015	July. 02 2020		
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A		
3	Spectrum Analyzer	Agilent	E4440A	GTS533	June 29 2016	June 28 2017		
4	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June 29 2016	June 28 2017		
5	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June 29 2016	June 28 2017		
6	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	9120D-829	GTS208	June 29 2016	June 28 2017		
7	Horn Antenna	ETS-LINDGREN	3160	GTS217	June 29 2016	June 28 2017		
8	EMI Test Software	AUDIX	E3	N/A	N/A	N/A		
9	Coaxial Cable	GTS	N/A	GTS213	June 29 2016	June 28 2017		
10	Coaxial Cable	GTS	N/A	GTS211	June 29 2016	June 28 2017		
11	Coaxial cable	GTS	N/A	GTS210	June 29 2016	June 28 2017		
12	Coaxial Cable	GTS	N/A	GTS212	June 29 2016	June 28 2017		
13	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June 29 2016	June 28 2017		
14	Amplifier(2GHz-20GHz)	HP	8349B	GTS206	June 29 2016	June 28 2017		
15	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June 29 2016	June 28 2017		
16	Band filter	Amindeon	82346	GTS219	June 29 2016	June 28 2017		

Cond	Conducted Emission:							
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)		
1	Shielding Room	ZhongYu Electron	7.0(L)x3.0(W)x3.0(H)	GTS264	June 29 2016	June 28 2017		
2	EMI Test Receiver	Rohde & Schwarz	ESCS30	GTS223	June 29 2016	June 28 2017		
3	10dB Pulse Limita	Rohde & Schwarz	N/A	GTS224	June 29 2016	June 28 2017		
4	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	June 29 2016	June 28 2017		
5	LISN	SCHWARZBECK MESS-ELEKTRONIK	NSLK 8127	GTS226	June 29 2016	June 28 2017		
6	Coaxial Cable	GTS	N/A	GTS227	June 29 2016	June 28 2017		
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A		

Gen	General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)	
1	Barometer	ChangChun	DYM3	GTS257	June 29 2016	June 28 2017	

Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102 Telephone: +86 (0) 755 2779 8480 Fax: +86 (0) 755 2779 8960



# 7 Test results and Measurement Data

# 7.1 Antenna requirement

**Standard requirement:** FCC Part15 C Section 15.203 /247(c)

#### 15.203 requirement:


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

## 15.247(c) (1)(i) requirement:

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

#### **E.U.T Antenna:**

The antenna is Integral antenna, the best case gain of the antenna is -0.9dBi






# 7.2 Conducted Emissions

	T						
Test Requirement:	FCC Part15 C Section 15.207						
Test Method:	ANSI C63.10:2013						
Test Frequency Range:	150KHz to 30MHz						
Receiver setup:	RBW=9KHz, VBW=30KHz, Sv	weep time=auto					
Limit:	Frequency range (MHz)  Limit (dBuV)						
		Quasi-peak	Average				
	0.15-0.5 66 to 56* 56 to 4 0.5-5 56 46						
	0.5-5     56     46       5-30     60     50						
	5-30 60 50  * Decreases with the logarithm of the frequency.						
Test setup:	3	n of the frequency.					
,	Reference Plane  LISN  40cm  80cm  Filter  AC power  Equipment  Test table/Insulation plane  Remark  E.U.T Equipment Under Test  LISN: Line Impedence Stabilization Network  Test table height=0.8m						
Test procedure:	<ol> <li>The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.</li> <li>The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</li> <li>Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement.</li> </ol>						
Test Instruments:	Refer to section 6.0 for details						
Test mode:	Refer to section 5.2 for details						
Test results:	Pass						

# Measurement data:




# Line:



Freq MHz	Reading level dBuV	1ISN/ISN factor dB	Cable loss dB	level dBuV	Limit level dBuV	Over limit dB	Remark
0.156	46.73	0.42	0.12	47.27	65.65	-18.38	QP
0.234	36.35	0.43	0.12	36.90	62.30	-25.40	QP
0.320	33.17	0.44	0.10	33.71	59.71	-26.00	QP
0.505	29.44	0.38	0.11	29.93	56.00	-26.07	QP
0.641	30.28	0.30	0.13	30.71	56.00	-25.29	QP
0.839	28.89	0.26	0.13	29.28	56.00	-26.72	QP







Freq MHz	Reading level dBuV	1ISN/ISN factor dB	Cable loss dB	level dBuV	Limit level dBuV	Over limit dB	Remark	
0.152 0.197	47.05 41.51	0.41 0.41	0.12 0.13	47.58 42.05	65.91 63.76	-18.33 -21.71	QP QP	
0.320 0.641	33.27 31.10	0.42 0.26	0.10 0.13	33.79 31.49	59.71 56.00	-25.92 -24.51	QP QP	
0.839 0.974	28.49 26.79	0.22 0.21	0.13 0.13	28.84 27.13	56.00 56.00	-27.16 -28.87	QP QP	

#### Notes:

- 1. An initial pre-scan was performed on the line and neutral lines with peak detector.
- 2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
- 3. Final Level =Receiver Read level + LISN Factor + Cable Loss



# 7.3 Conducted Peak Output Power

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)		
Test Method:	ANSI C63.10:2013		
Limit:	30dBm(for GFSK),20.97dBm(for EDR)		
Test setup:	Spectrum Analyzer  E.U.T  Non-Conducted Table  Ground Reference Plane		
Test Instruments:	Refer to section 6.0 for details		
Test mode:	Refer to section 5.2 for details		
Test results:	Pass		

# **Measurement Data**

Mode	Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
	Lowest	12.01		
GFSK	Middle	11.89	30.00	Pass
	Highest	11.87		
	Lowest	11.66		Pass
Pi/4QPSK	Middle	11.75	20.97	
	Highest	11.89		
	Lowest	11.64		
8DPSK	Middle	11.59	20.97	Pass
	Highest	11.78		



# 7.4 20dB Emission Bandwidth

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)		
Test Method:	ANSI C63.10:2013		
Limit:	N/A		
Test setup:	Spectrum Analyzer  E.U.T  Non-Conducted Table  Ground Reference Plane		
Test Instruments:	Refer to section 6.0 for details		
Test mode:	Refer to section 5.2 for details		
Test results:	Pass		


# **Measurement Data**

Mode	Test channel	20dB Emission Bandwidth (MHz)	Result
	Lowest	0.869	
GFSK	Middle	0.869	Pass
	Highest	0.874	
	Lowest	1.26	
Pi/4QPSK	Middle	1.231	Pass
	Highest	1.224	
	Lowest	1.216	
8DPSK	Middle	1.220	Pass
	Highest	1.217	





#### Test plot as follows:

Test mode: GFSK mode




#### Lowest channel







Highest channel

Test mode: Pi/4QPSK mode



#### Lowest channel







Highest channel

Test mode: 8DPSK mode



#### Lowest channel





Highest channel



# 7.5 Carrier Frequencies Separation

<del>_</del>	•		
Test Requirement:	FCC Part15 C Section 15.247 (a)(1)		
Test Method:	ANSI C63.10:2013		
Receiver setup:	RBW=100KHz, VBW=300KHz, detector=Peak		
Limit:	0.025MHz or 2/3 of the 20dB bandwidth (whichever is greater)		
Test setup:	Spectrum Analyzer  E.U.T  Non-Conducted Table  Ground Reference Plane		
Test Instruments: Refer to section 6.0 for details			
Test mode:	Refer to section 5.2 for details		
Test results:	Pass		

# **Measurement Data**

Mode	Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result
	Lowest	1005	583	Pass
GFSK	Middle	1005	583	Pass
	Highest	1005	583	Pass
	Lowest	1005	821	Pass
Pi/4QPSK	Middle	1005	821	Pass
	Highest	1005	821	Pass
	Lowest	1005	813	Pass
8DSK	Middle	1005	813	Pass
	Highest	1005	813	Pass


Note: According to section 7.4

Mode Mode		20dB bandwidth (kHz)	Limit (kHz)
		(worse case)	(Carrier Frequencies Separation)
	GFSK	874	583
	Pi/4QPSK	1231	821
	8DSK	1220	813




# Test plot as follows:


Modulation mode: GFSK



#### Lowest channel




# Middle channel




Highest channel

Test mode: Pi/4QPSK mode




#### Lowest channel







Highest channel

Test mode: 8DPSK mode



#### Lowest channel





Highest channel




# 7.6 Hopping Channel Number

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)		
Test Method:	ANSI C63.10:2013		
Receiver setup:	RBW=100kHz, VBW=300kHz, Frequency range=2400MHz-2483.5MHz, Detector=Peak		
Limit:	15 channels		
Test setup:	Spectrum Analyzer  E.U.T  Non-Conducted Table  Ground Reference Plane		
Test Instruments:	Refer to section 6.0 for details		
Test mode:	Refer to section 5.2 for details		
Test results:	Pass		

#### **Measurement Data:**

Mode	Hopping channel numbers	Limit	Result
GFSK	79	15	Pass
Pi/4QPSK	79	15	Pass
8DPSK	79	15	Pass





# 7.7 Dwell Time

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)		
Test Method:	ANSI C63.10:2013		
Receiver setup:	RBW=1MHz, VBW=1MHz, Span=0Hz, Detector=Peak		
Limit:	0.4 Second		
Test setup:	Spectrum Analyzer  E.U.T  Non-Conducted Table  Ground Reference Plane		
Test Instruments:	Refer to section 6.0 for details		
Test mode:	Refer to section 5.2 for details		
Test results:	Pass		

## **Measurement Data**


Frequency (MHz)	Packet	Dwell time(ms)	Limit(ms)	Result
2441	DH1/2-DH1/3-DH1	126.40	400	Pass
2441	DH3/2-DH3/3-DH3	264.00	400	Pass
2441	DH5/2-DH5/3-DH5	307.52	400	Pass

The test period: T= 0.4 Second/Channel x 79 Channel = 31.6 s


DH1 time slot=0.395(ms)\*(1600/ (2\*79))\*31.6=126.40ms

DH3 time slot=1.65(ms)\*(1600/ (4\*79))\*31.6=264.00ms


DH5 time slot=2.883(ms)\*(1600/ (6\*79))\*31.6=307.52ms








DH1/2-DH1/3-DH1



DH3/2-DH3/3-DH3



DH5/2-DH5/3-DH5



# 7.8 Pseudorandom Frequency Hopping Sequence

# Test Requirement: FCC Part15 C Section 15.247 (a)(1) requirement:


Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Alternatively. Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

### **EUT Pseudorandom Frequency Hopping Sequence**


The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence: 2<sup>9</sup>-1 = 511 bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.

The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.



# 7.9 Band Edge


# 7.9.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)			
Test Method:	ANSI C63.10:2013			
Receiver setup:	RBW=100kHz, VBW=300kHz, Detector=Peak			
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.			
Test setup:	Spectrum Analyzer  E.U.T  Non-Conducted Table  Ground Reference Plane			
Test Instruments:	Refer to section 6.0 for details			
Test mode:	Refer to section 5.2 for details			
Test results:	Pass			

# Test plot as follows:




#### **GFSK Mode:**



No-hopping mode

Hopping mode




No-hopping mode

Hopping mode




#### Pi/4QPSK Mode:



No-hopping mode

Hopping mode




No-hopping mode

Hopping mode




#### **8DPSK Mode:**



No-hopping mode

Hopping mode



No-hopping mode

Hopping mode



# 7.9.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 and 15.205					
Test Method:	ANSI C63.10:2013					
Test Frequency Range:	All restriction band have been tested, and 2.3GHz to 2.5GHz band is the worse case					
Test site:	Measurement D	istance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark	
Trootive. Cottap.		Peak	1MHz	3MHz	Peak Value	
	Above 1GHz	Peak	1MHz	10Hz	Average Value	
Limit:	Freque	ncy	Limit (dBuV/	m @3m)	Remark	
	Above 1	GHz	54.0		Average Value	
	7.5070 1	0.12	74.0	0	Peak Value	
Test setup:	Antenna Tower  Horn Antenna  Spectrum Analyzer  List Amplifier					
Test Procedure:	<ol> <li>The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> </ol>					
Test Instruments:	Refer to section	•		-		
Test mode:	Refer to section 5.3 for details					
Test results:	Pass					



#### Remark:

- 1. During the test, pre-scan the GFSK, Pi/4QPSK, 8DPSK modulation, and found the GFSK modulation which it is worse case.
- 2. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.

Test channel: Lowest	

#### Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	40.03	27.59	5.38	30.18	42.82	74.00	-31.18	Horizontal
2400.00	56.41	27.58	5.39	30.18	59.20	74.00	-14.80	Horizontal
2390.00	40.30	27.59	5.38	30.18	43.09	74.00	-30.91	Vertical
2400.00	58.14	27.58	5.39	30.18	60.93	74.00	-13.07	Vertical

## Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	31.22	27.59	5.38	30.18	34.01	54.00	-19.99	Horizontal
2400.00	42.29	27.58	5.39	30.18	45.08	54.00	-8.92	Horizontal
2390.00	30.96	27.59	5.38	30.18	33.75	54.00	-20.25	Vertical
2400.00	43.67	27.58	5.39	30.18	46.46	54.00	-7.54	Vertical

## Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	41.79	27.53	5.47	29.93	44.86	74.00	-29.14	Horizontal
2500.00	41.51	27.55	5.49	29.93	44.62	74.00	-29.38	Horizontal
2483.50	42.16	27.53	5.47	29.93	45.23	74.00	-28.77	Vertical
2500.00	42.23	27.55	5.49	29.93	45.34	74.00	-28.66	Vertical

### Average value:

7170.ugo ru								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	34.01	27.53	5.47	29.93	37.08	54.00	-16.92	Horizontal
2500.00	32.42	27.55	5.49	29.93	35.53	54.00	-18.47	Horizontal
2483.50	34.99	27.53	5.47	29.93	38.06	54.00	-15.94	Vertical
2500.00	32.11	27.55	5.49	29.93	35.22	54.00	-18.78	Vertical

## Remark:

- 1. Final Level =Receiver Read level + Antenna Factor + Cable Loss Preamplifier Factor
- 2. The emission levels of other frequencies are very lower than the limit and not show in test report.



# 7.10 Spurious Emission

# 7.10.1 Conducted Emission Method


Test Requirement:	FCC Part15 C Section 15.247 (d)			
Test Method:	ANSI C63.10:2013 and KDB558074 D01 Meas Guidance			
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.			
Test setup:	Spectrum Analyzer  E.U.T  Non-Conducted Table  Ground Reference Plane			
Test Instruments:	Refer to section 6.0 for details			
Test mode:	Refer to section 5.3 for details			
Test results:	Pass			

#### Remark:

During the test, pre-scan the GFSK, Pi/4QPSK, 8DPSK modulation, and found the GFSK modulation which it is worse case.




# Test channel: Lowest channel




30MHz~25GHz

Test channel: Middle channel



30MHz~25GHz

Test channel: Highest channel



30MHz~25GHz



# 7.10.2 Radiated Emission Method

Test Requirement:	FCC Part15 C S	Section 15.20	9			
Test Method:	ANSI C63.10:2013					
Test Frequency Range:	30MHz to 25GHz					
Test site:	Measurement Distance: 3m					
Receiver setup:	Frequency	Frequency Detector		VBW	Remark	
	30MHz- 1GHz	Quasi-peal	k 120KHz	300KHz	Quasi-peak Value	
	Above 1GHz	Peak	1MHz	3MHz	Peak Value	
	Above IGHZ	Peak	1MHz	10Hz	Average Value	
Limit:	Freque	ency	Limit (dBuV	/m @3m)	Remark	
	30MHz-8	88MHz	40.0	)	Quasi-peak Value	
	88MHz-2	16MHz	43.	5	Quasi-peak Value	
	216MHz-9	60MHz	46.0	)	Quasi-peak Value	
	960MHz	-1GHz	54.0		Quasi-peak Value	
	Above	Above 1GHz		)	Average Value	
	Above 1GHZ		74.0		Peak Value	
Test setup:	Below 1GHz    Cancel Value   Cancel					
	Above 1GHz					

Page 34 of 41



	Tum Table - Clm 4m > Clm				
Test Procedure:	1. The EUT was placed on the top of a rotating table (0.8 meters below 1G and 1.5 meters above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.				
	2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.				
	3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.				
	4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.				
	<ol><li>The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li></ol>				
	6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.				
Test Instruments:	Refer to section 6.0 for details				
Test mode:	Refer to section 5.3 for details				
Test results:	Pass				

# Remark:

- 1. During the test, pre-scan the GFSK, Pi/4QPSK, 8DPSK modulation, and found the GFSK modulation which it is worse case.
- 2. Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.



#### Measurement data:

#### ■ Below 1GHz

- Delow	GHZ							
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
123.27	42.54	9.07	1.38	29.55	23.44	43.50	-20.06	Vertical
187.10	38.76	9.40	1.78	29.25	20.69	43.50	-22.81	Vertical
271.33	40.24	12.53	2.23	29.81	25.19	46.00	-20.81	Vertical
502.94	30.25	17.55	3.32	29.30	21.82	46.00	-24.18	Vertical
665.80	36.11	19.62	3.97	29.23	30.47	46.00	-15.53	Vertical
860.04	31.14	21.83	4.69	29.14	28.52	46.00	-17.48	Vertical
114.11	41.48	10.60	1.31	29.60	23.79	43.50	-19.71	Horizontal
183.20	44.44	9.10	1.75	29.26	26.03	43.50	-17.47	Horizontal
272.28	41.94	12.63	2.24	29.81	27.00	46.00	-19.00	Horizontal
333.69	40.63	14.15	2.54	29.81	27.51	46.00	-18.49	Horizontal
502.94	34.17	17.55	3.32	29.30	25.74	46.00	-20.26	Horizontal
677.58	37.62	19.68	4.00	29.22	32.08	46.00	-13.92	Horizontal



#### ■ Above 1GHz

Test channel:	Lowest

#### Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804.00	37.87	31.78	8.60	32.09	46.16	74.00	-27.84	Vertical
7206.00	32.21	36.15	11.65	32.00	48.01	74.00	-25.99	Vertical
9608.00	31.80	37.95	14.14	31.62	52.27	74.00	-21.73	Vertical
12010.00	*					74.00		Vertical
14412.00	*					74.00		Vertical
4804.00	42.28	31.78	8.60	32.09	50.57	74.00	-23.43	Horizontal
7206.00	34.01	36.15	11.65	32.00	49.81	74.00	-24.19	Horizontal
9608.00	31.28	37.95	14.14	31.62	51.75	74.00	-22.25	Horizontal
12010.00	*					74.00		Horizontal
14412.00	*					74.00		Horizontal

# Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804.00	26.58	31.78	8.60	32.09	34.87	54.00	-19.13	Vertical
7206.00	20.83	36.15	11.65	32.00	36.63	54.00	-17.37	Vertical
9608.00	19.87	37.95	14.14	31.62	40.34	54.00	-13.66	Vertical
12010.00	*					54.00		Vertical
14412.00	*					54.00		Vertical
4804.00	30.87	31.78	8.60	32.09	39.16	54.00	-14.84	Horizontal
7206.00	23.04	36.15	11.65	32.00	38.84	54.00	-15.16	Horizontal
9608.00	19.65	37.95	14.14	31.62	40.12	54.00	-13.88	Horizontal
12010.00	*					54.00		Horizontal
14412.00	*					54.00		Horizontal

# Remark:

- 1. Final Level =Receiver Read level + Antenna Factor + Cable Loss Preamplifier Factor
- 2. "\*", means this data is the too weak instrument of signal is unable to test.
- 3. The emission levels of other frequencies are very lower than the limit and not show in test report.



Test channel:	Middle

#### Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4882.00	38.88	31.85	8.67	32.12	47.28	74.00	-26.72	Vertical
7323.00	32.88	36.37	11.72	31.89	49.08	74.00	-24.92	Vertical
9764.00	32.40	38.35	14.25	31.62	53.38	74.00	-20.62	Vertical
12205.00	*					74.00		Vertical
14646.00	*					74.00		Vertical
4882.00	43.49	31.85	8.67	32.12	51.89	74.00	-22.11	Horizontal
7323.00	34.77	36.37	11.72	31.89	50.97	74.00	-23.03	Horizontal
9764.00	31.97	38.35	14.25	31.62	52.95	74.00	-21.05	Horizontal
12205.00	*					74.00		Horizontal
14646.00	*					74.00		Horizontal

# Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4882.00	27.42	31.85	8.67	32.12	35.82	54.00	-18.18	Vertical
7323.00	21.40	36.37	11.72	31.89	37.60	54.00	-16.40	Vertical
9764.00	20.38	38.35	14.25	31.62	41.36	54.00	-12.64	Vertical
12205.00	*					54.00		Vertical
14646.00	*					54.00		Vertical
4882.00	31.82	31.85	8.67	32.12	40.22	54.00	-13.78	Horizontal
7323.00	23.68	36.37	11.72	31.89	39.88	54.00	-14.12	Horizontal
9764.00	20.24	38.35	14.25	31.62	41.22	54.00	-12.78	Horizontal
12205.00	*					54.00		Horizontal
14646.00	*					54.00		Horizontal

# Remark:

- 1. Final Level =Receiver Read level + Antenna Factor + Cable Loss Preamplifier Factor
- 2. "\*", means this data is the too weak instrument of signal is unable to test.
- 3. The emission levels of other frequencies are very lower than the limit and not show in test report.



Test channel: High	ghest
--------------------	-------

#### Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4960.00	39.06	31.93	8.73	32.16	47.56	74.00	-26.44	Vertical
7440.00	33.00	36.59	11.79	31.78	49.60	74.00	-24.40	Vertical
9920.00	32.51	38.81	14.38	31.88	53.82	74.00	-20.18	Vertical
12400.00	*					74.00		Vertical
14880.00	*					74.00		Vertical
4960.00	43.71	31.93	8.73	32.16	52.21	74.00	-21.79	Horizontal
7440.00	34.91	36.59	11.79	31.78	51.51	74.00	-22.49	Horizontal
9920.00	32.10	38.81	14.38	31.88	53.41	74.00	-20.59	Horizontal
12400.00	*					74.00		Horizontal
14880.00	*					74.00		Horizontal

# Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4960.00	27.69	31.93	8.73	32.16	36.19	54.00	-17.81	Vertical
7440.00	21.58	36.59	11.79	31.78	38.18	54.00	-15.82	Vertical
9920.00	20.54	38.81	14.38	31.88	41.85	54.00	-12.15	Vertical
12400.00	*					54.00		Vertical
14880.00	*					54.00		Vertical
4960.00	32.13	31.93	8.73	32.16	40.63	54.00	-13.37	Horizontal
7440.00	23.88	36.59	11.79	31.78	40.48	54.00	-13.52	Horizontal
9920.00	20.43	38.81	14.38	31.88	41.74	54.00	-12.26	Horizontal
12400.00	*					54.00		Horizontal
14880.00	*					54.00		Horizontal


#### Remark:


- 1. Final Level =Receiver Read level + Antenna Factor + Cable Loss Preamplifier Factor
- 2. "\*", means this data is the too weak instrument of signal is unable to test.
- 3. The emission levels of other frequencies are very lower than the limit and not show in test report.



# 8 Test Setup Photo

**Radiated Emission** 







# **Conducted Emission**



# 9 EUT Constructional Details

Reference to the test report No. GTS201701000007F01

-----End-----