

FCC TEST REPORT

Client Name : Autel Intelligent Tech. Corp., Ltd.

Address : 7th-8th, 10th Floor, Bldg. B1, Zhiyuan,Xueyuan Rd. Xili,
Nanshan Shenzhen China

Product Name : Intelligent TPMS & Tire Service tool

Date : Nov. 12, 2020

Shenzhen Anbotech Compliance Laboratory Limited



Contents

1. General Information.....	4
1.1. Client Information.....	4
1.2. Description of Device (EUT).....	4
1.3. Auxiliary Equipment Used During Test.....	6
1.4. Description of Test Modes.....	6
1.5. List of Channels.....	6
1.6. Description of Test Setup.....	7
1.7. Test Equipment List.....	8
1.8. Description of Test Facility.....	9
2. Summary of Test Results.....	10
3. Conducted Emission Test.....	11
3.1. Test Standard and Limit.....	11
3.2. Test Setup.....	11
3.3. Test Procedure.....	11
3.4. Test Data.....	12
4. Radiated Emission and Band Edge.....	20
4.1. Test Standard and Limit.....	20
4.2. Test Setup.....	21
4.3. Test Procedure.....	22
4.4. Test Data.....	23
5. 20DB Occupy Bandwidth Test.....	34
5.1. Test Standard and Limit.....	34
5.2. Test Setup.....	34
5.3. Test Procedure.....	34
5.4. Test Data.....	35
6. Dwell Time Test.....	38
6.1. Test Standard and Limit.....	38
6.2. Test Setup.....	38
6.3. Test Procedure.....	38
6.4. Test Data.....	38
7. Antenna Requirement.....	40
7.1. Test Standard and Requirement.....	40
7.2. Antenna Connected Construction.....	40



TEST REPORT

Applicant : Autel Intelligent Tech. Corp., Ltd.
Manufacturer : Autel Intelligent Tech. Corp., Ltd.
Product Name : Intelligent TPMS & Tire Service tool
Model No. : MaxiTPMS ITS600
Trade Mark : AUTEL
Rating(s) : Input: DC 5V, 1.8A (with DC 3.8V, 5000mAh Battery inside)
Adapter input: DC 5V,2A

Test Standard(s) : FCC Part15 Subpart C, Section 15.231

Test Method(s) : ANSI C63.10: 2013

The device described above is tested by Shenzhen Anbotech Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotech Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotech Compliance Laboratory Limited.

Date of Receipt

Sept. 07, 2020

Date of Test

Sept. 07~21, 2020

Prepared by

Yilia Zhong

(Engineer / Yilia Zhong)

Reviewer

Bibo Zhang

(Supervisor / Bibo Zhang)

Approved & Authorized Signer

Kingkong Jin

(Manager / Kingkong Jin)

Shenzhen Anbotech Compliance Laboratory Limited

Code:AB-RF-05-a

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.

Tel: (86) 755-26066440 Fax: (86) 755-26014772 Email: service@anbotech.com

 Hotline
400-003-0500
www.anbotech.com

1. General Information

1.1. Client Information

Applicant	:	Autel Intelligent Tech. Corp., Ltd.
Address	:	7th-8th, 10th Floor, Bldg. B1, Zhiyuan,Xueyuan Rd. Xili, Nanshan Shenzhen China
Manufacturer	:	Autel Intelligent Tech. Corp., Ltd.
Address	:	7th-8th, 10th Floor, Bldg. B1, Zhiyuan,Xueyuan Rd. Xili, Nanshan Shenzhen China
Factory 1	:	Autel Intelligent Technology Corp.,Ltd.
Address	:	6th Floor, Building 1, Yanxiang Zhigu, NO.11 Gaoxin West Rd, Guangming New District, Shenzhen City, Guangdong Province, China.
Factory 2	:	AUTEL VIETNAM COMPANY LIMITED
Address	:	4th Floor, Factory#6, Land#CN1, An Duong Industrial Zone, Hong Phong Township, An Duong County, Hai Phong, Viet Nam

1.2. Description of Device (EUT)

Product Name	:	Intelligent TPMS & Tire Service tool
Model No.	:	MaxiTPMS ITS600
Trade Mark	:	AUTEL
Test Power Supply	:	DC 3.8V Battery inside
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)
Product Description	:	Operation Frequency: WiFi 2.4G: 802.11g/ n(HT20) 2412-2462MHz BT: 2402-2480MHz WiFi 5.1G: 5180MHz~5240MHz WiFi 5.8G: 5745MHz~5825MHz 433.92MHz 315 MHz 125KHz
	:	Number of Channel: WiFi 2.4G: 11 Channels for 802.11g/ n(HT20) BDR&EDR: 79 Channels WiFi 5.1G: 4 Channels for 802.11a 4 Channels for 802.11n(HT20) 4 Channels for 802.11ac(HT20)

		2 Channels for 802.11n(HT40) 2 Channels for 802.11ac(HT40) 1 Channels for 802.11ac(HT80) WiFi 5.8G: 5 Channels for 802.11a 5 Channels for 802.11n(HT20) 5 Channels for 802.11ac(HT20) 2 Channels for 802.11n(HT40) 2 Channels for 802.11ac(HT40) 1 Channels for 802.11ac(HT80) 433.92MHz: 1 Channels
	Modulation Type:	WiFi 2.4G: 802.11g/n OFDM BDR&EDR: GFSK, $\pi/4$ -DQPSK, 8-DPSK WiFi 5.1G: OFDM with BPSK/QPSK/16QAM/64QAM/256QAM WiFi 5.8G: OFDM with BPSK/QPSK/16QAM/64QAM/256QAM 433.92MHz: ASK / FSK 315 MHz: ASK / FSK 125KHz: ASK
	Antenna Type:	BT: PIFA Antenna WiFi 2.4G & WiFi 5.1G & WiFi 5.8G: PIFA Antenna 433.92MHz: PCB Antenna 315 MHz: PCB Antenna 125KHz: Inductive loop coil Antenna
	Antenna Gain(Peak):	BT: 1.6 dBi WiFi 2.4G: 2.3 dBi WiFi 5.1G & WiFi 5.8G: 2.7 dBi 433.92MHz: -10 dBi 315 MHz: -10 dBi 125KHz: -10 dBi
Remark: 1)For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual. 2) This report is for 315MHz mouldle.		



1.3. Auxiliary Equipment Used During Test

Adapter	:	MODEL:GME10C-050200FUu I/P:100-240V~50-60Hz 0.28A O/P: DC 5V, 2A
---------	---	--

1.4. Description of Test Modes

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX Mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	TX Mode


Note:

1. During the test, the EUT was keeping continuous transmission.

1.5. List of Channels

Channel	Freq. (MHz)
1	315

1.6. Description of Test Setup



1.7. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	Nov. 04, 2019	1 Year
2.	EMI Test Receiver	Rohde & Schwarz	ESPI3	101604	Nov. 04, 2019	1 Year
3.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Nov. 04, 2019	1 Year
4.	MAX Spectrum Analysis	Agilent	N9020A	MY51170037	Nov. 04, 2019	1 Year
5.	Preamplifier	SKET Electronic	BK1G18G30 D	KD17503	Nov. 04, 2019	1 Year
6.	Double Ridged Horn Antenna	Instruments corporation	GTH-0118	351600	Nov. 01, 2019	1 Year
7.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	Nov. 01, 2019	1 Year
8.	Loop Antenna	Schwarzbeck	FMZB1519B	00053	Nov. 01, 2019	1 Year
9.	Horn Antenna	A-INFO	LB-180400-K F	J211060628	Nov. 01, 2019	1 Year
10.	Pre-amplifier	SONOMA	310N	186860	Nov. 04, 2019	1 Year
11.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
12.	RF Test Control System	YIHENG	YH3000	2017430	Nov. 04, 2019	1 Year
13.	Power Sensor	DAER	RPR3006W	15I00041SN045	Nov. 04, 2019	1 Year
14.	Power Sensor	DAER	RPR3006W	15I00041SN046	Nov. 04, 2019	1 Year
15.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Nov. 04, 2019	1 Year
16.	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Nov. 04, 2019	1 Year
17.	Signal Generator	Agilent	E4421B	MY41000743	Nov. 04, 2019	1 Year
18.	DC Power Supply	LW	TPR-6420D	374470	Nov. 04, 2019	1 Year
19.	Constant Temperature Humidity Chamber	ZHONGJIAN	ZJ-KHWS80 B	N/A	Nov. 04, 2019	1 Year

1.8. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 184111

Shenzhen Anbotech Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 184111, September 30, 2020.

ISED-Registration No.: 8058A-1

Shenzhen Anbotech Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A, September 30, 2020.

Test Location

Shenzhen Anbotech Compliance Laboratory Limited.

1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.518102



2. Summary of Test Results

Standard Section	Test Item	Result
15.203	Antenna Requirement	PASS
15.207	Conducted Emission	PASS
15.205/15.209/15.231(b)	Spurious Emission	PASS
15.231(c)	20dB Occupied Bandwidth	PASS
15.231(a)	Dwell time	PASS
Remark: "N/A" is an abbreviation for Not Applicable.		




3. Conducted Emission Test

3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
	5MHz~30MHz	60	50

Remark: (1) *Decreasing linearly with logarithm of the frequency.
(2) The lower limit shall apply at the transition frequency.

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10-2013 on Conducted Emission Measurement.

The bandwidth of test CAR REMOTE (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.


3.4. Test Data

Only the worst case data was showed in the report, please to see the following pages.

ASK:

Conducted Emission Test Data

Test Site: 1# Shielded Room
 Test Specification: AC 120V, 60Hz for adapter
 Comment: Live Line
 Tem.: 24.0°C Hum.: 53%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1620	22.67	29.46	52.13	65.36	-13.23	QP	
2	0.1740	9.51	29.46	38.97	54.76	-15.79	AVG	
3	0.2620	15.90	29.43	45.33	61.36	-16.03	QP	
4	0.5380	2.15	29.52	31.67	46.00	-14.33	AVG	
5	0.5500	12.30	29.52	41.82	56.00	-14.18	QP	
6	0.8740	-1.47	29.61	28.14	46.00	-17.86	AVG	
7	1.2780	8.99	29.65	38.64	56.00	-17.36	QP	
8	1.2980	-2.25	29.65	27.40	46.00	-18.60	AVG	
9	1.6900	8.45	29.64	38.09	56.00	-17.91	QP	
10	1.6900	-2.50	29.64	27.14	46.00	-18.86	AVG	
11	3.6540	7.08	29.69	36.77	56.00	-19.23	QP	
12	4.8140	-3.16	29.72	26.56	46.00	-19.44	AVG	


Report No.: 18220WC00130006

FCC ID: WQ8TPMS609T

Page13 of 40

Conducted Emission Test Data

Test Site: 1# Shielded Room
 Test Specification: AC 120V, 60Hz for adapter
 Comment: Neutral Line
 Tem.: 24.0°C Hum.: 53%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1660	23.07	29.46	52.53	65.15	-12.62	QP	
2	0.1740	8.47	29.46	37.93	54.76	-16.83	AVG	
3	0.2700	15.67	29.43	45.10	61.12	-16.02	QP	
4	0.3820	10.55	29.47	40.02	58.23	-18.21	QP	
5	0.5420	12.36	29.52	41.88	56.00	-14.12	QP	
6	0.5420	1.52	29.52	31.04	46.00	-14.96	AVG	
7	0.8820	9.15	29.61	38.76	56.00	-17.24	QP	
8	0.8900	-0.71	29.61	28.90	46.00	-17.10	AVG	
9	1.2260	-2.40	29.64	27.24	46.00	-18.76	AVG	
10	1.6700	8.25	29.64	37.89	56.00	-18.11	QP	
11	1.6700	-2.30	29.64	27.34	46.00	-18.66	AVG	
12	1.9860	-2.75	29.65	26.90	46.00	-19.10	AVG	




Report No.: 18220WC00130006

FCC ID: WQ8TPMS609T

Page14 of 40

Conducted Emission Test Data

Test Site: 1# Shielded Room
Test Specification: AC 240V, 60Hz for adapter
Comment: Live Line
Tem.: 24.0°C Hum.: 53%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1580	20.38	29.46	49.84	65.56	-15.72	QP	
2	0.2380	3.66	29.44	33.10	52.16	-19.06	AVG	
3	0.3700	13.30	29.46	42.76	58.50	-15.74	QP	
4	0.5500	0.63	29.52	30.15	46.00	-15.85	AVG	
5	0.5580	11.53	29.53	41.06	56.00	-14.94	QP	
6	0.8940	9.17	29.61	38.78	56.00	-17.22	QP	
7	0.8940	-0.82	29.61	28.79	46.00	-17.21	AVG	
8	1.2020	9.36	29.64	39.00	56.00	-17.00	QP	
9	1.2020	-2.10	29.64	27.54	46.00	-18.46	AVG	
10	1.7580	-1.75	29.65	27.90	46.00	-18.10	AVG	
11	3.2900	-2.69	29.68	26.99	46.00	-19.01	AVG	
12	4.5980	8.50	29.72	38.22	56.00	-17.78	QP	




Report No.: 18220WC00130006

FCC ID: WQ8TPMS609T

Page15 of 40

Conducted Emission Test Data

Test Site: 1# Shielded Room
 Test Specification: AC 240V, 60Hz for adapter
 Comment: Neutral Line
 Tem.: 24.0°C Hum.: 53%




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1700	20.53	29.46	49.99	64.96	-14.97	QP	
2	0.1740	6.59	29.46	36.05	54.76	-18.71	AVG	
3	0.2700	13.89	29.43	43.32	61.12	-17.80	QP	
4	0.4100	11.73	29.47	41.20	57.65	-16.45	QP	
5	0.5580	11.32	29.53	40.85	56.00	-15.15	QP	
6	0.5580	0.55	29.53	30.08	46.00	-15.92	AVG	
7	0.9900	-1.42	29.64	28.22	46.00	-17.78	AVG	
8	1.0060	9.62	29.64	39.26	56.00	-16.74	QP	
9	1.7180	9.55	29.64	39.19	56.00	-16.81	QP	
10	1.7260	-2.32	29.64	27.32	46.00	-18.68	AVG	
11	3.2780	-3.03	29.68	26.65	46.00	-19.35	AVG	
12	4.4380	-3.21	29.71	26.50	46.00	-19.50	AVG	



FSK:**Conducted Emission Test Data**

Test Site: 1# Shielded Room
 Test Specification: AC 120V, 60Hz for adapter
 Comment: Live Line
 Tem.: 24.0°C Hum.: 53%




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1500	24.96	29.46	54.42	65.99	-11.57	QP	
2	0.1740	9.23	29.46	38.69	54.76	-16.07	AVG	
3	0.2100	20.92	29.45	50.37	63.20	-12.83	QP	
4	0.2740	2.26	29.43	31.69	50.99	-19.30	AVG	
5	0.3300	12.18	29.44	41.62	59.45	-17.83	QP	
6	0.5420	2.73	29.52	32.25	46.00	-13.75	AVG	
7	0.5460	12.74	29.52	42.26	56.00	-13.74	QP	
8	0.8860	9.29	29.61	38.90	56.00	-17.10	QP	
9	0.8860	-0.57	29.61	29.04	46.00	-16.96	AVG	
10	1.2980	-2.16	29.65	27.49	46.00	-18.51	AVG	
11	1.6860	8.08	29.64	37.72	56.00	-18.28	QP	
12	1.6860	-2.68	29.64	26.96	46.00	-19.04	AVG	



Conducted Emission Test Data


Test Site: 1# Shielded Room
 Test Specification: AC 120V, 60Hz for adapter
 Comment: Neutral Line
 Tem.: 24.0°C Hum.: 53%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1740	9.19	29.46	38.65	54.76	-16.11	AVG	
2	0.1780	22.88	29.46	52.34	64.57	-12.23	QP	
3	0.2860	14.78	29.43	44.21	60.64	-16.43	QP	
4	0.3940	11.56	29.47	41.03	57.98	-16.95	QP	
5	0.5460	13.48	29.52	43.00	56.00	-13.00	QP	
6	0.5500	1.33	29.52	30.85	46.00	-15.15	AVG	
7	0.8900	10.32	29.61	39.93	56.00	-16.07	QP	
8	0.8900	-1.21	29.61	28.40	46.00	-17.60	AVG	
9	1.2420	9.15	29.64	38.79	56.00	-17.21	QP	
10	1.3260	-2.64	29.65	27.01	46.00	-18.99	AVG	
11	1.6700	-2.75	29.64	26.89	46.00	-19.11	AVG	
12	2.0020	-2.65	29.65	27.00	46.00	-19.00	AVG	

Conducted Emission Test Data


Test Site: 1# Shielded Room
Test Specification: AC 240V, 60Hz for adapter
Comment: Live Line
Tem.: 24.0°C Hum.: 53%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1700	20.02	29.46	49.48	64.96	-15.48	QP	
2	0.1740	6.40	29.46	35.86	54.76	-18.90	AVG	
3	0.2740	14.52	29.43	43.95	60.99	-17.04	QP	
4	0.5500	11.14	29.52	40.66	56.00	-15.34	QP	
5	0.5500	0.20	29.52	29.72	46.00	-16.28	AVG	
6	0.9660	10.66	29.63	40.29	56.00	-15.71	QP	
7	1.0220	-1.39	29.64	28.25	46.00	-17.75	AVG	
8	1.6780	8.81	29.64	38.45	56.00	-17.55	QP	
9	1.7700	-1.96	29.65	27.69	46.00	-18.31	AVG	
10	2.5220	9.42	29.66	39.08	56.00	-16.92	QP	
11	3.1980	-2.56	29.67	27.11	46.00	-18.89	AVG	
12	4.7180	-3.14	29.72	26.58	46.00	-19.42	AVG	

Conducted Emission Test Data

Test Site: 1# Shielded Room
Test Specification: AC 240V, 60Hz for adapter
Comment: Neutral Line
Tem.: 24.0°C Hum.: 53%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1700	21.12	29.46	50.58	64.96	-14.38	QP	
2	0.2020	5.05	29.45	34.50	53.52	-19.02	AVG	
3	0.2740	15.16	29.43	44.59	60.99	-16.40	QP	
4	0.3860	11.60	29.47	41.07	58.15	-17.08	QP	
5	0.5540	11.01	29.53	40.54	56.00	-15.46	QP	
6	0.5540	0.13	29.53	29.66	46.00	-16.34	AVG	
7	0.8860	10.84	29.61	40.45	56.00	-15.55	QP	
8	0.8900	-0.73	29.61	28.88	46.00	-17.12	AVG	
9	1.2500	-2.37	29.64	27.27	46.00	-18.73	AVG	
10	1.7140	-1.47	29.64	28.17	46.00	-17.83	AVG	
11	1.8340	9.21	29.65	38.86	56.00	-17.14	QP	
12	2.2940	-2.53	29.66	27.13	46.00	-18.87	AVG	



4. Radiated Emission and Band Edge

4.1. Test Standard and Limit

Test Standard	FCC Part 15 C Section 15.209, 15.205 and 15.231(b)				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
		-	74.0	Peak	3

Remark:

(1) The lower limit shall apply at the transition frequency.

(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

the formulas for calculating the maximum permitted fundamental field strengths are as follows:

for the band 260-470 MHz, $\mu\text{V/m}$ at 3 meters = $41.6667(F) - 7083.3333$.

The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level

Emission Level (dBuV/m) = $20 \log$ Emission Level ($\mu\text{V/m}$)

The field strength of emission limits have been calculated in below table:

Fundamental Frequency (MHz)	Field Strength of Fundamental (dBuV/m)@3m
315	75.62 (AVG)
315	95.62 (Peak)

4.2. Test Setup




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.

For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.

The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.

For 9kHz to 150kHz, Set the spectrum analyzer as:

RBW = 200Hz, VBW = 1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW = 30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:

RBW = 100kHz, VBW = 300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For above 1GHz, Set the spectrum analyzer as:

RBW = 1MHz, VBW = 1MHz, Detector= Peak, Trace mode= Max hold, Sweep- auto couple.

RBW = 1MHz, VBW = 10Hz, Detector= Average, Trace mode= Max hold, Sweep- auto couple.

4.4. Test Data

PASS

During the test, Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the X-axis is the worst case.

The test results of 9kHz-30MHz and above 1735.68MHz are attenuated more than 20dB below the permissible limits, so the results don't record in the report.



ASK:**Test Results (Fundamental 315MHz)**

Frequency	Antenna	Reading	Cable Loss	Ant Factor	Amplifier	Duty cycle Factor	Results	Limits	Det.
(MHz)	Pol.	(dBuV/m)	(dB)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	Mode
315.00	H	84.51	1.52	12.64	31.45	-	67.22	95.62	PK
315.00	H	84.51	1.52	12.64	31.45	-12.86	54.36	75.62	AV
315.00	V	97.73	1.52	12.64	31.45	-	80.44	95.62	PK
315.00	V	97.73	1.52	12.64	31.45	-12.86	67.58	75.62	AV

Remark:

1. Result = Reading + Cable Loss + Ant Factor – Amplifier + Duty cycle Factor

2. Pulse Desensitization Correction Factor

Pulse Width (PW)= 8.55ms

$2/PW = 2/8.55 = 0.23\text{kHz}$

$RBW(1000\text{kHz}) > 2/PW (0.23\text{kHz})$

Therefore PDCF is not needed.

3. Duty Cycle Factor

Calculate Formula:

$AV = \text{PEAK} + \text{Duty Cycle Factor}$

$\text{Duty Cycle Factor} = 20\log(\text{Duty Cycle})$

$\text{Duty Cycle} = \text{on time} / \text{period}$

Test Data:


$T \text{ on time} = 8.55 \times 10 = 85.5 \text{ ms}$

$T \text{ period} = 540.8 - 164.8 = 376 \text{ ms}$


$\text{Duty Cycle} = 22.74\%$

$\text{Duty Cycle Factor} = 20\log(\text{Duty Cycle}) = -12.86$

T on time slot-1



T period



Test Results (Spurious Emissions)

Frequency	Antenna	Reading	Cable Loss	Ant Factor	Amplifier	Duty cycle Factor	Results	Limits	Det
(MHz)	Pol.	(dBuV/m)	(dB)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	Mode
630.00	H	74.72	1.92	12.71	31.72	-	57.63	75.62	PK
630.00	H	74.72	1.92	12.71	31.72	-12.86	44.77	55.62	AV
630.00	V	76.64	1.92	12.71	31.72	-	59.55	75.62	PK
630.00	V	76.64	1.92	12.71	31.72	-12.86	46.69	55.62	AV
945.00	H	63.08	2.38	21.43	32.45	-	54.44	74.00	PK
945.00	H	63.08	2.38	21.43	32.45	-12.86	41.58	54.00	AV
945.00	V	65.09	2.38	18.56	32.45	-	53.58	74.00	PK
945.00	V	65.09	2.38	18.56	32.45	-12.86	40.72	54.00	AV
1735.68	H	*						74	PK
1735.68	H	*						54	AV
1735.68	V	*						74	PK
1735.68	V	*						54	AV
2169.60	H	*						74	PK
2169.60	H	*						54	AV
2169.60	V	*						74	PK
2169.60	V	*						54	AV

Remark:

1. Result = Reading + Cable Loss + Ant Factor – Amplifier + Duty cycle Factor
2. Pulse Desensitization Correction Factor
Pulse Width (PW)= 8.55ms
 $2/PW=2/8.55=0.23\text{kHz}$
 $RBW(1000\text{kHz}) > 2/PW (0.23\text{KHz})$
Therefore PDCF is not needed.
3. Duty Cycle Factor=-12.86
4. Only the worst data was recorded in this report.

Report No.: 18220WC00130006

FCC ID: WQ8TPMS609T

Page 27 of 40

Test Results (30~1000MHz)

Job No.: 18220WC00130001

Temp.(°C)/Hum.(%RH): 24.6°C/50%RH


Standard: FCC PART 15C

Power Source: DC 3.8V Battery inside

Test Mode: TX Mode

Polarization: Horizontal

Note:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	42.7496	31.34	-14.61	16.73	40.00	-23.27	QP	100	0	
2	109.4116	44.65	-21.13	23.52	43.50	-19.98	QP	100	360	
3	339.5888	32.53	-13.27	19.26	46.00	-26.74	QP	100	0	
4	407.5145	34.48	-12.84	21.64	46.00	-24.36	QP	100	360	
5	572.6144	32.24	-7.45	24.79	46.00	-21.21	QP	100	0	
6	952.0937	32.55	-0.79	31.76	46.00	-14.24	QP	100	360	



Report No.: 18220WC00130006

FCC ID: WQ8TPMS609T

Page 28 of 40

Test Results (30~1000MHz)

Job No.: 18220WC00130001

Temp.(°C)/Hum.(%RH): 24.6°C/50%RH


Standard: FCC PART 15C

Power Source: DC 3.8V Battery inside

Test Mode: TX Mode

Polarization: Vertical

Note:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	38.0783	36.36	-14.62	21.74	40.00	-18.26	QP	100	0	
2	117.7725	36.87	-17.55	19.32	43.50	-24.18	QP	100	360	
3	213.0151	36.79	-16.70	20.09	43.50	-23.41	QP	100	0	
4	454.3100	30.03	-10.11	19.92	46.00	-26.08	QP	100	360	
5	721.7259	32.83	-5.67	27.16	46.00	-18.84	QP	100	0	
6	972.3374	31.64	-0.33	31.31	54.00	-22.69	QP	100	360	

Remark:

1. Results = Reading + Cable Loss +Ant Factor –Amplifier



FSK:**Test Results (Fundamental 315MHz)**

Frequency	Antenna	Reading	Cable Loss	Ant Factor	Amplifier	Duty cycle Factor	Results	Limits	Det.
(MHz)	Pol.	(dBuV/m)	(dB)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	Mode
315.00	H	84.51	1.52	12.64	31.45	-	67.22	95.62	PK
315.00	H	84.51	1.52	12.64	31.45	-12.73	54.49	75.62	AV
315.00	V	97.92	1.52	12.64	31.45	-	80.63	95.62	PK
315.00	V	97.92	1.52	12.64	31.45	-12.73	67.90	75.62	AV

Remark:

1. Result = Reading + Cable Loss + Ant Factor – Amplifier + Duty cycle Factor

2. Pulse Desensitization Correction Factor

Pulse Width (PW)= 8.70ms

$2/PW = 2/8.70 = 0.23\text{kHz}$

$RBW(1000\text{kHz}) > 2/PW (0.23\text{kHz})$

Therefore PDCF is not needed.

3. Duty Cycle Factor**Calculate Formula:**

$AV = \text{PEAK} + \text{Duty Cycle Factor}$

$\text{Duty Cycle Factor} = 20\log(\text{Duty Cycle})$

$\text{Duty Cycle} = \text{on time} / \text{period}$

Test Data:

$T \text{ on time} = 8.70 \times 10 = 87.0 \text{ ms}$



$T \text{ period} = 477.6 - 100.8 = 376 \text{ ms}$

$\text{Duty Cycle} = 23.09\%$

$\text{Duty Cycle Factor} = 20\log(\text{Duty Cycle}) = -12.73$

T on time slot-1

T period



Test Results (Spurious Emissions)

Frequency	Antenna	Reading	Cable Loss	Ant Factor	Amplifier	Duty cycle Factor	Results	Limits	Det
(MHz)	Pol.	(dBuV/m)	(dB)	(dB)	(dB)	(dB)	(dBuV/m)	(dBuV/m)	Mode
630.00	H	74.08	1.92	12.71	31.72	-	56.99	75.62	PK
630.00	H	74.08	1.92	12.71	31.72	-12.73	44.26	55.62	AV
630.00	V	76.40	1.92	12.71	31.72	-	59.31	75.62	PK
630.00	V	76.40	1.92	12.71	31.72	-12.73	46.58	55.62	AV
945.00	H	63.28	2.38	21.43	32.45	-	54.64	74.00	PK
945.00	H	63.28	2.38	21.43	32.45	-12.73	41.91	54.00	AV
945.00	V	65.74	2.38	18.56	32.45	-	54.23	74.00	PK
945.00	V	65.74	2.38	18.56	32.45	-12.73	41.50	54.00	AV
1735.68	H	*						74	PK
1735.68	H	*						54	AV
1735.68	V	*						74	PK
1735.68	V	*						54	AV
2169.60	H	*						74	PK
2169.60	H	*						54	AV
2169.60	V	*						74	PK
2169.60	V	*						54	AV

Remark:

1. Result = Reading + Cable Loss + Ant Factor – Amplifier + Duty cycle Factor

2. Pulse Desensitization Correction Factor

Pulse Width (PW)= 8.70ms

$2/PW = 2/8.70 = 0.23\text{kHz}$

$RBW(1000\text{kHz}) > 2/PW (0.23\text{KHz})$

Therefore PDCF is not needed.

5. Duty Cycle Factor=-12.73

6. Only the worst data was recorded in this report.

Report No.: 18220WC00130006

FCC ID: WQ8TPMS609T

Page 32 of 40

Test Results (30~1000MHz)

Job No.: 18220WC00130001

Temp.(°C)/Hum.(%RH): 24.6°C/50%RH


Standard: FCC PART 15C

Power Source: DC 3.8V Battery inside

Test Mode: TX Mode

Polarization: Horizontal

Note:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	48.5016	29.12	-14.67	14.45	40.00	-25.55	QP	100	0	
2	113.3163	40.18	-21.47	18.71	43.50	-24.79	QP	100	360	
3	223.7334	39.91	-19.38	20.53	46.00	-25.47	QP	100	0	
4	375.9385	34.72	-12.99	21.73	46.00	-24.27	QP	100	360	
5	651.9417	32.62	-6.79	25.83	46.00	-20.17	QP	100	0	
6	1000.0000	31.24	0.32	31.56	54.00	-22.44	QP	100	360	



Report No.: 18220WC00130006

FCC ID: WQ8TPMS609T

Page 33 of 40

Test Results (30~1000MHz)

Job No.: 18220WC00130001

Temp.(°C)/Hum.(%RH): 24.6°C/50%RH


Standard: FCC PART 15C

Power Source: DC 3.8V Battery inside

Test Mode: TX Mode

Polarization: Vertical

Note:



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	40.2757	31.63	-13.61	18.02	40.00	-21.98	QP	100	0	
2	112.5244	36.89	-16.66	20.23	43.50	-23.27	QP	100	360	
3	219.8449	37.73	-16.44	21.29	46.00	-24.71	QP	100	0	
4	294.1137	31.60	-13.62	17.98	46.00	-28.02	QP	100	360	
5	597.2234	31.73	-6.82	24.91	46.00	-21.09	QP	100	0	
6	935.5463	31.88	-1.09	30.79	46.00	-15.21	QP	100	360	

Remark:

1. Results = Reading + Cable Loss +Ant Factor –Amplifier




5. 20DB Occupy Bandwidth Test

5.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.231 (c)				
Test Limit	According to FCC Part 15.231(c), The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70MHz and below 900MHz. For devices operating above 900MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20dB down from the modulated carrier. So the emission bandwidth limits have been calculated in below table: <table><tr><th>Fundamental Frequency</th><th>Limit of 20dB Bandwidth</th></tr><tr><td>315 MHz</td><td>$315000 \times 0.0025 = 787.50 \text{ kHz}$</td></tr></table>	Fundamental Frequency	Limit of 20dB Bandwidth	315 MHz	$315000 \times 0.0025 = 787.50 \text{ kHz}$
Fundamental Frequency	Limit of 20dB Bandwidth				
315 MHz	$315000 \times 0.0025 = 787.50 \text{ kHz}$				

5.2. Test Setup



5.3. Test Procedure

1. Place the EUT on the table and set it in the continuously transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as:
RBW = 30kHz, VBW $\geq 3 \times$ RBW = 100kHz,
Span= 1MHz
Detector= Peak
Trace mode= Max hold.
Sweep- auto couple.
4. Mark the peak frequency and -20dB (upper and lower) frequency.
5. Repeat until all the rest channels are investigated.

5.4. Test Data


Test Item	: 20dB Bandwidth	Test Mode	: Continuously transmitting
Test Voltage	: DC 3.8V Battery inside	Temperature	: 22.7℃
Test Result	: PASS	Humidity	: 55%RH

Freq. (MHz)	Modulation Type	20DB Bandwidth (kHz)	Limit (kHz)	99% BW (KHz)	Results
315	ASK	155.7	<787.5	208.62	PASS
315	FSK	205.0	<787.5	116.68	PASS




ASK:

Plot of 20DB Bandwidth




Plot of 99% Bandwidth




FSK:

Plot of 20DB Bandwidth



Plot of 99% Bandwidth




6. Dwell Time Test

6.1. Test Standard and Limit

Test Standard	FCC Part 15.231(a)(1)
Test Limit	According to FCC Part 15.231(a)(1), A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released

6.2. Test Setup



6.3. Test Procedure

1. Place the EUT on the table and set it in continuously transmitting mode. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set the spectrum analyzer as
RBW=1000kHz, VBW= 1000 kHz, Span= 0Hz, Sweep Time= 20 Seconds.
3. Record the Delta mark time.

6.4. Test Data


Test Item	: Dwell Time
Test Voltage	: DC 3.8V Battery inside
Test Result	: PASS

Test Mode	: Continuously transmitting
Temperature	: 22.7℃
Humidity	: 55%RH

Test Mode	Transmitting time(s)	Limit(s)	Result
ASK mode	0.27	≤5	PASS
FSK mode	0.27	≤5	PASS


Please refer the following plot.

ASK:



Dwell Time

FSK



7. Antenna Requirement

7.1. Test Standard and Requirement

Test Standard	FCC Part15 Section 15.203
Requirement	1) 15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. Antenna requirement must meet at least one of the following: 1) Antenna must be permanently attached to device. 2) The antenna must use a unique type of connector to attach to the device. 3) Device must be professionally installed. The installer shall be responsible for ensuring that the correct antenna is employed by the device.

7.2. Antenna Connected Construction

The antenna is a PCB Antenna which permanently attached, and the best case gain of the antenna is -10 dBi. It complies with the standard requirement.

----- End of Report -----

