Global EMC Inc. Labs EMC & RF Test Report

As per RSS 210 Issue 8:2010

&

FCC Part 15 Subpart C:2014

Unlicensed Intentional Radiators

on the

Athena RS

Min Xie

Project Engineer 11 Gordon Collins Dr, Gormley, ON, L0H 1G0 Canada

Ph: (905) 883-8189

Testing produced for



See Appendix A for full customer & EUT details.







#2555.01

FCC REGISTRATION #377448



Page 1 of 51

Report issue date: 9/8/2014

GEMC File #:GEMC-FCC-22009R1

Client	Ecobee Inc
Product	Athena RS
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014



Table of Contents

Table of Contents	2
Report Scope	3
Summary	4
Test Results Summary	6 7 8
Definitions and Acronyms	9
Testing Facility	10
Calibrations and Accreditations Testing Environmental Conditions and Dates	
Detailed Test Results Section	12
Radiated Emissions of Fundamental Spurious Radiated Emissions 20 dB Bandwidth Measurement – 15.249 Maximum Permissible Exposure	23 40
Appendix A – EUT Summary	44
Appendix B – EUT and Test Setup Photographs	47

Client	Ecobee Inc	CLODATE
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	EINICTAC

Report Scope

This report addresses the EMC verification testing and test results of Ecobee Inc's Athena RS, herein referred to as EUT (Equipment Under Test) performed at Global EMC Labs.

The EUT was tested for compliance against the following standards:

RSS 210 Issue 8:2010 FCC Part 15 Subpart C 15:2014

Test procedures, results, justifications, and engineering considerations, if any, follow later in this report.

The results contained in this report relate only to the item(s) tested.

This report does not imply product endorsement by A2LA or any other accreditation agency, any government, or Global EMC Inc.

Opinions/interpretations expressed in this report, if any, are outside the scope of Global EMC Inc accreditation. Any opinions expressed do not necessarily reflect the opinions of Global EMC Inc, unless otherwise stated.

Client	Ecobee Inc	OLODA PARTIES
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	EINCINC

Summary

The results contained in this report relate only to the item(s) tested.

EUT FCC Certification #, FCC ID:	WR9EBRSE3
EUT Industry Canada Certification #, IC:	7981A- EBRSE3
EUT Passed all tests performed.	Yes (see test results summary)
Tests conducted by	Min Xie

Client	Ecobee Inc	CI ODI
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	ENCINC

Test Results Summary

Standard/Method	Description	Class/Limit	Result
FCC 15.203	Antenna Requirement	Unique	Pass See Justification
FCC 15.207	Power line conducted emissions	QuasiPeak Average	N/A, See Justifications
FCC 15.209 RSS-210 (Table 2)	Spurious Radiated emissions	QuasiPeak Average	Pass
FCC 15.249(a), (c) RSS-210 A2	Power requirement	< 50 mV/m @ 3m	Pass
Overall	Result		PASS

All tests were performed by Min Xie.

If the product as tested or otherwise complies with the specification, the EUT is deemed to comply with the requirement and is deemed a 'PASS' grade. If not 'FAIL' grade will be issued. Note that 'PASS' / 'FAIL' grade is independent of any measurement uncertainties. A 'PASS' / 'FAIL' grade within measurement uncertainty is marked with a '*'.

Client	Ecobee Inc	CLODATE
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	EMUINU

Justifications, Descriptions, or Deviations

The following justifications for tests not performed or deviations from the above listed specifications apply:

For the Antenna requirement specified in FCC 15.203 (RSS 210 section 5.5), the unit uses a 0 dBi PCB trace antenna.

For the Restricted Bands of operation, the EUT is designed to only operate between 902 – 928 MHz.

For 15.207 power line conducted emissions, the EUT is a battery powered device; thus, this requirement is not applicable.

The unit was tested with a control board which also supply the 3.3VDC for the EUT. A discharged battery was installed in the battery compartment to reflect normal uasage.

For maximum permissible exposure, this device operates at less than 50 mV/m at 3 meters in the 902 - 928 MHz band and is designed to operate greater than 20 cm from any personnel during normal operation. No testing is required, however worst case calculated exposure compliance follows later in this report.

For the scope of this test report the EUT was mounted in three orthogonal axes to maximize emissions. Worst case results are presented.

Client	Ecobee Inc	CLODATE
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	EMUINU

Applicable Standards, Specifications and Methods

ANSI C63.4:2009	- Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
ANSI C63.10:2009	- American national standard for testing unlicensed wireless devices
CFR 47 FCC 15	- Code of Federal Regulations – Radio Frequency Devices
CISPR 22:2008	- Information technology equipment – Radio disturbance characteristics – Limits and methods of measurement
ICES-003:2012	- Digital Apparatus - Spectrum Management and Telecommunications Policy Interference-Causing Equipment Standard
ISO 17025:2005	- General Requirements for the competence of testing and calibration laboratories
RSS-GEN	General Requirements and Information for the Certification of Radio Apparatus
RSS 210:2010	- Issue 8: Spectrum Management and Telecommunications Policy. Radio Standards Specification Low Power License-Exempt Radiocommunication Devices

Client	Ecobee Inc	CLODATE
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	EINCINC

Sample calculation(s)

Margin = limit – (received signal + antenna factor + cable loss – pre-amp gain)

Margin = 50.5dBuV/m - (50dBuV + 10dB + 2.5dB - 20dB)

Margin = 8.5 dB

Document Revision Status

Revision 1 - Aug-19, 2014

Initial release

Revision 2 - Sept-8, 2014

Report updated per ACB review.

Client	Ecobee Inc	CLODATE
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	EMUINU

Definitions and Acronyms

The following definitions and acronyms are applicable in this report. See also ANSI C63.14.

AE – Auxiallary Equipment.

BW – Bandwidth. Unless otherwise stated, this is refers to the 6 dB bandwidth.

EMC – Electro-Magnetic Compatibility

EMI – Electro-Magnetic Immunity

EUT – Equipment Under Test

ITE – Information Technology Equipment with a primary function(s) of entry, storage, display, retrieval, transmission, processing, switching, or control, of data.

LISN – Line impedance stabilization network

NCR – No Calibration Required

RF – Radio Frequency

Client	Ecobee Inc	CLODAT
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	EINICINC

Testing Facility

Testing for EMC on the EUT was carried out at Global EMC labs in Toronto, Ontario, Canada. The testing lab consists of a 3m semi-anechoic chamber calibrated to be able to allow measurements on an EUT with a maximum width or length of up to 2m and height up to 3m. The chamber is equipped with a turn table that is capable of testing devices up to 3300lb in weight. This facility is capable of testing products that are rated for 120 Vac and 240Vac single phase, or 208 Vac 3 phase input. DC capability is also available. The chamber is equipped with an antenna mast that controls polarization and height from the control room adjoining the shielded chamber. Radiated emissions measurements are performed using a Bilog, and Horn antenna where applicable. Conducted emissions, unless otherwise stated, are performed using a LISN.

Calibrations and Accreditations

The 3m semi-anechoic chamber is registered with Federal Communications Commission (FCC, 377448), Industry Canada (IC, 6844A-3) and VCCI (R-4023, G-506, T-1246, and C-4498). This semi-anechoic chamber complies with the requirements of EN55016-2-3:2006, section 7.5 and the site attenuation requirements of EN55016-1-4. This chamber was additionally calibrated for Normalized Site Attenuation (NSA) using test procedures outlined in ANSI C63.4 "Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz". The chamber is lined with ferrite tiles and absorption cones to minimize any undesired reflections. The NSA data is kept on file at Global EMC. For radiated susceptibility testing, a 16 point field calibration has been performed on the chamber. The field uniformity data is kept on file at Global EMC. Global EMC Inc is accredited to ISO 17025 by A2LA with Testing Certificate #2555.01. The laboratories current scope of accreditation listing can be found as listed on the A2LA website. All measuring equipment is calibrated on an annual or bi-annual basis as listed for each respective test.

Client	Ecobee Inc	CLADA
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	ENCINC

Testing Environmental Conditions and Dates

Following were the environmental conditions in the facility during time of testing –

Date	Test	Init.	Temperature (°C)	Humidity (%)	Pressure (kPa)
4/24/2014	All	MX	20-24°C	35 - 41%	98 -103kPa

Client	Ecobee Inc	CLODA
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	EMUINU

Detailed Test Results Section

Client	Ecobee Inc	CLODA
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	EMUINU

Radiated Emissions of Fundamental

Purpose

The purpose of this test is to ensure that the RF energy intentionally emitted from the EUT does not exceed the limit listed below as defined in the applicable test standard, as measured from a receiving antenna. This helps protect other periodic operating devices, and licensed broadcasting devices, and so on, from unwanted interference.

Limit(s) and Method


The method is as defined in ANSI C63.10:2009. The limits are as specified in FCC Part 15, Section 15.249 (a)

902 MHz to 928 MHz $-50 \text{ mV/m} (94 \text{ dBuV/m})^1 \text{ at } 3\text{m}$.

¹ Limit is with Quasi Peak detector with bandwidths as defined in CISPR-16-1-1.

Client	Ecobee Inc	CLADAT
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	EINICING

Typical Radiated Emissions Setup



Measurement Uncertainty

The expanded measurement uncertainty is calculated in accordance with CISPR 16-4-2 and is +/-4.4 dB with a 'k=2' coverage factor and a 95% confidence level.


Preliminary Graphs

Note the graphs shown below are for graphical illustration only. For final measurements with the appropriate detector, please refer to the final measurement table where applicable. The graph shown below is a maximized peak measurement graph, measured with a 100 kHz resolution bandwidth, over a full 0-360 rotation and the antenna height was varied from 1 m to 4 m. This peaking process is done as a worst case measurement.

The EUT was mounted in three orthogonal axes to maximize emissions. Worst case results are presented.


Client	Ecobee Inc	CLODATE
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	EMUINU

Fundamental – Low Channel Horizontal – Peak Emission




Client	Ecobee Inc	CLODATE
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	EMUINU

Fundamental – Low Channel Vertical – Peak Emission




Client	Ecobee Inc	CLODATE
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	EMUINU

Fundamental – Mid Channel Horizontal – Peak Emission




Client	Ecobee Inc	CLODATE
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	EMUINU

Fundamental – Mid Channel Vertical – Peak Emission




Client	Ecobee Inc	CLODATE
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	EMUINU

Fundamental – High Channel Horizontal – Peak Emission



Client	Ecobee Inc	CLODATE
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	EMUINU

Fundamental – High Channel Vertical – Peak Emission



Client	Ecobee Inc	CLODATE
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	EMUINU

Final Measurements

Test Frequency (MHz)	Detection mode	Antenna polarity (Horz/Vert)	Raw signal dB(µV)	Antenna factor dB	Cable loss dB	Atten uator dB	Pre-Amp Gain dB	Received signal dB(µV/m)	Emission limit dB(µV/m)	Margin dB(μV)	Result
			Low C	hannel 903	MHz -	Y-Axis					
903	Peak	Vert	84.2	22.7	2.4	3.0	28.6	83.7	94.0	10.3	PASS
903	Peak	Horz	79.1	23.8	2.4	3.0	28.6	79.7	94.0	14.3	PASS
			Low (Channel 903	MHz)	(-Axis					
903	Peak	Vert	79.3	22.7	2.4	3.0	28.6	78.8	94.0	15.2	PASS
903	Peak	Horz	82.7	23.8	2.4	3.0	28.6	83.3	94.0	10.7	PASS
			Low (Channel 903	MHz Z	Z-Axis					
903	Peak	Vert	83.9	22.7	2.4	3.0	28.6	83.4	94.0	10.6	PASS
903	Peak	Horz	79.4	23.8	2.4	3.0	28.6	80.0	94.0	14.0	PASS
				Channel 915							
915	Peak	Vert	90.0	22.7	2.4	3.0	28.6	89.5	94.0	4.5	PASS
915	Peak	Horz	85.1	23.8	2.4	3.0	28.6	85.7	94.0	8.3	PASS
				Channel 915							
915	Peak	Vert	84.9	22.7	2.4	3.0	28.6	84.4	94.0	9.6	PASS
915	Peak	Horz	92.3	23.8	2.4	3.0	28.6	92.9	94.0	1.1	PASS
045	-			Channel 915			00.0	00.0	04.0	4.4	DA 00
915	Peak	Vert	90.4	22.7	2.4	3.0	28.6	89.9	94.0	4.1	PASS
915	Peak	Horz	85.2	23.8	2.4	3.0	28.6	85.8	94.0	8.2	PASS
			11: 1 01	1.007.14							
927	Peak	Vert	93.4	nnel 927 M 22.7	HZ Y-AX 2.4	3.0	28.6	92.9	94.0	1.1	PASS
			93.4 87.6	23.8	2.4	3.0					
927	Peak	Horz		annel 927 M			28.6	88.2	94.0	5.8	PASS
927	Peak	Vert	93.2	22.7	2.4	3.0	28.6	92.7	94.0	1.3	PASS
927	Peak	Horz	93.2	23.8	2.4	3.0	28.6	92.7	94.0	2.0	PASS
921	reak	ПОІД		annel 927 M			20.0	92.0	94.0	2.0	PASS
927	Peak	Vert	88.3	22.7	2.4	3.0	28.6	87.8	94.0	6.2	PASS
927	Peak	Horz	92.8	23.8	2.4	3.0	28.6	93.4	94.0	0.6	PASS

Table 1: Fundamental emissions

Client	Ecobee Inc	OLODA T
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	EINCINC

Test Equipment List

Equipment	Model No.	Manufacturer	Last calibration date	Next calibration due date	Asset #
Spectrum Analyzer	8566B	HP	2013-01-22	2015-01-22	GEMC169
Quasi Peak Adapter	85650A	HP	2013-01-23	2015-01-23	GEMC170
BiLog Antenna	3142-C	ETS	Feb 4, 2013	Feb 4, 2015	GEMC 137
Attenuator 3 dB	FP-50-3	Trilithic	NCR	NCR	GEMC 40
9kHz-1GHz, preamp	LNA 6901	Teseq	2013-02-25	2015-02-25	GEMC168
RF Cable 7m	LMR-400-7M- 50OHM-MN-MN	LexTec	NCR	NCR	GEMC 28
RF Cable 1m	LMR-400-1M- 50OHM-MN-MN	LexTec	NCR	NCR	GEMC 29
RF Cable 0.5M	LMR-400-0.5M- 50OHM-MN-MN	LexTec	NCR	NCR	GEMC 31

This report module is based on GEMC template "FCC - 15.209 - Radiated Emissions_Rev1.doc"

Client	Ecobee Inc	OLODA T
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	EINCINC

Spurious Radiated Emissions

Purpose

The purpose of this test is to ensure that the RF energy unintentionally emitted from the EUT does not exceed the limits listed below as defined in the applicable test standard, as measured from a receiving antenna. This helps protect broadcast radio services such as television, FM radio, pagers, cellular telephones, emergency services, and so on, from unwanted interference.

Limit(s) and Method


The method is as defined in ANSI C63.10:2009. The limits are as defined in FCC Part 15, Section 15.209:

```
0.009~\rm MHz - 0.490~\rm MHz,\ 2400/F(kHz)\ uV/m\ at\ 300\ m^1\\ 0.490~\rm MHz - 1.705~\rm MHz,\ 24000/F(kHz)\ uV/m\ at\ 30\ m^1\\ 1.705~\rm MHz - 30~\rm MHz,\ 30\ uV/m\ at\ 30\ m^1\\ 30~\rm MHz - 88~\rm MHz,\ 100\ uV/m\ (40.0\ dBuV/m^1)\ at\ 3\ m\\ 88~\rm MHz - 216~\rm MHz,\ 150\ uV/m\ (43.5\ dBuV/m^1)\ at\ 3\ m\\ 216~\rm MHz - 960~\rm MHz,\ 200\ uV/m\ (46.0\ dBuV/m^1)\ at\ 3\ m\\ Above\ 960~\rm MHz,\ 500\ uV/m\ (54.0\ dBuV/m^2)\ at\ 3m\\ Above\ 1000~\rm MHz,\ 500\ uV/m\ (74\ dBuV/m^3)\ at\ 3m\\ Above\ 1000~\rm MHz,\ 500\ uV/m\ (74\ dBuV/m^3)\ at\ 3m
```

¹Limit is with Quasi Peak detector with bandwidths as defined in CISPR-16-1-1 ²Limit is with 1 MHz measurement bandwidth and using an Average detector ³Limit is with 1 MHz measurement bandwidth and using a Peak detector

Client	Ecobee Inc	CLADAT
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	EINICING

Typical Radiated Emissions Setup



Measurement Uncertainty

The expanded measurement uncertainty is calculated in accordance with CISPR 16-4-2 and is +/-4.4 dB with a 'k=2' coverage factor and a 95% confidence level.

Preliminary Graphs

Note the graphs shown below are for graphical illustration only. For final measurements with the appropriate detector, please refer to the final measurement table where applicable. The graph shown below is a maximized peak measurement graph, measured with a resolution bandwidth greater than the final required detector and over a full 0-360 rotation. This peaking process is done as a worst case measurement. This process enables the detection of frequencies of concern for final measurement, and provides considerable time savings.


In accordance with FCC Part 15, Subpart A, Section 15.33, the device was scanned to the 10th harmonic (a minimum of a 10 GHz).

Devices scanned may be scanned at alternate test distances, and in accordance with FCC Part 15, Subpart A, Section 15.31, an extrapolation factor of 20 dB/decade was used above

Client	Ecobee Inc	OLODA PARTIES
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	ENICING

30 MHz and 40 dB/decade below 30 MHz. For example for 1 meter measurements, an extrapolation factor 9.5 dB from 20 Log (3m/1m) is applied.


Band edge measure graphs were shown for illustrations purpose. See final measurement section for all measurements.



Client	Ecobee Inc
Product	Athena RS
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014




150 kHz – 30 MHz



Client	Ecobee Inc	OLADA A
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	ENCINC


Mid Channel - 30 MHz - 1 GHz Vertical - Peak Emission Graph



Note: Emission at 927 MHz is the fundamental frequency of the EUT. See Final Measurements and Results section for numerical results.

Client	Ecobee Inc	CLADA
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	ENCINC

Mid Channel – 30 MHz – 1 GHz Horizontal - Peak Emission Graph




Note: Emission at 927 MHz is the fundamental frequency of the EUT. See Final Measurements and Results section for numerical results.

Client	Ecobee Inc	01.0
Product	Athena RS	GLO
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	E N




Mid Channel – 1 GHz – 2 GHz Vertical - Peak Emission Graph



Client	Ecobee Inc	01.0
Product	Athena RS	GLO
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	E N




Mid Channel – 1 GHz – 2 GHz Horizontal - Peak Emission Graph



Client	Ecobee Inc	01.0
Product	Athena RS	GLO
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	




Mid Channel - 2 GHz - 10 GHzVertical - Peak Emission Graph



Client	Ecobee Inc	
Product	Athena RS	G
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	E




Mid Channel – 2 GHz – 10 GHz Horizontal - Peak Emission Graph




Client	Ecobee Inc	CLODATE
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	EMUINU

Band Edge – High Channel Vertical - Peak Emission




Client	Ecobee Inc	CLODATE
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	EMUINU

Band Edge – High Channel Horizontal - Peak Emission




Client	Ecobee Inc	CLODATE
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	EMUINU

Band Edge – Low Channel Vertical - Peak Emission



Client	Ecobee Inc	CLADAT
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	EMUINU

Band Edge – Low Channel Horizontal - Peak Emission



Client	Ecobee Inc	CI ODI
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	ENCINC

Final Measurements and Results

The EUT passed the limits.

Product Ca	tegory	FCC 15.209					
Produ	ct	Athena RS					
Suppl	у			Batte	ry, 3.3 VD	C	
	Vertical Emission Table						
Frequency (MHz)	Detecto	r Raw (dBuV)	Factors	Level (dBuV)	Limit (dB)	Margin (dB)	Pass/Fail
244.079	Peak	55.9	-12.2	43.7	46	2.3	Pass
248.606	Peak	55.5	-12.1	43.4	46	2.6	Pass
239.423	Peak	55.8	-12.4	43.4	46	2.6	Pass
253.132	Peak	54.3	-12.1	42.2	46	3.8	Pass
230.499	Peak	53.3	-12.8	40.5	46	5.5	Pass
259.276	Peak	52.3	-12.0	40.3	46	5.7	Pass
1593	Peak	56.5	-5.7	50.8	74	23.2	Pass
1593	AVG	36.5	-5.7	30.8	54	23.2	Pass
		Н	orizontal	Emission '	Гable		
246.989	Peak	55.6	-12.2	43.4	46	2.6	Pass
251.354	Peak	55.4	-12.1	43.3	46	2.7	Pass
250.61	Peak	53.8	-12.2	41.6	46	4.4	Pass
256.107	Peak	53.3	-12.0	41.3	46	4.7	Pass
256.915	Peak	53.2	-11.9	41.3	46	4.7	Pass
233.28	Peak	53.6	-12.6	41.0	46	5.0	Pass
1597.67	Peak	56.0	-4.3	51.7	74	22.3	Pass
1597.67	AVG	39.6	-4.3	35.3	54	18.7	Pass

Table 2: Spurious radiated emission

Client	Ecobee Inc	CLODAT
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	EIVICING




Table 3: Band edge and harmonic measurements

Client	Ecobee Inc	CLODATE
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	EMUINU

Test Equipment List

Equipment	Model No.	Manufacturer	Last calibration date	Next calibration due date	Asset #
Spectrum Analyzer	8566B	HP	2013-01-22	2015-01-22	GEMC169
Quasi Peak Adapter	85650A	HP	2013-01-23	2015-01-23	GEMC170
Loop Antenna	EM 6871	Electro-Metrics	Feb 5, 2013	Feb 5, 2015	GEMC 70
Loop Antenna	EM 6872	Electro-Metrics	Feb 5, 2013	Feb 5, 2015	GEMC 71
BiLog Antenna	3142-C	ETS	Feb 4, 2013	Feb 4, 2015	GEMC 137
Attenuator 3 dB	FP-50-3	Trilithic	NCR	NCR	GEMC 40
9kHz-1GHz, preamp	LNA 6901	Teseq	2013-02-25	2015-02-25	GEMC168
Q-Par 1.5-18 GHz Horn	6878/24	Q-par	8/23/2012	8/23/2014	GEMC 6365
1-26G pre-amp	HP 8449B	HP	8/22/2012	8/22/2014	GEMC 6351
RF Cable 7m	LMR-400-7M- 50OHM-MN-MN	LexTec	NCR	NCR	GEMC 28
RF Cable 1m	LMR-400-1M- 50OHM-MN-MN	LexTec	NCR	NCR	GEMC 29
RF Cable 0.5M	LMR-400-0.5M- 50OHM-MN-MN	LexTec	NCR	NCR	GEMC 31

This report module is based on GEMC template "FCC - 15.209 - Radiated Emissions_Rev1.doc"

Client	Ecobee Inc	CLODA
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	EMUINU

20 dB Bandwidth Measurement – 15.249

15.215 c) intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated. The requirement to contain the designated bandwidth of the emission within the specified frequency band includes the effects from frequency sweeping, frequency hopping and other modulation techniques that may be employed as well as the frequency stability of the transmitter over expected variations in temperature and supply voltage. If a frequency stability is not specified in the regulations, it is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

Test Results


The EUT passed. The 20 dB BW was wholly contained within the 15.249 emission band of 902 - 928 MHz.

Channel Frequency (MHz)	20dB Measured Bandwidth (kHz)
927	371
915	378
903	368

Client	Ecobee Inc	CLODATE
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	ENICING

20 dB Bandwidth measurement graph

The graph below shows the 20 dB bandwidth the device. This is measured by a max hold on the spectrum analyzer and the highest resolution bandwidth that is sufficiently low to exhibit the 20 dB bandwidth of a channel during operation of the EUT. This measurement is a peak measurement. Max hold is performed for a duration of not less than 1 minute.



Client	Ecobee Inc	CLODATE
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	EMUINU

Test Equipment

Equipment	Model No.	Manufacturer	Last calibration date	Next calibration due date	Asset #
Spectrum Analyzer	8566B	HP	2013-01-22	2015-01-22	GEMC169
Quasi Peak Adapter	85650A	HP	2013-01-23	2015-01-23	GEMC170
BiLog Antenna	3142-C	ETS	Feb 4, 2013	Feb 4, 2015	GEMC 137
Attenuator 3 dB	FP-50-3	Trilithic	NCR	NCR	GEMC 40
9kHz-1GHz, preamp	LNA 6901	Teseq	2013-02-25	2015-02-25	GEMC168
RF Cable 7m	LMR-400-7M- 50OHM-MN-MN	LexTec	NCR	NCR	GEMC 28
RF Cable 1m	LMR-400-1M- 50OHM-MN-MN	LexTec	NCR	NCR	GEMC 29
RF Cable 0.5M	LMR-400-0.5M- 50OHM-MN-MN	LexTec	NCR	NCR	GEMC 31

This report module is based on GEMC template "FCC - 15.209 - Radiated Emissions_Rev1.doc"

Client	Ecobee Inc	CLODATE
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	EINCINC

Maximum Permissible Exposure

Purpose

The purpose of this test is to ensure that the RF energy intentionally transmitted, in terms of power density emitted from the EUT at a stated operating distance does not exceed the limits listed below as defined in the applicable test standard, as calculated based upon readings obtained during testing. This helps protect human exposure to excessive RF fields.

Limit(s) and Method

The limits, as defined FCC 1.1310 Table 1 (B) limits for general public exposure was applied. The limits for the frequency ranges 300 MHz to 1.5 GHz was applied. The limits are f/1500 mW/ cm². The distance used for calculations was 20 cm, as this is the minimum distance an operator will be from the EUT during normal operation, as stated by the manufacturer.

Results

The EUT passed the requirements. The worst case calculated power density was 0.000127 mW/cm^2 , this is significantly under the 0.618 mW/cm^2 requirement.

Calculations

Method 2 (EIRP) PCB antenna

$$P_d = EIRP / (4*pi*R^2)$$

Where EIRP = equivalent isotropic radiated power Where R = 20 cm

The EUT have highest output field strength, 93.1 dBuV, at 927 MHz.

EIRP = E(dBuV/m) - 95.2

EIRP = 93.3 - 95.2

EIRP = -1.9 dBm or 0.64 mW

 $P_d = 0.64 \text{ mW} / (4 * \text{pi} * 20 \text{cm}^2)$

 $P_d = 0.64 \text{ mW} / 5026 \text{ cm}^2$

 $P_d = 0.000127 \text{ mW/cm}^2$

The limit for 927 MHz is $(927/1500) = 0.618 \text{ mW/cm}^2$

Client	Ecobee Inc	CLODATE
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	ENICINC

Appendix A – EUT Summary

Client	Ecobee Inc	CLODA
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	EMCINC

For further details for filing purposes, refer to filing package.

General EUT Description

	Client		
Organization	Ecobee Inc 477 Richmond Street West, Ste 210 Toronto, ON, Canada M5R 3E7		
Contact	Kashif Ahmed		
Phone	416 987 1048		
Email	kashif@ecobee.com		
EUT Details			
EUT Name (for report title)	Athena RS		
EUT Model / SN (if known)			
FCC ID	WR9		
Industry Canada #	7981A-		
Equipment category	Wireless temperature and room occupancy sensor		
EUT is powered using	Battery		
Input voltage range(s) (V)	3.3 VDC		
Transmits RF energy? (describe)	Yes		
Basic EUT functionality description	Ecobee 3 temperature sensor		

Note the EUT is considered to have been received the date of the commencement of the first test, unless otherwise stated. For a close-up picture of the EUT, see 'Appendix B-EUT & Test Setup Photographs'.

Client	Ecobee Inc	CLODATE
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	EMCINC

EUT Configuration

Please see Appendix B for a picture of the unit running in normal conditions.

- Wireless were configured to transmit at 100% duty cycle
- The 15.249 902 928 MHz transmitter were configure with the following settings: v25 (25 kHz channel separation frequency), 0 dBm setting (max power level).

Operational Setup

These devices are required to be attached to the EUT for its normal operation.

- A debug board was connected to the EUT.
- The EUT was powered by the debug board. However a battery was install in the battery compartment.

Client	Ecobee Inc	CLODATE
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	EMUINU

Appendix B – EUT and Test Setup Photographs

Client	Ecobee Inc	OLODA PARA
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	EMCINC

Note: These photos are for information purposes only. Also refer to PDF files that are

separate from this test report.



Illustration 1: Radiated emission setup – photo 1

Client	Ecobee Inc	CLODA
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	EMUINU



Illustration 2: Radiated emission setup - photo 2

Client	Ecobee Inc	CLODATE
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	EMUINU



Illustration 3: Radiated setup - photo 3

Client	Ecobee Inc	CLODATE
Product	Athena RS	GLUBAL
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2014	EMUINU




Illustration 4: Radiated setup - photo 4