

683-3, Yubang-Dong, Yongin-Si, Kyunggi-Do, Korea. 449-080 Tel: +82-31-321-2664 Fax: +82-31-321-1664

http://www.digitalemc.com

SAR TEST REPORT

Dates of Tests: April 04~May 20, 2009 Test Report S/N:DR50110811C-r2 Test Site: DIGITAL EMC CO., LTD.

FCC ID

WRLWINDDUO2100

APPLICANT

WND TELECOM OFFSHORE S.A.L.

FCC Classification: Licensed Portable Transmitter Held to Ear (PCE)

EUT Type: Dual Face GSM/GPRS Mobile Phone with Bluetooth

Model Name WIND DUO 2100

Test Device Serial No.: Identical prototype

TX Frequency Range: 824.20 ~848.80 MHz (GSM850)

1850.20 ~ 1909.80 MHz (PCS1900)

RX Frequency Range: 869.2 ~893.8 MHz (GSM850)

1930.2 ~ 1989.8 MHz (PCS1900)

Max. RF Output Power: 0.391 W ERP GSM850(Black face) / 0.201 W ERP GSM850(Silver face)

0.292 W EIRP PCS1900(Black face) / 0.337 W EIRP PCS1900(Silver face)

Max. SAR Measurement: 0.240 mW/g GSM850 Head SAR // 0.255 mW/g GSM850 GPRS Body SAR

1.430 mW/g PCS1900 Head SAR // 0.404 mW/g PCS1900 GPRS Body SAR

Application Type: Certification

Rule Part(s): §2.1093; FCC/OET Bulletin Supplement C[July 2001]

FCC SAR Evaluation Considerations for Handsets with Multiple

Transmitters and Antennas (v01r03 #648474)

Data of issue: May 27, 2009

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE Std. C95.1-1992 and had been tested in accordance with the measurement procedures specified in FCC/OET Bulletin 65 Supplement C (2001) and IEEE Std. 1528-2003.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

7 20 3 3 4 400 5 5 5 6 5 7 7 20 8 8 9 9 10 8 8 9 9 10 8 8 9 10 8 9 10

Tested by:

Sun-Kyu Ryu (Engineer)

Reviewed by:

Harvey Sung (Chief Engineering Director)

TABLE OF CONTENTS

1. INTRODUCTION	3
SAR DEFINITION	3
2. SAR MEASUREMENT SETUP	4
Robotic System	4
System Hardware	4
System Electronics	4
3. DASY4 E-FIELD PROBE SYSTEM	5
Probe Measurement System	5
Probe Specifications	5
4. Probe Calibration Process	6
Dosimetric Assessment Procedure	6
Free Space Assessment	6
Temperature Assessment	6
5. PHANTOM & EQUIVALENT TISSUES	7
SAM Phantom	7
Brain & Muscle Simulating Mixture Characterization	7
Device Holder for Transmitters	7
6. TEST SYSTEM SPECIFICATIONS	8
Automated Test System Specifications	8
7. DOSIMETRIC ASSESSMENT & PHANTOM SPECS	9
Measurement Procedure	9
Specific Anthropomorphic Mannequin (SAM) Specifications	9
8. DEFINITION OF REFERENCE POINTS	_
	10
EAR Reference Point	10
Handset Reference Points	10
9. TEST CONFIGURATION POSITIONS	11
Positioning for Cheek/Touch	11
Positioning for Ear /15° Tilt	12
Body Holster /Belt Clip Configurations	13
10. ANSI / IEEE C95.1 1992 RF EXPOSURE LIMITS	14
Uncontrolled Environment	14
Controlled Environment	14
11. MEASUREMENT UNCERTAINTIES	15
SAR Measurement Uncertainties	15
12. SYSTEM VERIFICATION	16
Tissue Verification	16
Test System Verification	16
13. Multiple Transmitters SAR Considerations	17
Introduction	17
Output power thresholds for unlicensed Transmitters	17
Multiple antenna transmission information	17
Summary of SAR evaluation requirement for cell phones with multiple transmitters	18
14. SAR TEST DATA SUMMARY	19
See Measurement Result Data Pages	19
Procedures Used To Establish Test Signal	19
Device Test Conditions	19
EUT Handset Reference Points	19
15. SAR DATA SUMMARY	20- 31
16. SAR TEST EQUIPMENT	32
Equipment Calibration	32
17. CONCLUSION	33
Measurement Conclusion	33
18 REFERENCES	34

1. INTROCUCTION/SAR DEFINITION

In 1974, the International Radiation Protection Association (IRPA) formed a working group on non-ionizing radiation (NIR), which examined the problems arising in the field of Protection against the various types of NIR. At the IRPA Congress in Paris in 1977, this working group because the International Non-Ionizing Radiation Committee (INIRC).

In cooperation with the Environmental Health Division of the World Health Organization (WHO), the IRPA/INIRC developed a number of health criteria documents on NIR as part of WHO'S Environmental Health Criteria Programme, sponsored by the United Nations Environment Programme (UNEP). Each document includes an overview of the physical characteristics, measurement and instrumentation, sources, and applications of NIR, a thorough review of the literature on biological effects, and an evaluation of the health risks of exposure to NIR. These health criteria have provided the scientific database for the subsequent development of exposure limits and codes of practice relating to NIR.

At the Eighth International Congress of the IRPA (Monotreal, 18-22 May 1992), a new, independent scientific organization-the International Commission on Non-Ionizing Radiation Protection (ICNIRP)-was established as a successor to the IRPA/INIRC. The functions of the Commission are to investigate the hazards that may be association with the different forms of NIR, develop international guidelines on NIR exposure to static and extremely-low-frequency (ELF) electric and magnetic field have been reviewed by UNEP/WHO/IRPA (1984, 1987). Those publications and a number of others, including UNEP/WHO/IRPA (1993) and Allen et al. (1991), provided the scientific rationale for these guidelines.

A glossary of terms appears in the Appendix.

SAR Definition

Specific Absorption Rate (SAR) is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ) It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Fig. 1.1)

$$S A R = \frac{d}{d t} \left(\frac{d U}{d m} \right) = \frac{d}{d t} \left(\frac{d U}{\rho d v} \right)$$

Figure 1.1 SAR Mathematical Equation

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = E^2 / \rho$$

Where:

 σ = conductivity of the tissue-simulant material (S/m)

 ρ = mass density of the tissue-simulant material (kg/m3)

E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relations to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

2. SAR MEASUREMENT SETUP

Robotic System

Measurements are performed using the DASY4 automated dosimetric assessment system. The DASY4 is made by Schmid & Partner Engineering AG (SPEAG) in Zurich, Switzerland and consists of high precision robotics system (Staubli), robot controller, Pentium III computer, near-field probe, probe alignment sensor, and the generic twin phantom containing the brain equivalent material. The robot is a six-axis industrial robot performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF) (see Fig. 2.1).

System Hardware

A cell controller system contains the power supply, robot controller, teach pendant (Joystick), and a remote control used to drive the robot motors. The PC consists of the Micron Pentium IV 500 MHz computer with Windows NT system and SAR Measurement Software DASY4, A/D interface card, monitor, mouse, and keyboard. The Staubli Robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit that performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC plug-in card.




Figure 2.1 SAR Measurement System Setup

System Electronics

The DAE3 consists of a highly sensitive electrometer-grade preamplifier with autozeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer. The system is described in detail in [7].

3. SAR MEASUREMENT SETUP

Probe Measurement System



The SAR measurements were conducted with the dosimetric probe ET3DV6,designed in the classical triangular configuration [7] (see Fig. 3.2) and optimized for dosimetric evaluation. The probe is constructed using the thick film technique; with printed resistive lines on ceramic substrates. The probe is equipped with an optical multifiber line ending at the front of the probe tip (see Fig. 3.3). It is connected to the EOC box on the robot arm and provides an automatic detection of the phantom surface. Half of the fibers are connected to a pulsed infrared transmitter, the other half to a synchronized As the probe approaches the surface, the reflection from the surface produces a coupling from the transmitting to the receiving fibers. This reflection increases first during the approach, reaches maximum and then decreases. If the probe is flatly touching the surface, the coupling is zero. The distance the coupling maximum to the surface is independent of the surface reflectivity and largely independent of the surface to probe angle. The DASY4 software reads the reflection during a software approach and looks for the maximum using a 2nd order fitting (see Fig.3.1). The approach is stopped at reaching the maximum.

Figure 3.1 DAE System

Probe Specifications

Calibration: In air from 10 MHz to 6.0 GHz

In brain and muscle simulating tissue at

Frequencies of 900 MHz, 1810 MHz, 1950 MHz, 2450 MHz, 2600 MHz

Frequency: 10 MHz to 6 GHz

Linearity: $\pm 0.2 dB$ (30 MHz to 6 GHz)

Dynamic: 10 mW/kg to 100 W/kg

Range: Linearity: $\pm 0.2 \text{ dB}$

Dimensions: Overall length: 330 mm

Tip length: 20 mm

Body diameter: 12 mm

Tip diameter: 2.5 mm

Distance from probe tip to sensor center: 1 mm

Application: SAR Dosimetry Testing

Compliance tests of mobile phones




Figure 3.1 Triangular Probe Configuration



Figure 3.2 Probe Thick-Film Technique

4. Probe Calibration Process

Dosimetric Assessment Procedure

Each probe is calibrated according to a dosimetric assessment procedure described in [8] with accuracy better than +/- 10%. The spherical isotropy was evaluated with the procedure described in [9] and found to be better than +/-0.25dB. The sensitivity parameters (NormX, NormY, NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe is tested.

Free Space Assessment

The free space E-field from amplified probe outputs is determined in a test chamber. This is performed in a TEM cell for frequencies below 1 GHz (see Fig. 4.1), and in a waveguide above 1GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity at the proper orientation with the field. The probe is then rotated 360 degrees.

Temperature Assessment *

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The measured free space E-field in the medium correlates to temperature rise in a dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe (see Fig. 4.2).

$$SAR = C \frac{\Delta T}{\Delta t}$$

$$SAR = \frac{|E|^2 \cdot \sigma}{\rho}$$

where: where:

 Δt = exposure time (30 seconds), σ = simulated tissue conductivity,

C = heat capacity of tissue (brain or muscle), ρ = Tissue density (1.25 g/cm³ for brain tissue)

 ΔT = temperature increase due to RF exposure.

SAR is proportional to ΔT / Δt , the initial rate of tissue heating, before thermal diffusion takes place. Now it's possible to quantify the electric field in the simulated tissue by equating the thermally derived SAR to the E- field;




Figure 4.1 E-Field and Temperature Measurements at 900MHz[7]




Figure 4.2 E-Field and Temperature Measurements at 1900MHz[7]

5. PHANTOM & EQUIVALENT TISSUES

SAM Phantom



Figure 5.1 SAM Twin Phantom

The SAM Twin Phantom V4.0 is constructed of a fiberglass shell integrated in a wooden table. The shape of the shell is based on data from an anatomical study designed to determine the maximum exposure in at least 90% of all users [11][12]. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents the evaporation of the liquid. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot. (see Fig. 5.1)

Brain & Muscle Simulating Mixture Characterization



The brain and muscle mixtures consist of a viscous gel using hydroxethyl cellullose (HEC) gelling agent and saline solution (see Table 6.1). Preservation with a bacteriacide is added and visual inspection is made to make sure air bubbles are not trapped during the mixing process. The mixture is calibrated to obtain proper dielectric constant (permittivity) and conductivity of the desired tissue. The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 have been incorporated in the following table. Other head and body tissue parameters that have not bee specified in P1528 are derived from the issue dielectric parameters computed from he 4-Cole-Cole equations The mixture characterizations used for the brain and muscle tissue simulating liquids are according to the data by C. Gabriel and G. Hartsgrove [13].(see Fig. 5.2)

Figure 5.2 Simulated Tissue

Table 5.1 Composition of the Brain & Muscle Tissue Equivalent Matter

INCREDIENTS		SIMULATING TISSUE					
INGREDIENTS	INGREDIENTS		835 MHz Muscle	1900 MHz Brain	1900 MHz Muscle		
Mixture Percentage							
WATER		41.45	52.50	54.90	40.40		
DGBE	BBE		0.000	44.92	58.00		
SUGAR		56.00	45.00	0.000	0.000		
SALT		1.450	1.400	0.180	0.500		
BACTERICIDE		0.100	0.100	0.000	0.100		
HEC		1.000	1.000	0.000	1.000		
Dielectric Constant	Target	41.50	55.20	40.00	53.30		
Conductivity (S/m) Target		0.900	0.970	1.400	1.520		

Device Holder for Transmitters



Figure 5.2 Mounting Device

In combination with the SAM Twin Phantom V4.0, the Mounting Device (see Fig. 5.2) enables the rotation of the mounted transmitter in spherical coordinates where by the rotation point is the ear opening. The devices can be easily, accurately, and repeatably be positioned according to the FCC specifications. The device holder can be locked at different phantom locations (left head, right head, flat phantom).

 Note: A simulating human hand is not used due to the complex anatomical and geometrical structure of the hand that may produce infinite number of configurations [12]. To produce the worst-case condition (the hand absorbs antenna output power), the hand is omitted during the tests.

6. TEST SYSTEM SPECIFICATIONS

Automated Test System Specifications

<u>Positioner</u>

Robot: Stäubli Unimation Corp. Robot Model: RX60L

Repeatability: 0.02 mm

No. of axis: 6

Data Acquisition Electronic (DAE) System

Cell Controller

Processor: Pentium 4 CPU

Clock Speed: 3 GHz

Operating System: Window 2000

Data Card: DASY4 PC-Board



Figure 6.1 DASY4 Test System

Data Converter

Features: Signal, multiplexer,A/D converter. & control logic

Software: DASY4

Connecting Lines: Optical downlink for data and status info

Optical uplink for commands and clock

PC Interface Card

Function: 24 bit (64 MHz) DSP for real time processing

Link to DAE 3

16 bit A/D converter for surface detection system

serial link to robot

direct emergency stop output for robot

E-Field Probes

Model: EX3DV4 S/N: 3643

Construction: Triangular core fiber optic detection system

Frequency: 10 MHz to 6 GHz

Linearity: \pm 0.2 dB(30 MHz to 6 GHz)

Phantom

Phantom: SAM Twin Phantom (V4.0)

Shell Material: Vivac Composite

Thickness: $2.0 \pm 0.2 \text{ mm}$

7. DOSIMETRIC ASSESSMENT & PHANTOM SPECS

Measurement Procedure




Figure 7.1 Sample Sar Area Scan

The evaluation was performed using the following procedure:

- 1. The SAR measurement was taken at a selected spatial reference point to monitor power variations during testing. This fixed location point was measured and used as a reference value.
- 2. The SAR distribution at the exposed side of the head was measured at a distance of 3.9mm from the Inner surface of the shell. The area covered the entire dimension of the head and the horizontal grid spacing was $15 \text{ mm} \times 15 \text{ mm}$.
- 3. Based on the area scan data, the area of the maximum absorption was determined by spline interpolation. Around this point, a volume of $32 \text{mm} \times 32 \text{ mm} \times 30 \text{ mm}$ (fine resolution volume scan, zoom scan) was assessed by measuring $5 \times 5 \times 7$ points. On this basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see Fig. 7.1):
- a. The data at the surface was extrapolated, since the center of the dipoles is $2.7\,$ mm away from the tip of the probe and the distance between the surface and the lowest measuring point is $1.2\,$ mm. The extrapolation was based on a least square algorithm [15]. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip.
- b. The maximum interpolated value was searched with a straight-for war dalgorithm. Around this maximum the SAR values averaged over the spatial volumes (1g or 10g) were computed using the 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions) [15][16]. The volume was integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were interpolated to calculate the average.
- c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
- 4. The SAR reference value, at the same location as procedure #1, was re-measured. If the value changed by more than 5%, the evaluation is repeated.

Specific Anthropomorphic Mannequin (SAM) Specifications

The phantom for handset SAR assessment testing is a low-loss dielectric shell, with shape and dimensions derived from the anthropometric data of the 90th percentile adult male head dimensions as tabulated by the US Army. The SAM Twin Phantom shell is bisected along the mid-sagittal plane into right and left halves (see Fig. 7.2). The perimeter sidewalls of each phantom halves are extended to allow filling with liquid to a depth that is sufficient to minimized reflections from the upper surface. The liquid depth is maintained at a minimum depth of 15cm to minimize reflections from the upper surface.



Figure 7.2 SAM Twin Phantom shell

8. DEFINITION OF REFERENCE POINTS

EAR Reference Point




Figure 8.2 Close-up side view of ERPs

Figure 8.1 shows the front,, back and side views of the SAM Twin Phantom. The point "M" is the reference point for the center of the mouth, "LE" is the left ear reference point(ERP), and "RE" is the right ERP. The ERPs are 15mm posterior to the entrance to the Ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 9.2. The plane Passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck- Front) is perpendicular to the reference plane and passing through the RE (or LE) is called the Reference Pivoting Line (see Figure 8.2). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning [5]



Figure 8.1 Front, back and side view of SAM Twin Phantom

Handset Reference Points

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the "test device reference point" located along the "vertical centerline" on the front of the device aligned to the "ear reference point" (See Fig. 8.3). The "test device reference point" was than located at the same level as the center of the ear reference point. The test device was positioned so that the "vertical centerline" was bisecting the front surface of the handset at it's top and bottom edges, positioning the "ear reference point" on the outer surface of the both the left and right head phantoms on the ear reference point.




Figure 8.3 Handset Vertical Center & Horizontal Line Reference Points

9. TEST CONFIGURATION POSITIONS (Continued)

Positioning for Cheek/Touch

1. The test device was positioned with the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 9.1), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.



Figure 9.1 Front, Side and Top View of Cheek/Touch Position

- 2. The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the ear.
- 3. While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the plane normal to MB-NF including the line MB (reference plane).
- 3. The phone was hen rotated around the vertical centerline until the phone (horizontal line) was symmetrical was respect to the line NF.
 - 5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the phone contact with the ear, the handset was rotated about the line NF until any point on the handset made contact with a phantom point below the ear (cheek). See Figure 9.2)




Figure 9.2 Side view w/ relevant markings

9. TEST CONFIGURATION POSITIONS(Continued)

Positioning for Ear / 15 ° Tilt

With the test device aligned in the "Cheek/Touch Position":

- 1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15degree.
- 2. The phone was then rotated around the horizontal line by 15 degree.
- 3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the phone touches the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. The tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head (see Figure 9.3).



Figure 9.3 Front, Side and Top View of Ear/15° Tilt Position




Figure 9.4 Side view w/ relevant markings

9. TEST CONFIGURATION POSITIONS

Body Holster / Belt Clip Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to

the device and positioned against a flat phantom in a normal use configuration (see Figure 9.5). A device with a headset output is tested with a headset connected to the device. Body dielectric parameters are used.

Accessories for Body- worn operation configurations are divided into two categories: those that do not contain and those that do contain metallic components metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are supplied with the device, the device is tested with each accessory that contains a unique metallic component. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.





Figure 9.5 Body Belt Clip & Holster Configurations

Body-worn accessories may not always be supplied or available as options for some Devices intended to be authorized for body-worn use. In this case, a test configuration where a separation distance between the back of the device and the flat phantom is used.All test position spacings are documented.

Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessory(ies), including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

In all cases SAR measurements are performed to investigate the worst-case positioning. Worst-case positioning is then documented and used to perform Body SAR testing. In order for users to be aware of the body-worn operating requirements for meeting RF exposure compliance, operating instructions and cautions statements are included in the user's manual.

10. ANSI / IEEE C95.1-1992 RF EXPOSURE LIMITS

Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table 10.1.

SAR Human Exposure Specified in ANSI/IEEE C95.1-1992

	HUMAN EXPOSURE LIMITS	
	General Public Exposure (W/kg) or (mW/g)	Occupational Exposure (W/kg) or (mW/g)
Whole-Body average SAR (W/kg)	0.08	0.40
Localized SAR (head and trunk) (W/kg)	1.60	8.00
Localized SAR (limbs) (W/kg)	4.00	20.0

11. IEEE P1528 - MEASUREMENT UNCERTAINTIES

	Uncertaint	Probability		(Ci)	Standard	vi 2 or
Error Description	value ±%	Distribution	Divisor	1g	(1g)	Veff
Measurement System						
Probe calibration	± 4.8	Normal	1	1	± 4.8 %	∞
Axial isotropy	± 4.7	Rectangular	√3	0.7	± 1.9 %	∞
Hemispherical isotropy	± 9.6	Rectangular	√3	0.7	± 3.9 %	∞
Boundary Effects	± 1.0	Rectangular	√3	1	± 0.6 %	∞
Probe Linearity	± 4.7	Rectangular	√3	1	± 2.7 %	∞
Detection limits	± 1.0	Rectangular	√3	1	± 0.6 %	∞
Readout Electronics	± 1.0	Normal	1	1	± 1.0 %	∞
Response time	± 0.8	Rectangular	√3	1	± 0.5 %	∞
Integration time	± 2.6	Rectangular	√3	1	± 1.5 %	∞
RF Ambient Conditions	± 3.0	Rectangular	√3	1	± 1.7 %	∞
Probe Positioner	± 0.4	Rectangular	√3	1	± 0.2 %	∞
Probe Positioning	± 2.9	Rectangular	√3	1	± 1.7 %	∞
Algorithms for Max. SAR Eval.	± 1.0	Rectangular	√3	1	± 0.6 %	∞
Test Sample Related						
Device Positioning	± 2.9	Normal	1	1	± 2.9 %	145
Device Holder	± 3.6	Normal	1	1	± 3.6 %	5
Power Drift	± 5.0	Rectangular	√3	1	± 2.9 %	∞
Physical Parameters						
Phantom Shell	± 4.0	Rectangular	√3	1	± 2.3 %	∞
Liquid conductivity (Target)	± 5.0	Rectangular	√3	0.64	± 1.8 %	∞
Liquid conductivity (Meas.)	± 2.5	Normal	1	0.64	± 1.6 %	∞
Liquid permittivity (Target)	± 5.0	Rectangular	√3	0.6	± 1.7 %	∞
Liquid permittivity (Meas.)	± 2.5	Normal	1	0.6	± 1.5 %	∞
Combined Standard Uncertainty					± 10.3 %	330
Expanded Uncertainty (k=2)					± 20.6 %	

The above measurement uncertainties are according to IEEE P1528 (2003)

12. SYSTEM VERIFICATION

Tissue Verification

Table 12.1 Simulated Tissue Verification [5]

	MEASURED TISSUE PARAMETERS								
Data(a)	Target Freezischer	Dielectric	constant: ε	Conductivity: σ					
Date(s)	Target Frequency	Target	Measured	Target	Measured				
Apr. 21, 2009	835 MHz Brain	41.5	41.1	0.90	0.922				
Apr. 21, 2009	835 MHz Muscle	55.2	53.2	0.97	0.993				
Apr. 07, 2009	1900 MHz Brain	40.0	39.1	1.40	1.440				
Apr. 07, 2009	1900 MHz Muscle	53.3	52.7	1.52	1.545				
May. 20, 2009	835 MHz Brain	41.5	41.3	0.90	0.930				
May. 20, 2009	835 MHz Muscle	55.2	53.9	0.97	1.004				
May. 20, 2009	1900 MHz Brain	40.0	39.2	1.40	1.450				
May. 20, 2009	1900 MHz Muscle	53.3	52.8	1.52	1.583				

Test System Validation

Prior to assessment, the system is verified to the \pm 10 % of the specifications at 835 MHz and 1900 MHz by using the system validation kit(s). (Graphic Plots Attached)

Table 12.2 System Validation [5]

SYSTEM DIPOLE VALIDATION TARGET & MEASURED									
	(835 MHz / 1900 MHz values are normalized to a forward power of 1/4 W)								
Date(s)	Contain Validation Kita	Target Frequency	Targeted SAR _{1g}	Measured SAR_{1g}	Deviation				
Date(s)	System Validation Kit:	rarget rrequericy	(mW/g)	(mW/g)	(%)				
Apr. 21, 2009	D-835V2, S/N: 464	835 MHz Brain	2.375	2.44	2.74				
Apr. 07, 2009	D-1900V2, S/N: 5d029	1900 MHz Brain	9.925	10.1	1.76				
May. 20, 2009	D-835V2, S/N: 464	835 MHz Brain	2.375	2.35	-1.05				
May. 20, 2009	D-1900V2, S/N: 5d029	1900 MHz Brain	9.925	10.1	1.76				






Figure 12.1 Dipole Validation Test Setup

13. MULTIPLE TRANSMITTERS SAR CONSIDERATIONS

13.1 Introduction


The following procedures adopted from "FCC SAR Evaluation Considerations for Handsets with Multiple Transmitters" (v01r03 #648474) on May 2008 are applicable to handsets with built-in unlicensed transmitters such as 802.11 a/b/g and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

13.2 Output Power Thresholds for Unlicensed Transmitters

	2.45	5.15-5.35	5.47-5.85	GHz			
P Ref	12	5	5	mW			
Device output power should be rounded to the nearest mW to compare with values specified in this table							

13.3 Multiple Antenna Transmission Information for DUO2100

13.3.1 The closest separation distance between GSM and Bluetooth antennas:



Note: This device has 2 independent GSM modules and antennas and a Bluetooth module and antenna.

13.3.2 Bluetooth out power

Frequency		Power(dBm)	Power(mW)	
	2402MHz	-4.87	0.326	
Bluetooth	2441MHz	-4.86	0.327	
	2480MHz	-4.86	0.327	

Note 1: Unlicensed transmitter's stand alone SAR is not required when following 2 conditions

- Bluetooth Output power \leq P_{Ref}, antenna distance from other antennas > 2.5cm
- Bluetooth Output power \leq P_{Ref}, antenna distance from other antennas < 2.5cm, each with either output power \leq P_{Ref} or 1-g SAR < 1.2 W/kg

Therefore BT stand alone SAR is not performed.

Note 2: SAR For Simultaneous transmission

- When (GSM1_{sar} +GSM2_{sar}) ≥ 1.6 W/kg, then simultaneous transmission is performed.
- -When (GSM1_{sar} OR GSM2_{sar})+BT_{sar} \leq 1.6 W/kg, then simultaneous transmission is not performed. (The BT output power of this device is too low (0.327 mW), so the BT SAR is assumed as zero)

13.4 Summary of SAR Evaluation Requirements for Cell phones with Multiple Transmitters

	Individual Transmitter	Simultaneous Transmission
Licensed Transmitters	Routine evaluation required	SAR not required: <u>Unlicensed only</u> o when stand-alone 1-g SAR is not
Unlicensed Transmitters	When there is no simultaneous transmission – o output < 60/f: SAR not required o output ≥ 60/f: stand-alone SAR required When there is simultaneous transmission – Stand-alone SAR not required when O output ≤ 2.P _{Ref} and antenna is > 5.0 cm from other antennas o output ≤ P _{Ref} and antenna is > 2.5 cm from other antennas, each either output power output ≤ P _{Ref} or 1-g SAR < 1.2 W/Kg Otherwise stand-alone SAR is required o test SAR on highest output channel for each wireless mode and exposure condition o if SAR for highest output channel is > 50% of SAR limit, evaluate all channels according to normal procedures	required and antenna is > 5 cm from other antennas Licensed & Unlicensed o when the sum of the 1-g SAR is <1.6 W/kg for all simultaneous transmitting antennas o when SAR to antenna separation ratio of simultaneous transmitting antenna pair is < 0.3 SAR required: Licensed & Unlicensed antenna pairs with SAR to antenna separation ratio ≥ 0.3; test is only required for the configuration that results in the highest SAR in standalone configuration for each wireless mode and exposure condition Note: simultaneous transmission exposure conditions for head and body can be different for different style phones; therefore, different test requirements may apply

14. SAR TEST DATA SUMMARY

See Measurement Result Data Pages

Procedures Used To Establish Test Signal


The handset was placed into simulated call mode (GSM850, PCS1900 GSM) using manufacturers test codes. Such test signals offer a consistent means for testing SAR and are recommended for evaluating SAR [4]. When test modes are not available or inappropriate for testing a handset, the actual transmission is activated through a base station simulator or similar equipment. See data pages for actual procedure used in measurement.

Device Test Conditions

The handset is battery operated. Each SAR measurement was taken with a fully charged battery. In order to verify that the device was tested at full power, conducted output power measurements were performed before and after each SAR measurement to confirm the output power. If a conducted power deviation of more than 5% occurred, the test was repeated.

EUT Handset Reference Points

Figure 14.1 handset Reference Points



15.1 ME	15.1 MEASUREMENT RESULTS (GSM850 Head SAR)									
FREQU	FREQUENCY		End Power	Battery	Device Test	Antenna	SAR			
MHz	Ch	Power (dBm)	(dBm)	Туре	Position	Position	(W/kg)			
836.6	190	31.84	31.83	Standard	Right Cheek/Touch	Internal	0.127			
836.6	190	31.84	31.67	Standard	Right Ear/15° Tilt	Internal	0.056			
824.2	128	31.63	31.60	Standard	Left Cheek/Touch	Internal	0.167			
836.6	190	31.84	31.84	Standard	Left Cheek/Touch	Internal	0.172			
848.8	251	31.64	31.64	Standard	Left Cheek/Touch	Internal	0.240			
836.6	190	31.84	31.83	Standard	Left Ear/15° Tilt	Internal	0.058			
	A Un	Healer He	(mW/g)							

- 1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
- 2. All modes of operation were investigated, and worst-case results are reported.
- 3. Prior to testing the conducted output power was measured.
- 4. The EUT is tested 2nd hot-spot peak, if it is less than 2dB below the highest peak.
- 5. Battery is fully charged for all readings.
- 6.Test Signal Call Mode

 Continuous Tx On

 Manu.Test Codes

 BaseStation Simulator
- 7. Tissue parameters and temperatures are listed on the SAR plots.
- 8. Liquid tissue depth is 15.0 cm.±0.1
- 9. Justification for reduced test configurations: Per FCC/OET Bulletin 65 Supplement C (July,2001), if the SAR measured at the middle channel for each test configuration (left, right, cheek/touch, tilt/ear, extended and retracted) is least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).

Mixture Type: 850 MHz Head

* Black Side (GSM2)

15.2 MEASUREMENT RESULTS (GSM850 Head SAR)									
FREQU	IENCY	Begin Power	End Power	Battery	Device Test	Antenna	SAR		
MHz	Ch	(dBm)	(dBm) Type		Position	(W/kg)			
836.6	190	31.86	31.86	Standard	Right Cheek/Touch	Internal	0.106		
836.6	190	31.86	31.85	Standard	Right Ear/15° Tilt	Internal	0.048		
836.6	190	31.86	31.85	Standard	Left Cheek/Touch	Internal	0.127		
836.6	190	31.86	31.85	Standard	Left Ear/15° Tilt	Internal	0.046		
ANSI / IEEE C95.1 1992 - SAFETY LIMIT						He	ad		

ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population

Head 1.6 W/kg (mW/g) averaged over 1 gram

- 1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
- 2. All modes of operation were investigated, and worst-case results are reported.
- 3. Prior to testing the conducted output power was measured.
- 4. The EUT is tested 2nd hot-spot peak, if it is less than 2dB below the highest peak.
- 5. Battery is fully charged for all readings.
- 6.Test Signal Call Mode

 Continuous Tx On
 Manu.Test Codes

 BaseStation Simulator
- 7. Tissue parameters and temperatures are listed on the SAR plots.
- 8. Liquid tissue depth is 15.0 cm.± 0.1
- 9. Justification for reduced test configurations: Per FCC/OET Bulletin 65 Supplement C (July,2001), if the SAR measured at the middle channel for each test configuration (left, right, cheek/touch, tilt/ear, extended and retracted) is least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).

Mixture Type: 850 MHz body

** Facing Phantom: Black Side(GSM2) / TX On: Silver Side(GSM1)

15.3 MEASUREMENT RESULTS (GSM850 GPRS Body SAR)								
FREQUENCY		Begin Power	End Power	Battery	Device Test	Antenna	SAR	
MHz	Ch	(dBm)	(dBm)	Туре	Position	Position	(W/kg)	
824.2	128	31.63	31.63	Standard	1.5cm [w/o Holster]	Internal	0.158	
836.6	190	31.84	31.82	Standard	1.5cm [w/o Holster]	Internal	0.141	
848.8	251	31.64	31.60	Standard	1.5cm [w/o Holster]	Internal	0.136	
824.2	128	31.63	31.82	Standard	1.5cm [w/o Holster]	Internal	0.072	
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population						1.6 W/kg	dy J (mW/g) ver 1 gram	

- 1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
- 2. All modes of operation were investigated, and worst-case results are reported.
- 3. Prior to testing the conducted output power was measured.
- 4. The EUT is tested 2nd hot-spot peak, if it is less than 2dB below the highest peak.
- 5. Battery is fully charged for all readings.
- 6.Test Signal Call Mode

 Continuous Tx On
 Manu.Test Codes

 BaseStation Simulator
- 7. Tissue parameters and temperatures are listed on the SAR plots.
- 8. Liquid tissue depth is 15.0 cm.±0.1
- 9. Basically the Body SAR Tests were performed with GPRS Class10 (2TX, 1RX)
- 10. The body SAR test was repeated with GSM mode on the worst case channel of GPRS Class10

FREQU	UENCY Begin	End Power	Battery	Device Test	Antenna	SAR		
MHz	Ch	Power (dBm)	(dBm)	Туре	Type Position		(W/kg)	
824.2	128	31.63	31.62	Standard	1.5cm [w/o Holster]	Internal	0.237	
836.6	190	31.84	31.84	Standard	1.5cm [w/o Holster]	Internal	0.215	
848.8	251	31.64	31.64	Standard	1.5cm [w/o Holster]	Internal	0.190	
824.2	128	31.63	31.62	Standard	1.5cm [w/o Holster]	Internal	0.086	
	U	Bo 1.6 W/kg averaged o	-					

- 1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
- 2. All modes of operation were investigated, and worst-case results are reported.
- 3. Prior to testing the conducted output power was measured.
- 4. The EUT is tested 2nd hot-spot peak, if it is less than 2dB below the highest peak.
- 5. Battery is fully charged for all readings.
- 6.Test Signal Call Mode

 Continuous Tx On

 Manu.Test Codes

 BaseStation Simulator
- 7. Tissue parameters and temperatures are listed on the SAR plots.
- 8. Liquid tissue depth is 15.0 cm.±0.1
- 9. Basically the Body SAR Tests were performed with GPRS Class10 (2TX, 1RX)
- 10. The body SAR test was repeated with GSM mode on the worst case channel of GPRS Class10

averaged over 1 gram

15. SAR TEST DATA SUMMARY (Continue)

15.5 MEASUREMENT RESULTS (GSM850 GPRS Body SAR)									
FREQU	IENCY	Begin Power	End Battery	Device Test	Antenna	SAR			
MHz	Ch	(dBm)	Power (dBm)	Туре	Position	Position	(W/kg)		
824.2	128	31.63	31.63	Standard	1.5cm [w/o Holster]	Internal	0.137		
836.6	190	31.86	31.85	Standard	1.5cm [w/o Holster]	Internal	0.122		
848.8	251	31.79	31.77	Standard	1.5cm [w/o Holster]	Internal	0.189		
848.8	251	31.79	31.77	Standard	1.5cm [w/o Holster]	Internal	0.062		
	,	Bo 1.6 W/kg	dy ı (mW/g)						

NOTE:

- 1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
- 2. All modes of operation were investigated, and worst-case results are reported.

Uncontrolled Exposure/General Population

- 3. Prior to testing the conducted output power was measured.
- 4. The EUT is tested 2nd hot-spot peak, if it is less than 2dB below the highest peak.
- 5. Battery is fully charged for all readings.
- 6.Test Signal Call Mode

 Continuous Tx On

 Manu.Test Codes

 BaseStation Simulator
- 7. Tissue parameters and temperatures are listed on the SAR plots.
- 8. Liquid tissue depth is 15.0 cm.±0.1
- 9. Basically the Body SAR Tests were performed with GPRS Class10 (2TX, 1RX)
- 10. The body SAR test was repeated with GSM mode on the worst case channel of GPRS Class10

15.6 MEASUREMENT RESULTS (GSM850 GPRS Body SAR)								
FREQL	JENCY	Begin Power	End Power	Battery Type	Device Test	Antenna	SAR	
MHz	Ch	(dBm)	(dBm)		Position	Position	(W/kg)	
824.2	128	31.63	31.63	Standard	1.5cm [w/o Holster]	Internal	0.155	
836.6	190	31.86	31.86	Standard	1.5cm [w/o Holster]	Internal	0.172	
848.8	251	31.79	31.78	Standard	1.5cm [w/o Holster]	Internal	0.255	
848.8	251	31.79	31.79	Standard	1.5cm [w/o Holster]	Internal	0.093	
	U	1.6 W/kg	dy (mW/g) ver 1 gram					

- 1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
- 2. All modes of operation were investigated, and worst-case results are reported.
- 3. Prior to testing the conducted output power was measured.
- 4. The EUT is tested 2nd hot-spot peak, if it is less than 2dB below the highest peak.
- 5. Battery is fully charged for all readings.
- 6.Test Signal Call Mode

 Continuous Tx On

 Manu.Test Codes

 BaseStation Simulator
- 7. Tissue parameters and temperatures are listed on the SAR plots.
- 8. Liquid tissue depth is 15.0 cm.±0.1
- 9. Basically the Body SAR Tests were performed with GPRS Class10 (2TX, 1RX)
- 10. The body SAR test was repeated with GSM mode on the worst case channel of GPRS Class10

Mixture Type: 1900 MHz Head

* Silver Side (GSM1)

15.7 MEAS	15.7 MEASUREMENT RESULTS (PCS1900 Head SAR)							
FREQU	FREQUENCY		End Power	Battery	Device Test	Antenna	SAR	
MHz	Ch	Power (dBm)	(dBm)	Battery	Position	Position	(W/kg)	
1880.0	661	28.38	28.37	Standard	Right Cheek/Touch	Internal	0.681	
1880.0	661	28.38	28.23	Standard	Right Ear/15° Tilt	Internal	0.078	
1850.2	512	28.51	28.50	Standard	Left Cheek/Touch	Internal	0.604	
1880.0	661	28.38	28.37	Standard	Left Cheek/Touch	Internal	0.889	
1909.8	810	28.46	28.2	Standard	Left Cheek/Touch	Internal	0.784	
1880.0	661	28.38	28.38	Standard	Left Ear/15° Tilt	Internal	0.090	
1880.0	661	28.38	28.34	Standard	Loft Chook/Touch	Internal	*1.190	
+1909.8	+810	28.38	28.34	Standard	Left Cheek/Touch	Internal	*1.190	
1880.0	661	20 20	20.20	Standard	Loft Chook /Touch	Internal	*1.430	
+1880.0	+1880.0 +661 28.38 28.38 Standard Left Cheek/Touch						*1.430	
	ANS	1.6 W/kg	ead g (mW/g) over 1 gram					

NOTE:

- 1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
- 2. All modes of operation were investigated, and worst-case results are reported.
- 3. Prior to testing the conducted output power was measured.
- 4. The EUT is tested 2nd hot-spot peak, if it is less than 2dB below the highest peak.
- 5. Battery is fully charged for all readings.
- 6.Test Signal Call Mode

 Continuous Tx On Manu.Test Codes BaseStation Simulator
- 7. Tissue parameters and temperatures are listed on the SAR plots.
- 8. Liquid tissue depth is 15.0 cm.±0.1
- 9. Justification for reduced test configurations: Per FCC/OET Bulletin 65 Supplement C (July,2001), if the SAR measured at the middle channel for each test configuration (left, right, cheek/touch, tilt/ear, extended and retracted) is least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).
- 10. * Simultaneous SARs were repeated with each worst case channel of silver and black side and with same channel which is worst case channel of the silver side.

(Silver Side CH:661 + Black Side CH:810) and (Silver Side CH:661 + Black Side CH:661)

Mixture Type: 1900 MHz Head

** Black Side (GSM2)

15.8 MEAS	15.8 MEASUREMENT RESULTS (PCS1900 Head SAR)							
FREQUI	ENCY	Begin Power	End Power	Battery	Device Test	Antenna	SAR	
MHz	Ch	(dBm)	(dBm)	Battery	Position	Position	(W/kg)	
1880.0	661	28.40	28.40	Standard	Right Cheek/Touch	Internal	0.650	
1880.0	661	28.40	28.40	Standard	Right Ear/15° Tilt	Internal	0.070	
1850.2	512	28.65	28.64	Standard	Left Cheek/Touch	Internal	0.631	
1880.0	661	28.40	28.40	Standard	Left Cheek/Touch	Internal	0.924	
1909.8	810	28.43	28.43	Standard	Left Cheek/Touch	Internal	0.989	
1880.0	661	28.40	28.40	Standard	Left Ear/15° Tilt	Internal	0.074	
1909.8	810	28.43	28.42	Standard	Left Cheek/Touch	Internal	*1.030	
+1880.0	+661	20.43	20.42	Standard	Left Cheek/Touch	Internal		
1909.8	810	28.43	28.42	Standard	Left Cheek/Touch	Internal	*1.040	
+1909.8	+810	26.43	20.42	Stallualu	Left Cheek/Touch	Tilleriiai	*1.040	
	ANS Unco	1.6 W/kg	ead g (mW/g) over 1 gram					

NOTE:

- 1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
- 2. All modes of operation were investigated, and worst-case results are reported.
- 3. Prior to testing the conducted output power was measured.
- 4. The EUT is tested 2nd hot-spot peak, if it is less than 2dB below the highest peak.
- 5. Battery is fully charged for all readings.
- 6.Test Signal Call Mode

 Continuous Tx On Manu.Test Codes BaseStation Simulator
- 7. Tissue parameters and temperatures are listed on the SAR plots.
- 8. Liquid tissue depth is 15.0 cm.±0.1
- 9. Justification for reduced test configurations: Per FCC/OET Bulletin 65 Supplement C (July,2001), if the SAR measured at the middle channel for each test configuration (left, right, cheek/touch, tilt/ear, extended and retracted) is least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).
- 1010. * Simultaneous SARs were repeated with each worst case channel of silver and black side and with same channel which is worst case channel of the black side.

(Black Side CH:810 + Silver Side CH:661) and (Black Side CH:810 + Silver Side CH:810)

Mixture Type: 1900 MHz body
* Facing Phantom: Black Side(GSM2) / TX On: Silver Side(GSM1)

15.9 MEASUREMENT RESULTS (PCS1900 GPRS Body SAR)									
FREQU	FREQUENCY		End Power		Device Test	Antenna	SAR		
MHz	Ch	Power (dBm)	(dBm)	battery	Position Position		(W/kg)		
1850.2	512	28.51	28.40	Standard	1.5cm [w/o Holster]	Internal	0.287		
1880.0	661	28.38	28.33	Standard	1.5cm [w/o Holster]	Internal	0.367		
1909.8	810	28.46	28.45	Standard	1.5cm [w/o Holster]	Internal	0.274		
1880.0	661	28.38	28.38	Standard	1.5cm [w/o Holster]	Internal	0.195		

ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population

Body 1.6 W/kg (mW/g) averaged over 1 gram

- 1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
- 2. All modes of operation were investigated, and worst-case results are reported.
- 3. Prior to testing the conducted output power was measured.
- 4. The EUT is tested 2nd hot-spot peak, if it is less than 2dB below the highest peak.
- 5. Battery is fully charged for all readings.
- 6.Test Signal Call Mode

 Continuous Tx On

 Manu.Test Codes

 BaseStation Simulator
- 7. Tissue parameters and temperatures are listed on the SAR plots.
- 8. Liquid tissue depth is 15.0 cm.±0.1
- 9. Basically the Body SAR Tests were performed with GPRS Class10 (2TX, 1RX)
- 10. The body SAR test was repeated with GSM mode on the worst case channel of GPRS Class10

Mixture Type: 1900 MHz body
** Facing Phantom: Silver Side(GSM1) / TX On: Silver Side(GSM1)

15.10 MEASUREMENT RESULTS (PCS1900 GPRS Body SAR)										
FREQUENCY		Begin Power	End Power	Pattoni	Device Test	Antenna	SAR			
MHz	Ch	(dBm)	(dBm)	Battery Position					Position	(W/kg)
1850.2	512	28.51	28.30	Standard	1.5cm [w/o Holster]	Internal	0.352			
1880.0	661	28.38	28.37	Standard	1.5cm [w/o Holster]	Internal	0.404			
1909.8	810	28.46	28.44	Standard	1.5cm [w/o Holster]	Internal	0.356			
1880.0	661	28.38	28.31	Standard	1.5cm [w/o Holster]	Internal	0.202			
	ΔNS	Po	dv							

ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population

Body 1.6 W/kg (mW/g) averaged over 1 gram

- 1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
- 2. All modes of operation were investigated, and worst-case results are reported.
- 3. Prior to testing the conducted output power was measured.
- 4. The EUT is tested 2nd hot-spot peak, if it is less than 2dB below the highest peak.
- 5. Battery is fully charged for all readings.
- 6.Test Signal Call Mode

 Continuous Tx On

 Manu.Test Codes

 BaseStation Simulator
- 7. Tissue parameters and temperatures are listed on the SAR plots.
- 8. Liquid tissue depth is 15.0 cm.±0.1
- 9. Basically the Body SAR Tests were performed with GPRS Class10 (2TX, 1RX)
- 10. The body SAR test was repeated with GSM mode on the worst case channel of GPRS Class10

15. SAR TEST DATA SUMMARY

15.11 ME	15.11 MEASUREMENT RESULTS (PCS1900 GPRS Body SAR)								
FREQUENCY		Begin Power	End Power	Battery	Device Test	Antenna	SAR		
MHz	Ch	(dBm)	(dBm)	battery	Position		(W/kg)		
1850.2	512	28.65	28.56	Standard	1.5cm [w/o Holster]	Internal	0.247		
1880.0	661	28.40	28.22	Standard	1.5cm [w/o Holster]	Internal	0.325		
1909.8	810	28.43	28.42	Standard	1.5cm [w/o Holster]	Internal	0.334		
1909.8	810	28.43	28.43	Standard	1.5cm [w/o Holster]	Internal	0.177		
	ANS		dy (mW/a)						

ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population

Body 1.6 W/kg (mW/g) averaged over 1 gram

- 1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
- 2. All modes of operation were investigated, and worst-case results are reported.
- 3. Prior to testing the conducted output power was measured.
- 4. The EUT is tested 2nd hot-spot peak, if it is less than 2dB below the highest peak.
- 5. Battery is fully charged for all readings.
- 6.Test Signal Call Mode

 Continuous Tx On

 Manu.Test Codes

 BaseStation Simulator
- 7. Tissue parameters and temperatures are listed on the SAR plots.
- 8. Liquid tissue depth is 15.0 cm. ±0.1
- 9. Basically the Body SAR Tests were performed with GPRS Class10 (2TX, 1RX)
- 10. The body SAR test was repeated with GSM mode on the worst case channel of GPRS Class10

15. SAR TEST DATA SUMMARY

Mixture Type: 1900 MHz body

** Facing Phantom: Black Side(GSM2) / TX On: Black Side(GSM2)

15.12 MEASUREMENT RESULTS (PCS1900 GPRS Body SAR)										
FREQU	FREQUENCY	Begin Power	End Power	Datte	Device Test	Antenna	SAR			
MHz	Ch	(dBm)	(dBm)	Battery	Position	Position	(W/kg)			
1850.2	512	28.65	28.45	Standard	1.5cm [w/o Holster]	Internal	0.256			
1880.0	661	28.40	28.10	Standard	1.5cm [w/o Holster]	Internal	0.344			
1909.8	810	28.43	28.39	Standard	1.5cm [w/o Holster]	Internal	0.363			
1909.8	810	28.43	28.38	Standard	1.5cm [w/o Holster]	Internal	0.181			

ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population

Body 1.6 W/kg (mW/g) averaged over 1 gram

- 1. The test data reported are the worst-case SAR value with the antenna-head position set in a typical configuration. Test procedures used are according to FCC/OET Bulletin 65, Supp.C [July 2001].
- 2. All modes of operation were investigated, and worst-case results are reported.
- 3. Prior to testing the conducted output power was measured.
- 4. The EUT is tested 2nd hot-spot peak, if it is less than 2dB below the highest peak.
- 5. Battery is fully charged for all readings.
- 6.Test Signal Call Mode

 Continuous Tx On

 Manu.Test Codes

 BaseStation Simulator
- 7. Tissue parameters and temperatures are listed on the SAR plots.
- 8. Liquid tissue depth is 15.0 cm.±0.1
- 9. Basically the Body SAR Tests were performed with GPRS Class10 (2TX, 1RX)
- 10. The body SAR test was repeated with GSM mode on the worst case channel of GPRS Class10

16. SAR TEST EQUIPMENT

Table 16.1 Test Equipment Calibration

EQUIPMENT SPECIFICATIONS								
Туре	Calibration Date	Next	Serial Number					
		Calibration Date						
Robot	N/A	N/A	F02/5Q85A1/A/01					
Robot Controller	N/A	N/A	F02/5Q85A1/C/01					
Joystick	N/A	N/A	D221340031					
Hicron Computer 1.1GHz Pentium Celeron ,Window 2000	N/A	N/A	N/A					
Data Acquisition Electronics	November 12, 2008	November 12, 2009	519					
Dosimetric E-Field Probe	January 14, 2009	January 14, 2010	3643					
Dummy Probe	N/A	N/A	N/A					
Sam Phantom	N/A	N/A	N/A					
Probe Alignment Unit LB	N/A	N/A	321					
SPEAG Validation Dipole D835 MHz	January 28, 2008	January 28, 2010	464					
SPEAG Validation Dipole D1900 MHz	March 17, 2009	March 17, 2011	5d029					
Head/Body Equivalent Matter(835 MHz)	January 2009	January 2010	N/A					
Head/Body Equivalent Matter(1900 MHz)	January 2009	January 2010	N/A					
HP EPM-442A Power Meter	March 13, 2009	March 13, 2010	GB37170267					
HP E4421A Signal Generator	July 09, 2008	July 09, 2009	US37230529					
Attenuator (10 dB)	January 19, 2009	January 19, 2010	BP4387					
Attenuator (3 dB)	July 15, 2008	July 15,2009	MY39260699					
Low pass filter (1.5 GHz)	February 03, 2009	February 03, 2010	N/A					
Low pass filter (3.0 GHz)	October 01, 2008	October 01, 2009	N/A					
Dual Directional Coupler	February 03, 2009	February 03, 2010	50228					
Amplifier	February 02, 2009	February 02, 2010	1020 D/C 0221					
Network Analyzer	March 13, 2009	March 13, 2010	8753D					
HP85070D Dielectric Probe Kit	N/A	N/A	LISO1440118					
SEMITEC Engineering	N/A	N/A	Shield Room					

NOTE:

The E-field probe was calibrated by SPEAG, by temperature measurement procedure. Dipole Validation measurement is performed by Digital EMC. before each test. The brain simulating material is calibrated by Digital EMC using the dielectric probe system and network analyzer to determine the conductivity and permittivity (dielectric constant) of the brain-equivalent material.

17. CONCLUSION

Measurement Conclusion

The SAR measurement indicates that the EUT complies with the RF radiation exposure limits of the FCC. These measurements are taken to simulate the RF effects exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The tested device complies with the requirements in respect to all parameters subject to the test. The test results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease).

Because innumerable factors may interact to determine the specific biological outcome of an exposure to electromagnetic fields, any protection guide shall consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables.

18. REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1 1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 300kHz to 100GHz, New York: IEEE, April 2006.
- [3] ANSI/IEEE C95.3 2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields RF and Microwave, New York: IEEE, December 2002.
- [4] Federal Communications Commission, OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01), Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields, July 2001.
- [5] IEEE Standards Coordinating Committee 34 IEEE Std. 1528-2003, Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices: Experimental Techniques.
- [6] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for Radio Frequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [7] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [8] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 120-124.
- [9] K. Polovċ,T.Schmid,and N.Kuster ,E-field Probe with improved isotropy in brain simulating liquids. Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [10] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [11] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Head Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [12] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [13] G. Hartsgrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [14] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [15] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [16] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recepies in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [17] Federal Communications Commission, OET Bulletin 65, Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields. Supplement C, Dec. 1997.
- [18] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.
- [19] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [20] Prof. Dr. Niels Kuster ,ETH,EidgenŐssische Technische Technische Hoschschule Zűrich,Dosimetric Evaluation of the Cellular Phone.
- [21] FCC SAR Measurement Procedures for 3G Devices v2.0, October 2007
- [22] FCC SAR Considerations for handsets with Multiple Transmitters and Antennas v01r03 #648474, May 2008