

FCC RF Test Report

Report No.: FG3O2201

2353

APPLICANT : Doro AB

EQUIPMENT : GSM Mobile Telephone

BRAND NAME : doro

: Doro PhoneEasy 612i MODEL NAME : Doro PhoneEasy 612i MARKETING NAME STANDARD : FCC 47 CFR Part 2, 24(E)

CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Oct. 22, 2013 and testing was completed on Oct. 30, 2013. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI / TIA / EIA-603-C-2004 and shown to be compliant with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager

SPORTON INTERNATIONAL (SHENZHEN) INC.

No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P.R.C.

SPORTON INTERNATIONAL (SHENZHEN) INC.

Page Number : 1 of 40 TEL: 86-755-3320-2398 Report Issued Date: Nov. 11, 2013 Report Version : Rev. 01



TABLE OF CONTENTS

RE	VISIO	N HISTORY	3
SI I	МΜΔΕ	RY OF TEST RESULT	1
30	IAIIAI	VI OI ILSI KLOOLI	
1	GENE	ERAL DESCRIPTION	5
	1.1	Applicant	5
	1.2	Manufacturer	5
	1.3	Feature of Equipment Under Test	5
	1.4	Product Specification of Equipment Under Test	6
	1.5	Modification of EUT	
	1.6	Maximum EIRP Power, Frequency Tolerance, and Emission Designator	
	1.7	Testing Site	
	1.8	Applied Standards	7
2	TEST	CONFIGURATION OF EQUIPMENT UNDER TEST	8
	2.1	Test Mode	8
	2.2	Connection Diagram of Test System	9
	2.3	Support Unit used in test configuration and system	
	2.4	Measurement Results Explanation Example	
3	TEST	「RESULT	11
	3.1	Conducted Output Power Measurement	11
	3.2	Peak-to-Average Ratio	13
	3.3	Effective Isotropic Radiated Power Measurement	17
	3.4	99% Occupied Bandwidth and 26dB Bandwidth Measurement	19
	3.5	Band Edge Measurement	
	3.6	Conducted Spurious Emission Measurement	
	3.7	Field Strength of Spurious Radiation Measurement	
	3.8	Frequency Stability Measurement	35
4	LIST	OF MEASURING EQUIPMENT	39
5	UNCE	ERTAINTY OF EVALUATION	40
ΑP	PEND	IX A. PHOTOGRAPHS OF EUT	

APPENDIX B. SETUP PHOTOGRAPHS

TEL: 86-755-3320-2398

Page Number : 2 of 40 Report Issued Date: Nov. 11, 2013 Report Version : Rev. 01



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG3O2201	Rev. 01	Initial issue of report	Nov. 11, 2013



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	N/A	PASS	-
3.2	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.3	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.4	§2.1049 §24.238(b)	Occupied Bandwidth	N/A	PASS	-
3.5	§2.1051 §24.238(a)	Band Edge Measurement	< 43+10log ₁₀ (P[Watts])	PASS	-
3.6	§2.1051 §24.238(a)	Conducted Spurious Emission	< 43+10log ₁₀ (P[Watts])	PASS	-
3.7	§2.1053 §24.238(a)	Field Strength of Spurious Radiation	< 43+10log ₁₀ (P[Watts])	PASS	Under limit 34.44 dB at 5640.000 MHz
3.8	§2.1055 §24.235	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-

TEL: 86-755-3320-2398

Page Number : 4 of 40
Report Issued Date : Nov. 11, 2013

Report Version : Rev. 01



1 General Description

1.1 Applicant

Doro AB

Magistratsvägen 10 SE-226 43 Lund Sweden

1.2 Manufacturer

CK TELECOM LTD.

Technology Road. High-Tech Development Zone. Heyuan, Guangdong, P.R.China.

1.3 Feature of Equipment Under Test

Product Feature					
Equipment	GSM Mobile Telephone				
Brand Name	doro				
Model Name	Doro PhoneEasy 612i				
Marketing Name	Doro PhoneEasy 612i				
IMEI Number 359326050001052					
EUT supports Radios application GSM/GPRS/Bluetooth v3.0+EDR					
HW Version	YACHTPLUS-V2.0				
SW Version	YACHTPLUS-S01A_DORO612i_L18EN_200_131011				
EUT Stage	Production Unit				

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

SPORTON INTERNATIONAL (SHENZHEN) INC. TEL: 86-755-3320-2398

Page Number : 5 of 40
Report Issued Date : Nov. 11, 2013
Report Version : Rev. 01

1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard					
Tx Frequency	GSM1900: 1850.2 MHz ~ 1909.8MHz				
Rx Frequency	GSM1900: 1930.2 MHz ~ 1989.8 MHz				
Maximum Output Power to Antenna	GSM1900 : 30.05 dBm				
Antenna Type	Fixed Internal Antenna				
Type of Modulation	GSM: GMSK GPRS: GMSK				

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 24	GSM1900 GSM	GMSK	0.90	0.02 ppm	246KGXW

SPORTON INTERNATIONAL (SHENZHEN) INC. TEL: 86-755-3320-2398

Page Number : 6 of 40
Report Issued Date : Nov. 11, 2013
Report Version : Rev. 01

1.7 Testing Site

Test Site		SPORTON INT	ERNATIONAL (S	HENZHEN) INC.	
Toot	C:4a		the third floor of s	outh, Shahe River	west, Fengzeyuan warehouse,
Test Location	Site	Nanshan Distri	ct, Shenzhen, Gu	angdong, P.R.C.	
Location		TEL: +86-755-	3320-2398		
Toot Site N	la.		Sporton Site No	o.	FCC Registration No.
Test Site N	10.	TH01-SZ	03CH01-SZ	OTA01-SZ	831040

1.8 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC 47 CFR Part 2, 24(E)
- ANSI / TIA / EIA-603-C-2004
- FCC KDB 971168 D01 Power Meas. License Digital Systems v02r01

Remark:

- 1. All test items were verified and recorded according to the standards and without any deviation during the test.
- 2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

TEL: 86-755- 3320-2398

Page Number : 7 of 40
Report Issued Date : Nov. 11, 2013
Report Version : Rev. 01



2 Test Configuration of Equipment Under Test

2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

Frequency range investigated for radiated emission is as follows:

1. 30 MHz to 19000 MHz for GSM1900.

	Test Modes						
Band Radiated TCs Conducted TCs							
GSM 1900	■ GSM Link	■ GSM Link					


Note: The maximum power levels are GSM mode for GMSK link, only these modes were used for all tests.

The conducted power tables are as follows:

Conducted Power (*Unit: dBm)						
Band		GSM1900				
Channel	512 661 810					
Frequency	1850.2	1880.0	1909.8			
GSM	29.77	29.87	<mark>30.05</mark>			
GPRS class 8	29.76	29.86	30.01			
GPRS class 10	28.69	28.82	29.03			
GPRS class 11	26.43	26.56	26.78			
GPRS class 12	25.35	25.50	25.70			



2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	TOPWORD	3303DR	N/A	N/A	N/A

TEL: 86-755- 3320-2398

Page Number : 9 of 40
Report Issued Date : Nov. 11, 2013
Report Version : Rev. 01

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Report No.: FG3O2201

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 7.5 dB and 10dB attenuator.

Example:

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).
=
$$7.5 + 10 = 17.5$$
 (dB)

Page Number : 10 of 40 TEL: 86-755-3320-2398 Report Issued Date: Nov. 11, 2013 Report Version : Rev. 01



3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

- 1. The transmitter output port was connected to base station.
- 2. Set EUT at maximum power through base station.
- 3. Select lowest, middle, and highest channels for each band and different modulation.
- 4. Measure the maximum burst average power for GSM.

3.1.4 Test Setup





3.1.5 Test Result of Conducted Output Power

PCS Band							
Modes	GSM1900 (GSM)						
Channel	512 661 810 (Low) (Mid) (High)						
Frequency (MHz)	1850.2	1880	1909.8				
Conducted Power (dBm)	29.77	29.87	30.05				
Conducted Power (Watts)	0.95	0.97	1.01				

Note: maximum burst average power for GSM.

TEL: 86-755- 3320-2398 Report Version Report Versio

Page Number : 12 of 40
Report Issued Date : Nov. 11, 2013
Report Version : Rev. 01



3.2 Peak-to-Average Ratio

3.2.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

- 1. The EUT was connected to Spectrum Analyzer and System Simulator via power divider.
- 2. For GSM/GPRS operating modes:
 - a. Set EUT in maximum power output.
 - b. Set the RBW = 1MHz, VBW = 3MHz, Peak detector in spectrum analyzer for first trace.
 - c. Set the RBW = 1MHz, VBW = 3MHz, RMS detector in spectrum analyzer for second trace.
 - d. The wanted burst signal is triggered by spectrum analyzer, and measured respectively the peak level and Mean level without burst-off time, after system simulator synchronized with the spectrum analyzer.
- 3. Record the deviation as Peak to Average Ratio.

3.2.4 Test Setup



SPORTON INTERNATIONAL (SHENZHEN) INC.

Page Number

Report Issued |

Page Number

Page Number : 13 of 40
Report Issued Date : Nov. 11, 2013
Report Version : Rev. 01

3.2.5 Test Result of Peak-to-Average Ratio


PCS Band						
Modes	GSM1900 (GSM)					
Channel	512 (Low)	661 (Mid)	810 (High)			
Frequency (MHz)	1850.2	1880	1909.8			
Peak-to-Average Ratio (dB)	0.27	0.27	0.26			

Page Number : 14 of 40
Report Issued Date : Nov. 11, 2013
Report Version : Rev. 01

3.2.6 Test Result (Plots) of Peak-to-Average Ratio


Band :	GSM 1900	Test Mode :	GSM Link (GMSK)
--------	----------	-------------	-----------------

Peak-to-Average Ratio on Channel 512 (1850.2 MHz)



Date: 30.0CT.2013 06:53:25


Peak-to-Average Ratio on Channel 661 (1880.0 MHz)



Date: 30.0CT.2013 06:52:43

Page Number : 15 of 40
Report Issued Date : Nov. 11, 2013
Report Version : Rev. 01

Peak-to-Average Ratio on Channel 810 (1909.8 MHz)



Report No.: FG3O2201

Date: 30.0CT.2013 06:53:51

Page Number : 16 of 40 TEL: 86-755-3320-2398 Report Issued Date: Nov. 11, 2013 : Rev. 01 Report Version

3.3 Effective Isotropic Radiated Power Measurement

3.3.1 Description of the EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-C-2004, was used for EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02r01. The EIRP of mobile transmitters are limited to 2 Watts.

Report No.: FG3O2201

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

- 1. The EUT was placed on a turntable with 1.5 meter height in a fully anechoic chamber.
- 2. The EUT was set at 3 meters from the receiving antenna, which was mounted on the antenna tower
- GSM operating modes: Set RBW= 1MHz, VBW= 3MHz, RMS detector over burst;
 RMS detector over frame, and use channel power option with bandwidth=5MHz, per KDB 971168 D01.
- 4. The table was rotated 360 degrees to determine the position of the highest radiated power.
- 5. The height of the receiving antenna is adjusted to look for the maximum EIRP.
- 6. Taking the record of maximum EIRP.
- 7. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
- 8. The conducted power at the terminal of the dipole antenna is measured.
- 9. Repeat step 3 to step 5 to get the maximum EIRP of the substitution antenna.
- 10. EIRP = Ps + Et Es + Gs = Ps + Rt Rs + Gs

Ps (dBm): Input power to substitution antenna.

Gs (dBi or dBd): Substitution antenna Gain.

Et = Rt + AF

Es = Rs + AF

AF (dB/m): Receive antenna factor

Rt: The highest received signal in spectrum analyzer for EUT.

Rs: The highest received signal in spectrum analyzer for substitution antenna.


Page Number : 17 of 40

Report Issued Date : Nov. 11, 2013

Report Version : Rev. 01



3.3.4 Test Setup



3.3.5 Test Result of EIRP

GSM1900 (GSM) Radiated Power EIRP								
		Hoi	rizontal Polariza	tion				
Frequency	Rt	Rs	Ps	Gs	EIRP	EIRP		
(MHz)	(dBm)	(dBm)	(dBm)	(dBi)	(dBm)	(W)		
1850.20	-24.84	-51.88	0.00	1.96	29.00	0.79		
1880.00	-25.94	-52.99	0.00	2.00	29.05	0.80		
1909.80	-26.70	-54.28	0.00	1.98	29.56	0.90		
		Ve	ertical Polarizati	on				
Frequency	Rt	Rs	Ps	Gs	EIRP	EIRP		
(MHz)	(dBm)	(dBm)	(dBm)	(dBi)	(dBm)	(W)		
1850.20	-24.67	-52.13	0.00	1.96	29.42	0.87		
1880.00	-25.97	-53.17	0.00	2.00	29.20	0.83		
1909.80	-26.70	-54.13	0.00	1.98	29.41	0.87		

TEL: 86-755-3320-2398

Page Number : 18 of 40
Report Issued Date : Nov. 11, 2013
Report Version : Rev. 01



3.4 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.4.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

- 1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. The 99% occupied bandwidth were measured, set RBW= 1% of span, VBW= 3*RBW, sample detector, trace maximum hold.
- 4. The 26dB bandwidth were measured, set RBW= 1% of EBW, VBW= 3*RBW, peak detector, trace maximum hold.

3.4.4 Test Setup



SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-3320-2398

Page Number : 19 of 40
Report Issued Date : Nov. 11, 2013
Report Version : Rev. 01




3.4.5 Test Result of Occupied Bandwidth and 26dB Bandwidth

PCS Band						
Modes		GSM1900 (GSM)				
Chamal	512	661	810			
Channel	(Low)	(Mid)	(High)			
Frequency (MHz)	1850.2	1880	1909.8			
99% OBW (kHz)	246.00	246.00	244.00			
26dB BW (kHz)	310.00	306.00	316.00			

3.4.6 Test Result (Plots) of Occupied Bandwidth and 26dB Bandwidth


Band :	GSM 1900	Test Mode :	GSM Link (GMSK)
--------	----------	-------------	-----------------

99% Occupied Bandwidth Plot on Channel 512 (1850.2 MHz)



Date: 30.OCT.2013 10:44:44

26dB Bandwidth Plot on Channel 512 (1850.2 MHz)




Date: 30.OCT.2013 10:43:02




Report No.: FG3O2201

99% Occupied Bandwidth Plot on Channel 661 (1880.0 MHz)



Date: 30.OCT.2013 10:46:02

26dB Bandwidth Plot on Channel 661 (1880.0 MHz)




Date: 30.OCT.2013 10:41:47

Page Number TEL: 86-755-3320-2398 Report Issued Date: Nov. 11, 2013 Report Version : Rev. 01




Report No.: FG3O2201

99% Occupied Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 30.OCT.2013 10:48:23

26dB Bandwidth Plot on Channel 810 (1909.8 MHz)



Date: 30.OCT.2013 10:40:29

Page Number TEL: 86-755-3320-2398 Report Issued Date: Nov. 11, 2013 Report Version : Rev. 01



3.5 Band Edge Measurement

3.5.1 Description of Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

Report No.: FG3O2201

3.5.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

- 1. The EUT was connected to Spectrum Analyzer and Base Station via power divider.
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. The band edges of low and high channels for the highest RF powers were measured. Setting RBW as roughly BW/100.
- The RF fundamental frequency should be excluded against the limit line in the operating 4. frequency band.
- 5. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)
 - = P(W) [43 + 10log(P)] (dB)
 - = [30 + 10log(P)] (dBm) [43 + 10log(P)] (dB)
 - = -13dBm.

3.5.4 Test Setup

<Conducted Band Edge >



: 24 of 40 Page Number TEL: 86-755-3320-2398 Report Issued Date: Nov. 11, 2013 Report Version : Rev. 01



3.5.5 Test Result (Plots) of Conducted Band Edge


Band :	GSM1900	Test Mode :	GSM Link (GMSK)
Correction Factor :	0.23dB	Maximum 26dB Bandwidth :	0.316MHz
Band Edge :	-18.72dBm	Measurement Value :	-18.95dBm

Report No.: FG3O2201

: 25 of 40

: Rev. 01

Lower Band Edge Plot on Channel 512 (1850.2 MHz)




Date: 30.OCT.2013 10:37:36

- 1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
- 2. Band Edge= Measurement Value + Correction Factor(dB) For example, -18.95dBm + 0.23dB = -18.72dBm

Page Number TEL: 86-755-3320-2398 Report Issued Date: Nov. 11, 2013 Report Version

Band :	GSM1900	Test Mode :	GSM Link (GMSK)
Correction Factor :	0.23dB	Maximum 26dB Bandwidth :	0.316MHz
Band Edge :	-17.78dBm	Measurement Value :	-18.01dBm

Higher Band Edge Plot on Channel 810 (1909.8 MHz)



Date: 30.OCT.2013 10:38:44

- 1. Correction Factor(dB)= 10log(1% Emission BW/RBW)
- 2. Band Edge= Measurement Value + Correction Factor(dB)

TEL: 86-755- 3320-2398

Page Number : 26 of 40
Report Issued Date : Nov. 11, 2013
Report Version : Rev. 01



3.6 Conducted Spurious Emission Measurement

3.6.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

- 1. The EUT was connected to spectrum analyzer and base station via power divider.
- The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
 The path loss was compensated to the results for each measurement.
- 3. The middle channel for the highest RF power within the transmitting frequency was measured.
- 4. The conducted spurious emission for the whole frequency range was taken.
- 5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
- 6. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)
 - = P(W) [43 + 10log(P)] (dB)
 - = [30 + 10log(P)] (dBm) [43 + 10log(P)] (dB)
 - = -13dBm

3.6.4 Test Setup



TEL: 86-755-3320-2398

Page Number : 27 of 40
Report Issued Date : Nov. 11, 2013
Report Version : Rev. 01




3.6.5 Test Result (Plots) of Conducted Spurious Emission

Band :	GSM1900	Channel:	CH661
Test Mode :	GSM Link (GMSK)	Frequency:	1880.0 MHz


Conducted Spurious Emission Plot between 30MHz ~ 1GHz

Report No.: FG3O2201



Date: 30.OCT.2013 10:51:59

Conducted Spurious Emission Plot between 1GHz ~ 3GHz




Date: 30.OCT.2013 10:51:14

Page Number TEL: 86-755- 3320-2398 Report Issued Date: Nov. 11, 2013 Report Version : Rev. 01




Report No.: FG3O2201



Date: 30.OCT.2013 10:54:11

Conducted Emission Plot between 7GHz ~ 13.6GHz




Date: 30.OCT.2013 10:55:01

Page Number TEL: 86-755-3320-2398 Report Issued Date: Nov. 11, 2013 : Rev. 01 Report Version



Conducted Spurious Emission Plot between 13.6GHz ~ 19.1GHz



Date: 30.OCT.2013 10:56:21

TEL: 86-755-3320-2398

Page Number : 30 of 40
Report Issued Date : Nov. 11, 2013
Report Version : Rev. 01

3.7 Field Strength of Spurious Radiation Measurement

3.7.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

Report No.: FG3O2201

3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Procedures

- The EUT was placed on a rotatable wooden table with 0.8 meter above ground.
- 2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
- The table was rotated 360 degrees to determine the position of the highest spurious emission.
- The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
- Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
- A horn antenna was substituted in place of the EUT and was driven by a signal generator.
- 7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
- 8. Taking the record of output power at antenna port.
- Repeat step 7 to step 8 for another polarization.
- 10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
- 11. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)
 - = P(W) [43 + 10log(P)] (dB)
 - = [30 + 10log(P)] (dBm) [43 + 10log(P)] (dB)
 - = -13dBm.
- 12. EIRP (dBm) = S.G. Power Tx Cable Loss + Tx Antenna Gain


Page Number : 31 of 40 TEL: 86-755-3320-2398 Report Issued Date: Nov. 11, 2013 Report Version : Rev. 01




Report No.: FG3O2201

3.7.4 Test Setup

For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz




TEL: 86-755-3320-2398

Page Number : 32 of 40
Report Issued Date : Nov. 11, 2013
Report Version : Rev. 01

3.7.5 Test Result of Field Strength of Spurious Radiated

Band :	GSM1900	Temperature :	24~27°C		
Test Mode :	GSM Link (GMSK)	Relative Humidity :	55~58%		
Test Engineer :	Robin Luo	Polarization :	Horizontal		
Romark ·	Spurious emissions within 30-1000MHz were found more than 20dB below limit line				

Report No.: FG3O2201



: 03CH01-SZ

: -13DBM HF_EIRP_H_130101 HORIZONTAL Condition

Project : (FG)302201


Frequency	EIRP	Limit	Over Limit	SPA Reading	S.G. Power	TX Cable loss	TX Antenna Gain	Polarization	Result
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3760	-49.79	-13	-36.79	-63.21	-56.53	1.28	8.02	Н	Pass
5640	-47.44	-13	-34.44	-65.43	-55.86	1.58	10.00	Н	Pass
7520	-53.29	-13	-40.29	-75.23	-63.61	1.78	12.10	Н	Pass

Page Number : 33 of 40 TEL: 86-755-3320-2398 Report Issued Date: Nov. 11, 2013 Report Version : Rev. 01

FCC RF Test Report

Band :	GSM1900	Temperature :	24~27°C			
Test Mode :	GSM Link (GMSK)	Relative Humidity :	55~58%			
Test Engineer :	Robin Luo	Polarization :	Vertical			
Remark :	Spurious emissions within 30-1000MHz were found more than 20dB below limit line.					

Report No.: FG3O2201



: 03CH01-SZ Site

: -13DBM HF_EIRP_V_130101 VERTICAL Condition

: (FG)302201 Project

Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3760	-54.92	-13	-41.92	-69.95	-61.66	1.28	8.02	V	Pass
5640	-51.54	-13	-38.54	-68.62	-59.96	1.58	10	V	Pass
7520	-53.23	-13	-40.23	-75.48	-63.55	1.78	12.1	V	Pass

Page Number : 34 of 40 TEL: 86-755-3320-2398 Report Issued Date: Nov. 11, 2013 Report Version : Rev. 01

3.8 Frequency Stability Measurement

3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency.

3.8.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.8.3 Test Procedures for Temperature Variation

- 1. The EUT was set up in the thermal chamber and connected with the base station.
- With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
- 3. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.8.4 Test Procedures for Voltage Variation

- 1. The EUT was placed in a temperature chamber at 25±5° C and connected with the base station.
- 2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
- 3. The variation in frequency was measured for the worst case.

TEL: 86-755- 3320-2398


Page Number : 35 of 40
Report Issued Date : Nov. 11, 2013

Report No.: FG3O2201

Report Version : Rev. 01



3.8.5 Test Setup



TEL: 86-755-3320-2398

Page Number : 36 of 40
Report Issued Date : Nov. 11, 2013
Report Version : Rev. 01

3.8.6 Test Result of Temperature Variation

Band :	GSM 1900	Channel:	661
Limit (ppm) :	2.5	Frequency:	1880.0 MHz

Report No.: FG3O2201

	GS		
Temperature (°C)	Freq. Dev. (Hz)	Deviation (ppm)	Result
-30	-45	-0.02	
-20	-36	-0.02	
-10	-42	-0.02	
0	-39	-0.02	
10	-33	-0.02	PASS
20	-38	-0.02	
30	-31	-0.02	
40	-36	-0.02	
50	-41	-0.02	

: 37 of 40 Page Number TEL: 86-755-3320-2398 Report Issued Date: Nov. 11, 2013 Report Version : Rev. 01



FCC RF Test Report

3.8.7 Test Result of Voltage Variation

Band & Channel	Mode	Voltage (Volt)	Freq. Dev. (Hz)	Deviation (ppm)	Limit (ppm)	Result
GSM 1900 CH661	GSM	3.7	-35	-0.02		Pass
		BEP	-37	-0.02	2.5	
		4.2	-38	-0.02		

Note:

- 1. Normal Voltage = 3.7V.
- 2. Battery End Point (BEP) = 3.6 V.

TEL: 86-755- 3320-2398 Report

Page Number : 38 of 40
Report Issued Date : Nov. 11, 2013
Report Version : Rev. 01



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV30	100845	9kHz~30GHz	Nov. 06, 2012	Oct. 30, 2013	Nov. 05, 2013	Conducted (TH01-SZ)
Spectrum Analyzer	R&S	FSP30	101400	9kHz~30GHz	Mar. 28, 2013	Oct. 30, 2013	Mar. 27, 2014	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	N/A	Mar. 28, 2013	Oct. 30, 2013	Mar. 27, 2014	Conducted (TH01-SZ)
Power Sensor	Anritsu	MA2411B	1207253	N/A	Mar. 28, 2013	Oct. 30, 2013	Mar. 27, 2014	Conducted (TH01-SZ)
Thermal Chamber	Hongzhan	LP-150U	HD20120425	N/A	Mar. 28, 2013	Oct. 30, 2013	Mar. 27, 2014	Conducted (TH01-SZ)
Spectrum Analyzer	Agilent Technologies	N9038A	MY52260185	20Hz~26.5GHz	Apr. 04, 2013	Oct. 25, 2013	Apr. 03, 2014	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS Lindgren	3117	00119436	1GHz~18GHz	Nov. 12, 2012	Oct. 25, 2013	Nov. 11, 2013	Radiation (03CH01-SZ)
Bilog Antenna	SCHAFFNER	CBL6112B	2614	30MHz~2GHz	Nov. 03, 2012	Oct. 25, 2013	Nov. 02, 2013	Radiation (03CH01-SZ)
Amplifier	ADVANTEST	BB525C	E9007003	9kHz-3000MHz GAIN 30db	Mar. 28, 2013	Oct. 25, 2013	Mar. 27, 2014	Radiation (03CH01-SZ)
Amplifier	Yiai	AV3860B	04030	2GHz~26.5GHz	Mar. 28, 2013	Oct. 25, 2013	Mar. 27, 2014	Radiation (03CH01-SZ)
SHF-EHF-Hor n	Schwarzbeck	BBHA9170	BBHA917024 9	14GHz~40GHz	Nov. 23, 2012	Oct. 25, 2013	Nov. 22, 2013	Radiation (03CH01-SZ)
Turn Table	EM Electronice	EM 1000	N/A	0 ~ 360 degree	N/A	Oct. 25, 2013	N/A	Radiation (03CH01-SZ)
Antenna Mast	EM Electronice	EM 1000	N/A	1 m - 4 m	N/A	Oct. 25, 2013	N/A	Radiation (03CH01-SZ)
Spectrum Analyzer	R&S	FSP 7	100818	9kHz~7GHz	Sep. 03, 2013	Oct. 30, 2013	Sep. 02, 2014	EIRP (OTA01-SZ)
Quad-Ridged Horn	ETS-Lindgren	3164-08	00102954	700MHz~10000MH z	NCR	Oct. 30, 2013	NCR	EIRP (OTA01-SZ)
Multi-Devices Controller	ETS-Lindgren	2090-OPT1	00108147	N/A	NCR	Oct. 30, 2013	NCR	EIRP (OTA01-SZ)
Switch Control Mainframe	Agilent	3499A	MY42005451	N/A	NCR	Oct. 30, 2013	NCR	EIRP (OTA01-SZ)

TEL: 86-755- 3320-2398

Page Number : 39 of 40
Report Issued Date : Nov. 11, 2013
Report Version : Rev. 01



FCC RF Test Report

5 **Uncertainty of Evaluation**

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of	2.54
Confidence of 95% (U = 2Uc(y))	210 1

Report No.: FG3O2201

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of	4.72
Confidence of 95% (U = 2Uc(y))	4.72

Page Number TEL: 86-755-3320-2398 Report Issued Date: Nov. 11, 2013 Report Version : Rev. 01

Appendix A. Photographs of EUT

Please refer to Sporton report number EP3O2201 which is issued separately.

Report No.: FG3O2201

SPORTON INTERNATIONAL (SHENZHEN) INC.

Page Number : A1 of A1 TEL: 86-755-3320-2398 Report Issued Date: Nov. 11, 2013 Report Version : Rev. 01