

TEST REPORT

of

FCC Part 15 Subpart C §15.249

FCC ID : WU2SMRSFLASHWAVE5

Equipment Under Test : FLASH WIRELESS CONTROL SYSTEM
Model Name : FLASHWAVE-5
Variant Model Names : FLASHWAVE-5 TX, FLASHWAVE-5 TTL,
F5-TTL, F5-TTL TX, SWING-IV, POWERSYNC TTL,
POWERSYNC 16-80 TTL, BRIHT TX, BRIHT TTL TX,
TS-4
Applicant : SMDV
Manufacturer : SMDV
Date of Receipt : 2016.02.23
Date of Test(s) : 2016.03.02 ~ 2016.08.31
Date of Issue : 2016.08.31

In the configuration tested, the EUT complied with the standards specified above.

Tested By:



Date: 2016.08.31

Jinhyoung Cho

Technical Manager:



Date: 2016.08.31

Hyunchae You

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

INDEX

| <u>Table of Contents</u> | Page |
|--|------|
| 1. General information ----- | 3 |
| 2. Fundamental and Radiated Spurious emission----- | 6 |
| 3. 20 dB Bandwidth ----- | 23 |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-20(2015.10.01)(3)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

1. General information

1.1 Testing laboratory

SGS Korea Co., Ltd. (Gunpo Laboratory)

- Wireless Div. 2FL, 10-2, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807

All SGS services are rendered in accordance with the applicable SGS conditions of service available on request and accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx>.

Telephone : +82 31 688 0901

FAX : +82 31 688 0921

1.2 Details of applicant

Applicant : SMDV
Address : 1532 Nakdongdae-Ro, Sasang-Gu, Busan, Korea
Contact Person : Kim, Ji-Young
Phone No. : +82 51 324 0788

1.3. Description of EUT

| | |
|-----------------------|--|
| Kind of Product | FLASH WIRELESS CONTROL SYSTEM |
| Model Name | FLASHWAVE-5 |
| Variant Model Names | FLASHWAVE-5 TX, FLASHWAVE-5 TTL, F5-TTL, F5-TTL TX, SWING-IV, POWERSYNC TTL, POWERSYNC 16-80 TTL, BRIHT TX, BRIHT TTL TX, TS-4 |
| Power Supply | DC 3.0 V |
| Frequency Range | 2 402 MHz ~ 2 481 MHz (TX only) |
| Modulation Technique | GFSK |
| Number of Channels | 80 Channels |
| Operation Temperature | -20 °C ~ 50 °C |
| Antenna Type | PCB Antenna |
| Antenna Gain | 0 dB i |
| H/W Version | 1.0 |
| S/W Version | 1.0 |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

1.4. Test equipment list

| Equipment | Manufacturer | Model | S/N | Cal. Date | Cal. Interval | Cal. Due |
|-------------------|-----------------------------|--------------------------------------|---------------|---------------|---------------|---------------|
| Signal Generator | R&S | SMBV100A | 259067 | Jun. 20, 2016 | Annual | Jun. 20, 2017 |
| Signal Generator | Agilent | E8257D | MY51501169 | Jul. 07, 2016 | Annual | Jul. 07, 2017 |
| Spectrum Analyzer | Agilent | N9020A | MY53421758 | Sep. 24, 2015 | Annual | Sep. 24, 2016 |
| Spectrum Analyzer | R&S | FSV30 | 100768 | Mar. 30, 2016 | Annual | Mar. 30, 2017 |
| High Pass Filter | Wainwright Instrument GmbH | WHK3.0/18G-6SS | 4 | Jun. 18, 2016 | Annual | Jun. 18, 2017 |
| High Pass Filter | Wainwright Instrument GmbH | WHNX7.5/26.5G-6SS | 15 | Jun. 18, 2016 | Annual | Jun. 18, 2017 |
| Low Pass Filter | Mini-Circuits | NLP-1200+ | V8979400903-2 | Feb. 29, 2016 | Annual | Feb. 29, 2017 |
| Attenuator | Mini-Circuits | BW-N20W5+ | 0950-2 | Jun. 18, 2016 | Annual | Jun. 18, 2017 |
| DC Power Supply | R&S | HMP2020 | 020089489 | May 31, 2016 | Annual | May 31, 2017 |
| Preamplifier | H.P. | 8447F | 2944A03909 | Aug. 11, 2016 | Annual | Aug. 11, 2017 |
| Preamplifier | R&S | SCU-18 | 10117 | Apr. 07, 2016 | Annual | Apr. 07, 2017 |
| Preamplifier | MITEQ Inc. | JS44-18004000-35-8P | 1546891 | May 12, 2016 | Annual | May 12, 2017 |
| Loop Antenna | Schwarzbeck Mess-Elektronik | FMZB 1519 | 1519-039 | Aug. 19, 2015 | Biennial | Aug. 19, 2017 |
| Bilog Antenna | Schwarzbeck Mess-Elektronik | VULB 9163 | 396 | Jun. 18, 2015 | Biennial | Jun. 18, 2017 |
| Horn Antenna | R&S | HF906 | 100326 | Feb. 01, 2016 | Biennial | Feb. 01, 2018 |
| Horn Antenna | Schwarzbeck Mess-Elektronik | BBHA 9170 | 9170-540 | Sep. 01, 2015 | Biennial | Sep. 04, 2017 |
| Turn Table | INN-CO systems | CONTROLLER CO3000 | N/A | N. C. R | N/A | N. C. R |
| Antenna Master | INN-CO systems | MA4640-XP-ET | N/A | N. C. R | N/A | N. C. R |
| Test Receiver | R&S | ESU26 | 100109 | Mar. 07, 2016 | Annual | Mar. 07, 2017 |
| Anechoic Chamber | SY Corporation | L x W x H (9.6 m x 6.4 m x 6.6 m) | N/A | N.C.R. | N/A | N.C.R. |

Note:

The equipment calibrated during the test period was used after finished the calibration.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

1.5. Summary of test results

The EUT has been tested according to the following specifications:

| Applied Standard : FCC Part15, Subpart C | | |
|--|--|----------|
| Standard Section | Test Item | Result |
| 15.205 15.209(a) 15.249(a) 15.249(c) 15.249(d) | Fundamental and Radiated Spurious emission | Complied |
| 15.215(c) | 20 dB Bandwidth | Complied |

1.6. Test Procedure(s)

The measurement procedures described in the American National Standard for Testing Unlicensed Wireless Devices (ANSI C63.10-2013) was used in the measurement of the DUT.

1.7. Sample calculation

Where relevant, the following sample calculation is provided

1.7.1. Radiation test

Field strength level (dB μ V/m) = Measured level (dB μ V) + Antenna factor (dB) + Cable loss (dB) – Amplifier gain (dB)

1.8. Test report revision

| Revision | Report number | Date of Issue | Description |
|----------|----------------------|---------------|-------------|
| 0 | F690501/RF-RTL010302 | 2016.08.31 | Initial |

1.9. Variant models

| Model name | Information |
|---|---|
| FLASHWAVE-5 | - Basic model. |
| FLASHWAVE-5 TX, FLASHWAVE-5 TTL, F5-TTL, F5-TTL TX, SWING-IV, POWERSYNC TTL, POWERSYNC 16-80 TTL, BRIHT TX, BRIHT TTL TX TS-4 | - Same to basic model. - There are no difference electrical and electronic properties, circuits, components, features, appearance and structure. |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

2. Fundamental and Radiated Spurious emission


2.1. Test setup

2.1.1. Fundamental and Radiated Spurious Emissions

The diagram below shows the test setup that is utilized to make the measurements for emission from 9 kHz to 30 MHz Emissions.



The diagram below shows the test setup that is utilized to make the measurements for emission from 30 MHz to 1 GHz Emissions.



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-20(2015.10.01)(3)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

The diagram below shows the test setup that is utilized to make the measurements for emission. The spurious emissions were investigated from 1 GHz to the 10th harmonic of the highest fundamental frequency or 40 GHz, whichever is lower.



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-20(2015.10.01)(3)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

2.2. Test procedures

Radiated emissions from the EUT were measured according to the dictates of ANSI C63.10-2013.

2.2.1. Test Procedures for emission below 30 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site. The table was rotated 360 degrees to determine the position of the highest radiation.
2. Then antenna is a loop antenna is fixed at one meter above the ground to determine the maximum value of the field strength. Both parallel and perpendicular of the antenna are set to make the measurement.
3. For each suspected emission, the EUT was arranged to its worst case and then the table was turned from 0 degrees to 360 degrees to find the maximum reading.
4. The test-receiver system was set to average or quasi peak detect function and Specified Bandwidth with Maximum Hold Mode.

Note:

Although these tests were performed other than open field test site, adequate comparison measurements were confirmed against 30 meter open field test site.

Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 937606.

2.2.2. Test Procedures for emission from above 30 MHz

1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter anechoic chamber test site below 1 GHz and 1.5 meters above the ground at a 3 meter anechoic chamber test site above 1 GHz. The table was rotated 360 degrees to determine the position of the highest radiation.
2. During performing radiated emission below 1 GHz, the EUT was set 3 meters away from the interference receiving antenna, which was mounted on the top of a variable-height antenna tower. During performing radiated emission above 1 GHz, the EUT was set 3 meter away from the interference-receiving antenna.
3. The antenna is a trilog broadband antenna, a horn antenna and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1 GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection and frequency above 1 GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1 GHz.
4. To get a maximum emission level from the EUT, the EUT is manipulated through three orthogonal planes (X, Y, Z). Worst orthogonal plan of EUT is X – axis during radiation test.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

2.3. Limit

According to §15.249(a), Except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

| Fundamental frequency | Field strength of fundamental (mV/m) | Field strength of harmonics ($\mu\text{V/m}$) |
|-----------------------|--|--|
| 902 – 928 MHz | 50 | 500 |
| 2 400 – 2 483.5 MHz | 50 | 500 |
| 5 725 – 5 875 MHz | 50 | 500 |
| 24.0 – 24.25 GHz | 250 | 2 500 |

According to §15.249(d), Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever the lesser attenuation.

According to §15.209(a), Except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

| Frequency (MHz) | Distance (Meters) | Field Strength (dB $\mu\text{V/m}$) | Field Strength ($\mu\text{V/m}$) |
|--------------------|----------------------|---|---------------------------------------|
| 0.009 – 0.490 | 300 | 20 log (2 400/F(kHz)) | 2 400/F(kHz) |
| 0.490 – 1.705 | 30 | 20 log (24 000/F(kHz)) | 24 000/F(kHz) |
| 1.705 – 30.0 | 30 | 29.54 | 30 |
| 30 – 88 | 3 | 40.0 | 100 |
| 88 – 216 | 3 | 43.5 | 150 |
| 216 – 960 | 3 | 46.0 | 200 |
| Above 960 | 3 | 54.0 | 500 |

Remark:

Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

2.4. Test result

Ambient temperature : $(23 \pm 1)^\circ\text{C}$

Relative humidity : 47 % R.H.


2.4.1. Radiated Spurious Emission below 1 000 MHz

The frequency spectrum from 9 kHz to 1 000 MHz was investigated. All reading values are peak values.

| Radiated Emissions | | | Ant. | Correction Factors | | Total | FCC Limit | |
|--------------------|----------------------|-------------|------|--------------------|---------------|-----------------------|----------------------|-------------|
| Frequency (MHz) | Reading (dB μ V) | Detect Mode | Pol. | AF (dB/m) | AMP + CL (dB) | Actual (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
| 52.47 | 33.30 | Peak | H | 15.49 | -26.96 | 21.83 | 40.00 | 18.17 |
| 508.82 | 34.20 | Peak | V | 18.68 | -25.54 | 27.34 | 46.00 | 18.66 |
| 734.22 | 34.90 | Peak | V | 22.21 | -25.23 | 31.88 | 46.00 | 14.12 |
| 988.40 | 34.00 | Peak | H | 23.48 | -23.31 | 34.17 | 54.00 | 19.83 |

Remark

1. Spurious emissions for all channels were investigated and almost the same below 1 GHz.
2. Reported spurious emissions are in **Low channel** as worst case among other channels.
3. Radiated spurious emission measurement as below.
(Actual = Reading + AF + AMP + CL)
4. According to §15.31(o), emission levels are not report much lower than the limits by over 20 dB.



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-20(2015.10.01)(3)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

2.4.2. Radiated Spurious Emission above 1 000 MHz

A. Low Channel (2 402 MHz)

| Fundamental level | | | Ant. | Correction Factors | | Total | Limit | |
|-------------------|----------------------|-------------|------|--------------------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz) | Reading (dB μ V) | Detect Mode | Pol. | AF (dB/m) | CL (dB) | Actual (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
| 2 402.30 | 32.83 | Peak | H | 28.16 | 5.85 | 66.84 | 114.00 | 47.16 |
| 2 402.06 | 23.00 | Average | H | 28.16 | 5.85 | 57.01 | 94.00 | 36.99 |

| Radiated Emissions | | | Ant. | Correction Factors | | Total | Limit | |
|--------------------|----------------------|-------------|------|--------------------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz) | Reading (dB μ V) | Detect Mode | Pol. | AF (dB/m) | CL (dB) | Actual (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
| *2 310.00 | 24.58 | Peak | H | 28.07 | 5.31 | 58.16 | 74.00 | 15.84 |
| *2 310.00 | 15.35 | Average | H | 28.07 | 5.31 | 48.74 | 54.00 | 5.26 |
| *2 387.60 | 26.19 | Peak | H | 28.15 | 5.79 | 60.13 | 74.00 | 13.87 |
| *2 388.90 | 15.57 | Average | H | 28.15 | 5.79 | 49.51 | 54.00 | 4.49 |
| *2 390.00 | 25.14 | Peak | H | 28.15 | 5.80 | 59.24 | 74.00 | 14.76 |
| *2 390.00 | 15.57 | Average | H | 28.15 | 5.80 | 49.54 | 54.00 | 4.46 |
| 2 400.00 | 24.94 | Peak | H | 28.16 | 5.87 | 58.97 | 74.00 | 15.03 |
| 2 400.00 | 15.76 | Average | H | 28.16 | 5.87 | 49.79 | 54.00 | 4.21 |

| Radiated Emissions | | | Ant. | Correction Factors | | Total | Limit | |
|--------------------|----------------------|-------------|------|--------------------|-------------|-----------------------|----------------------|-------------|
| Frequency (MHz) | Reading (dB μ V) | Detect Mode | Pol. | AF (dB/m) | AMP+CL (dB) | Actual (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
| *4 802.82 | 59.59 | Peak | H | 32.65 | -30.28 | 61.96 | 74.00 | 12.04 |
| *4 804.10 | 50.56 | Average | H | 32.65 | -30.26 | 52.95 | 54.00 | 1.05 |
| Above 4 900.00 | Not detected | - | - | - | - | - | - | - |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-20(2015.10.01)(3)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

B. Middle Channel (2 441 MHz)

| Fundamental level | | | Ant. | Correction Factors | | Total | Limit | |
|-------------------|----------------------|-------------|------|--------------------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz) | Reading (dB μ V) | Detect Mode | Pol. | AF (dB/m) | CL (dB) | Actual (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
| 2 440.95 | 32.41 | Peak | H | 28.20 | 5.62 | 66.23 | 114.00 | 47.77 |
| 2 441.07 | 22.52 | Average | H | 28.20 | 5.62 | 56.34 | 94.00 | 37.66 |

| Radiated Emissions | | | Ant. | Correction Factors | | Total | Limit | |
|--------------------|----------------------|-------------|------|--------------------|-------------|-----------------------|----------------------|-------------|
| Frequency (MHz) | Reading (dB μ V) | Detect Mode | Pol. | AF (dB/m) | AMP+CL (dB) | Actual (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
| *4 880.92 | 59.00 | Peak | H | 32.86 | -29.70 | 62.16 | 74.00 | 11.84 |
| *4 882.12 | 49.10 | Average | H | 32.86 | -29.69 | 52.27 | 54.00 | 1.73 |
| Above 4 900.00 | Not detected | - | - | - | - | - | - | - |

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

C. High Channel (2 481 MHz)

| Fundamental level | | | Ant. | Correction Factors | | Total | Limit | |
|-------------------|----------------------|-------------|------|--------------------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz) | Reading (dB μ V) | Detect Mode | Pol. | AF (dB/m) | CL (dB) | Actual (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
| 2 481.34 | 31.90 | Peak | H | 28.24 | 5.55 | 65.69 | 114.00 | 48.31 |
| 2 481.06 | 21.91 | Average | H | 28.24 | 5.55 | 55.70 | 94.00 | 38.30 |

| Radiated Emissions | | | Ant | Correction Factors | | Total | Limit | |
|--------------------|----------------------|-------------|------|--------------------|---------|-----------------------|----------------------|-------------|
| Frequency (MHz) | Reading (dB μ V) | Detect Mode | Pol. | AF (dB/m) | CL (dB) | Actual (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
| *2 483.50 | 25.38 | Peak | H | 28.24 | 5.54 | 59.16 | 74.00 | 14.84 |
| *2 483.50 | 16.02 | Average | H | 28.24 | 5.54 | 49.80 | 54.00 | 4.20 |
| *2 495.19 | 28.32 | Peak | H | 28.26 | 5.51 | 62.09 | 74.00 | 11.91 |
| *2 484.76 | 16.03 | Average | H | 28.24 | 5.54 | 49.81 | 54.00 | 4.19 |
| *2 500.00 | 25.94 | Peak | H | 28.26 | 5.49 | 59.69 | 74.00 | 14.31 |
| *2 500.00 | 16.06 | Average | H | 28.26 | 5.49 | 49.81 | 54.00 | 4.19 |

| Radiated Emissions | | | Ant | Correction Factors | | Total | Limit | |
|--------------------|----------------------|-------------|------|--------------------|-------------|-----------------------|----------------------|-------------|
| Frequency (MHz) | Reading (dB μ V) | Detect Mode | Pol. | AF (dB/m) | AMP+CL (dB) | Actual (dB μ V/m) | Limit (dB μ V/m) | Margin (dB) |
| *4 961.59 | 56.78 | Peak | H | 33.08 | -29.47 | 60.39 | 74.00 | 13.61 |
| *4 962.09 | 46.11 | Average | H | 33.08 | -29.47 | 49.72 | 54.00 | 4.28 |
| Above 5 000.00 | Not detected | - | - | - | - | - | - | - |

Remarks:

- “*” means the restricted band.
- Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
- Radiated emissions measured in frequency above 1 000 MHz were made with an instrument using peak/average detector mode.
- Actual = Reading + AF + AMP + CL or Reading + AF + CL
- According to §15.31(o), emission levels are not reported much lower than the limits by over 20 dB.
- Emission was scanned up to 25 GHz; No emissions were detected above the noise floor which was at least 20 dB below the specification limit.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>


RTT5041-20(2015.10.01)(3)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370


A4(210 mm x 297 mm)

2.4.2. Radiated Spurious Emission above 1 000 MHz

Low channel fundamental (Peak)



Low channel fundamental (Average)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-20(2015.10.01)(3)


Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

Low channel band edge (Peak)



Low channel band edge (Average)




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-20(2015.10.01)(3)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370


A4(210 mm x 297 mm)

Low channel 2nd harmonic (Peak)Low channel 2nd harmonic (Average)


The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

Middle channel fundamental (Peak)



Middle channel fundamental (Average)





The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-20(2015.10.01)(3)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

Middle channel 2nd harmonic (Peak)

Middle channel 2nd harmonic (Average)


The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-20(2015.10.01)(3)


Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

High channel fundamental (Peak)



High channel fundamental (Average)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-20(2015.10.01)(3)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

High channel band edge (Peak)



High channel band edge (Average)





The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-20(2015.10.01)(3)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

High channel 2nd harmonic (Peak)

High channel 2nd harmonic (Average)


The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>


RTT5041-20(2015.10.01)(3)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370


A4(210 mm x 297 mm)

2.4.3. Pre-scan Test Plots

1 GHz ~ 3 GHz



3 GHz ~ 18 GHz



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-20(2015.10.01)(3)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)

3. 20 dB Bandwidth

3.1. Test Setup



3.2. Limit

Limit: Not Applicable

3.3. Test Procedure

1. The transmitter output is connected to the spectrum analyzer.
2. The bandwidth of the fundamental frequency was measured with the spectrum analyzer using RBW=20 kHz, VBW=50 kHz and Span=3 MHz.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

3.4. Test Results

Ambient temperature : $(23 \pm 1)^\circ\text{C}$
 Relative humidity : 47 % R.H.

| Channel | Frequency (MHz) | 20 dB Bandwidth (MHz) |
|---------|-----------------|-----------------------|
| Low | 2 402 | 1.493 |
| Middle | 2 441 | 1.247 |
| High | 2 481 | 1.672 |


Low Channel




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>
 RTT5041-20(2015.10.01)(3) Tel. +82 31 428 5700 / Fax. +82 31 427 2370 A4(210 mm x 297 mm)

Middle Channel



High Channel



- End of the Test Report -

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

SGS Korea Co., Ltd. (Gunpo Laboratory) 4, LS-ro 182beon-gil, Gunpo-si, Gyeonggi-do, Korea, 15807 <http://www.sgsgroup.kr>

RTT5041-20(2015.10.01)(3)

Tel. +82 31 428 5700 / Fax. +82 31 427 2370

A4(210 mm x 297 mm)