



198 Kezhu Road, Scientech Park, Guangzhou Economic & Technology Development District, Guangzhou, Guangdong, China 510663

Telephone: +86 (0) 20 82155555

Fax: +86 (0) 20 82075059

Email: [sgs\\_internet\\_operations@sgs.com](mailto:sgs_internet_operations@sgs.com)

FEDERAL COMMUNICATIONS COMMISSION

Registration number: 282399

Report No.: GLEMO081003184RFT

Page: 1 of 55

FCC ID: WUIBT30404F

## TEST REPORT

**Application No. :** GLEMO081003184RF

**Applicant:** WINPLUS COMPANY LIMITED

**FCC ID:** WUIBT30404F

**Fundamental Carrier Frequency :** 2.402GHz to 2.480GHz

**Equipment Under Test (EUT):**

Name: YD-V16 Rear View Speakerphone with Caller ID

Model: BT30404F-1

Serial No.: Not supplied by client

**Standards:** FCC PART 15 Subpart C: 2008

**Date of Receipt:** 22 October 2008

**Date of Test:** 22 October 2008 to 9 November 2008

**Date of Issue:** 10 November, 2008

<b>Test Result :</b>	<b>PASS *</b>
----------------------	---------------

\* In the configuration tested, the EUT detailed in this report complied with the standards specified above. Please refer to section 2 of this report for further detail.

Authorized Signature:

2008 - Nov.

Stephen Guo  
Manager

The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government. All test results in this report can be traceable to National or International Standards.

This document is issued by the Company under its General Conditions of Service printed overleaf or available on request and accessible at [http://www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law." Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This document cannot be reproduced except in full, without prior approval of the Company.

SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center

Report No.: GLEMO081003184RFT  
Page: 2 of 55  
FCC ID: WUIBT30404F

## 2 Test Summary

Test	Test Requirement	Standard Paragraph	Result
Antenna Requirement	FCC PART 15 :2008	Section 15.247 (c)	PASS
Occupied Bandwidth	FCC PART 15 :2008	Section 15.247 (a1)	PASS
Carrier Frequencies Separated	FCC PART 15 :2008	Section 15.247(a)(1)	PASS
Hopping Channel Number	FCC PART 15 :2008	Section 15.247(a)(1)(iii)	PASS
Dwell Time	FCC PART 15 :2008	Section 15.247(a)(1)(iii)	PASS
Pseudorandom Frequency Hopping Sequence	FCC PART 15 :2008	Section 15.247(a)(1)	PASS
Maximum Peak Output Power	FCC PART 15 :2008	Section 15.247(b)(1)	PASS
RF Exposure Compliance Requirement	FCC PART 15 :2008	15.247(b)(4)& TCB Exclusion List (7 July 2002)	PASS
Conducted Emission	FCC PART 15 :2008	Section 15.207	PASS
Conducted Spurious Emission (30MHz to 25GHz)	FCC PART 15 :2008	Section 15.209 &15.247(d)	PASS
Radiated Spurious Emission (30MHz to 25GHz)	FCC PART 15 :2008	Section 15.209 &15.247(d)	PASS
Band Edges Measurement	FCC PART 15 :2008	Section 15.247 (d) &15.205	PASS

SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center

Report No.: GLEMO081003184RFT  
Page: 3 of 55  
FCC ID: WUIBT30404F

### 3 Contents

	Page
<b>1 COVER PAGE .....</b>	<b>1</b>
<b>2 TEST SUMMARY .....</b>	<b>2</b>
<b>3 CONTENTS .....</b>	<b>3</b>
<b>4 GENERAL INFORMATION .....</b>	<b>4</b>
4.1 CLIENT INFORMATION .....	4
4.2 GENERAL DESCRIPTION OF E.U.T .....	4
4.3 DESCRIPTION OF SUPPORT UNITS .....	4
4.4 STANDARDS APPLICABLE FOR TESTING .....	4
4.5 TEST LOCATION .....	4
4.6 OTHER INFORMATION REQUESTED BY THE CUSTOMER .....	4
4.7 TEST FACILITY .....	5
<b>5 EQUIPMENTS USED DURING TEST.....</b>	<b>6</b>
<b>6 TEST RESULTS .....</b>	<b>7</b>
6.1 E.U.T. TEST CONDITIONS .....	7
6.2 ANTENNA REQUIREMENT.....	9
6.2.1 <i>Standard requirement</i> .....	9
6.2.2 <i>EUT Antenna</i> .....	9
6.3 CONDUCTED EMISSIONS AT MAINS TERMINALS 150 KHZ TO 30MHZ .....	10
6.4 OCCUPIED BANDWIDTH .....	13
6.5 CARRIER FREQUENCIES SEPARATED .....	17
6.6 HOPPING CHANNEL NUMBER.....	20
6.7 DWELL TIME .....	21
6.8 PSEUDORANDOM FREQUENCY HOPPING SEQUENCE .....	29
6.8.1 <i>Standard requirement</i> .....	29
6.8.2 <i>EUT Pseudorandom Frequency Hopping Sequence</i> .....	29
6.9 MAXIMUM PEAK OUTPUT POWER .....	30
6.10 RF EXPOSURE COMPLIANCE REQUIREMENT .....	35
6.10.1 <i>Standard requirement</i> .....	35
(b) <i>Limits for General Population / Uncontrolled Exposure</i> .....	35
6.10.2 <i>MPE Calculation Method</i> .....	36
6.10.3 <i>3 Calculated Result and Limit</i> .....	36
6.11 CONDUCTED SPURIOUS EMISSIONS .....	37
6.12 RADIATED SPURIOUS EMISSIONS .....	43
6.12.1 <i>Harmonic and other spurious emissions</i> .....	46
6.12.2 <i>Radiated Emissions which fall in the restricted bands</i> .....	50
6.13 BAND EDGES REQUIREMENT .....	52

## 4 General Information

### 4.1 Client Information

Applicant: WINPLUS COMPANY LIMITED  
Address of Applicant: Suites 6-11, 7<sup>TH</sup> Floor, Corporation Park 11 On Lai Street, Shatin, N.T., Hong Kong

### 4.2 General Description of E.U.T.

Product Name: YD-V16 Rear View Speakerphone with Caller ID  
Model: BT30404F-1  
Number of Channels: 79 Channels  
Channel Separation: 1 MHz  
Type of Modulation: FHSS (Frequency Hopping Spread Spectrum);  
Dwell time: Per channel is less than 0.4s.  
Antenna Type: Integral  
Speciality: Bluetooth 2.0 with EDR  
Power Supply: Rechargeable battery inside DC 5V 650mA  
Power Supply information supplied: Car charger or USB or Solar in

### 4.3 Description of Support Units

The EUT has been tested with PC for fixed frequency by testing lab.

### 4.4 Standards Applicable for Testing

The customer requested FCC tests for the EUT.

The standard used was FCC PART 15 Subpart C: 2008. ANSI C63.4:2003. DA 00-705.

### 4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory. 198 Kezhu Road, Scientech Park, Guangzhou Economic & Technology Development District, Guangzhou, Guangdong, China 510663

Tel: +86 20 82155555 Fax: +86 20 82075059

No tests were sub-contracted.

### 4.6 Other Information Requested by the Customer

None.

SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center

Report No.: GLEMO081003184RFT  
Page: 5 of 55  
FCC ID: WUIBT30404F

#### 4.7 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **NVLAP – Lab Code: 200611-0**

SGS-CSTC Standards Technical Services Co., Ltd., Guangzhou EMC Laboratory is recognized under the National Voluntary Laboratory Accreditation Program (NVLAP/NIST). NVLAP Code: 200611-0.

- **FCC – Registration No.: 282399**

SGS-CSTC Standards Technical Services Co., Ltd., EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 282399. May 31. 2002. With the above and NVLAP's accreditation. SGS-CSTC is an authorized test laboratory for the DoC process.

SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center

Report No.: GLEMO081003184RFT  
Page: 6 of 55  
FCC ID: WUIBT30404F

## 5 Equipments Used during Test

RE in Chamber						
No:	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (dd-mm-yy)	Cal.Due date (dd-mm-yy)
EMC0525	Compact Semi-Anechoic Chamber	ChangZhou ZhongYu	N/A	N/A	N/A	N/A
EMC0522	EMI Test Receiver	Rohde & Schwarz	ESIB26	100249	28-01-2008	28-01-2009
N/A	EMI Test Software	Audix	E3	N/A	N/A	N/A
EMC0514	Coaxial cable	SGS	N/A	N/A	04-12-2007	04-12-2008
EMC0524	Bi-log Type Antenna	Schaffner -Chase	CBL6112B	2966	12-08-2008	12-08-2009
EMC0519	Bilog Type Antenna	Schaffner -Chase	CBL6143	5070	12-08-2008	12-08-2009
EMC0517	Horn Antenna	Rohde & Schwarz	HF906	100095	12-08-2008	12-08-2009
EMC0040	Spectrum Analyzer	Rohde & Schwarz	FSP30	100324	05-12-2008	05-12-2009
EMC0520	0.1-1300 MHz Pre-Amplifier	HP	8447D OPT 010	2944A06252	11-03-2008	11-03-2009
EMC0521	1-26.5 GHz Pre-Amplifier	Agilent	8449B	3008A01649	11-03-2008	11-03-2009
EMC0075	310N Amplifier	Sonama	310N	272683	10-09-2008	10-09-2009
EMC0523	Active Loop Antenna	EMCO	6502	00042963	09-08-2008	09-08-2010
EMC0530	10m Semi- Anechoic Chamber	ETS	N/A	N/A	10-08-2008	10-08-2009

Conducted Emission						
No:	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date (dd-mm-yy)	Cal.Due date (dd-mm-yy)
EMC0306	Shielding Room	Zhong Yu	8 x 3 x 3.8 m <sup>3</sup>	N/A	N/A	N/A
EMC0102	LISN	Schaffner Chase	MNZ050D/1	1421	14-12-2007	14-12-2008
EMC0118	Two-line v-netwok	Rohde & Schwarz	ENV216	3560.6550.02	28-07-2008	28-07-2009
EMC0506	EMI Test Receiver	Rohde & Schwarz	ESCS30	100085	14-12-2007	14-12-2008
EMC0107	Coaxial Cable	SGS	2m	N/A	24-11-2007	26-11-2008
EMC0106	Voltage Probe	SGS	N/A	N/A	N/A	N/A
EMC0120	8 Line LISN	Fischer Custom Communications Inc.	FCC-TLISN-T8-02	20550	21-02-2008	21-02-2009
EMC0121	4 Line LISN	Fischer Custom Communications Inc.	FCC-TLISN-T4-02	20549	21-02-2008	21-02-2009
EMC0122	2 Line LISN	Fischer Custom Communications Inc.	FCC-TLISN-T2-02	20548	21-02-2008	21-02-2009

Reference Equipment					
No:	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. Date
No. 1	Notebook	IBM	T40	99-FBAF9 03/09	N/A
No. 2	Philip Bluetooth	Philip	N/A	N/A	N/A

This document is issued by the Company under its General Conditions of Service printed overleaf or available on request and accessible at [http://www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law." Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This document cannot be reproduced except in full, without prior approval of the Company.

## 6 Test Results

### 6.1 E.U.T. test conditions

Power supply: DC 5V 650mA

Type of antenna: Integral

Operating Environment:

Temperature: 20.0 -25.0 °C

Humidity: 38-52 % RH

Atmospheric Pressure: 992 -1010 mbar

Test frequencies: According to the 15.31(m) Measurements on intentional radiators or receivers, other than TV broadcast receivers, shall be performed and, if required, reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table:

Frequency range over which device operates	Number of frequencies	Location in the range of operation
1 MHz or less	1	Middle
1 to 10 MHz	2	1 near top and 1 near bottom
More than 10 MHz	3	1 near top, 1 near middle and 1 near bottom

EUT channels and frequencies list:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	14	2416	28	2430
1	2403	15	2417	29	2431
2	2404	16	2418	30	2432
3	2405	17	2419	31	2433
4	2406	18	2420	32	2434
5	2407	19	2421	33	2435
6	2408	20	2422	34	2436
7	2409	21	2423	35	2437
8	2410	22	2424	36	2438
9	2411	23	2425	37	2439
10	2412	24	2426	38	2440
11	2413	25	2427	39	2441
12	2414	26	2428	40	2442
13	2415	27	2429	41	2443

SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center

Report No.: GLEMO081003184RFT  
Page: 8 of 55  
FCC ID: WUIBT30404F

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
42	2444	55	2457	68	2470
43	2445	56	2458	69	2471
44	2446	57	2459	70	2472
45	2447	58	2460	71	2473
46	2448	59	2461	72	2474
47	2449	60	2462	73	2475
48	2450	61	2463	74	2476
49	2451	62	2464	75	2477
50	2452	63	2465	76	2478
51	2453	64	2466	77	2479
52	2454	65	2467	78	2480
53	2455	66	2468		
54	2456	67	2469		

Test frequency is the lowest channel: 0 channel(2402MHz), middle channel: 39 channel(2441MHz) and highest channel: 78 channel(2480MHz)

## 6.2 Antenna Requirement

### 6.2.1 Standard requirement

15.203 requirement:


For intentional device. According to 15.203. an intentional radiator shall be designed to Ensure that no antenna other than that furnished by the responsible party shall be used with the device.

15.247(c) (1)(i) requirement:

(i) Systems operating in the 2400-2483.5 MHz bands that are used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

### 6.2.2 EUT Antenna

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 3.0dBi.



**Test result: The unit does meet the FCC requirements.**


### 6.3 Conducted Emissions at Mains Terminals 150 kHz to 30MHz

Test Requirement:	FCC Part 15.207
Test Method:	ANSI C63.4
Test Date:	31 October, 2008
Frequency Range:	150KHz to 30MHz
Detector:	Peak for pre-scan (9kHz Resolution Bandwidth) Quasi-Peak if maximised peak within 6dB of Quasi-Peak limit
EUT Operation:	Pretest the EUT in Bluetooth normal mode and EDR mode, find the EDR mode is the worse case, and report the EDR mode test data.

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

Plan View of Test Setup




SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center

Report No.: GLEMO081003184RFT  
Page: 11 of 55  
FCC ID: WUIBT30404F

Connect to PC:

LISN live line




Quasi-peak and Average measurement:

Freq	Read	Cable	LISN	Limit	Over	Over	Remark
	Level	Loss	Factor				
MHz	dBuV	dB	dB	dBuV	dBuV	dB	
0.262	30.96	0.16	9.58	40.70	61.38	-20.68	QP
0.262	28.35	0.16	9.58	38.09	51.38	-13.29	AVERAGE
0.661	26.78	0.26	9.58	36.62	56.00	-19.38	QP
0.661	23.90	0.26	9.58	33.74	46.00	-12.26	AVERAGE
1.088	25.72	0.29	9.59	35.60	56.00	-20.40	QP
1.088	19.63	0.29	9.59	29.51	46.00	-16.49	AVERAGE
2.110	24.80	0.20	9.61	34.61	56.00	-21.39	QP
2.110	20.03	0.20	9.61	29.84	46.00	-16.16	AVERAGE
3.346	21.42	0.14	9.62	31.18	56.00	-24.82	QP
3.346	17.43	0.14	9.62	27.19	46.00	-18.81	AVERAGE
4.407	19.94	0.11	9.63	29.67	56.00	-26.33	QP
4.407	15.45	0.11	9.63	25.18	46.00	-20.82	AVERAGE

SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center

Report No.: GLEMO081003184RFT  
Page: 12 of 55  
FCC ID: WUIBT30404F

LISN neutral line



Quasi-peak and Average measurement:

Freq	Read	Cable	LISN	Limit	Over	Remark
	Level	Loss	Factor			
MHz	dBuV	dB	dB	dBuV	dBuV	dB
0.259	24.96	0.16	9.59	34.71	61.47	-26.76 QP
0.259	22.75	0.16	9.59	32.50	51.47	-18.97 AVERAGE
0.661	26.06	0.26	9.58	35.90	56.00	-20.10 QP
0.661	23.15	0.26	9.58	32.99	46.00	-13.01 AVERAGE
1.147	27.04	0.28	9.58	36.91	56.00	-19.09 QP
1.147	19.97	0.28	9.58	29.84	46.00	-16.16 AVERAGE
1.628	21.18	0.24	9.59	31.01	46.00	-14.99 AVERAGE
1.628	23.86	0.24	9.59	33.69	56.00	-22.31 QP
3.860	18.68	0.12	9.62	28.43	56.00	-27.57 QP
3.860	15.21	0.12	9.62	24.96	46.00	-21.04 AVERAGE
14.288	2.35	0.31	9.84	12.50	50.00	-37.50 AVERAGE
14.288	10.56	0.31	9.84	20.71	60.00	-39.29 QP

Remark: Level = Real Level + Cable loss + LISN factor

**TEST RESULTS: The unit does meet the FCC requirements.**

SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center

Report No.: GLEMO081003184RFT  
Page: 13 of 55  
FCC ID: WUIBT30404F

## 6.4 Occupied Bandwidth

Test Requirement: FCC Part 15 C  
Test Method: Based on FCC Part15 C Section 15.247 & DA 00-705  
Test Date: 30 October, 2008  
Test Status: Test in fixing operating frequency at lowest, Middle, highest channel.  
Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum;
2. Set the spectrum analyzer: Span = approximately 2 to 3 times the 20dB bandwidth, centered on a hopping channel;
3. Set the spectrum analyzer: RBW  $\geq$  1% of the 20dB bandwidth (set 100kHz). VBW  $\geq$  RBW. Sweep = auto; Detector Function = Peak. Trace = Max Hold.
4. Mark the peak frequency and -20dB points or 99% bandwidth.

### Test result:

#### GFSK mode:

Test Channel	bandwidth
Low	336.673KHz
Middle	336.673KHz
High	334.669KHz

#### 8DPSK mode:

Test Channel	bandwidth	2/3 bandwidth
Low	1.130MHz	649.299KHz
Middle	1.122MHz	665.330KHz
High	1.098MHz	681.363KHz


Result plot as follows:

SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center


Report No.: GLEMO081003184RFT  
Page: 14 of 55  
FCC ID: WUIBT30404F

Normal mode:

Lowest Channel:




Middle Channel:



SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center


Report No.: GLEMO081003184RFT  
Page: 15 of 55  
FCC ID: WU1BT30404F

Highest Channel:



EDR mode:


Lowest Channel:




SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center

Report No.: GLEMO081003184RFT  
Page: 16 of 55  
FCC ID: WUIBT30404F

Middle channel:



Highest channel:



## 6.5 Carrier Frequencies Separated

Test Requirement: FCC Part 15 C

Test Method: Based on FCC Part15 C Section 15.247 & DA 00-705

Test Date: 30 October, 2008

Test requirements: Regulation 15.247(a),(1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Test Status: Test in hopping transmitting operating mode.

Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW  $\geq$  1% of the span (set 100 kHz). VBW  $\geq$  RBW, Span = 6MHz. Sweep = auto; Detector Function = Peak. Trace = Max,hold.
3. Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot.

### Test result:

Test Channel	Carrier Frequencies Separated	PASS/FAIL
Lower Channels (channel 0 and channel 1)	1.010MHz	Pass
Middle Channels (channel 39 and channel 40)	1.010MHz	Pass
Upper Channels (channel 77 and channel 78)	1.002MHz	Pass


Remark:

Pre-test in Bluetooth normal mode and EDR mode, find the worse case is in normal mode, and the limit in normal mode is maximum 20dB channel bandwidth 351KHz. So report the normal mode data.


SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center

Report No.: GLEMO081003184RFT  
Page: 18 of 55  
FCC ID: WUIBT30404F

1. Lowest Channels: Carrier Frequencies Separated




2. Middle Channels: Carrier Frequencies Separated



SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center

Report No.: GLEMO081003184RFT  
Page: 19 of 55  
FCC ID: WUIBT30404F

3. Highest Channels: Carrier Frequencies Separated



Test result: The unit does meet the FCC requirements.

SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center

Report No.: GLEMO081003184RFT  
Page: 20 of 55  
FCC ID: WUIBT30404F

## 6.6 Hopping Channel Number

Test Requirement: FCC Part15 C

Test Method: Based on FCC Part15 C Section 15.247 & DA 00-705

Test Date: 26 October, 2008


Requirements: Regulation 15.247 (a) (1)(iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

Test Status: Test in hopping transmitting operating mode.

Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 100 kHz. VBW = 300 kHz. Sweep = auto; Detector Function = Peak. Trace = Max hold.
3. Allow the trace to stabilize. It may prove necessary to break the span up to sections. in order to clearly show all of the hopping frequencies. The limit is specified in one of the subparagraphs of this Section.
4. Set the spectrum analyzer: start frequency = 2400MHz. stop frequency = 2483.5MHz. Submit the test result graph.

**Test result:** Total channels are 79 channels.



**Test result:** The unit does meet the FCC requirements.

SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center

Report No.: GLEMO081003184RFT  
Page: 21 of 55  
FCC ID: WUIBT30404F

## 6.7 Dwell Time

Test Requirement: FCC Part 15 C  
Test Method: Based on FCC Part15 C Section 15.247 & DA 00-705  
Test Date: 30 October, 2008  
Test requirements: Regulation 15.247(a)(1)(iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.  
Test Status: Test in hopping transmitting operating mode.

Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set spectrum analyzer span = 0. centered on a hopping channel;
3. Set RBW = 1MHz and VBW = 3MHz. Sweep = as necessary to capture the entire dwell time per hopping channel. Detector Function = Peak. Trace = Max hold;
4. Use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g.. data rate. modulation format. etc.). repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s). An oscilloscope may be used instead of a spectrum analyzer.

Pre-test the Bluetooth normal mode and EDR mode, find the EDR mode is worse case and report it.

Test Result:

The test period:  $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$

1. **Channel 0: 2.402GHz**

DH1 time slot =  $0.431 \text{ (ms)} \times (1600/(2*79)) \times 31.6 = 137.920\text{ms}$

DH3 time slot =  $1.693 \text{ (ms)} \times (1600/(4*79)) \times 31.6 = 270.880\text{ms}$

DH5 time slot =  $2.936 \text{ (ms)} \times (1600/(6*79)) \times 31.6 = 313.173\text{ms}$

2. **Channel 39: 2.441GHz**

DH1 time slot =  $0.431 \text{ (ms)} \times (1600/(2*79)) \times 31.6 = 137.920\text{ms}$

DH3 time slot =  $1.693 \text{ (ms)} \times (1600/(4*79)) \times 31.6 = 270.880\text{ms}$

DH5 time slot =  $2.896 \text{ (ms)} \times (1600/(6*79)) \times 31.6 = 308.907\text{ms}$

3. **Channel 78: 2.480GHz**

DH1 time slot =  $0.431 \text{ (ms)} \times (1600/(2*79)) \times 31.6 = 137.920\text{ms}$

DH3 time slot =  $1.693 \text{ (ms)} \times (1600/(4*79)) \times 31.6 = 270.880\text{ms}$

DH5 time slot =  $2.896 \text{ (ms)} \times (1600/(6*79)) \times 31.6 = 308.907\text{ms}$

The results are not greater than 0.4 seconds.

### The unit does meet the FCC requirements.


SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center

Report No.: GLEMO081003184RFT  
Page: 22 of 55  
FCC ID: WUIBT30404F


Please refer the graph as below:

1. Lowest channel (2.402 GHz):

(1). DH1



(2) DH3:




SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center

Report No.: GLEMO081003184RFT  
Page: 23 of 55  
FCC ID: WUIBT30404F


1. Lowest channel (2.402 GHz):

(3). DH5:



2. Middle Channel (2.441GHz)

(1) DH1




SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center

Report No.: GLEMO081003184RFT  
Page: 24 of 55  
FCC ID: WUIBT30404F

2. Middle Channel (2.441GHz)

(2) DH3



(3) DH5

Delta 1 [T1] -3.62 dB  
Ref Lvl 10 dBm  
RBW 1 MHz  
VBW 3 MHz  
SWT 2.895792 ms  
RF Att 30 dB  
Unit dBm

Center 2.441 GHz 2 ms/

Y-axis: -90 to 10 dBm  
X-axis: 2 ms/


Annotations: ▼1 [T1] -14.57 dBm 7.585170 ms  
▲1 [T1] -3.62 dB 2.895792 ms

SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center


Report No.: GLEMO081003184RFT  
Page: 25 of 55  
FCC ID: WUIBT30404F

3. Highest channel (2.480GHz)

(1). DH1



(2). DH3




SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center

Report No.: GLEMO081003184RFT  
Page: 26 of 55  
FCC ID: WUIBT30404F

3. Highest channel (2.480GHz)

(3). DH5



Remark:

In communication data link mode (expect inquiry or page mode) the hopping rate is 1600 per second, the 79 channels will be randomly selected for RF channel, and each channel have equal probability to be selected. The hop selection scheme is defined in Clause 2.6 of Part B of Volume 2 of core specification of Bluetooth.

The Dwell time must be calculated via following formula:

**Dwell time = Pulse wide x (Hopping rate / Number of channels) x Period**

**Period = 0.4 (seconds/ channel) x 79 (channel) = 31.6 seconds**

So

Dwell time DH1= slot time \* (1600/2/79) \* 31.6

Dwell time DH3= slot time \* (1600/4/79) \* 31.6

Dwell time DH5= slot time \* (1600/6/79) \* 31.6

The **RF channel will remain fixed for duration of a packet**, that means for DH3 packet the RF frequency will remain unchanged during 3 slots (1slot=1/1600=625us), and for DH5 packet the RF frequency will remain unchanged during 5 slots, illustrated the principle as below:




Figure 2.14: Single- and multi-slot packets.

Therefore, in a certain period for different packet types, the quantities of hops (**not hopping rate 1600**) are different, accurately, the quantity of hops for DH1 is double of DH3's and triple of DH5's. “for DH1 packet, 1 hop in 1 slot; for DH3 packet, ½ hop in 1 slot; for DH5 packet, 1/3 hop in 1 slot.”, explained as below:

From the illustrated hopping scheme:

For DH1, in two slots, there are two hops, i.e.  $f(k)$  in Slot(k),  $f(k+1)$  in Slot(k+1), means DH1 1 hop in 1 slot;

For DH3, in four slots, there are two hops, i.e.  $f(k)$  in Slot(k) & Slot(k+1) & Slot(k+2),  $f(k+3)$  in Slot(k+3), means DH3 2 hops in four slots  $\rightarrow \frac{1}{2}$  hop in 1 slot;

For DH5, in six slots, there are two hops, i.e.  $f(k)$  in Slot(k) & Slot(k+1) & Slot(k+2) & Slot(k+3) & Slot(k+4),  $f(k+5)$  in Slot(k+5), means DH3 2 hops in six slots  $\rightarrow \frac{1}{3}$  hop in 1 slot.

The **Hopping rate** in the formula should **not** be fixed value, for DH1, it is 1600/2; for DH3, it is 1600/4; for DH5, it is 1600/6.

To calculate Dwell time of data transmission of Bluetooth system, the worst case is for Bluetooth PICONET that contains two devices only (although Bluetooth PICONET can support up to eight devices), and for Bluetooth data transmission, after device A sending a packet to device B, device A must get response packet from device B to continue data transmission;

For DH1 packet: assume device A is EUT, the worst case is after device A sending a DH1 packet to device B, device A gets a DH1 response packet from device B, that means device A needs 1 time slot for transmitting and 1 time slot for receiving, therefore, the actual hopping rate of device A is half of 1600, i.e. 800 hops per second for EUT;

SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center

Report No.: GLEMO081003184RFT  
Page: 28 of 55  
FCC ID: WUIBT30404F

For DH3 packet: assume device A is EUT, the worst case is after device A sending a DH3 packet to device B, device A gets a DH1 response packet from device B, that means device A needs 3 time slots for transmitting and 1 time slot for receiving, therefore, the actual hopping rate of device A is quarter of 1600, i.e. 400 hops per second for EUT;

For DH5 packet: assume device A is EUT, the worst case is after device A sending a DH5 packet to device B, device A gets a DH1 response packet from device B, that means device A needs 5 time slots for transmitting and 1 time slot for receiving, therefore, the actual hopping rate of device A is sixth of 1600, i.e.  $1600/6=266.7$  hops per second for EUT;

## 6.8 Pseudorandom Frequency Hopping Sequence

### 6.8.1 Standard requirement

15.247(a)(1) requirement:


Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

### 6.8.2 EUT Pseudorandom Frequency Hopping Sequence


The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage, and the result is fed back to the input of the first stage. The sequence begins with the first ONE of 9 consecutive ONEs; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence:  $2^9 - 1 = 511$  bits
- Longest sequence of zeros: 8 (non-inverted signal)



*Linear Feedback Shift Register for Generation of the PRBS sequence*

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.


The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center

Report No.: GLEMO081003184RFT  
Page: 30 of 55  
FCC ID: WUIBT30404F

## 6.9 Maximum Peak Output Power

Test Requirement: FCC Part 15.247 & DA 00-705  
Test Method: Base on ANSI 63.4.  
Test Date: 29 October, 2008  
Test Limit: Regulation 15.247 (b)(1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.  
Refer to the result "Hopping channel number" of this document. The 1 watt (30.0dBm) limit applies.  
Test mode: Test in fixing frequency transmitting mode.  
Test Configuration:



### Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 1 MHz. VBW = 3 MHz. Sweep = auto; Detector Function = Peak.
3. Keep the EUT in transmitting at lowest, medium and highest channel individually. Record the max value.

SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center

Report No.: GLEMO081003184RFT  
Page: 31 of 55  
FCC ID: WUIBT30404F

**Test Result:**

**Normal mode:**

Test Channel	Fundamental Frequency (MHz)	Reading Power (dBm)	Cable Loss (dB)	Output Power (dBm)	Limit (dBm)	Margin (dB)
Lowest	2.402	-12.27	0.20	-12.07	30.0	42.07
Middle	2.441	-12.85	0.20	-12.65	30.0	42.65
Highest	2.480	-14.42	0.20	-14.22	30.0	44.22

**EDR mode:**

Test Channel	Fundamental Frequency (MHz)	Reading Power (dBm)	Cable Loss (dB)	Output Power (dBm)	Limit (dBm)	Margin (dB)
Lowest	2.402	-12.73	0.20	-12.53	30.0	42.53
Middle	2.441	-13.31	0.20	-13.11	30.0	43.11
Highest	2.480	-14.76	0.20	-14.56	30.0	44.56

**Test result: The unit does meet the FCC requirements.**


**Test result plot as follows:**

SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center


Report No.: GLEMO081003184RFT  
Page: 32 of 55  
FCC ID: WUIBT30404F

**Normal mode:**

**Lowest Channel:**




**Middle Channel:**



SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center


Report No.: GLEMO081003184RFT  
Page: 33 of 55  
FCC ID: WUIBT30404F

**Highest Channel:**



**EDR mode:**


**Lowest channel:**




SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center

Report No.: GLEMO081003184RFT  
Page: 34 of 55  
FCC ID: WUIBT30404F

**Middle channel:**



**Highest channel:**



## 6.10 RF Exposure Compliance Requirement

### 6.10.1 Standard requirement

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

#### (a) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S)(mW/cm <sup>2</sup> )	Averaging Times  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100000			5	6

#### (b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S)(mW/cm <sup>2</sup> )	Averaging Times  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/500	30
1500-100000			1.0	30

Note: f=frequency in MHz; \*Plane-wave equivalent power density

SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center

Report No.: GLEMO081003184RFT  
Page: 36 of 55  
FCC ID: WUIBT30404F

#### 6.10.2 MPE Calculation Method

$E \text{ (V/m)} = (30 \cdot P \cdot G) \cdot 0.5 / d$  Power Density:  $P_d \text{ (W/m}^2\text{)} = E^2 / 377$

E=Electric Field (V/m)

P=Peak RF output Power (W)

G=EUT Antenna numeric gain (numeric)

d= Separation distance between radiator and human body (m)

The formula can be changed to

$P_d = (30 \cdot P \cdot G) / (377 \cdot d^2)$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

#### 6.10.3 3 Calculated Result and Limit

Normal mode:

Frequency (MHz)	Antenna Gain (Numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm <sup>2</sup> )	Limit of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
2402	3.0	-12.27	0.059	0.070	1	Complies
2441	3.0	-12.85	0.052	0.062	1	Complies
2480	3.0	-14.42	0.036	0.043	1	Complies


EDR mode:

Frequency (MHz)	Antenna Gain (Numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm <sup>2</sup> )	Limit of Power Density (S) (mW/cm <sup>2</sup> )	Test Result
2402	3.0	-12.73	0.053	0.063	1	Complies
2441	3.0	-13.31	0.047	0.056	1	Complies
2480	3.0	-14.76	0.033	0.040	1	Complies

## 6.11 Conducted Spurious Emissions

Test Requirement: FCC Part 15.247 & DA 00-705  
Test Method: Based on FCC Part15 C Section 15.247&15.209:  
Test Date: 30 October, 2008  
Test requirements: (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. based on either an RF conducted or a radiated measurement. provided the transmitter demonstrates compliance with the peak conducted power limits.  
Test Status: Test the lowest. Middle, highest channel.

Test Configuration:



Test Procedure:

1. Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
2. Set the spectrum analyzer: RBW = 100KHz. VBW >= RBW. Sweep = auto; Detector Function = Peak (Max. hold).

Pretest Bluetooth normal mode and EDR mode, find the EDR mode is worse case and report it.


Test result plot as follows:

SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center


Report No.: GLEMO081003184RFT  
Page: 38 of 55  
FCC ID: WUIBT30404F

Lowest Channel:

30M to 1GHz




1G to 5GHz




SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center

Report No.: GLEMO081003184RFT  
Page: 39 of 55  
FCC ID: WUIBT30404F

5G to 25GHz




Middle Channel: 30M to 1GHz




SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center

Report No.: GLEMO081003184RFT  
Page: 40 of 55  
FCC ID: WUIBT30404F

1G to 5GHz




5G to 25GHz




SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center

Report No.: GLEMO081003184RFT  
Page: 41 of 55  
FCC ID: WUIBT30404F

Highest Channel: 30M to 1GHz



1G to 5GHz




This document is issued by the Company under its General Conditions of Service printed overleaf or available on request and accessible at [http://www.sgs.com/terms\\_and\\_conditions.htm](http://www.sgs.com/terms_and_conditions.htm). Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law." Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This document cannot be reproduced except in full, without prior approval of the Company.

SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center

Report No.: GLEMO081003184RFT  
Page: 42 of 55  
FCC ID: WUIBT30404F

5G to 25GHz



SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center

Report No.: GLEMO081003184RFT  
Page: 43 of 55  
FCC ID: WUIBT30404F

## 6.12 Radiated Spurious Emissions

Test Requirement:	FCC 15.247(d) & 15.209
Test Method:	ANSI C63.4 section 8 & 13
Test Date:	29 October, 2008
Test Status:	Test lowest channel, Middle, highest channel.
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)  Test instrumentation resolution bandwidth 120 kHz, VBW 300kHz and Quasi-Peak detector applies (30 MHz – 1000 MHz). 1MHz resolution bandwidth, VBW 3MHz and Peak and Average-Peak detector apply (1000 MHz – 25GHz).
	Receive antenna scan height 1 m – 4 m. polarization Vertical / Horizontal
15.209 Limit:	40.0 dB $\mu$ V/m between 30MHz & 88MHz  43.5 dB $\mu$ V/m between 88MHz & 216MHz  46.0 dB $\mu$ V/m between 216MHz & 960MHz  54.0 dB $\mu$ V/m above 960MHz
15.247(d) limit:	(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating. The radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that  Contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, and provided the transmitter demonstrates compliance with the peak conducted power limits.

### Test Configuration:




Figure 1. 30MHz to 1GHz radiated emissions test configuration




Figure 2. Above 1GHz radiated emissions test configuration

SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center

Report No.: GLEMO081003184RFT  
Page: 45 of 55  
FCC ID: WUIBT30404F

**Test Procedure:** The procedure used was ANSI Standard C63.4-2001. The receiver was scanned from 30MHz to 25GHz. When an emission was found, the table was rotated to produce the maximum signal strength. An initial pre-scan was performed for in peak detection mode using the receiver. The EUT was measured for both the Horizontal and Vertical polarities and performed a pre-test three orthogonal planes. For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. The worst case emissions were reported.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from  $20\log(\text{dwell time}/100 \text{ ms})$ , in an effort to demonstrate compliance with the 15.209 limit.

Submit this data.

## 6.12.1 Harmonic and other spurious emissions

### 6.12.1.1 Test in low Channel in transmitting status

30MHz~1GHz Spurious Emissions .Quasi-Peak Measurement

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Antenna polarization
317.120	14.03	2.17	24.51	37.54	29.23	46.00	Vertical
167.740	10.00	1.40	24.85	49.98	36.53	43.50	Horizontal

1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

#### Peak Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Antenna polarization
4804.000	33.19	6.90	33.01	50.42	57.50	74.00	Vertical
7206.000	36.00	8.36	32.20	40.01	48.92	74.00	V
9608.000	36.42	8.80	32.50	40.53	52.72	74.00	V
4804.000	33.19	6.90	33.01	43.51	50.59	74.00	Horizontal
7206.000	36.08	8.36	32.20	40.24	48.70	74.00	H
9608.000	36.40	8.80	32.50	35.27	48.00	74.00	H

#### Average Measurement:

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Antenna polarization
4804.000	33.19	6.90	33.01	45.88	52.96	54.00	Vertical
7206.000	36.05	8.36	32.20	23.23	35.44	54.00	V
9608.000	36.40	8.80	32.50	21.47	34.17	54.00	V
4804.000	33.19	6.90	33.01	36.58	43.66	54.00	Horizontal
7206.000	36.11	8.36	32.20	22.77	35.04	54.00	H
9608.000	36.42	8.80	32.50	22.81	35.53	54.00	H

The field strength is calculated by adding the Antenna Factor. Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading + Antenna Factor + Cable Factor -Preamplifier Factor.

SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center

Report No.: GLEMO081003184RFT  
Page: 47 of 55  
FCC ID: WUIBT30404F

**6.12.1.2 Test in middle Channel in transmitting status**

30MHz~1GHz Spurious Emissions .Quasi-Peak Measurement

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Antenna polarization
408.300	16.45	2.50	25.09	32.03	25.89	46.00	Vertical
191.020	10.10	1.60	24.69	52.01	39.03	43.50	Horizontal

1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

**Peak Measurement:**

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Antenna polarization
4882.000	33.27	7.20	32.97	50.55	58.04	74.00	Vertical
7323.000	36.16	6.95	32.29	36.68	47.50	74.00	V
9764.000	36.40	7.20	32.44	38.44	49.60	74.00	V
4882.000	33.27	7.20	32.97	50.31	57.81	74.00	Horizontal
7323.000	36.16	6.95	32.29	36.95	47.77	74.00	H
9764.000	36.40	7.20	32.44	38.19	49.35	74.00	H

**Average Measurement:**

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Antenna polarization
4882.000	33.27	7.20	32.97	42.65	50.14	54.00	Vertical
7323.000	36.16	6.95	32.29	21.99	32.81	54.00	V
9764.000	36.40	7.20	32.44	23.46	34.62	54.00	V
4882.000	33.27	7.20	32.97	45.28	52.78	54.00	Horizontal
7323.000	36.16	6.95	32.29	22.45	33.27	54.00	H
9764.000	36.40	7.20	32.44	21.82	32.98	54.00	H

The field strength is calculated by adding the Antenna Factor. Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading + Antenna Factor + Cable Factor –Preamplifier Factor.

SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center

Report No.: GLEMO081003184RFT  
Page: 48 of 55  
FCC ID: WUIBT30404F

**6.12.1.3 Test in high Channel in transmitting status**

30MHz~1GHz Spurious Emissions .Quasi-Peak Measurement

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Antenna polarization
157.070	10.44	1.34	24.90	36.86	23.74	46.00	Vertical
325.850	14.00	2.20	24.57	50.70	42.33	46.00	Horizontal

1~25 GHz Harmonics & Spurious Emissions. Peak & Average Measurement

**Peak Measurement:**

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Antenna polarization
4960.000	33.36	7.33	32.92	50.12	57.90	74.00	Vertical
7440.000	36.23	6.05	32.37	39.49	49.40	74.00	V
9920.000	36.50	7.04	32.50	40.16	51.20	74.00	V
4960.000	33.36	7.33	32.92	50.43	58.20	74.00	Horizontal
7440.000	36.23	6.05	32.37	39.82	49.73	74.00	H
9920.000	36.50	7.04	32.50	41.53	52.57	74.00	H

**Average Measurement:**

Frequency (MHz)	Antenna factors (dB/m)	Cable loss (dB)	Preamp factor (dB)	Reading Level (dB $\mu$ V)	Emission Level (dB $\mu$ V/m)	Limit (dB $\mu$ V/m)	Antenna polarization
4960.000	33.36	7.33	32.92	42.56	50.34	54.00	Vertical
7440.000	36.23	6.05	32.37	24.19	34.10	54.00	V
9920.000	36.50	7.04	32.50	23.52	34.56	54.00	V
4960.000	33.36	7.33	32.92	42.57	50.34	54.00	Horizontal
7440.000	36.23	6.05	32.37	34.35	44.26	54.00	H
9920.000	36.50	7.04	32.50	31.84	42.88	54.00	H

The field strength is calculated by adding the Antenna Factor. Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading + Antenna Factor + Cable Factor –Preamplifier Factor.

Remark: No any other emissions level which are attenuated less than 20dB below the limit.

According to 15.31(o), The amplitude of spurious emissions from intentional radiators and emissions from unintentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this Part.

Hence there no other emissions have been reported.

SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center

Report No.: GLEMO081003184RFT  
Page: 49 of 55  
FCC ID: WUIBT30404F

Remark:

- 1). N/A: For this intentional radiator operates below 25 GHz. The spectrum shall be investigated to the tenth harmonic of the highest fundamental frequency. And above the third harmonic of this intentional radiator, the disturbance is very low. So the test result only displays to 3<sup>rd</sup> harmonic.
- 2). As shown in Section, for frequencies above 1000 MHz. the above field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.
- 3). The test only perform the EUT in transmitting status since the test frequencies were over 1GHz only required transmitting status.
- 4) Pre-test the Bluetooth normal mode and EDR mode, find the worse case is in EDR mode and report it.

**Test result: The unit does meet the FCC requirements.**

SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center

Report No.: GLEMO081003184RFT  
Page: 50 of 55  
FCC ID: WUIBT30404F

### 6.12.2 Radiated Emissions which fall in the restricted bands

Test Requirement:

Section 15.247(d) In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

Test Method:

Base on ANSI 63.4

Test Date:

29 October 2008

Measurement Distance:

3m (Semi-Anechoic Chamber)

Limit:

40.0 dB $\mu$ V/m between 30MHz & 88MHz;

43.5 dB $\mu$ V/m between 88MHz & 216MHz;

46.0 dB $\mu$ V/m between 216MHz & 960MHz;

54.0 dB $\mu$ V/m above 960MHz.

Detector:

Peak for pre-scan:

100kHz resolution bandwidth and 100kHz video bandwidth within 1GHz.  
1MHz resolution bandwidth and 1MHz video bandwidth above 1GHz

#### Test Result:

Pre-test the Bluetooth normal mode and EDR mode, find the worse case is in EDR mode and report it.

#### 1. Low Channel

Frequency (MHz)	Antenna factors (dB/m)	Cable loss(dB)	Preamp factor(dB)	Peak Reading Level (dB $\mu$ V)	Average Reading Level (dB $\mu$ V)	Peak Emission Level (dB $\mu$ V/m)	Average Emission Level (dB $\mu$ V/m)
2390.000	27.88	4.65	34.30	51.7	32.4	49.9	30.6
2483.500	28.74	4.80	34.73	53.8	33.5	52.6	32.3

#### 2. Middle Channel

Frequency (MHz)	Antenna factors (dB/m)	Cable loss(dB)	Preamp factor(dB)	Peak Reading Level (dB $\mu$ V)	Average Reading Level (dB $\mu$ V)	Peak Emission Level (dB $\mu$ V/m)	Average Emission Level (dB $\mu$ V/m)
2390.000	27.88	4.65	34.30	51.6	33.2	49.8	31.5
2483.500	28.74	4.80	34.73	54.1	32.7	52.4	31.0

#### 3. High Channel

Frequency (MHz)	Antenna factors (dB/m)	Cable loss(dB)	Preamp factor(dB)	Peak Reading Level (dB $\mu$ V)	Average Reading Level (dB $\mu$ V)	Peak Emission Level (dB $\mu$ V/m)	Average Emission Level (dB $\mu$ V/m)
2390.000	27.88	4.65	34.30	52.6	33.1	50.8	31.4
2483.500	28.74	4.80	34.73	54.5	32.6	52.7	30.8

Remark: No any other emission which falls in restricted bands can be detected and be reported.

**The unit does meet the FCC requirements.**

SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center

Report No.: GLEMO081003184RFT  
Page: 51 of 55  
FCC ID: WUIBT30404F

Section 15.205 Restricted bands of operation.

(a) Except as shown in paragraph (d) of this section. only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
<sup>1</sup> 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	
13.36 - 13.41	322 - 335.4		

## 6.13 Band Edges Requirement

Test Requirement: FCC Part 15 C

Test Method: Based on ANSI 63.4

Operation within the band 2400 – 2483.5 MHz

Test Date: 30 October, 2008

Requirements: Section 15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

Method of Measurement: Set RBW of spectrum analyzer to 100 kHz and VBW of spectrum analyzer to 100 kHz with suitable frequency span including 100 kHz bandwidth from band edge.

Pretest the EUT in hopping on and hopping off, found the worse case was the hopping off, The band edges was measured and recorded the worse case.

Normal mode:

The band edges was measured and recorded Result:

The Lower Edges attenuated more than 20dB.


The Upper Edges attenuated more than 20dB.

The graph as below. represents the emissions take for this device.


SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center

Report No.: GLEMO081003184RFT  
Page: 53 of 55  
FCC ID: WUIBT30404F

Lowest Channel:



Highest Channel:



SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center

Report No.: GLEMO081003184RFT  
Page: 54 of 55  
FCC ID: WUIBT30404F

EDR mode:


The band edges was measured and recorded Result:

The Lower Edges attenuated more than 20dB.

The Upper Edges attenuated more than 20dB.

The graph as below. Represents the emissions take for this device.

Lowest Channel:



SGS-CSTC Standards Technical Services Co., Ltd.  
GuangZhou Branch Testing Center

Report No.: GLEMO081003184RFT  
Page: 55 of 55  
FCC ID: WUIBT30404F

Highest Channel:

