

1 Profile

TS-NC380M tag is active active tags, tag will take the initiative to send card number and status information to reader . The tag is based MicroTag embedded operating system which for active tag appropriate, and the tag is integrated i-Power intelligent power management technology, making TS-NC380M smart tag very power saving. The built-in lithium battery can sustainable work 2 years.

TS-NC380M tag work at 2.4 GHz ISM band, you can use free of charge, without the need for the use of wireless spectrum licenses.

TS-NC380M Tag can be sticked on the object surface, when the object be moved, or the tag be removed illegal, the tag will be send alarm signal.

TS-NC380M tag use LocNet patented localizer technology, can locate the tag's position.

2 Specification

Rang	>50M (at visibility condition)
Operation Temperature	-40°C ~ +85°C
Operation Relative Humidity	10% ~ 95%
Frequency	2.4GHz
RF Power	1mW
Alarm Mode	Shock / LED
Battery Life	>2 years
Weight	20 g

3 Device Picture



Warning statement

FCC ID Number: WUJTSNC380M

Changes or modifications to this unit not expressly approved by the party responsible for compliance could void the user authority to operate the equipment .

This device complies with part 15 of the FCC rules, Operation is subject to the following conditions :

- (1) this device may not cause harmful interference, and (2) this device must accept any interference received , Including interference that may cause undesired operation.