

Global EMC Inc. Labs

EMC & RF Test Report

As per

RSS 210 Issue 8:2010

FCC Part 15 Subpart C:2010

Unlicensed Intentional Radiators

On the

Wireless Audio Transmitter Module – WTX1015



Ashwani Malhotra
Global EMC Inc.
180 Brodie Dr, Unit 2
Richmond Hill, ON L4B 3K8
Canada
Ph: (905) 883-3919

Testing produced for

SONAUOX
Audio Solution

See Appendix A for full customer & EUT details.



Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



Table of Contents

Table of Contents	2
Report Scope	3
Summary	4
Test Results Summary	5
Justifications, Descriptions, or Deviations	6
Applicable Standards, Specifications and Methods	7
Sample calculation(s)	8
Document Revision Status	8
Definitions and Acronyms	9
Testing Facility	10
Calibrations and Accreditations	10
Testing Environmental Conditions and Dates	11
Detailed Test Results Section	12
Spurious Radiated Emissions	13
6dB Bandwidth of Digitally Modulated Systems	34
Maximum Peak Envelope Conducted Power	42
Antenna Spurious Conducted Emissions (- 20 dbc Requirement)	46
Power Spectral Density	56
Maximum Permissible Exposure	61
Appendix A – EUT Summary	62
Appendix B – EUT and Test Setup Photographs	63

Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



Report Scope

This report addresses the EMC verification testing and test results of the Wireless Audio Transceiver Module – WTX1015, herein referred to as EUT (Equipment Under Test) performed at Global EMC Labs.

The EUT was tested for compliance against the following standards:

RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010

Test procedures, results, justifications, and engineering considerations, if any, follow later in this report.

The results contained in this report relate only to the item(s) tested.

This report does not imply product endorsement by A2LA or any other accreditation agency, any government, or Global EMC Inc.

Opinions/interpretations expressed in this report, if any, are outside the scope of Global EMC Inc accreditation. Any opinions expressed do not necessarily reflect the opinions of Global EMC Inc, unless otherwise stated.

Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



Summary

The results contained in this report relate only to the item(s) tested.

EUT FCC Certification #, FCC ID:	WUO-WTX1015
EUT Industry Canada Certification #, IC:	7985A-WTX1015
EUT Passed all tests performed.	Yes (see test results summary)
Tests conducted by	Ashwani Malhotra

Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



Test Results Summary

Standard/Method	Description	Class/Limit	Result
FCC 15.203	Antenna Requirement	Unique / PCB mounted	Pass See Justification
FCC 15.205 RSS 210 (Table 1)	Restricted Bands for intentional operation	QuasiPeak Average	Pass
FCC 15.207	Power line conducted emissions	QuasiPeak Average	N/A
FCC 15.209 RSS-210 (Table 2)	Spurious Radiated emissions	QuasiPeak Average	Pass
FCC 15.247(a)2 RSS-210 A8.2(a)	6 dB Bandwidth	> 500 kHz	Pass
FCC 15.247(b)2 RSS-210 A8.4(4)	Max output power	< 1 Watt	Pass
FCC 15.247(b)(4) RSS-210 A8.4(5)	Antenna Gain	< 6 dBi	Pass
FCC 15.247(d) RSS-210 A8.5	Antenna conducted spurious	< 20 dBc	Pass
FCC 15.247(e) RSS-210 A8.2(b)	Spectral Density	< 8 dBm (3 kHz BW)	Pass
FCC 15.247(i) IC Safety code 6	Maximum Permissible Exposure	> 2.5 cm separation.	Pass See justification and calculations
Overall Result			PASS

All tests were performed by Ashwani Malhotra

If the product as tested or otherwise complies with the specification, the EUT is deemed to comply with the requirement and is deemed a 'PASS' grade. If not 'FAIL' grade will be issued. Note that 'PASS' / 'FAIL' grade is independent of any measurement uncertainties. A 'PASS' / 'FAIL' grade within measurement uncertainty is marked with a '*'.

Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



Justifications, Descriptions, or Deviations

The following justifications for tests not performed or deviations from the above listed specifications apply:

For the Antenna requirement specified in FCC 15.203 (RSS 210 section 5.5), the unit uses a ceramic chip antenna (0.5 dbi gain - Johanson 2450AT43A100).

For the Restricted Bands of operation, the EUT is designed to only operate between 2400 – 2477.0 MHz (Channel 0-15).

For the scope of this testing the EUT was mounted horizontally and vertically to maximize emissions. Maximum emissions were found in the horizontal EUT polarization. This setup was used for all testing in this report.

For maximum permissible exposure, this device operates at less than 1 Watt at 2400 – 2480.0 MHz and can be operated at less than 2.5cm from the body. No testing is required, however worst case calculated exposure compliance follows later in this report.

The EUT is not a hybrid system and FCC 15.247 (f) does not apply to it. However the 15.247 (d) requirement of power density were met and are detailed later in this test report.

Power line conducted emissions were not applicable to the EUT as it runs from the iPod charging slot. iPod cannot be charged while the EUT is connected to it. EUT is purely a battery operated device.

Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



Applicable Standards, Specifications and Methods

ANSI C63.4:2003 - Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

ANSI C63.10:2009 - American national standard for testing unlicensed wireless devices

CFR 47 FCC 15 - Code of Federal Regulations – Radio Frequency Devices

CISPR 22:1997 - Information technology equipment – Radio disturbance characteristics – Limits and methods of measurement

ICES-003:2004 - Digital Apparatus - Spectrum Management and Telecommunications Policy Interference-Causing Equipment Standard

ISO 17025:2005 - General Requirements for the competence of testing and calibration laboratories

RSS 210:2010 - Issue 7: Spectrum Management and Telecommunications Policy. Radio Standards Specification Low Power Licence-Exempt Radiocommunication Devices

Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



Sample calculation(s)

Margin = limit – (received signal + antenna factor + cable loss – pre-amp gain)

Margin = 50.5dBuV/m – (50dBuV + 10dB + 2.5dB – 20dB)

Margin = 8.5 dB

Document Revision Status

Revision 1 - March 21st, 2011 – Initial report release.

Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



Definitions and Acronyms

The following definitions and acronyms are applicable in this report.
See also ANSI C63.14.

AE – Auxillary Equipment.

BW – Bandwidth. Unless otherwise stated, this is refers to the 6 dB bandwidth.

EMC – Electro-Magnetic Compatibility

EMI – Electro-Magnetic Immunity

EUT – Equipment Under Test

ITE – Information Technology Equipment with a primary function(s) of entry, storage, display, retrieval, transmission, processing, switching, or control, of data.

LISN – Line impedance stabilization network

NCR – No Calibration Required

RF – Radio Frequency

Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



Testing Facility

Testing for EMC on the EUT was carried out at Global EMC labs in Toronto, Ontario, Canada. The testing lab consists of a 3m semi-anechoic chamber calibrated to be able to allow measurements on an EUT with a maximum width or length of up to 2m and height up to 3m. The chamber is equipped with a turn table that is capable of testing devices up to 3300lb in weight. This facility is capable of testing products that are rated for 120 Vac and 240Vac single phase, or 208 Vac 3 phase input. DC capability is also available. The chamber is equipped with an antenna mast that controls polarization and height from the control room adjoining the shielded chamber. Radiated emissions measurements are performed using a Bilog, and Horn antenna where applicable. Conducted emissions, unless otherwise stated, are performed using a LISN.

Calibrations and Accreditations

The measurement site used is registered with Federal Communications Commission (FCC) and Industry Canada (IC). This site is calibrated for Normalized Site Attenuation (NSA) using test procedures outlined in ANSI C63.4 “Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz”. The semi-anechoic chamber is lined with ferrite tiles and absorption cones to minimize any undesired reflections. All measuring equipment is calibrated on an annual or bi-annual basis as listed for each respective test.

Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



Testing Environmental Conditions and Dates

Following were the environmental conditions in the facility during time of testing –

Date	Test	Init.	Temperature (°C)	Humidity (%)	Pressure (kPa)
Mar 15 – 18, 2011	All	AM	23 - 26 °C	32%-42%	100.8 -101.6 kPa

Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



Detailed Test Results Section

Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



Spurious Radiated Emissions

Purpose

The purpose of this test is to ensure that the RF energy unintentionally emitted from the EUT does not exceed the limits listed below as defined in the applicable test standard, as measured from a receiving antenna. This helps protect broadcast radio services such as television, FM radio, pagers, cellular telephones, emergency services, and so on, from unwanted interference.

Limit(s) and Method

The limits, as defined in 15.247(d) for unintentional radiated emissions apply for those emissions that fall in the restricted bands, as defined in Section 15.205(a). These emissions must comply with the radiated emission limits specified in Section 15.209(a).

All unintentional emissions must also meet the ‘Spurious Conducted Emissions’ requirements of -20 dBc or greater. See also ‘Spurious Conducted Emissions’ for further details.

30 MHZ – 88 MHz, 100 uV/m (40.0 dBuV/m¹) at 3 m

88 MHz – 216 MHz, 150 uV/m (43.5 dBuV/m¹) at 3 m

216 MHz – 960 MHz, 200 uV/m (46.4 dBuV/m¹) at 3 m

Above 960 MHz, 500 uV/m (54.0 dBuV/m¹) at 3 m

Above 1000 MHz, 500 uV/m (54.0 dBuV/m²) at 3m


¹Limit is with 120 kHz measurement bandwidth and a using a Quasi Peak detector.

²Limit is with 1 MHz measurement bandwidth and using an Average detector, scanned in accordance with 15.33 to above the 10th harmonic.

Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



Typical Radiated Emissions Setup



Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



Measurement Uncertainty

The expanded measurement uncertainty is calculated in accordance with CISPR 16-4-2 and is +/-4.4 dB with a 'k=2' coverage factor and a 95% confidence level.

Preliminary Graphs


Note the graphs shown below are for graphical illustration only. For final measurements with the appropriate detector, please refer to the final measurement table where applicable. The graph shown below is a maximized peak measurement graph, measured with a resolution bandwidth greater than the final required detector and over a full 0-360 rotation. This peaking process is done as a worst case measurement. This process enables the detection of frequencies of concern for final measurement, and provides considerable time savings.

In accordance with FCC Part 15, Subpart A, Section 15.33, the device was scanned to a minimum of a 25 GHz.

Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010




Hi Channel – 30MHz – 1 GHz
Vertical – Peak Emissions Graph



Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010




**Hi Channel – 30MHz – 1 GHz
Horizontal – Peak Emissions Graph**



Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010




**Hi Channel – 1 – 2GHz
Vertical – Peak Emissions Graph**



Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010




**Hi Channel – 1 – 2GHz
Horizontal – Peak Emissions Graph**



Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010




Hi Channel – 2-10 GHz
Vertical – Peak Emissions Graph



Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010




**Hi Channel – 2-10 GHz
Horizontal – Peak Emissions Graph**



Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010




Band Edge – Low channel
Vertical peak emissions



Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010




Band Edge – Low channel
Horizontal peak emissions



Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010




Band Edge – Low channel
Vertical Average emissions



Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010




Band Edge – Low channel
Horizontal Average emissions



Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010




Band Edge – Hi channel
Vertical peak emissions



Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010




Band Edge – Hi channel
Horizontal peak emissions



Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010




Band Edge – Hi channel
Vertical Average emissions



Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



Band Edge – Hi channel
Horizontal Average emissions



Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



Final Measurements

Note:

1. In accordance with 15.247(d), only radiated emissions exceeding the 15.209 limit that occur within the bands listed in 15.205, need to be verified with a quasi-peak detector or an average detector.
2. Hi channel had the worst case emissions and results are documented below in the test report.

The requirement of -20dBc is verified by the conducted method; please see 'Spurious Antenna Conducted Emissions' section of this report.

Some of the frequencies shown on the peak graph do not fall within a restricted band as listed in FCC 15.205 and does not need to be verified.

For information purposes, the fundamental was measured to be 98.8 dBuV/m at 3 meters, and none of the unintentional radiated emissions that fall outside of the restricted bands exceeded the -20dBc requirement.

The following measurements were made at the harmonics shown in the above graphs.

See 'Spurious Antenna Conducted Emissions' measurements for -20 dBc requirements.

Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



Radiated Emissions Measurements

Test Frequency (MHz)	Detection mode (Q-Peak)	Antenna polarity (Horz/Vert)	Raw signal dB(µV)	Antenna factor dB	Cable loss dB + Preselecor	Attenuator dB	Pre-Amp Gain dB	Received signal dB(µV/m)	Emission limit dB(µV/m)	Margin dB(µV)	Result
Low Channel Board Hoz											
2402	Peak	Vert	97.9	31.5	2.2	0.0	36.0	95.6			PASS
2402	Avg	Vert	95.8	31.5	2.2	0.0	36.0	93.5			PASS
2402	Peak	Horz	97.7	31.5	2.2	0.0	36.0	95.4			PASS
2402	Avg	Horz	94.2	31.5	2.2	0.0	36.0	91.9			PASS
2390	Peak	Horz	47.3	31.5	2.2	0.0	36.0	45.0	74.0	29.0	PASS
2390	Avg	Horz	35.4	31.5	2.2	0.0	36.0	33.1	54.0	20.9	PASS
2390	Peak	Vert	47.1	31.5	2.2	0.0	36.0	44.8	74.0	29.2	PASS
2390	Avg	Vert	35.7	31.5	2.2	0.0	36.0	33.4	54.0	20.6	PASS
4808	Peak	Horz	49.3	32.4	2.9	0.0	36.0	48.6	74.0	25.4	PASS
4804	Avg	Horz	36.5	32.4	2.9	0.0	36.0	35.8	54.0	18.2	PASS
4804	Peak	Vert	50.0	32.4	2.9	0.0	36.0	49.3	74.0	24.7	PASS
4804	Avg	Vert	39.9	32.4	2.9	0.0	36.0	39.2	54.0	14.8	PASS
Mid Channel											
2445	Peak	Vert	98.3	31.5	5.0	0.0	36.0	98.8			PASS
2445	Avg	Vert	95.7	31.5	5.0	0.0	36.0	96.2			PASS
2445	Peak	Horz	95.0	31.5	5.0	0.0	36.0	95.5			PASS
2445	Avg	Horz	92.5	31.5	5.0	0.0	36.0	93.0			PASS
4884	Peak	Horz	47.7	32.4	6.5	0.0	36.0	50.6	74.0	23.4	PASS
4890	Avg	Horz	36.0	32.4	6.5	0.0	36.0	38.9	54.0	15.1	PASS
4890	Peak	Vert	50.7	32.4	6.5	0.0	36.0	53.6	74.0	20.4	PASS

Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



4890	Avg	Vert	39.2	32.4	6.5	0.0	36.0	42.1	54.0	11.9	PASS
Hi Channel											
2477	Peak	Vert	95.3	31.5	5.0	0.0	36.0	95.8			PASS
2475	Avg	Vert	93.0	31.5	5.0	0.0	36.0	93.5			PASS
2475	Peak	Horz	96.4	31.5	5.0	0.0	36.0	96.9			PASS
2475	Avg	Horz	93.9	31.5	5.0	0.0	36.0	94.4			PASS
2483.5	Peak	Horz	63.3	31.5	5.0	0.0	36.0	63.8	74.0	10.2	PASS
2483.5	Avg	Horz	50.9	31.5	5.0	0.0	36.0	51.4	54.0	2.6	PASS
2483.5	Peak	Vert	62.6	31.5	5.0	0.0	36.0	63.1	74.0	10.9	PASS
2483.5	Avg	Vert	50.8	31.5	5.0	0.0	36.0	51.3	54.0	2.7	PASS
4956	Peak	Horz	48.6	32.4	6.5	0.0	36.0	51.5	74.0	22.5	PASS
4956	Avg	Horz	32.0	32.4	6.5	0.0	36.0	34.9	54.0	19.1	PASS
4954	Peak	Vert	48.5	32.4	6.5	0.0	36.0	51.4	74.0	22.6	PASS
4954	Avg	Vert	37.0	32.4	6.5	0.0	36.0	39.9	54.0	14.1	PASS

Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



Test Equipment List

Equipment	Model No.	Manufacturer	Last calibration date	Next calibration due date	Asset #
IFR Spectrum Analyzer	AN940	IFR	12/29/2009	12/29/2011	GEMC 6350
BiLog Antenna	3142-C	ETS	2011-01-17	2013-01-17	GEMC 136
Attenuator 3 dB	FP-50-3	Trilithic	NCR	NCR	GEMC 40
Chase Preamp 9kHz - 2 GHz	CPA9231A	Chase	8/25/2010	8/25/2012	GEMC 6403
Q-Par 1.5-18 GHz Horn	6878/24	Q-par	8/25/2010	8/25/2012	GEMC 65
1-26G pre-amp	HP 8449B	HP	8/25/2010	8/25/2012	GEMC 68
RF Cable 7m	LMR-400-7M-50OHM-MN-MN	LexTec	NCR	NCR	GEMC 28
RF Cable 1m	LMR-400-1M-50OHM-MN-MN	LexTec	NCR	NCR	GEMC 29
RF Cable 0.5M	LMR-400-0.5M-50OHM-MN-MN	LexTec	NCR	NCR	GEMC 31

This report module is based on GEMC template "FCC - 15.209 - Radiated Emissions_Rev1.doc"

Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



6dB Bandwidth of Digitally Modulated Systems

Purpose

The purpose of this test is to ensure that the bandwidth occupied exceeds a stated minimum. This helps ensure the utilization of the frequency allocation is sufficiently wide. This also helps prevent corruption of data by ensuring adequate data separation to distinguish the reception of the intended information.

Limits

Systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz. This should be measured with a 100 kHz RBW and a 300 kHz VBW.

Results

The EUT passed. The 6 dB BW measured was 1.819 MHz.


Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



Graph(s)

The graphs shown below show the channel spacing during the operation of the device. This is measured by a max hold on the spectrum analyzer. This measurement is a peak measurement. Max hold is performed for a duration of not less then 1 minute.


Low Channel



Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010




Medium Channel



Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



High Channel




Note: See 'Appendix B – EUT & Test Setup Photographs' for photos showing the test set-up.

Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010




20 db Bandwidth for Low channel



Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



20 db Bandwidth for Mid channel



Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



20 db Bandwidth for Hi channel



Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



Test Equipment List

Equipment	Model No.	Manufacturer	Last calibration date	Next calibration due date	Asset #
Attenuator 20 dB	FP-50-20	Trilithic	NCR	NCR	GEMC 43
IFR Spectrum Analyzer	AN940	IFR	12/29/2009	12/29/2011	GEMC 6350
RF Cable 0.5M	LMR-400-0.5M-50OHM-MN-MN	LexTec	NCR	NCR	GEMC 31
RF Cable 1m	LMR-400-1M-50OHM-MN-MN	LexTec	NCR	NCR	GEMC 29
Power Attenuator 20 dB	25-A-FFN-20	Bird / Hutton	NCR	NCR	GEMC 49

This report module is based on GEMC template "FCC – Power Line Conducted Emissions Class B_Rev1"

Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



Maximum Peak Envelope Conducted Power

Purpose

The purpose of this test is to ensure that the maximum power conducted to the radiating element does not exceed the limits specified. This ensures that if the end-user replaces the antenna, that the maximum power does not exceed an amount which may create an excessive power level.

Limits

The limits are defined in 15.247(b).

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands, the peak limit is 1 watt.

Results

The EUT passed. The peak power measured was -1.6 dbm (0.69 mW).

Sample –

A 10db pad was used in these measurements. A worst case reading was recorded on Hi channel.

$-11.6 \text{ dbm} + 10\text{db} = -1.6 \text{ dbm}$.

Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



Table(s)

The tables shown below shows the peak power output of the device during the antenna conducted measurement during transmit operation of the EUT.


Lo Channel



Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010




Mid channel



Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



Hi Channel



Note: See 'Appendix B – EUT & Test Setup Photographs' for photos showing the test set-up.

Test Equipment List

Equipment	Model No.	Manufacturer	Last calibration date	Next calibration due date	Asset #
IFR Spectrum Analyzer	AN940	IFR	12/29/2009	12/29/2011	GEMC 6350
BiLog Antenna	3142-C	ETS	01/17/2011	01/17/2013	GEMC 137
RF Cable 1m	LMR-400-1M-50OHM-MN-MN	LexTec	NCR	NCR	GEMC 29
Power Attenuator 10 dB	25-A-FFN-10	Bird / Hutton	NCR	NCR	GEMC 49

This report module is based on GEMC template "FCC – Power Line Conducted Emissions Class B_Rev1"

Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



Antenna Spurious Conducted Emissions (- 20 dbc Requirement)

Purpose

The purpose of this test is to ensure that the maximum power conducted to the radiating element at frequencies outside of the authorized spectrum does not exceed the limits specified. This ensures that the only the intended signal is delivered to the radiating element.

Limits

The limits are defined in 15.247(d). In any 100 kHz band, the peak spurious harmonics emissions must be at least 20 dB below the fundamental. Spurious Conducted emissions are to be evaluated up to the 10th harmonic. This -20 dBc requirement also applies at the 'band edge' or 2.4 GHz and 2.4835 GHz.

Results

The EUT passed the limits. Low, middle and high band was measured. The worst case for each mode is presented as a graph for the spectrum. The -20 dBc requirement is shown for the lower band edge at 2.4 GHz in the low band. The -20 dBc requirement is also shown for the higher band edge at 2.4835 GHz in the high band.


Graph(s)

The graphs shown below shows the peak power output of the device during the antenna conducted measurement during transmit operation of the EUT.

Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010




9 kHz – 2.5 GHz Lo



Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010




9kHz – 2.5 GHz Mid



Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010




9 kHz – 2.5 GHz Hi



Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



2 GHz – 22.5 GHz Lo



Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010




2 GHz – 22.5 GHz Mid



Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



2 GHz – 22.5 GHz Hi



Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010




2483.5 MHz Band edge



Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



2400 MHz Band edge



Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



The frequency range of 22.5 – 25 GHz, the 10th harmonic and 9th harmonic where applicable, was additionally scanned using an alternate spectrum analyzer, in low, middle and high band for each mode. No emissions were detected at the 9th and 10th harmonic.

The plots show raw data and no correction factors are applied. They simply show a 20dbc differential between the peak and the band edge

Note: See 'Appendix B – EUT & Test Setup Photographs' for photos showing the test set-up.

Test Equipment List

Equipment	Model No.	Manufacturer	Last calibration date	Next calibration due date	Asset #
Attenuator 1 dB	FP-50-1	Trilithic	NCR	NCR	GEMC 38
Attenuator 3 dB	FP-50-3	Trilithic	NCR	NCR	GEMC 40
Attenuator 6 dB	FP-50-6	Trilithic	NCR	NCR	GEMC 41
Attenuator 10 dB	FP-50-10	Trilithic	NCR	NCR	GEMC 42
Attenuator 20 dB	FP-50-20	Trilithic	NCR	NCR	GEMC 43
Spectrum Analyzer	AN940	IFR	Dec 29, 2009	Dec 29, 2011	GEMC 6350
RF Cable 1m	LMR-400-1M-50OHM-MN-MN	LexTec	NCR	NCR	GEMC 29
Power Attenuator 20 dB	25-A-FFN-20	Bird / Hutton	NCR	NCR	GEMC 49

This report module is based on GEMC template "FCC – Power Line Conducted Emissions Class B_Rev1"

Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



Power Spectral Density

Purpose

The purpose of this test is to ensure that the maximum power spectral density to the radiating element does not exceed the limits specified. This ensures that the modulation is significantly wide enough, or low enough in power that it will allow for co-operation of other wireless devices operating within this frequency allocation.

Limits

The limits are defined in 15.247(e).

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

Results

The EUT passed. Each mode was tested at low, medium, and high band. The worst case value is -17.7 dbm {-27.7 + 10 db (attenuator) = -17.7 dbm}.


Graph(s)

The graphs shown below show the power spectral density of the device during the conducted measurement operation of the EUT. Low, middle, and high channel was investigated in each mode.

Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010




Low channel



Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010




Mid channel



Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



High channel



Note: See 'Appendix B – EUT & Test Setup Photographs' for photos showing the test set-up.

Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



Test Equipment List

Equipment	Model No.	Manufacturer	Last calibration date	Next calibration due date	Asset #
Spectrum Analyzer	AN940	IFR	Dec 29, 2009	Dec 29, 2011	GEMC 6350
RF Cable 1m	LMR-400-1M-50OHM-MN-MN	LexTec	NCR	NCR	GEMC 29
Power Attenuator 20 dB	25-A-FFN-20	Bird / Hutton	NCR	NCR	GEMC 49

This report module is based on GEMC template "FCC – Power Line Conducted Emissions Class B_Rev1"

Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



Maximum Permissible Exposure

Purpose

The purpose of this test is to ensure that the RF energy intentionally transmitted, in terms of power density emitted from the EUT at a stated operating distance does not exceed the limits listed below as defined in the applicable test standard, as calculated based upon readings obtained during testing. This helps protect human exposure to excessive RF fields.

Limit(s) and Method

The limits, as defined in FCC 15.247(i) and FCC 1.1310 Table 1 (B) limits for general public exposure was applied. The limit for the frequency range of 1.5 GHz to 100 GHz was applied. This is a limit of 1.0 mW/ cm². The distance used for calculations was 1cm, as this unit could be body worn in the end use.

Results

The EUT passed the requirements. The worst case calculated power density was 0.087 mW/cm², this is significantly under the 1.0 mW/cm² requirement.

Calculations

Method 1 (conducted power)

$$P_d = (P_t * G) / (4 * \pi * R^2)$$

Where Pt = -1.6 dbm or 0.69mW as per Peak power conducted output

Where G = 2.0 dBi, or numerically 1.58

Where R = 1 cm

$$P_d = (0.69 \times 1.58) / (4 \times \pi \times 1\text{cm}^2)$$

$$P_d = 1.09 \text{ mW} / 12.56 \text{ cm}^2$$

$$P_d = 0.087 \text{ mW/cm}^2$$

Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



Appendix A – EUT Summary

General EUT Description

EUT Details	
Manufacturer	Sonavox Audio Solutions
EUT Model number	WTX1015
Equipment Category	Wireless module for audio applications.
Basic EUT Functionality	WTX1015 is a wireless audio transmitter for iPod devices.
Input Voltage and Frequency	5 Vdc
Connectors available on EUT	None. A SMA connector was soldered on the EUT for conducted testing.
Peripherals Required for Test	None.
Release type	Final
Intentional Radiator Frequency	2400 – 2477.0 MHz

Note the EUT is considered to have been received the date of the commencement of the first test, unless otherwise stated. For a close-up picture of the EUT, see 'Appendix B – EUT & Test Setup Photographs'.

Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



Appendix B – EUT and Test Setup Photographs

Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



Figure 1 – Radiated emission setup

Client	Sonavox Audio Solution
Product	Wireless Audio Transceiver Module – WTX1015
Standard(s)	RSS 210 Issue 8:2010 / FCC Part 15 Subpart C 15:2010



Figure 2 – Conducted power output setup

Note: These photos are for information purposes only. Also refer to PDF files that are separate from this test report.