





**BUREAU
VERITAS**

Curtis-Straus LLC, a wholly owned subsidiary of BV CPS

Test Report

Report No	EL0240-1
Client	AirPointe of New Hampshire
Address	35E Industrial Way Suite 101 Rochester, NH 03867
Phone	603-994-2200
Items tested FCC ID FRN	Sushi 433 WUS00036 0018228197
Equipment Type Equipment Code	Part 15 Security/Remote Control Transmitter DSC
FCC Rule Parts	47 CFR 15.231(e)
Test Dates	April 21, 2011
Results	As detailed within this report
Prepared by	 Tuyen Truong – Test Engineer
Authorized by	 Mairaj Hussain – EMC Supervisor
Issue Date	4/22/2011
Conditions of Issue	This Test Report is issued subject to the conditions stated in the 'Conditions of Testing' section on page 9 of this report.

Curtis-Straus LLC is accredited by the American Association for Laboratory Accreditation for the specific scope of accreditation under Certificate Number 1627-01. This report may contain data which is not covered by the A2LA accreditation.



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



Contents

Contents.....	2
Summary.....	3
Test Methodology.....	3
Product Tested - Configuration Documentation	4
Test Results	5
Fundamental Emission.....	5
Harmonics and Spurious Emissions.....	6
Measurement Uncertainty.....	8
Conditions Of Testing.....	9

Form Final Report REV 7-20-07 (DW)



Summary

This test report supports an application for class II permissive change of a transmitter operating pursuant to 47 CFR 15.231(e). The product is the Sushi 433. The operating frequency is 433.9MHz. It is powered by +3VDC coin cell batteries. Fresh batteries were used during all testing. Line Conducted Emissions was not performed.

Class II permissive change is requested due to the enclosure's change. Please see attached class II permissive change request letter for more details.

We found that the product met the above requirements without modification. The test sample was received in good condition.

Test Methodology

Testing was performed according to ANSI C63.4-2009 and ANSI C63.10-2009. Radiated emissions were maximized by rotating the device around its three orthogonal axes, as well as varying the test antenna's height and polarity. The EUT's antenna cannot be maximized separately. Only fundamental and spurious emissions were checked.

Frequency range investigated: 30MHz – 1000MHz

Measurement distance: 3m

This device has no receiver portion.

Release Control Record

Issue No.	Reason for change	Date Issued
1	Original Release	May 2, 2011



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-8828



page 3 of 10

Product Tested - Configuration Documentation

EUT Configuration																																	
Work Order: L0240 Company: airPointe Company Address: 35E Industrial Way Rochester, NH 03867 Contact: Don Proulx Person Present: Don Proulx																																	
MN						SN																											
EUT: Sushi 433						sample 1																											
EUT Description: Sushi 433 - Active RFID Tag																																	
EUT TX Frequency: 433.92 MHz																																	
Support Equipment:						MN																											
None																																	
EUT Ports:																																	
<table border="1"> <thead> <tr> <th>Port Label</th> <th>Port Type</th> <th>No. of ports</th> <th>No. Populated</th> <th>Cable Type</th> <th>Shielded</th> <th>Ferrites</th> <th>Length</th> <th>Max Length</th> <th>In/Out NEBS Type</th> <th>Unpopulated Reason</th> </tr> </thead> <tbody> <tr> <td colspan="11">None</td> </tr> </tbody> </table>												Port Label	Port Type	No. of ports	No. Populated	Cable Type	Shielded	Ferrites	Length	Max Length	In/Out NEBS Type	Unpopulated Reason	None										
Port Label	Port Type	No. of ports	No. Populated	Cable Type	Shielded	Ferrites	Length	Max Length	In/Out NEBS Type	Unpopulated Reason																							
None																																	
Software / Operating Mode Description:																																	
EUT is transmitting 433.92 MHz signal every 10 seconds.																																	

Test Results**Fundamental Emission****LIMIT**

Fundamental Frequency	Field Strength of Fundamental (microvolts/meter)	Field Strength of Spurious Emission (microvolts/meter)
433.9MHz	1,500 to 5,000	150 to 500
[15.231(e)]		

Average Limit[dBμV/m] = $20\log(16.6667(F[\text{in MHz}]) - 2833.3333) @ 3\text{m}$

Example Calculation: $20\log(16.6667(433.9) - 2833.3333) = 72.9\text{dB}\mu\text{V/m} @ 3\text{m}$

MEASUREMENT

Radiated Emissions Table											
Date: 21-Apr-11			Company: Airpointe			Work Order: L0240					
Engineer: Tuyen Truong			EUT Desc: Sushi433			EUT Operating Voltage/Frequency: 3V Battery					
Temp: 25°C			Humidity: 21%			Pressure: 1015 mBar					
Frequency Range: 433.9 MHz							Measurement Distance: 3 m				
Notes: Duty cycle correction factor is 21.1							Peak Limit = Average Limit + 20dB				
Average reading = Peak reading - Duty cycle correction factor							Duty cycle correction factor = 20*log(8.81/100)				
							EUT Max Freq: 433.9 MHz				
Antenna Polarization (H / V)	Frequency (MHz)	Reading (dBµV)	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Adjusted Reading (dBµV/m)	FCC 15.231(e)				
							Limit (dBµV/m)	Margin (dB)	Result (Pass/Fail)		
EUT is in X-orientation											
v, peak	433.9	82.8	25.4	16.5	1.4	75.3	92.9	-17.6	Pass		
v, average	433.9	61.7	25.4	16.5	1.4	54.2	72.9	-18.7	Pass		
h, peak	433.9	94.2	25.4	16.5	1.4	86.7	92.9	-6.2	Pass		
h, average	433.9	73.1	25.4	16.5	1.4	65.6	72.9	-7.3	Pass		
EUT is in Y-orientation											
v, peak	433.9	92.6	25.4	16.5	1.4	85.1	92.9	-7.8	Pass		
v, average	433.9	71.5	25.4	16.5	1.4	64.0	72.9	-8.9	Pass		
h, peak	433.9	84.4	25.4	16.5	1.4	76.9	92.9	-16.1	Pass		
h, average	433.9	63.3	25.4	16.5	1.4	55.8	72.9	-17.2	Pass		
EUT is in Z-orientation											
v, peak	433.9	88.9	25.4	16.5	1.4	81.4	92.9	-11.5	Pass		
v, average	433.9	67.8	25.4	16.5	1.4	60.3	72.9	-12.6	Pass		
h, peak	433.9	89.2	25.4	16.5	1.4	81.7	92.9	-11.2	Pass		
h, average	433.9	68.1	25.4	16.5	1.4	60.6	72.9	-12.3	Pass		
Table Result: Pass by -6.2 dB											
Worst Freq: 433.9 MHz											
Test Site: EMI Chamber 1			Cable 1: Asset #1505			Cable 2: Asset #1507					
Analyzer: G91rl			Preamp: Red-White			Antenna: Red-Black					

Rev: 14-Apr-2011

Spectrum Analyzers / Receivers / Preselectors

Gold

Range
100Hz-26.5 GHzMN
E4407BMfr
AgilentSN
MY45113816Asset
1284Cat
ICalibration Due
9-May-2011**Radiated Emissions Sites**

EMI Chamber 1

FCC Code
719150IC Code
2762A-6VCCI Code
R-3032, G-106Cat
ICalibration Due
12-Mar-2013**Preamps / Couplers Attenuators / Filters**

Red-White

Range
0.009-2000MHzMN
ZFL-1000-LNMfr
CSSN
N/AAsset
1258Cat
IICalibration Due
21-Mar-2012**Antennas**

Red-Black Bilog

Range
30-2000MHzMN
JB1Mfr
SunolSN
A091604-2Asset
1106Cat
ICalibration Due
3-Dec-2012**Cables**Asset #1505
Asset #1508Range
9kHz - 18GHz
9kHz - 18GHzMfr
Florida RF
Florida RFCat
II
IICalibration Due
18-Aug-2011
9-Apr-2012**Meteorological Meters**

CHAMBER1 Thermohygrometer

MN
35519-044Mfr
Control CompanySN
72457642Asset
1345Cat
IICalibration Due
18-Aug-2011

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS

One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-



page 5 of 10

Harmonics and Spurious Emissions

LIMIT

<i>Fundamental Frequency</i>	<i>Field Strength of Fundamental (microvolts/meter)</i>	<i>Field Strength of Spurious Emission (microvolts/meter)</i>
260 - 470 MHz	1,500 to 5,000	150 to 500

[15.231(e)]

Average Limit[dBμV/m] = $20\log(16.6667(F[\text{in MHz}]) - 2833.3333) - 20$ @ 3m

Example Calculation: $20\log(16.6667(433.9) - 2833.3333) - 20 = 72.9\text{dB}\mu\text{V/m}$ @ 3m

MEASUREMENTS

Radiated Emissions Table												
Date: 02-May-11			Company: Airpointe			Work Order: K1259						
Engineer: Matthew Burman			EUT Desc: Sushi433			EUT Operating Voltage/Frequency: 3V Battery						
Temp: 22.9°C			Humidity: 21%			Pressure: 1020mBar						
Frequency Range: 30-1000MHz						Measurement Distance: 3 m						
Notes: peak readings						EUT Max Freq: 433.9MHz						
Antenna Polarization (H / V)	Frequency (MHz)	Reading (dBuV)	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Adjusted Reading (dBuV/m)	FCC Class B					
							Limit (dBuV/m)	Margin (dB)	Result (Pass/Fail)	Limit (dBuV/m)	Margin (dB)	Result (Pass/Fail)
H - nf	122.2	25.1	25.3	13.9	0.9	14.6	---	---	---	43.5	-28.9	Pass
V - nf	153.7	23.4	25.4	12.2	0.9	11.1	---	---	---	43.5	-32.4	Pass
H - nf	420.4	21.9	25.3	16.2	1.4	14.2	---	---	---	46.0	-31.8	Pass
H - nf	466.5	21.0	25.1	17.2	1.5	14.6	---	---	---	46.0	-31.4	Pass
H - nf	515.0	21.0	25.1	17.7	1.6	15.2	---	---	---	46.0	-30.8	Pass
H - nf	614.4	21.5	25.2	18.8	1.8	16.9	---	---	---	46.0	-29.2	Pass
Table Result: Pass by -28.9 dB						Worst Freq: 122.2 MHz						
Test Site: EMI Chamber 1			Cable 1: Asset #1505			Cable 2: Asset #1507			Cable 3: ---			
Analyzer: Asset #1328			Preamp: Red-White			Antenna: Red-Black			Preselector: ---			

Restricted Bands of Operation												
Date: 02-May-11			Company: Airpointe						Work Order: K1259			
Engineer: Matthew Burman			EUT Desc: Sushi433						EUT Operating Voltage/Frequency: 3V Battery			
Temp: 22.9°C			Humidity: 21%						Pressure: 1020mBar			
Measurement Distance: 3 m												
Notes:												
Antenna Polarization (H / V)	Frequency (MHz)	Reading (dBuV)	Preamp Factor (dB)	Antenna Factor (dB/m)	Cable Factor (dB)	Adjusted Reading (dBuV/m)	---			FCC Class B		
							Limit (dBuV/m)	Margin (dB)	Result (Pass/Fail)	Limit (dBuV/m)	Margin (dB)	Result (Pass/Fail)
H peak - nf	410.0	22.8	25.1	15.9	1.4	15.0	---	---	---	46.0	-31.0	Pass
Table Result:						Pass	by	-31.0 dB	Worst Freq: 410.0 MHz			
Test Site: EMI Chamber 1			Cable 1: Asset #1505			Cable 2: Asset #1507			Cable 3: ---			
Analyzer: Asset #1328			Preamp: Red-White			Antenna: Red-Black			Preselector: ---			



Rev: 21-Apr-2011

Spectrum Analyzers / Receivers / Preselectors							
SA EMI Chamber (1328)	Range 9kHz-13.2 GHz	MN E4405B	Mfr Agilent	SN MY44210241	Asset 1328	Cat I	Calibration Due 4-Mar-2012
Radiated Emissions Sites							
EMI Chamber 1	FCC Code 719150	IC Code 2762A-6	VCCI Code R-3032, G-106			Cat I	Calibration Due 12-Mar-2013
Preamps / Couplers Attenuators / Filters							
Red-White	Range 0.009-2000MHz	MN ZFL-1000-LN	Mfr CS	SN N/A	Asset 1258	Cat II	Calibration Due 21-Mar-2012
Antennas							
Red-Black Bilog	Range 30-2000MHz	MN JB1	Mfr Sunol	SN A091604-2	Asset 1106	Cat I	Calibration Due 3-Dec-2012
Meteorological Meters							
Temp./Humidity/Atm. Pressure Gauge		MN 7400 Perception II	Mfr Davis	SN N/A	Asset 965	Cat I	Calibration Due 4-Apr-2013
CHAMBER1 Thermohygrometer		35519-044	Control Company	72457642	1345	II	18-Aug-2011
Cables							
Asset #1505	Range 9kHz - 18GHz		Mfr Florida RF			Cat II	Calibration Due 18-Aug-2011
Asset #1507	9kHz - 26.5GHz		Florida RF			II	18-Jan-2012

All equipment is calibrated using standards traceable to NIST or other nationally recognized calibration standard.

Note: 15.231(b)(3) states “*Spurious emissions shall be attenuated to the average...limits shown in this table [15.231(e)] or to the general limits shown in Section 15.209, whichever limit permits a higher field strength.*” Since the emissions above 1GHz meet the 15.209 limits, those limits are displayed in the data table to show worst case.



Measurement Uncertainty

The listed uncertainties are the worst case uncertainty for the entire range of measurement. Please note that the uncertainty values are provided for informational purposes only and are not used in determining the PASS/FAIL results.

Measurement	Expanded Uncertainty k=2	Maximum allowable uncertainty
Radiated Emissions (30-1000MHz)		
NIST	5.6dB	N/A
CISPR	4.6dB	5.2dB (Ucisprr)
Radiated Emissions (1-26.5GHz)	4.6dB	N/A
Radiated Emissions (above 26.5GHz)	4.9dB	N/A
Magnetic Radiated Emissions	5.6dB	N/A
Conducted Emissions		
NIST	3.9dB	N/A
CISPR	3.6dB	3.6dB (Ucisprr)
Telco Conducted Emissions (Current)	2.9dB	N/A
Telco Conducted Emissions (Voltage)	4.4dB	N/A
Electrostatic Discharge	11.5%	N/A
Radiated RF Immunity (Uniform Field)	1.6dB	N/A
Electrical Fast Transients	23.1%	N/A
Surge	23.1%	N/A
Conducted RF Immunity	3dB	N/A
Magnetic Immunity	12.8%	N/A
Dips and Interrupts	2.3V	N/A
Harmonics	3.5%	N/A
Flicker	3.5%	N/A
Radio frequency (@ 2.4GHz)	3.23×10^{-8}	1×10^{-7}
RF power, conducted	0.40dB	0.75dB
Maximum frequency deviation:		
• Within 300Hz and 6kHz of audio frequency / Within 6kHz and 25kHz of audio frequency	3.4% 0.3dB	5% 3dB
Adjacent channel power	1.9dB	3dB
Conducted spurious emission of transmitter, valid up to 12.75GHz	2.39dB	3dB
Conducted emission of receivers	1.3dB	3dB
Radiated emission of transmitter, valid up to 26.5GHz	3.9dB	6dB
Radiated emission of transmitter, valid up to 80GHz	3.3dB	6dB
Radiated emission of receiver, valid up to 26.5GHz	3.9dB	6dB
Radiated emission of receiver, valid up to 80GHz	3.3dB	6dB
Humidity	2.37%	5%
Temperature	0.7 °C	1.0 °C
Time	4.1%	10%
RF Power Density, Conducted	0.4dB	3dB
DC and low frequency voltages	1.3%	3%
Voltage (AC, <10kHz)	1.3%	2%
Voltage (DC)	0.62%	1%
The above reflects a 95% confidence level		



Conditions Of Testing

[Bureau Veritas Consumer Products Services, Inc., a Massachusetts corporation], and/or its affiliates (collectively, the "Company") will conduct, at the request of the Submitter ("Client"), the tests specified on the submitted Test Request Form or equivalent in accordance with, and subject to, the following terms and conditions (collectively, "Conditions"):

1. All orders for tests are subject to acceptance by the Company, and no order will constitute a binding commitment of the Company unless and until such order is accepted by it, as evidenced by the issuance of a written report ("Test Report") by the Company. The Test Report is issued solely by the Company, is intended for the exclusive use of Client and shall not be published, used for advertising purposes, copied or replicated for distribution to any other person or entity or otherwise publicly disclosed without the prior written consent of the Company. By submitting a request for services to the Company, Client consents to the disclosure to accreditation bodies of those records of Client relevant to the accreditation body's assessment of the Company's competence and compliance with relevant accreditation criteria. The Company shall not be liable for any loss or damage whatsoever resulting from the failure of the Company to provide its services within any time period for completion estimated by the Company. If Client anticipates using the Test Report in any legal proceeding, arbitration, dispute resolution forum or other proceeding, it shall so notify the Company prior to submitting the Test Report in such proceeding. The Company has no obligation to provide a fact or expert witness at such proceeding unless the Company agrees in advance to do so for a separate and additional fee.
2. The Test Report will set forth the findings of the Company solely with respect to the test samples identified therein. Unless specifically and expressly indicated in the Test Report, the results set forth in such Test Report are not intended to be indicative or representative of the quality or characteristics of the lot from which a test sample is taken, and Client shall not rely upon the Test Report as being so indicative or representative of the lot or of the tested product in general. The Test Report will reflect the findings of the Company at the time of testing only, and the Company shall have no obligation to update the Test Report after its issuance. The Test Report will set forth the results of the tests performed by the Company based upon the written information provided to the Company. The Test Report will be based solely on the samples and written information submitted to the Company by Client, and the Company shall not be obligated to conduct any independent investigation or inquiry with respect thereto.
3. The Company may, in its sole discretion, destroy samples which have been furnished to the Company for testing and which have not been destroyed in the course of testing. The Company may delegate the performance of all or a portion of the services contemplated hereunder to an affiliate, agent or subcontractor of the Company, and Client consents to such delegation.
4. These Conditions and the Test Report represent the entire understanding of the parties hereto with respect to the subject matter hereof and of the Test Report, and no modification, variance or extrapolation with respect thereto shall be permitted without the prior written consent of the Company.
5. The names, service marks, trademarks and copyrights of the Company and its affiliates, including the names "BUREAU VERITAS," "BUREAU VERITAS CONSUMER PRODUCTS SERVICES," "BVCPS," "MTL," "ACTS," "MTL-ACTS" and "CURTIS-STRAUS" (collectively, the "Marks") are and shall remain the sole property of the Company or its affiliates and shall not be used by Client except solely to the extent that Client obtains the prior written approval of the Company and then only in the manner prescribed by the Company. Client shall not contest the validity of the Marks or take any action that might impair the value or goodwill associated with the Marks or the image or reputation of the Company or its affiliates.
6. Payment in full shall be due 30 days after the date of invoice. Interest shall be due on overdue amounts from the due date until paid at an interest rate of 1.5% per month or, if less, the maximum rate permitted by law. The Company reserves the right, at any time and from time to time, to revoke any credit extended to Client. Client shall reimburse the Company for any costs it incurs in collecting past due amounts, including court costs and fees and expenses of attorneys and collection agencies. The Test Report may not be used or relied upon by Client if and for so long as Client fails to pay when due any invoice issued by the Company or any affiliate of it to Client or any affiliate or subsidiary of Client together with interest and penalties, if any, accrued thereon.
7. The Company disclaims any and all responsibility or liability arising out of or in connection with e-mail transmissions of such information.
8. Client understands and agrees that the Company is neither an insurer nor a guarantor, that the Company does not take the place of Client or any designer, manufacturer, agent, buyer, distributor or transportation or shipping company, and that the Company disclaims all liability in such capacities. Client further understands that if it seeks assurance against loss or damage, it should obtain appropriate insurance.
9. Client agrees that the Company, by providing the services, does not take the place of Client nor any third party, nor does the Company release them from any of their obligations, nor does the Company otherwise assume, abridge, abrogate or undertake to discharge any duty of any third party to Client or any duty of Client or any third party to any other third party, and Client will not release any third party from its obligations and duties with respect to the tested goods.
10. Client shall, on a timely basis, (a) provide adequate instructions to the Company in order to enable the Company to perform properly its services, (b) provide, or cause Client's suppliers and contractors to provide, the Company with all documents necessary to enable the Company to perform its services, (c) furnish the Company with all relevant information regarding Client's intended use and purposes of the tested goods, (d) advise the Company of essential dates and deadlines relevant to the tested goods and (e) fully exercise all rights and remedies available to Client against third parties in respect of the tested goods.
11. The Company shall undertake due care and ordinary skill in the performance of its services to Client, and the Company shall accept responsibility only where such skill has not been exercised and, even in such event, only to the extent of the limitation of liability set forth herein.
12. If Client desires to assert a claim arising from or relating to (i) the performance, purported performance or non-performance of any services by the Company or (ii) the sale, resale, manufacture, distribution or use of any tested goods, it must submit that claim to the Company in a writing that sets forth with particularity the basis for such claim within 60 days from discovery of the potential claim and not more than six months after the date of issuance of the Test Report to Client. Client waives any and all such claims including, without limitation, claims that the Test Report is inaccurate, incomplete or misleading or that additional or different testing is required, unless and then only to the extent that Client submits a written claim to the Company within both such time periods.
13. CLIENT SHALL, EXCEPT TO THE EXTENT OF COMPANY'S LIABILITY TO CLIENT HEREUNDER (WHICH IN NO EVENT SHALL EXCEED THE LIMITATION OF LIABILITY HEREIN), HOLD HARMLESS AND INDEMNIFY THE COMPANY, ITS AFFILIATES AND THEIR RESPECTIVE DIRECTORS, OFFICERS, EMPLOYEES, AGENTS AND SUBCONTRACTORS AGAINST



Curtis-Straus LLC, a wholly owned subsidiary of BV CPS
One Distribution Center Circle, #1 • Littleton, MA • TEL (978) 486-8880 • FAX (978) 486-



ALL ACTUAL OR ALLEGED THIRD PARTY CLAIMS FOR LOSS, DAMAGE OR EXPENSE OF WHATSOEVER NATURE AND HOWSOEVER ARISING FROM OR RELATING TO (i) THE PERFORMANCE, PURPORTED PERFORMANCE OR NON-PERFORMANCE OF ANY SERVICES BY THE COMPANY OR (ii) THE SALE, RESALE, MANUFACTURE, DISTRIBUTION OR USE OF ANY TESTED GOODS.

14. EXCEPT AS MAY OTHERWISE BE EXPRESSLY AGREED TO IN WRITING BY THE COMPANY AND NOTWITHSTANDING ANY PROVISION TO THE CONTRARY CONTAINED HEREIN OR IN ANY TEST REPORT, NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR USE, IS MADE.

15. (A) IN NO EVENT WHATSOEVER SHALL THE COMPANY BE LIABLE FOR ANY CONSEQUENTIAL, SPECIAL, INCIDENTAL, EXEMPLARY OR PUNITIVE DAMAGES IN CONNECTION WITH, RELATING TO OR ARISING OUT OF THE TEST REPORT OR THE SERVICES PROVIDED BY THE COMPANY HEREUNDER, INCLUDING WITHOUT LIMITATION LOSS OF OR DAMAGE TO PROPERTY; LOSS OF INCOME, PROFIT OR USE; OR ANY CLAIMS OR DEMANDS MADE AGAINST CLIENT OR ANY OTHER PERSON BY ANY THIRD PARTY IN CONNECTION WITH, RELATING TO OR ARISING OUT OF THE SERVICES PROVIDED BY THE COMPANY HEREUNDER.

(B) NOTWITHSTANDING ANY PROVISION TO THE CONTRARY CONTAINED HEREIN, AND IN RECOGNITION OF THE RELATIVE RISKS AND BENEFITS TO CLIENT AND THE COMPANY ASSOCIATED WITH THE TESTING SERVICES CONTEMPLATED HEREBY, THE RISKS HAVE BEEN ALLOCATED SUCH THAT UNDER NO CIRCUMSTANCES WHATSOEVER SHALL THE LIABILITY OF THE COMPANY TO CLIENT OR ANY THIRD PARTY IN RESPECT OF ANY CLAIM FOR LOSS, DAMAGE OR EXPENSE, OF WHATSOEVER NATURE OR MAGNITUDE, AND HOWSOEVER ARISING, EXCEED AN AMOUNT EQUAL TO FIVE (5) TIMES THE AMOUNT OF THE FEES PAID TO THE COMPANY FOR THE SPECIFIC SERVICES WHICH GAVE RISE TO SUCH CLAIM OR U.S.\$10,000, WHICHEVER IS THE LESSER AMOUNT.

16. The Company shall not be liable for any loss or damage resulting from any delay or failure in performance of its obligations hereunder resulting directly or indirectly from any event of force majeure or any event outside the control of the Company. If any such event occurs, the Company may immediately cancel or suspend its performance hereunder without incurring any liability whatsoever to Client.

17. Company's services, including these Conditions, shall be governed by, and construed in accordance with, the local laws of the country where the Company performs the tests or, in the case of tests performed in the United States of America, the laws of Massachusetts without regard to conflicts of laws principles. If any aspect(s) of these Conditions is found to be illegal or unenforceable, the validity, legality and enforceability of all remaining aspects of these Conditions shall not in any way be affected or impaired thereby. Any proceeding related to the subject matter hereof shall be brought, if at all, in the courts of the country where the Company performs the tests or, in the case of tests performed in the United States of America, in the courts of Massachusetts. Client waives the right to interpose any counterclaim or setoffs of any nature in any litigation arising hereunder.

Rev.160009121(2)_#684340 v13CS

