



## 47 CFR PART 15 SUBPART B

# TEST REPORT

of

### GSM/GPRS Mobile Phone

Model Name: 809  
Brand Name: Neoi  
Report No.: SZ08090120E03  
FCC ID: WV8-NEOI-809-08

*prepared for*

P.I.C Technology Ltd.

13/F1., Rm.6, Tung Sun commercial Centre 200 Lockhart Road, Wanchai, Hong Kong

  
Shenzhen Electronic Product Quality Testing Center  
Morlab Laboratory  
3/F, Electronic Testing Building, Shike Road, Xili,  
Nanshan District, Shenzhen 518055 P. R. China  
Tel: +86 755 86130398  
Fax: +86 755 86130218



**NOTE:** This test report can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen Electronic Product Quality Testing Center Morlab Laboratory. Any objections should be raised to us within thirty workdays since the date of issue.

## TABLE OF CONTENTS

<b>2.1</b>	<b>EUT Description.....</b>	<b>4</b>
<b>2.2</b>	<b>Test Standards and Results.....</b>	<b>5</b>
<b>2.3</b>	<b>Facilities and Accreditations .....</b>	<b>6</b>
2.3.1	Facilities .....	6
2.3.2	Test Environment Conditions .....	6
2.3.3	Measurement Uncertainty .....	6
<b>3.1</b>	<b>Test Mode .....</b>	<b>7</b>
3.1.1	GSM Test Mode.....	7
3.1.2	USB Test Mode .....	7
<b>3.2</b>	<b>Test Setup and Equipments List .....</b>	<b>8</b>
3.2.1	Conducted Emission.....	8
3.2.2	Radiated Emission .....	9
<b>4.1</b>	<b>Conducted Emission.....</b>	<b>10</b>
4.1.1	Requirement .....	10
4.1.2	Test Description.....	10
4.1.3	Test Result .....	10
<b>4.2</b>	<b>Radiated Emission.....</b>	<b>13</b>
4.2.1	Requirement .....	13
4.2.2	Test Description.....	13
4.2.3	Test Result .....	13



## 1. TEST CERTIFICATION

Equipment under Test: GSM/GPRS Mobile Phone

Brand Name: Neoi  
Model Name: 809  
FCC ID: WV8-NEOI-809-08  
Applicant: P.I.C Technology Ltd.  
13/F1., Rm.6, Tung Sun commercial Centre 200 Lockhart Road, Wanchai, Hong Kong  
Manufacturer: Aplustec Limit  
Zheng Tian District, Jiekou Village, ChangAn Town, DongGuan City, China 523883  
Emission Designator 300KGXW  
Test Standards: 47 CFR Part 15 Subpart B  
Test Date(s): November 05, 2008 –November 12, 2008  
Test Result: PASS

**\* We Hereby Certify That:**

The equipment under test was tested by Shenzhen Electronic Product Quality Testing Center Morlab Laboratory. The test data, data evaluation, test procedures and equipment configurations shown in this report were made in accordance with the requirement of related FCC rules.

The test results of this report only apply for the tested sample equipment identified above. The test report shall be invalid without all the signatures of the test engineer, the reviewer and the approver.

Tested by: ..... Ni Yong ..... Dated: ..... 2008.11.17 .....  
Ni Yong



Reviewed by: ..... Wei Yanquan ..... Dated: ..... 2008.11.17 .....  
Wei Yanquan

Approved by: ..... Shu Luan ..... Dated: ..... 2008.11.17 .....  
Shu Luan

## 2. GENERAL INFORMATION

### 2.1 EUT Description

EUT Type ..... GSM/GPRS Mobile Phone

Model Name..... 809

Serial No. ..... (n.a, marked #1 by test site)

IMEI ..... 13579024681122 EMEISV:87

Hardware Version..... Z7\_01 main071115

Software Version ..... 809\_JA\_FRGE\_GO\_OV\_SM\_V1.2

Modulation Type ..... GMSK

Power Supply ..... Battery

Model Name: 363443

Brand name: TONGDA

Capacitance: 500mAh

Rated voltage: 3.7V

Manufacturer: SHENZHEN TONGDA ELECTRONICS CO., LTD

Manufacturer Address: ZhengTian District, Jiekou Village, ChangAn Town, DongGuan City, China 523883

Ancillary Equipment 1 ... AC Adapter (Charger for Battery)

Model Name: EU001

Brand Name: Aplustec Limit

Serial No.: (n.a. marked #1 by test site)

Rated Input: ~ 100-240V, 0.2A,50/60Hz

Rated Output: == 5.5V, 500mA

Manufacturer: Aplustec Limit

Manufacturer Address: ZhengTian District, Jiekou Village, ChangAn Town, DongGuan City, China 523883

*Note 1:* The EUT is a GSM/GPRS Mobile Phone; it supports GSM 900MHz, 1800MHz, 1900MHz and ISM 2.4GHz Bluetooth module. GSM 1900MHz was tested in this report.

*Note 2:* A communication link between the EUT and the Bluetooth Earphone are established at the start of the test, and maintained during the all test in this report.

*Note 3:* The EUT is equipped with a T-Flash card slot; equipped with a special port which can be connected to the ancillary equipments supplied by the manufacturer e.g. the AC Adapter and the USB Adapter Cable. And the EUT can perform as a WebCam connected with PC.

*Note 4:* For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

## 2.2 Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart B:

No.	Identity	Document Title
1	47 CFR Part 15 (10-1-05 Edition)	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Result	Test date
1	15.107	Conducted Emission	PASS	2008-11-05
2	15.109	Radiated Emission	PASS	2008-11-11

NOTE:

The tests were performed according to the method of measurements prescribed in ANSI C63.4 2003.

## 2.3 Facilities and Accreditations

### 2.3.1 Facilities

Shenzhen Electronic Product Quality Testing Center Morlab Laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L1659.

All measurement facilities used to collect the measurement data are located at Electronic Testing Building, Shahe Road, Xili, Nanshan District, Shenzhen 518055 CHINA. The test site is constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22; the FCC registration number is 741109.

### 2.3.2 Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	20 - 25
Relative Humidity (%):	40 - 60
Atmospheric Pressure (kPa):	96

### 2.3.3 Measurement Uncertainty

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

Uncertainty of Conducted Emission:	±1.8dB
Uncertainty of Radiated Emission:	±3.1dB

### 3. TEST CONDITIONS SETTING

#### 3.1 Test Mode

##### 3.1.1 GSM Test Mode

(1) The first test mode (GSM)

The EUT configuration of the emission tests is EUT + Battery + Charger.

In this test mode, the EUT will be working under the Traffic operating mode and Idle operating mode.

During the measurement of Traffic operating mode, a communication link was established between the EUT and a System Simulator (SS). The EUT operated at GSM 1900MHz mid ARFCN (661) and maximum output power (level 0).

(2) The second test mode (GPRS)

The EUT configuration of the emission tests is EUT + Battery + Charger.

In this test mode, a GPRS link was established between the EUT and a System Simulator (SS); date was transmitted between EUT and System Simulator (SS), and maintained during the measurement.

NOTE: These test modes are performed, only the worst cases are recorded in this report.

##### 3.1.2 USB Test Mode

(1) The first test mode (USB)

The EUT configuration of the emission tests is TransFlash Card + EUT + Battery + PC.

In this test mode, the EUT with a TransFlash Card embedded is connected with a PC via a special USB cable supplied by applicant. During the measurement, a communication link was established between the EUT and a System Simulator (SS), simultaneity, the date is transmitting between the PC and the TransFlash Card of the EUT.

(2) The second test mode (PC Web Camera)

The EUT configuration of the emission tests is EUT + Battery + PC.


The EUT supports PC Web Camera function. During the measurement, the EUT was connected with a PC via a special USB cable supplied by applicant, and the EUT working by way of the PC Web Camera.

NOTE: These test modes are performed, only the worst cases are recorded in this report.

### 3.2 Test Setup and Equipments List

#### 3.2.1 Conducted Emission

##### A. Test Setup:




The EUT is placed on a 0.8m high insulating table, which stands on the grounded conducting floor, and keeps 0.4m away from the grounded conducting wall. The EUT is connected to the power mains through a LISN which provides  $50\Omega/50\mu\text{H}$  of coupling impedance for the measuring instrument. The Common Antenna is used for the call between the EUT and the System Simulator (SS). A Pulse Limiter is used to protect the measuring instrument. The factors of the whole test system are calibrated to correct the reading.

##### B. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Receiver	Agilent	E7405A	US44210471	2008.09	1year
LISN	Schwarzbeck	NSLK 8127	812744	2008.09	1year
Pulse Limiter (20dB)	Schwarzbeck	VTSD 9561-D	9391	(n.a.)	(n.a.)
System Simulator	Agilent	E5515C	GB43130131	2008.09	1year
Personal Computer	IBM	IBM_T20	(n.a.)	(n.a.)	(n.a.)
Bluetooth-Headset	Nokia	HS-36W	(n.a.)	(n.a.)	(n.a.)
T-Flash Card	SanDisk	256MB	(n.a.)	(n.a.)	(n.a.)

### 3.2.2 Radiated Emission

#### C. Test Setup:



The test is performed in a 3m Semi-Anechoic Chamber; the antenna factor, cable loss and so on of the site (factors) is calculated to correct the reading. The EUT is placed on a 0.8m high insulating Turn Table, and keeps 3m away from the Test Antenna, which is mounted on a variable-height antenna master tower. The Common Antenna is used for the call between the EUT and the System Simulator (SS).

#### D. Equipments List:

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Receiver	Agilent	E7405A	US44210471	2008.09	1year
Semi-Anechoic Chamber	Albatross	9m*6m*6m	(n.a.)	2008.08	2year
Test Antenna - Bi-Log	Schwarzbeck	VULB 9163	9163-274	2008.08	1year
Test Antenna - Horn	Schwarzbeck	BBHA 9120C	9120C-384	2008.08	1year
System Simulator	Agilent	E5515C	GB43130131	2008.09	1year
Personal Computer	IBM	IBM_T20	(n.a.)	(n.a.)	(n.a.)
Bluetooth-Headset	Nokia	HS-36W	(n.a.)	(n.a.)	(n.a.)
T-Flash Card	SanDisk	256MB	(n.a.)	(n.a.)	(n.a.)

## 4. 47 CFR PART 15B REQUIREMENTS

### 4.1 Conducted Emission

#### 4.1.1 Requirement

According to FCC section 15.107, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 $\mu$ H/50 $\Omega$  line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

- a) The limit subjects to the Class B digital device.
- b) The lower limit shall apply at the band edges.
- c) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

#### 4.1.2 Test Description

See section 3.2.1 of this report.

#### 4.1.3 Test Result

The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. All test modes are considered, refer to recorded points and plots below.


##### 4.1.3.1 GSM Test Mode

###### A. Test Verdict Recorded for Suspicious Points:


No.	@Frequency (MHz)	Measured Emission Level (dB $\mu$ V)				Limit (dB $\mu$ V)		Verdict
		PK	QP	AV	Phase	QP	AV	
1	0.18	62.09	63.22	50.45	L	64.8	54.8	PASS
2	0.24	56.82	56.74	44.78	L	62.5	52.5	PASS

No.	@Frequency (MHz)	Measured Emission Level (dB $\mu$ V)				Limit (dB $\mu$ V)		Verdict
		PK	QP	AV	Phase	QP	AV	
3	0.299	54.84	51.82	37.94	L	60.2	50.2	PASS
4	0.538	47.14	47.19	36.65	L	56.0	46.0	PASS
5	0.717	49.24	44.64	30.64	L	56.0	46.0	PASS
6	0.956	48.14	45.24	36.22	L	56.0	46.0	PASS
7	2.420	48.50	50.94	28.86	L	56.0	46.0	PASS
8	0.180	60.90	50.66	27.50	N	64.8	54.8	PASS
9	0.240	55.81	46.72	26.30	N	63.5	53.2	PASS
10	0.299	51.00	49.36	29.69	N	60.2	50.2	PASS
11	0.478	49.31	44.01	26.18	N	56.7	46.7	PASS
12	0.717	48.48	41.05	27.66	N	56.0	46.0	PASS
13	1.250	51.29	39.05	22.74	N	56.0	46.0	PASS
14	1.940	48.51	41.25	23.35	N	56.0	46.0	PASS
15	2.720	47.56	38.01	22.55	N	56.0	46.0	PASS

## B. Test Plot:



(Plot A: L Phase)



### (Plot B: N Phase)

## 4.2 Radiated Emission

### 4.2.1 Requirement

According to FCC section 15.109, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency range (MHz)	Field Strength	
	$\mu$ V/m	dB $\mu$ V/m
30 - 88	100	40
88 - 216	150	43.5
216 - 960	200	46
Above 960	500	54

NOTE:

- Field Strength (dB $\mu$ V/m) =  $20 \log_{10} [\text{Field Strength } (\mu\text{V/m})]$ .
- In the emission tables above, the tighter limit applies at the band edges.

### 4.2.2 Test Description


See section 3.2.2 of this report.

### 4.2.3 Test Result

The maximum radiated emission is searched using PK, QP and AV detectors; the emission levels more than the limits, and that have narrow margins from the limits will be re-measured with AV and QP detectors. Both the vertical and the horizontal polarizations of the Test Antenna are considered to perform the tests. All test modes are considered, refer to recorded points and plots below.

#### 4.2.3.1 GSM Test Mode

##### A. Test Plot and Suspicious Points




(Plot A: Test Antenna Vertical)




(Plot B: Test Antenna Horizontal)

#### 4.2.3.2 USB Test Mode

##### B. Test Plot and Suspicious Points



(Plot A: Test Antenna Vertical)



(Plot B: Test Antenna Horizontal)

Test result: pass

\*\* END OF REPORT \*\*