

# **FCC SAR Test Report**

**APPLICANT**: Brightstar Coporation

**EQUIPMENT**: Mobile phone

BRAND NAME : Avvio

MODEL NAME : Avvio 921 FCC ID : WVBA921

**STANDARD** : FCC 47 CFR Part 2 (2.1093)

**ANSI/IEEE C95.1-1992** 

**IEEE 1528-2003** 

FCC OET Bulletin 65 Supplement C (Edition 01-01)

The product was received on Jun. 07, 2012 and completely tested on Jul. 16, 2012. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures and shown the compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Reviewed by:

Jones Tsai / Manager

lac-MRA



SPORTON INTERNATIONAL (KUNSHAN) INC. No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 1 of 32
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01

: 2 of 32

: Rev. 01

Report Issued Date: Jul. 25, 2012

Page Number

Report Version

# **Table of Contents**

1. Statement of Compliance	4
2. Administration Data	5
2.1 Testing Laboratory	5
2.2 Applicant	5
2.3 Manufacturer	5
2.4 Application Details	5
3. General Information	6
3.1 Description of Equipment Under Test (DUT)	6
3.2 Product Photos	6
3.3 Applied Standards	
3.4 Device Category and SAR Limits	7
3.5 Test Conditions	
4. Specific Absorption Rate (SAR)	
4.1 Introduction	8
4.2 SAR Definition	
5. SAR Measurement System	
5.1 E-Field Probe	
5.2 Data Acquisition Electronics (DAE)	
5.3 Robot	
5.4 Measurement Server	
5.5 Phantom	
5.6 Device Holder	
5.7 Data Storage and Evaluation	14
5.8 Test Equipment List	
6. Tissue Simulating Liquids	
7. Uncertainty Assessment	
8. SAR Measurement Evaluation	20
8.1 Purpose of System Performance check	
8.2 System Setup	
8.3 Validation Results	
9. DUT Testing Position	
9.1 Define two imaginary lines on the handset	
9.2 Cheek Position	
9.3 Tilted Position	
9.4 Body Worn Position	
10. Measurement Procedures	
10.1 Spatial Peak SAR Evaluation	
10.2 Area & Zoom Scan Procedures	
10.3 Volume Scan Procedures	
10.4 SAR Averaged Methods	
10.5 Power Drift Monitoring	
11. SAR Test Configurations	
11.1 Exposure Positions Consideration	27
11.2 Simultaneous Transmitting Configurations	
12. SAR Test Results	
12.1 Conducted Power (Unit: dBm)	
12.2 Test Records for Head SAR Test	
12.3 Test Records for Body-worn SAR Test	
13. References	
Appendix A. Plots of System Performance Check	
Appendix B. Plots of SAR Measurement	
Appendix C. DASY Calibration Certificate	
Appendix D. Product Photos	
Appendix E. Test Setup Photos	
Appendix F. Product Equality Declaration	



# **Revision History**

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA260403-01	Rev. 01	Initial issue of report	Jul. 25, 2012

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 3 of 32
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01



1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for **Brightstar Coporation DUT: Mobile phone; Brand Name: Avvio; Model Name: Avvio 921** are as follows.

#### <Standalone SAR>

Band	Position	SAR <sub>1g</sub> (W/kg)
GSM850	Head	0.560
GSM1900	Head	0.329
GSM850	Body-worn (1.5 cm Gap)	0.512
GSM1900	Body-worn (1.5 cm Gap)	0.455

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2003 and FCC OET Bulletin 65 Supplement C (Edition 01-01).

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 4 of 32
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01

# FCC SAR Test Report

# 2. Administration Data

# 2.1 Testing Laboratory

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C. TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958

# 2.2 Applicant

Company Name	Brightstar Coporation
Address	9725 NW 117th Ave., Miami, Florida, United States

# 2.3 Manufacturer

Company Name	Skycom Telecommunications Co Limited								
Address	Room China	604,	East	Block,	Shengtang	Building,	Futian	District,	Shenzhen,

# 2.4 Application Details

Date of Receipt of Application	Jun. 07, 2012
Date of Start during the Test	Jul. 16, 2012
Date of End during the Test	Jul. 16, 2012

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 5 of 32
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01



# 3. General Information

# 3.1 <u>Description of Equipment Under Test (DUT)</u>

	Product Feature & Specification
DUT	Mobile phone
Brand Name	Avvio
Model Name	Avvio 921
FCC ID	WVBA921
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Rx Frequency	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Maximum Average	GSM850: 32.29 dBm
Output Power to	GSM1900: 29.76 dBm
Antenna	Bluetooth: 8.37 dBm
Antenna Type	WWAN: Fixed Internal Antenna Bluetooth: Dipole Antenna
HW Version	X225-MB-V2.1
SW Version	X225_7E_COMCEL_BT_FM_NMI60X_TP_12832_LCD240X320_V15_120524_1033
Type of Modulation	GSM: GMSK GPRS: GMSK Bluetooth (1Mbps): GFSK
Type of Modulation	Bluetooth EDR (2Mbps): π/4-DQPSK
	Bluetooth EDR (3Mbps): 8-DPSK
Dual Transfer Mode	Class B – DUT cannot support Packet Switched and Circuit Switched Network simultaneously
(DTM) Category	but can automatically switch between Packet and Circuit Switched Network.
DUT Stage	Production Unit
Remark: The above DUT manual for more detailed	Γ's information was declared by manufacturer. Please refer to the specifications or user's description.

# 3.2 Product Photos

Please refer to Appendix D.

SPORTON INTERNATIONAL (KUNSHAN) INC.

FAX: 86-0512-5790-0958 FCC ID: WVBA921

TEL: 86-0512-5790-0158

: 6 of 32 Page Number Report Issued Date: Jul. 25, 2012 Report Version : Rev. 01

# FCC SAR Test Report

### 3.3 Applied Standards

The Specific Absorption Rate (SAR) testing specification, method and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2003
- FCC OET Bulletin 65 Supplement C (Edition 01-01)
- FCC KDB 447498 D01 v04
- FCC KDB 648474 D01 v01r05
- FCC KDB 941225 D03 v01

### 3.4 Device Category and SAR Limits

This device belongs to portable device category because its radiating structure is allowed to be used within 20 centimeters of the body of the user. Limit for General Population/Uncontrolled exposure should be applied for this device, it is 1.6 W/kg as averaged over any 1 gram of tissue.

### 3.5 Test Conditions

#### 3.5.1. Ambient Condition

Ambient Temperature	20 to 24 ℃
Humidity	< 60 %

### 3.5.2. Test Configuration

The device was controlled by using a base station emulator. Communication between the device and the emulator was established by air link. The distance between the DUT and the antenna of the emulator is larger than 50 cm and the output power radiated from the emulator antenna is at least 30 dB smaller than the output power of DUT. The DUT was set from the emulator to radiate maximum output power during all tests.

SPORTON INTERNATIONAL (KUNSHAN) INC.

FAX: 86-0512-5790-0958 FCC ID: WVBA921

TEL: 86-0512-5790-0158

Page Number : 7 of 32
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01



# 4. Specific Absorption Rate (SAR)

### 4.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

### 4.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density ( $\rho$ ). The equation description is as below:

$$SAR = \frac{d}{dt} \left( \frac{dW}{dm} \right) = \frac{d}{dt} \left( \frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be either related to the temperature elevation in tissue by

$$SAR = C\left(\frac{\delta T}{\delta t}\right)$$

Where: C is the specific heat capacity,  $\delta T$  is the temperature rise and  $\delta t$  is the exposure duration, or related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where:  $\sigma$  is the conductivity of the tissue,  $\rho$  is the mass density of the tissue and E is the RMS electrical field strength.

However for evaluating SAR of low power transmitter, electrical field measurement is typically applied.

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 8 of 32
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01



# 5. SAR Measurement System




Fig 5.1 SPEAG DASY System Configurations

The DASY system for performance compliance tests is illustrated above graphically. This system consists of the following items:

- A standard high precision 6-axis robot with controller, a teach pendant and software
- A data acquisition electronic (DAE) attached to the robot arm extension
- A dosimetric probe equipped with an optical surface detector system
- > The electro-optical converter (EOC) performs the conversion between optical and electrical signals
- A measurement server performs the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- A probe alignment unit which improves the accuracy of the probe positioning
- > A computer operating Windows XP
- DASY software
- > Remove control with teach pendant and additional circuitry for robot safety such as warming lamps, etc.
- The SAM twin phantom
- A device holder
- > Tissue simulating liquid
- Dipole for evaluating the proper functioning of the system

Some of the components are described in details in the following sub-sections.

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 9 of 32
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01



### 5.1 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG). The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

### 5.1.1. E-Field Probe Specification

#### <ES3DV3>

Construction	Symmetrical design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)		
Frequency	10 MHz to 4 GHz; Linearity: ± 0.2 dB		
Directivity	± 0.2 dB in HSL (rotation around probe axis) ± 0.3 dB in tissue material (rotation normal to probe axis)	Fig 5.2 Photo of ES3DV3	
Dynamic Range	5 μW/g to 100 mW/g; Linearity: ± 0.2 dB		
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 3.9 mm (Body: 12 mm) Distance from probe tip to dipole centers: 2.0 mm		

#### 5.1.2. E-Field Probe Calibration

Each probe needs to be calibrated according to a dosimetric assessment procedure with accuracy better than  $\pm$  10%. The spherical isotropy shall be evaluated and within  $\pm$  0.25 dB. The sensitivity parameters (NormX, NormY, and NormZ), the diode compression parameter (DCP) and the conversion factor (ConvF) of the probe are tested. The calibration data can be referred to appendix C of this report.

## 5.2 <u>Data Acquisition Electronics (DAE)</u>

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.

The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



Fig 5.3 Photo of DAE

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 10 of 32
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01



### 5.3 <u>Robot</u>

The SPEAG DASY system uses the high precision robots (DASY5: TX90XL) type from Stäubli SA (France). For the 6-axis controller system, the robot controller version (DASY5: CS8c) from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- ➤ High precision (repeatability ±0.035 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- ➤ Low ELF interference (the closed metallic construction shields against motor control fields)



Fig 5.4 Photo of DASY5

### 5.4 Measurement Server

The measurement server is based on a PC/104 CPU board with CPU (DASY5: 400 MHz, Intel Celeron), chipdisk (DASY5: 128 MB), RAM (DASY5: 128 MB). The necessary circuits for communication with the DAE electronic box, as well as the 16 bit AD converter system for optical detection and digital I/O interface are contained on the DASY I/O board, which is directly connected to the PC/104 bus of the CPU board.

The measurement server performs all the real-time data evaluation for field measurements and surface detection, controls robot movements and handles safety operations.



Fig 5.5 Photo of Server for DASY5

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 11 of 32
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01



## 5.5 Phantom

#### <SAM Twin Phantom>

SAM I WILL HALLOTT		
Shell Thickness	2 ± 0.2 mm;	
	Center ear point: 6 ± 0.2 mm	
Filling Volume	Approx. 25 liters	The state of the s
Dimensions	Length: 1000 mm; Width: 500 mm;	
	Height: adjustable feet	<u> </u>
Measurement Areas	Left Hand, Right Hand, Flat Phantom	
		C 2 2 2
		Fig 5.6 Photo of SAM Phantom

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921

Page Number : 12 of 32 Report Issued Date: Jul. 25, 2012 Report Version : Rev. 01



# 5.6 <u>Device Holder</u>

### <Device Holder for SAM Twin Phantom>

The SAR in the phantom is approximately inversely proportional to the square of the distance between the source and the liquid surface. For a source at 5 mm distance, a positioning uncertainty of  $\pm$  0.5 mm would produce a SAR uncertainty of  $\pm$  20 %. Accurate device positioning is therefore crucial for accurate and repeatable measurements. The positions in which the devices must be measured are defined by the standards.

The DASY device holder is designed to cope with different positions given in the standard. It has two scales for the device rotation (with respect to the body axis) and the device inclination (with respect to the line between the ear reference points). The rotation center for both scales is the ear reference point (EPR). Thus the device needs no repositioning when changing the angles.

The DASY device holder is constructed of low-loss POM material having the following dielectric parameters: relative permittivity  $\varepsilon$  = 3 and loss tangent  $\delta$  = 0.02. The amount of dielectric material has been reduced in the closest vicinity of the device, since measurements have suggested that the influence of the clamp on the test results could thus be lowered.



Fig 5.7 Device Holder

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 13 of 32
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01

### 5.7 Data Storage and Evaluation

### 5.7.1. Data Storage

The DASY software stores the assessed data from the data acquisition electronics as raw data (in microvolt readings from the probe sensors), together with all the necessary software parameters for the data evaluation (probe calibration data, liquid parameters and device frequency and modulation data) in measurement files. The post-processing software evaluates the desired unit and format for output each time the data is visualized or exported. This allows verification of the complete software setup even after the measurement and allows correction of erroneous parameter settings. For example, if a measurement has been performed with an incorrect crest factor parameter in the device setup, the parameter can be corrected afterwards and the data can be reevaluated.

The measured data can be visualized or exported in different units or formats, depending on the selected probe type (e.g., [V/m], [A/m], [mW/g]). Some of these units are not available in certain situations or give meaningless results, e.g., a SAR-output in a non-lose media, will always be zero. Raw data can also be exported to perform the evaluation with other software packages.

#### 5.7.2. Data Evaluation

The DASY post-processing software (SEMCAD) automatically executes the following procedures to calculate the field units from the microvolt readings at the probe connector. The parameters used in the evaluation are stored in the configuration modules of the software:

**Probe parameters**: - Sensitivity Norm<sub>i</sub>, a<sub>i0</sub>, a<sub>i1</sub>, a<sub>i2</sub>

 $\begin{array}{lll} \text{- Conversion factor} & \text{ConvF}_i \\ \text{- Diode compression point} & \text{dcp}_i \end{array}$ 

**Device parameters**: - Frequency f

- Crest factor cf - Conductivity σ

- Density ρ

These parameters must be set correctly in the software. They can be found in the component documents or they can be imported into the software from the configuration files issued for the DASY components. In the direct measuring mode of the multi-meter option, the parameters of the actual system setup are used. In the scan visualization and export modes, the parameters stored in the corresponding document files are used.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power.

SPORTON INTERNATIONAL (KUNSHAN) INC.

Media parameters:

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 14 of 32
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01



# FCC SAR Test Report

The formula for each channel can be given as :

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

with Vi

 $V_i$  = compensated signal of channel i, (i = x, y, z)

 $U_i$  = input signal of channel i, (i = x, y, z)

cf = crest factor of exciting field (DASY parameter)

dcp<sub>i</sub> = diode compression point (DASY parameter)

From the compensated input signals, the primary field data for each channel can be evaluated:

E-field Probes : 
$$\mathbf{E_i} = \sqrt{\frac{\mathbf{V_i}}{\mathbf{Norm_i \cdot ConvF}}}$$

H-field Probes : 
$$H_i = \sqrt{V_i} \cdot \frac{a_{i0} + a_{i1}f + a_{i2}f^2}{f}$$

with

 $V_i$  = compensated signal of channel i, (i = x, y, z)

Norm<sub>i</sub> = sensor sensitivity of channel i, (i = x, y, z),  $\mu V/(V/m)^2$  for E-field Probes

ConvF = sensitivity enhancement in solution

a<sub>ij</sub> = sensor sensitivity factors for H-field probes

f = carrier frequency [GHz]

E<sub>i</sub> = electric field strength of channel i in V/m

H<sub>i</sub> = magnetic field strength of channel i in A/m

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{tot} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{tot}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$$

with

SAR = local specific absorption rate in mW/g

E<sub>tot</sub> = total field strength in V/m

 $\sigma$  = conductivity in [mho/m] or [Siemens/m]

ρ = equivalent tissue density in g/cm<sup>3</sup>

Note that the density is set to 1, to account for actual head tissue density rather than the density of the tissue simulating liquid.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 15 of 32
Report Issued Date : Jul. 25, 2012

Report No.: FA260403-01

Report Version : Rev. 01

# 5.8 Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
wanulacturer	Name of Equipment	Type/Model	Type/Model Serial Number		Due Date
SPEAG	Dosimetric E-Field Probe	ES3DV3	3270	Sep. 12, 2011	Sep. 11, 2012
SPEAG	Data Acquisition Electronics	DAE4	1303	Nov. 10, 2011	Nov. 09, 2012
SPEAG	835MHz System Validation Kit	D835V2	4d091	Nov. 18, 2011	Nov. 17, 2012
SPEAG	1900MHz System Validation Kit	D1900V2	5d118	Nov. 21, 2011	Nov. 20, 2012
SPEAG	Test Arch Phantom	Par phantom	1105	NCR	NCR
SPEAG	Phone Positioner	N/A	N/A	NCR	NCR
SPEAG	SAM Twin Phantom	QD 000 P40 CD	TP-1670	NCR	NCR
SPEAG	SAM Twin Phantom	QD 000 P40 CD	TP-1671	NCR	NCR
Anritsu	Radio Communication Analyzer	MT8820C	6201091028	Jun. 10, 2012	Jun. 09, 2013
Agilent	Base Station	E5515C	MY50267224	Dec. 29, 2011	Dec. 28, 2012
Agilent	ENA Series Network Analyzer	E5071C	MY46111157	Apr. 13, 2012	Apr. 12, 2013
R&S	Signal Generator	SMR40	100455	Dec. 30, 2011	Dec. 29, 2012
Agilent	Power Meter	E4416A	MY45101555	Aug. 23, 2011	Aug. 22, 2012
Agilent	Power Sensor	E9327A	MY44421198	Aug. 23, 2011	Aug. 22, 2012
R&S	Spectrum Analyzer	FSP30	101400	Jun. 01, 2012	May 31, 2013

**Table 5.1 Test Equipment List** 

**Note:** The calibration certificate of DASY can be referred to appendix C of this report.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 16 of 32
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01



# 6. Tissue Simulating Liquids

For the measurement of the field distribution inside the SAM phantom with DASY, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 6.1. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 6.2.





Fig 6.1 Photo of Liquid Height for Head SAR

Fig 6.2 Photo of Liquid Height for Body SAR

The following table gives the recipes for tissue simulating liquid.

Frequency	Water	Sugar	Cellulose	Salt	Preventol	DGBE	Conductivity	Permittivity
(MHz)	(%)	(%)	(%)	(%)	(%)	(%)	(σ)	(ε <sub>r</sub> )
For Head								
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.40	40.0
				For Body				
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3

Table 6.1 Recipes of Tissue Simulating Liquid

The dielectric parameters of the liquids were verified prior to the SAR evaluation using an Agilent 85070D Dielectric Probe Kit and an Agilent Network Analyzer.

Freq. (MHz)	Liquid Type	Temp. (°C)	Conductivity (σ)	Permittivity (ε <sub>r</sub> )	Conductivity Target (σ)	Permittivity Target (ε <sub>r</sub> )	Delta (σ) (%)	Delta (ε <sub>r</sub> ) (%)	Limit (%)	Date
835	Head	21.5	0.914	41.826	0.90	41.5	1.56	0.79	±5	Jul. 16, 2012
835	Body	21.3	0.97	56.499	0.97	55.2	0.00	2.35	±5	Jul. 16, 2012
1900	Head	21.4	1.427	41.191	1.40	40.0	1.93	2.98	±5	Jul. 16, 2012
1900	Body	21.6	1.519	53.569	1.52	53.3	-0.07	0.50	±5	Jul. 16, 2012

Table 6.2 Measuring Results for Simulating Liquid

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921

Page Number : 17 of 32 Report Issued Date: Jul. 25, 2012 Report Version : Rev. 01



# 7. Uncertainty Assessment

The component of uncertainly may generally be categorized according to the methods used to evaluate them. The evaluation of uncertainly by the statistical analysis of a series of observations is termed a Type An evaluation of uncertainty. The evaluation of uncertainty by means other than the statistical analysis of a series of observation is termed a Type B evaluation of uncertainty. Each component of uncertainty, however evaluated, is represented by an estimated standard deviation, termed standard uncertainty, which is determined by the positive square root of the estimated variance.

A Type A evaluation of standard uncertainty may be based on any valid statistical method for treating data. This includes calculating the standard deviation of the mean of a series of independent observations; using the method of least squares to fit a curve to the data in order to estimate the parameter of the curve and their standard deviations; or carrying out an analysis of variance in order to identify and quantify random effects in certain kinds of measurement.

A type B evaluation of standard uncertainty is typically based on scientific judgment using all of the relevant information available. These may include previous measurement data, experience and knowledge of the behavior and properties of relevant materials and instruments, manufacture's specification, data provided in calibration reports and uncertainties assigned to reference data taken from handbooks. Broadly speaking, the uncertainty is either obtained from an outdoor source or obtained from an assumed distribution, such as the normal distribution, rectangular or triangular distributions indicated in Table 7.1

<b>Uncertainty Distributions</b>	Normal	Rectangular	Triangular	U-Shape
Multi-plying Factor <sup>(a)</sup>	1/k <sup>(b)</sup>	1/√3	1/√6	1/√2

<sup>(</sup>a) standard uncertainty is determined as the product of the multiplying factor and the estimated range of variations in the measured quantity

**Table 7.1 Standard Uncertainty for Assumed Distribution** 

The combined standard uncertainty of the measurement result represents the estimated standard deviation of the result. It is obtained by combining the individual standard uncertainties of both Type A and Type B evaluation using the usual "root-sum-squares" (RSS) methods of combining standard deviations by taking the positive square root of the estimated variances.

Expanded uncertainty is a measure of uncertainty that defines an interval about the measurement result within which the measured value is confidently believed to lie. It is obtained by multiplying the combined standard uncertainty by a coverage factor. Typically, the coverage factor ranges from 2 to 3. Using a coverage factor allows the true value of a measured quantity to be specified with a defined probability within the specified uncertainty range. For purpose of this document, a coverage factor two is used, which corresponds to confidence interval of about 95 %. The DASY uncertainty Budget is showed in Table 7.2.

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 18 of 32
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01

<sup>(</sup>b)  $\kappa$  is the coverage factor

SPORTON LAB.	FCC SAR Test Report

Error Description	Uncertainty Value (±%)	Probability Distribution	Divisor	Ci (1g)	Standard Uncertainty (1g)		
Measurement System							
Probe Calibration	6.0	Normal	1	1	± 6.0 %		
Axial Isotropy	4.7	Rectangular	√3	0.7	± 1.9 %		
Hemispherical Isotropy	9.6	Rectangular	√3	0.7	± 3.9 %		
Boundary Effects	1.0	Rectangular	√3	1	± 0.6 %		
Linearity	4.7	Rectangular	√3	1	± 2.7 %		
System Detection Limits	1.0	Rectangular	√3	1	± 0.6 %		
Readout Electronics	0.3	Normal	1	1	± 0.3 %		
Response Time	0.8	Rectangular	√3	1	± 0.5 %		
Integration Time	2.6	Rectangular	√3	1	± 1.5 %		
RF Ambient Noise	3.0	Rectangular	√3	1	± 1.7 %		
RF Ambient Reflections	3.0	Rectangular	√3	1	± 1.7 %		
Probe Positioner	0.4	Rectangular	√3	1	± 0.2 %		
Probe Positioning	2.9	Rectangular	√3	1	± 1.7 %		
Max. SAR Eval.	1.0	Rectangular	√3	1	± 0.6 %		
Test Sample Related							
Device Positioning	2.9	Normal	1	1	± 2.9 %		
Device Holder	3.6	Normal	1	1	± 3.6 %		
Power Drift	5.0	Rectangular	√3	1	± 2.9 %		
Phantom and Setup							
Phantom Uncertainty	4.0	Rectangular	√3	1	± 2.3 %		
Liquid Conductivity (Target)	5.0	Rectangular	√3	0.64	± 1.8 %		
Liquid Conductivity (Meas.)	2.5	Normal	1	0.64	± 1.6 %		
Liquid Permittivity (Target)	5.0	Rectangular	√3	0.6	± 1.7 %		
Liquid Permittivity (Meas.)	2.5	Normal	1	0.6	± 1.5 %		
Combined Standard Uncertainty							
Coverage Factor for 95 %							
Expanded Uncertainty							

Table 7.2 Uncertainty Budget of DASY for frequency range 300 MHz to 3 GHz

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921

Page Number : 19 of 32 Report Issued Date: Jul. 25, 2012 Report Version : Rev. 01



# 8. SAR Measurement Evaluation

Each DASY system is equipped with one or more system validation kits. These units, together with the predefined measurement procedures within the DASY software, enable the user to conduct the system performance check and system validation. System validation kit includes a dipole, tripod holder to fix it underneath the flat phantom and a corresponding distance holder.

## 8.1 Purpose of System Performance check

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

## 8.2 System Setup

In the simplified setup for system evaluation, the DUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:




Fig 8.1 System Setup for System Evaluation

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 20 of 32
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01



- 1. Signal Generator
- 2. Amplifier
- 3. Directional Coupler
- 4. Power Meter
- 5. Calibrated Dipole

The output power on dipole port must be calibrated to 24 dBm (250 mW) before dipole is connected.



Fig 8.2 Photo of Dipole Setup

### 8.3 Validation Results

Comparing to the original SAR value provided by SPEAG, the validation data should be within its specification of 10 %. Table 8.1 shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Measurement Date	Frequency (MHz)	Liquid Type	Targeted SAR <sub>1g</sub> (W/kg)	Measured SAR <sub>1g</sub> (W/kg)	Normalized SAR <sub>1g</sub> (W/kg)	Deviation (%)
Jul. 16, 2012	835	Head	9.40	2.38	9.52	1.28
Jul. 16, 2012	835	Body	9.42	2.34	9.36	-0.64
Jul. 16, 2012	1900	Head	40.3	9.97	39.88	-1.04
Jul. 16, 2012	1900	Body	41.8	10.1	40.40	-3.35

**Table 8.1 Target and Measurement SAR after Normalized** 

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 21 of 32
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01



# 9. <u>DUT Testing Position</u>

This DUT was tested in three different positions. They are right cheek, left cheek, and Back of the DUT with phantom 1.5 cm gap, as illustrated below:

## 9.1 Define two imaginary lines on the handset

- The vertical centerline passes through two points on the front side of the handset the midpoint of the width w<sub>t</sub> of the handset at the level of the acoustic output, and the midpoint of the width w<sub>b</sub> of the bottom of the handset.
- The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output. The horizontal line is also tangential to the face of the handset at point A.
- The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset, especially for clamshell handsets, handsets with flip covers, and other irregularly shaped handsets.




Fig 9.1 Illustration for Handset Vertical and Horizontal Reference Lines

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921

: 22 of 32 Page Number Report Issued Date: Jul. 25, 2012

Report Version : Rev. 01



### 9.2 Cheek Position

- (a) To position the device with the vertical center line of the body of the device and the horizontal line crossing the center piece in a plane parallel to the sagittal plane of the phantom. While maintaining the device in this plane, align the vertical center line with the reference plane containing the three ear and mouth reference point (M: Mouth, RE: Right Ear, and LE: Left Ear) and align the center of the ear piece with the line RE-LE.
- (b) To move the device towards the phantom with the ear piece aligned with the line LE-RE until the phone touched the ear. While maintaining the device in the reference plane and maintaining the phone contact with the ear, move the bottom of the phone until any point on the front side is in contact with the cheek of the phantom or until contact with the ear is lost (see Fig. 9.2).



Fig 9.2 **Illustration for Cheek Position** 

### 9.3 Tilted Position

- (a) To position the device in the "cheek" position described above.
- (b) While maintaining the device the reference plane described above and pivoting against the ear, moves it outward away from the mouth by an angle of 15 degrees or until contact with the ear is lost (see Fig. 9.3).



Fig 9.3 **Illustration for Tilted Position** 

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921

Page Number : 23 of 32 Report Issued Date: Jul. 25, 2012 Report Version : Rev. 01



# 9.4 Body Worn Position

- (a) To position the device parallel to the phantom surface with either keypad up or down.
- (b) To adjust the device parallel to the flat phantom.
- (c) To adjust the distance between the device surface and the flat phantom to 1.5 cm.




Fig 9.4 Illustration for Body Worn Position

### <DUT Setup Photos>

Please refer to Appendix E for the test setup photos.

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 24 of 32
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01

# 10. Measurement Procedures

The measurement procedures are as follows:

- (a) Use base station simulator (if applicable) or engineering software to transmit RF power continuously (continuous Tx) in the highest power channel.
- (b) Keep DUT to radiate maximum output power or 100% duty factor (if applicable)
- (c) Measure output power through RF cable and power meter.
- (d) Place the DUT in the positions as Appendix E demonstrates.
- (e) Set scan area, grid size and other setting on the DASY software.
- (f) Measure SAR results for the highest power channel on each testing position.
- (g) Find out the largest SAR result on these testing positions of each band
- (h) Measure SAR results for other channels in worst SAR testing position if the SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

### 10.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values form the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

SPORTON INTERNATIONAL (KUNSHAN) INC.

FAX: 86-0512-5790-0958 FCC ID: WVBA921

TEL: 86-0512-5790-0158

Page Number : 25 of 32
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01

### 10.2 Area & Zoom Scan Procedures

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan measures 5x5x7 points with step size 8, 8 and 5 mm for 300 MHz to 3 GHz, and 8x8x8 points with step size 4, 4 and 2.5 mm for 3 GHz to 6 GHz. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g.

## 10.3 Volume Scan Procedures

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the DUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing (step-size is 4, 4 and 2.5 mm). When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

### 10.4 SAR Averaged Methods

In DASY, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5 mm.

### 10.5 Power Drift Monitoring

All SAR testing is under the DUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of DUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 26 of 32
Report Issued Date : Jul. 25, 2012


Report No.: FA260403-01

Report Version : Rev. 01



# 11. SAR Test Configurations

# 11.1 Exposure Positions Consideration



WWAN Antenna	GSM850, GSM1800 <tx rx=""></tx>
Bluetooth Antenna	Bluetooth <tx rx=""></tx>
TV Antenna	receiving only

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 27 of 32
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01



# FCC SAR Test Report

# 11.2 Simultaneous Transmitting Configurations

	Applicable Combination
Simultaneous Transmission	WWAN + Bluetooth

Note: Per KDB KDB 648474 D01, Bluetooth (8.37 dBm) output power ≤ 2Pref and the distance to other antennas ≥ 5cm, therefore, stand-alone SAR is not required; the simultaneous transmission SAR for WWAN and Bluetooth were not required, because Bluetooth standalone SAR is not required and the maximum WWAN SAR (0.560 W/kg), so the SAR summation is less than 1.6 W/kg.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921

Page Number : 28 of 32 Report Issued Date: Jul. 25, 2012

Report No. : FA260403-01

Report Version : Rev. 01



# 12. SAR Test Results

## 12.1 Conducted Power (Unit: dBm)

#### <GSM>

Burst Average Power								
Band		GSM850			GSM1900			
Channel	128	189	251	512	661	810		
Frequency (MHz)	824.2	836.4	848.8	1850.2	1880.0	1909.8		
GSM (1 Uplink)	32.22	32.23	<b>32.29</b>	29.75	29.73	<b>29.76</b>		
GPRS 8 (1 Uplink) - CS1	32.22	32.22	32.28	29.59	29.62	29.65		
GPRS 10 (2 Uplink) - CS1	31.43	31.33	31.34	28.64	28.65	28.66		
GPRS 11 (3 Uplink) - CS1	29.37	29.25	29.23	26.70	26.72	26.75		
GPRS 12 (4 Uplink) - CS1	28.31	28.20	28.19	25.67	25.68	25.79		

Source-Based Time-Averaged Power									
Band		GSM850			GSM1900				
Channel	128	189	251	512	661	810			
Frequency (MHz)	824.2	836.4	848.8	1850.2	1880.0	1909.8			
GSM (1 Uplink)	23.22	23.23	23.29	20.75	20.73	20.76			
GPRS 8 (1 Uplink) – CS1	23.22	23.22	23.28	20.59	20.62	20.65			
GPRS 10 (2 Uplink) - CS1	<b>25.43</b>	25.33	25.34	22.64	22.65	22.66			
GPRS 11 (3 Uplink) – CS1	25.11	24.99	24.97	22.44	22.46	22.49			
GPRS 12 (4 Uplink) – CS1	25.31	25.20	25.19	22.67	22.68	22.79			

**Remark:** The source-based time-averaged power is linearly scaled the maximum burst averaged power based on time slots. The calculated method are shown as below:

Source based time averaged power = Maximum burst averaged power (1 Uplink) - 9 dB

Source based time averaged power = Maximum burst averaged power (2 Uplink) - 6 dB

Source based time averaged power = Maximum burst averaged power (3 Uplink) - 4.26 dB

Source based time averaged power = Maximum burst averaged power (4 Uplink) - 3 dB

### Note:

- 1. For Head SAR testing, GSM should be evaluated, therefore the DUT was set in GSM for GSM850 and set in GSM for GSM1900 due to its highest source-based time-average power.
- 2. For Body-worn SAR testing, GPRS should be evaluated, therefore the DUT was set in GPRS 10 for GSM850 and set in GPRS 12 for GSM1900 due to its highest source-based time-average power.
- 3. Per 2010/10 workshop, the maximum output power channel is used for SAR testing and for further SAR test reduction.
- 4. The DUT do not support DTM function.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 29 of 32
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01



# FCC SAR Test Report

<Bluetooth>

						Avera	ge powe	er (dBm)	)		
Channel Frequency (MHz) Data Rate											
Dissets atla			DH1	DH3	DH5	2DH1	2DH3	2DH5	3DH1	3DH3	3DH5
Bluetooth	CH 00	2402 MHz	5.63	6.07	6.08	4.01	3.71	3.67	4.00	3.70	3.72
	CH 39	2441 MHz	7.43	7.82	7.86	5.67	5.47	5.41	5.71	5.55	5.51
	CH 78	2480 MHz	8.07	8.10	<mark>8.37</mark>	6.29	6.14	6.19	6.44	6.25	6.27

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 30 of 32
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01



# FCC SAR Test Report

# 12.2 Test Records for Head SAR Test

### <GSM>

Plot No.	Band	Mode	Mode Test Ch.		SAR <sub>1g</sub> (W/kg)
1	GSM850	GSM	Left Cheek	251	<mark>0.560</mark>
	GSM1900	GSM	Right Cheek	810	0.329

**Note:** Per KDB 447498, if the highest output channel SAR for each exposure position ≤ 0.8 W/kg other channels SAR tests are not necessary.

# 12.3 Test Records for Body-worn SAR Test

#### <GSM>

Plot No.	Band	Mode	Test Position	Gap (cm)	Ch.	SAR <sub>1g</sub> (W/kg)
3	GSM850	GPRS10	Back	1.5	128	<mark>0.512</mark>
4	GSM1900	GPRS12	Back	1.5	810	<mark>0.455</mark>

**Note:**Per KDB 447498, if the highest output channel SAR for each exposure position ≤ 0.8 W/kg other channels SAR tests are not necessary.

Test Engineer: Jeme Li

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 31 of 32
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01



# 13. References

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2003, "Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- [4] FCC OET Bulletin 65 (Edition 97-01) Supplement C (Edition 01-01), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields", June 2001
- [5] SPEAG DASY System Handbook
- [6] FCC KDB 248227 D01 v01r02, "SAR Measurement Procedures for 802.11 a/b/g Transmitters", May 2007
- [7] FCC KDB 447498 D01 v04, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", November 2009
- [8] FCC KDB 648474 D01 v01r05, "SAR Evaluation Considerations for Handsets with Multiple Transmitters and Antennas", September 2008
- [9] FCC KDB 941225 D01 v02, "SAR Measurement Procedures for 3G Devices CDMA 2000 / Ev-Do / WCDMA / HSDPA / HSPA", October 2007
- [10] FCC KDB 941225 D02 v02 "3GPP R6 HSPA and R7 HSPA+ SAR Guidance", December 2009.
- [11] FCC KDB 941225 D03 v01, "Recommended SAR Test Reduction Procedures for GSM / GPRS / EDGE", December 2008
- [12] FCC KDB 941225 D04 v01, "Evaluating SAR for GSM/(E)GPRS Dual Transfer Mode", January 27 2010
- [13] FCC KDB 941225 D06 v01, "SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities", April 2011
- [14] FCC KDB 388624 D02, "Permit But Ask List", December 2011.

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 32 of 32
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01



# FCC SAR Test Report

# Appendix A. Plots of System Performance Check

The plots are shown as follows.

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : A1 of A1
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01

## System Check\_Head\_835MHz\_120716

#### **DUT: D835V2 - SN: 4d091**

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: HSL\_835\_120716 Medium parameters used: f = 835 MHz;  $\sigma = 0.914$  mho/m;  $\epsilon_r = 41.826$ ;  $\rho$ 

Date: 16.07.2012

 $= 1000 \text{ kg/m}^3$ 

Ambient Temperature : 23.5 °C; Liquid Temperature : 21.5 °C

### DASY5 Configuration:

- Probe: ES3DV3 SN3270; ConvF(6.04, 6.04, 6.04); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

**Pin=250mW/Area Scan (61x61x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 2.55 mW/g


Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 53.204 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 3.597 mW/g

SAR(1 g) = 2.38 mW/g; SAR(10 g) = 1.55 mW/g

Maximum value of SAR (measured) = 2.56 mW/g



### System Check Body 835MHz 120716

#### **DUT: D835V2 - SN: 4d091**

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium: MSL\_835\_120716 Medium parameters used: f = 835 MHz;  $\sigma = 0.97$  mho/m;  $\epsilon_r = 56.499$ ;  $\rho$ 

Date: 16.07.2012

 $= 1000 \text{ kg/m}^3$ 

Ambient Temperature : 23.3 °C; Liquid Temperature : 21.3 °C


### DASY5 Configuration:

- Probe: ES3DV3 SN3270; ConvF(6.16, 6.16, 6.16); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

**Pin=250mW/Area Scan (61x61x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 2.52 mW/g

**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 51.228 V/m; Power Drift = -0.02 dB Peak SAR (extrapolated) = 3.538 mW/g

SAR(1 g) = 2.34 mW/g; SAR(10 g) = 1.52 mW/gMaximum value of SAR (measured) = 2.52 mW/g



## System Check\_Head\_1900MHz\_120716

#### **DUT: D1900V2 - SN: 5d118**

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: HSL\_1900\_120716 Medium parameters used: f = 1900 MHz;  $\sigma = 1.427$  mho/m;  $\varepsilon_r =$ 

Date: 16.07.2012

41.191;  $\rho = 1000 \text{ kg/m}^3$ 

Ambient Temperature: 23.4 °C; Liquid Temperature: 21.4 °C

### DASY5 Configuration:

- Probe: ES3DV3 SN3270; ConvF(5.14, 5.14, 5.14); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)


**Pin=250mW/Area Scan (61x61x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 11.4 mW/g

**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 89.190 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 18.330 mW/g

SAR(1 g) = 9.97 mW/g; SAR(10 g) = 5.21 mW/g

Maximum value of SAR (measured) = 11.2 mW/g



0 dB = 11.2 mW/g = 20.98 dB mW/g

### System Check Body 1900MHz 120716

#### **DUT: D1900V2 - SN: 5d118**

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium: MSL\_1900\_120716 Medium parameters used: f = 1900 MHz;  $\sigma = 1.519$  mho/m;  $\varepsilon_r =$ 

Date: 16.07.2012

53.569;  $\rho = 1000 \text{ kg/m}^3$ 

Ambient Temperature: 23.6 °C; Liquid Temperature: 21.6 °C

### DASY5 Configuration:


- Probe: ES3DV3 SN3270; ConvF(4.64, 4.64, 4.64); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

**Pin=250mW/Area Scan (61x61x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 11.4 mW/g

**Pin=250mW/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm Reference Value = 87.868 V/m; Power Drift = -0.08 dB Peak SAR (extrapolated) = 18.471 mW/g

SAR(1 g) = 10.1 mW/g; SAR(10 g) = 5.25 mW/g

Maximum value of SAR (measured) = 11.5 mW/g





# Appendix B. Plots of SAR Measurement

The plots are shown as follows.

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : B1 of B1
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01

### 01 GSM850\_Left Cheek\_Ch251

#### **DUT: 260403-01**

Communication System: Generic GSM; Frequency: 848.8 MHz; Duty Cycle: 1:8.3

Medium: HSL\_835\_120716 Medium parameters used: f = 849 MHz;  $\sigma = 0.925$  mho/m;  $\epsilon_r = 41.676$ ;  $\rho$ 

Date: 16.07.2012

 $= 1000 \text{ kg/m}^3$ 

Ambient Temperature : 23.5 °C; Liquid Temperature : 21.5 °C

### DASY5 Configuration:

- Probe: ES3DV3 SN3270; ConvF(6.04, 6.04, 6.04); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

**Ch251/Area Scan (51x81x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.592 mW/g


Ch251/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.067 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.720 mW/g

SAR(1 g) = 0.560 mW/g; SAR(10 g) = 0.409 mW/g

Maximum value of SAR (measured) = 0.595 mW/g



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 16.07.2012

### 01 GSM850\_Left Cheek\_Ch251\_2D

#### DUT: 260403-01

Communication System: Generic GSM; Frequency: 848.8 MHz; Duty Cycle: 1:8.3

Medium: HSL\_835\_120716 Medium parameters used: f = 849 MHz;  $\sigma = 0.925$  mho/m;  $\varepsilon_r = 41.676$ ;

 $\rho = 1000 \text{ kg/m}^3$ 

Ambient Temperature : 23.5 °C; Liquid Temperature : 21.5 °C

### **DASY5** Configuration:

- Probe: ES3DV3 SN3270; ConvF(6.04, 6.04, 6.04); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

**Ch251/Area Scan (51x81x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.592 mW/g


Ch251/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.067 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.720 mW/g

SAR(1 g) = 0.560 mW/g; SAR(10 g) = 0.409 mW/g

Maximum value of SAR (measured) = 0.595 mW/g



## 02 GSM1900\_Right Cheek\_Ch810

#### **DUT: 260403-01**

Communication System: Generic GSM; Frequency: 1909.8 MHz; Duty Cycle: 1:8.3

Medium: HSL\_1900\_120716 Medium parameters used: f = 1910 MHz;  $\sigma = 1.436$  mho/m;  $\varepsilon_r =$ 

Date: 16.07.2012

41.187;  $\rho = 1000 \text{ kg/m}^3$ 

Ambient Temperature: 23.4 °C; Liquid Temperature: 21.4 °C

### DASY5 Configuration:

- Probe: ES3DV3 SN3270; ConvF(5.14, 5.14, 5.14); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

**Ch810/Area Scan (51x81x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.334 mW/g


Ch810/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.414 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.595 mW/g

SAR(1 g) = 0.329 mW/g; SAR(10 g) = 0.164 mW/g

Maximum value of SAR (measured) = 0.339 mW/g



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 16.07.2012

### 02 GSM1900\_Right Cheek\_Ch810\_2D

#### DUT: 260403-01

Communication System: Generic GSM; Frequency: 1909.8 MHz; Duty Cycle: 1:8.3

Medium: HSL\_1900\_120716 Medium parameters used: f = 1910 MHz;  $\sigma = 1.436$  mho/m;  $\varepsilon_r =$ 

41.187;  $\rho = 1000 \text{ kg/m}^3$ 

Ambient Temperature : 23.4 °C; Liquid Temperature : 21.4 °C

### DASY5 Configuration:

- Probe: ES3DV3 SN3270; ConvF(5.14, 5.14, 5.14); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

**Ch810/Area Scan (51x81x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.334 mW/g


Ch810/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 3.414 V/m; Power Drift = 0.09 dB

Peak SAR (extrapolated) = 0.595 mW/g

SAR(1 g) = 0.329 mW/g; SAR(10 g) = 0.164 mW/g

Maximum value of SAR (measured) = 0.339 mW/g



### 03 GSM850\_GPRS10\_Back\_1.5cm\_Ch128

#### DUT: 260403-01

Communication System: GPRS/EDGE10; Frequency: 824.2 MHz; Duty Cycle: 1:4

Medium: MSL\_835\_120716 Medium parameters used: f = 824.2 MHz;  $\sigma = 0.96$  mho/m;  $\varepsilon_r = 56.589$ ;

Date: 16.07.2012

 $\rho = 1000 \text{ kg/m}^3$ 

Ambient Temperature : 23.5 °C; Liquid Temperature : 21.5 °C

### DASY5 Configuration:

- Probe: ES3DV3 SN3270; ConvF(6.16, 6.16, 6.16); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

**Ch128/Area Scan (51x81x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.569 mW/g


Ch128/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.147 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.787 mW/g

SAR(1 g) = 0.512 mW/g; SAR(10 g) = 0.335 mW/g

Maximum value of SAR (measured) = 0.545 mW/g



### 03 GSM850\_GPRS10\_Back\_1.5cm\_Ch128\_2D

#### DUT: 260403-01

Communication System: GPRS/EDGE10; Frequency: 824.2 MHz; Duty Cycle: 1:4

Medium: MSL\_835\_120716 Medium parameters used: f = 824.2 MHz;  $\sigma = 0.96$  mho/m;  $\epsilon_r =$ 

56.589;  $\rho = 1000 \text{ kg/m}^3$ 

Ambient Temperature : 23.5 °C; Liquid Temperature : 21.5 °C

### DASY5 Configuration:

- Probe: ES3DV3 SN3270; ConvF(6.16, 6.16, 6.16); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM1; Type: QD000P40CD; Serial: TP:1670
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

**Ch128/Area Scan (51x81x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.569 mW/g


Ch128/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.147 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 0.787 mW/g

SAR(1 g) = 0.512 mW/g; SAR(10 g) = 0.335 mW/g

Maximum value of SAR (measured) = 0.545 mW/g



### 04 GSM1900\_GPRS12\_Back\_1.5cm\_Ch810

#### DUT: 260403-01

Communication System: GPRS/EDGE12; Frequency: 1909.8 MHz; Duty Cycle: 1:2

Medium: MSL\_1900\_120716 Medium parameters used: f = 1910 MHz;  $\sigma = 1.529$  mho/m;  $\varepsilon_r =$ 

Date: 16.07.2012

53.552;  $\rho = 1000 \text{ kg/m}^3$ 

Ambient Temperature : 23.6 °C; Liquid Temperature : 21.6 °C

### **DASY5** Configuration:

- Probe: ES3DV3 SN3270; ConvF(4.64, 4.64, 4.64); Calibrated: 12.09.2011;
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

**Ch810/Area Scan (51x81x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.465 mW/g


Ch810/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.017 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.769 mW/g

SAR(1 g) = 0.455 mW/g; SAR(10 g) = 0.245 mW/g

Maximum value of SAR (measured) = 0.488 mW/g



Test Laboratory: Sporton International Inc. SAR/HAC Testing Lab Date: 16.07.2012

### 04 GSM1900\_GPRS12\_Back\_1.5cm\_Ch810\_2D

#### DUT: 260403-01

Communication System: GPRS/EDGE12; Frequency: 1909.8 MHz; Duty Cycle: 1:2

Medium: MSL\_1900\_120716 Medium parameters used: f = 1910 MHz;  $\sigma = 1.529$  mho/m;  $\epsilon_r =$ 

53.552;  $\rho = 1000 \text{ kg/m}^3$ 

Ambient Temperature : 23.6 °C; Liquid Temperature : 21.6 °C

### DASY5 Configuration:

- Probe: ES3DV3 - SN3270; ConvF(4.64, 4.64, 4.64); Calibrated: 12.09.2011;

- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1303; Calibrated: 10.11.2011
- Phantom: SAM2; Type: QD000P40CD; Serial: TP:1671
- Measurement SW: DASY52, Version 52.8 (1); SEMCAD X Version 14.6.5 (6469)

**Ch810/Area Scan (51x81x1):** Measurement grid: dx=15mm, dy=15mm Maximum value of SAR (interpolated) = 0.465 mW/g

Ch810/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 12.017 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.769 mW/g

SAR(1 g) = 0.455 mW/g; SAR(10 g) = 0.245 mW/g

Maximum value of SAR (measured) = 0.488 mW/g

