

APPLICANT : Brightstar Coporation

EQUIPMENT: Mobile phone

BRAND NAME : Avvio MODEL NAME : Avvio 921 FCC ID : WVBA921

STANDARD : FCC 47 CFR Part 2, 22(H), 24(E)

CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

This is a variant report which is only valid together with the original test report. The product was received on Jun. 07, 2012 and completely tested on Jul. 17, 2012. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI / TIA / EIA-603-C-2004 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Reviewed by:

Jones Tsai / Manager

ilac-MRA



Report No.: FG260403-01

SPORTON INTERNATIONAL (KUNSHAN) INC. No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 1 of 22
Report Issued Date : Jul. 25, 2012

Report Version : Rev. 01



TABLE OF CONTENTS

RE	VISIO	N HISTORY	3
SU	ΙΜΜΔΙ	RY OF TEST RESULT	4
1		ERAL DESCRIPTION	
	1.1 1.2 1.3 1.4 1.5 1.6 1.7	Applicant	5 5 6 6
2	2.1 2.2	T CONFIGURATION OF EQUIPMENT UNDER TEST Test Mode Connection Diagram of Test System	7
3	3.1 3.2 3.3	Conducted Output Power Measurement Effective Radiated Power and Effective Isotropic Radiated Power Measurement Field Strength of Spurious Radiation Measurement	9 11
4	LIST	OF MEASURING EQUIPMENT	21
5	UNC	ERTAINTY OF EVALUATION	22
ΑF	PEND	DIX A. PHOTOGRAPHS OF EUT	
ΑP	PEND	DIX B. SETUP PHOTOGRAPHS	
ΑF	PEND	DIX C. PRODUCT EQUALITY DECLARATION	

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 2 of 22
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG260403-01	Rev. 01	This is a variant report for Avvio 921. The product equality declaration can be referred to Appendix C. All the test cases were performed in original report which can be referred to Sporton Report Number FG260403. Based on original report, only the Conducted Power, ERP/EIRP and Radiated Spurious Emissions were verified.	Jul. 25, 2012

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 3 of 22
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01



SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	§2.1046	N/A	Conducted Output Power	N/A	PASS	-
3.2	§22.913(a)(2)	RSS-132(4.4) SRSP-503(5.1.3)	Effective Radiated Power	< 7 Watts	PASS	-
3.2	§24.232(c)	RSS-133 (6.4) SRSP-510(5.1.2)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
3.3	§2.1053 §22.917(a) §24.238(a)	RSS-132 (4.5.1) RSS-133 (6.5.1)	Field Strength of Spurious Radiation	< 43+10log ₁₀ (P[Watts])	PASS	Under limit 15.43 dB at 3345.000 MHz

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 4 of 22
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01



1 General Description

1.1 Applicant

Brightstar Coporation

9725 NW 117th Ave., Miami, Florida, United States

1.2 Manufacturer

Skycom Telecommunications Co Limited

Room 604, East Block, Shengtang Building, Futian District, Shenzhen, China

1.3 Feature of Equipment Under Test

Product Feature					
Equipment	Mobile phone				
Brand Name	Avvio				
Model Name	Avvio 921				
FCC ID	WVBA921				
EUT supports Radios application	GSM / Bluetooth				
HW Version	X225-MB-V2.1				
SW Version	X225_7E_COMCEL_BT_FM_NMI60X_TP_12832_LCD240 X320_V15_120524_1033				
EUT Stage	Production Unit				

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

r door o mandar for more detailed decomption.					
Product Specification subjective to this standard					
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz				
Rx Frequency	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz				
Maximum Output Power to Antenna	GSM850 : 32.29 dBm GSM1900 : 29.76 dBm				
Antenna Type Fixed Internal Antenna					
Type of Modulation GSM / GPRS: GMSK					

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 5 of 22
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01



1.4 Maximum ERP/EIRP Power

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)
Part 22	GSM850 GSM	GMSK	0.3639
Part 24	GSM1900 GSM	GMSK	0.7079

1.5 Testing Site

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.				
	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P.R.C.				
Test Site Location	TEL: +86-0512-5790-0158				
	FAX: +86-0512-5790-0958				
Took Site No	Sporton Site No.		FCC/IC Registration No.		
Test Site No.	TH01-KS	03CH01-KS	149928/4086E-1		

1.6 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC 47 CFR Part 2, 22(H), 24(E)
- ANSI / TIA / EIA-603-C-2004
- FCC KDB 971168 D01 Power Meas. License Digital Systems v01
- IC RSS-132 Issue 2
- IC RSS-133 Issue 5

Remark:

- 1. All test items were verified and recorded according to the standards and without any deviation during the test.
- 2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

1.7 Ancillary Equipment List

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GWINSTEK	GPS-3030D	N/A	N/A	Unshielded, 1.8 m

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 6 of 22
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01



2 Test Configuration of Equipment Under Test

2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

Frequency range investigated for radiated emission is as follows:

- 30 MHz to 9000 MHz for GSM850.
- 30 MHz to 19000 MHz for GSM1900.

Test Modes							
Band	Radiated TCs	Conducted TCs					
GSM 850	■ GSM Link + SIM 2	■ GSM Link + SIM 2					
GSM 1900	■ GSM Link + SIM 2	■ GSM Link + SIM 2					

Note:

- 1. The maximum power level is GSM mode for GMSK link, only this mode was used for all tests.
- 2. Because there are individual antennas for each WWAN and Bluetooth, the co-location test modes are not required.

The conducted power tables are as follows:

Conducted Power (*Unit: dBm)							
Band		GSM850			GSM1900		
Channel	128	189	251	512	661	810	
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8	
GSM	32.22	32.23	<mark>32.29</mark>	29.75	29.73	<mark>29.76</mark>	
GPRS 8	32.22	32.22	32.28	29.59	29.62	29.65	
GPRS 10	31.43	31.33	31.34	28.64	28.65	28.66	
GPRS 12	28.31	28.20	28.19	25.67	25.68	25.79	


SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 7 of 22
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01



Report No.: FG260403-01

2.2 Connection Diagram of Test System



TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 8 of 22
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01



3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedures

- 1. The transmitter output port was connected to base station.
- 2. Set EUT at maximum power through base station.
- 3. Select lowest, middle, and highest channels for each band and different modulation.
- 4. Compare each band and different modulation combination to show the worst data rate.

3.1.4 Test Setup



TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 9 of 22
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01



3.1.5 Test Result of Conducted Output Power

Cellular Band					
Modes	GSM850 (GSM) 128 189 251 (Low) (Mid) (High)				
Channel					
Frequency (MHz)	824.2	836.4	848.8		
Conducted Power (dBm)	32.22	32.23	32.29		
Conducted Power (Watts)	1.67	1.67	1.69		

PCS Band						
Modes	GSM1900 (GSM)					
Channel	512 661 810 (Low) (Mid) (High					
Frequency (MHz)	1850.2	1880	1909.8			
Conducted Power (dBm)	29.75	29.73	29.76			
Conducted Power (Watts)	0.94	0.94	0.95			

Note: maximum burst average power for GSM.

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 10 of 22
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01



3.2 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

3.2.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-C-2004, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v01. The ERP of mobile transmitters must not exceed 7 Watts and the EIRP of mobile transmitters are limited to 2 Watts.

3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

- 1. The EUT was placed on a turntable with 1.0 meter height in a fully anechoic chamber.
- 2. The EUT was set at 1.2 meters from the receiving antenna, which was mounted on the antenna tower.
- 3. The table was rotated 360 degrees to determine the position of the highest radiated power.
- 4. The height of the receiving antenna is adjusted to look for the maximum ERP/EIRP.
- 5. Taking the record of maximum ERP/EIRP.
- 6. A dipole antenna was substituted in place of the EUT and was driven by a signal generator.
- 7. The conducted power at the terminal of the dipole antenna is measured.
- 8. Repeat step 3 to step 5 to get the maximum ERP/EIRP of the substitution antenna.
- 9. ERP/EIRP = Ps + Et Es + Gs = Ps + Rt Rs + Gs

Ps (dBm): Input power to substitution antenna.

Gs (dBi or dBd): Substitution antenna Gain.

Et = Rt + AF

Es = Rs + AF

AF (dB/m): Receive antenna factor

Rt: The highest received signal in spectrum analyzer for EUT.


Rs: The highest received signal in spectrum analyzer for substitution antenna.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921



Report No.: FG260403-01

3.2.4 Test Setup



TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 12 of 22
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01



3.2.5 Test Result of ERP

	GSM850 (GSM) Radiated Power ERP								
	Horizontal Polarization								
Frequency	Rt	Rs	Ps	Gs	ERP	ERP			
(MHz)	(dBm)	(dBm)	(dBm)	(dBd)	(dBm)	(W)			
824.20	-21.57	-48.12	0.00	-1.08	25.47	0.3524			
836.40	-22.00	-48.28	0.00	-0.93	25.35	0.3428			
848.80	-21.98	-48.35	0.00	-0.76	25.61	0.3639			
		Ve	ertical Polarizati	on					
Frequency	Rt	Rs	Ps	Gs	ERP	ERP			
(MHz)	(dBm)	(dBm)	(dBm)	(dBd)	(dBm)	(W)			
824.20	-33.61	-47.97	0.00	-1.08	13.28	0.0213			
836.40	-34.28	-48.01	0.00	-0.93	12.80	0.0191			
848.80	-34.39	-48.05	0.00	-0.76	12.90	0.0195			

3.2.6 Test Result of EIRP

	GSM1900 (GSM) Radiated Power EIRP									
	Horizontal Polarization									
Frequency (MHz)	Rt (dBm)									
1850.20	-25.54	-51.88	0.00	1.96	28.30	0.6761				
1880.00	-26.49	-52.99	0.00	2.00	28.50	0.7079				
1909.80	-28.71	-54.28	0.00	1.98	27.55	0.5689				
		Ve	ertical Polarizati	on						
Frequency (MHz)	Rt (dBm)	Rs (dBm)	Ps (dBm)	Gs (dBi)	EIRP (dBm)	EIRP (W)				
1850.20	-26.37	-52.13	0.00	1.96	27.72	0.5916				
1880.00	-27.09	-53.17	0.00	2.00	28.08	0.6427				
1909.80	-28.84	-54.13	0.00	1.98	27.27	0.5333				

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 13 of 22
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01



3.3 Field Strength of Spurious Radiation Measurement

3.3.1 Description of Field Strength of Spurious Radiated Measurement

The radiated spurious emission was measured by substitution method according to ANSI / TIA / EIA-603-C-2004. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

- 1. The EUT was placed on a rotatable wooden table with 0.8 meter above ground.
- 2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
- 3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
- 4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
- 5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
- 6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
- 7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
- 8. Taking the record of output power at antenna port.
- 9. Repeat step 7 to step 8 for another polarization.
- 10. EIRP (dBm) = S.G. Power Tx Cable Loss + Tx Antenna Gain
- 11. ERP (dBm) = EIRP 2.15


TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 14 of 22
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01




Report No. : FG260403-01

3.3.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz




SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 15 of 22
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01



Report No.: FG260403-01

For radiated emissions above 1GHz



3.3.5 Test Results of Radiated Emissions (9 KHz ~ 30 MHz)

The low frequency, which started from 9 KHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.


TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 16 of 22
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01



3.3.6 Test Result of Field Strength of Spurious Radiated

Band :	GSM850	Temperature :	21~22°C		
Test Mode :	GSM Link	Relative Humidity :	41~42%		
Test Engineer :	Steven Hao	Polarization :	Horizontal		
Domork .	Spurious emissions within 20.4000MHz wars found mare than 20dB holow limit line				

emark : Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



Site : 03CH01-KS

Condition: FCC PART22 24 HF EIRP FACTOR-09020 HORIZONTAL

EUT : (FG)260403-01

Plan : H


Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
1672	-47.23	-13	-34.23	-47.58	-47.96	1.2	4.08	Н	Pass
2508	-33.45	-13	-20.45	-39.47	-35.98	1.55	6.23	Н	Pass
3345	-36.32	-13	-23.32	-44.39	-39.50	2.1	7.43	Н	Pass
4182	-55.08	-13	-42.08	-63.37	-58.51	2.89	8.47	Н	Pass
5018	-49.79	-13	-36.79	-62.15	-54.27	3.17	9.80	Н	Pass
5854	-47.22	-13	-34.22	-61.93	-52.16	3.12	10.21	Н	Pass
6691	-45.00	-13	-32.00	-62.50	-50.58	3	10.73	Н	Pass

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 17 of 22
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01

Band :	GSM850	Temperature :	21~22°C
Test Mode :	GSM Link	Relative Humidity :	41~42%
Test Engineer :	Steven Hao	Polarization :	Vertical

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



Site : 03CH01-KS

Condition: FCC PART22 24 HF EIRP FACTOR-09020 VERTICAL

EUT : (FG) 260403-01


Plan : H

1757									
Frequency	ERP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
1672	-38.67	-13	-25.67	-40.31	-39.40	1.20	4.08	V	Pass
2509	-29.97	-13	-16.97	-37.45	-32.50	1.55	6.23	V	Pass
3345	-28.43	-13	-15.43	-36.79	-31.61	2.10	7.43	V	Pass
4182	-51.68	-13	-38.68	-58.96	-55.11	2.89	8.47	V	Pass
5018	-56.99	-13	-43.99	-66.01	-61.47	3.17	9.80	V	Pass
5854	-46.15	-13	-33.15	-60.61	-51.09	3.12	10.21	V	Pass
6691	-42.98	-13	-29.98	-59.32	-48.56	3.00	10.73	V	Pass

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 18 of 22
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01

Band :	GSM1900	Temperature :	21~22°C
Test Mode :	GSM Link	Relative Humidity :	41~42%
Test Engineer :	Steven Hao	Polarization :	Horizontal

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



Site : 03CH01-KS

Condition: FCC PART22 24 HF EIRP FACTOR-09020 HORIZONTAL


EUT : (FG) 260403-01

Plan	: H								
Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3760	-39.98	-13	-26.98	-47.53	-45.38	2.51	7.91	Н	Pass
5640	-34.05	-13	-21.05	-52.53	-41.09	3.09	10.13	Н	Pass
7520	-51.59	-13	-38.59	-67.47	-60.06	3.11	11.58	Н	Pass

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 19 of 22
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01

Band :	GSM1900	Temperature :	21~22°C
Test Mode :	GSM Link	Relative Humidity :	41~42%
Test Engineer :	Steven Hao	Polarization :	Vertical

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



Site : 03CH01-KS

Condition: FCC PART22 24 HF EIRP FACTOR-09020 VERTICAL

EUT : (FG) 260403-01

Plan : H

Frequency	EIRP	Limit	Over	SPA	S.G.	TX Cable	TX Antenna	Polarization	Result
			Limit	Reading	Power	loss	Gain		
(MHz)	(dBm)	(dBm)	(dB)	(dBm)	(dBm)	(dB)	(dBi)	(H/V)	
3760	-33.33	-13	-20.33	-44.09	-38.73	2.51	7.91	V	Pass
5640	-36.13	-13	-23.13	-52.57	-43.17	3.09	10.13	V	Pass
7520	-53.21	-13	-40.21	-68.52	-61.68	3.11	11.58	V	Pass

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 20 of 22
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
System Simulator	R&S	CMU200	837587/066	2G Full-Band	Dec. 30, 2011	Jul. 16, 2012	Dec. 29, 2012	Conducted (TH01-KS)
DC Power Supply	GWINSTEK	GPS-3030D	E1884515	N/A	Aug. 23, 2011	Jul. 16, 2012	Aug. 22, 2012	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESCI	100534	9kHz~3GHz	Nov. 09, 2011	Jul. 17, 2012	Nov. 08, 2012	Radiation (03CH01-KS)
Spectrum Analyzer	R&S	FSP40	100319	9kHz~40GHz	Dec. 30, 2011	Jul. 17, 2012	Dec. 29, 2012	Radiation (03CH01-KS)
Bilog Antenna	SCHAFFNER	CBL6112D	23182	25MHz~2GHz	Dec. 08, 2011	Jul. 17, 2012	Dec. 07, 2012	Radiation (03CH01-KS)
Double Ridge Horn Antenna	EMCO	3117	00075959	1GHz~18GHz	Jan. 06, 2012	Jul. 17, 2012	Jan. 05, 2013	Radiation (03CH01-KS)
Amplifier	Wireless	FPA-6592G	060007	30MHz~2GHz	Dec. 30, 2011	Jul. 17, 2012	Dec. 29, 2012	Radiation (03CH01-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Dec. 30, 2011	Jul. 17, 2012	Dec. 29, 2012	Radiation (03CH01-KS)
SHE-EHF Horn	Schwarzbeck	BBHA9170	BBHA170249	15GHz-40GHz	Oct. 11, 2011	Jul. 17, 2012	Oct. 10, 2012	Radiation (03CH01-KS)
Loop Antenna	R&S	HFH2-Z2	860004/00	9kHz~30 MHz	Jul. 28, 2011	Jul. 17, 2012	Jul. 27, 2012	Radiation (03CH01-KS)
System Simulator	R&S	CMU200	116456	Full-Band	Sep. 20, 2011	Jul. 17, 2012	Sep. 19, 2012	Radiation (03CH01-KS)

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 21 of 22
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01



5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of	2.54
Confidence of 95% (U = 2Uc(y))	210-1

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of	
Confidence of 95%	4.72
(U = 2Uc(y))	

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : 22 of 22
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01



Appendix A. Photographs of EUT

Please refer to Sporton report number EP260403-01 as below.

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921 Page Number : A1 of A1
Report Issued Date : Jul. 25, 2012
Report Version : Rev. 01



Appendix C. Product Equality Declaration

SPORTON INTERNATIONAL (KUNSHAN) INC.

TEL: 86-0512-5790-0158 FAX: 86-0512-5790-0958 FCC ID: WVBA921

Page Number : C1 of C1 Report Issued Date: Jul. 25, 2012

Report No.: FG260403-01

Report Version : Rev. 01

Brightstar Corporation

9725 NW 117th Ave., Miami, Florida, United States, 33178 Tel: 1 305.921-1470; Fax: 1 305.863-3367

Date: July 25, 2012

Product Equality Declaration

We, Brightstar Corporation, declare on our sole responsibility for the product of Avvio 921below:

The differences between previous and current model of Avvio 921 are as below:

- 1. Bluetooth part: resistor C501 is change from 0 ohms to 1 ohm
- 2. RF part:

Part Reference	Previous model of Avvio 921	Current model of Avvio 921
SF600 No	No	S)FILTER,SAW,EGSM/DCS
	RX,SFW942PY002,WISOL	
C632	No	22pF
C640	No	6pF
C628 C629	No	2pF
L609 L611	No	18nH 4.7nH
C630 C633	No	2.7pF
C623 C627	22pF 10nH	1.0nH 5.6nH

3. SIM part: Current model of Avvio 921 have two SIM slot, while previous have only one SIM slot.

Except listings above, the others are all the same as previous version.

Should you have any questions or comments regarding this matter, please have my best attention.

Sincerely yours,

Welton Gid