FCC RF Test Report

APPLICANT: Brightstar Corporation

EQUIPMENT: Smartphone

BRAND NAME : Avvio

MODEL NAME : Avvio Q770S, Avvio Q770

MARKETING NAME : Claro Colombia FCC ID : WVBAQ770X

STANDARD : FCC 47 CFR Part 2, 22(H), 24(E)

CLASSIFICATION: PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Mar. 16, 2016 and testing was completed on Mar. 30, 2016. We, SPORTON INTERNATIONAL (SHENZHEN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-D-2010 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (SHENZHEN) INC., the test report shall not be reproduced except in full.

Prepared by: Ken Chen / Manager

Von Cher

Approved by: Jones Tsai / Manager

SPORTON INTERNATIONAL (SHENZHEN) INC.

1F & 2F, Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town, Nanshan District, Shenzhen, Guangdong, P. R. China

Testing Laboratory

Report No.: FG631606

TABLE OF CONTENTS

RE	VISIO	N HISTORY	3
SU	ММА	RY OF TEST RESULT	4
1	GEN	ERAL DESCRIPTION	5
•	1.1	Applicant	
	1.2	Manufacturer	
	1.3	Product Feature of Equipment Under Test	
	1.4	Product Specification of Equipment Under Test	
	1.5	Modification of EUT	
	1.6	Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator	
	1.7	Testing Location	
	1.8	Applicable Standards	8
2	TEST	CONFIGURATION OF EQUIPMENT UNDER TEST	g
	2.1	Test Mode	
	2.2	Connection Diagram of Test System	
	2.3	Support Unit used in test configuration	
	2.4	Measurement Results Explanation Example	
3	CON	DUCTED TEST RESULT	11
	3.1	Measuring Instruments	
	3.2	Test Setup	11
	3.3	Test Result of Conducted Test	11
	3.4	Conducted Output Power	12
	3.5	Peak-to-Average Ratio	13
	3.6	99% Occupied Bandwidth and 26dB Bandwidth Measurement	14
	3.7	Conducted Band Edge	15
	3.8	Conducted Spurious Emission	16
	3.9	Frequency Stability	17
4	RAD	IATED TEST ITEMS	18
	4.1	Measuring Instruments	18
	4.2	Test Setup	18
	4.3	Test Result of Radiated Test	18
	4.4	Effective Radiated Power and Effective Isotropic Radiated Power Measurement	19
	4.5	Field Strength of Spurious Radiation Measurement	21
5	LIST	OF MEASURING EQUIPMENT	22
6	UNC	ERTAINTY OF EVALUATION	23
ΑP	PEND	IX A. TEST RESULTS OF CONDUCTED TEST	
ΑP	PEND	IX B. TEST RESULTS OF RADIATED TEST	
ΑP	PEND	IX C. TEST SETUP PHOTOGRAPHS	

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: WVBAQ770X Page Number : 2 of 23
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report Template No.: BU5-FG22/24 Version 1.1

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG631606	Rev. 01	Initial issue of report	Apr. 25, 2016

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: WVBAQ770X Page Number : 3 of 23
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report Template No.: BU5-FG22/24 Version 1.1

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark	
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-	
3.5	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-	
3.6	§2.1049 §22.917(b) §24.238(b)	Occupied Bandwidth	Reporting Only	PASS	-	
3.7	§2.1051 §22.917(a) §24.238(a)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	-	
3.8	§2.1051 §22.917(a) Conducted Emission §24.238(a)		< 43+10log10(P[Watts])	PASS	-	
3.9	§2.1055 §22.355 Frequency Stability		< 2.5 ppm	DACC		
3.9	§2.1055 §24.235	Temperature & Voltage	Within Authorized Band	PASS	-	
	§22.913(a)(2)	Effective Radiated Power	< 7 Watts	PASS	-	
4.4	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-	
4.5	§2.1053 §22.917(a) §24.238(a)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 20.05 dB at 5640.000 MHz	

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: WVBAQ770X Page Number : 4 of 23
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report Template No.: BU5-FG22/24 Version 1.1

1 General Description

1.1 Applicant

Brightstar Corporation

9725 NW 117th Ave., Miami, Florida, FL 33178, United States

1.2 Manufacturer

KCMobile Co., Itd.

#1305-1, Kolon Digital Tower Villant II, 31, Digital-ro 30-gil, Guro-Gu, Seoul, KOREA (152-727)

1.3 Product Feature of Equipment Under Test

Product Feature				
Equipment	Smartphone			
Brand Name	Avvio			
Model Name	Avvio Q770S, Avvio Q770			
FCC ID	WVBAQ770X			
EUT supports Radios application	GSM/GPRS/EGPRS(Downlink Only)/ WCDMA/HSPA/HSPA+(16QAM uplink is not supported)/ WLAN2.4GHz 802.11b/g/n HT20/HT40 Bluetooth v3.0+EDR/Bluetooth v4.0 LE			
IMEI Code	Conducted: 353041070000796/353041070001109 Radiation: 353041070000499/353041070001141 ERP/EIRP: NA			
HW Version	Y811_MB_V2			
SW Version	Y811.CQ4007.FCC.ROOT.double.V0.1.2016.2.00			
EUT Stage	Production Unit			

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

 ${\it SPORTON\ INTERNATIONAL\ (SHENZHEN)\ INC.}$

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: WVBAQ770X Page Number : 5 of 23
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report Template No.: BU5-FG22/24 Version 1.1

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification				
	GSM/GPRS/EDGE(Downlink Only):			
	850:	824.2 MHz ~ 848.8 MHz		
Ty Francisco	1900:	1850.2 MHz ~ 1909.8MHz		
Tx Frequency	WCDMA:			
	Band V:	826.4 MHz ~ 846.6 MHz		
	Band II:	1852.4 MHz ~ 1907.6 MHz		
	GSM/GPF	RS/EDGE(Downlink Only):		
	850:	869.2 MHz ~ 893.8 MHz		
Dy Fraguency	1900:	1930.2 MHz ~ 1989.8 MHz		
Rx Frequency	WCDMA:			
	Band V:	871.4 MHz ~ 891.6 MHz		
	Band II:	1932.4 MHz ~ 1987.6 MHz		
	GSM/GPRS/EDGE(Downlink Only):			
	850:	31.54 dBm		
Maximum Output Bayyar to Antanna	1900:	29.60 dBm		
Maximum Output Power to Antenna	WCDMA:			
	Band V:	23.79 dBm		
	Band II:	23.31 dBm		
Antenna Type	PIFA Antenna			
	GSM: GMS	K		
	GPRS: GMSK			
	EDGE: GMSK / 8PSK(Downlink Only)			
Type of Modulation	WCDMA: QPSK (Uplink)			
	HSDPA: QPSK (Uplink) HSUPA: QPSK (Uplink)			
		QAM (Uplink)		

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: WVBAQ770X Page Number : 6 of 23
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report Template No.: BU5-FG22/24 Version 1.1

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	C Rule System		Maximum ERP/EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 22	GSM850 GSM	GMSK	0.3603	0.0454 ppm	244KGXW
Part 22	WCDMA Band V RMC 12.2Kbps	QPSK	0.1174	0.0670 ppm	4M16F9W
Part 24	GSM1900 GSM	GMSK	0.2823	0.0340 ppm	244KGXW
Part 24	WCDMA Band II RMC 12.2Kbps	QPSK	0.0905	0.0420 ppm	4M16F9W

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: WVBAQ770X Page Number : 7 of 23
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report Template No.: BU5-FG22/24 Version 1.1

1.7 Testing Location

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.				
	1F & 2F,Building A, Morning Business Center, No. 4003 ShiGu Rd., Xili Town,				
T4 0'4- 14'	Nanshan District, Shenzhen, Guangdong, P. R. China				
Test Site Location	TEL: +86-755-8637-9589				
	FAX: +86-755-8637-9595				
Toot Site No	Sporton Site No.				
Test Site No.	TH01-SZ				

Test Site	SPORTON INTERNATIONAL (SHENZHEN) INC.					
Test Site Location	No. 3 Building, the third floor of south, Shahe River west, Fengzeyuan warehouse, Nanshan District, Shenzhen, Guangdong, P. R. China					
	TEL: +86-755- 3320-2398					
Toot Site No	Sporton Site No. FCC Registration No.					
Test Site No.	03CH01-SZ	831040				

Note: The test site complies with ANSI C63.4 2009 requirement.

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, 22(H), 24(E)
- ANSI / TIA / EIA-603-D-2010
- FCC KDB 971168 D01 Power Meas. License Digital Systems v02r02

Remark:

- All test items were verified and recorded according to the standards and without any deviation during the test.
- 2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

SPORTON INTERNATIONAL (SHENZHEN) INC. TEL: 86-755-8637-9589

FAX: 86-755-8637-9595 FCC ID: WVBAQ770X Page Number : 8 of 23
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report No.: FG631606

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r02 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:

- 1. 30 MHz to 10th harmonic for GSM850 and WCDMA Band V.
- 2. 30 MHz to 10th harmonic for GSM1900 and WCDMA Band II.

All modes and data rates and positions were investigated.


Test modes are chosen to be reported as the worst case configuration below:

Test Modes							
Band	Radiated TCs	Conducted TCs					
GSM 850	■ GSM Link	■ GSM Link					
GSM 1900	■ GSM Link	■ GSM Link					
WCDMA Band V	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link					
WCDMA Band II	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link					

FAX: 86-755-8637-9595 FCC ID: WVBAQ770X Page Number : 9 of 23
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report No.: FG631606

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration

Item Equipment		Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	TOPWORD	3303DR	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.5 dB and a 10dB attenuator.

Example:

 $Offset(dB) = RF \ cable \ loss(dB) + attenuator \ factor(dB).$ = 4.5 + 10 = 14.5 (dB)

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: WVBAQ770X Page Number : 10 of 23
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report No.: FG631606

3 Conducted Test Result

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: WVBAQ770X Page Number : 11 of 23
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report Template No.: BU5-FG22/24 Version 1.1

3.4 Conducted Output Power

3.4.1 Description of the Conducted Output Power

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.4.2 Test Procedures

- 1. The transmitter output port was connected to the system simulator.
- 2. Set EUT at maximum power through system simulator.
- 3. Select lowest, middle, and highest channels for each band and different modulation.
- 4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: WVBAQ770X Page Number : 12 of 23
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report Template No.: BU5-FG22/24 Version 1.1

3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

- 1. The testing follows FCC KDB 971168 D01 v02r02 Section 5.7.1.
- 2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
- 3. Set EUT to transmit at maximum output power.
- 4. When the duty cycle is less than 98%, then signal gating will be implemented on the spectrum analyzer by triggering from the system simulator.
- 5. Set the CCDF (Complementary Cumulative Distribution Function) option of the spectrum analyzer. Record the maximum PAPR level associated with a probability of 0.1%.

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: WVBAQ770X Page Number : 13 of 23
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report Template No.: BU5-FG22/24 Version 1.1

3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.6.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

- 1. The testing follows FCC KDB 971168 v02r02 Section 4.2.
- 2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
- The spectrum analyzer center frequency is set to the nominal EUT channel center frequency.
 The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
- 4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
- 5. Set the detection mode to peak, and the trace mode to max hold.
- 6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace. (this is the reference value)
- 7. Determine the "-26 dB down amplitude" as equal to (Reference Value X).
- 8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the "–X dB down amplitude" determined in step 6. If a marker is below this "-X dB down amplitude" value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
- 9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

Report No.: FG631606

3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

3.7.2 Test Procedures

- 1. The testing follows FCC KDB 971168 D01 v02r02 Section 6.0.
- 2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
- The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator.The path loss was compensated to the results for each measurement.
- 4. The band edges of low and high channels for the highest RF powers were measured.
- 5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
- 6. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)
 - = P(W) [43 + 10log(P)] (dB)
 - = [30 + 10log(P)] (dBm) [43 + 10log(P)] (dB)
 - = -13dBm.

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: WVBAQ770X Page Number : 15 of 23
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report Template No.: BU5-FG22/24 Version 1.1

3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

- 1. The testing follows FCC KDB 971168 D01 v02r02 Section 6.0.
- 2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
- 3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 4. The middle channel for the highest RF power within the transmitting frequency was measured.
- 5. The conducted spurious emission for the whole frequency range was taken.
- 6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
- 7. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)
 - = P(W) [43 + 10log(P)] (dB)
 - = [30 + 10log(P)] (dBm) [43 + 10log(P)] (dB)
 - = -13dBm.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: WVBAQ770X Page Number : 16 of 23
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report No.: FG631606

3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

- 1. The testing follows FCC KDB 971168 D01 v02r02 Section 9.0.
- 2. The EUT was set up in the thermal chamber and connected with the system simulator.
- 3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
- 4. With power OFF, the temperature was raised in 10°C steps up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

- 1. The testing follows FCC KDB 971168 D01 v02r02 Section 9.0.
- 2. The EUT was placed in a temperature chamber at 25±5° C and connected with the system simulator.
- 3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
- 4. The variation in frequency was measured for the worst case.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: WVBAQ770X Page Number : 17 of 23
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report No.: FG631606


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test from 30MHz to 1GHz



4.2.2 For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: WVBAQ770X Page Number : 18 of 23
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report No.: FG631606

4.4 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

4.4.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-D-2010, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02r02. The ERP of mobile transmitters must not exceed 7 Watts (Cellular Band) and the EIRP of mobile transmitters are limited to 2 Watts (PCS Band).

4.4.2 Test Procedures

- The testing follows FCC KDB 971168 D01 v02r02 Section 5.2.1. (for CDMA/WCDMA), Section 5.2.2.2 (for GSM/GPRS/EDGE) and ANSI / TIA-603-D-2010 Section 2.2.17.
- The EUT was placed on a non-conductive rotating platform 0.8 meters high in a semi-anechoic chamber. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and a spectrum analyzer with RMS detector per section 5. of KDB 971168 D01.
- 3. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power. The maximum emission was recorded from analyzer power level (LVL) from the 360 degrees rotation of the turntable and the test antenna raised and lowered over a range from 1 to 4 meters in both horizontally and vertically polarized orientations.
- 4. Effective Isotropic Radiated Power (EIRP) was measured by substitution method according to TIA/EIA-603-D. The EUT was replaced by the substitution antenna at same location, and then a known power from S.G. was applied into the dipole antenna through a Tx cable, and then recorded the maximum Analyzer reading through raised and lowered the test antenna. The correction factor (in dB) = S.G. Tx Cable loss + Substitution antenna gain Analyzer reading. Then the EUT's EIRP was calculated with the correction factor, EIRP = LVL + Correction factor and ERP = EIRP 2.15. Take the record of the output power at substitution antenna.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: WVBAQ770X Page Number : 19 of 23
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report Template No.: BU5-FG22/24 Version 1.1

	GSM/GPRS/EDGE	WCDMA/HSPA
SPAN	500kHz	10MHz
RBW	10kHz	100kHz
VBW	30kHz	300kHz
Detector	RMS	RMS
Trace	Average	Average
Average Type	Power	Power
Sweep Count	100	100

Page Number : 20 of 23
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report Template No.: BU5-FG22/24 Version 1.1

4.5 Field Strength of Spurious Radiation Measurement

4.5.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.5.2 Test Procedures

- The testing follows FCC KDB 971168 D01 v02r02 Section 5.8 and ANSI / TIA-603-D-2010 Section 2.2.12.
- 2. The EUT was placed on a rotatable wooden table 0.8 meters above the ground.
- The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
- 4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
- 5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
- 6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
- 7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
- 8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
- 9. Taking the record of output power at antenna port.
- 10. Repeat step 7 to step 8 for another polarization.
- 11. EIRP (dBm) = S.G. Power Tx Cable Loss + Tx Antenna Gain
- 12.ERP (dBm) = EIRP 2.15
- 13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
- 14. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)
 - = P(W) [43 + 10log(P)] (dB)
 - = [30 + 10log(P)] (dBm) [43 + 10log(P)] (dB)
 - = -13dBm.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: WVBAQ770X Page Number : 21 of 23
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report No.: FG631606

5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	9kHz~40GHz	May 05, 2015	Mar. 17, 2016~ Mar. 18, 2016	May 04, 2016	Conducted (TH01-SZ)
Thermal Chamber	Ten Billion Hongzhangroup	LP-150U	H2014081803	-40~+150°C	Aug. 07, 2015	Mar. 17, 2016~ Mar. 18, 2016	Aug. 06, 2016	Conducted (TH01-SZ)
EMI Test Receiver&SA	Agilent Technologies	N9038A	MY52260185	20Hz~26.5GHz	May 26, 2015	Mar. 30, 2016	May 25, 2016	Radiation (03CH01-SZ)
Spectrum Analyzer	KEYSIGHT	N9010A	MY55150213	10Hz~44GHz; Max 30dBm	Jun. 07, 2015	Mar. 30, 2016	Jun. 06, 2016	Radiation (03CH01-SZ)
Bilog Antenna	TeseQ	CBL6112D	23188	30MHz~2GHz	Oct. 17, 2015	Mar. 30, 2016	Oct. 16, 2016	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS Lindgren	3117	00119436	1GHz~18GHz	Oct. 17, 2015	Mar. 30, 2016	Oct. 16, 2016	Radiation (03CH01-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18GHz~40GHz	Aug. 19, 2015	Mar. 30, 2016	Aug. 18, 2016	Radiation (03CH01-SZ)
Amplifier	Agilent Technologies	83017A	MY39501302	500MHz~26.5GHz	Jan. 12, 2016	Mar. 30, 2016	Jan. 11, 2017	Radiation (03CH01-SZ)
Amplifier	HP	8447F	3113A04622	9kHz~1300MHz / 30 dB	Aug. 07, 2015	Mar. 30, 2016	Aug. 06, 2016	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	TTA1840-35 -HG	1871923	18GHz~40GHz	Jul. 18, 2015	Mar. 30, 2016	Jul. 17, 2016	Radiation (03CH01-SZ)
AC Power Source	Chroma	61601	61601000198 5	N/A	NCR	Mar. 30, 2016	NCR	Radiation (03CH01-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Mar. 30, 2016	NCR	Radiation (03CH01-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Mar. 30, 2016	NCR	Radiation (03CH01-SZ)

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: WVBAQ770X Page Number : 22 of 23
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report Template No.: BU5-FG22/24 Version 1.1

6 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of	4.0 15
_	4.8 dB
Confidence of 95% (U = 2Uc(y))	

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: WVBAQ770X Page Number : 23 of 23
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report Template No.: BU5-FG22/24 Version 1.1

Appendix A. Test Results of Conducted Test

Conducted Output Power (Average power)

SIM1 Card:

Conducted Power (*Unit: dBm)						
Band		GSM850		GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GSM	31.50	<mark>31.54</mark>	31.49	29.35	29.45	29.60
GPRS class 8	31.49	31.52	31.48	29.33	29.43	29.56
GPRS class 10	30.69	30.71	30.68	28.53	28.67	28.82
GPRS class 11	28.87	28.88	28.86	26.40	26.59	26.79
GPRS class 12	27.74	27.76	27.71	24.88	25.06	25.33

	Conducted Power (*Unit: dBm)						
Band	W	CDMA Band	V	WCDMA Band II			
Channel	4132	4182	4233	9262	9400	9538	
Frequency	826.4	836.4	846.6	1852.4	1880	1907.6	
AMR 12.2Kbps	23.78	23.42	23.71	23.20	23.28	22.48	
RMC 12.2Kbps	<mark>23.79</mark>	23.44	23.75	23.21	<mark>23.31</mark>	22.50	
HSDPA Subtest-1	23.15	22.39	23.06	22.17	22.31	21.51	
HSDPA Subtest-2	23.12	22.38	23.00	22.17	22.32	21.51	
HSDPA Subtest-3	22.62	21.89	22.55	21.72	21.86	21.05	
HSDPA Subtest-4	22.58	21.87	22.52	21.71	21.83	21.05	
HSUPA Subtest-1	21.05	20.48	20.97	20.28	20.45	19.81	
HSUPA Subtest-2	21.07	20.45	20.95	20.27	20.40	19.76	
HSUPA Subtest-3	22.11	21.45	21.93	21.25	21.41	20.67	
HSUPA Subtest-4	20.61	19.92	20.49	19.73	19.84	19.09	
HSUPA Subtest-5	23.13	22.52	22.90	22.24	22.42	21.63	

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: WVBAQ770X Page Number : A-1 of 20
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report Template No.: BU5-FG22/24 Version 1.1

SIM2 Card:

	Conducted Power (*Unit: dBm)					
Band		GSM850		GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GSM	31.48	31.52	31.49	29.35	29.43	<mark>29.55</mark>
GPRS class 8	31.47	31.50	31.47	29.32	29.41	29.54
GPRS class 10	30.65	30.70	30.65	28.50	28.65	28.78
GPRS class 11	28.85	28.75	28.80	26.38	26.56	26.76
GPRS class 12	27.70	27.65	27.68	24.83	25.05	25.30

Conducted Power (*Unit: dBm)						
Band	W	CDMA Band	V	WCDMA Band II		
Channel	4132	4182	4233	9262	9400	9538
Frequency	826.4	836.4	846.6	1852.4	1880	1907.6
AMR 12.2Kbps	23.76	23.40	23.71	23.18	23.28	22.46
RMC 12.2Kbps	23.78	23.42	23.73	23.20	<mark>23.29</mark>	22.47
HSDPA Subtest-1	23.14	22.36	23.06	22.12	22.25	21.45
HSDPA Subtest-2	23.09	22.38	23.01	22.15	22.25	21.38
HSDPA Subtest-3	22.58	21.88	22.55	21.71	21.84	20.92
HSDPA Subtest-4	22.56	21.86	22.52	21.72	21.80	20.90
HSUPA Subtest-1	21.06	20.44	20.99	20.27	20.42	19.79
HSUPA Subtest-2	21.06	20.44	20.98	20.25	20.36	19.73
HSUPA Subtest-3	22.09	21.42	21.98	21.24	21.38	20.62
HSUPA Subtest-4	20.59	19.90	20.48	19.71	19.83	19.09
HSUPA Subtest-5	23.10	22.50	23.00	22.20	22.40	21.60

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: WVBAQ770X Page Number : A-2 of 20
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report No.: FG631606

Peak-to-Average Ratio

Mode	GSM850	GSM1900	Limit: 13dB
Mod.	GSM	GSM	Result
Lowest CH	0.14	0.17	
Middle CH	0.14	0.12	PASS
Highest CH	0.17	0.12	

Mode	WCDMA Band V	WCDMA Band II	Limit: 13dB
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	Result
Lowest CH	2.52	2.46	
Middle CH	3.01	2.70	PASS
Highest CH	3.01	2.81	

SPORTON INTERNATIONAL (SHENZHEN) INC.


TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: WVBAQ770X Page Number : A-3 of 20
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report No.: FG631606

GSM1900 (GSM) GSM850 (GSM) Lowest Channel Lowest Channel 14.50 dB 2 ms - RBW 10 MHz 0.01% **Middle Channel Middle Channel** Ref Level 34.50 dBm Offset 14.50 dB Att 30 dB AQT 2 ms ■ RBW 10 MHz | Samples: 130000 | 0.1% | 0.01% | | 0.14 dB | 0.20 dB 0.01% 0.12 dB **Highest Channel Highest Channel** THE STREET 14.50 dB 2 ms • RBW 10 MHz

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: WVBAQ770X Page Number : A-4 of 20
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report No.: FG631606



Page Number : A-5 of 20
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01
Report Template No.: BU5-FG22/24 Version 1.1

26dB Bandwidth

Mode	GSM850	GSM1900
Mod.	GSM	GSM
Lowest CH	0.315	0.317
Middle CH	0.317	0.316
Highest CH	0.319	0.316

Mode	WCDMA Band V	WCDMA Band II
Mod.	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.71	4.71
Middle CH	4.68	4.68
Highest CH	4.68	4.69

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: WVBAQ770X Page Number : A-6 of 20
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report Template No.: BU5-FG22/24 Version 1.1

GSM850 (GSM) GSM1900 (GSM) Lowest Channel Lowest Channel CF 824.2 MHz CF 1.8502 GHz Type | Ref | Trc | Type | Ref | Trc | **Middle Channel Middle Channel** (IIII) 26.00 Type | Ref | Trc | Type Ref Trc Y-value Function 24.54 dam nd8 down **Highest Channel Highest Channel** (W) 27.00 dE

1.0 MHz

CF 1.9098 GHz

Type Ref Trc

SPORTON INTERNATIONAL (SHENZHEN) INC.


TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: WVBAQ770X

CF 848.8 MH: Marker

Type | Ref | Trc |

Page Number : A-7 of 20
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report No.: FG631606



SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: WVBAQ770X Page Number : A-8 of 20
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report No.: FG631606

Occupied Bandwidth

Mode	GSM850	GSM1900
Mod.	GSM	GSM
Lowest CH	0.242	0.243
Middle CH	0.244	0.244
Highest CH	0.243	0.242

Mode	WCDMA Band V	WCDMA Band II
Mod.	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.16	4.16
Middle CH	4.15	4.16
Highest CH	4.15	4.16

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: WVBAQ770X Page Number : A-9 of 20
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report Template No.: BU5-FG22/24 Version 1.1


GSM850 (GSM) GSM1900 (GSM) Lowest Channel Lowest Channel 241.758241758 ki Span 1.0 MHz CF 1.8502 GHz CF 824.2 MHz Type | Ref | Trc | Type | Ref | Trc | Function **Function Result** Function **Function Result** Occ Bw 241.758241758 kHz 242.757242757 kHz **Middle Channel Middle Channel** 31.14 dB 836.416000 Mi 243.756243756 ki CF 1,88 GH Type | Ref | Trc | Type Ref Trc X-value Y-value Function
1.880013 GHz 28.70 dam Function Result 243.756243756 kHz 243.756243756 kHz Occ Bw **Highest Channel Highest Channel** ₩ V 28,91 dBi 1,909775000 GF 241,758241758 kF 242.757242757 ki CF 848.8 MHz Span 1.0 MHz CF 1.9098 GHz 1001 pt Type Ref Trc Type Ref Trc |

242.757242757 kHz

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: WVBAQ770X Page Number : A-10 of 20
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report Template No.: BU5-FG22/24 Version 1.1


241.758241758 kHz



Page Number : A-11 of 20
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01


Report Template No.: BU5-FG22/24 Version 1.1

Conducted Band Edge




TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: WVBAQ770X Page Number : A-12 of 20
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report No.: FG631606




Page Number : A-13 of 20
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report No.: FG631606



Page Number : A-14 of 20
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report No.: FG631606



Page Number : A-15 of 20
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report No.: FG631606

Conducted Spurious Emission

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: WVBAQ770X Page Number : A-16 of 20
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report Template No.: BU5-FG22/24 Version 1.1

GSM850 (GSM) GSM1900 (GSM) Lowest Channel Lowest Channel Ref Level 25.00 dBm Offset 15.00 dB SGL Count 10/10 1 Max LINE_ABS Stop 19.1 GHz Start 30.0 MHz **Middle Channel Middle Channel** Ref Level 24.50 dBm Stop 19.1 GHz Start 30.0 MHz **Highest Channel Highest Channel =** THE I Ref Level 24.50 dBr Ref Level 25.00 Range Low 30.000 MHz

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: WVBAQ770X Page Number : A-17 of 20
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report Template No.: BU5-FG22/24 Version 1.1

WCDMA Band V (RMC 12.2Kbps) WCDMA Band II (RMC 12.2Kbps) **Lowest Channel Lowest Channel** Start 30.0 MHz Range Up **Middle Channel Middle Channel** Stop 9.0 GHz **Highest Channel Highest Channel □** THE T Ref Level 24.50 dBm Ref Level 25.00 dBm Stop 9.0 GHz

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: WVBAQ770X Page Number : A-18 of 20
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report Template No.: BU5-FG22/24 Version 1.1

Frequency Stability

Test Conditions	Middle Channel	GSM850 (GSM)	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0048	
40	Normal Voltage	0.0012	
30	Normal Voltage	0.0036	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0024	
0	Normal Voltage	0.0036	
-10	Normal Voltage	0.0418	PASS
-20	Normal Voltage	0.0048	
-30	Normal Voltage	0.0454	
20	Maximum Voltage	0.0012	
20	Normal Voltage	0.0024	
20	Battery End Point	0.0000	

Test Conditions	Middle Channel	GSM1900 (GSM)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0011	
40	Normal Voltage	0.0340	
30	Normal Voltage	0.0016	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0021	
0	Normal Voltage	0.0298	
-10	Normal Voltage	0.0005	PASS
-20	Normal Voltage	0.0016	
-30	Normal Voltage	0.0319	
20	Maximum Voltage	0.0011	
20	Normal Voltage	0.0021	
20	Battery End Point	0.0037	

Note:

- 1. Normal Voltage = 3.8V.; Battery End Point (BEP) = 3.5 V.; Maximum Voltage =4.35V
- 2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: WVBAQ770X Page Number : A-19 of 20
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report Template No.: BU5-FG22/24 Version 1.1

Test Conditions	Middle Channel	WCDMA Band V (RMC 12.2KbpsRMC 12.2Kbps)	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0670	
40	Normal Voltage	0.0048	
30	Normal Voltage	0.0012	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0084	
0	Normal Voltage	0.0526	
-10	Normal Voltage	0.0024	PASS
-20	Normal Voltage	0.0000	
-30	Normal Voltage	0.0036	
20	Maximum Voltage	0.0036	
20	Normal Voltage	0.0072	
20	Battery End Point	0.0024	

Test Conditions	Middle Channel	WCDMA Band II (RMC 12.2Kbps)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0399	
40	Normal Voltage	0.0005	
30	Normal Voltage	0.0367	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0399	
0	Normal Voltage	0.0420	
-10	Normal Voltage	0.0394	PASS
-20	Normal Voltage	0.0016	
-30	Normal Voltage	0.0404	
20	Maximum Voltage	0.0362	
20	Normal Voltage	0.0351	
20	Battery End Point	0.0372	

Note:

- 1. Normal Voltage = 3.8V. ; Battery End Point (BEP) = 3.5 V.; Maximum Voltage =4.35 V
- 2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: WVBAQ770X Page Number : A-20 of 20
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report Template No.: BU5-FG22/24 Version 1.1

Appendix B. Test Results of Radiated Test

ERP/EIRP

Channel	Mode	Horiz	ontal	Vertical		
Chamilei	Wiode	ERP(dBm)	ERP(W)	ERP(dBm)	ERP(W)	
Lowest	CCMOEO	24.35	0.2724	9.74	0.0094	
Middle	GSM850 GSM	24.84	0.3051	10.27	0.0106	
Highest		25.57	0.3603	10.14	0.0103	
Lowest	MCDMA Bond V	17.36	0.0544	2.82	0.0019	
Middle	WCDMA Band V RMC 12.2Kbps	15.80	0.0380	1.47	0.0014	
Highest		20.70	0.1174	4.54	0.0028	
Limit	ERP < 7W	Res	sult	PASS		

Channel	Mode	Horiz	ontal	Vertical		
Channel	Wode	EIRP(dBm)	EIRP(W)	EIRP(dBm)	EIRP(W)	
Lowest	CCM4000	22.73	0.1876	23.41	0.2193	
Middle	GSM1900	23.16	0.2069	23.85	0.2426	
Highest	GSM	24.05	0.2543	24.51	0.2823	
Lowest	WCDMA Band II	17.67	0.0585	18.49	0.0706	
Middle		18.65	0.0733	19.57	0.0905	
Highest	RMC 12.2Kbps	18.05	0.0638	18.59	0.0723	
Limit	EIRP < 2W	Re	sult	PASS		

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: WVBAQ770X Page Number : B1 of B3
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report No.: FG631606

Radiated Spurious Emission

GSM850 (GSM)										
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	
	1672	-44.26	-13	-31.26	-47.53	-47.23	0.88	6.00	Н	
	2510	-41.94	-13	-28.94	-47.84	-44.55	1.08	5.84	Н	
	3346	-53.76	-13	-40.76	-63.06	-58.13	1.14	7.66	Н	
	4182	-50.28	-13	-37.28	-61.10	-55.55	1.37	8.79	Н	
	5018	-46.83	-13	-33.83	-60.25	-52.97	1.51	9.80	Н	
	5854	-51.37	-13	-38.37	-64.60	-57.90	1.62	10.30	Н	
Middle	6691	-50.28	-13	-36.23	-67.48	-56.80	1.51	11.23	Н	
Middle	1672	-49.19	-13	-36.19	-53.34	-52.16	0.88	6.00	V	
	2510	-37.53	-13	-24.53	-45.65	-40.14	1.08	5.84	V	
	3346	-58.79	-13	-45.79	-65.65	-63.16	1.14	7.66	V	
	4182	-52.65	-13	-39.65	-62.94	-57.92	1.37	8.79	V	
	5018	-54.44	-13	-41.44	-66.43	-60.58	1.51	9.80	V	
	5854	-47.58	-13	-34.58	-63.23	-54.11	1.62	10.30	V	
	6691	-51.20	-13	-22.05	-67.83	-42.62	1.51	11.23	V	

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

GSM1900 (GSM)										
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)	
	3760	-44.12	-13	-31.12	-55.37	-50.86	1.28	8.02	Н	
	5640	-33.05	-13	-20.05	-50.62	-41.47	1.58	10.00	Н	
Middle	7520	-42.82	-13	-29.82	-61.14	-53.14	1.78	12.10	Н	
Middle	3760	-45.74	-13	-32.74	-58.21	-52.48	1.28	8.02	V	
	5640	-37.21	-13	-24.21	-54.11	-45.63	1.58	10.00	V	
	7520	-44.30	-13	-31.30	-62.52	-54.62	1.78	12.10	V	

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

SPORTON INTERNATIONAL (SHENZHEN) INC.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: WVBAQ770X Page Number : B2 of B3
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report No.: FG631606

	WCDMA Band V(RMC 12.2Kbps)										
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)		
	1672	-62.54	-13	-49.54	-64.15	-65.51	0.88	6.00	Н		
	2510	-63.18	-13	-50.18	-67.08	-65.79	1.08	5.84	Н		
Middle	3346	-58.13	-13	-45.13	-67.43	-62.50	1.14	7.66	Н		
Middle	1672	-61.70	-13	-48.70	-64.15	-64.67	0.88	6.00	V		
	2510	-62.62	-13	-49.62	-67.00	-65.23	1.08	5.84	V		
	3346	-60.88	-13	-47.88	-67.74	-65.25	1.14	7.66	V		

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

	WCDMA Band II(RMC 12.2Kbps)										
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)		
	3760	-52.39	-13	-39.39	-63.64	-59.13	1.28	8.02	Н		
	5640	-51.71	-13	-38.71	-67.59	-60.13	1.58	10.00	Н		
Middle	7520	-50.97	-13	-37.97	-69.29	-61.29	1.78	12.10	Н		
Middle	3760	-49.24	-13	-36.24	-61.71	-55.98	1.28	8.02	V		
	5640	-52.55	-13	-39.55	-68.87	-60.97	1.58	10.00	V		
	7520	-52.18	-13	-39.18	-70.4	-62.50	1.78	12.10	V		

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

TEL: 86-755-8637-9589 FAX: 86-755-8637-9595 FCC ID: WVBAQ770X Page Number : B3 of B3
Report Issued Date : Apr. 25, 2016
Report Version : Rev. 01

Report Template No.: BU5-FG22/24 Version 1.1