

# Inter Lab

# FCC Measurement/Technical Report on

# Bluetooth transceiver SS11-J01

Report Reference: ODE\_MJP\_TSBCP\_1007\_FCCa

#### **Test Laboratory:**

7 layers AG Borsigstrasse 11 40880 Ratingen Germany

email: info@7Layers.de



#### Note:

The following test results relate only to the devices specified in this document. This report shall not be reproduced in parts without the written approval of the testing laboratory.

7 layers AG Borsigstrasse 11 40880 Ratingen, Germany Phone: +49 (0) 2102 749 0 Fax: +49 (0) 2102 749 350 www.7Layers.com Aufsichtsratsvorsitzender • Chairman of the Supervisory Board: Markus Becker Vorstand • Board: Dr. H.-J. Meckelburg Wilfried Klassmann

Registergericht • registered in: Düsseldorf, HRB 44096 USt-IdNr • VAT No.: DE 203159652

TAX No. 147/5869/0385



# **Table of Contents**

0	Su	mmary	3
	0.1 0.2	Technical Report Summary Measurement Summary	3 4
1	Ad	ministrative Data	7
	1.1 1.2 1.3 1.4	Testing Laboratory Project Data Applicant Data Manufacturer Data	7 7 7 7
2	Tes	st object Data	8
	2.1 2.2 2.3 2.4 2.5 2.6 2.7	General EUT Description EUT Main components Ancillary Equipment Auxiliary Equipment EUT Setups Operating Modes Product labelling	8 9 9 10 10
3	Tes	st Results	11
	3.1 3.2 3.3 3.4 3.5 3.6 3.7 3.8 3.9	Conducted emissions (AC power line) Occupied bandwidth Peak power output Spurious RF conducted emissions Spurious radiated emissions Band edge compliance Dwell time Channel separation Number of hopping frequencies	11 13 16 19 22 28 32 34 36
4	Tes	st Equipment	37
5	Ph	oto Report	45
6	Se	tup Drawings	47
7	An	nex measurement plots	48
	7.1 7.2 7.3 7.4 7.5 7.6 7.7 7.8 7.9	AC Mains conducted Occupied bandwidth Peak power output Band edge compliance conducted and Spurious RF conducted emissions Band edge compliance radiated Radiated emissions (f < 30 MHz) Dwell time Channel separation Number of hopping frequencies	48 49 58 67 85 88 92 93



# 0 Summary

# 0.1 Technical Report Summary

# Type of Authorization

Certification for an Intentional Radiator (Frequency Hopping Spread Spectrum).

#### **Applicable FCC Rules**

Prepared in accordance with the requirements of FCC Rules and Regulations as listed in 47 CFR Ch.1 Parts 2 (10-1-09 Edition) and 15 (10-1-09 Edition). The following subparts are applicable to the results in this test report.

Part 2, Subpart J - Equipment Authorization Procedures, Certification

Part 15, Subpart C - Intentional Radiators

§ 15.201 Equipment authorization requirement

§ 15.207 Conducted limits

§ 15.209 Radiated emission limits; general requirements

§ 15.247 Operation within the bands 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz

#### Note:

The tests were selected and performed with reference to the FCC Public Notice DA 00-705, released March 30, 2000.

Instead of applying ANSI C63.4-1992 which is referenced in the FCC Public Note, the newer ANSI C63.4-2003 is applied.

#### **Summary Test Results:**

The EUT complied with all performed tests as listed in chapter 0.2 Measurement Summary.



# 0.2 Measurement Summary

FCC Part 15, Subpart C § 15.207							
Conducted emission							
	The measurement was performed according to ANSI C63.4 2003						
OP-Mode	Setup	Port	Final Result				
op-mode 5	Setup_c01	AC Port (power line)	passed				
•	, –	,	•				
FCC Part 15, Subp	art C	§ 15.247 (a) (1)					
Occupied bandwidth	า		_				
The measurement v	vas performed accord	ing to FCC § 15.31	10-1-09 Edition				
OP-Mode	Setup	Port	Final Result				
op-mode 1	Setup_b01	Temp ant.connector	passed				
op-mode 2	Setup_b01	Temp ant.connector	passed				
op-mode 3	Setup_b01	Temp ant.connector	passed				
op-mode 6	Setup_b01	Temp ant.connector	passed				
op-mode 7	Setup_b01	Temp ant.connector	passed				
op-mode 8	Setup_b01	Temp ant.connector	passed				
op-mode 10	Setup_b01	Temp ant.connector	passed				
op-mode 11	Setup_b01	Temp ant.connector	passed				
op-mode 12	Setup_b01	Temp ant.connector	passed				
500 D 45 C		C 4E 047 (b) (4)					
FCC Part 15, Subp	eart C	§ 15.247 (b) (1)					
Peak power output	use performed asserd	ing to ECC & 1E 21	10 1 00 Edition				
	vas performed accord	_	10-1-09 Edition				
OP-Mode op-mode 1	<b>Setup</b> Setup_b01	Port Temp ant.connector	Final Result				
op-mode 2	Setup_b01 Setup_b01	Temp ant.connector	passed passed				
op-mode 3	Setup_b01	Temp ant.connector	passed				
op-mode 6	Setup_b01	Temp ant.connector	passed				
op-mode 7	Setup_b01	Temp ant.connector	passed				
op-mode 8	Setup_b01	Temp ant.connector	passed				
op-mode 10	Setup_b01	Temp ant.connector	passed				
op-mode 11	Setup_b01	Temp ant.connector	passed				
op-mode 12	Setup_b01	Temp ant.connector	passed				
op-mode 12	octup_bo1	remp ant.connector	passeu				
FCC Part 15, Subp	art C	§ 15.247 (d)					
Spurious RF conduc	ted emissions						
	vas performed accord	ing to FCC § 15.31	10-1-09 Edition				
OP-Mode	Setup	Port	Final Result				
op-mode 1	Setup_b01	Temp ant.connector	passed				
op-mode 2	Setup_b01	Temp ant.connector	passed				
op-mode 3	Setup_b01	Temp ant.connector	passed				
op-mode 6	Setup_b01	Temp ant.connector	passed				
op-mode 7	Setup_b01	Temp ant.connector	passed				
op-mode 8	Setup_b01	Temp ant.connector	passed				
op-mode 10	Setup_b01	Temp ant.connector	passed				
op-mode 11	Setup_b01	Temp ant.connector	passed				
op-mode 12	Setup_b01	Temp ant.connector	passed				



# FCC Part 15, Subpart C

§ 15.247 (d), § 15.35 (b), § 15.209

	emissions

The measuremen	t was performed acc	cording to ANSI C63.4	2003
OP-Mode	Setup	Port	Final Result
op-mode 1	Setup_a01	Enclosure	passed
op-mode 2	Setup_a01	Enclosure	passed
op-mode 3	Setup_a01	Enclosure	passed
op-mode 6	Setup_a01	Enclosure	passed
op-mode 7	Setup_a01	Enclosure	passed
op-mode 8	Setup_a01	Enclosure	passed
op-mode 10	Setup_a01	Enclosure	passed
op-mode 11	Setup_a01	Enclosure	passed
op-mode 12	Setup_a01	Enclosure	passed

# FCC Part 15, Subpart C § 15.247 (d)

Band edge compliance

The measurement was performed according to FCC § 15.31 / 10-1-09 Edition / ANSI C63.4 2003

OP-Mode	Setup	Port	Final Result
op-mode 1	Setup_b01	Temp ant.connector	passed
op-mode 3	Setup_b01	Temp ant.connector	passed
op-mode 3	Setup_a01	Enclosure	passed
op-mode 6	Setup_b01	Temp ant.connector	passed
op-mode 8	Setup_b01	Temp ant.connector	passed
op-mode 8	Setup_a01	Enclosure	passed
op-mode 10	Setup_b01	Temp ant.connector	passed
op-mode 12	Setup_b01	Temp ant.connector	passed
op-mode 12	Setup_a01	Enclosure	passed



FCC Part 15, Subpart C

§ 15.247 (a) (1) (iii)

Dwell time

The measurement was performed according to FCC § 15.31

OP-Mode

Setup

Port

10-1-09 Edition Final Result

op-mode 2

Setup b01

Temp ant.connector

passed

FCC Part 15, Subpart C

Channel separation

§ 15.247 (a) (1)

10-1-09 Edition

The measurement was performed according to FCC § 15.31 OP-Mode

Setup

**Final Result** 

op-mode 4

Setup\_b01

Temp ant.connector

passed

FCC Part 15, Subpart C

§ 15.247 (a) (iii) Number of hopping frequencies

The measurement was performed according to FCC § 15.31 OP-Mode

Setup

10-1-09 Edition Final Result

op-mode 4

Setup\_b01

Temp ant.connector

passed



7 layers AG, Borsigstr. 11 40880 Ratingen, Germany Phone +49 (0)2102 749 0

Responsible for Accreditation Scope:

Responsible for Test Report:

Page 6 of 94



# 1 Administrative Data

# 1.1 Testing Laboratory

3	
Company Name:	7 Layers AG
Address	Borsigstr. 11 40880 Ratingen Germany
This facility has been fully described in a under the registration number 96716.	report submitted to the FCC and accepted
The test facility is also accredited by the - Deutscher Akkreditierungs Rat	following accreditation organisation: DAR-Registration no. DGA-PL-192/99-02
Responsible for Accreditation Scope:	DiplIng. Bernhard Retka DiplIng. Robert Machulec DiplIng. Thomas Hoell DiplIng. Andreas Petz
Report Template Version:	2010-05-07
1.2 Project Data	
Responsible for testing and report:	DiplIng. Andreas Petz
Date of Test(s): Date of Report:	2010-06-30 to 2010-07-13 2010-07-28
1.3 Applicant Data	
Company Name:	Toshiba Corporation, Mobile Communications Co.
Address:	1-1, Asahigaoka 3-Chome Hino-Shi, Tokyo, 191-8555
Contact Person:	Japan Mr. Takao Kamei
1.4 Manufacturer Data	
Company Name:	please see applicant data
Address:	
Contact Person:	



# 2 Test object Data

# 2.1 General EUT Description

**Equipment under Test** Bluetooth transceiver

Type Designation: SS11-J01

**Kind of Device:** Mobile Phone with integrated Bluetooth

(optional) Transceiver

**Voltage Type:** AC / DC (of AC/DC converter) /

DC (internal battery)

Voltage level: 120 V / 3.7 V

**Modulation Type:** GFSK, 8DPSK,  $\pi/4$  DQPSK

# General product description:

Bluetooth is a short-range radio link intended to be a cable replacement between portable and/or fixed electronic devices.

Bluetooth operates in the unlicensed ISM Band at 2.4 GHz. In the US a band of 83.5 MHz width is available. In this band, the Bluetooth technology defines 79 RF channels spaced 1 MHz (2402 - 2480 MHz). The actual RF channel is chosen from a pseudo-random hopping sequence through the 79 channels. A channel is occupied for a defined amount of time slots, with a nominal slot length of 625  $\mu$ s. The maximum time slot length on one channel is defined by the packet type and is 0.625 ms for DH1 packets, 1.875 ms for DH3 and 3.125 ms for DH5. The nominal hop rate is 1600 hops/s for DH1, 1600/3 for DH3 and 1600/5 for DH5. All frequencies are equally used. The maximum nominal average time of occupancy is 0.4 s within a period of 79\*0.4 seconds.

The basic data rate of 1 Mbps uses GFSK modulation and the enhanced data rate uses PSK modulation. For the enhanced data rate of 3 Mbps 8DPSK modulation and of 2 Mbps  $\pi/4$  DQPSK modulation is used.

#### Specific product description for the EUT:

The EUT is a mobile phone which uses Bluetooth technology to be connected to peripheral Bluetooth devices.

# The EUT provides the following ports:

#### **Ports**

Temp antenna connector Enclosure Micro-USB port DC Power Supply (by Desktop Station)

The main components of the EUT are listed and described in Chapter 2.2.



# 2.2 EUT Main components

# Type, S/N, Short Descriptions etc. used in this Test Report

Short Description	Equipment under Test	Type Designation	Serial No.	HW Status	SW Status	Date of Receipt
EUT A	Bluetooth	SS11-J01	STSGV0010	001	5009 1907	2010-06-29
(Code:	transceiver		42 09		0961	
Y2001s04)	in mobile					
	phone					
Remark: EUT	A is equipped w	ith an integral a	ntenna (gain =	4.2 dBi).		
EUT B	Bluetooth	SS11-J01	STSGV0010	001	5009 1907	2010-06-29
(Code:	transceiver		53 88		0961	
Y2001t04)	in mobile					
	phone					
Remark: EUT	B is equipped w	ith a temporary	antenna conne	ctor.		

NOTE: The short description is used to simplify the identification of the EUT in this test report.

# 2.3 Ancillary Equipment

For the purposes of this test report, ancillary equipment is defined as equipment which is used in conjunction with the EUT to provide operational and control features to the EUT. It is necessary to configure the system in a typical fashion, as a customer would normally use it. But nevertheless Ancillary Equipment can influence the test results.

Short Description	Equipment under Test	Type Designation	Serial no.	HW Status	SW Status	FCC ID
AE 1 (Code: Y2001- AC01)	AC/DC converter	see photo at chapter 5	see photo at chapter 5	0203PQA	_	-

# 2.4 Auxiliary Equipment

For the purposes of this test report, auxiliary equipment is defined as equipment which is used temporarily to enable operational and control features especially used for the tests of the EUT which is not used during normal operation or equipment that is used during the tests in combination with the EUT but is not subject of this test report. It is necessary to configure the system in a typical fashion, as a customer would normally use it. But nevertheless Auxiliary Equipment can influence the test results.

Short Description	Equipment under Test	Type Designation	Serial no.	HW Status	SW Status	FCC ID
_	_	_	_	_	_	_



# 2.5 EUT Setups

This chapter describes the combination of EUTs and ancillary equipment used for testing.

Setup No.	Combination of EUTs	Description
Setup_a01	EUT A	setup for radiated measurements
Setup_b01	EUT B	setup for conducted measurements
Setup_c01	EUT A + AE1	setup for test conducted emissions (AC power line)

# 2.6 Operating Modes

This chapter describes the operating modes of the EUTs used for testing.

Op. Mode	<b>Description of Operating Modes</b>	Remarks
op-mode 1	The EUT transmits on 2402 MHz	Loopback mode, basic data rate 1 Mbps
op-mode 2	The EUT transmits on 2441 MHz	Loopback mode, basic data rate 1 Mbps
op-mode 3	The EUT transmits on 2480 MHz	Loopback mode, basic data rate 1 Mbps
op-mode 4	The EUT is in Hopping mode	The EUT is hopping on 79 channels, basic data rate 1 Mbps
op-mode 5	Bluetooth "standby", EUT powered	BT module is powered and active; WLAN module is powered and active; GSM link in 1900 band at TCH661 at max. power
op-mode 6	The EUT transmits on 2402 MHz	Loopback mode, enhanced data rate 3 Mbps
op-mode 7	The EUT transmits on 2441 MHz	Loopback mode, enhanced data rate 3 Mbps
op-mode 8	The EUT transmits on 2480 MHz	Loopback mode, enhanced data rate 3 Mbps
op-mode 10	The EUT transmits on 2402 MHz	Loopback mode, enhanced data rate, 2 Mbps
op-mode 11	The EUT transmits on 2441 MHz	Loopback mode, enhanced data rate, 2 Mbps
op-mode 12	The EUT transmits on 2480 MHz	Loopback mode, enhanced data rate, 2 Mbps

# 2.7 Product labelling

#### 2.7.1 FCC ID label

Please refer to the documentation of the applicant.

# 2.7.2 Location of the label on the EUT

Please refer to the documentation of the applicant.



# 3 Test Results

# 3.1 Conducted emissions (AC power line)

Standard FCC Part 15, 10-1-09 Edition Subpart C

The test was performed according to: ANSI C 63.4, 2003

#### 3.1.1 Test Description

The test set-up was made in accordance to the general provisions of ANSI C 63.4-2003. The Equipment Under Test (EUT) was setup in a shielded room to perform the conducted emissions measurements in a typical installation configuration. The EUT was powered from 50µH || 50 Ohm Line Impedance Stabilization Network (LISN). The LISN's unused connections were terminated with 50 Ohm loads.

The measurement procedure consists of two steps. It is implemented into the EMI test software ES-K1 from R&S.

#### Step 1: Preliminary scan

Intention of this step is, to determine the conducted EMI-profile of the EUT. EMI receiver settings:

- Detector: Peak - Maxhold

- Frequency range: 150 kHz - 30 MHz

Frequency steps: 5 kHzIF-Bandwidth: 9 kHz

- Measuring time / Frequency step: 20 ms

- Measurement on phase + neutral lines of the power cords

On basis of this preliminary scan the highest amplitudes and the corresponding frequencies relative to the limit are identified. Emissions above the limit and emissions which are in the 10 dB range below the limit are considered.

#### Step 2: Final measurement

Intention of this step is, to determine the highest emissions with the settings defined in the test specification for the frequencies identified in step 1.

EMI receiver settings:

Detector: Quasi-PeakIF - Bandwidth: 9 kHz

- Measuring time: 1 s / frequency

At each frequency determined in step 1, four measurements are performed in the following combinations:

- 1) Neutral lead reference ground (PE grounded)
- 2) Phase lead reference ground (PE grounded)
- 3) Neutral lead reference ground (PE floating)
- 4) Phase lead reference ground (PE floating)

The highest value is reported.



#### 3.1.2 Test Requirements / Limits

FCC Part 15, Subpart C, §15.207

Frequency Range (MHz) QP Limit (dBμV) AV Limit (dBμV) 0.15 - 0.5 66 to 56 56 to 46 0.5 - 5 56 46 5 - 30 60 50

Used conversion factor: Limit (dB $\mu$ V) = 20 log (Limit ( $\mu$ V)/1 $\mu$ V).

# 3.1.3 Test Protocol

Temperature: 27 °C Air Pressure: 1014 hPa Humidity: 41 %

Op. ModeSetupPortop-mode 5Setup\_c01AC Port (power line)

Power	Frequency	Measured value	Delta to limit	Remarks
line	MHz	dBµV	dBµV	
_	_	_	_	_

Remark: No final measurement was performed because no frequencies (peaks) were found within the offset for acceptance analysis during the preliminary scan. Please see annex for the measurement plot.

# 3.1.4 Test result: Conducted emissions (AC power line)

FCC Part 15, Subpart C	Op. Mode	Result	
	op-mode 5	passed	



#### 3.2 Occupied bandwidth

Standard FCC Part 15, 10-1-09 Edition Subpart C

The test was performed according to: FCC §15.31

# 3.2.1 Test Description

The Equipment Under Test (EUT) was setup to perform the occupied bandwidth measurements.

The reference level is the level of the highest amplitude signal observed from the transmitter at either the fundamental frequency or first-order modulation products in all typical modes of operation, including the unmodulated carrier, even if atypical. The results recorded were measured with the modulation which produces the worst-case (widest) occupied bandwidth. The resolution bandwidth for measuring the reference level and the occupied bandwidth was 30 kHz.

The EUT was connected to the spectrum analyzer via a short coax cable.

#### 3.2.2 Test Requirements / Limits

FCC Part 15, Subpart C, §15.247 (a) (1)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

#### Implication by the test laboratory:

Since the Bluetooth technology defines a fixed channel separation of 1 MHz this design parameter defines the maximum allowed occupied bandwidth depending on the EUT's output power:

- 1. Under the provision that the system operates with an output power not greater than 125 mW (21.0 dBm):
  - Implicit Limit: Max. 20 dB BW = 1.0 MHz / 2/3 = 1.5 MHz
- 2. If the system output power exceeds 125 mW (21.0 dBm): Implicit Limit: Max. 20 dB BW = 1.0 MHz

Used conversion factor: Output power (dBm) = 10 log (Output power (W) / 1mW)

The measured output power of the system is below 125 mW (21.0 dBm). For the results, please refer to the related chapter of this report.

Therefore the limit is determined as 1.5 MHz.



#### 3.2.3 Test Protocol

Temperature: 22-23 °C

Air Pressure: 1006-1007 hPa

Humidity: 32-34 %

Op. Mode Setup Port

op-mode 1 Setup\_b01 Temp ant.connector

20 dB bandwidth MHz	Remarks
0.950	T-

Remark: Please see annex for the measurement plot.

Op. Mode Setup Port

op-mode 2 Setup\_b01 Temp ant.connector

20 dB bandwidth	Remarks
MHz	
0.950	-

Remark: Please see annex for the measurement plot.

Op. Mode Setup Port

op-mode 3 Setup\_b01 Temp ant.connector

20 dB bandwidth	Remarks
MHz	
0.950	_

Remark: Please see annex for the measurement plot.

Op. Mode Setup Port

op-mode 6 Setup\_b01 Temp ant.connector

20 dB bandwidth	Remarks	
MHz		
1 312	_	

Remark: Please see annex for the measurement plot.

Op. Mode Setup Port

op-mode 7 Setup\_b01 Temp ant.connector

20 dB bandwidth	Remarks
MHz	
1.160	-

Remark: Please see annex for the measurement plot.



Op. Mode	Setup	Port
op-mode 8	Setup_b01	Temp ant.connector

20 dB bandwidth MHz	Remarks
1.282	-

Remark: Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 10	Setup b01	Temp ant.connector

20 dB bandwidth MHz	Remarks
1.270	-

Remark: Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 11	Setup b01	Temp ant.connector

20 dB bandwidth MHz	Remarks
1.270	-

Remark: Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 12	Setup_b01	Temp ant.connector

20 dB bandwidth MHz	Remarks
1.270	I.

Remark: Please see annex for the measurement plot.

# 3.2.4 Test result: Occupied bandwidth

FCC Part 15, Subpart C Op. Mode Result

op-mode 1 passed
op-mode 2 passed

op-mode 2	passed
op-mode 3	passed
op-mode 6	passed
op-mode 7	passed
op-mode 8	passed
op-mode 10	passed
op-mode 11	passed
op-mode 12	passed



# 3.3 Peak power output

Standard FCC Part 15, 10-1-09 Edition Subpart C

The test was performed according to: FCC §15.31

# 3.3.1 Test Description

The Equipment Under Test (EUT) was set up to perform the output power measurements. The resolution bandwidth for measuring the output power was set to 3 MHz. The reference level of the spectrum analyzer was set higher than the output power of the EUT. The EUT was connected to the spectrum analyzer via a short coax cable with a known loss.

#### 3.3.2 Test Requirements / Limits

FCC Part 15, Subpart C, §15.247 (b) (1)

- (b) The maximum peak conducted output power of the intentional radiator shall not exceed the following:
- (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt.

Used conversion factor: Limit (dBm) = 10 log (Limit (W)/1mW) ==> Maximum Output Power: 30 dBm



#### 3.3.3 Test Protocol

Temperature: 22-23 °C

Air Pressure: 1006-1007 hPa

Humidity: 32-34 %

Op. Mode Setup Port

op-mode 1 Setup\_b01 Temp.ant.connector

Output power dBm	Remarks
1.4	The EIRP including antenna gain (4.2 dBi) is 5.6 dBm

Remark: Please see annex for the measurement plot.

Op. Mode Setup Port

op-mode 2 Setup\_b01 Temp.ant.connector

Output power dBm	Remarks
1.6	The EIRP including antenna gain (4.2 dBi) is 5.8 dBm

Remark: Please see annex for the measurement plot.

Op. Mode Setup Port

op-mode 3 Setup\_b01 Temp.ant.connector

Output power dBm	Remarks
0.2	The EIRP including antenna gain (4.2 dBi) is 4.4 dBm

Remark: Please see annex for the measurement plot.

Op. Mode Setup Port

op-mode 6 Setup\_b01 Temp.ant.connector

Output power dBm	Remarks
1.0	The FIRP including antenna gain (4.2 dBi) is 5.2 dBm

Remark: Please see annex for the measurement plot.

Op. Mode Setup Port

op-mode 7 Setup\_b01 Temp.ant.connector

Output power dBm	Remarks
1.5	The EIRP including antenna gain (4.2 dBi) is 5.7 dBm

Remark: Please see annex for the measurement plot.

Op. Mode Setup Port

op-mode 8 Setup\_b01 Temp.ant.connector

Output power dBm		Remarks
	-3.5	The EIRP including antenna gain (4.2 dBi) is 0.7 dBm

Remark: Please see annex for the measurement plot.



Op. Mode	Setup	Port
op-mode 10	Setup_b01	Temp.ant.connector

Output power	Remarks	
dBm		
-2.9	The EIRP including antenna gain (4.2 dBi) is 1.3 dBm	

Remark: Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 11	Setup_b01	Temp.ant.connector

Output power dBm		Remarks
	-2.6	The EIRP including antenna gain (4.2 dBi) is 1.6 dBm

Remark: Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 12	Setup_b01	Temp.ant.connector

Output power dBm	Remarks
-3.9	The EIRP including antenna gain (4.2 dBi) is 0.3 dBm

Remark: Please see annex for the measurement plot.

# 3.3.4 Test result: Peak power output

FCC Part 15, Subpart C	Op. M
	op-mo
	010 100 0

Op. Mode	Result
op-mode 1	passed
op-mode 2	passed
op-mode 3	passed
op-mode 6	passed
op-mode 7	passed
op-mode 8	passed
op-mode 10	passed
op-mode 11	passed
op-mode 12	passed



# 3.4 Spurious RF conducted emissions

Standard FCC Part 15, 10-1-09 Edition Subpart C

The test was performed according to: FCC §15.31

# 3.4.1 Test Description

The Equipment Under Test (EUT) was set up to perform the spurious emissions measurements.

The EUT was connected to spectrum analyzer via a short coax cable with a known loss. Analyzer settings:

- Detector: Peak-Maxhold

Frequency range: 30 – 25000 MHz
Resolution Bandwidth (RBW): 100 kHz
Video Bandwidth (VBW): 300 kHz

- Sweep Time: 330 s

The reference value for the measurement of the spurious RF conducted emissions is determined during the test "band edge compliance" (cf. chapter 3.6). This value is used to calculate the 20 dBc limit.

# 3.4.2 Test Requirements / Limits

FCC Part 15, Subpart C, §15.247 (c)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.



#### 3.4.3 Test Protocol

Temperature: 22-23 °C

Air Pressure: 1006-1007 hPa

Humidity: 32-34 %

Op. Mode Setup Port

op-mode 1 Setup\_b01 Temp ant.connector

Frequency	Corrected measurement value dBm	Reference value	Limit	Delta to limit
MHz		dBm	dBm	dB
_	_	1.1	-18.9	_

Remark: No (further) spurious emissions in the range 20 dB below the limit found. Please see annex for the measurement plot.

Op. ModeSetupPortop-mode 2Setup\_b01Temp ant.connector

Frequency MHz	Corrected measurement value dBm	Reference value dBm	Limit dBm	Delta to limit dB
_	_	1.4	-18.6	_

Remark: No (further) spurious emissions in the range 20 dB below the limit found. Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 3	Setup_b01	Temp ant.connector

Frequency MHz	Corrected measurement value dBm	Reference value dBm	Limit dBm	Delta to limit dB
-	_	-0.1	-20.1	_

Remark: No (further) spurious emissions in the range 20 dB below the limit found. Please see annex for the measurement plot.

 Op. Mode
 Setup
 Port

 op-mode 6
 Setup\_b01
 Temp ant.connector

Frequency MHz	Corrected measurement value dBm	Reference value dBm	Limit dBm	Delta to limit dB
_	_	-4.6	-24.6	_
_	_	-4.0	-24.0	

Remark: No (further) spurious emissions in the range 20 dB below the limit found. Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 7	Setup_b01	Temp ant.connector

Frequency MHz	Corrected measurement value dBm	Reference value dBm	Limit dBm	Delta to limit dB
_	ı	-4.5	-24.5	-

Remark: No (further) spurious emissions in the range 20 dB below the limit found. Please see annex for the measurement plot.



Op. Mode	Setup	Port	
op-mode 8	Setup_b01	Temp ant.connector	

Frequency MHz	Corrected measurement value dBm	Reference value dBm	Limit dBm	Delta to limit dB
_	_	-5.6	-25.6	_

Remark: No (further) spurious emissions in the range 20 dB below the limit found. Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 10	Setup_b01	Temp ant.connector

Frequency MHz	Corrected measurement value dBm	Reference value dBm	Limit dBm	Delta to limit dB
_	_	-4.8	-24.8	_

Remark: No (further) spurious emissions in the range 20 dB below the limit found. Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 11	Setup_b01	Temp ant.connector

Frequency MHz	Corrected measurement value dBm	Reference value dBm	Limit dBm	Delta to limit dB
_	_	-4.5	-24.5	_

Remark: No (further) spurious emissions in the range 20 dB below the limit found. Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 12	Setup_b01	Temp ant.connector

Frequency MHz	Corrected measurement value dBm	Reference value dBm	Limit dBm	Delta to limit dB
_	_	-5.8	-25.8	_

Remark: No (further) spurious emissions in the range 20 dB below the limit found. Please see annex for the measurement plot.

# 3.4.4 Test result: Spurious RF conducted emissions

#### FCC Part 15, Subpart C Op. Mode Result op-mode 1 passed op-mode 2 passed op-mode 3 passed op-mode 6 passed op-mode 7 passed op-mode 8 passed op-mode 10 passed

passed passed

op-mode 11

op-mode 12



# 3.5 Spurious radiated emissions

Standard FCC Part 15, 10-1-09 Edition Subpart C

The test was performed according to: ANSI C 63.4, 2003

#### 3.5.1 Test Description

The test set-up was made in accordance to the general provisions of ANSI C 63.4-2003. The Equipment Under Test (EUT) was set up on a non-conductive table  $1.0 \times 2.0 \text{ m}$  in the semi-anechoic chamber. The test was performed at the distance of 3 m between the EUT and the receiving antenna.

The radiated emissions measurements were made in a typical installation configuration. The measurement procedure is implemented into the EMI test software ES-K1 from R&S.

#### 1. Measurement up to 30 MHz

The test set-up was made in accordance to the general provisions of ANSI C 63.4-2003. The Equipment Under Test (EUT) was set up on a non-conductive table in the anechoic chamber

The radiated emissions measurements were made in a typical installation configuration. The measurement procedure is implemented into the EMI test software ES-K1 from R&S. The Loop antenna HFH2-Z2 is used.

**Step 1:** pre-measurement

- Anechoic chamber
- Antenna distance: 10 m
- Detector: Peak-Maxhold
- Frequency range: 0.009 0.15 and 0.15 30 MHz
- Frequency steps: 0.1 kHz and 5 kHz
- IF-Bandwidth: 0.2 kHz and 10 kHz
- Measuring time / Frequency step: 100 ms

Intention of this step is, to determine the radiated EMI-profile of the EUT. Afterwards the relevant emissions for the final measurement are identified.

#### Step 2: final measurement

For the relevant emissions determined in step 1, an additional measurement with the following settings will be performed. Intention of this step is to find the maximum emission level.

- Open area test side
- Antenna distance: according to the Standard
- Detector: Quasi-Peak
- Frequency range: 0.009 30 MHz
- Frequency steps: measurement at frequencies detected in step 1
- IF-Bandwidth: 200 Hz 10 kHz
- Measuring time / Frequency step: 100 ms

# 2. Measurement above 30 MHz and up to 1 GHz

Step 1: Preliminary scan

Preliminary test to identify the highest amplitudes relative to the limit.

Settings for step 1:

- Detector: Peak-Maxhold
- Frequency range: 30 1000 MHz
- Frequency steps: 60 kHzIF-Bandwidth: 120 kHz
- Measuring time / Frequency step: 100 µs (BT Timing 1.25 ms)



- Turntable angle range: -180 to 180°

- Turntable step size: 90°

Height variation range: 1 – 3 m
Height variation step size: 2 m
Polarisation: Horizontal + Vertical

Intention of this step is, to determine the radiated EMI-profile of the EUT. Afterwards the relevant emissions for the final measurement are identified.

#### Step 2: second measurement

For the relevant emissions determined in step 1, an additional measurement with the following settings will be performed. Intention of this step is, to find out the approximate turntable angle and antenna height for each frequency.

- Detector: Peak - Maxhold

- Measured frequencies: in step 1 determined frequencies

IF – Bandwidth: 120 kHzMeasuring time: 100 ms

- Turntable angle range: -180 to 180°

- Turntable step size: 45°

Height variation range: 1 – 4 m
Height variation step size: 0.5 m
Polarisation: horizontal + vertical

After this step the EMI test system has determined the following values for each frequency (of step 1):

- Frequency

- Azimuth value (of turntable)

- Antenna height

The last two values have now the following accuracy:

- Azimuth value (of turntable): 45°

- Antenna height: 0.5 m

#### **Step 3:** final measurement

In this step the accuracy of the turntable azimuth and antenna height will be improved. This is necessary to find out the maximum value of every frequency.

For each frequency, which was determined the turntable azimuth and antenna height will be adjusted. The turntable azimuth will be slowly varied by +/- 22.5° around this value. During this action the value of emission is continuously measured. The turntable azimuth at the highest emission will be recorded and adjusted. In this position the antenna height is also slowly varied by +/- 25 cm around the antenna height determined. During this action the value of emission is also continuously measured. The antenna height of the highest emission will also be recorded and adjusted.

- Detector: Peak - Maxhold

- Measured frequencies: in step 1 determined frequencies

IF – Bandwidth: 120 kHzMeasuring time: 100 ms

- Turntable angle range:  $-22.5^{\circ}$  to + 22.5  $^{\circ}$  around the determined value

- Height variation range: -0.25 m to + 0.2 5m around the determined value

Step 4: final measurement with QP detector

With the settings determined in step 3, the final measurement will be performed: EMI receiver settings for step 4:

- Detector: Quasi-Peak (< 1 GHz)

- Measured frequencies: in step 1 determined frequencies

IF – Bandwidth: 120 kHzMeasuring time: 1 s



#### 3. Measurement above 1 GHz

The following modifications apply to the measurement procedure for the frequency range above 1 GHz:

The measurement distance was reduced to 1 m. The results were extrapolated by the extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements, inverse linear-distance squared for the power reference level measurements). Due to the fact that in this frequency range a double ridged wave guided horn antenna (up to 18 GHz) and a horn antenna (18-25 GHz) are used, the steps 2-4 are omitted. Step 1 was performed with one height of the receiving antenna only. EMI receiver settings:

- Detector: Peak, Average

- IF Bandwidth = 1 MHz

After the measurement a plot will be generated which contains a diagram with the results of the preliminary scan and a chart with the frequencies and values of the results of the final measurement.

For the enhanced data rate packets the test is performed as worst-case-check in order to verify that emissions have a comparable level as found at basic data rate. Typically, the measurement for these packets is performed in the frequency range 1 to 8 GHz but it depends on the emissions found during the test for the basic data rate. Please refer to the results for the used frequency range.

# 3.5.2 Test Requirements / Limits

FCC Part 15, Subpart C, §15.247 (d)

... In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

FCC Part 15, Subpart C, §15.209, Radiated Emission Limits

Frequency in MHz	Limit (μV/m)	Measurement distance (m)	Limit(dBµV/m @10m)
0.009 - 0.49	2400/F(kHz)	300	Limit (dBµV/m)+30dB
0.49 - 1.705	24000/F(kHz)	30	Limit (dBµV/m)+10dB
1.705 - 30	30	30	Limit (dBµV/m)+10dB

Frequency in MHz	Limit (μV/m)	Measurement distance (m)	Limit (dBµV/m)
30 - 88	100	3	40.0
88 - 216	150	3	43.5
216 - 960	200	3	46.0
above 960	500	3	54.0

§15.35(b)

..., there is also a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20 dB above the maximum permitted average limit....

Used conversion factor: Limit  $(dB\mu V/m) = 20 \log (Limit (\mu V/m)/1\mu V/m)$ 



#### 3.5.3 Test Protocol

Temperature: 27-31 °C

Air Pressure: 1008-1014 hPa

Humidity: 38–41 %

# 3.5.3.1 Measurement up to 30 MHz

Op. Mode	Setup	Port
op-mode 1	Setup_a01	Enclosure

Polari- sation	Frequency MHz	Corrected value dBµV/m		Limit dBµV/ m	Limit dBµV/ m	Limit dBµV/ m	Delta to limit dB	Delta to limit dB	
		QP	Peak	AV	QP	Peak	AV	QP/Peak	AV
0°	-	-	-	-	-	_	-	-	-
90°	-	_	_	_	_	-	-	-	-

Remark: No (further) spurious emissions in the range 20 dB below the limit found therefore step 2 was not performed. The found peak at 99.2 kHz is emission from loop antenna power supply.

#### 3.5.3.2 Measurement above 30 MHz

Op. Mode	Setup	Port
op-mode 1	Setup_a01	Enclosure

Polari- sation	Frequency MHz	Corrected value dBµV/m			Limit dBµV/ m	Limit dBµV/ m	Limit dBµV/ m	Delta to limit dB	Delta to limit dB
		QP	Peak	AV	QP	Peak	AV	QP/Peak	AV
Vertical + horizontal	2386	-	53.6	36.3	-	74.0	54.0	20.4	17.7

Remark: No (further) spurious emissions in the range 20 dB below the limit found.

Op. Mode	Setup	Port
op-mode 2	Setup_a01	Enclosure

Polari- sation	Frequency MHz	Corrected value dBµV/m			Limit dBµV/ m	Limit dBµV/ m	Limit dBµV/ m	Delta to limit dB	Delta to limit dB
		QP	Peak	AV	QP	Peak	AV	QP/Peak	AV
Vertical + horizontal	-	-	-	-	-	-	-	-	-

Remark: No (further) spurious emissions in the range 20 dB below the limit found.



Op. Mode Setup Port

op-mode 3 Setup\_a01 Enclosure

Polari- sation	Frequency MHz	Corrected value dBµV/m			Limit dBµV/ m	Limit dBµV/ m	Limit dBµV/ m	Delta to limit dB	Delta to limit dB
		QP	Peak	AV	QP	Peak	AV	QP/Peak	AV
Vertical + horizontal	2484	-	74.0	54.0	-	64.8	36.5	9.2	17.5

Remark: No (further) spurious emissions in the range 20 dB below the limit found.

Op. ModeSetupPortop-mode 6Setup\_a01Enclosure

Polari- sation	Frequency MHz	Cor	Corrected value dBµV/m			Limit dBµV/ m	Limit dBµV/ m	Delta to limit dB	Delta to limit dB
		QP	Peak	AV	QP	Peak	AV	QP/Peak	AV
Vertical +	-	-	-	-	-	-	-	-	-

Remark: No (further) spurious emissions in the range 20 dB below the limit found.

The measurement was performed from 1 GHz up to 8 GHz because no significant spurious emissions were found outside this frequency range in op-mode 1, 2 and 3.

Op. ModeSetupPortop-mode 7Setup\_a01Enclosure

Polari- sation	Frequency MHz	Cor	Corrected value dBµV/m			Limit dBµV/ m	Limit dBµV/ m	Delta to limit dB	Delta to limit dB
		QP	Peak	AV	QP	Peak	AV	QP/Peak	AV
Vertical + horizontal	-	=	=	-	-	-	-	-	-

Remark: No (further) spurious emissions in the range 20 dB below the limit found.

The measurement was performed from 1 GHz up to 8 GHz because no significant spurious emissions were found outside this frequency range in op-mode 1, 2 and 3.

Op. ModeSetupPortop-mode 8Setup\_a01Enclosure

Polari- sation	Frequency MHz	Corrected value dBµV/m			Limit dBµV/ m	Limit dBµV/ m	Limit dBµV/ m	Delta to limit dB	Delta to limit dB
		QP	Peak	AV	QP	Peak	AV	QP/Peak	AV
Vertical + horizontal	2484	İ	64.1	36.4	-	74.0	54.0	9.9	17.6

Remark: No (further) spurious emissions in the range 20 dB below the limit found.

The measurement was performed from 1 GHz up to 8 GHz because no significant spurious emissions were found outside this frequency range in op-mode 1, 2 and 3.



Op. Mode Setup Port

op-mode 10 Setup\_a01 Enclosure

Polari- sation	Frequency MHz	Corrected value dBµV/m			Limit dBµV/ m	Limit dBµV/ m	Limit dBµV/ m	Delta to limit dB	Delta to limit dB
		QP	Peak	AV	QP	Peak	AV	QP/Peak	AV
Vertical + horizontal	-	-	-	-	-	-	-	-	-

Remark: No (further) spurious emissions in the range 20 dB below the limit found.

The measurement was performed from 1 GHz up to 8 GHz because no significant spurious emissions were found outside this frequency range in op-mode 1, 2 and 3.

Op. ModeSetupPortop-mode 11Setup\_a01Enclosure

Polari- sation	Frequency MHz	Cor	Corrected value dBµV/m			Limit dBµV/ m	Limit dBµV/ m	Delta to limit dB	Delta to limit dB
		QP	Peak	AV	QP	Peak	AV	QP/Peak	AV
Vertical + horizontal	-	-	-	-	-	-	-	-	-

Remark: No (further) spurious emissions in the range 20 dB below the limit found.

The measurement was performed from 1 GHz up to 8 GHz because no significant spurious emissions were found outside this frequency range in op-mode 1, 2 and 3.

Op. Mode	Setup	Port
op-mode 12	Setup_a01	Enclosure

Polari- sation	Frequency MHz	Corrected value dBµV/m			Limit dBµV/ m	Limit dBµV/ m	Limit dBµV/ m	Delta to limit dB	Delta to limit dB
		QP	Peak	AV	QP	Peak	AV	QP/Peak	AV
Vertical + horizontal	2484	-	60.0	36.5	-	74.0	54.0	14.0	17.5

Remark: No (further) spurious emissions in the range 20 dB below the limit found.

The measurement was performed from 1 GHz up to 8 GHz because no significant spurious emissions were found outside this frequency range in op-mode 1, 2 and 3.

#### 3.5.4 Test result: Spurious radiated emissions

FCC Part 15, Subpart C

Op. Mode	Result
op-mode 1	passed
op-mode 2	passed
op-mode 3	passed
op-mode 6	passed
op-mode 7	passed
op-mode 8	passed
op-mode 10	passed
op-mode 11	passed
op-mode 12	passed



# 3.6 Band edge compliance

Standard FCC Part 15, 10-1-09 Edition Subpart C

The test was performed according to: ANSI C 63.4, 2003 FCC §15.31

#### 3.6.1 Test Description

The procedure to show compliance with the band edge requirement is divided into two measurements: 1. Show compliance of the lower band edge by a conducted measurement and 2. show compliance of the higher band edge by a radiated and conducted measurement.

For the first measurement the EUT is set to transmit on the lowest channel (2402 MHz). The lower band edge is 2400 MHz.

Analyzer settings:
- Detector: Peak
- RBW= 100 kHz
- VBW= 300 kHz

For the second measurement the EUT is set to transmit on the highest channel (2480 MHz). The higher band edge is 2483.5 MHz.

Analyzer settings for conducted measurement:

Detector: Peak
RBW= 100 kHz
VBW= 300 kHz
EMI receiver settings:
Detector: Peak, Average
IF Bandwidth = 1 MHz

#### 3.6.2 Test Requirements / Limits

FCC Part 15.247 (d)

"In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

. . .

Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c))."

For the measurement of the **lower band edge** the RF power at the band edge shall be "at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power..."

For the measurement of the **higher band edge** the limit is "specified in Section 15.209(a)".



#### 3.6.3 Test Protocol

# 3.6.3.1 Lower band edge

# **Conducted measurement**

Temperature: 22-23 °C

Air Pressure: 1006-1007 hPa

Humidity: 32-34 %

Op. Mode Setup Port

op-mode 1 Setup\_b01 Temp ant.connector

Frequency	requency Measured value Reference value		Limit	Delta to limit	
MHz dBm		dBm	dBm	dB	
2400.00	-36.4	1.1	-18.9	17.5	

Remark: Please see annex for the measurement plot.

Op. ModeSetupPortop-mode 6Setup\_b01Temp ant.connector

Frequency MHz	• •		Limit dBm	Delta to limit dB	
2400.00	-43.9	-4.6	-24.6	19.3	

Remark: Please see annex for the measurement plot.

Op. ModeSetupPortop-mode 10Setup\_b01Temp ant.connector

Frequency MHz	•		Limit dBm	Delta to limit dB	
2400.00	-44.0	-4.8	-24.8	19.2	

Remark: Please see annex for the measurement plot.



# 3.6.3.2 Higher band edge

#### **Conducted measurement**

Temperature: 22-23 °C

Air Pressure: 1006-1007 hPa

Humidity: 32-34 %

Op. ModeSetupPortop-mode 3Setup\_b01Temp ant.connector

Frequency	Measured value	Reference value	Limit	Delta to limit
MHz	dBm	dBm	dBm	dB
2483.50	-44.9	-0.1	-20.1	24.8

Remark: Please see annex for the measurement plot.

Op. Mode	Setup	Port	
op-mode 8	Setup_b01	Temp ant.connector	

Frequency Measured value MHz dBm		Reference value dBm		
2483.50	-50.9	-5.6	-25.6	25.3

Remark: Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 12	Setup_b01	Temp ant.connector

	Frequency Measured value MHz dBm		Reference value Limit		Delta to limit	
			dBm	dBm	dB	
	2483.50	-50.7	-5.8	-25.8	24.9	

Remark: Please see annex for the measurement plot.



#### **Radiated measurement**

Temperature: 28 °C Air Pressure: 1013 hPa Humidity: 38 %

Op. ModeSetupPortop-mode 3Setup\_a01Enclosure

Frequency MHz	Polarisation	Corrected value dBµV/m		Limit Peak	Limit AV	Delta to Peak	Delta to AV limit
		Peak	AV	dBµV/m	dBμV/m	limit/dB	dB
2483.50	Vertical + horizontal	64.8	36.5	74.0	54.0	9.2	17.5

Remark: Please see annex for the measurement plot.

Op. Mode	Setup	Port
op-mode 8	Setup_a01	Enclosure

Frequency MHz	Polarisation		ed value V/m	Limit Peak	Limit AV	Delta to Peak	Delta to AV limit
		Peak	AV	dBµV/m	dBµV/m	limit/dB	dB
2483.50	Vertical + horizontal	64.1	36.4	74.0	54.0	9.9	17.6

Remark: Please see annex for the measurement plot.

Op. Mode	Setup	Port	
op-mode 12	Setup_a01	Enclosure	

Frequency MHz	Polarisation		ed value V/m	Limit Peak	Limit AV	Delta to Peak	Delta to AV limit
		Peak	AV	dBµV/m	dBμV/m	limit/dB	dB
2483.50	Vertical + horizontal	60.0	36.6	74.0	54.0	14.0	17.4

Remark: Please see annex for the measurement plot.

# 3.6.4 Test result: Band edge compliance

 FCC Part 15, Subpart C
 Op. Mode op-mode 1 passed op-mode 3 passed op-mode 6 passed op-mode 8 op-mode 8 op-mode 10 passed

passed

op-mode 12



#### 3.7 Dwell time

Standard FCC Part 15, 10-1-09 Edition Subpart C

The test was performed according to: FCC §15.31

# 3.7.1 Test Description

The Equipment Under Test (EUT) was set up to perform the dwell time measurements. The EUT was connected to the spectrum analyzer via a short coax cable. The dwell time is calculated by:

Dwell time = time slot length \* hop rate / number of hopping channels \* 31.6 s

#### with:

- hop rate = 1600 \* 1/s for DH1 packets =  $1600 s^{-1}$
- hop rate =  $1600/3 \times 1/s$  for DH3 packets =  $533.33 \text{ s}^{-1}$
- hop rate = 1600/5 \* 1/s for DH5 packets =  $320 s^{-1}$
- number of hopping channels = 79
- 31.6 s = 0.4 seconds multiplied by the number of hopping channels = 0.4 s \* 79

The highest value of the dwell time is reported.

#### 3.7.2 Test Requirements / Limits

FCC Part 15, Subpart C, §15.247 (a) (1) (iii)

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Since the Bluetooth technology uses 79 channels this period is calculated to be 31.6 seconds.



#### 3.7.3 Test Protocol

Temperature: 22 °C Air Pressure: 1007 hPa Humidity: 32 %

Op. Mode Setup Port

op-mode 2 Setup\_b01 Temp ant.connector

Packet type	Time slot length	Dwell time	Dwell time
	ms		ms
DH5	2.906	time slot length * 1600/5 /79 * 31.6	371.97

Remark: Please see annex for the measurement plots.

# 3.7.4 Test result: Dwell time

FCC Part 15, Subpart C	Op. Mode	Result
	op-mode 2	passed



#### 3.8 Channel separation

Standard FCC Part 15, 10-1-09 Edition Subpart C

The test was performed according to: FCC §15.31

# 3.8.1 Test Description

The Equipment Under Test (EUT) was set up to perform the channel separation measurements. The channel separation is independent from the modulation pattern. The EUT was connected to spectrum analyzer via a short coax cable.

Analyzer settings:

- Detector: Peak-Maxhold

- Span: 3 MHz

- Centre Frequency: a mid frequency of the 2.4 GHz ISM band

Resolution Bandwidth (RBW): 30 kHzVideo Bandwidth (VBW): 100 kHz

- Sweep Time: Coupled

# 3.8.2 Test Requirements / Limits

FCC Part 15, Subpart C, §15.247 (a) (1)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.



#### 3.8.3 Test Protocol

Temperature: 22 °C Air Pressure: 1007 hPa Humidity: 32 %

Op. Mode Setup Port

op-mode 4 Setup\_b01 Temp ant.connector

Channel separation MHz	Remarks
1.000	-

Remark: Please see annex for the measurement plot.

# 3.8.4 Test result: Channel separation

FCC Part 15, Subpart C	Op. Mode	Result
	op-mode 4	passed



# 3.9 Number of hopping frequencies

Standard FCC Part 15, 10-1-09 Edition Subpart C

The test was performed according to: FCC §15.31

#### 3.9.1 Test Description

The Equipment Under Test (EUT) was set up to perform the number of hopping frequencies measurement. The number of hopping frequencies is independent from the modulation pattern.

The EUT was connected to spectrum analyzer via a short coax cable.

Analyzer settings:

Detector: Peak-MaxholdCentre frequency: 2442 MHzFrequency span: 84 MHz

Resolution Bandwidth (RBW): 100 kHzVideo Bandwidth (VBW): 300 kHz

- Sweep Time: Coupled

# 3.9.2 Test Requirements / Limits

FCC Part 15, Subpart C, §15.247 (a) (iii)

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

#### 3.9.3 Test Protocol

Temperature: 22 °C Air Pressure: 1007 hPa Humidity: 32 %

Op. Mode	Setup	Port
op-mode 4	Setup_b01	Temp ant.connector

Number of hopping channels	Remarks
79	-

Remark: Please see annex for the measurement plot.

#### 3.9.4 Test result: Number of hopping frequencies

FCC Part 15, Subpart C	Op. Mode	Result
	op-mode 4	passed



# 4 Test Equipment

The calibration, hardware and software states are shown for the testing period.

#### **Test Equipment Anechoic Chamber**

Lab 1D: Lab 2
Manufacturer: Frankonia

Description: Anechoic Chamber for radiated testing

*Type:* 10.58x6.38x6

 IC renewal
 2009/01/21
 2011/01/20

 FCC renewal
 2009/01/07
 2011/01/06

#### Single Devices for Anechoic Chamber

Single Device Name	Туре	Serial Number	Manufacturer
Air compressor	none	-	Atlas Copco
Anechoic Chamber	10.58 x 6.38 x 6 Calibration Details	none	Frankonia Last Execution Next Exec.
	FCC listing 96716 3m Part15/18 ANSI C64.3 NSA		2009/01/07 2011/01/06 2009/01/21 2011/01/20
Controller Innco 2000	CO 2000	CO2000/328/1247 406/L	70 Innco innovative constructions GmbH
EMC camera	CE-CAM/1	-	CE-SYS
EMC camera Nr.2	CCD-400E	0005033	Mitsubishi
Filter ISDN	B84312-C110-E1		Siemens&Matsushita
Filter Universal 1A	BB4312-C30-H3	-	Siemens&Matsushita

#### **Test Equipment Auxiliary Equipment for Conducted emissions**

Lab ID: Lab 1

Manufacturer: Rohde & Schwarz GmbH & Co.KG

Description: EMI Conducted Auxiliary Equipment

#### Single Devices for Auxiliary Equipment for Conducted emissions

Single Device Name	Туре	Serial Number	Manufacturer
Cable "LISN to ESI"	RG214	W18.03+W48.03	Huber&Suhner
Coupling-Decoupling- Network	CDN ENY41	100002	Rohde & Schwarz GmbH & Co. KG
	Calibration Details		Last Execution Next Exec.
	Standard Calibration		2008/03/06 2011/03/05
Two-Line V-Network	ESH 3-Z5	828304/029	Rohde & Schwarz GmbH & Co. KG
Two -Line V-Network	ESH 3-Z5	829996/002	Rohde & Schwarz GmbH & Co. KG
	Calibration Details		Last Execution Next Exec.
	DKD calibration		2008/10/13 2011/10/12



## Test Equipment Auxiliary Equipment for Radiated emissions

Lab ID: Lab 2

Description: Equipment for emission measurements

Serial Number: see single devices

## Single Devices for Auxiliary Equipment for Radiated emissions

Single Device Name	Туре	Serial Number	Manufacturer
Antenna mast	AS 620 P		HD GmbH
Biconical dipole	VUBA 9117 Calibration Details	9117108	Schwarzbeck Last Execution Next Exec.
	Standard Calibration		2008/10/27 2013/10/26
Broadband Amplifier 18MHz-26GHz	JS4-18002600-32-5P	849785	Miteq
	Path Calibration		2010/05/10 2010/11/09
Broadband Amplifier 1GHz-4GHz	AFS4-01000400-1Q-10P-4	-	Miteq
	Path Calibration		2010/05/10 2010/11/09
Broadband Amplifier 30MHz-18GHz	JS4-00101800-35-5P	896037	Miteq
	Path Calibration		2010/05/10 2010/11/09
Cable "ESI to EMI Antenna"	EcoFlex10	W18.01-2+W38.01 2	- Kabel Kusch
	Path Calibration		2010/05/10 2010/11/09
Cable "ESI to Horn Antenna"	UFB311A+UFB293C	W18.02-2+W38.02 2	- Rosenberger Micro-Coax
	Path Calibration		2010/05/10 2010/11/09
Double -ridged horn	HF 906	357357/001	Rohde & Schwarz GmbH & Co. KG
	Calibration Details		Last Execution Next Exec.
	Standard Calibration		2009/04/16 2012/04/15
Double -ridged horn	HF 906	357357/002	Rohde & Schwarz GmbH & Co. KG
	Calibration Details		Last Execution Next Exec.
	Standard Calibration		2009/04/28 2012/04/27
Dreheinheit	DE 325		HD GmbH
High Pass Filter	4HC1600/12750-1.5-KK Path Calibration	9942011	Trilithic 2010/05/10 2010/11/09
High Pass Filter	5HC2700/12750-1.5-KK Path Calibration	9942012	Trilithic 2010/05/10 2010/11/09
High Pass Filter	5HC3500/12750-1.2-KK Path Calibration	200035008	Trilithic 2010/05/10 2010/11/09
Logper. Antenna	HL 562 Ultralog	830547/003	Rohde & Schwarz GmbH & Co. KG
	Calibration Details		Last Execution Next Exec.
	Standard Calibration		2009/05/27 2012/05/26
Loop Antenna	HFH2-Z2	829324/006	Rohde & Schwarz GmbH & Co. KG
	Calibration Details		Last Execution Next Exec.
	DKD calibration		2008/10/07 2011/10/06
Pyramidal Horn Antenna 26,5 GHz	3160-09	00083069	EMCO Elektronik GmbH
Pyramidal Horn Antenna 40 GHz	3160-10	00086675	EMCO Elektronik GmbH

Test report Reference: ODE\_MJP\_TSBCP\_1007\_FCCa



## **Test Equipment Auxiliary Test Equipment**

Lab ID: Lab 2

Manufacturer: see single devices

Description: Single Devices for various Test Equipment

Type: various Serial Number: none

## **Single Devices for Auxiliary Test Equipment**

Single Device Name	Туре	Serial Number	Manufacturer
AC Power Source	Chroma 6404	64040001304	Chroma ATE INC.
Broadband Power Divide N (Aux)	er1506A / 93459	LM390	Weinschel Associates
Broadband Power Divide SMA	erWA1515	A855	Weinschel Associates
Digital Multimeter 01 (Multimeter)	Voltcraft M-3860M	IJ096055	Conrad Electronics
Digital Multimeter 03 (Multimeter)	Fluke 177	86670383	Fluke Europe B.V.
(Mattineter)	Standard calibration		2009/10/07 2011/10/06
Digital Oscilloscope [SA2] (Aux)	TDS 784C	B021311	Tektronix GmbH
Fibre optic link Satellite (Aux)	FO RS232 Link	181-018	Pontis
Fibre optic link Transceiver (Aux)	FO RS232 Link	182-018	Pontis
Isolating Transformer	LTS 604	1888	Thalheimer Transformatorenwerke GmbH
Notch Filter Ultra Stable (Aux)	e WRCA800/960-6EEK	24	Wainwright
Spectrum Analyser	FSP3	836722/011	Rohde & Schwarz GmbH & Co. KG
	Calibration Details		Last Execution Next Exec.
	DKD calibration		2008/10/06 2011/10/05
Vector Signal Generator	r SMIQ B3	832492/061	



## **Test Equipment Digital Signalling Devices**

Lab ID: Lab 1, Lab 2

Description: Signalling equipment for various wireless technologies.

#### **Single Devices for Digital Signalling Devices**

•			
Single Device Name	Туре	Serial Number	Manufacturer
Bluetooth Signalling Unit	t CBT	100589	Rohde & Schwarz GmbH & Co. KG
	Calibration Details		Last Execution Next Exec.
	Standard Calibration		2008/08/14 2011/08/13
Digital Radio Communication Tester	CMD 55	831050/020	Rohde & Schwarz GmbH & Co. KG
	Calibration Details		Last Execution Next Exec.
	Standard calibration		2008/10/07 2010/10/06
Digital Radio Test Set	6103E	2359	Racal Instruments, Ltd.
Universal Radio Communication Tester	CMU 200	102366	Rohde & Schwarz GmbH & Co. KG
	Calibration Details		Last Execution Next Exec.
	Standard calibration		2009/02/16 2012/02/15
	HW/SW Status		Date of Start Date of End
	B11, B21V14, B21-2, B41, B52V14, B5. B53-2, B56V14, B68 3v04, PCMCIA, U6 Software:  K21 4v21, K22 4v21, K23 4v21, K24 4v K43 4v21, K53 4v21, K56 4v22, K57 4v K59 4v22, K61 4v22, K62 4v22, K63 4v K65 4v22, K66 4v22, K67 4v22, K68 4v Firmware:  μP1 8v50 02.05.06	5V04 /21, K42 4v21, v22, K58 4v22, v22, K64 4v22,	
Universal Radio Communication Tester	CMU 200	837983/052	Rohde & Schwarz GmbH & Co. KG
	Calibration Details		Last Execution Next Exec.
	Standard calibration		2008/12/01 2011/11/30
	HW/SW Status		Date of Start Date of End
	HW options: B11, B21V14, B21-2, B41, B52V14, B5. B54V14, B56V14, B68 3v04, B95, PCM0 SW options: K21 4v11, K22 4v11, K23 4v11, K24 4v K28 4v10, K42 4v11, K43 4v11, K53 4v K66 4v10, K68 4v10, Firmware: μP1 8v40 01.12.05	CIA, U65V02 v11, K27 4v10,	2007/01/02
	SW: K62, K69		2008/11/03
Vector Signal Generator	SMU200A	100912	Rohde & Schwarz GmbH & Co. KG
	Calibration Details		Last Execution Next Exec.
	Standard calibration		2008/10/28 2011/10/27



#### Test Equipment Emission measurement devices

Lab ID: Lab 1, Lab 2

Description: Equipment for emission measurements

Serial Number: see single devices

#### Single Devices for Emission measurement devices

Single Device Name	Туре	Serial Number	Manufacturer
Personal Computer	Dell	30304832059	Dell
Signal Generator	SMR 20	846834/008	Rohde & Schwarz GmbH & Co. KG
	Calibration Details		Last Execution Next Exec.
	Standard Calibration		2007/12/05 2010/12/04
Spectrum Analyzer	ESIB 26	830482/004	Rohde & Schwarz GmbH & Co. KG
	Standard Calibration		2009/12/03 2011/12/02

## **Test Equipment Multimeter 12**

Lab 1D:Lab 3, Lab 4Description:Ex-Tech 520Serial Number:05157876

#### **Single Devices for Multimeter 12**

Single Device Name	Туре	Serial Number	Manufacturer	
Digital Multimeter 12 (Multimeter)	EX520	05157876	Extech Instrur	ments Corp.
,	Standard calibration		2009/10/07	2010/10/06
	Standard calibration		2009/10/07	2011/10/06



#### **Test Equipment Regulatory Bluetooth RF Test Solution**

Lab ID: Lab 3

Description: Regulatory Bluetooth RF Tests

Type: Bluetooth RF

Serial Number: 001

#### Single Devices for Regulatory Bluetooth RF Test Solution

Single Device Name	Туре	Serial Number	Manufacturer
ADU 200 Relay Box 7	Relay Box	A04380	Ontrak Control Systems Inc.
Bluetooth Signalling Uni CBT	t 1153.9000.35	100302	Rohde & Schwarz GmbH & Co.KG
	Calibration Details		Last Execution Next Exec.
	Standard Calibration		2009/08/06 2010/08/05
	Standard Calibration		2010/06/23 2011/06/22
Power Meter NRVD	857.8008.02	832025/059	
	Standard Calibration		2010/06/21 2011/06/20
Power Sensor NRV Z1 A	A 828.3018.03	832279/013	
	Standard Calibration		2010/06/22 2011/06/21
Power Supply	NGSM 32/10	2725	
Rubidium Frequency Normal MFS	828.3018.03	002	Datum GmbH
	Standard Calibration		2010/07/05 2011/07/04
Signal Analyser FSIQ26	1119.6001.26	832695/007	Rohde & Schwarz GmbH & Co.KG
	Standard Calibration		2009/06/24 2011/06/23
Signal Generator	SMP03	833680/003	Rohde & Schwarz GmbH & Co.KG
	Standard Calibration		2009/06/23 2012/06/22
Vector Signal Generator SMIQ03B B	1125.5555.03	832870/017	
	Standard Calibration		2010/06/23 2013/06/20

# Test Equipment Shielded Room 02

Lab ID:Lab 1Manufacturer:Frankonia

Description: Shielded Room for conducted testing

Type: 12 qm Serial Number: none

#### **Test Equipment Shielded Room 07**

Lab ID: Lab 3, Lab 4

Description: Shielded Room 4m x 6m



#### Test Equipment T/H Logger 04

Lab ID:Lab 3, Lab 4Description:Lufft Opus10Serial Number:7481

Single Devices for T/H Logger 04

Single Device Name	Туре	Serial Number	Manufacturer
ThermoHygro Datalogge 04 (Environ)	erOpus10 THI (8152.00)	7481	Lufft Mess- und Regeltechnik GmbH
	Calibration Details		Last Execution Next Exec.
	Standard calibration		2009/01/23 2011/01/22

#### Test Equipment Temperature Chamber 01

Lab 1D: Lab 3, Lab 4

Manufacturer: see single devices

Description: Temperature Chamber KWP 120/70

Type: Weiss

Serial Number: see single devices

#### Single Devices for Temperature Chamber 01

Single Device Name	Туре	Serial Number	Manufacturer
Temperature Chamber Weiss 01	KWP 120/70	59226012190010	Weiss Umwelttechnik GmbH
VVC133 U I	Specific calibration		2010/03/16 2011/03/15



## **Test Equipment WLAN RF Test Solution**

Lab 1D: Lab 4
Manufacturer: 7 layers AG

Description: Regulatory WLAN RF Tests

Type: WLAN RF Serial Number: 001

#### Single Devices for WLAN RF Test Solution

Single Device Name	Туре	Serial Number	Manufacturer
Arbitrary Waveform Generator	TGA12101	284482	
Power Meter NRVD	857.8008.02 Standard Calibration	832025/059	2010/06/21 2011/06/20
Power Sensor NRV Z1 A	828.3018.03	832279/013	
	Standard Calibration		2010/06/22 2011/06/21
Power Supply	NGSM 32/10	2725	
Rubidium Frequency Normal MFS	828.3018.03	002	Datum GmbH
	Standard Calibration		2010/07/05 2011/07/04
Signal Analyser FSIQ26	1119.6001.26	832695/007	Rohde & Schwarz GmbH & Co.KG
	Standard Calibration		2009/06/24 2011/06/23
Signal Generator	SMP03	833680/003	Rohde & Schwarz GmbH & Co.KG
	Standard Calibration		2009/06/23 2012/06/22
TOCT Switching Unit	Switching Unit	030106	7 layers, Inc.
Vector Signal Generator SMIQ03B B	1125.5555.03	832870/017	
	Standard Calibration		2010/06/23 2013/06/20



# 5 Photo Report

Detailed photos of the OUT and test setups are declared as confidential.



Photo 1: Type Label of AC/DC converter






Photo 2: Connector side of AC/DC converter



# 6 Setup Drawings



<u>Remark:</u> Depending on the frequency range suitable antenna types, attenuators or preamplifiers are used.

#### **Drawing 1:** Setup in the Anechoic chamber:

Measurements below 1 GHz: Semi-anechoic, conducting ground plane. Measurements above 1 GHz: Fully-anechoic, absorbers on all surfaces



# 7 Annex measurement plots


## 7.1 AC Mains conducted

# Op. Mode

op-mode 5

Start Stop Step Detector Meas. IF Transducer Frequency Frequency Width Time Bandw.

150.0 kHz 30.0 MHz 5.0 kHz MaxPeak 20.0 ms 9 kHz ESH3-Z5






# 7.2 Occupied bandwidth

#### 7.2.1 Occupied bandwidth operating mode 1

#### Op. Mode

op-mode 1



Title: 20dB Bandwidth

Comment A: CH B: 2402 MHz; 20dB bandwidth (kHz):950.4


Date: 12.JUL.2010 10:27:10



# 7.2.2 Occupied bandwidth operating mode 2

## Op. Mode

op-mode 2



Title: 20dB Bandwidth

Comment A: CH M: 2441 MHz; 20dB bandwidth (kHz):950.4


Date: 12.JUL.2010 10:51:54



# 7.2.3 Occupied bandwidth operating mode 3

## Op. Mode

op-mode 3



Title: 20dB Bandwidth

Comment A: CH T: 2480 MHz; 20dB bandwidth (kHz):950.4


Date: 12.JUL.2010 11:10:13



# 7.2.4 Occupied bandwidth operating mode 6

#### Op. Mode

op-mode 6



Title: 20dB Bandwidth

Comment A: CH B: 2402 MHz; 20dB bandwidth (kHz):1311.6


Date: 13.JUL.2010 13:36:43



# 7.2.5 Occupied bandwidth operating mode 7

# Op. Mode

op-mode 7



Title: 20dB Bandwidth

Comment A: CH M: 2441 MHz; 20dB bandwidth (kHz):1160.4


Date: 13.JUL.2010 14:00:21



# 7.2.6 Occupied bandwidth operating mode 8

#### Op. Mode

op-mode 8



Title: 20dB Bandwidth

Comment A: CH T: 2480 MHz; 20dB bandwidth (kHz):1281.6


Date: 13.JUL.2010 14:17:05



# 7.2.7 Occupied bandwidth operating mode 10

## Op. Mode

op-mode 10



Title: 20dB Bandwidth

Comment A: CH B: 2402 MHz; 20dB bandwidth (kHz):1269.6


Date: 12.JUL.2010 14:13:35



# 7.2.8 Occupied bandwidth operating mode 11

#### Op. Mode

op-mode 11



Title: 20dB Bandwidth

Comment A: CH M: 2441 MHz; 20dB bandwidth (kHz):1269.6


Date: 12.JUL.2010 14:42:00



# 7.2.9 Occupied bandwidth operating mode 12

#### Op. Mode

op-mode 12



Title: 20dB Bandwidth

Comment A: CH T: 2480 MHz; 20dB bandwidth (kHz):1269.6

Date: 12.JUL.2010 15:03:00




# 7.3 Peak power output

## 7.3.1 Peak power output operating mode 1

#### Op. Mode

op-mode 1



Title: Peak outputpower Power

Comment A: CH B: 2402 MHz


Date: 12.JUL.2010 10:27:37



# 7.3.2 Peak power output operating mode 2

## Op. Mode

op-mode 2



Title: Peak outputpower Power

Comment A: CH M: 2441 MHz


Date: 12.JUL.2010 10:52:21



# 7.3.3 Peak power output operating mode 3

## Op. Mode

op-mode 3



Title: Peak outputpower Power

Comment A: CH T: 2480 MHz


Date: 12.JUL.2010 11:10:40



# 7.3.4 Peak power output operating mode 6

## Op. Mode

op-mode 6



Title: Peak outputpower Power

Comment A: CH B: 2402 MHz


Date: 13.JUL.2010 13:37:10



# 7.3.5 Peak power output operating mode 7

## Op. Mode

op-mode 7



Title: Peak outputpower Power

Comment A: CH M: 2441 MHz


Date: 13.JUL.2010 14:00:48



# 7.3.6 Peak power output operating mode 8

## Op. Mode

op-mode 8



Title: Peak outputpower Power

Comment A: CH T: 2480 MHz


Date: 13.JUL.2010 14:17:32



# 7.3.7 Peak power output operating mode 10

## Op. Mode

op-mode 10



Title: Peak outputpower Power

Comment A: CH B: 2402 MHz


Date: 12.JUL.2010 14:14:01



# 7.3.8 Peak power output operating mode 11

## Op. Mode

op-mode 11



Title: Peak outputpower Power

Comment A: CH M: 2441 MHz


Date: 12.JUL.2010 14:42:27



# 7.3.9 Peak power output operating mode 12

## Op. Mode

op-mode 12



Title: Peak outputpower Power

Comment A: CH T: 2480 MHz


Date: 12.JUL.2010 15:03:26



# 7.4 Band edge compliance conducted and Spurious RF conducted emissions

## 7.4.1 Band edge compliance conducted operating mode 1

#### Op. Mode



Title: Band Edge Compliance

Comment A: CH B: 2402 MHz

Date: 12.JUL.2010 10:12:10


(determination of reference value for spurious emissions measurement)



# 7.4.2 Spurious RF conducted emissions operating mode 1

#### Op. Mode

op-mode 1



spurious emissions Title: Comment A: CH B: 2402 MHz

12.JUL.2010 10:23:48


(spurious emissions measurement)



# 7.4.3 Spurious RF conducted emissions operating mode 2

#### Op. Mode

op-mode 2




Title: Band Edge Compliance

Comment A: CH M: 2441 MHz

Date: 12.JUL.2010 10:37:02

(determination of reference value for spurious emissions measurement)





Title: spurious emissions
Comment A: CH M: 2441 MHz
Date: 12.JUL.2010 10:48:40


(spurious emissions measurement)



# 7.4.4 Band edge compliance conducted operating mode 3

#### Op. Mode

op-mode 3



Title: Band Edge Compliance

Comment A: CH T: 2480 MHz

Date: 12.JUL.2010 10:55:17


(determination of reference value for spurious emissions measurement)



# 7.4.5 Spurious RF conducted emissions operating mode 3

#### Op. Mode

op-mode 3



Title: spurious emissions
Comment A: CH T: 2480 MHz
Date: 12.JUL.2010 11:06:55


(spurious emissions measurement)



### 7.4.6 Band edge compliance conducted operating mode 6

### Op. Mode

op-mode 6



Title: Band Edge Compliance

Comment A: CH B: 2402 MHz


Date: 13.JUL.2010 13:22:03



### 7.4.7 Spurious RF conducted emissions operating mode 6

#### Op. Mode

op-mode 6




Title: spurious emissions
Comment A: CH B: 2402 MHz
Date: 13.JUL.2010 13:33:41



### 7.4.8 Spurious RF conducted emissions operating mode 7

### Op. Mode

op-mode 7




Title: Band Edge Compliance

Comment A: CH M: 2441 MHz

Date: 12.JUL.2010 14:27:25






Title: spurious emissions
Comment A: CH M: 2441 MHz
Date: 12.JUL.2010 14:39:03



### 7.4.9 Band edge compliance conducted operating mode 8

#### Op. Mode

op-mode 8



Title: Band Edge Compliance

Comment A: CH T: 2480 MHz


Date: 13.JUL.2010 14:02:26



### 7.4.10 Spurious RF conducted emissions operating mode 8

#### Op. Mode

op-mode 8




Title: spurious emissions
Comment A: CH T: 2480 MHz
Date: 13.JUL.2010 14:14:05



### 7.4.11 Band edge compliance conducted operating mode 10

### Op. Mode





Title: Band Edge Compliance

Comment A: CH B: 2402 MHz


Date: 12.JUL.2010 13:58:52



### 7.4.12 Spurious RF conducted emissions operating mode 10

### Op. Mode

op-mode 10




Title: spurious emissions
Comment A: CH B: 2402 MHz
Date: 12.JUL.2010 14:10:30



### 7.4.13 Spurious RF conducted emissions operating mode 11

### Op. Mode

op-mode 11




Title: Band Edge Compliance

Comment A: CH M: 2441 MHz

Date: 12.JUL.2010 14:27:25






Title: spurious emissions
Comment A: CH M: 2441 MHz
Date: 12.JUL.2010 14:39:03



### 7.4.14 Band edge compliance conducted operating mode 12

### Op. Mode

op-mode 12



Title: Band Edge Compliance

Comment A: CH T: 2480 MHz


Date: 12.JUL.2010 14:48:20



### 7.4.15 Spurious RF conducted emissions operating mode 12

#### Op. Mode

op-mode 12



Title: spurious emissions
Comment A: CH T: 2480 MHz
Date: 14.MAR.2008 12:13:58




# 7.5 Band edge compliance radiated

### 7.5.1 Band edge compliance radiated operating mode 3

#### Op. Mode

op-mode 3




Radiated measurement (higher band edge)



### 7.5.2 Band edge compliance radiated operating mode 8

### Op. Mode

op-mode 8




Radiated measurement (higher band edge)



### 7.5.3 Band edge compliance radiated operating mode 12

### Op. Mode

op-mode 12



Radiated measurement (higher band edge)




# 7.6 Radiated emissions (f < 30 MHz)

### Op. Mode


op-mode 2

Antenna position 90° EUT position front side






Antenna position 90° EUT position right side






Antenna position 0° EUT position front side



Antenna position 0° EUT position right side







#### 7.7 Dwell time

### Op. Mode

Time slot measurement of a DH5 packet op-mode 2 Marker 1 [T1 ndB] RBW 1 MHz RF Att 20 dB Ref Lvl 6.00 dB VBW ndB 1 MHz 10 dBm BW 2.905812 ms SWT 10 ms dBmUnit 2 1 dB Offset ▼<sub>1</sub>|[T1] .63 dBm Α s<u>ע 000,000 100.000</u> 6.00 ndl SGL ₿W 2.905812 ms -10 TRG -39.078156 Иs **†**T2 [T1] .69 -20 2.866733 1MAK 1MA -30 EXT -40 TDF -50 Tople of a for the one of the state of the s -70 -80 TR

1 ms/

Dwell time Comment A: CH M: 2441 MHz

Center 2.441 GHz


12.JUL.2010 13:52:56 Date:



# 7.8 Channel separation

### Op. Mode

op-mode 4



Title: Number of hopping frequencies

Comment A: CH H: Hopping


Date: 12.JUL.2010 13:55:02



# 7.9 Number of hopping frequencies

#### Op. Mode

op-mode 4



Title: Number of hopping frequencies Comment A: CH H: Hopping

12.JUL.2010 13:57:52 Date: