

MPE (for FCC) and RF Exposure (for ISED) Calculation

Project: C5985

Report number: 14294TR1 Customer Details

Company name	IceRobotics Ltd
Address	Bankhead Steading
	Bankhead Road
	South Queensferry
	Midlothian
	EH30 9TF
	United Kingdom
Tel:	+44 131 541 2010
Contact	Mr Gavin Saxby
Email	g.saxby@icerobotics.com

Date received:	12 th March 2021
Product Marketing Name:	IceQube wireless sensor
FCC ID	WWP-1-QUBE
ISED Number	8143A-I-QUBE



1574

Registered Address:

Eurofins York
i54 Business Park, Valiant Way
Wolverhampton, WV9 5GB, UK

Registered in England and Wales
Company Reg. No. 6048589
VAT Reg. No. GB 887 1276 83

MPE and RF Exposure Calculation for Ice Robotics

MPE Calculation – FCC

Mobile devices are defined by the FCC as transmitters designed to be used in other than fixed locations and generally to be used in such a way that a separation distance of 20cm is normally maintained between radiating structures and the body of the user or nearby persons. These devices are normally evaluated for exposure potential with relation to the MPE limit. As the 20cm separation may not be achievable under normal operating conditions, an RF exposure calculation is used to demonstrate the minimum distance required to be less than the power density limit, as required under FCC rules.

FCC rule part:47CFR2.1091(3)

Power density (S) relates to Equivalent Isotropic Radiated power (EIRP) according to the following:

$$S = \frac{EIRP}{4\pi R^2}$$

Where,

R is the distance to the centre of radiation of the antenna (cm)

S is power density in mW/cm²

Rearranging,

$$R = \sqrt{\frac{EIRP}{S4\pi}}$$

Using the measured value of EIRP (derived from electric field strength, and using the limit for S , it is possible to determine the value R i.e. distance from the EUT, where the limit is met.

MPE and RF Exposure Calculation for Ice Robotics

The distance R is calculated as:

Frequency (MHz)	Conducted power (mW)	Antenna gain	Maximum EIRP (mW)	Power density limit (S) (mW/cm ²) 47CFR1.1310 Table 1 (Notes 2 and 3)	Distance (R) (cm) required to be less than S
903.2	0.081	1.71	0.139	0.6	0.14
914.4	0.065	1.71	0.111	0.61	0.12
926.3	0.024	1.71	0.041	0.62	0.07

Note 1:

Limits for General Population / Uncontrolled Exposure.

Note 2:

The limit is defined in Table 1 of 47CFR1.1310(e)(1) as:

Between 300 and 1500MHz as $f/1500$ mW/cm²

Where f is frequency in MHz

Conclusion

The product met the 20cm distance requirement.

MPE and RF Exposure Calculation for Ice Robotics

RF Exposure Evaluation - ISED

RSS Standard:

RSS-102 Issue 5 Posted on ISED website: March 19, 2015

Clause:2.5.2 Exemption Limits for Routine Evaluation — RF Exposure Evaluation

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

At or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than

$$1.31 \times 10^{-2} f^{0.6834} \text{ W}$$

(adjusted for tune-up tolerance),

where f is in MHz

Evaluation

Frequency (MHz)	Conducted power (mW)	Antenna gain	Maximum EIRP (mW) (Conducted measurement)	Maximum EIRP (W) (From above formula)	Maximum ERP (mW) (From above formula)
903.2	0.081	1.71	0.139	1.37	1370
914.4	0.065	1.71	0.111	1.38	1380
926.3	0.024	1.71	0.041	1.4	1400

Conclusion

The apparatus meets the exclusion requirements for RF exposure.