



CETECOM ICT Services

consulting - testing - certification >>>

TEST REPORT

Test report no.: 1-1780/16-01-02



Testing laboratory

CETECOM ICT Services GmbH

Untertuerkheimer Strasse 6 – 10
66117 Saarbruecken / Germany
Phone: + 49 681 5 98 - 0
Fax: + 49 681 5 98 - 9075
Internet: http://www.cetecom.com
e-mail: ict@cetecom.com

Accredited Testing Laboratory:

The testing laboratory (area of testing) is accredited according to DIN EN ISO/IEC 17025 (2005) by the Deutsche Akkreditierungsstelle GmbH (DAkkS)

The accreditation is valid for the scope of testing procedures as stated in the accreditation certificate with

the registration number: D-PL-12076-01-01

Applicant

Roche Diabetes Care, Inc.

9115 Hague Road

46250 Indianapolis / UNITED STATES

Phone: -/-

Fax: 317-521-3089 Contact: Tony Heleine

e-mail: tony.heleine@roche.com

Phone: 317-521-3404

Manufacturer

Roche Diabetes Care, Inc.

9115 Hague Road

46250 Indianapolis / UNITED STATES

Test standard/s

47 CFR Part 15 Title 47 of the Code of Federal Regulations; Chapter I; Part 15 - Radio frequency

devices

RSS - 247 Issue 1 Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and

Licence - Exempt Local Area Network (LE-LAN) Devices

For further applied test standards please refer to section 3 of this test report.

Test Item

Kind of test item: Blood Glucose Meter Model name: Accu-Chek Instant

FCC ID: WX3-122 IC: 3100A-122

Frequency: DTS band 2400 MHz to 2483.5 MHz

Technology tested: Bluetooth®, LE

Antenna: Integrated antenna

Power supply: 3.0 V DC by battery

Temperature range: -10°C to +60°C



This test report is electronically signed and valid without handwriting signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Test report authorized:	Test performed:		
Marco Bertolino	Mihail Dorongovskij		
Lab Manager	Testing Manager		

Radio Communications & EMC

Lab Manager Radio Communications & EMC



Table of contents

1	Table of contents2								
2	General information								
	2.1	Notes and disclaimer							
	2.2	Application details							
3	Test s	tandard/s and references	3						
4	Test e	nvironment	ţ						
5		em							
	5.1	General description							
	5.2	Additional information							
6	Test la	aboratories sub-contracted							
7	Descr	iption of the test setup	е						
	7.1	Shielded semi anechoic chamber							
	7.2	Shielded fully anechoic chamber							
	7.3	Radiated measurements > 18 GHz	9						
	7.4	Conducted measurements C.BER system	10						
8	Seque	nce of testing	11						
	8.1	Sequence of testing radiated spurious 9 kHz to 30 MHz	4.						
	8.2	Sequence of testing radiated spurious 9 KHz to 30 MHz	1 12						
	8.3	Sequence of testing radiated spurious 1 GHz to 18 GHz							
	8.4	Sequence of testing radiated spurious above 18 GHz							
9	Measu	rement uncertainty	15						
10	Sun	nmary of measurement results	16						
11	Add	itional comments	17						
12	Mea	surement results	18						
	12.1	System gain	15						
	12.2	Power spectral density							
	12.3	DTS bandwidth – 6 dB bandwidth							
	12.4	Occupied bandwidth – 99% emission bandwidth	2						
	12.5	Maximum output power							
	12.6	Detailed spurious emissions @ the band edge - conducted							
	12.7	Band edge compliance radiated							
	12.8	TX spurious emissions conductedSpurious emissions radiated below 30 MHz							
	12.9 12.10	Spurious emissions radiated below 30 MHzSpurious emissions radiated 30 MHz to 1 GHz							
	12.10	Spurious emissions radiated 30 MHz to 1 GHz							
13		ervations							
_									
	ex A	Document history							
	ex B	Further information							
Δnr	ex C	Accreditation Certificate	57						



2 General information

2.1 Notes and disclaimer

The test results of this test report relate exclusively to the test item specified in this test report. CETECOM ICT Services GmbH does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item.

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CETECOM ICT Services GmbH.

The testing service provided by CETECOM ICT Services GmbH has been rendered under the current "General Terms and Conditions for CETECOM ICT Services GmbH".

CETECOM ICT Services GmbH will not be liable for any loss or damage resulting from false, inaccurate, inappropriate or incomplete product information provided by the customer.

Under no circumstances does the CETECOM ICT Services GmbH test report include any endorsement or warranty regarding the functionality, quality or performance of any other product or service provided.

Under no circumstances does the CETECOM ICT Services GmbH test report include or imply any product or service warranties from CETECOM ICT Services GmbH, including, without limitation, any implied warranties of merchantability, fitness for purpose, or non-infringement, all of which are expressly disclaimed by CETECOM ICT Services GmbH.

All rights and remedies regarding vendor's products and services for which CETECOM ICT Services GmbH has prepared this test report shall be provided by the party offering such products or services and not by CETECOM ICT Services GmbH.

In no case this test report can be considered as a Letter of Approval.

This test report is electronically signed and valid without handwritten signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

2.2 Application details

Date of receipt of order: 2016-04-27
Date of receipt of test item: 2016-05-04
Start of test: 2016-05-19

Person(s) present during the test: -/-

3 Test standard/s and references

Test standard	Date	Description
47 CFR Part 15	-/-	Title 47 of the Code of Federal Regulations; Chapter I; Part 15 - Radio frequency devices
RSS - 247 Issue 1	May 2015	Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence - Exempt Local Area Network (LE- LAN) Devices



Guidance	Version	Description
DTS: KDB 558074 D01	v03r05	Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247
ANSI C63.4-2014	-/-	American national standard for methods of measurement of radio- noise emissions from low-voltage electrical and electronic equipment in the range of 9 kHz to 40 GHz
ANSI C63.10-2013	-/-	American national standard of procedures for compliance testing of unlicensed wireless devices



4 Test environment

T (T _{nom}	+22 °C during room temperature tests
Temperature	÷	T _{max}	No tests under extreme conditions required.
		T_{min}	No tests under extreme conditions required.
Relative humidity content	:		55 %
Barometric pressure :			not relevant for this kind of testing
		V _{nom}	3.0 V DC by battery (5 V DC by USB during tests)
Power supply	:	V_{max}	No tests under extreme conditions required.
		V_{min}	No tests under extreme conditions required.

5 Test item

5.1 General description

IZin di effe et iteme	Disad Olygon Mater
Kind of test item :	Blood Glucose Meter
Type identification :	Accu-Chek Instant
HMN :	-/-
PMN :	Accu-Chek Instant
HVIN :	013X
FVIN :	1.6.9
S/N serial number :	Rad. 95800011372 Cond. 95800011392
HW hardware status :	013X
SW software status :	1.6.9
Frequency band :	DTS band 2400 MHz to 2483.5 MHz (lowest channel 00 – 2402 MHz; highest channel 39 – 2480 MHz)
Type of radio transmission: Use of frequency spectrum:	DSSS
Type of modulation :	GFSK
Number of channels :	40
Antenna :	Integrated antenna
Power supply :	3.0 V DC by battery
Temperature range :	-10°C to +60°C

5.2 Additional information

The content of the following annexes is defined in the QA. It may be that not all of the listed annexes are necessary for this report, thus some values in between may be missing.

Test setup- and EUT-photos are included in test report: 1-1780/16-01-01_AnnexA

1-1780/16-01-01_AnnexB 1-1780/16-01-01_AnnexD

6 Test laboratories sub-contracted

None



7 Description of the test setup

Typically, the calibrations of the test apparatus are commissioned to and performed by an accredited calibration laboratory. The calibration intervals are determined in accordance with the DIN EN ISO/IEC 17025. In addition to the external calibrations, the laboratory executes comparison measurements with other calibrated test systems or effective verifications. Weekly chamber inspections and range calibrations are performed. Where possible, RF generating and signaling equipment as well as measuring receivers and analyzers are connected to an external high-precision 10 MHz reference (GPS-based or rubidium frequency standard).

In order to simplify the identification of the equipment used at some special tests, some items of test equipment and ancillaries can be provided with an identifier or number in the equipment list below (Lab/Item).


Agenda: Kind of Calibration

k ne	calibration / calibrated not required (k, ev, izw, zw not required)	EK zw	limited calibration cyclical maintenance (external cyclical maintenance)
ev	periodic self verification	izw	internal cyclical maintenance
Ve	long-term stability recognized	g	blocked for accredited testing
vlkl!	Attention: extended calibration interval	_	-
NK!	Attention: not calibrated	*)	next calibration ordered / currently in progress



7.1 Shielded semi anechoic chamber

The radiated measurements are performed in vertical and horizontal plane in the frequency range from 9 kHz to 1 GHz in semi-anechoic chambers. The EUT is positioned on a non-conductive support with a height of 0.80 m above a conductive ground plane that covers the whole chamber. The receiving antennas are confirmed with specifications ANSI C63. These antennas can be moved over the height range between 1.0 m and 4.0 m in order to search for maximum field strength emitted from EUT. The measurement distances between EUT and receiving antennas are indicated in the test setups for the various frequency ranges. For each measurement, the EUT is rotated in all three axes until the maximum field strength is received. The wanted and unwanted emissions are received by spectrum analyzers where the detector modes and resolution bandwidths over various frequency ranges are set according to requirement ANSI C63.



Measurement distance: tri-log antenna 10 meter

FS = UR + CL + AF

(FS-field strength; UR-voltage at the receiver; CL-loss of the cable; AF-antenna factor)


Example calculation:

FS $[dB\mu V/m] = 12.35 [dB\mu V/m] + 1.90 [dB] + 16.80 [dB/m] = 31.05 [dB\mu V/m] (35.69 \(\mu V/m \))$

No.	Lab / Item	Equipment	Туре	Manufacturer	Serial No.	INV. No Cetecom	Kind of Calibration	Last Calibration	Next Calibration
1	Α	Switch-Unit	3488A	HP	2719A14505	300000368	ev	-/-	-/-
2	Α	DC power supply, 60Vdc, 50A, 1200 W	6032A	HP	2920A04466	300000580	ne	-/-	-/-
3	Α	EMI Test Receiver	ESCI 3	R&S	100083	300003312	k	08.03.2016	08.03.2017
4	Α	Antenna Tower	Model 2175	ETS-Lindgren	64762	300003745	izw	-/-	-/-
5	Α	Positioning Controller	Model 2090	ETS-Lindgren	64672	300003746	izw	-/-	-/-
6	Α	TRILOG Broadband Test-Antenna 30 MHz - 3 GHz	VULB9163	Schwarzbeck	295	300003787	k	25.04.2016	25.04.2018



7.2 Shielded fully anechoic chamber



Measurement distance: tri-log antenna and horn antenna 3 meter; loop antenna 3 meter

FS = UR + CA + AF

(FS-field strength; UR-voltage at the receiver; CA-loss of the signal path; AF-antenna factor)


Example calculation:

 $FS [dB\mu V/m] = 40.0 [dB\mu V/m] + (-35.8) [dB] + 32.9 [dB/m] = 37.1 [dB\mu V/m] (71.61 \ \mu V/m)$

No.	Lab / Item	Equipment	Туре	Manufacturer	Serial No.	INV. No Cetecom	Kind of Calibration	Last Calibration	Next Calibration
1	A, B, C	DC power supply, 60Vdc, 50A, 1200 W	6032A	HP	2818A03450	300001040	Ve	20.01.2015	20.01.2018
2	Α	Double-Ridged Waveguide Horn Antenna 1-18.0GHz	3115	EMCO	8812-3088	300001032	vlKI!	20.05.2015	20.05.2017
3	A, B, C	Anechoic chamber	FAC 3/5m	MWB / TDK	87400/02	300000996	ev	-/-	-/-
4	A, B, C	Switch / Control Unit	3488A	HP	*	300000199	ne	-/-	-/-
5	AC	Active Loop Antenna 10 kHz to 30 MHz	6502	EMCO/2	8905-2342	300000256	k	24.06.2015	24.06.2017
6	Α	Amplifier	js42-00502650-28- 5a	Parzich GMBH	928979	300003143	ne	-/-	-/-
7	Α	Band Reject filter	WRCG2400/2483- 2375/2505-50/10SS	Wainwright	11	300003351	ev	-/-	-/-
8	Α	Highpass Filter	WHKX7.0/18G-8SS	Wainwright	18	300003789	ne	-/-	-/-
9	A, B	TRILOG Broadband Test-Antenna 30 MHz - 3 GHz	VULB9163	Schwarzbeck	371	300003854	vIKI!	29.10.2014	29.10.2017
10	A, B, C	4U RF Switch Platform	L4491A	Agilent Technologies	MY50000037	300004509	ne	-/-	-/-
11	A, B, C	EMI Test Receiver 9kHz-26,5GHz	ESR26	R&S	101376	300005063	k	04.09.2015	04.09.2016



7.3 Radiated measurements > 18 GHz



Measurement distance: horn antenna 50 cm

 $FS = U_R + CA + AF$

(FS-field strength; U_R-voltage at the receiver; CA-loss signal path & distance correction; AF-antenna factor)


Example calculation:

 $\overline{\text{FS [dB}\mu\text{V/m]}} = 40.0 \text{ [dB}\mu\text{V/m]} + (-60.1) \text{ [dB]} + 36.74 \text{ [dB/m]} = 16.64 \text{ [dB}\mu\text{V/m]} (6.79 \ \mu\text{V/m})$

No.	Lab / Item	Equipment	Туре	Manufacturer	Serial No.	INV. No Cetecom	Kind of Calibration	Last Calibration	Next Calibration
1	Α	Std. Gain Horn Antenna 18.0 to 26.5 GHz	638	Narda	-/-	300000486	k	10.09.2015	10.09.2017
2	Α	Signal Analyzer 40 GHz	FSV40	R&S	101042	300004517	k	21.01.2016	21.01.2017
3	Α	Amplifier 2-40 GHz	JS32-02004000-57- 5P	MITEQ	1777200	300004541	ev	-/-	-/-
4	Α	DC Power Supply 0 - 32V	1108-32	Heiden Elektronik	001802	300001383	Ve	29.01.2014	29.01.2017
5	Α	RF-Cable	ST18/SMAm/SMAm/ 60	Huber & Suhner	Batch no. 606844	400001181	ev	-/-	-/-
6	Α	RF-Cable	ST18/SMAm/SMAm/ 48	Huber & Suhner	Batch no. 600918	400001182	ev	-/-	-/-



7.4 Conducted measurements C.BER system



OP = AV + CA

(OP-output power; AV-analyzer value; CA-loss signal path)

Example calculation:

OP [dBm] = 6.0 [dBm] + 11.7 [dB] = 17.7 [dBm] (58.88 mW)

No.	Lab / Item	Equipment	Туре	Manufacturer	Serial No.	INV. No Cetecom	Kind of Calibration	Last Calibration	Next Calibration
1	Α	Switch / Control Unit	3488A	HP		300000929	ne	-/-	-/-
2	Α	System DC Power Supply	N5767A	Agilent Technologies	US14J1569P	300004851	vIKI!	04.09.2014	04.09.2016
3	Α	Signal Analyzer 30GHz	FSV30	R&S	103170	300004855	k	25.01.2016	25.01.2017
4	Α	DC-Blocker	8143	Inmet Corp.	none	300002842	ne	-/-	-/-
5	Α	Powersplitter	6005-3	Inmet Corp.	none	300002841	ev	-/-	-/-
6	Α	Temperature Test Chamber	VT 4002	Heraeus Voetsch	5856604682001 0	300003019	ev	03.09.2015	03.09.2017
7	Α	RF-Cable	ST18/SMAm/SMAm/ 72	Huber & Suhner	Batch no. 605505	400001187	ev	-/-	-/-
8	Α	RF-Cable	Sucoflex 104	Huber & Suhner	147636/4	400001188	ev	-/-	-/-



8 Sequence of testing

8.1 Sequence of testing radiated spurious 9 kHz to 30 MHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, a 2-axis positioner with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed directly on the turn table.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 3 m (see ANSI C 63.4) see test details.
- EUT is set into operation.

Premeasurement

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 1.5 m.
- At each turntable position the analyzer sweeps with positive-peak detector to find the maximum of all
 emissions.

- Identified emissions during the premeasurement are maximized by the software by rotating the turntable from 0° to 360°. In case of the 2-axis positioner is used the elevation axis is also rotated from 0° to 360°.
- The final measurement is done in the position (turntable and elevation) causing the highest emissions with quasi-peak (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. A plot with the graph of the premeasurement and the limit is stored.



8.2 Sequence of testing radiated spurious 30 MHz to 1 GHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 10 m or 3 m (see ANSI C 63.4) see test details.
- EUT is set into operation.

Premeasurement

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 m to 3 m.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

- The final measurement is performed for at least six highest peaks according to the requirements of the ANSI C63.4.
- Based on antenna and turntable positions at which the peak values are measured the software maximize the peaks by changing turntable position ± 45° and antenna height between 1 and 4 m.
- The final measurement is done with quasi-peak detector (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement with marked maximum final results and the limit is stored.



8.3 Sequence of testing radiated spurious 1 GHz to 18 GHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- If the EUT is a tabletop system, a 2-axis positioner with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed directly on the turn table.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- Measurement distance is 3 m (see ANSI C 63.4) see test details.
- EUT is set into operation.

Premeasurement

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height is 1.5 m.
- At each turntable position and antenna polarization the analyzer sweeps with positive peak detector to find the maximum of all emissions.

- The final measurement is performed for at least six highest peaks according to the requirements of the ANSI C63.4.
- Based on antenna and turntable positions at which the peak values are measured the software maximizes the peaks by rotating the turntable from 0° to 360°. This measurement is repeated for different EUT-table positions (0° to 150° in 30°-steps) and for both antenna polarizations.
- The final measurement is done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and RMS detector (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement with marked maximum final results and the limit is stored.



8.4 Sequence of testing radiated spurious above 18 GHz

Setup

- The equipment is set up to simulate normal operation mode as described in the user manual or defined by the manufacturer.
- Auxiliary equipment and cables are positioned to simulate normal operation conditions as described in ANSI C 63.4.
- The AC power port of the EUT (if available) is connected to a power outlet.
- The measurement distance is as appropriate (e.g. 0.5 m).
- The EUT is set into operation.

Premeasurement

• The test antenna is handheld and moved carefully over the EUT to cover the EUT's whole sphere and different polarizations of the antenna.

- The final measurement is performed at the position and antenna orientation causing the highest emissions with Peak and RMS detector (as described in ANSI C 63.4).
- Final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit are recorded. A plot with the graph of the premeasurement and the limit is stored.



9 Measurement uncertainty

Measurement uncertainty						
Test case	Uncertainty					
Antenna gain	± 3 dB					
Spectrum bandwidth	± 21.5 kHz absolute; ± 15.0 kHz relative					
Maximum output power	± 1 dB					
Detailed conducted spurious emissions @ the band edge	± 1 dB					
Band edge compliance radiated	± 3 dB					
Spurious emissions conducted	± 3 dB					
Spurious emissions radiated below 30 MHz	± 3 dB					
Spurious emissions radiated 30 MHz to 1 GHz	± 3 dB					
Spurious emissions radiated 1 GHz to 12.75 GHz	± 3.7 dB					
Spurious emissions radiated above 12.75 GHz	± 4.5 dB					
Spurious emissions conducted below 30 MHz (AC conducted)	± 2.6 dB					



10 Summary of measurement results

\boxtimes	No deviations from the technical specifications were ascertained
	There were deviations from the technical specifications ascertained
	This test report is only a partial test report. The content and verdict of the performed test cases are listed below.

TC Identifier	Description	Verdict	Date	Remark
RF-Testing	CFR Part 15 RSS - 247, Issue 1	See table!	2016-06-01	-/-

Test specification clause	Test case	Guideline	Temperature conditions	Power source voltages	Mode	С	NC	NA	NP	Remark
§15.247(b)(4) RSS - 247 / 5.4 (4)	System gain	-/-	Nominal	Nominal	GFSK	\boxtimes				-/-
§15.247(e) RSS - 247 / 5.2 (2)	Power spectral density	KDB 558074 DTS clause: 10.6	Nominal	Nominal	GFSK	\boxtimes				-/-
§15.247(a)(2) RSS - 247 / 5.2 (1)	DTS bandwidth – 6 dB bandwidth	KDB 558074 DTS clause: 8.1	Nominal	Nominal	GFSK	\boxtimes				-/-
RSS Gen clause 4.6.1	Occupied bandwidth	-/-	Nominal	Nominal	GFSK	\boxtimes				-/-
§15.247(b)(3) RSS - 247 / 5.4 (4)	Maximum output power	KDB 558074 DTS clause: 9.1.1	Nominal	Nominal	GFSK	\boxtimes				-/-
§15.247(d) RSS - 247 / 5.5	Detailed spurious emissions @ the band edge - conducted	-/-	Nominal	Nominal	GFSK	×				-/-
§15.205 RSS - 247 / 5.5 RSS - Gen	Band edge compliance radiated	KDB 558074 DTS clause: 13.3.2	Nominal	Nominal	GFSK	×				-/-
§15.247(d) RSS - 247 / 5.5	TX spurious emissions conducted	KDB 558074 DTS clause: 11.1 & 11.2 11.3	Nominal	Nominal	GFSK	\boxtimes				-/-
§15.209(a) RSS - Gen	Spurious emissions radiated below 30 MHz	-/-	Nominal	Nominal	GFSK	\boxtimes				-/-
15.247(d) RSS - 247 / 5.5 §15.109 RSS - Gen	Spurious emissions radiated 30 MHz to 1 GHz	-/-	Nominal	Nominal	-/-	\boxtimes				-/-
§15.247(d) RSS - 247 / 5.5 §15.109 RSS - Gen	Spurious emissions radiated above 1 GHz	-/-	Nominal	Nominal	GFSK	\boxtimes				-/-
§15.107(a) §15.207	Conducted emissions below 30 MHz (AC conducted)	-/-	Nominal	Nominal	GFSK			\boxtimes		-/-

Note: C = Compliant; NC = Not compliant; NA = Not applicable; NP = Not performed



11 Additional comments

The Bluetooth $^{\circ}$ word mark and logos are owned by the Bluetooth SIG Inc. and any use of such marks by Cetecom ICT Services GmbH is under license.

Reference documents:	None	
Special test descriptions:	None	
Configuration descriptions:	static F RX/Sta	ts: were performed with LE packets (37 byte payload) and PRBS pattern. Indby tests: BT enabled, TX Idle channels: lowest: 2402 MHz (Ch 0) middle: 2440 MHz (Ch 19) highest: 2480 MHz (Ch 39)
Test mode:		Bluetooth LE Test mode enabled (EUT is controlled over CBT)
		Special software is used. EUT is transmitting pseudo random data by itself



12 Measurement results

12.1 System gain

Measurement:

The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module. For normal Bluetooth® devices, the GFSK modulation is used.

Measurement parameters			
Detector	Peak		
Sweep time	Auto		
Resolution bandwidth	3 MHz		
Video bandwidth	3 MHz		
Span	5 MHz		
Trace mode	Max hold		
Test setup	See sub clause 7.2 B (radiated) See sub clause 7.4 A (conducted)		
Measurement uncertainty	See sub clause 9		

Limits:

FCC	IC
6 dBi / > 6 dBi output power and	power density reduction required

Results:

Tnom	V _{nom}	2402 MHz	2440 MHz	2480 MHz
Conducted power [dBm] Measured with GFSK modulation		-1.1	-1.9	-2.4
Radiated power [dBm] Measured with GFSK modulation		4.3	4.3	2.4
Gain [dBi] Calculated		5.4	6.2	4.8



12.2 Power spectral density

Description:

Measurement of the power spectral density of a digital modulated system.

Measurement parameters				
Detector	Peak			
Sweep time	Auto			
Resolution bandwidth	3 kHz			
Video bandwidth	10 kHz			
Span	≥ EBW			
Trace mode	Max hold			
Test setup	See sub clause 7.4 A			
Measurement uncertainty	See sub clause 9			

Limits:

FCC	IC		
Power spectral density			

For digitally modulated systems the transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission or over 1.0 second if the transmission exceeds 1.0-second duration.


Results:

	Frequency		
	2402 MHz	2440 MHz	2480 MHz
Power spectral density [dBm / 3kHz]	-3.1	-3.9	-4.7




Plots:

Plot 1: lowest channel




Plot 2: mid channel





Plot 3: highest channel





12.3 DTS bandwidth - 6 dB bandwidth

Description:

Measurement of the 6 dB bandwidth of the modulated signal.

Measurement parameters			
According to DTS clause: 8.1			
Detector Peak			
Sweep time	Auto		
Resolution bandwidth	100 kHz		
Video bandwidth	300 kHz		
Span	5 MHz		
Measurement procedure	Using 3 marker (max + 2x-6dB)		
Trace mode	Max hold (allow trace to stabilize)		
Test setup	See sub clause 7.4 A		
Measurement uncertainty	See sub clause 9		

Limits:

FCC	IC		
DTS bandwidth – 6 dB bandwidth			
Systems using digital modulation techniques may operate in the 2400–2483.5 MHz band. The minimum 6 dB bandwidth shall be at least 500 kHz.			


Results:

		Frequency	
	2402 MHz	2440 MHz	2480 MHz
6 dB bandwidth [kHz]	670	680	710




Plots:

Plot 1: lowest channel




Plot 2: mid channel





Plot 3: highest channel





12.4 Occupied bandwidth - 99% emission bandwidth

Description:

Measurement of the 99% bandwidth of the modulated signal acc. RSS-GEN.

Measurement parameters		
Detector	Peak	
Sweep time	Auto	
Resolution bandwidth	30 kHz	
Video bandwidth	100 kHz	
Span	5 MHz	
Measurement procedure	Measurement of the 99% bandwidth using the integration function of the analyzer	
Trace mode	Max hold (allow trace to stabilize)	
Test setup	See sub clause 7.4 A	
Measurement uncertainty	See sub clause 9	

Usage:

-/-	IC
Occupied bandwidth – 99% emission bandwidth	
OBW is necessary for emission designator	


Results:

		Frequency	
	2402 MHz	2440 MHz	2480 MHz
99% bandwidth [kHz]	3073	3093	3263




Plots:

Plot 1: lowest channel



Plot 2: mid channel





Plot 3: highest channel





12.5 Maximum output power

Description:

Measurement of the maximum output power conducted and radiated. EUT in single channel mode.

Measurement parameters		
Detector	Peak	
Sweep time	Auto	
Resolution bandwidth	3 MHz	
Video bandwidth	10 MHz	
Span	10 MHz	
Trace mode	Max hold	
Test setup	See sub clause 7.4 A	
Measurement uncertainty	See sub clause 9	

Limits:

FCC	IC
Maximum output power	
[Conducted: 0.125 W – antenna gain max. 6 dBi] Systems using more than 75 hopping channels: Conducted: 1.0 W – antenna gain max. 6 dBi	


Results:

		Frequency	
	2402 MHz	2440 MHz	2480 MHz
Maximum output power conducted [dBm]	-1.1	-1.8	-2.4




Plots:

Plot 1: lowest channel




Plot 2: mid channel





Plot 3: highest channel





12.6 Detailed spurious emissions @ the band edge - conducted

Description:

Measurement of the conducted band edge compliance. EUT is measured at the lower and upper band edge in single channel.

Measurement parameters		
Detector	Peak	
Sweep time	Auto	
Resolution bandwidth	100 kHz	
Video bandwidth	300 kHz / 500 kHz	
Span	Lower Band Edge: 2395 – 2405 MHz higher Band Edge: 2478 – 2489 MHz	
Trace mode	Max hold	
Test setup	See sub clause 7.4 A	
Measurement uncertainty	See sub clause 9	

Limits:

FCC	IC

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required.


Result:

Scenario	Spurious band edge conducted [dB]
Modulation	GFSK
Lower band edge – hopping off	> 20 dB
Upper band edge – hopping off	> 20 dB




Plots:

Plot 1: Lower band edge



Plot 2: Upper band edge





12.7 Band edge compliance radiated

Description:

Measurement of the radiated band edge compliance. The EUT is turned in the position that results in the maximum level at the band edge. Then a sweep over the corresponding restricted band is performed. The EUT is set to single channel mode and the transmit channel is channel 00 for the lower restricted band and channel 39 for the upper restricted band. Measurement distance is 3m.

Measurement parameters		
Detector	Peak / RMS	
Sweep time	Auto	
Resolution bandwidth	1 MHz	
Video bandwidth	3 MHz	
Span	Lower Band: 2300 – 2400 MHz higher Band: 2480 – 2500 MHz	
Trace mode	Max hold	
Test setup	See sub clause 7.2 B	
Measurement uncertainty	See sub clause 9	

Limits:

FCC	IC		
Band edge compliance radiated			
In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 5.205(c)).			
54 dBμV/m AVG 74 dBμV/m Peak			


Result:

Scenario	Band edge compliance radiated [dBµV/m]	
Modulation	GFSK	
Lower restricted band	< 54 AVG / < 74 PP	
Upper restricted band	< 54 AVG / < 74 PP	




Plots:

Plot 1: Lower restricted band



Plot 2: Upper restricted band





12.8 TX spurious emissions conducted

Description:

Measurement of the conducted spurious emissions in transmit mode. The EUT is set to single channel mode and the transmit channel is channel 00, channel 19 and channel 39.

Measurement parameters				
Detector	Peak			
Sweep time	Auto			
Resolution bandwidth	100 kHz			
Video bandwidth	300 kHz or 500 kHz			
Span	9 kHz to 25 GHz			
Trace mode	Max hold			
Test setup	See sub clause 7.4 A			
Measurement uncertainty	See sub clause 9			

Limits:

FCC	IC			
TX spurious emissions conducted				

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required


Results:

TX spurious emissions conducted						
f [MHz]		amplitude of emission [dBm]	limit max. allowed emission power	actual attenuation below frequency of operation [dB]	results	
2402		-2.2	30 dBm		Operating frequency	
All detected emissions are compliant with the -20 dBc limit!		-20 dBc		compliant		
2440		-2.8	30 dBm		Operating frequency	
All detected emissions are compliant with the -20 dBc limit!		-20 dBc		compliant		
2480		-3.6	30 dBm		Operating frequency	
All detected emissions are compliant with the -20 dBc limit!		-20 dBc		compliant		




Plots:

Plot 1: lowest channel




Plot 2: mid channel





Plot 3: highest channel





12.9 Spurious emissions radiated below 30 MHz

Description:

Measurement of the radiated spurious emissions in transmit mode below 30 MHz. The EUT is set to single channel mode and the transmit channel is channel 19. This measurement is representative for all channels and modes. If critical peaks are found channel 00 and channel 39 will be measured too. The measurement is performed in the mode with the highest output power. The limits are recalculated to a measurement distance of 3 m according the ANSI C63.10.

Measurement parameters								
Detector	Peak / Quasi peak							
Sweep time	Auto							
Resolution bandwidth	F < 150 kHz: 1 kHz F > 150 kHz: 100 kHz							
Video bandwidth	F < 150 kHz: 200 Hz F > 150 kHz: 9 kHz							
Span	9 kHz to 30 MHz							
Trace mode	Max hold							
Test setup	See sub clause 7.2 C							
Measurement uncertainty	See sub clause 9							

Limits:

FCC		IC					
TX spurious emissions radiated below 30 MHz							
Frequency (MHz)	Field streng	th (dBµV/m)	Measurement distance				
0.009 – 0.490	2400/F(kHz)		300				
0.490 – 1.705	24000/F(kHz)		24000/F(kHz)		30		
1.705 – 30.0	3	0	30				


Results:

TX spurious emissions radiated below 30 MHz [dBμV/m]									
F [MHz] Detector Level [dBμV/m]									
All detect	ed emissions are more than 20 dB below	the limit.							




Plots:

Plot 1: 9 kHz to 30 MHz, channel 00, transmit mode




Plot 2: 9 kHz to 30 MHz, channel 19, transmit mode





Plot 3: 9 kHz to 30 MHz, channel 39, transmit mode





12.10 Spurious emissions radiated 30 MHz to 1 GHz

Description:

Measurement of the radiated spurious emissions in transmit mode. The EUT is set to single channel mode and the transmit channel is channel 00, channel 19 and channel 39. The measurement is performed in the mode with the highest output power.

Measurement parameters						
Detector	Peak / Quasi Peak					
Sweep time	Auto					
Resolution bandwidth	3 x VBW					
Video bandwidth	120 kHz					
Span	30 MHz to 1 GHz					
Trace mode	Max hold					
Measured modulation	GFSK					
Test setup	See sub clause 7.1 A					
Measurement uncertainty	See sub clause 9					

The modulation with the highest output power was used to perform the transmitter spurious emissions. If spurious were detected a re-measurement was performed on the detected frequency with each modulation.


Limits:

FCC		IC								
TX spurious emissions radiated										
In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).										
	§15.	209								
Frequency (MHz)	Field streng	th (dBµV/m)	Measurement distance							
30 - 88	30	30.0 10								
88 – 216	33	.5	10							
216 – 960 36.0 10										
Above 960	54	.0	3							



Plots: Transmit mode


Plot 1: 30 MHz to 1 GHz, TX mode, channel 00, vertical & horizontal polarization



Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
38.699250	15.02	30.00	14.98	1000.0	120.000	185.0	٧	148.0	14.0
47.363400	19.06	30.00	10.94	1000.0	120.000	179.0	٧	129.0	13.3
385.475250	12.37	36.00	23.63	1000.0	120.000	98.0	Н	343.0	16.6
512.753100	14.89	36.00	21.11	1000.0	120.000	98.0	٧	315.0	18.9
710.214150	18.89	36.00	17.11	1000.0	120.000	179.0	٧	129.0	21.8
937.713750	21.11	36.00	14.89	1000.0	120.000	98.0	Н	222.0	24.2




Plot 2: 30 MHz to 1 GHz, TX mode, channel 19, vertical & horizontal polarization



Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
38.730750	18.67	30.00	11.33	1000.0	120.000	101.0	٧	332.0	14.0
44.703750	19.53	30.00	10.47	1000.0	120.000	101.0	٧	6.0	13.9
47.922450	19.41	30.00	10.59	1000.0	120.000	98.0	٧	62.0	13.1
336.005400	23.21	36.00	12.79	1000.0	120.000	98.0	٧	20.0	15.6
431.986200	23.63	36.00	12.37	1000.0	120.000	98.0	٧	131.0	17.3
888.772500	21.03	36.00	14.97	1000.0	120.000	185.0	Н	131.0	24.0



Plot 3: 30 MHz to 1 GHz, TX mode, channel 39, vertical & horizontal polarization




Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
43.489500	18.19	30.00	11.81	1000.0	120.000	185.0	٧	266.0	13.9
45.016050	20.46	30.00	9.54	1000.0	120.000	98.0	٧	17.0	13.9
72.020850	13.68	30.00	16.32	1000.0	120.000	101.0	٧	294.0	8.4
177.114000	21.67	33.50	11.83	1000.0	120.000	98.0	٧	130.0	10.2
254.991450	20.05	36.00	15.95	1000.0	120.000	101.0	٧	344.0	13.5
726.512850	19.15	36.00	16.85	1000.0	120.000	185.0	Н	96.0	22.2



Plots: Receiver mode

Plot 1: 30 MHz to 1 GHz, RX / idle – mode, vertical & horizontal polarization



Frequency (MHz)	QuasiPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)
44.856450	16.87	30.00	13.13	1000.0	120.000	101.0	٧	158.0	13.9
157.235550	21.33	33.50	12.17	1000.0	120.000	98.0	٧	158.0	9.0
177.283350	22.06	33.50	11.44	1000.0	120.000	98.0	٧	351.0	10.2
249.982500	20.22	36.00	15.78	1000.0	120.000	101.0	٧	158.0	13.3
732.562950	19.38	36.00	16.62	1000.0	120.000	185.0	Н	122.0	22.3
927.285150	21.06	36.00	14.94	1000.0	120.000	179.0	Н	106.0	24.2



12.11 Spurious emissions radiated above 1 GHz

Description:

Measurement of the radiated spurious emissions in transmit mode. The EUT is set to single channel mode and the transmit channel is channel 00, channel 19 and channel 39. The measurement is performed in the mode with the highest output power.

Measurement parameters						
Detector	Peak / RMS					
Sweep time	Auto					
Resolution bandwidth	1 MHz					
Video bandwidth	3 x RBW					
Span	1 GHz to 26 GHz					
Trace mode	Max hold					
Measured modulation	GFSK					
Test setup	See sub clause 7.2 A (1 GHz - 18 GHz) See sub clause 7.3 A (18 GHz - 26 GHz)					
Measurement uncertainty	See sub clause 9					

The modulation with the highest output power was used to perform the transmitter spurious emissions. If spurious were detected a re-measurement was performed on the detected frequency with each modulation.

Limits:

FCC		IC							
TX spurious emissions radiated									
In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).									
Frequency (MHz)	Field streng	th (dBµV/m)	Measurement distance						
Above 960 54.0 (Average) 3									
Above 960	74.0 (Peak)	3						



Results: Transmitter mode

	TX spurious emissions radiated [dBμV/m]											
2402 MHz			2440 MHz			2480 MHz						
F [MHz]	Detector	Level [dBµV/m]				F [MHz]	Detector	Level [dBµV/m]				
	Peak			Peak		16026	Peak	54.5				
	AVG			AVG		10020	AVG	49.7				
	Peak			Peak			Peak					
	AVG			AVG			AVG					
	Peak			Peak			Peak					
	AVG			AVG			AVG					

Results: Receiver mode


RX spurious emissions radiated [dBμV/m]			
F [MHz]	Detector	Level [dBµV/m]	
4806	Peak	45.0	
	AVG	-/-	

Note: The limit was recalculated with 20 dB / decade (Part 15.31) for all radiated spurious emissions 30 MHz to 1 GHz from 3 meter limit to a 10 meter distance. (40dB/decade for emissions < 30MHz)




Plots: Transmitter mode

Plot 1: 1 GHz to 18 GHz, TX mode, channel 00, vertical & horizontal polarization




The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 2: 17.7 GHz to 18 GHz, TX mode, channel 00, vertical & horizontal polarization






Plot 3: 18 GHz to 26 GHz, TX mode, channel 00, vertical & horizontal polarization



Date: 19.MAY.2016 10:15:08




Plot 4: 1 GHz to 18 GHz, TX mode, channel 19, vertical & horizontal polarization




The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 5: 17.7 GHz to 18 GHz, TX mode, channel 19, vertical & horizontal polarization






Plot 6: 18 GHz to 26 GHz, TX mode, channel 19, vertical & horizontal polarization



Date: 19.MAY.2016 10:15:45




Plot 7: 1 GHz to 18 GHz, TX mode, channel 39, vertical & horizontal polarization




The carrier signal is notched with a 2.4 GHz band rejection filter.

Plot 8: 17.7 GHz to 18 GHz, TX mode, channel 39, vertical & horizontal polarization





Plot 9: 18 GHz to 26 GHz, TX mode, channel 39, vertical & horizontal polarization




Date: 19.MAY.2016 10:16:23




Plots: Receiver mode

Plot 1: 1 GHz to 18 GHz, RX / idle – mode, vertical & horizontal polarization




Plot 2: 17.7 GHz to 18 GHz, RX / idle – mode, vertical & horizontal polarization





Plot 3: 18 GHz to 26 GHz, RX / idle – mode, vertical & horizontal polarization



Date: 19.MAY.2016 10:17:01



13 Observations

No observations except those reported with the single test cases have been made.

Annex A Document history

Version	Applied changes	Date of release
	Initial release	2016-05-31

Annex B Further information

Glossary

AVG - Average

DUT - Device under test

EMC - Electromagnetic Compatibility

EN - European Standard
EUT - Equipment under test

ETSI - European Telecommunications Standard Institute

FCC - Federal Communication Commission

FCC ID - Company Identifier at FCC

HW - Hardware

IC - Industry Canada
Inv. No. - Inventory number
N/A - Not applicable
PP - Positive peak
QP - Quasi peak
S/N - Serial number
SW - Software

PMN - Product marketing name HMN - Host marketing name

HVIN - Hardware version identification number FVIN - Firmware version identification number



Annex C Accreditation Certificate

Front side of certificate

Back side of certificate

Deutsche Akkreditierungsstelle GmbH

Belinne gmäß is Absatz 1 Akkreiderungsstelle GmbH

Belinne gmäß is Absatz 1 Akkreiderungstelle GmbH

Belinne gmäß is Absatz 1 Akkreiderungstel

Note:

The current certificate including annex can be received from CETECOM ICT Services GmbH on request.