

APPLICATION CERTIFICATION
On Behalf of
VenSet A/S

Remote System
Model No.: R1100809(RF)

FCC ID: WX6R1100809

Prepared for : VenSet A/S
Address : Nygade 63, DK-6900 Skjern, Denmark

Prepared by : ACCURATE TECHNOLOGY CO. LTD
Address : F1, Bldg. A, Changyuan New Material Port, Keyuan Rd.
Science & Industry Park, Nanshan, Shenzhen,
Guangdong P.R. China

Tel: (0755) 26503290
Fax: (0755) 26503396

Report Number : ATE20082057
Date of Test : October 29 - November 4, 2008
Date of Report : November 4, 2008

TABLE OF CONTENTS

Description	Page
Test Report Certification	
1. GENERAL INFORMATION	4
1.1. Description of Device (EUT).....	4
1.2. Description of Test Facility	5
1.3. Measurement Uncertainty.....	5
2. MEASURING DEVICE AND TEST EQUIPMENT	6
3. SUMMARY OF TEST RESULTS.....	7
4. THE FIELD STRENGTH OF RADIATION EMISSION	8
4.1. Block Diagram of Test Setup.....	8
4.2. The Field Strength of Radiation Emission Measurement Limits.....	9
4.3. Configuration of EUT on Measurement	9
4.4. Operating Condition of EUT	9
4.5. Test Procedure	10
4.6. The Field Strength of Radiation Emission Measurement Results	11
5. 20DB OCCUPIED BANDWIDTH	12
5.1. Block Diagram of Test Setup.....	12
5.2. The Bandwidth of Emission Limit According To FCC Part 15 Section 15.231(c)	12
5.3. EUT Configuration on Measurement	13
5.4. Operating Condition of EUT	13
5.5. Test Procedure	13
5.6. Measurement Result	14
6. RELEASE TIME MEASUREMENT.....	15
6.1. Block Diagram of Test Setup.....	15
6.2. Release Time Measurement According To FCC Part 15 Section 15.231(a)	15
6.3. EUT Configuration on Measurement	16
6.4. Operating Condition of EUT	16
6.5. Test Procedure	16
6.6. Measurement Result	17
7. AVERAGE FACTOR MEASUREMENT	18
7.1. Block Diagram of Test Setup.....	18
7.2. Average factor Measurement according to ANSI 63.4: 2003.....	18
7.3. EUT Configuration on Measurement	19
7.4. Operating Condition of EUT	19
7.5. Test Procedure	19
7.6. Measurement Result	20

APPENDIX I (TEST CURVES) (9 pages)

Test Report Certification

Applicant : VenSet A/S
 Manufacturer : Shenzhen Yaoertai Technology Development Co., Ltd.
 EUT Description : Remote System
 (A) MODEL NO.: R1100809(RF)
 (B) SERIAL NO.: N/A
 (C) POWER SUPPLY: 12V DC ("27A" battery 1×)

Measurement Procedure Used:


FCC Rules and Regulations Part 15 Subpart C Section 15.231: 2008 & ANSI C63.4: 2003

The device described above is tested by ACCURATE TECHNOLOGY CO. LTD to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C Section 15.231. The measurement results are contained in this test report and ACCURATE TECHNOLOGY CO. LTD is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of ACCURATE TECHNOLOGY CO. LTD.


Date of Test : October 29 - November 4, 2008

Prepared by :



(Engineer)

Approved & Authorized Signer :



(Manager)

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT : Remote System

Model Number : R1100809(RF)

Power Supply : 12V DC (“27A” battery 1×)

Operation Frequency : 433.92 MHz

Applicant : VenSet A/S

Address : Nygade 63, DK-6900 Skjern, Denmark

Manufacturer : Shenzhen Yaoertai Technology Development Co., Ltd.

Address : 4/F, C Building, Xingzhongzheng Industry Park, 428 Jihua Road, Bantian Village, Longgang District, Shenzhen, China

Date of sample received : October 23, 2008

Date of Test : October 29 - November 4, 2008

1.2.Description of Test Facility

EMC Lab	: Accredited by TUV Rheinland Shenzhen
	Listed by FCC The Registration Number is 752051
	Listed by Industry Canada The Registration Number is 5077A-2
	Accredited by China National Accreditation Committee for Laboratories The Certificate Registration Number is L3193
Name of Firm	: ACCURATE TECHNOLOGY CO. LTD
Site Location	: F1, Bldg. A, Changyuan New Material Port, Keyuan Rd. Science & Industry Park, Nanshan, Shenzhen, Guangdong P.R. China

1.3.Measurement Uncertainty

Conducted Emission Expanded Uncertainty = 2.23dB, k=2

Radiated emission expanded uncertainty = 3.08dB, k=2
(9kHz-30MHz)

Radiated emission expanded uncertainty = 4.42dB, k=2
(30MHz-1000MHz)

Radiated emission expanded uncertainty = 4.06dB, k=2
(Above 1GHz)

2. MEASURING DEVICE AND TEST EQUIPMENT

Table 1: List of Test and Measurement Equipment

Kind of equipment	Manufacturer	Type	S/N	Calibrated until
EMI Test Receiver	Rohde&Schwarz	ESCS30	100307	03.29.2009
EMI Test Receiver	Rohde&Schwarz	ESPI3	101526/003	03.29.2009
Spectrum Analyzer	Agilent	E7405A	MY45115511	03.29.2009
Pre-Amplifier	Rohde&Schwarz	CBLU118354 0-01	3791	03.31.2009
Loop Antenna	Schwarzbeck	FMZB1516	1516131	03.28.2009
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	03.29.2009
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	12.20.2008
Horn Antenna	Schwarzbeck	BBHA9170	9170-359	10.09.2009
LISN	Rohde&Schwarz	ESH3-Z5	100305	03.29.2009
LISN	Schwarzbeck	NSLK8126	8126431	03.29.2009

3. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
Section 15.207	Conducted Emission	N/A
Section 15.231(b)	Radiated Emission	Compliant
Section 15.231(c)	20dB Bandwidth	Compliant
Section 15.231(a)(1)	Release Time Measurement	Compliant

The product is a manually operated Remote System transmitter.

Section 15.231 (a) (2), (3), (4) and (5) are not applicable.

4. THE FIELD STRENGTH OF RADIATION EMISSION


4.1. Block Diagram of Test Setup

4.1.1. Block diagram of connection between the EUT and simulators



(EUT: Remote System)

4.1.2. Anechoic Chamber Test Setup Diagram



(EUT: Remote System)

4.2.The Field Strength of Radiation Emission Measurement Limits

4.2.1.Radiation Emission Measurement Limits According to FCC Part 15 Section 15.231(b)

Frequency Range of Fundamental [MHz]	Field Strength of Fundamental Emission [Average] [μ V/m]	Field Strength of Spurious Emission [Average] [μ V/m]
40.66-40.70	2250	225
70-130	1250	125
130-174	1250-3750	125-375
174-260	3750	375
260-470	3750-12500	375-1250
Above 470	12500	1250

Where F is the frequency in MHz, the formulas for calculating the maximum permitted fundamental field strengths are as follows: for the band 130-174 MHz, μ V/m at 3 meters = $56.81818(F) - 6136.3636$; for the band 260-470 MHz, μ V/m at 3 meters = $41.6667(F) - 7083.3333$. The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.

4.2.2.Restricted Band Radiation Emission Measurement Limits According to FCC part 15 Section 15.205 and Section15.209.

4.3.Configuration of EUT on Measurement

The following equipment is installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

4.3.1. Remote System (EUT)

Model Number : R1100809(RF)
 Serial Number : N/A
 Manufacturer : VenSet A/S

4.4.Operating Condition of EUT

4.4.1.Setup the EUT and simulator as shown as Section 4.1.

4.4.2.Turn on the power of all equipment.

4.4.3.Let the EUT work in TX mode measure it.

4.5. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground. The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bi-log antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the EUT location must be manipulated according to ANSI 63.4 on radiated emission measurement.

The bandwidth of test receiver is set at 120kHz in 30-1000MHz, and 1MHz in 1000-5000MHz.

The frequency range from 30MHz to 5000MHz is checked.

4.6. The Field Strength of Radiation Emission Measurement Results PASS.

The frequency range 30MHz to 4000MHz is investigated.

Date of Test:	November 1, 2008	Temperature:	25°C
EUT:	Remote System	Humidity:	52%
Model No.:	R1100809(RF)	Power Supply:	12V DC ("27A" battery 1×)
Test Mode:	TX	Test Engineer:	Joe

Frequency (MHz)	Reading (dB μ V/m)	Factor	Average Factor	Result(dB μ V/m)		Limit(dB μ V/m)		Margin(dB)		Polarization
	PEAK	Corr.	(dB)	AV	PEAK	AV	PEAK	AV	PEAK	
433.9040	60.68	22.95	-8.0	75.63	83.63	80.8	100.8	5.17	-17.17	Horizontal
867.8080	29.18	28.64	-8.0	49.82	57.82	60.8	80.8	10.98	-22.98	
*1301.712	70.63	-12.20	-8.0	50.43	58.43	54.0	74.0	3.57	-15.57	
1735.616	74.57	-10.39	-8.0	56.18	64.18	60.8	80.8	4.62	-16.62	
2169.520	71.54	-8.38	-8.0	55.16	63.16	60.8	80.8	5.64	-17.64	
2603.424	68.16	-6.72	-8.0	53.44	61.44	60.8	80.8	7.36	-19.36	
433.9040	61.15	22.95	-8.0	76.10	84.10	80.8	100.8	4.70	-16.70	Vertical
867.8080	30.18	28.64	-8.0	50.82	58.82	60.8	80.8	9.98	-21.98	
*1301.712	70.20	-12.20	-8.0	50.00	58.00	54.0	74.0	4.00	-16.00	
1735.616	74.21	-10.39	-8.0	55.82	63.82	60.8	80.8	4.98	-16.98	
2169.520	70.15	-8.38	-8.0	53.77	61.77	60.8	80.8	7.03	-19.03	
2603.424	64.55	-6.72	-8.0	49.83	57.83	60.8	80.8	10.97	-22.97	

Note:

1. *: Denotes restricted band of operation.

Measurements were made using a peak detector and average detector. Any emission falling within the restricted bands of FCC Part 15 Section 15.205 were compliance with the emission limit of FCC Part 15 Section 15.209.

2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:

$$\text{Result} = \text{Reading} + \text{Corrected Factor}$$

Where Corrected Factor = Antenna Factor + Cable Loss + High Pass Filter Loss – Amplifier Gain


3. FCC Limit for Average Measurement = $41.6667(433.9)-7083.3333 = 10995.85\mu\text{V/m} = 80.8\text{dB}\mu\text{V/m}$

4. The spectral diagrams in appendix I display the measurement of peak values.


5. 20DB OCCUPIED BANDWIDTH

5.1. Block Diagram of Test Setup

5.1.1. Block diagram of connection between the EUT and simulators



5.1.2. Anechoic Chamber Test Setup Diagram



(EUT: Remote System)

5.2. The Bandwidth of Emission Limit According To FCC Part 15 Section

15.231(c)

The bandwidth of emission shall be no wider than 0.25% of the center frequency. Therefore, the bandwidth of the emission limit is $433.9\text{MHz} \times 0.25\% = 1.08\text{MHz}$. Bandwidth is determined at the two points 20 dB down from the top of modulated carrier.

5.3.EUT Configuration on Measurement

The following equipment are installed on the bandwidth of emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

5.3.1.Remote System (EUT)

Model Number : R1100809(RF)
Serial Number : N/A
Manufacturer : VenSet A/S

5.4.Operating Condition of EUT

5.4.1.Setup the EUT and simulator as shown as Section 5.1.

5.4.2.Turn on the power of all equipment.

5.4.3.Let the EUT work in TX mode measure it.

5.5.Test Procedure

5.5.1.Set SPA Center Frequency = Fundamental frequency, RBW = 10kHz, VBW = 30kHz, Span = 1MHz.

5.5.2.Set SPA Max hold. Mark peak, -20dB

5.6.Measurement Result

The EUT does meet the FCC requirement.

-20dB bandwidth = 62.0kHz < 1.08MHz.

The spectral diagrams in appendix I.

6. RELEASE TIME MEASUREMENT


6.1. Block Diagram of Test Setup

6.1.1. Block diagram of connection between the EUT and simulators



(EUT: Remote System)

6.1.2. Anechoic Chamber Test Setup Diagram



6.2. Release Time Measurement According To FCC Part 15 Section 15.231(a)

Section 15.231(a) (1) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

6.3.EUT Configuration on Measurement

The following equipment are installed on Release Time Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

6.3.1. Remote System (EUT)

Model Number : R1100809(RF)
Serial Number : N/A
Manufacturer : VenSet A/S

6.4.Operating Condition of EUT

6.4.1. Setup the EUT and simulator as shown as Section 6.1.

6.4.2. Turn on the power of all equipment.

6.4.3. Let the EUT work in TX mode measure it.

6.5.Test Procedure

6.5.1. Set SPA Center Frequency = Fundamental frequency, RBW = 100kHz, VBW = 300kHz, Span = 0Hz. Sweep time = 5 seconds.

6.5.2. Set EUT as normal operation and press Transmitter button.

6.5.3. Set SPA View. Delta Mark time.

6.6. Measurement Result

The release time less than 5 seconds.


Release Time= 1.86 s

The spectral diagrams in appendix I.


7. AVERAGE FACTOR MEASUREMENT

7.1. Block Diagram of Test Setup

7.1.1. Block diagram of connection between the EUT and simulators



7.1.2. Anechoic Chamber Test Setup Diagram



7.2. Average factor Measurement according to ANSI 63.4: 2003

ANSI 63.4: 2003 Section 13.1.4.2 Devices transmitting pulsed emissions and subject to a limit requiring an average detector function for radiated emissions shall initially be measured with an instrument that uses a peak detector. A radiated emission measured with a peak detector may then be corrected to a true average using the appropriate factor for emission duty cycle. This correction factor relates the measured peak level to the average limit and is derived by averaging absolute field strength over one complete pulse train that is 0.1 s, or less, in length. If the pulse train is longer than 0.1 s, the average shall be determined from the average absolute field strength during the 0.1 s interval in which the field strength is at a maximum. Instructions on calculating the duty cycle of a transmitter with pulsed emissions are provided in ANSI 63.4 H.4, step j.

Average factor in dB = $20 \log (\text{duty cycle})$

7.3.EUT Configuration on Measurement

The following equipment are installed on average factor Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

7.3.1. Remote System (EUT)

Model Number : R1100809(RF)
 Serial Number : N/A
 Manufacturer : VenSet A/S

7.4.Operating Condition of EUT

7.4.1. Setup the EUT and simulator as shown as Section 7.1.

7.4.2. Turn on the power of all equipment.

7.4.3. Let the EUT work in TX mode measure it.

7.5.Test Procedure

7.5.1. The time period over which the duty cycle is measured is 100 milliseconds, or the repetition cycle, whichever is a shorter time frame. The worst case (highest percentage on) duty cycle is used for the calculation.

7.5.2. Set SPA Center Frequency = Fundamental frequency, RBW = 100kHz, VBW = 300kHz, Span = 0Hz.

7.5.3. Set EUT as normal operation.

7.5.4. Set SPA View. Delta Mark time.

7.6. Measurement Result

The duty cycle is simply the on time divided by the period:

The duration of one cycle = 47.70ms

Effective period of the cycle = $(11 \times 1.18) + (14 \times 0.43)$ ms = 19.00ms

$$DC = 19.00\text{ms}/47.70\text{ms} = 0.3983$$

Therefore, the average factor is found by $20\log 0.3983 = -8.0\text{dB}$

The spectral diagrams in appendix I.

APPENDIX I (Test Curves)


ACCURATE TECHNOLOGY CO., LTD.


 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 966 chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: RTTE #750
 Standard: FCC Class B 3M Radiated
 Test item: Radiation Test
 Temp.(C)/Hum.(%) 25 C / 52 %
 EUT: REMOTE SYSTEM
 Mode: TX
 Model: R1100809(RF)
 Manufacturer: VenSet A/S

Polarization: Horizontal
 Power Source: DC 12V
 Date: 08/11/01/
 Time: 10/07/13
 Engineer Signature: Joe
 Distance: 3m

Note: Sample No.:083857 Report No.:ATE20082057



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	433.9040	60.68	22.95	83.63	100.8	-17.17	peak	
2	867.8080	29.18	28.64	57.82	80.8	-22.98	peak	


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 966 chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: RTTE #751

Polarization: Vertical

Standard: FCC Class B 3M Radiated

Power Source: DC 12V

Test item: Radiation Test

Date: 08/11/01/

Temp.(C)/Hum.(%) 25 C / 52 %

Time: 10/08/25

EUT: REMOTE SYSTEM

Engineer Signature: Joe


Mode: TX

Distance: 3m

Model: R1100809(RF)

Manufacturer: VenSet A/S

Note: Sample No.:083857 Report No.:ATE20082057



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	433.9040	61.15	22.95	84.10	100.8	-16.70	peak	
2	867.8080	30.18	28.64	58.82	80.8	-21.98	peak	


ACCURATE TECHNOLOGY CO., LTD.


 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

 Site: 966 chamber
 Tel:+86-0755-26503290
 Fax:+86-0755-26503396

Job No.: RTTE #748
 Standard: FCC Class B 3M Radiated
 Test item: Radiation Test
 Temp.(C)/Hum.(%) 25 C / 52 %
 EUT: REMOTE SYSTEM
 Mode: TX
 Model: R1100809(RF)
 Manufacturer: VenSet A/S

Polarization: Horizontal
 Power Source: DC 12V
 Date: 08/11/01/
 Time: 9/49/41
 Engineer Signature: Joe
 Distance: 3m

Note: Sample No.:083857 Report No.:ATE20082057



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	1301.712	70.63	-12.20	58.43	74.0	-15.57	peak	
2	1735.616	74.57	-10.39	64.18	80.8	-16.62	peak	
3	2169.520	71.54	-8.38	63.16	80.8	-17.64	peak	
4	2603.424	68.16	-6.72	61.44	80.8	-19.36	peak	


ACCURATE TECHNOLOGY CO., LTD.

 F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
 Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 966 chamber


Tel:+86-0755-26503290

Fax:+86-0755-26503396


Job No.: RTTE #749
 Standard: FCC Class B 3M Radiated
 Test item: Radiation Test
 Temp.(C)/Hum.(%) 25 C / 52 %
 EUT: REMOTE SYSTEM
 Mode: TX
 Model: R1100809(RF)
 Manufacturer: VenSet A/S

Polarization: Vertical
 Power Source: DC 12V
 Date: 08/11/01/
 Time: 9/53/03
 Engineer Signature: Joe
 Distance: 3m


Note: Sample No.:083857 Report No.:ATE20082057




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Remark
1	1301.712	70.20	-12.20	58.00	74.0	-16.00	peak	
2	1735.616	74.21	-10.39	63.82	80.8	-16.98	peak	
3	2169.520	70.15	-8.38	61.77	80.8	-19.03	peak	
4	2603.424	64.55	-6.72	57.83	80.8	-22.97	peak	



Date: 3.NOV.2008 08:08:04




Date: 4.NOV.2008 10:11:02




Date: 3.NOV.2008 08:16:31

The graph shows the pattern of coding during the signal transmission. It sums of 11 long 'on' signals and 14 short 'on' signals.



Date: 3.NOV.2008 08:30:06

The graph shows the duration of long 'on' signal. From marker 1 to marker 2, duration is 1.18ms.



Date: 3.NOV.2008 08:27:43

The graph shows the duration of short 'on' signal. From marker 1 to marker 2, duration is 0.43ms.