

GIGA-TMS INC.
8F, NO.31, LANE 169, KANG-NING ST.,HSI-CHIH, NEW TAIPEI CITY,
22180 TAIWAN

Federal Communications Commission
Authorization and Evaluation Division
Equipment Authorization Branch
7435 Oakland Mills Road
Columbia, MD 21046

Applicant's declaration concerning RF Radiation Exposure

We hereby indicate that the product
Product description: NEXT-GEN UHF RFID Reader
Model No: RU224-51

The equipment complies with FCC RF radiation exposure limits set forth for an uncontrolled environment. The integral antennas used for this transmitter must not be co-located or operating in conjunction with any other antenna or transmitter within the host device.

A safety statement concerning minimum separation distances from enclosure of the
Product : NEXT-GEN UHF RFID Reader
will be integrated in the user's manual to provide end-users with transmitter operating
conditions for satisfying RF exposure compliance.

The appropriate information can be drawn from the test report no: W6R21907-19234-C-1
and the accompanying calculations.

Company: GIGA-TMS INC.
Address: 8F, NO.31, LANE 169, KANG-NING ST.,HSI-CHIH, NEW TAIPEI CITY, 22180
TAIWAN

Date: 2019.12.09

Signature

A handwritten signature in blue ink, appearing to read "M. T. Wang".



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6R21907-19234-C-1

FCC ID: WXARU224RB

3.2 Equivalent isotropic radiated power (EIRP)

FCC Rule: 15.247(b)(3)

EIRP = max. conducted output power + antenna gain

UHF (902.5-927.5 MHz)

EIRP = 29.37 dBm + (6 dBi [antenna gain claimed by manufacturer]) = 35.37 dBm = 3443.50 mW

3.3 Exemption Limits for Routine Evaluation according to 47 CFR FCC Part 2 Subpart J, section 2.1091

FCC OET Bulletin 65 Edition 97.01 determines the equations for predicting RF fields and applicable limits.

The prediction for power density in the far-field but will over-predict power density in the near field, where it could be used for walking a “worst case” or conservative prediction.

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 25 cm normally can be maintained between the user and the device.

MPE Calculation Method

(A) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6

(B) Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/1500	30
1500-100,000	--	--	1.0	30

f = frequency in MHz


*Plane-wave equivalent power density

E = Electric field (V/m) P = output power (W) G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd \cdot \frac{30 \times P \times G}{377 \times d^2} \text{ mW/m}^2.$$



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6R21907-19234-C-1

FCC ID: WXARU224RB

UHF

Established separation distance is 25 cm.

Operating frequency band: 902.5-927.5 MHz

The product meets RF exposure requirement.

Because the power density of 0.4384 mW/cm² at 902.5 MHz is below the power density limit of 0.6017 mW/cm².