

# FCC MEASUREMENT REPORT

# **CERTIFICATION OF COMPLIANCE**

PRODUCT : CDMA Repeater

MODEL/TYPE NO : JI-43CP

FCC ID : WYFJI-43CP

TRADE NAME : \langle Iir Point

Airpoint Co., Ltd.

APPLICANT : 946 Dunsan-dong, Seo-qu, Daejeon, 302-120, Korea.

Yoon-Sun, Lee / Research Engineer

CLASSIFICATION : TNB Licensed Non-Broadcast Station Transmitter

RULE PART(S) : FCC Part 24
FCC PROCEDURE : Certification

DATES OF TEST : January 9 to 30, 2009

DATES OF ISSUE : February 3, 2009
TEST REPORT No. : BWS-09-RF-003

TEST LAB. : BWS TECH Inc. (Registration No. : 553281)

This CDMA Repeater JI-43CP has been tested in accordance with the measurement procedures specified in ANSI C63.4-2003 and ANSI/TIA-603-C-2004 at the BWS TECH/EMC Test Laboratory and has been shown to be complied with the electromagnetic radiated emission limits specified in FCC Rule Part 24.

I attest to the accuracy of data. All measurement herein was performed by me or were made under my supervision. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. The results of testing in this report apply to the product/system, which was tested only. Other similar equipment may not necessarily produce the same results due to production tolerance and measurement uncertainties.

February 3, 2009

(Date)

Reviewed by HyunSup, Jin

February 3, 2009

(Date)

Reviewed by TaeHyun, Nam

# **BWS TECH Inc.**

www.bws.co.kr

#611-1 Maesan-Ri, Mohyeon-Myeon, Yongin-Si, Gyeonggi-Do, 449-853 Korea TEL: +82 31 333 5997 FAX: +82 31 333 0017



# **TABLE OF CONTENTS**

		Pages
1. Gene	eral Information	3
2. Desc	ription of Test Facility	4
3. Prod	uct Information	5
4. Sum	mary of Test Results	6~7
5. Test	Data	8
5.1	Power Line Conducted Emission	8~9
5.2	RF Power Output	10~11
5.3	Occupied Bandwidth	12~13
5.4	Spurious Emission at Antenna Terminal	14~15
5.5	Field Strength of Spurious Radiation	16~17
5.6	Frequency Stability/ Temperature Variation	18~19
6. Test	Plot	20
6.1	Power Line Conducted Emission	20~23
6.2	RF Power Output	24~29
6.3	Occupied Bandwidth	30~32
6.4	Spurious Emissions at Antenna Terminals	33~46
6.5	Out of band Rejection	47~48
6.6	Field Strength of Spurious Radiation	49~50
6.7	Frequency Stability/ Temperature Variation	51~60
7. Test	Equipment List	61

Data of Issue:



# FCC TEST REPORT

**Scope** - Measurement and determination of electromagnetic emission(EME) of radio frequency devices including intentional radiators and/or unintentional radiators for compliance with the technical rules and regulations of the U.S Federal Communications Commission(FCC)

### 1. General Information

### **Applicant**

Company Name Airpoint Co., Ltd.

**Company Address** 946 Dunsan-dong, Seo-gu, Daejeon, 302-120, Korea.

**Phone/Fax** Phone: 82-42-484-5460(ex. 131) Fax: 82-42-485-5460

**Manufacturer** 

Company Name Airpoint Co., Ltd.

 Company Address
 946 Dunsan-dong, Seo-gu, Daejeon, 302-120, Korea.

 Phone/Fax
 Phone: 82-42-484-5460(ex. 131)
 Fax: 82-42-485-5460

• EUT Type CDMA Repeater

Model Number
 FCC Identifier
 S/N
 FCC Rule Part(s)
 JI-43CP
 WYFJI43CP
 Prototype
 FCC Part 24

• FCC Classification TNB / Licensed Non-Broadcast Station Transmitter

■ Block A: 1850-1865 MHz
■ Block D: 1865-1870 MHz
■ Block B: 1870-1885 MHz
■ Block E: 1885-1890 MHz
■ Block F: 1890-1895 MHz
■ Block C: 1895-1910 MHz
■ Block G: 1910-1915 MHz
■ Block G: 1990-1995 MHz

Modulation Method CDMA

Service Block

• Emission Designator F9W

• RF Power Output 20 W / 0.5 W

Test Procedure ANSI C63.4-2003 and ANSI/TIA-603-C-2004

Dates of Tests
 January 9 to 30, 2009

BWS TECH Inc. (FCC Registration Number: 553281)


• Place of Tests #611-1 Maesan-Ri, Mohyeon-Myeon, Yongin-Si, Gyeonggi-Do, 449-853 Korea

TEL: +82 31 333 5997 FAX: +82 31 333 0017

• Test Report No. BWS-09-RF-003

Report No: BWS-09-RF-003 **FCC Test Report**Page Number: 3 of 61

Data of Issue: February 3, 2009





# 2. Description of Test Facility

The measurement for radiated and conducted emission test were conducted at the open area test site of BWS TECH Inc. facility located at #611-1 Maesan-Ri, Mohyeon-Myeon, Yongin-Si, Gyeonggi-Do, 449-853 Korea. The site is constructed in conformance with the requirements of the ANSI C63.4-2003 and CISPR Publication 16. The BWS TECH measurement facility has been filed to the Commission with the FCC for 3 and 10-meter site configurations. Detailed description of test facility was found to be in compliance with the requirements of Section 2.948 FCC Rules according to the ANSI C63.4-2003 and registered to the Federal Communications Commission (Registration Number : 553281).

The measurement procedure described in American National Standard for Method of Measurement of Radio-Noise Emission from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz (ANSI C.63.4-2003) was used in determining radiated and conducted emissions from the Hutech21. Co., Ltd. CDMA Repeater Model: **JI-43CP** 



# 3. Product Information

3.1 General Specification

Description	Unit	JI-43CP	Comment
	R	F Specifications	
Frequency Band	DL	1930.625MHz~1994.375MHz	
	UL	1850.625MHz~1914.375MHz	
Bandwidth Total BV	V	63.75MHz	
DL Power Out(Per Band	) dBm	43dBm(20W)	
UL Power Out(Per Band	) dBm	27dBm(0.5W)	
Gain	dB	DL=105dB / UL=100dB	
Gain Range	dB	35	
Gain Accuracy	±dB	2	
Ripple	±dB	2	
AGC Range	dB	35	
Noise Figure	dB	6/12	UL Max.
3			Gain/Min. Gair
Total System Delay	us	12	
VSWR		1.5:1	
Antenna Port Impedence	e Ohms	50	
DL Input Range	dBm	-62~-27	
UL Input Range	dBm	-73~-38	
Number of FA(MAX)	9.2	7FA	
	Adiad	cent Channel Power	1
885 kHZ	30kHz BW	≥45dBc	
1.125 MHz	30kHz BW	≥45dBc	
1.1980 MHz	30kHz BW	≥45dBc	
2.250 MHz	30kHz BW	≥50dBm	
≥4MHz	1MHz BW	≤-13dBm	
= 11VII 12	•	tem Measurements	<u> </u>
Frequency Error	Hz	$\leq \pm 0.05$ ppm(1800MHzx( $\pm 0.05$ ppm)= $\pm 90$ Hz	
RHO	112	≥0.912	
1410	L	Physical	
Size	mm	W X L X H(mm)=430X625X330	Include ROOF
0.20		, 2,()	and BRACKE
Sound level max @1met	er dBA	<55dBA	
Cabinet IP		IP-55	
Operating temperature	°C	-40~55℃	
Humidity	%	5~95%	
Voltage	VAC	115VAC~240VAC±10%	
Power(W)	W	<450W	
RF ports	V V	7/16 DIN-Female	1
CDMA Modem antenna p	ort	Type N Female	



# 3.2 EUT operating conditions & test configuration

### 3.2.1 Client Condition

Temperature : -20 °C  $\sim +50$  °C

Humidity : 95 %

3.2.2 EUT Operating Condition

E LOT Operating	, containen
Mode	
Down Link	RF signal from the CDMA signal generator injecteted to the Doner port of the repeater and the amplified RF output signal from the Service port of the repeater was connected to the Spectrom analyzer.
Up Link	RF signal from the CDMA signal generator injecteted to the Service port of the repeater and the amplified RF output signal from the Donor port of the repeater was connected to the Spectrom analyzer.

# 3.2.3 Test Frequency

Mode	Channel	Frequency
	Bottom channel	1931.25 MHz
Down Link	Mid channel	1962.50 MHz
	Top channel	1993.75 MHz
	Bottom channel	1851.25 MHz
Up Link	Mid channel	1882.50 MHz
	Top channel	1913.75 MHz

# 3.2.4 Test Signal Source

The carrier from the signal generator applied to the repeater was a IS-95 CDMA standard signal.

Report No: BWS-09-RF-003 Page Number: 6 of 61 **FCC Test Report** Data of Issue: February 3, 2009



# 4. Applied Standards

# 4.1. FCC Rules and Regulations

- 47 CFR Part 24 Subpart E Personal Communication Service-Broadband PCS
- 47 CFT Part 15 Subpart B General Technical requirements

# 4.2. Supporting Standards

- EIA/TIA-603-C:2004 Land Mobile FM or PM Communications Equipment Measurement and Performance
- ITU-R Recommendation SM.329-10(2003)
- ANSI C63.4:2003 Methods of Measurement of Radio-Noise Emissions from Low Voltage Electrical and Electronic Equipment in Range of 9 kHz to 40 GHz
- FCC 2-11-04 EAB/RF Amplifier, Booster, and Repeater reminder

#### 4.3. Test Items

The following requirements and test specifications within Table 1 are relevant to the conformity to FCC rules and regulations.

Table 1 Summary of test items

FCC Measurement Specification	FCC Limit	Description	Test Result	
§ 15.107	§ 15.107	Power Line Conducted Emission	Pass	
§2.1046	§24.232	RF Power Output	Pass	
§2.1049	-	Occupied Bandwidth	Pass	
§2.1051	§24.238	Spurious Emissions at Antenna Terminals	Pass	
§2.1053	§24.238	Radiated Spurious Emission	Pass	
§2.1055	§24.235	Frequency Stability	Pass	
		Out of band Rejention	Pass	

Report No: BWS-09-RF-003 Page Number: 7 of 61 **FCC Test Report** Data of Issue: February 3, 2009



# 5. TEST DATA

#### 5.1 Power Line Conducted Emission


### 5.1.1 Specification

Conducted Emissions were measured from 150 kHz to 30 MHz with a bandwidth of 9 kHz on the 230V AC power and return leads of the EUT according to the methods defined in FCC Part 15.107. The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane as shown in section 3.1.5. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position producing maximum conducted emissions.

#### 5.1.2 Method of Measurement

The EUT was placed on a nonmetallic stand in a shielded room 0.8 meters above the ground plane as shown in section 3.1.5. The interface cables and equipment positioning were varied within limits of reasonable applications to determine the position producing maximum conducted emissions

#### 5.1.3 Measurement Set-Up



#### 5.1.4 Limit

Frequency Range	Limit (dBuV)			
(MHz)	Quasi-Peak	Average		
0.15 ~ 0.5	79	66		
0.5 ~ 30	73	60		

#### 5.1.6 Test Result

Frequency Range of Test : 150 kHz to 30 MHz

Test Standard : FCC Part 15.107 Test Date : January 11, 2009

Temperature/Humidity : 20 °C/ 52 %

Report No: BWS-09-RF-003 Page Number: 8 of 61 **FCC Test Report** Data of Issue: February 3, 2009



#### 5.1.6.1 Down link

	Corre	Correction			Quasi-I	Peak Mode			Averag	e Mode	
Freq [MHz]	AMN	C.L	Phase [H/N]	Limit	Reading	Emission Level	Margin	Limit	Reading	Emission Level	Margin
				[dBuV]	[dBuV]	[dBuV]	[dBuV]	[dBuV]	[dBuV]	[dBuV]	[dBuV]
0.150	0.06	0.03	N		49.08	49.17	29.83				
0.202	0.07	0.10	Н	79.00	44.70	44.87	34.13	66.00			
0.262	0.07	0.16	Н	79.00	60.21	60.44	18.56	00.00			
0.390	0.08	0.24	Н		54.50	54.82	24.18				
0.650	0.07	0.30	Н		55.96	56.33	16.67		44.80	45.17	14.83
1.430	0.03	0.46	Н	73.00	61.14	61.63	11.37	60.00	45.93	46.42	13.58
5.738	0.06	0.89	N	73.00	69.26	70.21	2.79	00.00	52.28	53.23	6.77
13.758	0.07	1.21	Н		59.14	60.42	12.58		42.72	44.00	16.00

# 5.1.6.2 Up link

	Corre	ection			Quasi-I	Peak Mode			Averag	e Mode	
Freq [MHz]	AMN	C.L	Phase [H/N]	Limit	Reading	Emission Level	Margin	Limit	Reading	Emission Level	Margin
				[dBuV]	[dBuV]	[dBuV]	[dBuV]	[dBuV]	[dBuV]	[dBuV]	[dBuV]
0.150	0.06	0.03	Н		60.89	60.98	18.02				
0.202	0.07	0.10	N	79.00	47.43	47.60	31.40	66.00			
0.262	0.07	0.16	N	79.00	60.34	60.57	18.43	00.00			
0.390	0.08	0.24	N		56.03	56.35	22.65				
0.650	0.07	0.30	N		55.56	55.93	17.07		44.97	45.34	14.66
1.570	0.03	0.48	N	73.00	59.65	60.16	12.84	60.00	44.79	45.30	14.70
5.698	0.06	0.89	Н	73.00	70.06	71.01	1.99	00.00	53.91	54.86	5.14
9.458	0.07	1.01	Н		59.75	60.83	12.17		40.85	41.93	18.07

# Notes:

- 1. All modes of operation were investigated and the worst-case emissions are reported. See the plots in next 2 pages.
- 2. Line N = (Neutral), Line H = (Hot)
- 3. Measurement uncertainty estimated at  $\pm 1.38$  dB.

The measurement uncertainty is given with a confidence of 95.45 % with the coverage factor, k=2

4. The detail plot data is refer to 6.1.



# **5.2 RF Power Output**

### 5.2.1 Specification


-. Measurements were made in the laboratory environment. For RF power measurements, all caculations and methods used by the applicant for determining carrier power or peak envelope power, as appropriate, on the basis of measured power in the radio frequency load attached to the transmitter output terminals shall be shown. The EUT was adjusted to produce maximum power rating of the product specification. The measurement were made at the EUT input and output ports in downlink and uplink transmit modes of operation at B,M,T channels.

#### 5.2.2 Method of Measurement

ANSI/TIA-603-C-2004 Section 2.2.1

- -. The EUT was connected to a Signal Analyzer via the main RF connector, and through an appropriate Attenuator.
- -. Diversity RF connectors were connected to 50 Ohm match load.
- -. The EUT was controlled to power amplifier of each block by a LapTop Computer.
- -. Measure and record the maximum channel power of the EUT by the Spectrum Analyzer.
- -. The transmitter was tested while in a continuous transmit mode.
- -. The EUT was tuned to a low, middle, and high channel in both the downlink and uplink directions.

### 5.2.3 Measurement Set-Up



### 5.2.4 Limit

§ 24.232

Report No: BWS-09-RF-003 Page Number: 10 of 61 **FCC Test Report** Data of Issue: February 3, 2009



#### 5.2.5 Test Result

### RF output power measured data

Carrier Band	Frequency(MHz)	Loss offset(dB)	Measured Power(dBm)
	1931.250	42.3	43.52
Downlink	1962.500	42.3	43.61
	1993.750	42.3	43.20
	1851.250	42.3	27.36
Uplink	1882.500	42.3	27.72
	1913.750	42.3	27.42

### Supplement information:

- -. Modulation signal CDMA, Power measurement : Channel power w/ mean value
- -. Before the measurement, the system calibration for compensation of cable loss and attenuator has been made and include in the test result.

# Maximum composite output power data (7FA)

Carrier Band	Frequency(MHz)	Loss offset(dB)	Measured Power(dBm)
	1935.000	41.5	43.12
Downlink	1962.500	41.5	43.96
	1990.000	41.5	43.01
	1855.000	41.3	27.35
Uplink	1882.500	41.3	27.77
	1910.000	41.3	27.38

#### Supplement information:

- -. Modulation signal CDMA, Power measurement : Channel power w/ mean value
- -. Before the measurement, the system calibration for compensation of cable loss and attenuator has been made and include in the test result.

### 5.3.6 Conclusion

The equipment **passed** the requirement of this clause. Also refer to 6.2 of the present test report for detailed.



# 5.3 Occupied Bandwidth

#### 5.3.1 Specification


Measurements were made in the laboratory environment. The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured.

#### 5.3.2 Method of Measurement

ANSI/TIA-603-C-2004 Section 2.2.11

- -. The EUT was connected to a Signal Analyzer via the main RF connector, and through an appropriate Attenuator.
- -. Diversity RF connectors were connected to 50 Ohm match load.
- -. The EUT was controlled to power amplifier of each block by a Laptop Computer.
- -. Measure and record the occupied bandwidth of the EUT by the Spectrum Analyzer.
- -. The transmitter was tested while in a continuous transmit mode.
- -. The EUT was tuned to a low, middle, and high channel in both the downlink and uplink directions.
- -. The main settings of the Signal Analyzer were as below: Measurement bandwidth (RBW): 30kHz

### 5.3.3 Measurement Set-Up



#### 5.3.4 Limit

-. According to 47 CFR Part 2 section § 2.1049 and Part 24, no specific modulation characteristics requirement limits is applicable.

Report No: BWS-09-RF-003 Page Number: 12 of 61 **FCC Test Report** Data of Issue: February 3, 2009



# 5.3.5 Test Result

# **Occupied Bandwidth measured results**

Carrier Band	Frequency(MHz)	Occupied bandwidth (MHz)
	1931.250	1.266
Downlink	1962.500	1.260
	1993.750	1.266
	1851.250	1.266
Uplink	1882.500	1.266
	1913.750	1.266

Supplement information:

### 5.3.6 Conclusion

The equipment **passed** the requirement of this clause. Also refer to 6.3 of the present test report for detailed.

<sup>-.</sup> Modulation signal CDMA, modulation applied, 99% bandwidth



# 5.4 Spurious Emissions at Antenna Terminals

### 5.4.1 Specification


-. Measurements were made in the laboratory environment. Conducted spurious emission measurement wsa made using a direct connection between RF output of the EUT and spectrum analyzer. A modulated carrier signal from the generator was applied to the both uplink and down link port of the EUT. Measurement has been performed with the EUT set to maximum output level at low, mid, and high channel frequencies.

#### 5.4.2 Method of Measurement

ANSI/TIA-603-C-2004 Section 2.2.13

- -. The EUT was connected to a Signal Analyzer via the main RF connector, and through an appropriate
- -. Diversity RF connectors were connected to 50 Ohm match load.
- -. The EUT was controlled to power amplifier of each block by a LapTop Computer.
- -. Measure and record the spurious emissions bandwidth of the EUT by the Spectrum Analyzer.
- -. The transmitter was tested while in a continuous transmit mode.
- -. The EUT was tuned to a low, middle, and high channel in both the downlink and uplink directions.

### 5.4.3 Measurement Set-Up



### 5.4.5 Limit

-. The limit is calculated to be  $P(W) - \{43 dB + 10 log [P(W)]\} = -13 dBm$ .

Report No: BWS-09-RF-003 Page Number: 14 of 61 **FCC Test Report** Data of Issue: February 3, 2009



#### 5.4.6 Data

### Antenna terminal conducted spurious emission results

Carrier Band	Tuned Frequency(MHz)	Loss offset(dB)	Spurious emission measured (dBm)	Limit (dBm)	Margin (dB)
	1931.250	42.3	-19.606	-13	6.606
Downlink	1962.500	42.3	-19.480	-13	6.480
	1993.750	42.3	-19.590	-13	6.590
	1851.250	42.3	-19.320	-13	6.320
Uplink	1882.500	42.3	-20.342	-13	7.342
	1913.750	42.3	-19.680	-13	6.680

Supplement information:

- -. Carrier signal was modulated with CDMA, Power measurement : Peak power measured.
- -. For each tuned carrier frequency, the maximum spurious emission detected was recorded.

#### Two carrier Intermodulation

Carrier Band		Tuned Frequency(MHz)	Loss offset(dB)	Spurious emission measured (dBm)	Limit (dBm)	Margin (dB)
Downlink	Lower edge	1932.500	42.3	-29.32	-13	16.32
	Higher edge	1992.500	42.3	-29.21	-13	16.21
Uplink	Lower edge	1852.500	42.3	-40.42	-13	26.58
	Higher edge	1912.500	42.3	-44.15	-13	30.85

Supplement information:

- -. Carrier signal was modulated with CDMA, Power measurement : Peak power measured.
- -. For each tuned carrier frequency, the maximum spurious emission detected was recorded.

#### 5.4.7 Conclusion

The equipment **passed** the requirement of this clause. Also refer to 6.4 of the present test report for detailed.



# 5.5 Field Strength of Spurious Radiation

### 5.5.1 Specification

According to 47 CFR Part 2 section § 2.1053 and Part 24 section § 24.238, the power of any emissions outside the licensee's frequency bands of operation must be attenuated below the transmitter power (P in watts) by at least 43 +10 log (P) dB. Compliance with these rules is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater

#### 5.5.2 Method of Measurement


ANSI/TIA-603-C-2004 Section 2.2.12

The EUT, equipped with non-integral antenna, was connected to 50 Ohm match load. The EUT was controlled to transmit maximum power by a Console computer.

For transmitters other then single sideband, independent sideband and controlled carrier radiotelephone, the values of current and voltage on the circuit elements specified in section § 2.1033(c)(8). The EUT was connected to ancillary in order to simulate normal operating conditions with reference to the guidance given in the standard for this type equipment.

- Step (a): Measure the radiated maximum output power by the Test Receiver received from the Test Antenna.
- Step (b): Use substitution method to verify the maximum output power. The EUT was substituted by a dipole antenna. The dipole is connected to a Signal Generator. And then adjust the output level Of the Signal Generator to get the same received power recorded in step (b) on Test Receiver, and record the power level of Signal Generator. The cable loss at the test frequency should be compensated.

### 5.5.3 Measurement Set-Up





# 5.5.4 Limit

-.The limit is calculated to be P (W) -  $\{43 \text{ dB} + 10 \text{ log [P (W)]}\}\ = -13 \text{ dBm}.$ 

# 5.5.5 Data

Test frequency range	Measured maximum spurious emission levels (dBm)	Limit (dBm)
30 MHz to 10 <sup>th</sup>	20.002	. 12
harmonic included	-29.803	<-13

### 5.5.6 Conclusion

The equipment **passed** the requirement of this clause. Also refer to 6.6 of the present test report for detailed.



# 5.6 Frequency Stability

### 5.6.1 Specification

According to 47 CFR Part 2 section §2.1055 and Part 24 section §24.135, §24.235 the frequency stability shall be sufficient to ensure that the fundamental emission stay within the authorized bands of operation.

#### **5.6.2 Method of Measurement**


ANSI/TIA-603-C-2004 Section 2.2.2

The frequency stability shall be measured with variation of ambient temperature form -20  $^{\circ}$ C to +50  $^{\circ}$ C. Frequency measurements shall be made at the extremes of the specified temperature range and at intervals of not more than 10°C through the range. A period of time sufficient to stabilize all of the components of the oscillator circuit at each temperature level shall be allowed prior to frequency measurement.

The frequency stability shall be measured with variation of primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

The sample was permitted to stabilize at each step for at least one-half hour. Power was applied and the maximum frequency change was noted within one minute.

# 5.6.3 Measurement Set-Up



#### 5.6.5 Limit

The frequency tolerance is limited to ±2ppm.

Report No: BWS-09-RF-003 Page Number: 18 of 61 **FCC Test Report** Data of Issue: February 3, 2009



# 5.6.6 Data

TX frequency stability

Tank a	•	Measured maximum frequency error					
Test environment		Down Link 1962.5MHz		Up Link 1882.5MHz		Limit(ppm)	
Voltage (V)	Temperature (℃)	Hz	ppm	Hz	ppm		
	-20	0.0	0.0	0.0	0.0	<±2	
	-10	0.0	0.0	0.0	0.0	<±2	
	0	0.0	0.0	0.0	0.0	<±2	
100	10	0.0	0.0	0.0	0.0	<±2	
100	20	0.0	0.0	0.0	0.0	<±2	
	30	0.0	0.0	0.0	0.0	<±2	
	40	0.0	0.0	0.0	0.0	<±2	
	50	0.0	0.0	0.0	0.0	<±2	
85	20	0.0	0.0	0.0	0.0	<±2	
115	20	0.0	0.0	0.0	0.0	<±2	

# 5.6.7 Conclusion

The equipment **passed** the requirement of this clause. Also refer to 6.7 of the present test report for detailed.

Page Number: 19 of 61

Data of Issue:

February 3, 2009



# 6. TEST PLOT

# 6.1 Power Line Conducted Emission

# 6.1.1 Down Link / HOT


FCC Rules : Part 15 §15.107

Operating Path:
Test Mode:
Input Level:
System Gain:
Down Link
HOT
-62 dBm
105 dB

ystem Gain : 105 dB
Bandwidth : 8.75 MHz



RBW 9 kHz
MT 100 ms





# 6.1.2 Down Link / Neutral

FCC Rules : Part 15 §15.107


Operating Path : Down Link
Test Mode : Neutral

Input Level : -62 dBm
System Gain : 105 dB

Bandwidth: 8.25 MHz



RBW 9 kHz
MT 100 ms





# 6.1.3 Up Link / HOT

FCC Rules : Part 15 §15.107


Operating Path : Up Link
Test Mode : HOT

Input Level : -73 dBm System Gain : 100 dB

Bandwidth: 8.25 MHz

❄

RBW 9 kHz MT 100 ms



Date: 2.FEB.2009 01:38:53



# 6.1.4 Up Link / Neutral

FCC Rules : Part 15 §15.107


Operating Path : Up Link
Test Mode : Neutral

Input Level : -73 dBm
System Gain : 100 dB

Bandwidth: 8.25 MHz




RBW 9 kHz MT 100 ms





# 6.2 RF output power


# 6.2.1 Low frequency



Page Number : Data of Issue :




# 6.2.2 Mid Frequency



Page Number :
Data of Issue :



# 6.2.3 High frequency




# 6.2.4 Low frequency (7FA)

Data of Issue:


February 3, 2009





# 6.2.5 Mid Frequency (7FA)






# 6.2.6 High frequency (7FA)

Data of Issue:

February 3, 2009






# 6.3 Occupied Bandwidth




# 6.3.1 Low frequency




# 6.3.2 Mid Frequency





# 6.3.3 High frequency






# 6.4 Spurious Emissions at Antenna Terminals

# 6.4.1 Down link, Channel tuned :1931.25MHz





33 of 61


Page Number : Data of Issue :

February 3, 2009










Page Number : Data of Issue :


February 3, 2009







# 6.4.3 Down link, Channel tuned :1993.75MHz




Page Number : Data of Issue :








# 6.4.4 Up link, Channel tuned :1851.25MHz



39 of 61


Page Number : Data of Issue :







# 6.4.5 Up link, Channel tuned :1882.50MHz



Page Number: 41 of 61


Data of Issue:








# 6.4.6 Up link, Channel tuned :1913.75MHz



43 of 61


Page Number : Data of Issue :








### 6.4.7 Two Carrier Intermodulation Down link





### 6.4.8 Two Carrier Intermodulation Up link




Page Number:

Data of Issue:



#### Out of band Filter Rejection 6.5

#### 6.5.1 **Down link**




Page Number:

Data of Issue:



### 6.5.2 Up link




Page Number : Data of Issue :



# 6.6 Field Strength of Spurious Radiation

## 6.6.1 [1962.5MHz] Down Link




Page Number :
Data of Issue :

49 of 61

**FCC Test Report** 



#### 6.6.2 [1882.5MHz] Up Link




Page Number:

Data of Issue:




# 6.7 Frequency Stability

# 6.7.1 [MID Frequency: 1962.5MHz ] Down link



Data of Issue: February 3, 2009






Page Number: 52 of 61


Data of Issue: February 3, 2009






Page Number : Data of Issue :





Data of Issue:






6.7.2 [MID Frequency: 1882.5MHz ] Up link

 Report No: BWS-09-RF-003
 Page Number:
 55 of 61


 BWS TECH Inc.
 Data of Issue:
 February 3, 2009






Page Number : Data of Issue :





Page Number : Data of Issue :






58 of 61


Page Number : Data of Issue :





Page Number :
Data of Issue :





# 7. TEST EQUIPMENTS LIST

61 of 61

February 3, 2009



	EQUIPMENT	MODEL	MANUFACTURE	SERIAL NUMBER	Calibration Due date
1	Receiver	ESVS30	Rohde & Schwarz	832854/010	07/25/09
2	Spectrum analyzer	FSP7	Rohde & Schwarz	100001	10/30/09
4	Spectrum analyzer	N9020A	Agilent	US46220101	10/07/09
3	Signal Generator	E4432B	Agilent	US40053157	07/08/09
4	Signal Generator	N5182A	Agilent	MY46240037	10/02/09
5	Signal Generator	GT9000	Gigatronics	9604010	10/30/09
6	Frequency Counter	R5372	Advantest	41855204	10/29/09
7	Power Meter	E4418A	Agilent	GB38272621	10/29/09
8	Power Sensor	E9301B	Agilent	US40010238	10/29/09
9	Power supply	1001P	California Instrument	8137	N/A
10	Attenuator	RFA500NMF30	RES-NET	9522	10/30/09
11	50W Termination	6515.19.A	SUHNER	N/A	N/A
12	Shield Room (7m x 4m x 3m)	N/A	SJEMC	0003	N/A
13	Turn Table	OSC-30	N/A	BWS-01	N/A
14	Antenna Mast	JAC-3	Dail EMC	N/A	N/A
15	Temperature & Humidity chanber	EN-GLMP-3000	Enex	MY41018053	03/21/09
16	Bilog Antenna	VULB9160	Schwarzbeck	VULB9160-3122	01/24/10
17	Bilog Antenna	VULB9161	Schwarzbeck	VULB9161-4067	11/19/09
18	Bilog Antenna	VULB9161	Schwarzbeck	VULB9161-4068	12/11/09
19	Horn Antenna	BBHA 9120 D	Schwarzbeck	BBHA 9120 D 234	03/15/09
20	Horn Antenna	BBHA 9120 D	Schwarzbeck	BBHA 9120 D 517	12/18/10

Page Number:

Data of Issue: