



## **MET Laboratories, Inc.** Safety Certification - EMC - Telecom- Environmental Simulation

914 WEST PATAPSCO AVENUE • BALTIMORE, MARYLAND 21230 • PHONE (410) 354-3300 • FAX (410) 354-3313

33439 WESTERN AVENUE • UNION CITY, CALIFORNIA 94587 • PHONE (510) 489-6300 • FAX (510) 489-6372

3162 BELICK STREET • SANTA CLARA, CALIFORNIA 95054 • PHONE (408) 748-3585 • FAX (510) 489-6372

13301 MCCALLEN PASS • AUSTIN, TEXAS 78753 • PHONE (512) 287-2500 • FAX (512) 287-2513

March 22, 2012

Fortress Technologies, Inc.  
2 Technology Park Drive  
Westford, MA 01886

Dear John Pacheco,

Enclosed is the EMC Wireless report for the Fortress Technologies, Inc., Infrastructure Mesh Point ES440 (containing M5 Radio) as tested to the requirements of Title 47 of the CFR, FCC Part 15 Subpart C, and RSS-210, Issue 8, Dec. 2010 for Intentional Radiators.

Thank you for using the services of MET Laboratories, Inc. If you have any questions regarding these results or if MET can be of further service to you, please feel free to contact me.

Sincerely yours,  
MET LABORATORIES, INC.

Jill Valdes  
Documentation Department

Reference: (\Fortress Technologies, Inc.\EMC31152B-FCC247 Rev. 1)

Certificates and reports shall not be reproduced except in full, without the written permission of MET Laboratories, Inc.

---

## Electromagnetic Compatibility Criteria Test Report

For the:

**Fortress Technologies, Inc.  
Infrastructure Mesh Point ES440 (containing M5 Radio)**

Tested Under:  
**the FCC Certification Rules**  
contained in  
**15.247 Subpart C & RSS-210, Issue 8, Dec. 2010**  
for Intentional Radiators

**MET Report: EMC31152B-FCC247 Rev. 1**

March 22, 2012

Prepared For:  
**Fortress Technologies, Inc.  
2 Technology Park Drive  
Westford, MA 01886**


**Prepared By:**  
**MET Laboratories, Inc.**  
914 W. Patapsco Ave  
Baltimore, MD 21230

## Electromagnetic Compatibility Criteria Test Report

For the:

**Fortress Technologies, Inc.  
Infrastructure Mesh Point ES440 (containing M5 Radio)**

Tested Under:  
**the FCC Certification Rules**  
**contained in**  
**15.247 Subpart C & RSS-210, Issue 8, Dec. 2010**  
**for Intentional Radiators**



Dusmantha Tennakoon, Project Engineer  
Electromagnetic Compatibility Lab



Jill Valdes  
Documentation Department

**Engineering Statement:** The measurements shown in this report were made in accordance with the procedures indicated, and the emissions from this equipment were found to be within the limits applicable. I assume full responsibility for the accuracy and completeness of these measurements, and for the qualifications of all persons taking them. It is further stated that upon the basis of the measurements made, the equipment tested is capable of operation in accordance with the requirements of the FCC Rules Part 15.247 and Industry Canada standard RSS-210, Issue 8, Dec. 2010 under normal use and maintenance.



Shawn McMillen,  
Wireless Manager, Electromagnetic Compatibility Lab

## Report Status Sheet

Revision	Report Date	Reason for Revision
Ø	January 25, 2012	Initial Issue.
1	March 22, 2012	Revised to reflect editorial corrections.

## Table of Contents

<b>I.</b>	<b>Executive Summary .....</b>	<b>1</b>
	A. Purpose of Test .....	2
	B. Executive Summary .....	2
<b>II.</b>	<b>Equipment Configuration .....</b>	<b>3</b>
	A. Overview.....	4
	B. References.....	5
	C. Test Site .....	5
	D. Description of Test Sample .....	6
	E. Equipment Configuration.....	7
	F. Support Equipment .....	7
	G. Ports and Cabling Information.....	7
	H. Mode of Operation.....	7
	I. Modifications .....	7
	a) Modifications to EUT .....	7
	b) Modifications to Test Standard.....	7
	J. Disposition of EUT .....	7
<b>III.</b>	<b>Electromagnetic Compatibility Criteria for Intentional Radiators.....</b>	<b>8</b>
	§ 15.203 Antenna Requirement .....	9
	§ 15.247(a)(a) 6 dB and 99% Bandwidth .....	10
	§ 15.247(b) Peak Power Output .....	15
	§ 15.247(d) Radiated Spurious Emissions Requirements and Band Edge.....	19
	§ 15.247(d) RF Conducted Spurious Emissions Requirements and Band Edge.....	36
	§ 15.247(e) Peak Power Spectral Density .....	45
	RSS-GEN Receiver Spurious Emissions .....	48
<b>IV.</b>	<b>Test Equipment .....</b>	<b>52</b>
<b>V.</b>	<b>Certification &amp; User's Manual Information .....</b>	<b>54</b>
	A. Certification Information .....	55
	B. Label and User's Manual Information .....	59
<b>VI.</b>	<b>ICES-003 Procedural &amp; Labeling Requirements .....</b>	<b>61</b>

## List of Tables

Table 1. Executive Summary of EMC Part 15.247 Compliance Testing .....	2
Table 2. EUT Summary Table.....	4
Table 3. References .....	5
Table 4. Equipment Configuration .....	7
Table 5. Ports and Cabling Information .....	7
Table 6. Occupied Bandwidth, Test Results.....	10
Table 7. Output Power Requirements from §15.247(b) .....	15
Table 8. Peak Power Output, Test Results .....	16
Table 9. Restricted Bands of Operation.....	19
Table 10. Radiated Emissions Limits Calculated from FCC Part 15, § 15.209 (a) .....	20
Table 11. Peak Power Spectral Density, Test Results .....	45
Table 12. Spurious Emission Limits for Receivers .....	48
Table 13. Test Equipment List .....	53

## List of Plots

Plot 1. 6 dB Occupied Bandwidth, Low Channel, HT20 .....	11
Plot 2. 6 dB Occupied Bandwidth, Mid Channel, HT20 .....	11
Plot 3. 6 dB Occupied Bandwidth, High Channel, HT20 .....	11
Plot 4. 6 dB Occupied Bandwidth, Low Channel, HT40 .....	12
Plot 5. 6 dB Occupied Bandwidth, Low Channel, HT40 .....	12
Plot 6. 6 dB Occupied Bandwidth, High Channel, HT40 .....	12
Plot 7. 99% Occupied Bandwidth, Low Channel, HT20 .....	13
Plot 8. 99% Occupied Bandwidth, Mid Channel, HT20 .....	13
Plot 9. 99% Occupied Bandwidth, High Channel, HT20 .....	13
Plot 10. 99% Occupied Bandwidth, Low Channel, HT40 .....	14
Plot 11. 99% Occupied Bandwidth, Mid Channel, HT40 .....	14
Plot 12. 99% Occupied Bandwidth, High Channel, HT40 .....	14
Plot 13. Peak Power Output, Low Channel, HT20 .....	17
Plot 14. Peak Power Output, Mid Channel, HT20 .....	17
Plot 15. Peak Power Output, High Channel, HT20 .....	17
Plot 16. Peak Power Output, Low Channel, HT40 .....	18
Plot 17. Peak Power Output, Mid Channel, HT40 .....	18
Plot 18. Peak Power Output, High Channel, HT40 .....	18
Plot 19. Radiated Spurious Emissions, Low Channel, 30 MHz – 1 GHz, HT20 .....	21
Plot 20. Radiated Spurious Emissions, Low Channel, 1 GHz – 5.725 GHz, Average Detector, HT20 .....	21
Plot 21. Radiated Spurious Emissions, Low Channel, 1 GHz – 5.725 GHz, Peak, HT20 .....	21
Plot 22. Radiated Spurious Emissions, Low Channel, 5.850 GHz – 7 GHz, Average, HT20 .....	22
Plot 23. Radiated Spurious Emissions, Low Channel, 5.850 GHz – 7 GHz, Peak, HT20 .....	22
Plot 24. Radiated Spurious Emissions, Low Channel, 7 GHz – 18 GHz, Average, HT20 .....	22
Plot 25. Radiated Spurious Emissions, Low Channel, 7 GHz – 18 GHz, Peak, HT20 .....	23
Plot 26. Radiated Spurious Emissions, Mid Channel, 30 MHz – 1 GHz, HT20 .....	23
Plot 27. Radiated Spurious Emissions, Mid Channel, 1 GHz – 5.725 GHz, Average Detector, HT20 .....	23
Plot 28. Radiated Spurious Emissions, Mid Channel, 1 GHz – 5.725 GHz, Peak, HT20 .....	24
Plot 29. Radiated Spurious Emissions, Mid Channel, 5.850 GHz – 7 GHz, Average, HT20 .....	24
Plot 30. Radiated Spurious Emissions, Mid Channel, 5.850 GHz – 7 GHz, Peak, HT20 .....	24
Plot 31. Radiated Spurious Emissions, Mid Channel, 7 GHz – 18 GHz, Average, HT20 .....	25
Plot 32. Radiated Spurious Emissions, Mid Channel, 7 GHz – 18 GHz, Peak, HT20 .....	25
Plot 33. Radiated Spurious Emissions, High Channel, 30 MHz – 1 GHz, HT20 .....	25
Plot 34. Radiated Spurious Emissions, High Channel, 1 GHz – 5.725 GHz, Average Detector, HT20 .....	26
Plot 35. Radiated Spurious Emissions, High Channel, 1 GHz – 5.725 GHz, Peak, HT20 .....	26
Plot 36. Radiated Spurious Emissions, High Channel, 5.850 GHz – 7 GHz, Average, HT20 .....	26
Plot 37. Radiated Spurious Emissions, High Channel, 5.850 GHz – 7 GHz, Peak, HT20 .....	27
Plot 38. Radiated Spurious Emissions, High Channel, 7 GHz – 18 GHz, Average, HT20 .....	27
Plot 39. Radiated Spurious Emissions, High Channel, 7 GHz – 18 GHz, Peak, HT20 .....	27
Plot 40. Radiated Spurious Emissions, Low Channel, 30 MHz – 1 GHz, HT40 .....	28
Plot 41. Radiated Spurious Emissions, Low Channel, 1 GHz – 5.725 GHz, Average Detector, HT40 .....	28
Plot 42. Radiated Spurious Emissions, Low Channel, 1 GHz – 5.725 GHz, Peak, HT40 .....	28
Plot 43. Radiated Spurious Emissions, Low Channel, 5.850 GHz – 7 GHz, Average, HT40 .....	29
Plot 44. Radiated Spurious Emissions, Low Channel, 5.850 GHz – 7 GHz, Peak, HT40 .....	29
Plot 45. Radiated Spurious Emissions, Low Channel, 7 GHz – 18 GHz, Average, HT40 .....	29
Plot 46. Radiated Spurious Emissions, Low Channel, 7 GHz – 18 GHz, Peak, HT40 .....	30
Plot 47. Radiated Spurious Emissions, Mid Channel, 30 MHz – 1 GHz, HT40 .....	30
Plot 48. Radiated Spurious Emissions, Mid Channel, 1 GHz – 5.725 GHz, Average Detector, HT40 .....	30
Plot 49. Radiated Spurious Emissions, Mid Channel, 1 GHz – 5.725 GHz, Peak, HT40 .....	31
Plot 50. Radiated Spurious Emissions, Mid Channel, 5.850 GHz – 7 GHz, Average, HT40 .....	31

Plot 51. Radiated Spurious Emissions, Mid Channel, 5.850 GHz – 7 GHz, Peak, HT40 .....	31
Plot 52. Radiated Spurious Emissions, Mid Channel, 7 GHz – 18 GHz, Average, HT40 .....	32
Plot 53. Radiated Spurious Emissions, Mid Channel, 7 GHz – 18 GHz, Peak HT40 .....	32
Plot 54. Radiated Spurious Emissions, High Channel, 30 MHz – 1 GHz, HT40 .....	32
Plot 55. Radiated Spurious Emissions, High Channel, 1 GHz – 5.725 GHz, Average Detector, HT40.....	33
Plot 56. Radiated Spurious Emissions, High Channel, 1 GHz – 5.725 GHz, Peak, HT40.....	33
Plot 57. Radiated Spurious Emissions, High Channel, 5.850 GHz – 7 GHz, Average, HT40 .....	33
Plot 58. Radiated Spurious Emissions, High Channel, 5.850 GHz – 7 GHz, Peak, HT40.....	34
Plot 59. Radiated Spurious Emissions, High Channel, 7 GHz – 18 GHz, Average, HT40 .....	34
Plot 60. Radiated Spurious Emissions, High Channel, 7 GHz – 18 GHz, Peak, HT40.....	34
Plot 61. Conducted Spurious Emissions, Low Channel, 30 MHz – 1 GHz, HT20 .....	37
Plot 62. Conducted Spurious Emissions, Low Channel, 1 GHz – 18 GHz, HT20 .....	37
Plot 63. Conducted Spurious Emissions, Low Channel, 18 GHz – 40 GHz, HT20 .....	37
Plot 64. Conducted Spurious Emissions, Mid Channel, 30 MHz – 1 GHz, HT20 .....	38
Plot 65. Conducted Spurious Emissions, Mid Channel, 1 GHz – 18 GHz, HT20.....	38
Plot 66. Conducted Spurious Emissions, Mid Channel, 18 GHz – 40 GHz, HT20.....	38
Plot 67. Conducted Spurious Emissions, High Channel, 30 MHz – 1 GHz, HT20.....	39
Plot 68. Conducted Spurious Emissions, High Channel, 1 GHz – 18 GHz, HT20 .....	39
Plot 69. Conducted Spurious Emissions, High Channel, 18 GHz – 40 GHz, HT20.....	39
Plot 70. Conducted Spurious Emissions, Low Channel, 30 MHz – 1 GHz, HT40 .....	40
Plot 71. Conducted Spurious Emissions, Low Channel, 1 GHz – 18 GHz, HT40 .....	40
Plot 72. Conducted Spurious Emissions, Low Channel, 1 GHz – 40 GHz, HT40 .....	40
Plot 73. Conducted Spurious Emissions, Mid Channel, 30 MHz – 1 GHz, HT40 .....	41
Plot 74. Conducted Spurious Emissions, Mid Channel, 1 GHz – 18 GHz, HT40.....	41
Plot 75. Conducted Spurious Emissions, Mid Channel, 1 GHz – 40 GHz, HT40.....	41
Plot 76. Conducted Spurious Emissions, High Channel, 30 MHz – 1 GHz, HT40 .....	42
Plot 77. Conducted Spurious Emissions, High Channel, 1 GHz – 18 GHz, HT40 .....	42
Plot 78. Conducted Spurious Emissions, High Channel, 18 GHz – 40 GHz, HT40.....	42
Plot 79. Conducted Band Edge, Low Channel, HT20.....	43
Plot 80. Conducted Band Edge, High Channel, HT20 .....	43
Plot 81. Conducted Band Edge, Low Channel, HT40.....	44
Plot 82. Conducted Band Edge, Mid Channel, HT40.....	44
Plot 83. Conducted Band Edge, High Channel, HT40 .....	44
Plot 84. Peak Power Spectral Density, Low Channel, HT20 .....	46
Plot 85. Peak Power Spectral Density, Mid Channel, HT20 .....	46
Plot 86. Peak Power Spectral Density, High Channel, HT20.....	46
Plot 87. Peak Power Spectral Density, Low Channel, HT40 .....	47
Plot 88. Peak Power Spectral Density, Mid Channel, HT40 .....	47
Plot 89. Peak Power Spectral Density, High Channel, HT40 .....	47
Plot 90. Receiver Spurious Emission, 30 MHz – 1 GHz, HT20.....	49
Plot 91. Receiver Spurious Emission, 1 GHz – 6 GHz, HT20 .....	49
Plot 92. Receiver Spurious Emission, 6 GHz – 12 GHz, HT20 .....	50
Plot 93. Receiver Spurious Emission, 12 GHz – 18 GHz, HT20 .....	50
Plot 94. Receiver Spurious Emission, 30 MHz – 1 GHz, HT40.....	51
Plot 95. Receiver Spurious Emission, 1 GHz – 18 GHz, HT40 .....	51

## List of Figures

Figure 1. Block Diagram, Occupied Bandwidth Test Setup.....	10
Figure 2. Peak Power Output Test Setup.....	16
Figure 3. Block Diagram, Conducted Spurious Emissions Test Setup.....	36
Figure 4. Block Diagram, Peak Power Spectral Density Test Setup .....	45
Figure 5. Block Diagram, Conducted Receiver Spurious Emissions Test Setup .....	48

## List of Photographs

Photograph 1. Fortress Technologies, Inc. Infrastructure Mesh Point ES440 (containing M5 Radio).....	6
Photograph 2. Radiated Spurious Emissions, Test Setup .....	35

## List of Terms and Abbreviations

<b>AC</b>	Alternating Current
<b>ACF</b>	Antenna Correction Factor
<b>Cal</b>	Calibration
<i>d</i>	Measurement Distance
<b>dB</b>	Decibels
<b>dB<sub>μ</sub>A</b>	Decibels above one <b>microamp</b>
<b>dB<sub>μ</sub>V</b>	Decibels above one <b>microvolt</b>
<b>dB<sub>μ</sub>A/m</b>	Decibels above one <b>microamp per meter</b>
<b>dB<sub>μ</sub>V/m</b>	Decibels above one <b>microvolt per meter</b>
<b>DC</b>	Direct Current
<b>E</b>	Electric Field
<b>DSL</b>	Digital Subscriber Line
<b>ESD</b>	Electrostatic Discharge
<b>EUT</b>	Equipment Under Test
<i>f</i>	Frequency
<b>FCC</b>	Federal Communications Commission
<b>GRP</b>	Ground Reference Plane
<b>H</b>	Magnetic Field
<b>HCP</b>	Horizontal Coupling Plane
<b>Hz</b>	Hertz
<b>IEC</b>	International Electrotechnical Commission
<b>kHz</b>	kilohertz
<b>kPa</b>	kilopascal
<b>kV</b>	kilovolt
<b>LISN</b>	Line Impedance Stabilization Network
<b>MHz</b>	Megahertz
<b>μH</b>	<b>microhenry</b>
<b>μ</b>	<b>microfarad</b>
<b>μs</b>	<b>microseconds</b>
<b>NEBS</b>	Network Equipment-Building System
<b>PRF</b>	Pulse Repetition Frequency
<b>RF</b>	Radio Frequency
<b>RMS</b>	Root-Mean-Square
<b>TWT</b>	Traveling Wave Tube
<b>V/m</b>	<b>Volts per meter</b>
<b>VCP</b>	Vertical Coupling Plane

# I. Executive Summary



Fortress Technologies, Inc.

Infrastructure Mesh Point ES440 (containing M5 Radio)

Electromagnetic Compatibility

Executive Summary

CFR Title 47, 15.247; RSS-210, Issue 8, Dec. 2010

## A. Purpose of Test

An EMC evaluation was performed to determine compliance of the Fortress Technologies, Inc. Infrastructure Mesh Point ES440 (containing M5 Radio), with the requirements of Part 15, §15.247. All references are to the most current version of Title 47 of the Code of Federal Regulations in effect. In accordance with §2.1033, the following data is presented in support of the Certification of the Infrastructure Mesh Point ES440 (containing M5 Radio). Fortress Technologies, Inc. should retain a copy of this document which should be kept on file for at least two years after the manufacturing of the Infrastructure Mesh Point ES440 (containing M5 Radio), has been **permanently** discontinued.

## B. Executive Summary

The following tests were conducted on a sample of the equipment for the purpose of demonstrating compliance with Part 15, §15.247, in accordance with Fortress Technologies, Inc., purchase order number 3018. All tests were conducted using measurement procedure ANSI C63.4-2003.

FCC Reference 47 CFR Part 15.247:2005	IC Reference RSS-210 Issue 8: 2010; RSS-GEN Issue 3: 2010	Description	Compliance
Title 47 of the CFR, Part 15 §15.203	N/A	Antenna Requirement	Compliant
Title 47 of the CFR, Part 15 §15.207(a)	RSS-GEN (7.2.4)	Conducted Emission Limits	N/A – Class II PC
Title 47 of the CFR, Part 15 §15.247(a)(2)	RSS-Gen(4.6)	6dB Occupied Bandwidth	Compliant
		99% Occupied Bandwidth	Compliant
Title 47 of the CFR, Part 15 §15.247(b)	RSS-210(A8.4)	Peak Power Output	Compliant
Title 47 of the CFR, Part 15 §15.247(d); §15.209; §15.205	RSS-210(A8.5)	Radiated Spurious Emissions Requirements	Compliant
Title 47 of the CFR, Part 15 §15.247(d)	RSS-210(A8.5)	RF Conducted Spurious Emissions Requirements	Compliant
Title 47 of the CFR, Part 15 §15.247(d)	RSS-210(A8.5)	RF Conducted Band Edge	Compliant
Title 47 of the CFR, Part 15; §15.247(e)	RSS-210(A8.2)	Peak Power Spectral Density	Compliant
Title 47 of the CFR, Part 15 §15.247(i)	RSS-Gen(5.6)	Maximum Permissible Exposure (MPE)	N/A – Class II PC
N/A	RSS-Gen(4.10)	Receiver Spurious Emissions	Compliant

Table 1. Executive Summary of EMC Part 15.247 Compliance Testing

## II. Equipment Configuration



Fortress Technologies, Inc.

Infrastructure Mesh Point ES440 (containing M5 Radio)

Electromagnetic Compatibility  
Equipment Configuration

CFR Title 47, 15.247; RSS-210, Issue 8, Dec. 2010

## A. Overview

MET Laboratories, Inc. was contracted by Fortress Technologies, Inc. to perform testing on the Infrastructure Mesh Point ES440 (containing M5 Radio), under Fortress Technologies, Inc.'s purchase order number 3018.

This document describes the test setups, test methods, required test equipment, and the test limit criteria used to perform compliance testing of the Fortress Technologies, Inc., Infrastructure Mesh Point ES440 (containing M5 Radio).

The results obtained relate only to the item(s) tested.

<b>Model(s) Tested:</b>	Infrastructure Mesh Point ES440 (containing M5 Radio)	
<b>Model(s) Covered:</b>	Infrastructure Mesh Point ES440 (containing M5 Radio)	
<b>Filing Info:</b>	Class II change to add HT20 and HT40 modes	
<b>EUT Specifications:</b>	Primary Power: 120 VAC, 60 Hz	
	FCC ID: WYK-ES440	
	IC: 8190A-ES440	
	Type of Modulations:	OFDM
	Equipment Code:	DTS
	Peak RF Output Power:	HT20 383.7 mW HT40 375.80 mW
	EUT Frequency Ranges:	HT20 5745 – 5825 MHz HT40 5755 – 5795 MHz
<b>Analysis:</b>	The results obtained relate only to the item(s) tested.	
<b>Environmental Test Conditions:</b>	Temperature: 15-35° C	
	Relative Humidity: 30-60%	
	Barometric Pressure: 860-1060 mbar	
<b>Evaluated by:</b>	Dusmantha Tennakoon	
<b>Report Date(s):</b>	March 22, 2012	

**Table 2. EUT Summary Table**

## B. References

<b>CFR 47, Part 15, Subpart C</b>	Federal Communication Commission, Code of Federal Regulations, Title 47, Part 15: General Rules and Regulations, Allocation, Assignment, and Use of Radio Frequencies
<b>RSS-210, Issue 8, Dec. 2010</b>	Low-power Licence-exempt Radiocommunications Devices (All Frequency Bands): Category I Equipment
<b>RSS-GEN, Issue 3, Dec. 2010</b>	General Requirements and Information for the Certification of Radio Apparatus
<b>ANSI C63.4:2003</b>	Methods and Measurements of Radio-Noise Emissions from Low-Voltage Electrical And Electronic Equipment in the Range of 9 kHz to 40 GHz
<b>ANSI/NCSL Z540-1-1994</b>	Calibration Laboratories and Measuring and Test Equipment - General Requirements
<b>ANSI/ISO/IEC 17025:2000</b>	General Requirements for the Competence of Testing and Calibration Laboratories
<b>ANSI C63.10-2009</b>	American National Standard for Testing Unlicensed Wireless Devices

**Table 3. References**

## C. Test Site

All testing was performed at MET Laboratories, Inc., 914 W. Patapsco Ave., Baltimore, MD 21230. All equipment used in making physical determinations is accurate and bears recent traceability to the National Institute of Standards and Technology.

Radiated Emissions measurements were performed in a 3 meter semi-anechoic chamber (equivalent to an Open Area Test Site). In accordance with §2.948(a)(3), a complete site description is contained at MET Laboratories.

## D. Description of Test Sample

The Fortress Technologies Infrastructure Mesh Point ES440 (containing M25 Radio), Equipment Under Test (EUT), is a dual radio access point/bridge. It embeds two COTS high power radios and two Ethernet ports in a ruggedized enclosure. The radio operates in accordance to the 802.11a, 802.11b, 802.11g and 802.11n standards. This test report addresses the 802.11n mode (i.e. HT20 and HT40).

The ES440 is intended to provided outdoor mobile connectivity in a secure manner both wired and wirelessly.



Photograph 1. Fortress Technologies, Inc. Infrastructure Mesh Point ES440 (containing M5 Radio)

## E. Equipment Configuration

All cards, racks, etc., incorporated as part of the EUT is included in the following list.

Ref. ID	Name / Description	Model Number	Serial Number
1	Fortress Infrastructure Mesh Point	ES440	110310076

**Table 4. Equipment Configuration**

## F. Support Equipment

Support equipment was not necessary for the operation and testing of the Infrastructure Mesh Point ES440 (containing M5 Radio).

## G. Ports and Cabling Information

Ref. ID	Port Name on EUT	Cable Description	Qty.	Termination Point
N/A	Ant (1 & 2)	Antenna	2	Spectrum Analyzer
N/A	AC Power Port	Provides power	1	External AC Charger

**Table 5. Ports and Cabling Information**

## H. Mode of Operation

HT20 and HT40 modes may be configured using the UI of the product. Additionally, these modes may be configured using the UI of the product. Additionally, these modes may be entered by using ART, the Atheros Radio Test tool. This is a standard tool provided by Atheros for directly manipulating and configuring their chips during testing and manufacturing.

## I. Modifications

### a) Modifications to EUT

No modifications were made to the EUT.

### b) Modifications to Test Standard

No modifications were made to the test standard.

## J. Disposition of EUT

The test sample including all support equipment submitted to the Electro-Magnetic Compatibility Lab for testing was returned to Fortress Technologies, Inc. upon completion of testing.



Fortress Technologies, Inc.

Infrastructure Mesh Point ES440 (containing M5 Radio)

Electromagnetic Compatibility  
Intentional Radiators  
CFR Title 47, 15.247; RSS-210, Issue 8, Dec. 2010

### III. Electromagnetic Compatibility Criteria for Intentional Radiators

## Electromagnetic Compatibility Criteria for Intentional Radiators

### § 15.203 Antenna Requirement

**Test Requirement:**

**§ 15.203:** An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

The structure and application of the EUT were analyzed to determine compliance with Section 15.203 of the Rules. Section 15.203 states that the subject device must meet at least one of the following criteria:

- a.) Antenna must be permanently attached to the unit.
- b.) Antenna must use a unique type of connector to attach to the EUT.
- c.) Unit must be professionally installed. Installer shall be responsible for verifying that the correct antenna is employed with the unit.

**Results:**

The EUT as tested is compliant the criteria of §15.203. The EUT uses a 9 dBi Omni antenna for the 5.8 GHz band. The antenna is professionally installed.

**Test Engineer(s):** Dusmantha Tennakoon

**Test Date(s):** 05/12/11

## Electromagnetic Compatibility Criteria for Intentional Radiators

### § 15.247(a)(2) 6 dB and 99% Bandwidth

**Test Requirements:** § 15.247(a)(2): Operation under the provisions of this section is limited to frequency hopping and digitally modulated intentional radiators that comply with the following provisions:

For systems using digital modulation techniques, the EUT may operate in the 902-928 MHz, 2400-2483.5 MHz and 5725-5850 MHz bands. The minimum 6dB bandwidth shall be at least 500 kHz.


**Test Procedure:** The transmitter was on and transmitting at the highest output power. The bandwidth of the fundamental frequency was measured with the spectrum analyzer using a RBW approximately 1% of the total emission bandwidth,  $VBW > RBW$ . The 6 dB Bandwidth was measured and recorded. The measurements were performed on the low, mid and high channels.

**Test Results** The EUT was compliant with § 15.247 (a)(2).

The 6 dB and 99% Bandwidth was determined from the plots on the following pages.

**Test Engineer(s):** Dusmantha Tennakoon

**Test Date(s):** 05/12/11



**Figure 1. Block Diagram, Occupied Bandwidth Test Setup**

### Occupied Bandwidth Test Results

Mode	Channel	6 dB Bandwidth (MHz)	99 % Bandwidth (MHz)
HT20	5745	17.502	17.4430
	5785	17.716	17.7904
	5825	17.659	17.8149
HT40	5755	36.260	36.7297
	5795	36.658	36.8619

**Table 6. Occupied Bandwidth, Test Results**



Fortress Technologies, Inc.


Infrastructure Mesh Point ES440 (containing M5 Radio)

Electromagnetic Compatibility


Intentional Radiators

CFR Title 47, 15.247; RSS-210, Issue 8, Dec. 2010


## 6 dB Occupied Bandwidth Test Results, HT20



Plot 1. 6 dB Occupied Bandwidth, Low Channel, HT20



Plot 2. 6 dB Occupied Bandwidth, Mid Channel, HT20



Plot 3. 6 dB Occupied Bandwidth, High Channel, HT20



Fortress Technologies, Inc.


Infrastructure Mesh Point ES440 (containing M5 Radio)

Electromagnetic Compatibility


Intentional Radiators

CFR Title 47, 15.247; RSS-210, Issue 8, Dec. 2010


## 6 dB Occupied Bandwidth Test Results, HT40



Plot 4. 6 dB Occupied Bandwidth, Low Channel, HT40



Plot 5. 6 dB Occupied Bandwidth, Low Channel, HT40



Plot 6. 6 dB Occupied Bandwidth, High Channel, HT40



Fortress Technologies, Inc.


Infrastructure Mesh Point ES440 (containing M5 Radio)

Electromagnetic Compatibility


Intentional Radiators

CFR Title 47, 15.247; RSS-210, Issue 8, Dec. 2010


## 99% Occupied Bandwidth Test Results, HT20



Plot 7. 99% Occupied Bandwidth, Low Channel, HT20



Plot 8. 99% Occupied Bandwidth, Mid Channel, HT20



Plot 9. 99% Occupied Bandwidth, High Channel, HT20



Fortress Technologies, Inc.


Infrastructure Mesh Point ES440 (containing M5 Radio)

Electromagnetic Compatibility


Intentional Radiators

CFR Title 47, 15.247; RSS-210, Issue 8, Dec. 2010


## 99% Occupied Bandwidth Test Results, HT40



Plot 10. 99% Occupied Bandwidth, Low Channel, HT40



Plot 11. 99% Occupied Bandwidth, Mid Channel, HT40



Plot 12. 99% Occupied Bandwidth, High Channel, HT40

## Electromagnetic Compatibility Criteria for Intentional Radiators

### § 15.247(b) Peak Power Output

**Test Requirements:** **§15.247(b):** The maximum peak output power of the intentional radiator shall not exceed the following:

Digital Transmission Systems (MHz)	Output Limit (Watts)
902-928	1.000
2400-2483.5	1.000
5725- 5850	1.000

**Table 7. Output Power Requirements from §15.247(b)**

**§15.247(c):** if transmitting antennas of directional gain greater than 6 dBi are used the peak output power from the intentional radiator shall be reduced below the stated values in the Table 7, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Systems operating in the 2400 – 2483.5 MHz band and using a point to point application may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

Systems operating in the 5725 – 5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter peak output power.


Fixed, point-to-point operation excludes the use of point-to-multipoint systems, Omni-directional applications, and multiple co-located intentional radiators transmitting the same information. The operator of the spread spectrum intentional radiator or, if the equipment is professionally installed, the installer is responsible for ensuring that the system is used exclusively for fixed, point-to-point operations. The instruction manual furnished with the intentional radiator shall contain language in the installation instructions informing the operator and the installer of this responsibility.

**Test Procedure:** The transmitter was connected to a calibrated spectrum analyzer. The EUT was measured at the low, mid and high channels of each band at the maximum power level.

**Test Results:** The EUT was compliant with the Peak Power Output limits of §15.247(b) and is lower than the originally granted values.

**Test Engineer(s):** Dusmantha Tennakoon

**Test Date(s):** 05/12/11



**Figure 2. Peak Power Output Test Setup**

### Peak Power Output Test Results


Mode	Channel	Conducted Power (dBm)	Conducted Power (mW)
HT20	5745	25.33	341.20
	5785	25.49	354.00
	5825	25.84	383.70
HT40	5755	25.75	375.80
	5795	25.74	375.00

**Table 8. Peak Power Output, Test Results**


## Peak Power Output Test Results, HT20



**Plot 13. Peak Power Output, Low Channel, HT20**




**Plot 14. Peak Power Output, Mid Channel, HT20**




**Plot 15. Peak Power Output, High Channel, HT20**


## Peak Power Output Test Results, 2.4 GHz, HT40



**Plot 16. Peak Power Output, Low Channel, HT40**



**Plot 17. Peak Power Output, Mid Channel, HT40**



**Plot 18. Peak Power Output, High Channel, HT40**



Fortress Technologies, Inc.

Infrastructure Mesh Point ES440 (containing M5 Radio)

Electromagnetic Compatibility

Intentional Radiators

CFR Title 47, 15.247; RSS-210, Issue 8, Dec. 2010

## Electromagnetic Compatibility Criteria for Intentional Radiators

### § 15.247(d) Radiated Spurious Emissions Requirements and Band Edge

**Test Requirements:** §15.247(d); §15.205: Emissions outside the frequency band.

**§15.247(d):** In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a).

**§15.205(a):** Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090–0.110-----	16.42–16.423	399.9–410	4.5–5.15
<sup>1</sup> 0.495–0.505-----	16.69475–16.69525	608–614	5.35–5.46
2.1735–2.1905-----	16.80425–16.80475	960–1240	7.25–7.75
4.125–4.128-----	25.5–25.67	1300–1427	8.025–8.5
4.17725–4.17775-----	37.5–38.25	1435–1626.5	9.0–9.2
4.20725–4.20775-----	73–74.6	1645.5–1646.5	9.3–9.5
6.215–6.218-----	74.8–75.2	1660–1710	10.6–12.7
6.26775–6.26825-----	108–121.94	1718.8–1722.2	13.25–13.4
6.31175–6.31225-----	123–138	2200–2300	14.47–14.5
8.291–8.294-----	149.9–150.05	2310–2390	15.35–16.2
8.362–8.366-----	156.52475–156.52525	2483.5–2500	17.7–21.4
8.37625–8.38675-----	156.7–156.9	2655–2900	22.01–23.12
8.41425–8.41475-----	162.0125–167.17	3260–3267	23.6–24.0
12.29–12.293-----	167.72–173.2	3332–3339	31.2–31.8
12.51975–12.52025-----	240–285	3345.8–3358.36.	43–36.5
12.57675–12.57725-----	322–335.4	3600–4400	( <sup>2</sup> )

**Table 9. Restricted Bands of Operation**

<sup>1</sup> Until February 1, 1999, this restricted band shall be 0.490 – 0.510 MHz.

<sup>2</sup> Above 38.6

**Test Requirement(s):** **§ 15.209 (a):** Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in Table 10.

Frequency (MHz)	§ 15.209(a), Radiated Emission Limits (dB $\mu$ V) @ 3m
30 - 88	40.00
88 - 216	43.50
216 - 960	46.00
Above 960	54.00

**Table 10. Radiated Emissions Limits Calculated from FCC Part 15, § 15.209 (a)**


**Test Procedures:** The transmitter was turned on. Measurements were performed of the low, mid and high Channels. The EUT was rotated orthogonally through all three axes. Plots shown are corrected for both antenna correction factor and distance and compared to a 3 m limit line. Only noise floor was measured above 18 GHz.

**Test Results:** The EUT was compliant with the Radiated Spurious Emission limits of **§ 15.247(d)**.


**Test Engineer(s):** Dusmantha Tennakoon

**Test Date(s):** 05/13/11


## Radiated Spurious Emissions Test Results, HT20



Plot 19. Radiated Spurious Emissions, Low Channel, 30 MHz – 1 GHz, HT20




Plot 20. Radiated Spurious Emissions, Low Channel, 1 GHz – 5.725 GHz, Average Detector, HT20




Plot 21. Radiated Spurious Emissions, Low Channel, 1 GHz – 5.725 GHz, Peak, HT20




Plot 22. Radiated Spurious Emissions, Low Channel, 5.850 GHz – 7 GHz, Average, HT20




Plot 23. Radiated Spurious Emissions, Low Channel, 5.850 GHz – 7 GHz, Peak, HT20




Plot 24. Radiated Spurious Emissions, Low Channel, 7 GHz – 18 GHz, Average, HT20




Plot 25. Radiated Spurious Emissions, Low Channel, 7 GHz – 18 GHz, Peak, HT20




Plot 26. Radiated Spurious Emissions, Mid Channel, 30 MHz – 1 GHz, HT20




Plot 27. Radiated Spurious Emissions, Mid Channel, 1 GHz – 5.725 GHz, Average Detector, HT20




Plot 28. Radiated Spurious Emissions, Mid Channel, 1 GHz – 5.725 GHz, Peak, HT20




Plot 29. Radiated Spurious Emissions, Mid Channel, 5.850 GHz – 7 GHz, Average, HT20




Plot 30. Radiated Spurious Emissions, Mid Channel, 5.850 GHz – 7 GHz, Peak, HT20




Plot 31. Radiated Spurious Emissions, Mid Channel, 7 GHz – 18 GHz, Average, HT20




Plot 32. Radiated Spurious Emissions, Mid Channel, 7 GHz – 18 GHz, Peak, HT20




Plot 33. Radiated Spurious Emissions, High Channel, 30 MHz – 1 GHz, HT20




**Plot 34. Radiated Spurious Emissions, High Channel, 1 GHz – 5.725 GHz, Average Detector, HT20**



**Plot 35. Radiated Spurious Emissions, High Channel, 1 GHz – 5.725 GHz, Peak, HT20**




**Plot 36. Radiated Spurious Emissions, High Channel, 5.850 GHz – 7 GHz, Average, HT20**



Plot 37. Radiated Spurious Emissions, High Channel, 5.850 GHz – 7 GHz, Peak, HT20




Plot 38. Radiated Spurious Emissions, High Channel, 7 GHz – 18 GHz, Average, HT20




Plot 39. Radiated Spurious Emissions, High Channel, 7 GHz – 18 GHz, Peak, HT20


## Radiated Spurious Emissions Test Results, HT40




Plot 40. Radiated Spurious Emissions, Low Channel, 30 MHz – 1 GHz, HT40




Plot 41. Radiated Spurious Emissions, Low Channel, 1 GHz – 5.725 GHz, Average Detector, HT40



Plot 42. Radiated Spurious Emissions, Low Channel, 1 GHz – 5.725 GHz, Peak, HT40




Plot 43. Radiated Spurious Emissions, Low Channel, 5.850 GHz – 7 GHz, Average, HT40




Plot 44. Radiated Spurious Emissions, Low Channel, 5.850 GHz – 7 GHz, Peak, HT40




Plot 45. Radiated Spurious Emissions, Low Channel, 7 GHz – 18 GHz, Average, HT40




Plot 46. Radiated Spurious Emissions, Low Channel, 7 GHz – 18 GHz, Peak, HT40




Plot 47. Radiated Spurious Emissions, Mid Channel, 30 MHz – 1 GHz, HT40




Plot 48. Radiated Spurious Emissions, Mid Channel, 1 GHz – 5.725 GHz, Average Detector, HT40




Plot 49. Radiated Spurious Emissions, Mid Channel, 1 GHz – 5.725 GHz, Peak, HT40




Plot 50. Radiated Spurious Emissions, Mid Channel, 5.850 GHz – 7 GHz, Average, HT40




Plot 51. Radiated Spurious Emissions, Mid Channel, 5.850 GHz – 7 GHz, Peak, HT40




Plot 52. Radiated Spurious Emissions, Mid Channel, 7 GHz – 18 GHz, Average, HT40




Plot 53. Radiated Spurious Emissions, Mid Channel, 7 GHz – 18 GHz, Peak HT40




Plot 54. Radiated Spurious Emissions, High Channel, 30 MHz – 1 GHz, HT40




**Plot 55. Radiated Spurious Emissions, High Channel, 1 GHz – 5.725 GHz, Average Detector, HT40**




**Plot 56. Radiated Spurious Emissions, High Channel, 1 GHz – 5.725 GHz, Peak, HT40**




**Plot 57. Radiated Spurious Emissions, High Channel, 5.850 GHz – 7 GHz, Average, HT40**



Plot 58. Radiated Spurious Emissions, High Channel, 5.850 GHz – 7 GHz, Peak, HT40




Plot 59. Radiated Spurious Emissions, High Channel, 7 GHz – 18 GHz, Average, HT40



Plot 60. Radiated Spurious Emissions, High Channel, 7 GHz – 18 GHz, Peak, HT40

## Radiated Spurious Emissions Test Setup



Photograph 2. Radiated Spurious Emissions, Test Setup

## Electromagnetic Compatibility Criteria for Intentional Radiators

### § 15.247(d) RF Conducted Spurious Emissions Requirements and Band Edge

**Test Requirement:**

**15.247(d)** In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

**Test Procedure:**


For intentional radiators with a digital device portion which operates below 10 GHz, the spectrum was investigated as per §15.33(a)(1) and §15.33(a)(4); i.e., the lowest RF signal generated or used in the device up to the 10<sup>th</sup> harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

See following pages for detailed test results with RF Conducted Spurious Emissions.

**Test Results:** The EUT was compliant with the Conducted Spurious Emission limits of **§15.247(d)**.


**Test Engineer(s):** Jeff Pratt

**Test Date(s):** 04/11/11



**Figure 3. Block Diagram, Conducted Spurious Emissions Test Setup**

## Conducted Spurious Emissions Test Results, HT20




Plot 61. Conducted Spurious Emissions, Low Channel, 30 MHz – 1 GHz, HT20




Plot 62. Conducted Spurious Emissions, Low Channel, 1 GHz – 18 GHz, HT20



Plot 63. Conducted Spurious Emissions, Low Channel, 18 GHz – 40 GHz, HT20




**Plot 64. Conducted Spurious Emissions, Mid Channel, 30 MHz – 1 GHz, HT20**




**Plot 65. Conducted Spurious Emissions, Mid Channel, 1 GHz – 18 GHz, HT20**



**Plot 66. Conducted Spurious Emissions, Mid Channel, 18 GHz – 40 GHz, HT20**



Plot 67. Conducted Spurious Emissions, High Channel, 30 MHz – 1 GHz, HT20




Plot 68. Conducted Spurious Emissions, High Channel, 1 GHz – 18 GHz, HT20




Plot 69. Conducted Spurious Emissions, High Channel, 18 GHz – 40 GHz, HT20


## Conducted Spurious Emissions Test Results, HT40




Plot 70. Conducted Spurious Emissions, Low Channel, 30 MHz – 1 GHz, HT40




Plot 71. Conducted Spurious Emissions, Low Channel, 1 GHz – 18 GHz, HT40



Plot 72. Conducted Spurious Emissions, Low Channel, 1 GHz – 40 GHz, HT40




Plot 73. Conducted Spurious Emissions, Mid Channel, 30 MHz – 1 GHz, HT40




Plot 74. Conducted Spurious Emissions, Mid Channel, 1 GHz – 18 GHz, HT40




Plot 75. Conducted Spurious Emissions, Mid Channel, 1 GHz – 40 GHz, HT40



Plot 76. Conducted Spurious Emissions, High Channel, 30 MHz – 1 GHz, HT40



Plot 77. Conducted Spurious Emissions, High Channel, 1 GHz – 18 GHz, HT40




Plot 78. Conducted Spurious Emissions, High Channel, 18 GHz – 40 GHz, HT40




## Conducted Band Edge Test Results



Plot 79. Conducted Band Edge, Low Channel, HT20



Plot 80. Conducted Band Edge, High Channel, HT20


**Plot 81. Conducted Band Edge, Low Channel, HT40**

**Plot 82. Conducted Band Edge, Mid Channel, HT40**

**Plot 83. Conducted Band Edge, High Channel, HT40**

## Electromagnetic Compatibility Criteria for Intentional Radiators

### § 15.247(e) Peak Power Spectral Density

**Test Requirements:** **§15.247(e):** For digitally modulated systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.


**Test Procedure:** The transmitter was connected directly to a Spectrum Analyzer through an attenuator. The power level was set to the maximum level throughout each of the 100 sweeps of power averaging. The RBW was set to 3 kHz and a VBW set to 9 kHz or greater. The spectrum analyzer was set to an auto sweep time and a peak detector was used. Measurements were carried out at the low, mid and high channels.

**Test Results:** The EUT was compliant with the peak power spectral density limits of **§ 15.247 (e)**.

The peak power spectral density was determined from plots on the following page(s).

**Test Engineer:** Dusmantha Tennakoon

**Test Date:** 05/12/11




**Figure 4. Block Diagram, Peak Power Spectral Density Test Setup**


Mode	Channel (MHz)	Spectral Density (dBm/MHz)
HT20	5745	0.634
	5785	-4.322
	5825	-1.621
HT40	5755	-4.725
	5795	-8.894

**Table 11. Peak Power Spectral Density, Test Results**


## Peak Power Spectral Density, HT20



Plot 84. Peak Power Spectral Density, Low Channel, HT20




Plot 85. Peak Power Spectral Density, Mid Channel, HT20




Plot 86. Peak Power Spectral Density, High Channel, HT20


## Peak Power Spectral Density, HT40



**Plot 87. Peak Power Spectral Density, Low Channel, HT40**



**Plot 88. Peak Power Spectral Density, Mid Channel, HT40**



**Plot 89. Peak Power Spectral Density, High Channel, HT40**

## Electromagnetic Compatibility Criteria for Intentional Radiators

### RSS-GEN    Receiver Spurious Emissions Requirements

**Test Requirements:** The following receiver spurious emission limits shall be complied with:

(a) If a radiated measurement is made, all spurious emissions shall comply with the limits of Table 12.

Spurious Frequency (MHz)	Field Strength (microvolt/m at 3 meters)
30 – 88	100
88 – 216	150
216 – 960	200
Above 960	500

**Table 12. Spurious Emission Limits for Receivers**


(b) If a conducted measurement is made, no spurious output signals appearing at the antenna terminals shall exceed 2 nanowatts per any 4 kHz spurious frequency in the band 30-1000 MHz, or 5 nanowatts above 1 GHz.

**Test Procedures:** The EUT was programmed for receive mode only. Conducted measurements were taken at the antenna port of the EUT.

**Test Results:** Equipment is compliant with the Receiver Spurious Emissions Requirements of RSS-GEN.


**Test Engineer(s):** Dusmantha Tennakoon

**Test Date(s):** 05/12/11




**Figure 5. Block Diagram, Conducted Receiver Spurious Emissions Test Setup**


## Conducted Receiver Spurious Emissions, HT20




Plot 90. Receiver Spurious Emission, 30 MHz – 1 GHz, HT20



Plot 91. Receiver Spurious Emission, 1 GHz – 6 GHz, HT20




Plot 92. Receiver Spurious Emission, 6 GHz – 12 GHz, HT20




Plot 93. Receiver Spurious Emission, 12 GHz – 18 GHz, HT20

## Conducted Receiver Spurious Emissions, HT40



Plot 94. Receiver Spurious Emission, 30 MHz – 1 GHz, HT40



Plot 95. Receiver Spurious Emission, 1 GHz – 18 GHz, HT40

## IV. Test Equipment

## Test Equipment

Calibrated test equipment utilized during testing was maintained in a current state of calibration per the requirements of ANSI/NCSL Z540-1-1994 and ANSI/ISO/IEC 17025:2000.

MET Asset #	Equipment	Manufacturer	Model	Last Cal Date	Cal Due Date
1T4300	SEMI-ANECHOIC CHAMBER # 1	EMC TEST SYSTEMS	NONE	08/23/2010	08/23/2011
1T4612	ESA-E SERIES SPECTRUM ANALYZER	AGILENT	E4407B	09/27/2010	09/27/2011
1T4681	SPECTRUM ANALYZER	AGILENT	E4448A	1/27/2011	1/27/2012
1T2665	HORN ANTENNA	EMCO	3115	07/15/2010	07/15/2011
1T4409	EMI RECEIVER	ROHDE & SCHWARZ	ESIB7	05/25/2010	05/25/2011
1T4354	SIGNAL GENERATOR	HEWLETT PACKARD	83752A	03/11/2010	03/11/2011
1T4737	HIGH FREQUENCY PREAMP	MITEQ	AFS42-01001800	SEE NOTE	
1T4592	RF FILTER KIT	VARIOUS	N/A	SEE NOTE	

**Table 13. Test Equipment List**

Note: Functionally tested equipment is verified using calibrated instrumentation at the time of testing.



Fortress Technologies, Inc.

Infrastructure Mesh Point ES440 (containing M5 Radio)

Electromagnetic Compatibility

End of Report

CFR Title 47, 15.247; RSS-210, Issue 8, Dec. 2010

## V. Certification & User's Manual Information

## Certification & User's Manual Information

### A. Certification Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 2, Subpart I — Marketing of Radio frequency devices:

#### **§ 2.801 Radio-frequency device defined.**

As used in this part, a radio-frequency device is any device which in its operation is capable of Emitting radio-frequency energy by radiation, conduction, or other means. Radio- frequency devices include, but are not limited to:

- (a) The various types of radio communication transmitting devices described throughout this chapter.
- (b) *The incidental, unintentional and intentional radiators defined in Part 15 of this chapter.*
- (c) The industrial, scientific, and medical equipment described in Part 18 of this chapter.
- (d) Any part or component thereof which in use emits radio-frequency energy by radiation, conduction, or other means.

#### **§ 2.803 Marketing of radio frequency devices prior to equipment authorization.**

- (a) Except as provided elsewhere in this chapter, no person shall sell or lease, or offer for sale or lease (including advertising for sale or lease), or import, ship or distribute for the purpose of selling or leasing or offering for sale or lease, any radio frequency device unless:
  - (1) In the case of a device subject to certification, such device has been authorized by the Commission in accordance with the rules in this chapter and is properly identified and labeled as required by §2.925 and other relevant sections in this chapter; or
  - (2) In the case of a device that is not required to have a grant of equipment authorization issued by the Commission, but which must comply with the specified technical standards prior to use, such device also complies with all applicable administrative (including verification of the equipment or authorization under a Declaration of Conformity, where required), technical, labeling and identification requirements specified in this chapter.
- (d) Notwithstanding the provisions of paragraph (a) of this section, the offer for sale solely to business, commercial, industrial, scientific or medical users (but not an offer for sale to other parties or to end users located in a residential environment) of a radio frequency device that is in the conceptual, developmental, design or pre-production stage is permitted prior to equipment authorization or, for devices not subject to the equipment authorization requirements, prior to a determination of compliance with the applicable technical requirements *provided* that the prospective buyer is advised in writing at the time of the offer for sale that the equipment is subject to the FCC rules and that the equipment will comply with the appropriate rules before delivery to the buyer or to centers of distribution.

(e)(1) Notwithstanding the provisions of paragraph (a) of this section, prior to equipment authorization or determination of compliance with the applicable technical requirements any radio frequency device may be operated, but not marketed, for the following purposes and under the following conditions:

- (i) *Compliance testing;*
- (ii) Demonstrations at a trade show provided the notice contained in paragraph (c) of this section is displayed in a conspicuous location on, or immediately adjacent to, the device;
- (iii) Demonstrations at an exhibition conducted at a business, commercial, industrial, scientific or medical location, but excluding locations in a residential environment, provided the notice contained in paragraphs (c) or (d) of this section, as appropriate, is displayed in a conspicuous location on, or immediately adjacent to, the device;
- (iv) Evaluation of product performance and determination of customer acceptability, provided such operation takes place at the manufacturer's facilities during developmental, design or pre-production states; or
- (v) Evaluation of product performance and determination of customer acceptability where customer acceptability of a radio frequency device cannot be determined at the manufacturer's facilities because of size or unique capability of the device, provided the device is operated at a business, commercial, industrial, scientific or medical user's site, but not at a residential site, during the development, design or pre-production stages.

(e)(2) For the purpose of paragraphs (e)(1)(iv) and (e)(1)(v) of this section, the term *manufacturer's facilities* includes the facilities of the party responsible for compliance with the regulations and the manufacturer's premises, as well as the facilities of other entities working under the authorization of the responsible party in connection with the development and manufacture, but not the marketing, of the equipment.

(f) For radio frequency devices subject to verification and sold solely to business, commercial, industrial, scientific and medical users (excluding products sold to other parties or for operation in a residential environment), parties responsible for verification of the devices shall have the option of ensuring compliance with the applicable technical specifications of this chapter at each end user's location after installation, provided that the purchase or lease agreement includes a proviso that such a determination of compliance be made and is the responsibility of the party responsible for verification of the equipment.

## Certification & User's Manual Information

**The following is extracted from Title 47 of the Code of Federal Regulations, Part 2, Subpart J — Equipment Authorization Procedures:**

### § 2.901 Basis and Purpose

- (a) In order to carry out its responsibilities under the Communications Act and the various treaties and international regulations, and in order to promote efficient use of the radio spectrum, the Commission has developed technical standards for radio frequency equipment and parts or components thereof. The technical standards applicable to individual types of equipment are found in that part of the rules governing the service wherein the equipment is to be operated.<sup>1</sup> *In addition to the technical standards provided, the rules governing the service may require that such equipment be verified by the manufacturer or importer,* be authorized under a Declaration of Conformity, or receive an equipment authorization from the Commission by one of the following procedures: certification or registration.
- (b) The following sections describe the verification procedure, the procedure for a Declaration of Conformity, and the procedures to be followed in obtaining certification from the Commission and the conditions attendant to such a grant.

### § 2.907 Certification.

- (a) Certification is an equipment authorization issued by the Commission, based on representation and test data submitted by the applicant.
- (b) Certification attaches to all units subsequently marketed by the grantee which are identical (see Section 2.908) to the sample tested except for permissive changes or other variations authorized by the Commission pursuant to Section 2.1043.

<sup>1</sup> In this case, the equipment is subject to the rules of Part 15. More specifically, the equipment falls under Subpart B (of Part 15), which deals with unintentional radiators.

## Certification & User's Manual Information

### § 2.948 Description of measurement facilities.

- (a) Each party making measurements of equipment that is subject to an equipment authorization under Part 15 or Part 18 of this chapter, regardless of whether the measurements are filed with the Commission or kept on file by the party responsible for compliance of equipment marketed within the U.S. or its possessions, shall compile a description of the measurement facilities employed.
  - (1) If the measured equipment is subject to the verification procedure, the description of the measurement facilities shall be retained by the party responsible for verification of the equipment.
    - (i) *If the equipment is verified through measurements performed by an independent laboratory, it is acceptable for the party responsible for verification of the equipment to rely upon the description of the measurement facilities retained by or placed on file with the Commission by that laboratory. In this situation, the party responsible for the verification of the equipment is not required to retain a duplicate copy of the description of the measurement facilities.*
    - (ii) If the equipment is verified based on measurements performed at the installation site of the equipment, no specific site calibration data is required. It is acceptable to retain the description of the measurement facilities at the site at which the measurements were performed.
  - (2) If the equipment is to be authorized by the Commission under the certification procedure, the description of the measurement facilities shall be filed with the Commission's Laboratory in Columbia, Maryland. The data describing the measurement facilities need only be filed once but must be updated as changes are made to the measurement facilities or as otherwise described in this section. At least every three years, the organization responsible for filing the data with the Commission shall certify that the data on file is current.

## Certification & User's Manual Information

### 1. Label and User's Manual Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 15, Subpart A — General:

#### § 15.19 Labeling requirements.

(a) *In addition to the requirements in Part 2 of this chapter, a device subject to certification or verification shall be labeled as follows:*

(1) Receivers associated with the operation of a licensed radio service, e.g., FM broadcast under Part 73 of this chapter, land mobile operation under Part 90, etc., shall bear the following statement in a conspicuous location on the device:

This device complies with Part 15 of the FCC Rules. Operation is subject to the condition that this device does not cause harmful interference.

(2) A stand-alone cable input selector switch, shall bear the following statement in a conspicuous location on the device:

This device is verified to comply with Part 15 of the FCC Rules for use with cable television service.

(3) All other devices shall bear the following statement in a conspicuous location on the device:

*This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.*

(4) Where a device is constructed in two or more sections connected by wires and marketed together, the statement specified under paragraph (a) of this section is required to be affixed only to the main control unit.

(5) When the device is so small or for such use that it is not practicable to place the statement specified under paragraph (a) of this section on it, the information required by this paragraph shall be placed in a prominent location in the instruction manual or pamphlet supplied to the user or, alternatively, shall be placed on the container in which the device is marketed. However, the FCC identifier or the unique identifier, as appropriate, must be displayed on the device.

#### § 15.21 Information to user.

The users manual or instruction manual for an intentional or unintentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

## Verification & User's Manual Information

The following is extracted from Title 47 of the Code of Federal Regulations, Part 15, Subpart B — Unintentional Radiators:

### § 15.105 Information to the user.

(a) For a Class A digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual:

Note: This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at own expense.

(b) For a Class B digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual:

Note: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a residential environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

## ICES-003 Procedural & Labeling Requirements

From the Industry Canada Electromagnetic Compatibility Advisory Bulletin entitled, "Implementation and Interpretation of the Interference-Causing Equipment Standard for Digital Apparatus, ICES-003" (EMCAB-3, Issue 2, July 1995):

"At present, CISPR 22: 2002 and ICES technical requirements are essentially equivalent. Therefore, if you have CISPR 22: 2002 approval by meeting CISPR Publication 22, the only additional requirements are: to attach a note to the report of the test results for compliance, indicating that these results are deemed satisfactory evidence of compliance with ICES-003 of the Canadian Interference-Causing Equipment Regulations; to maintain these records on file for the requisite five year period; and to provide the device with a notice of compliance in accordance with ICES-003."

### Procedural Requirements:

According to Industry Canada's Interference Causing Equipment Standard for Digital Apparatus ICES-003 Issue 4, February 2004:

Section 6.1: A record of the measurements and results, showing the date that the measurements were completed, shall be retained by the manufacturer or importer for a period of at least five years from the date shown in the record and made available for examination on the request of the Minister.

Section 6.2: A written notice indicating compliance must accompany each unit of digital apparatus to the end user. The notice shall be in the form of a label that is affixed to the apparatus. Where because of insufficient space or other constraints it is not feasible to affix a label to the apparatus, the notice may be in the form of a statement in the user's manual.

### Labeling Requirements:

The suggested text for the notice, in English and in French, is provided below, from the Annex of ICES-003:

This Class <sup>[2]</sup> digital apparatus complies with Canadian ICES-003.

Cet appareil numérique de la classe <sup>[1]</sup> est conforme à la norme NMB-003 du Canada.

<sup>2</sup> Insert either A or B but not both as appropriate for the equipment requirements.