



# FCC RF Test Report

**APPLICANT** : Sonim Technologies, Inc.  
**EQUIPMENT** : Mobile Hotspot  
**BRAND NAME** : Sonim  
**MODEL NAME** : H700B  
**FCC ID** : WYPH700B  
**STANDARD** : 47 CFR Part 22(H), 24(E), 27(L)  
**CLASSIFICATION** : PCS Licensed Transmitter (PCB)  
**TEST DATE(S)** : Aug. 29, 2024 ~ May 13, 2025

We, Sporton International Inc. (ShenZhen), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (ShenZhen), the test report shall not be reproduced except in full.

Fly Liang



Approved by: Fly Liang

**Sportun International Inc. (ShenZhen)**

**1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055**

**People's Republic of China**



## TABLE OF CONTENTS

<b>REVISION HISTORY.....</b>	<b>3</b>
<b>SUMMARY OF TEST RESULT .....</b>	<b>4</b>
<b>1 GENERAL DESCRIPTION.....</b>	<b>5</b>
1.1 Applicant.....	5
1.2 Manufacturer .....	5
1.3 Product Feature of Equipment Under Test .....	5
1.4 Product Specification of Equipment Under Test .....	6
1.5 Modification of EUT .....	6
1.6 Maximum ERP/EIRP Power and Emission Designator .....	7
1.7 Testing Location .....	7
1.8 Test Software .....	7
1.9 Applicable Standards .....	8
<b>2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....</b>	<b>9</b>
2.1 Test Mode.....	9
2.2 Connection Diagram of Test System .....	10
2.3 Support Unit used in test configuration .....	10
2.4 Measurement Results Explanation Example .....	11
2.5 Frequency List of Low/Middle/High Channels.....	11
<b>3 CONDUCTED TEST RESULT.....</b>	<b>12</b>
3.1 Measuring Instruments.....	12
3.2 Test Setup .....	12
3.3 Test Result of Conducted Test.....	12
3.4 Conducted Output Power and ERP/EIRP .....	13
3.5 Peak-to-Average Ratio .....	14
3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	15
3.7 Conducted Band Edge .....	16
3.8 Conducted Spurious Emission .....	17
3.9 Frequency Stability.....	18
<b>4 RADIATED TEST ITEMS .....</b>	<b>19</b>
4.1 Measuring Instruments.....	19
4.2 Test Setup .....	19
4.3 Test Result of Radiated Test.....	20
4.4 Field Strength of Spurious Radiation Measurement .....	21
<b>5 LIST OF MEASURING EQUIPMENT .....</b>	<b>22</b>
<b>6 MEASUREMENT UNCERTAINTY .....</b>	<b>23</b>
<b>APPENDIX A. TEST RESULTS OF CONDUCTED TEST</b>	
<b>APPENDIX B. TEST RESULTS OF RADIATED TEST</b>	
<b>APPENDIX C. TEST SETUP PHOTOGRAPHS</b>	



# REVISION HISTORY



## SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	-	Report Only	-
	§22.913(a)(5)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
	§27.50(d)(4)	Equivalent Isotropic Radiated Power	< 1 Watts	PASS	-
3.5	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.6	§2.1049	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Conducted Emission	< 43+10log10(P[Watts])	PASS	-
3.9	§2.1055 §22.355	Frequency Stability for Temperature & Voltage	< 2.5 ppm for Part 22	PASS	-
	§2.1055 §24.235 §27.54		Within Authorized Band		
4.4	§2.1053; §22.917(a); §24.238(a); §27.53(h)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 41.75 dB at 7520.00 MHz

### Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

### Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



## 1 General Description

### 1.1 Applicant

**Sonim Technologies, Inc.**

4445 Eastgate Mall, Suite 200, San Diego, CA92121, USA

### 1.2 Manufacturer

**Sonim Technologies, Inc.**

4445 Eastgate Mall, Suite 200, San Diego, CA92121, USA

### 1.3 Product Feature of Equipment Under Test

Product Feature	
<b>Equipment</b>	Mobile Hotspot
<b>Brand Name</b>	Sonim
<b>Model Name</b>	H700B
<b>FCC ID</b>	WYPH700B
<b>IMEI Code</b>	Conducted: 351393280000468 Radiation: 351393280007273
<b>HW Version</b>	V3.0
<b>SW Version</b>	H70.0-01-22.3.0-10.25.00
<b>EUT Stage</b>	Identical Prototype

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



## 1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
<b>Tx Frequency</b>	<b>WCDMA:</b> Band V: 824 MHz ~ 849 MHz Band II: 1850 MHz ~ 1910 MHz Band IV: 1710 MHz ~ 1755 MHz
<b>Rx Frequency</b>	<b>WCDMA:</b> Band V: 869 MHz ~ 894 MHz Band II: 1930 MHz ~ 1990 MHz Band IV: 2110 MHz ~ 2155 MHz
<b>Maximum Output Power to Antenna</b>	<ANT0> <b>WCDMA:</b> Band V: 23.40 dBm Band II: 23.28 dBm Band IV: 23.30 dBm
<b>Antenna Type</b>	External Antenna: PIFA Internal Antenna: PIFA
<b>Antenna Gain</b>	<External Antenna> <ANT0> Cellular Band: 5.0 dBi PCS Band: 4.5 dBi AWS Band: 4.0 dBi <Internal Antenna> <ANT0> Cellular Band: -1.95 dBi PCS Band: -0.11 dBi AWS Band: -0.03 dBi
<b>Type of Modulation</b>	WCDMA : BPSK HSPA : QPSK HSPA+ : 16QAM DC-HSDPA : 64QAM

Note:

1. The device supports two types of WWAN antennas: Internal Antenna and External Antenna, they share the same RF test port, and the two antennas cannot work at the same time. After evaluation, the antenna difference does not affect the Conducted measurement. For RSE, only the test results of the worse External Antenna are shown.
2. The maximum ERP/EIRP is calculated from max output power and max antenna gain, so only the maximum ERP/EIRP of External Antenna are shown in the report.

## 1.5 Modification of EUT

No modifications are made to the EUT during all test items.



## 1.6 Maximum ERP/EIRP Power and Emission Designator

FCC Rule	Frequency Band	Frequency Range (MHz)	Type of Modulation	Maximum ERP/EIRP (W)	Emission Designator
Part 22	WCDMA Band V	826.4 ~ 846.6	BPSK	0.4217	4M15F9W
Part 24	WCDMA Band II	1852.4 ~ 1907.6	BPSK	0.5998	4M17F9W
Part 27	WCDMA Band IV	1712.4 ~ 1752.6	BPSK	0.5370	4M17F9W

## 1.7 Testing Location

Sportun International Inc. (ShenZhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sportun International Inc. (ShenZhen)		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China TEL: +86-755-86066985		
Test Site No.	Sportun Site No.	FCC Designation No.	FCC Test Firm Registration No.
	TH01-SZ 03CH02-SZ	CN1256	421272

## 1.8 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH02-SZ	AUDIX	E3	6.2009-8-24a



## 1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 22(H), 24(E), 27(L)
- ANSI C63.26-2015
- FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- FCC KDB 412172 D01 Determining ERP and EIRP v01r01

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test

### 2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:

1. 30 MHz to 9000 MHz for WCDMA Band V.
2. 30 MHz to 18000 MHz for WCDMA Band IV.
3. 30 MHz to 19100 MHz for WCDMA Band II.


All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	Radiated TCs	Conducted TCs
WCDMA Band V	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band II	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band IV	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link



## 2.2 Connection Diagram of Test System



The EUT has been configuration operated in a manner tended to maximize its emission characteristics in a typical application.

## 2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	Power Supply	GWINSTEK	PSS-2002	N/A	N/A	Unshielded, 1.8 m
2.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
3.	External Antenna	N/A	N/A	N/A	N/A	N/A



## 2.4 Measurement Results Explanation Example

### For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

$\text{Offset} = \text{RF cable loss} + \text{attenuator factor}$ .

The following shows an offset computation example with RF cable loss 4.0 dB and a 10dB attenuator.

Example :

$\text{Offset(dB)} = \text{RF cable loss(dB)} + \text{attenuator factor(dB)}$ .

$$= 4.0 + 10 = 14.0 \text{ (dB)}$$

## 2.5 Frequency List of Low/Middle/High Channels

Frequency List				
Band	Channel/Frequency(MHz)	Lowest	Middle	Highest
WCDMA Band V	Channel	4132	4182	4233
	Frequency	826.4	836.4	846.6
WCDMA Band II	Channel	9262	9400	9538
	Frequency	1852.4	1880.0	1907.6
WCDMA Band IV	Channel	1312	1413	1513
	Frequency	1712.4	1732.6	1752.6


### 3 Conducted Test Result

#### 3.1 Measuring Instruments


See list of measuring instruments of this test report.

#### 3.2 Test Setup


##### 3.2.1 Conducted Output Power



##### 3.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



##### 3.2.3 Frequency Stability



#### 3.3 Test Result of Conducted Test

Please refer to Appendix A.



### 3.4 Conducted Output Power and ERP/EIRP

#### 3.4.1 Description of the Conducted Output Power and ERP/EIRP

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for WCDMA Band V.

The EIRP of mobile transmitters must not exceed 2 Watts for WCDMA Band II.

The EIRP of mobile transmitters must not exceed 1 Watts for WCDMA Band IV.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$ ,  $ERP = EIRP - 2.15$ , where

$P_T$  = transmitter output power in dBm

$G_T$  = gain of the transmitting antenna in dBi

$L_C$  = signal attenuation in the connecting cable between the transmitter and antenna in dB

#### 3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.



## 3.5 Peak-to-Average Ratio

### 3.5.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

### 3.5.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.



## 3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement

### 3.6.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

### 3.6.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace. (this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



## 3.7 Conducted Band Edge

### 3.7.1 Description of Conducted Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

### 3.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)



## 3.8 Conducted Spurious Emission

### 3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10<sup>th</sup> harmonic.

### 3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)



## 3.9 Frequency Stability

### 3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within  $\pm 0.00025\%$  ( $\pm 2.5\text{ppm}$ ) of the center frequency.

### 3.9.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to  $-30^{\circ}\text{C}$  and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in  $10^{\circ}\text{C}$  step up to  $50^{\circ}\text{C}$ . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

### 3.9.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5
2. The EUT was placed in a temperature chamber at  $20\pm 5^{\circ}\text{C}$  and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.


## 4 Radiated Test Items

### 4.1 Measuring Instruments


See list of measuring instruments of this test report.

### 4.2 Test Setup


#### 4.2.1 For radiated test below 30MHz



#### 4.2.2 For radiated test from 30MHz to 1GHz



#### 4.2.3 For radiated test above 1GHz



### 4.3 Test Result of Radiated Test

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.



## 4.4 Field Strength of Spurious Radiation Measurement

### 4.4.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

### 4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a rotatable wooden table 0.8 meters for frequency below 1GHz and 1.5 meter for frequency above 1GHz above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
12. ERP (dBm) = EIRP - 2.15
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)



## 5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 09, 2024	Aug. 29, 2024	Apr. 08, 2025	Conducted (TH01-SZ)
DC Power Supply	TTI	PL330P	290070	Max 32V, 3A	Oct. 16, 2023	Aug. 29, 2024	Oct. 15, 2024	Conducted (TH01-SZ)
Power Divider	TOJOIN	PS-2SM-04 265	60.06.020.007 7	0.4GHz~26.5GHz	Dec. 25, 2023	Aug. 29, 2024	Dec. 24, 2024	Conducted (TH01-SZ)
Thermal Chamber	Ten Billion Hongzhangroup	LP-150U	H2014081803	-40~+150°C	Jul. 03, 2024	Aug. 29, 2024	Jul. 02, 2025	Conducted (TH01-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150213	10Hz~44GHz	Jul. 03, 2024	Apr. 17, 2025 ~ May 13, 2025	Jul. 02, 2025	Radiation (03CH02-SZ)
Loop Antenna	R&S	HFH2-Z2E	101141	9kHz~30MHz	Dec. 28, 2024	Apr. 17, 2025 ~ May 13, 2025	Dec. 27, 2025	Radiation (03CH02-SZ)
Bilog Antenna	TeseQ	CBL6112D	35407	30MHz-2GHz	Oct. 24, 2023	Apr. 17, 2025 ~ May 13, 2025	Oct. 23, 2025	Radiation (03CH02-SZ)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00119436	1GHz~18GHz	Jul. 04, 2024	Apr. 17, 2025 ~ May 13, 2025	Jul. 04, 2025	Radiation (03CH02-SZ)
HF Amplifier	MITEQ	TTA1840-35 -HG	1871923	18GHz~40GHz	Jul. 03, 2024	Apr. 17, 2025 ~ May 13, 2025	Jul. 03, 2025	Radiation (03CH02-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz-40GHz	Apr. 03, 2025	Apr. 17, 2025 ~ May 13, 2025	Apr. 02, 2027	Radiation (03CH02-SZ)
LF Amplifier	EM Electronics	EM330	060788	20MHz-3GHz	Dec. 25, 2024	Apr. 17, 2025 ~ May 13, 2025	Dec. 24, 2025	Radiation (03CH02-SZ)
HF Amplifier	KEYSIGHT	83017A	MY53270105	0.5GHz~26.5Ghz	Oct. 14, 2024	Apr. 17, 2025 ~ May 13, 2025	Oct. 13, 2025	Radiation (03CH02-SZ)
AC Power Source	Chroma	61601	61601000304 3	N/A	Oct. 18, 2024	Apr. 17, 2025 ~ May 13, 2025	Oct. 17, 2025	Radiation (03CH02-SZ)
Turn Table	Chaintek	T-200	N/A	0~360 degree	NCR	Apr. 17, 2025 ~ May 13, 2025	NCR	Radiation (03CH02-SZ)
Antenna Mast	Chaintek	MBS-400	N/A	1 m~4 m	NCR	Apr. 17, 2025 ~ May 13, 2025	NCR	Radiation (03CH02-SZ)

NCR: No Calibration Required



## 6 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

### Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Spurious Emission & Bandedge	$\pm 1.34$ dB
Occupied Channel Bandwidth	$\pm 0.012$ MHz
Conducted Power	$\pm 1.34$ dB
Peak to Average Ratio	$\pm 1.34$ dB
Frequency Stability	$\pm 1.3$ Hz

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_{c(y)}$ )	2.47 dB
--	---------

### Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_{c(y)}$ )	3.31 dB
--	---------

### Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_{c(y)}$ )	3.72 dB
--	---------

----- THE END -----



## Appendix A. Test Results of Conducted Test

Test Engineer :	Nina Cheng	Temperature :	24~26°C
		Relative Humidity :	50~53%

### Conducted Output Power(Average power) and ERP/EIRP

#### WCDMA Band V:

Band		WCDMA V			ERP(W)		
TX Channel		4132	4182	4233			
Rx Channel		4357	4407	4458			
Frequency (MHz)		826.4	836.4	846.6	L	M	H
3GPP Rel 99	RMC 12.2Kbps	23.37	23.40	23.39	0.4188	0.4217	0.4207
3GPP Rel 6	HSDPA Subtest-1	22.45	22.47	22.41	0.3388	0.3404	0.3357
3GPP Rel 6	HSDPA Subtest-2	22.49	22.50	22.46	0.3420	0.3428	0.3396
3GPP Rel 6	HSDPA Subtest-3	21.97	21.98	21.93	0.3034	0.3041	0.3006
3GPP Rel 6	HSDPA Subtest-4	21.96	21.95	21.92	0.3027	0.3020	0.2999
3GPP Rel 8	DC-HSDPA Subtest-1	22.43	22.42	22.38	0.3373	0.3365	0.3334
3GPP Rel 8	DC-HSDPA Subtest-2	22.43	22.44	22.41	0.3373	0.3381	0.3357
3GPP Rel 8	DC-HSDPA Subtest-3	21.91	21.93	21.88	0.2992	0.3006	0.2972
3GPP Rel 8	DC-HSDPA Subtest-4	21.95	21.94	21.85	0.3020	0.3013	0.2951
3GPP Rel 6	HSUPA Subtest-1	22.37	22.31	22.32	0.3327	0.3281	0.3289
3GPP Rel 6	HSUPA Subtest-2	20.38	20.33	20.33	0.2104	0.2080	0.2080
3GPP Rel 6	HSUPA Subtest-3	21.34	21.35	21.32	0.2624	0.2630	0.2612
3GPP Rel 6	HSUPA Subtest-4	20.34	20.33	20.34	0.2084	0.2080	0.2084
3GPP Rel 6	HSUPA Subtest-5	22.40	22.30	22.30	0.3350	0.3273	0.3273
3GPP Rel 7	HSPA+ (16QAM) Subtest-1	20.21	20.18	20.15	0.2023	0.2009	0.1995

**WCDMA Band II:**

Band		WCDMA II			EIRP(W)		
TX Channel		9262	9400	9538			
Rx Channel		9662	9800	9938			
Frequency (MHz)		1852.4	1880	1907.6	L	M	H
3GPP Rel 99	RMC 12.2Kbps	23.21	23.28	23.23	0.5902	0.5998	0.5929
3GPP Rel 6	HSDPA Subtest-1	22.17	22.29	22.28	0.4645	0.4775	0.4764
3GPP Rel 6	HSDPA Subtest-2	22.16	22.28	22.26	0.4634	0.4764	0.4742
3GPP Rel 6	HSDPA Subtest-3	21.67	21.79	21.79	0.4140	0.4256	0.4256
3GPP Rel 6	HSDPA Subtest-4	21.65	21.75	21.77	0.4121	0.4217	0.4236
3GPP Rel 8	DC-HSDPA Subtest-1	22.12	22.24	22.23	0.4592	0.4721	0.4710
3GPP Rel 8	DC-HSDPA Subtest-2	22.13	22.24	22.20	0.4603	0.4721	0.4677
3GPP Rel 8	DC-HSDPA Subtest-3	21.61	21.74	21.72	0.4083	0.4207	0.4188
3GPP Rel 8	DC-HSDPA Subtest-4	21.58	21.74	21.71	0.4055	0.4207	0.4178
3GPP Rel 6	HSUPA Subtest-1	22.17	22.30	22.31	0.4645	0.4786	0.4797
3GPP Rel 6	HSUPA Subtest-2	20.16	20.28	20.30	0.2924	0.3006	0.3020
3GPP Rel 6	HSUPA Subtest-3	21.13	21.25	21.28	0.3656	0.3758	0.3784
3GPP Rel 6	HSUPA Subtest-4	20.08	20.27	20.25	0.2871	0.2999	0.2985
3GPP Rel 6	HSUPA Subtest-5	22.10	22.30	22.30	0.4571	0.4786	0.4786
3GPP Rel 7	HSPA+ (16QAM) Subtest-1	20.11	20.11	20.05	0.2891	0.2891	0.2851

**WCDMA Band IV:**


Band		WCDMA IV			EIRP(W)		
TX Channel		1312	1413	1513			
Rx Channel		1537	1638	1738			
Frequency (MHz)		1712.4	1732.6	1752.6	L	M	H
3GPP Rel 99	RMC 12.2Kbps	23.26	23.30	23.23	0.5321	0.5370	0.5284
3GPP Rel 6	HSDPA Subtest-1	22.11	22.26	22.21	0.4083	0.4227	0.4178
3GPP Rel 6	HSDPA Subtest-2	22.22	22.27	22.22	0.4188	0.4236	0.4188
3GPP Rel 6	HSDPA Subtest-3	21.72	21.72	21.66	0.3733	0.3733	0.3681
3GPP Rel 6	HSDPA Subtest-4	21.70	21.79	21.68	0.3715	0.3793	0.3698
3GPP Rel 8	DC-HSDPA Subtest-1	22.04	22.23	22.19	0.4018	0.4198	0.4159
3GPP Rel 8	DC-HSDPA Subtest-2	22.15	22.21	22.17	0.4121	0.4178	0.4140
3GPP Rel 8	DC-HSDPA Subtest-3	21.67	21.68	21.62	0.3690	0.3698	0.3648
3GPP Rel 8	DC-HSDPA Subtest-4	21.63	21.77	21.61	0.3656	0.3776	0.3639
3GPP Rel 6	HSUPA Subtest-1	22.16	22.20	22.22	0.4130	0.4169	0.4188
3GPP Rel 6	HSUPA Subtest-2	20.18	20.20	20.15	0.2618	0.2630	0.2600
3GPP Rel 6	HSUPA Subtest-3	21.18	21.21	21.15	0.3296	0.3319	0.3273
3GPP Rel 6	HSUPA Subtest-4	20.18	20.24	20.17	0.2618	0.2655	0.2612
3GPP Rel 6	HSUPA Subtest-5	22.20	22.20	22.20	0.4169	0.4169	0.4169
3GPP Rel 7	HSPA+ (16QAM) Subtest-1	20.05	20.05	20.08	0.2541	0.2541	0.2559




## A2. WCDMA

### Peak-to-Average Ratio


Mode	WCDMA Band V(dB)	WCDMA Band II(dB)	WCDMA Band IV(dB)	Limit: 13dB
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps	Result
Lowest CH	2.90	2.29	2.93	PASS
Middle CH	2.87	2.23	2.43	
Highest CH	2.99	2.38	2.72	






**26dB Bandwidth**

Mode	WCDMA Band V(MHz)	WCDMA Band II(MHz)	WCDMA Band IV(MHz)
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.71	4.76	4.74
Middle CH	4.74	4.77	4.76
Highest CH	4.73	4.79	4.75









## Occupied Bandwidth


Mode	WCDMA Band V(MHz)	WCDMA Band II(MHz)	WCDMA Band IV(MHz)
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.14	4.17	4.17
Middle CH	4.15	4.17	4.16
Highest CH	4.13	4.17	4.15














## Conducted Band Edge








## Conducted Spurious Emission

WCDMA Band V (RMC 12.2Kbps)	WCDMA Band II (RMC 12.2Kbps)																																																																														
<b>Lowest Channel</b>	<b>Lowest Channel</b>																																																																														
 <p><b>Spurious Emissions</b></p> <table border="1"> <thead> <tr> <th>Range Low</th> <th>Range Up</th> <th>RBW</th> <th>Frequency</th> <th>Power Abs</th> <th>ALimit</th> </tr> </thead> <tbody> <tr> <td>30.000 MHz</td> <td>820.000 MHz</td> <td>1.000 MHz</td> <td>884.01049 MHz</td> <td>-37.76 dBm</td> <td>-24.76 dB</td> </tr> <tr> <td>855.000 MHz</td> <td>1.000 GHz</td> <td>1.000 MHz</td> <td>988.73188 MHz</td> <td>-37.43 dBm</td> <td>-24.43 dB</td> </tr> <tr> <td>1.000 GHz</td> <td>3.000 GHz</td> <td>1.000 MHz</td> <td>2.85414 GHz</td> <td>-37.43 dBm</td> <td>-24.43 dB</td> </tr> <tr> <td>3.000 GHz</td> <td>7.000 GHz</td> <td>1.000 MHz</td> <td>6.09536 GHz</td> <td>-32.17 dBm</td> <td>-19.17 dB</td> </tr> <tr> <td>7.000 GHz</td> <td>9.000 GHz</td> <td>1.000 MHz</td> <td>8.09799 GHz</td> <td>-35.28 dBm</td> <td>-22.28 dB</td> </tr> </tbody> </table> <p>Date: 29 AUG 2024 10:24:46</p>	Range Low	Range Up	RBW	Frequency	Power Abs	ALimit	30.000 MHz	820.000 MHz	1.000 MHz	884.01049 MHz	-37.76 dBm	-24.76 dB	855.000 MHz	1.000 GHz	1.000 MHz	988.73188 MHz	-37.43 dBm	-24.43 dB	1.000 GHz	3.000 GHz	1.000 MHz	2.85414 GHz	-37.43 dBm	-24.43 dB	3.000 GHz	7.000 GHz	1.000 MHz	6.09536 GHz	-32.17 dBm	-19.17 dB	7.000 GHz	9.000 GHz	1.000 MHz	8.09799 GHz	-35.28 dBm	-22.28 dB	 <p><b>Spurious Emissions</b></p> <table border="1"> <thead> <tr> <th>Range Low</th> <th>Range Up</th> <th>RBW</th> <th>Frequency</th> <th>Power Abs</th> <th>ALimit</th> </tr> </thead> <tbody> <tr> <td>30.000 MHz</td> <td>1.000 GHz</td> <td>1.000 MHz</td> <td>997.47276 GHz</td> <td>-37.19 dBm</td> <td>-26.10 dB</td> </tr> <tr> <td>1.000 GHz</td> <td>1.845 GHz</td> <td>1.000 MHz</td> <td>1.04479 GHz</td> <td>-31.88 dBm</td> <td>-19.88 dB</td> </tr> <tr> <td>1.915 GHz</td> <td>3.000 GHz</td> <td>1.000 MHz</td> <td>2.55365 GHz</td> <td>-37.30 dBm</td> <td>-24.30 dB</td> </tr> <tr> <td>3.000 GHz</td> <td>7.000 GHz</td> <td>1.000 MHz</td> <td>6.38783 GHz</td> <td>-32.88 dBm</td> <td>-19.88 dB</td> </tr> <tr> <td>7.000 GHz</td> <td>13.600 GHz</td> <td>1.000 MHz</td> <td>13.29147 GHz</td> <td>-35.67 dBm</td> <td>-22.67 dB</td> </tr> <tr> <td>13.600 GHz</td> <td>19.100 GHz</td> <td>1.000 MHz</td> <td>16.53070 GHz</td> <td>-31.69 dBm</td> <td>-18.69 dB</td> </tr> </tbody> </table> <p>Date: 29 AUG 2024 10:46:05</p>	Range Low	Range Up	RBW	Frequency	Power Abs	ALimit	30.000 MHz	1.000 GHz	1.000 MHz	997.47276 GHz	-37.19 dBm	-26.10 dB	1.000 GHz	1.845 GHz	1.000 MHz	1.04479 GHz	-31.88 dBm	-19.88 dB	1.915 GHz	3.000 GHz	1.000 MHz	2.55365 GHz	-37.30 dBm	-24.30 dB	3.000 GHz	7.000 GHz	1.000 MHz	6.38783 GHz	-32.88 dBm	-19.88 dB	7.000 GHz	13.600 GHz	1.000 MHz	13.29147 GHz	-35.67 dBm	-22.67 dB	13.600 GHz	19.100 GHz	1.000 MHz	16.53070 GHz	-31.69 dBm	-18.69 dB
Range Low	Range Up	RBW	Frequency	Power Abs	ALimit																																																																										
30.000 MHz	820.000 MHz	1.000 MHz	884.01049 MHz	-37.76 dBm	-24.76 dB																																																																										
855.000 MHz	1.000 GHz	1.000 MHz	988.73188 MHz	-37.43 dBm	-24.43 dB																																																																										
1.000 GHz	3.000 GHz	1.000 MHz	2.85414 GHz	-37.43 dBm	-24.43 dB																																																																										
3.000 GHz	7.000 GHz	1.000 MHz	6.09536 GHz	-32.17 dBm	-19.17 dB																																																																										
7.000 GHz	9.000 GHz	1.000 MHz	8.09799 GHz	-35.28 dBm	-22.28 dB																																																																										
Range Low	Range Up	RBW	Frequency	Power Abs	ALimit																																																																										
30.000 MHz	1.000 GHz	1.000 MHz	997.47276 GHz	-37.19 dBm	-26.10 dB																																																																										
1.000 GHz	1.845 GHz	1.000 MHz	1.04479 GHz	-31.88 dBm	-19.88 dB																																																																										
1.915 GHz	3.000 GHz	1.000 MHz	2.55365 GHz	-37.30 dBm	-24.30 dB																																																																										
3.000 GHz	7.000 GHz	1.000 MHz	6.38783 GHz	-32.88 dBm	-19.88 dB																																																																										
7.000 GHz	13.600 GHz	1.000 MHz	13.29147 GHz	-35.67 dBm	-22.67 dB																																																																										
13.600 GHz	19.100 GHz	1.000 MHz	16.53070 GHz	-31.69 dBm	-18.69 dB																																																																										
<b>Middle Channel</b>	<b>Middle Channel</b>																																																																														
 <p><b>Spurious Emissions</b></p> <table border="1"> <thead> <tr> <th>Range Low</th> <th>Range Up</th> <th>RBW</th> <th>Frequency</th> <th>Power Abs</th> <th>ALimit</th> </tr> </thead> <tbody> <tr> <td>30.000 MHz</td> <td>820.000 MHz</td> <td>1.000 MHz</td> <td>580.01049 MHz</td> <td>-36.85 dBm</td> <td>-23.45 dB</td> </tr> <tr> <td>855.000 MHz</td> <td>1.000 GHz</td> <td>1.000 MHz</td> <td>973.22464 MHz</td> <td>-36.49 dBm</td> <td>-23.49 dB</td> </tr> <tr> <td>1.000 GHz</td> <td>3.000 GHz</td> <td>1.000 MHz</td> <td>2.97438 GHz</td> <td>-37.59 dBm</td> <td>-24.59 dB</td> </tr> <tr> <td>3.000 GHz</td> <td>7.000 GHz</td> <td>1.000 MHz</td> <td>6.85827 GHz</td> <td>-33.13 dBm</td> <td>-20.13 dB</td> </tr> <tr> <td>7.000 GHz</td> <td>9.000 GHz</td> <td>1.000 MHz</td> <td>8.43970 GHz</td> <td>-35.36 dBm</td> <td>-22.36 dB</td> </tr> </tbody> </table> <p>Date: 29 AUG 2024 10:37:28</p>	Range Low	Range Up	RBW	Frequency	Power Abs	ALimit	30.000 MHz	820.000 MHz	1.000 MHz	580.01049 MHz	-36.85 dBm	-23.45 dB	855.000 MHz	1.000 GHz	1.000 MHz	973.22464 MHz	-36.49 dBm	-23.49 dB	1.000 GHz	3.000 GHz	1.000 MHz	2.97438 GHz	-37.59 dBm	-24.59 dB	3.000 GHz	7.000 GHz	1.000 MHz	6.85827 GHz	-33.13 dBm	-20.13 dB	7.000 GHz	9.000 GHz	1.000 MHz	8.43970 GHz	-35.36 dBm	-22.36 dB	 <p><b>Spurious Emissions</b></p> <table border="1"> <thead> <tr> <th>Range Low</th> <th>Range Up</th> <th>RBW</th> <th>Frequency</th> <th>Power Abs</th> <th>ALimit</th> </tr> </thead> <tbody> <tr> <td>30.000 MHz</td> <td>1.000 GHz</td> <td>1.000 MHz</td> <td>976.97401 MHz</td> <td>-37.33 dBm</td> <td>-24.33 dB</td> </tr> <tr> <td>1.000 GHz</td> <td>1.845 GHz</td> <td>1.000 MHz</td> <td>1.04479 GHz</td> <td>-32.99 dBm</td> <td>-20.99 dB</td> </tr> <tr> <td>1.915 GHz</td> <td>3.000 GHz</td> <td>1.000 MHz</td> <td>1.97094 GHz</td> <td>-36.99 dBm</td> <td>-23.99 dB</td> </tr> <tr> <td>3.000 GHz</td> <td>7.000 GHz</td> <td>1.000 MHz</td> <td>6.69079 GHz</td> <td>-32.49 dBm</td> <td>-19.49 dB</td> </tr> <tr> <td>7.000 GHz</td> <td>13.600 GHz</td> <td>1.000 MHz</td> <td>12.82526 GHz</td> <td>-35.19 dBm</td> <td>-22.19 dB</td> </tr> <tr> <td>13.600 GHz</td> <td>19.100 GHz</td> <td>1.000 MHz</td> <td>16.41128 GHz</td> <td>-31.23 dBm</td> <td>-18.23 dB</td> </tr> </tbody> </table> <p>Date: 29 AUG 2024 10:50:56</p>	Range Low	Range Up	RBW	Frequency	Power Abs	ALimit	30.000 MHz	1.000 GHz	1.000 MHz	976.97401 MHz	-37.33 dBm	-24.33 dB	1.000 GHz	1.845 GHz	1.000 MHz	1.04479 GHz	-32.99 dBm	-20.99 dB	1.915 GHz	3.000 GHz	1.000 MHz	1.97094 GHz	-36.99 dBm	-23.99 dB	3.000 GHz	7.000 GHz	1.000 MHz	6.69079 GHz	-32.49 dBm	-19.49 dB	7.000 GHz	13.600 GHz	1.000 MHz	12.82526 GHz	-35.19 dBm	-22.19 dB	13.600 GHz	19.100 GHz	1.000 MHz	16.41128 GHz	-31.23 dBm	-18.23 dB
Range Low	Range Up	RBW	Frequency	Power Abs	ALimit																																																																										
30.000 MHz	820.000 MHz	1.000 MHz	580.01049 MHz	-36.85 dBm	-23.45 dB																																																																										
855.000 MHz	1.000 GHz	1.000 MHz	973.22464 MHz	-36.49 dBm	-23.49 dB																																																																										
1.000 GHz	3.000 GHz	1.000 MHz	2.97438 GHz	-37.59 dBm	-24.59 dB																																																																										
3.000 GHz	7.000 GHz	1.000 MHz	6.85827 GHz	-33.13 dBm	-20.13 dB																																																																										
7.000 GHz	9.000 GHz	1.000 MHz	8.43970 GHz	-35.36 dBm	-22.36 dB																																																																										
Range Low	Range Up	RBW	Frequency	Power Abs	ALimit																																																																										
30.000 MHz	1.000 GHz	1.000 MHz	976.97401 MHz	-37.33 dBm	-24.33 dB																																																																										
1.000 GHz	1.845 GHz	1.000 MHz	1.04479 GHz	-32.99 dBm	-20.99 dB																																																																										
1.915 GHz	3.000 GHz	1.000 MHz	1.97094 GHz	-36.99 dBm	-23.99 dB																																																																										
3.000 GHz	7.000 GHz	1.000 MHz	6.69079 GHz	-32.49 dBm	-19.49 dB																																																																										
7.000 GHz	13.600 GHz	1.000 MHz	12.82526 GHz	-35.19 dBm	-22.19 dB																																																																										
13.600 GHz	19.100 GHz	1.000 MHz	16.41128 GHz	-31.23 dBm	-18.23 dB																																																																										
<b>Highest Channel</b>	<b>Highest Channel</b>																																																																														
 <p><b>Spurious Emissions</b></p> <table border="1"> <thead> <tr> <th>Range Low</th> <th>Range Up</th> <th>RBW</th> <th>Frequency</th> <th>Power Abs</th> <th>ALimit</th> </tr> </thead> <tbody> <tr> <td>30.000 MHz</td> <td>820.000 MHz</td> <td>1.000 MHz</td> <td>884.01049 MHz</td> <td>-37.58 dBm</td> <td>-24.37 dB</td> </tr> <tr> <td>855.000 MHz</td> <td>1.000 GHz</td> <td>1.000 MHz</td> <td>988.73188 MHz</td> <td>-36.79 dBm</td> <td>-23.79 dB</td> </tr> <tr> <td>1.000 GHz</td> <td>3.000 GHz</td> <td>1.000 MHz</td> <td>1.79853 GHz</td> <td>-37.69 dBm</td> <td>-24.69 dB</td> </tr> <tr> <td>3.000 GHz</td> <td>7.000 GHz</td> <td>1.000 MHz</td> <td>6.69529 GHz</td> <td>-32.55 dBm</td> <td>-19.55 dB</td> </tr> <tr> <td>7.000 GHz</td> <td>9.000 GHz</td> <td>1.000 MHz</td> <td>7.76853 GHz</td> <td>-35.55 dBm</td> <td>-22.55 dB</td> </tr> </tbody> </table> <p>Date: 29 AUG 2024 10:32:08</p>	Range Low	Range Up	RBW	Frequency	Power Abs	ALimit	30.000 MHz	820.000 MHz	1.000 MHz	884.01049 MHz	-37.58 dBm	-24.37 dB	855.000 MHz	1.000 GHz	1.000 MHz	988.73188 MHz	-36.79 dBm	-23.79 dB	1.000 GHz	3.000 GHz	1.000 MHz	1.79853 GHz	-37.69 dBm	-24.69 dB	3.000 GHz	7.000 GHz	1.000 MHz	6.69529 GHz	-32.55 dBm	-19.55 dB	7.000 GHz	9.000 GHz	1.000 MHz	7.76853 GHz	-35.55 dBm	-22.55 dB	 <p><b>Spurious Emissions</b></p> <table border="1"> <thead> <tr> <th>Range Low</th> <th>Range Up</th> <th>RBW</th> <th>Frequency</th> <th>Power Abs</th> <th>ALimit</th> </tr> </thead> <tbody> <tr> <td>30.000 MHz</td> <td>1.000 GHz</td> <td>1.000 MHz</td> <td>805.36982 MHz</td> <td>-37.37 dBm</td> <td>-24.37 dB</td> </tr> <tr> <td>1.000 GHz</td> <td>1.845 GHz</td> <td>1.000 MHz</td> <td>1.01415 GHz</td> <td>-38.42 dBm</td> <td>-25.42 dB</td> </tr> <tr> <td>1.915 GHz</td> <td>3.000 GHz</td> <td>1.000 MHz</td> <td>1.91179 GHz</td> <td>-30.99 dBm</td> <td>-18.99 dB</td> </tr> <tr> <td>3.000 GHz</td> <td>7.000 GHz</td> <td>1.000 MHz</td> <td>6.71179 GHz</td> <td>-33.23 dBm</td> <td>-19.23 dB</td> </tr> <tr> <td>7.000 GHz</td> <td>12.600 GHz</td> <td>1.000 MHz</td> <td>12.71926 GHz</td> <td>-34.23 dBm</td> <td>-21.23 dB</td> </tr> <tr> <td>12.600 GHz</td> <td>19.100 GHz</td> <td>1.000 MHz</td> <td>15.79022 GHz</td> <td>-31.48 dBm</td> <td>-18.48 dB</td> </tr> </tbody> </table> <p>Date: 29 AUG 2024 10:53:53</p>	Range Low	Range Up	RBW	Frequency	Power Abs	ALimit	30.000 MHz	1.000 GHz	1.000 MHz	805.36982 MHz	-37.37 dBm	-24.37 dB	1.000 GHz	1.845 GHz	1.000 MHz	1.01415 GHz	-38.42 dBm	-25.42 dB	1.915 GHz	3.000 GHz	1.000 MHz	1.91179 GHz	-30.99 dBm	-18.99 dB	3.000 GHz	7.000 GHz	1.000 MHz	6.71179 GHz	-33.23 dBm	-19.23 dB	7.000 GHz	12.600 GHz	1.000 MHz	12.71926 GHz	-34.23 dBm	-21.23 dB	12.600 GHz	19.100 GHz	1.000 MHz	15.79022 GHz	-31.48 dBm	-18.48 dB
Range Low	Range Up	RBW	Frequency	Power Abs	ALimit																																																																										
30.000 MHz	820.000 MHz	1.000 MHz	884.01049 MHz	-37.58 dBm	-24.37 dB																																																																										
855.000 MHz	1.000 GHz	1.000 MHz	988.73188 MHz	-36.79 dBm	-23.79 dB																																																																										
1.000 GHz	3.000 GHz	1.000 MHz	1.79853 GHz	-37.69 dBm	-24.69 dB																																																																										
3.000 GHz	7.000 GHz	1.000 MHz	6.69529 GHz	-32.55 dBm	-19.55 dB																																																																										
7.000 GHz	9.000 GHz	1.000 MHz	7.76853 GHz	-35.55 dBm	-22.55 dB																																																																										
Range Low	Range Up	RBW	Frequency	Power Abs	ALimit																																																																										
30.000 MHz	1.000 GHz	1.000 MHz	805.36982 MHz	-37.37 dBm	-24.37 dB																																																																										
1.000 GHz	1.845 GHz	1.000 MHz	1.01415 GHz	-38.42 dBm	-25.42 dB																																																																										
1.915 GHz	3.000 GHz	1.000 MHz	1.91179 GHz	-30.99 dBm	-18.99 dB																																																																										
3.000 GHz	7.000 GHz	1.000 MHz	6.71179 GHz	-33.23 dBm	-19.23 dB																																																																										
7.000 GHz	12.600 GHz	1.000 MHz	12.71926 GHz	-34.23 dBm	-21.23 dB																																																																										
12.600 GHz	19.100 GHz	1.000 MHz	15.79022 GHz	-31.48 dBm	-18.48 dB																																																																										





## Frequency Stability

Test Conditions	Middle Channel	WCDMA Band V (RMC 12.2Kbps)	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0005	PASS
40	Normal Voltage	0.0002	
30	Normal Voltage	0.0002	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0004	
0	Normal Voltage	0.0001	
-10	Normal Voltage	0.0001	
-20	Normal Voltage	0.0005	
-30	Normal Voltage	0.0008	
20	Maximum Voltage	0.0029	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0010	

Test Conditions	Middle Channel	WCDMA Band II (RMC 12.2Kbps)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0004	PASS
40	Normal Voltage	0.0005	
30	Normal Voltage	0.0003	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0016	
0	Normal Voltage	0.0003	
-10	Normal Voltage	0.0004	
-20	Normal Voltage	0.0002	
-30	Normal Voltage	0.0002	
20	Maximum Voltage	0.0013	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0015	

**Note:**

1. Normal Voltage = 3.8V. ; Battery End Point = 3.5 V.; Maximum Voltage =4.3 V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.



Test Conditions	Middle Channel	WCDMA Band IV (RMC 12.2Kbps)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0003	PASS
40	Normal Voltage	0.0002	
30	Normal Voltage	0.0003	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0002	
0	Normal Voltage	0.0001	
-10	Normal Voltage	0.0002	
-20	Normal Voltage	0.0003	
-30	Normal Voltage	0.0001	
20	Maximum Voltage	0.0002	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0000	

**Note:**

1. Normal Voltage = 3.8V. ; Battery End Point = 3.5 V.; Maximum Voltage =4.3 V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.



## Appendix B. Test Results of Radiated Test

### Radiated Spurious Emission

Test Engineer :	Wenbo Xiao	Temperature :		22~25°C
		Relative Humidity :		48~52%

WCDMA Band V(RMC 12.2Kbps)									
Channel	Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading (dBm)	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1672.8	-63.18	-13	-50.18	-69.93	-66.43	4.00	9.40	H
	2509.2	-63.88	-13	-50.88	-75.15	-67.45	4.88	10.60	H
	3345.6	-62.91	-13	-49.91	-76.79	-67.84	5.52	12.60	H
	1672.8	-66.53	-13	-53.53	-73.47	-69.78	4.00	9.40	V
	2509.2	-63.78	-13	-50.78	-75.17	-67.35	4.88	10.60	V
	3345.6	-63.13	-13	-50.13	-77.03	-68.06	5.52	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

WCDMA Band II(RMC 12.2Kbps)									
Channel	Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading (dBm)	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	3760	-60.18	-13	-47.18	-77.97	-66.93	5.85	12.60	H
	5640	-58.76	-13	-45.76	-81.33	-64.56	7.30	13.10	H
	7520	-54.83	-13	-41.83	-80.98	-57.98	8.35	11.50	H
	3760	-61.48	-13	-48.48	-79.2	-68.23	5.85	12.60	V
	5640	-59.40	-13	-46.40	-81.22	-65.20	7.30	13.10	V
	7520	-54.75	-13	-41.75	-80.88	-57.90	8.35	11.50	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

WCDMA Band IV(RMC 12.2Kbps)									
Channel	Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading (dBm)	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	3465.2	-62.61	-13	-49.61	-76.72	-69.46	5.65	12.50	H
	5197.8	-61.26	-13	-48.26	-80.08	-66.93	7.13	12.80	H
	6930.4	-57.78	-13	-44.78	-79.95	-61.18	8.40	11.80	H
	3465.2	-62.56	-13	-49.56	-76.7	-69.41	5.65	12.50	V
	5197.8	-61.70	-13	-48.70	-80.14	-67.37	7.13	12.80	V
	6930.4	-57.53	-13	-44.53	-79.99	-60.93	8.40	11.80	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.