

FCC TEST REPORT

(PART 24)


Applicant:	Sonim Technologies, Inc.
Address:	1825 S. Grant St., Suite 200., San Mateo, CA, 94402

Manufacturer or Supplier	Sonim Technologies (Shenzhen) Limited
Address	2nd Floor, No. 2 Building Phase B, Daqian Industrial park, Longchang Road, 67 District, Baoan, Shenzhen, P. R. China
Product	Mobile Phone
Brand Name	Sonim
Model Name	XP8800
FCC ID	WYPPC4000
Date of tests	Nov. 06, 2017 ~ Dec. 04, 2017

The tests have been carried out according to the requirements of the following standard:

☒ **FCC PART 24, Subpart E** ☒ **ANSI C63.26-2015**
☒ **ANSI/TIA/EIA-603-D** ☒ **ANSI/TIA/EIA-603-E**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Yuqiang Yin Engineer / Mobile Department	Approved by Bill Yao Manager / Mobile Department
 Date: Dec. 05, 2017	 Date: Dec. 05, 2017

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

TABLE OF CONTENTS

RELEASE CONTROL RECORD	4
1 SUMMARY OF TEST RESULTS.....	5
1.1 MEASUREMENT UNCERTAINTY	5
1.2 TEST SITE AND INSTRUMENTS	6
2 GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 CONFIGURATION OF SYSTEM UNDER TEST	11
2.3 DESCRIPTION OF SUPPORT UNITS.....	12
2.4 TEST ITEM AND TEST CONFIGURATION	12
2.5 EUT OPERATING CONDITIONS	18
2.6 GENERAL DESCRIPTION OF APPLIED STANDARDS	18
3 TEST TYPES AND RESULTS.....	19
3.1 OUTPUT POWER MEASUREMENT	19
3.1.1 LIMITS OF OUTPUT POWER MEASUREMENT	19
3.1.2 TEST PROCEDURES	19
3.1.3 TEST SETUP	20
3.1.4 TEST RESULTS	21
3.2 FREQUENCY STABILITY MEASUREMENT	48
3.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT	48
3.2.2 TEST PROCEDURE.....	48
3.2.3 TEST SETUP	48
3.2.4 TEST RESULTS	49
3.3 OCCUPIED BANDWIDTH MEASUREMENT	65
3.3.1 TEST PROCEDURES	65
3.3.2 TEST SETUP	65
3.3.3 TEST RESULTS	66
3.4 BAND EDGE MEASUREMENT	87
3.4.1 LIMITS OF BAND EDGE MEASUREMENT.....	87
3.4.2 TEST SETUP.....	87
3.4.3 TEST PROCEDURES	88
3.4.4. TEST RESULTS.....	89
3.5 CONDUCTED SPURIOUS EMISSIONS	103
3.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT.....	103
3.5.2 TEST PROCEDURE.....	103
3.5.3 TEST SETUP.....	103
3.5.4 TEST RESULTS	104
3.6 RADIATED EMISSION MEASUREMENT	120
3.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT	120
3.6.2 TEST PROCEDURES	120
3.6.3 DEVIATION FROM TEST STANDARD	120
3.6.4 TEST SETUP	121
3.6.5 TEST RESULTS	123
3.7 PEAK TO AVERAGE RATIO	181
3.7.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT.....	181
3.7.2 TEST SETUP.....	181
3.7.3 TEST PROCEDURES	181
3.7.4 TEST RESULTS	182



Test Report No.: RF170730W002-5

4	INFORMATION ON THE TESTING LABORATORIES	206
5	APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	207



Test Report No.: RF170730W002-5

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF170730W002-5	Original release	Dec. 05, 2017

1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 24 & Part 2			
STANDARD SECTION	TEST TYPE	RESULT	REMARK
2.1046 24.232	Equivalent Isotropic Radiated Power	PASS	Meet the requirement of limit.
2.1055 24.235	Frequency Stability	PASS	Meet the requirement of limit.
2.1049 24.238(b)	Occupied Bandwidth	PASS	Meet the requirement of limit.
24.232(d)	Peak to average ratio	PASS	Meet the requirement of limit.
24.238(b)	Band Edge Measurements	PASS	Meet the requirement of limit.
2.1051 24.238	Conducted Spurious Emissions	PASS	Meet the requirement of limit.
2.1053 24.238	Radiated Spurious Emissions	PASS	Meet the requirement of limit. Minimum passing margin is -20.18dB at 36.790MHz.

1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.66dB
Radiated emissions	9KHz ~ 30MHz	2.68dB
	30MHz ~ 1GHz	3.26dB
	1GHz ~ 18GHz	4.48dB
	18GHz ~ 40GHz	4.12dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

1.2 TEST SITE AND INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Mar. 01,17	Feb. 28,18
EXA Signal Analyzer	KEYSIGHT	N9010A-544	MY54510332	Mar. 01,17	Feb. 28,18
Bilog Antenna 1	ETS-LINDGREN	3143B	00161964	Nov. 26,16	Nov. 25,18
Bilog Antenna 2	ETS-LINDGREN	3143B	00161965	Nov. 26,16	Nov. 25,18
Horn Antenna 1	ETS-LINDGREN	3117	00168728	Nov. 26,16	Nov. 25,18
Horn Antenna 2	ETS-LINDGREN	3117	00168692	Nov. 26,16	Nov. 25,18
Loop antenna	Daze	ZN30900A	0708	Nov. 20,17	Nov. 19,18
Horn Antenna (18GHz-40GHz)	N/A	QWH-SL-18-40 -K-SG/QMS-00 361	15433	Dec. 16,16	Dec. 15,17
Radio Communication Analyzer	ANRITSU	MT8820C	6201465426	Mar. 01,17	Feb. 28,18
Signal Pre-Amplifier	EMSI	EMC 9135	980249	Jul. 24,17	Jul. 23,18
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	Jul. 24,17	Jul. 23,18
Signal Pre-Amplifier	EMSI	EMC 184045B	980259	Jul. 24,17	Jul. 23,18
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn- CT0001143-1216	May 06,17	May 05,18
Test Software	E3	V 9.160323	N/A	N/A	N/A
Test Software	ADT	ADT_Radiated _V7.6.15.9.2	N/A	N/A	N/A
10dB Attenuator	JFW/USA	50HF-010-SM A	1505	Jul. 24,17	Jul. 23,18
Power Meter	Anritsu	ML2495A	1506002	Mar. 01,17	Feb. 28,18
Power Sensor	Anritsu	MA2411B	1339352	Mar. 01,17	Feb. 28,18
Humid & Temp Programmable Tester	Juyi	ITH-120-45-CP -AR	IAA1504-001	Jul. 18,17	Jul. 17,18
MXG Analog Microwave Signal Generator	KEYSIGHT	N5183A	MY50143024	Mar. 01,17	Feb. 28,18

- NOTE:** 1. The calibration interval of the above test instruments is 12 months or 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in 3m Semi-anechoic Chamber and RF Oven Room.
3. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 525120.

2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Mobile Phone	
BRAND NAME	Sonim	
MODEL NAME	XP8800	
TYPE NUMBER	PC4011/PT4000	
POWER SUPPLY	5/9Vdc (adapter or host equipment) 3.85Vdc (Li-ion, battery)	
MODULATION TYPE	GSM, GPRS: GMSK EDGE: GMSK, 8PSK WCDMA : BPSK CDMA : GMSK LTE Band 2: QPSK, 16QAM, 64QAM	
FREQUENCY RANGE	GSM, GPRS, EDGE	1850.2MHz ~ 1909.8MHz
	WCDMA	1852.4MHz ~ 1907.6MHz
	CDMA BC1	1851.25MHz ~ 1908.75MHz
	LTE Band 2 Channel Bandwidth: 1.4MHz	1850.7MHz ~ 1909.3MHz
	LTE Band 2 Channel Bandwidth: 3MHz	1851.5MHz ~ 1908.5MHz
	LTE Band 2 Channel Bandwidth: 5MHz	1852.5MHz ~ 1907.5MHz
	LTE Band 2 Channel Bandwidth: 10MHz	1855.0MHz ~ 1905.0MHz
	LTE Band 2 Channel Bandwidth: 15MHz	1857.5MHz ~ 1902.5MHz
	LTE Band 2 Channel Bandwidth: 20MHz	1860.0MHz ~ 1900.0MHz
	LTE Band 25 Channel Bandwidth: 1.4MHz	1850.7MHz ~ 1914.3MHz
	LTE Band 25 Channel Bandwidth: 3MHz	1851.5MHz ~ 1913.5MHz
	LTE Band 25 Channel Bandwidth: 5MHz	1852.5MHz ~ 1912.5MHz
	LTE Band 25 Channel Bandwidth: 10MHz	1855MHz ~ 1910MHz
	LTE Band 25 Channel Bandwidth: 15MHz	1857.5MHz ~ 1907.5MHz
	LTE Band 25 Channel Bandwidth: 20MHz	1860MHz ~ 1905MHz

MAX. EIRP POWER	GSM	490mW
	EDGE	494mW
	WCDMA	238mW
	CDMA BC1	544mW
	LTE Band 2 Channel Bandwidth: 1.4MHz	247mW
	LTE Band 2 Channel Bandwidth: 3MHz	250mW
	LTE Band 2 Channel Bandwidth: 5MHz	248mW
	LTE Band 2 Channel Bandwidth: 10MHz	248mW
	LTE Band 2 Channel Bandwidth: 15MHz	240mW
	LTE Band 2 Channel Bandwidth: 20MHz	209mW
	LTE Band 25 Channel Bandwidth: 1.4MHz	294mW
	LTE Band 25 Channel Bandwidth: 3MHz	295mW
	LTE Band 25 Channel Bandwidth: 5MHz	298mW
	LTE Band 25 Channel Bandwidth: 10MHz	304mW
	LTE Band 25 Channel Bandwidth: 15MHz	290mW
	LTE Band 25 Channel Bandwidth: 20MHz	249mW
EMISSION DESIGNATOR	GSM	246KGXW
	EDGE	244KG7W
	WCDMA	4M15F9W
	CDMA BC1	1M27F9W
	LTE Band 2 Channel Bandwidth: 1.4MHz	QPSK: 1M09G7D
		16QAM: 1M08W7D
		64QAM: 1M08W7D
	LTE Band 2 Channel Bandwidth: 3MHz	QPSK: 2M69G7D
		16QAM: 2M68W7D
		64QAM: 2M68W7D

EMISSION DESIGNATOR	LTE Band 2 Channel Bandwidth: 5MHz	QPSK: 4M48G7D
		16QAM: 4M47W7D
		64QAM: 4M48W7D
	LTE Band 2 Channel Bandwidth: 10MHz	QPSK: 8M95G7D
		16QAM: 8M95W7D
		64QAM: 8M95W7D
	LTE Band 2 Channel Bandwidth: 15MHz	QPSK: 13M4G7D
		16QAM: 13M4W7D
		64QAM: 13M4W7D
	LTE Band 2 Channel Bandwidth: 20MHz	QPSK: 17M9G7D
		16QAM: 17M8W7D
		64QAM: 17M9W7D
	LTE Band 25 Channel Bandwidth: 1.4MHz	QPSK: 1M09G7D
		16QAM: 1M09W7D
		64QAM: 1M09W7D
	LTE Band 25 Channel Bandwidth: 3MHz	QPSK: 2M69G7D
		16QAM: 2M69W7D
		64QAM: 2M69W7D
	LTE Band 25 Channel Bandwidth: 5MHz	QPSK: 4M49G7D
		16QAM: 4M47W7D
		64QAM: 4M49W7D
	LTE Band 25 Channel Bandwidth: 10MHz	QPSK: 8M95G7D
		16QAM: 8M95W7D
		64QAM: 8M94W7D
	LTE Band 25 Channel Bandwidth: 15MHz	QPSK: 13M4G7D
		16QAM: 13M4W7D
		64QAM: 13M4W7D
	LTE Band 25 Channel Bandwidth: 20MHz	QPSK: 17M9G7D
		16QAM: 17M9W7D
		64QAM: 17M9W7D
ANTENNA TYPE	Fixed Internal antenna	
ANTENNA GAIN	-1dBi gain for GSM1900/ WCDMA Band 2/LTE Band 2 -2dBi gain for CDMA BC1	
HW VERSION	A	
SW VERSION	8A.0.0-00-7.1.1-00.01.26	
I/O PORTS	Refer to user's manual	
CABLE SUPPLIED	USB cable 1: With shield, detachable, 1.5meter USB cable 2: non-shielded, detachable, 1.0meter	

NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. The EUT was powered by the following adapter:

ADAPTER	
BRAND:	Sonim
MODEL:	S42A02
INPUT:	AC 100-240V, 500mA
OUTPUT:	DC 5V, 1500mA DC 9V, 1500mA DC 12V,1100mA

3. The EUT matched the following USB cables:


USB CABLE 1	
BRAND:	N/A
MODEL:	N/A
SIGNAL LINE:	1.5 METER

USB CABLE 2	
BRAND:	N/A
MODEL:	N/A
SIGNAL LINE:	1.0 METER


4. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

2.2 CONFIGURATION OF SYSTEM UNDER TEST

FOR RADIATION EMISSION TEST



FOR CONDUCTED & E.I.R.P. TEST



2.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	DC source	LONG WEI	PS-6403D	010934269	N/A
2	PC	HP	A6608CN	3CR83825X3	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	DC Line: Unshielded, Detachable 1.0m
2	AC Line: Unshielded, Detachable 1.5m

NOTE:

1. All power cords of the above support units are non shielded (1.8m).

2.4 TEST ITEM AND TEST CONFIGURATION

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports

The worst case in EIRP and radiated emission was found when positioned on X-plane for GSM/EDGE/WCDMA/CDMA/LTE. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	DESCRIPTION
A	EUT + Adapter + USB Cable with GSM, WCDMA, CDMA or LTE link
B	EUT + Battery with GSM, WCDMA, CDMA or LTE link

GSM MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
B	EIRP	512 to 810	512, 661, 810	GSM, EDGE
B	FREQUENCY STABILITY	512 to 810	512, 810	GSM, EDGE
B	OCCUPIED BANDWIDTH	512 to 810	512, 661, 810	GSM, EDGE
B	PEAK TO AVERAGE RATIO	512 to 810	512, 661, 810	GSM, EDGE
B	BAND EDGE	512 to 810	512, 810	GSM, EDGE
B	CONDUCTED EMISSION	512 to 810	512, 661, 810	GSM, EDGE
A	RADIATED EMISSION	512 to 810	512, 661, 810	GSM, EDGE

WCDMA MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
B	EIRP	9262 to 9538	9262, 9400, 9538	WCDMA
B	FREQUENCY STABILITY	9262 to 9538	9262, 9538	WCDMA
B	OCCUPIED BANDWIDTH	9262 to 9538	9262, 9400, 9538	WCDMA
B	PEAK TO AVERAGE RATIO	9262 to 9538	9262, 9400, 9538	WCDMA
B	BAND EDGE	9262 to 9538	9262, 9538	WCDMA
B	CONDCUDED EMISSION	9262 to 9538	9262, 9400, 9538	WCDMA
A	RADIATED EMISSION	9262 to 9538	9262, 9400, 9538	WCDMA

CDMA BC 1 MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
B	ERP	25 to 1175	25, 600, 1175	CDMA BC 1
B	FREQUENCY STABILITY	25 to 1175	25, 1175	CDMA BC 1
B	OCCUPIED BANDWIDTH	25 to 1175	25, 600, 1175	CDMA BC 1
B	PEAK TO AVERAGE RATIO	25 to 1175	25, 600, 1175	CDMA BC 1
B	BAND EDGE	25 to 1175	25, 1175	CDMA BC 1
B	CONDCUDED EMISSION	25 to 1175	25, 600, 1175	CDMA BC 1
A	RADIATED EMISSION	25 to 1175	25, 600, 1175	CDMA BC 1

LTE BAND 2 MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	CHANNEL BANDWIDTH	MODULATION	MODE
B	EIRP	18607 to 19193	18607, 18900, 19193	1.4MHz	QPSK,16QAM, 64QAM	1 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3MHz	QPSK,16QAM, 64QAM	1 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5MHz	QPSK,16QAM, 64QAM	1 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10MHz	QPSK,16QAM, 64QAM	1 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15MHz	QPSK,16QAM, 64QAM	1 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20MHz	QPSK,16QAM, 64QAM	1 RB / 0 RB Offset
B	FREQUENCY STABILITY	18607 to 19193	18607, 19193	1.4MHz	QPSK	1 RB / 0 RB Offset
		18615 to 19185	18615, 19185	3MHz	QPSK	1 RB / 0 RB Offset
		18625 to 19175	18625, 19175	5MHz	QPSK	1 RB / 0 RB Offset
		18650 to 19150	18650, 19150	10MHz	QPSK	1 RB / 0 RB Offset
		18675 to 19125	18675, 19125	15MHz	QPSK	1 RB / 0 RB Offset
		18700 to 19100	18700, 19100	20MHz	QPSK	1 RB / 0 RB Offset
B	OCCUPIED BANDWIDTH	18607 to 19193	18607, 18900, 19193	1.4MHz	QPSK,16QAM, 64QAM	6 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3MHz	QPSK,16QAM, 64QAM	15 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5MHz	QPSK,16QAM, 64QAM	25 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10MHz	QPSK,16QAM, 64QAM	50 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15MHz	QPSK,16QAM, 64QAM	75 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20MHz	QPSK,16QAM, 64QAM	100 RB / 0 RB Offset
B	PEAK TO AVERAGE RATIO	18607 to 19193	18607, 18900, 19193	1.4MHz	QPSK,16QAM, 64QAM	1 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3MHz	QPSK,16QAM, 64QAM	1 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5MHz	QPSK,16QAM, 64QAM	1 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10MHz	QPSK,16QAM, 64QAM	1 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15MHz	QPSK,16QAM, 64QAM	1 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20MHz	QPSK,16QAM, 64QAM	1 RB / 0 RB Offset

B	BAND EDGE	18607 to 19193	18607	1.4MHz	QPSK	1 RB / 0 RB Offset
			19193	1.4MHz	QPSK	6 RB / 0 RB Offset
		18615 to 19185	18615	3MHz	QPSK	1 RB / 5 RB Offset
			19185	3MHz	QPSK	6 RB / 0 RB Offset
		18625 to 19175	18625	5MHz	QPSK	1 RB / 0 RB Offset
			19175	5MHz	QPSK	15 RB / 0 RB Offset
		18650 to 19150	18650	10MHz	QPSK	1 RB / 14 RB Offset
			19150	10MHz	QPSK	15 RB / 0 RB Offset
		18675 to 19125	18675	15MHz	QPSK	1 RB / 0 RB Offset
			19125	15MHz	QPSK	25 RB / 0 RB Offset
		18700 to 19100	18700	20MHz	QPSK	1 RB / 24 RB Offset
			19100	20MHz	QPSK	25 RB / 0 RB Offset
B	CONDCUDED EMISSION	18607 to 19193	18607, 18900, 19193	1.4MHz	QPSK	1 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3MHz	QPSK	1 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5MHz	QPSK	1 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10MHz	QPSK	1 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15MHz	QPSK	1 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20MHz	QPSK	1 RB / 0 RB Offset
A	RADIATED EMISSION	18607 to 19193	18900	1.4MHz	QPSK	1 RB / 0 RB Offset
		18615 to 19185	18900	3MHz	QPSK	1 RB / 0 RB Offset
		18625 to 19175	18900	5MHz	QPSK	1 RB / 0 RB Offset
		18650 to 19150	18900	10MHz	QPSK	1 RB / 0 RB Offset
		18675 to 19125	18900	15MHz	QPSK	1 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20MHz	QPSK	1 RB / 0 RB Offset

LTE BAND 25 MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	CHANNEL BANDWIDTH	MODULATION	MODE
B	EIRP	26047 to 26683	26047, 26365, 26683	1.4MHz	QPSK,16QAM, 64QAM	1 RB / 0 RB Offset
		26055 to 26675	26055, 26365, 26675	3MHz	QPSK,16QAM, 64QAM	1 RB / 0 RB Offset
		26065 to 26665	26065, 26365, 26665	5MHz	QPSK,16QAM, 64QAM	1 RB / 0 RB Offset
		26090 to 26640	26090, 26365 26640	10MHz	QPSK,16QAM, 64QAM	1 RB / 0 RB Offset
		26115 to 26615	26115, 26365, 26615	15MHz	QPSK,16QAM, 64QAM	1 RB / 0 RB Offset
		26140 to 26590	26140, 26365, 26590	20MHz	QPSK,16QAM, 64QAM	1 RB / 0 RB Offset
B	FREQUENCY STABILITY	26047 to 26683	26047, 26683	1.4MHz	QPSK	1 RB / 0 RB Offset
		26055 to 26675	26055, 26675	3MHz	QPSK	1 RB / 0 RB Offset
		26065 to 26665	26065, 26665	5MHz	QPSK	1 RB / 0 RB Offset
		26090 to 26640	26090, 26640	10MHz	QPSK	1 RB / 0 RB Offset
		26115 to 26615	26115, 26615	15MHz	QPSK	1 RB / 0 RB Offset
		26140 to 26590	26140, 26590	20MHz	QPSK	1 RB / 0 RB Offset
B	OCCUPIED BANDWIDTH	26047 to 26683	26047, 26365, 26683	1.4MHz	QPSK,16QAM, 64QAM	6 RB / 0 RB Offset
		26055 to 26675	26055, 26365, 26675	3MHz	QPSK,16QAM, 64QAM	15 RB / 0 RB Offset
		26065 to 26665	26065, 26365, 26665	5MHz	QPSK,16QAM, 64QAM	25 RB / 0 RB Offset
		26090 to 26640	26090, 26365 26640	10MHz	QPSK,16QAM, 64QAM	50 RB / 0 RB Offset
		26115 to 26615	26115, 26365, 26615	15MHz	QPSK,16QAM, 64QAM	75 RB / 0 RB Offset
		26140 to 26590	26140, 26365, 26590	20MHz	QPSK,16QAM, 64QAM	100 RB / 0 RB Offset
B	PEAK TO AVERAGE RATIO	26047 to 26683	26047, 26365, 26683	1.4MHz	QPSK,16QAM, 64QAM	1 RB / 0 RB Offset
		26055 to 26675	26055, 26365, 26675	3MHz	QPSK,16QAM, 64QAM	1 RB / 0 RB Offset
		26065 to 26665	26065, 26365, 26665	5MHz	QPSK,16QAM, 64QAM	1 RB / 0 RB Offset
		26090 to 26640	26090, 26365 26640	10MHz	QPSK,16QAM, 64QAM	1 RB / 0 RB Offset
		26115 to 26615	26115, 26365, 26615	15MHz	QPSK,16QAM, 64QAM	1 RB / 0 RB Offset
		26140 to 26590	26140, 26365, 26590	20MHz	QPSK,16QAM, 64QAM	1 RB / 0 RB Offset



B	BAND EDGE	26047 to 26683	26047	1.4MHz	QPSK	1 RB / 0 RB Offset
			26683	1.4MHz	QPSK	1 RB / 5 RB Offset
		26055 to 26675	26055	3MHz	QPSK	1 RB / 0 RB Offset
			26675	3MHz	QPSK	1 RB / 14 RB Offset
		26065 to 26665	26065	5MHz	QPSK	1 RB / 0 RB Offset
			26665	5MHz	QPSK	1 RB / 24 RB Offset
		26090 to 26640	26090	10MHz	QPSK	1 RB / 0 RB Offset
			26640	10MHz	QPSK	1 RB / 49 RB Offset
26115 to 26615	26115	15MHz	QPSK	1 RB / 0 RB Offset		
					75 RB / 0 RB Offset	
	26615	15MHz	QPSK	1 RB / 74 RB Offset		
					75 RB / 0 RB Offset	
26140 to 26590	26140	20MHz	QPSK	1 RB / 0 RB Offset		
					100 RB / 0 RB Offset	
B	CONDCUDED EMISSION	26047 to 26683	26047, 26365, 26683	1.4MHz	QPSK	1 RB / 0 RB Offset
		26055 to 26675	26055, 26365, 26675	3MHz	QPSK	1 RB / 0 RB Offset
		26065 to 26665	26065, 26365, 26665	5MHz	QPSK	1 RB / 0 RB Offset
		26090 to 26640	26090, 26365 26640	10MHz	QPSK	1 RB / 0 RB Offset
		26115 to 26615	26115, 26365, 26615	15MHz	QPSK	1 RB / 0 RB Offset
		26140 to 26590	26140, 26365, 26590	20MHz	QPSK	1 RB / 0 RB Offset
A	RADIATED EMISSION	26047 to 26683	26047, 26365, 26683	1.4MHz	QPSK	1 RB / 0 RB Offset
		26055 to 26675	26365	3MHz	QPSK	1 RB / 0 RB Offset
		26065 to 26665	26365	5MHz	QPSK	1 RB / 0 RB Offset
		26090 to 26640	26365	10MHz	QPSK	1 RB / 0 RB Offset
		26115 to 26615	26365	15MHz	QPSK	1 RB / 0 RB Offset
		26140 to 26590	26365	20MHz	QPSK	1 RB / 0 RB Offset

TEST ITEM	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
EIRP	25deg. C, 57%RH	3.85Vdc from Battery	Simon Yang
FREQUENCY STABILITY	23deg. C, 61%RH	DC 3.5V/3.85V/4.2V	Wenliang Wu
OCCUPIED BANDWIDTH	23deg. C, 61%RH	3.85Vdc from Battery	Wenliang Wu
PEAK TO AVERAGE RATIO	23deg. C, 61%RH	3.85Vdc from Battery	Wenliang Wu
BAND EDGE	23deg. C, 61%RH	3.85Vdc from Battery	Wenliang Wu
CONDCUDETED EMISSION	23deg. C, 61%RH	3.85Vdc from Battery	Wenliang Wu
RADIATED EMISSION	23deg. C, 70%RH	DC 5/9V from adaptor	Simon Yang



2.5 EUT OPERATING CONDITIONS

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

2.6 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 24

KDB 971168 D01 Power Meas License Digital Systems v03

ANSI/TIA/EIA-603-D

ANSI/TIA/EIA-603-E

ANSI C63.26-2015

NOTE: All test items have been performed and recorded as per the above standards.



3 TEST TYPES AND RESULTS

3.1 OUTPUT POWER MEASUREMENT

3.1.1 LIMITS OF OUTPUT POWER MEASUREMENT

Mobile and portable stations are limited to 2 watts EIRP.

3.1.2 TEST PROCEDURES

EIRP MEASUREMENT:

- a. All measurements were done at low, middle and high operational frequency range. RBW and VBW is 1MHz for GSM, GPRS, EDGE & CDMA, 5MHz for WCDMA mode and 10MHz for LTE mode.
- b. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- c. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a tx cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value " of step b. Record the power level of S.G
- d. $EIRP = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}.$


CONDUCTED POWER MEASUREMENT:

The EUT was set up for the maximum power with GSM, GPRS, EDGE & WCDMA link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.




3.1.3 TEST SETUP

ERP MEASUREMENT:




EIRP MEASUREMENT:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

CONDUCTED POWER MEASUREMENT:



For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.1.4 TEST RESULTS

CONDUCTED OUTPUT POWER (dBm)

Band	GSM1900		
Channel	512	661	810
Frequency (MHz)	1850.2	1880.0	1909.8
GSM	29.91	29.85	29.69
GPRS 8	29.90	29.84	29.68
GPRS 10	29.79	29.73	29.57
GPRS 11	29.65	29.59	29.43
GPRS 12	29.47	29.41	29.25
EDGE 8 (MCS9)	25.20	25.14	24.98
EDGE 10 (MCS9)	24.99	24.93	24.77
EDGE 11 (MCS9)	24.78	24.72	24.56
EDGE 12 (MCS9)	24.57	24.51	24.35

Band	WCDMA II		
Channel	9262	9400	9538
Frequency (MHz)	1852.4	1880.0	1907.6
RMC 12.2K	24.31	24.23	24.29
HSPA			
HSDPA Subtest-1	22.82	22.74	22.80
HSDPA Subtest-2	22.81	22.73	22.79
HSDPA Subtest-3	22.15	22.07	22.13
HSDPA Subtest-4	22.13	22.05	22.11
HSUPA Subtest-1	23.25	23.17	23.23
HSUPA Subtest-2	21.07	20.99	21.05
HSUPA Subtest-3	22.11	22.03	22.09
HSUPA Subtest-4	21.06	20.98	21.04
HSUPA Subtest-5	23.21	23.13	23.19

Band	CDMA2000 BC1		
Channel	1013	384	777
Frequency (MHz)	1851.25	1880	1908.75
RC1+SO55	24.56	24.42	24.51
RC3+SO55	24.58	24.44	24.53
RC3+SO32(FCH)	24.61	24.47	24.56
RC3+SO32(SCH)	24.57	24.43	24.52
RTAP 153.6	24.50	24.36	24.45
RETAP 4096	24.38	24.24	24.33
RC1+SO3	24.70	24.65	24.66
RC3+SO3	24.48	24.44	24.42

LTE Band 2							
BW	Modulation	RB Size	RB Offset	Low CH 18607	Mid CH 18900	High CH 19193	3GPP MPR (dB)
				Frequency 1850.7 MHz	Frequency 1880 MHz	Frequency 1909.3 MHz	
1.4MHz	QPSK	1	0	23.49	23.38	23.41	0
		1	2	23.37	23.26	23.29	0
		1	5	23.26	23.15	23.18	0
		3	0	23.48	23.37	23.40	0
		3	1	23.36	23.25	23.28	0
		3	3	23.25	23.14	23.17	0
		6	0	22.52	22.41	22.44	1
	16QAM	1	0	22.75	22.64	22.67	1
		1	2	22.71	22.60	22.63	1
		1	5	22.68	22.57	22.60	1
		3	0	22.73	22.62	22.65	1
		3	1	22.69	22.58	22.61	1
		3	3	22.66	22.55	22.58	1
		6	0	21.56	21.45	21.48	2
	64QAM	1	0	21.67	21.56	21.59	2
		1	2	21.64	21.53	21.56	2
		1	5	21.59	21.48	21.51	2
		3	0	20.47	20.36	20.39	3
		3	1	20.44	20.33	20.36	3
		3	3	20.40	20.29	20.32	3
		6	0	20.45	20.34	20.37	3

LTE Band 2							
BW	Modulation	RB Size	RB Offset	Low CH 18615	Mid CH 18900	High CH 19185	3GPP MPR (dB)
				Frequency 1851.5 MHz	Frequency 1880 MHz	Frequency 1908.5 MHz	
3MHz	QPSK	1	0	23.52	23.41	23.44	0
		1	7	23.40	23.29	23.32	0
		1	14	23.29	23.18	23.21	0
		8	0	22.66	22.55	22.58	1
		8	3	22.61	22.50	22.53	1
		8	7	22.58	22.47	22.50	1
		15	0	22.55	22.44	22.47	1
	16QAM	1	0	22.78	22.67	22.70	1
		1	7	22.74	22.63	22.66	1
		1	14	22.71	22.60	22.63	1
		8	0	21.71	21.60	21.63	2
		8	3	21.68	21.57	21.60	2
		8	7	21.64	21.53	21.56	2
		15	0	21.59	21.48	21.51	2
	64QAM	1	0	21.72	21.61	21.64	2
		1	7	21.69	21.58	21.61	2
		1	14	21.64	21.53	21.56	2
		8	0	20.52	20.41	20.44	3
		8	3	20.49	20.38	20.41	3
		8	7	20.45	20.34	20.37	3
		15	0	20.50	20.39	20.42	3

LTE Band 2							
BW	Modulation	RB Size	RB Offset	Low CH 18625	Mid CH 18900	High CH 19175	3GPP MPR (dB)
				Frequency 1852.5 MHz	Frequency 1880 MHz	Frequency 1907.5 MHz	
5MHz	QPSK	1	0	23.55	23.44	23.47	0
		1	12	23.43	23.32	23.35	0
		1	24	23.32	23.21	23.24	0
		12	0	22.69	22.58	22.61	1
		12	6	22.64	22.53	22.56	1
		12	13	22.61	22.50	22.53	1
		25	0	22.58	22.47	22.50	1
	16QAM	1	0	22.81	22.70	22.73	1
		1	12	22.77	22.66	22.69	1
		1	24	22.74	22.63	22.66	1
		12	0	21.74	21.63	21.66	2
		12	6	21.71	21.60	21.63	2
		12	13	21.67	21.56	21.59	2
		25	0	21.62	21.51	21.54	2
	64QAM	1	0	21.77	21.66	21.69	2
		1	12	21.74	21.63	21.66	2
		1	24	21.69	21.58	21.61	2
		12	0	20.57	20.46	20.49	3
		12	6	20.54	20.43	20.46	3
		12	13	20.50	20.39	20.42	3
		25	0	20.55	20.44	20.47	3

LTE Band 2							
BW	Modulation	RB Size	RB Offset	Low CH 18650	Mid CH 18900	High CH 19150	3GPP MPR (dB)
				Frequency 1855 MHz	Frequency 1880 MHz	Frequency 1905 MHz	
10MHz	QPSK	1	0	23.57	23.46	23.49	0
		1	24	23.45	23.34	23.37	0
		1	49	23.34	23.23	23.26	0
		25	0	22.71	22.60	22.63	1
		25	12	22.66	22.55	22.58	1
		25	25	22.63	22.52	22.55	1
		50	0	22.60	22.49	22.52	1
	16QAM	1	0	22.83	22.72	22.75	1
		1	24	22.79	22.68	22.71	1
		1	49	22.76	22.65	22.68	1
		25	0	21.76	21.65	21.68	2
		25	12	21.73	21.62	21.65	2
		25	25	21.69	21.58	21.61	2
		50	0	21.64	21.53	21.56	2
	64QAM	1	0	21.82	21.71	21.74	2
		1	24	21.79	21.68	21.71	2
		1	49	21.74	21.63	21.66	2
		25	0	20.62	20.51	20.54	3
		25	12	20.59	20.48	20.51	3
		25	25	20.55	20.44	20.47	3
		50	0	20.60	20.49	20.52	3

LTE Band 2							
BW	Modulation	RB Size	RB Offset	Low CH 18675	Mid CH 18900	High CH 19125	3GPP MPR (dB)
				Frequency 1857.5 MHz	Frequency 1880 MHz	Frequency 1902.5 MHz	
15MHz	QPSK	1	0	23.60	23.49	23.52	0
		1	37	23.48	23.37	23.40	0
		1	74	23.37	23.26	23.29	0
		36	0	22.74	22.63	22.66	1
		36	19	22.69	22.58	22.61	1
		36	39	22.66	22.55	22.58	1
		75	0	22.63	22.52	22.55	1
	16QAM	1	0	22.86	22.75	22.78	1
		1	37	22.82	22.71	22.74	1
		1	74	22.79	22.68	22.71	1
		36	0	21.79	21.68	21.71	2
		36	19	21.76	21.65	21.68	2
		36	39	21.72	21.61	21.64	2
		75	0	21.67	21.56	21.59	2
	64QAM	1	0	21.87	21.76	21.79	2
		1	37	21.84	21.73	21.76	2
		1	74	21.79	21.68	21.71	2
		36	0	20.67	20.56	20.59	3
		36	19	20.64	20.53	20.56	3
		36	39	20.60	20.49	20.52	3
		75	0	20.65	20.54	20.57	3

LTE Band 2							
BW	Modulation	RB Size	RB Offset	Low CH 18700	Mid CH 18900	High CH 19100	3GPP MPR (dB)
				Frequency 1860 MHz	Frequency 1880 MHz	Frequency 1900 MHz	
20MHz	QPSK	1	0	23.65	23.54	23.57	0
		1	50	23.53	23.42	23.45	0
		1	99	23.42	23.31	23.34	0
		50	0	22.79	22.68	22.71	1
		50	25	22.74	22.63	22.66	1
		50	50	22.71	22.60	22.63	1
		100	0	22.68	22.57	22.60	1
	16QAM	1	0	22.91	22.80	22.83	1
		1	50	22.87	22.76	22.79	1
		1	99	22.84	22.73	22.76	1
		50	0	21.84	21.73	21.76	2
		50	25	21.81	21.70	21.73	2
		50	50	21.77	21.66	21.69	2
		100	0	21.72	21.61	21.64	2
	64QAM	1	0	21.92	21.81	21.84	2
		1	50	21.89	21.78	21.81	2
		1	99	21.84	21.73	21.76	2
		50	0	20.72	20.61	20.64	3
		50	25	20.69	20.58	20.61	3
		50	50	20.65	20.54	20.57	3
		100	0	20.70	20.59	20.62	3

LTE Band 25							
BW	Modulation	RB Size	RB Offset	Low CH 26047	Mid CH 26365	High CH 26683	3GPP MPR (dB)
				Frequency 1850.7 MHz	Frequency 1882.5 MHz	Frequency 1914.3 MHz	
1.4MHz	QPSK	1	0	23.40	23.46	23.43	0
		1	2	23.35	23.41	23.38	0
		1	5	23.32	23.38	23.35	0
		3	0	22.47	22.53	22.50	0
		3	1	22.43	22.49	22.46	0
		3	3	22.38	22.44	22.41	0
		6	0	22.48	22.54	22.51	1
	16QAM	1	0	22.68	22.74	22.71	1
		1	2	22.64	22.70	22.67	1
		1	5	22.60	22.66	22.63	1
		3	0	21.52	21.58	21.55	1
		3	1	21.48	21.54	21.51	1
		3	3	21.44	21.50	21.47	1
		6	0	21.49	21.55	21.52	2
	64QAM	1	0	21.52	21.58	21.55	2
		1	2	21.48	21.54	21.51	2
		1	5	21.44	21.50	21.47	2
		3	0	20.50	20.56	20.53	3
		3	1	20.47	20.53	20.50	3
		3	3	20.44	20.50	20.47	3
		6	0	20.48	20.54	20.51	3

LTE Band 25							
BW	Modulation	RB Size	RB Offset	Low CH 26055	Mid CH 26365	High CH 26675	3GPP MPR (dB)
				Frequency 1851.5 MHz	Frequency 1882.5 MHz	Frequency 1913.5 MHz	
3MHz	QPSK	1	0	23.43	23.49	23.46	0
		1	7	23.38	23.44	23.41	0
		1	14	23.35	23.41	23.38	0
		8	0	22.50	22.56	22.53	1
		8	3	22.46	22.52	22.49	1
		8	7	22.41	22.47	22.44	1
		15	0	22.51	22.57	22.54	1
	16QAM	1	0	22.71	22.77	22.74	1
		1	7	22.67	22.73	22.70	1
		1	14	22.63	22.69	22.66	1
		8	0	21.55	21.61	21.58	2
		8	3	21.51	21.57	21.54	2
		8	7	21.47	21.53	21.50	2
		15	0	21.52	21.58	21.55	2
	64QAM	1	0	21.55	21.61	21.58	2
		1	7	21.51	21.57	21.54	2
		1	14	21.47	21.53	21.50	2
		8	0	20.53	20.59	20.56	3
		8	3	20.50	20.56	20.53	3
		8	7	20.47	20.53	20.50	3
		15	0	20.51	20.57	20.54	3

LTE Band 25							
BW	Modulation	RB Size	RB Offset	Low CH 26065	Mid CH 26365	High CH 26665	3GPP MPR (dB)
				Frequency 1852.5 MHz	Frequency 1882.5 MHz	Frequency 1912.5 MHz	
5MHz	QPSK	1	0	23.46	23.52	23.49	0
		1	12	23.41	23.47	23.44	0
		1	24	23.38	23.44	23.41	0
		12	0	22.53	22.59	22.56	1
		12	6	22.49	22.55	22.52	1
		12	13	22.44	22.50	22.47	1
		25	0	22.54	22.60	22.57	1
	16QAM	1	0	22.74	22.80	22.77	1
		1	12	22.70	22.76	22.73	1
		1	24	22.66	22.72	22.69	1
		12	0	21.58	21.64	21.61	2
		12	6	21.54	21.60	21.57	2
		12	13	21.50	21.56	21.53	2
		25	0	21.55	21.61	21.58	2
	64QAM	1	0	21.58	21.64	21.61	2
		1	12	21.54	21.60	21.57	2
		1	24	21.50	21.56	21.53	2
		12	0	20.56	20.62	20.59	3
		12	6	20.53	20.59	20.56	3
		12	13	20.50	20.56	20.53	3
		25	0	20.54	20.60	20.57	3

LTE Band 25							
BW	Modulation	RB Size	RB Offset	Low CH 26090	Mid CH 26365	High CH 26640	3GPP MPR (dB)
				Frequency 1855 MHz	Frequency 1882.5 MHz	Frequency 1910 MHz	
10MHz	QPSK	1	0	23.48	23.54	23.51	0
		1	24	23.43	23.49	23.46	0
		1	49	23.40	23.46	23.43	0
		25	0	22.55	22.61	22.58	1
		25	12	22.51	22.57	22.54	1
		25	25	22.46	22.52	22.49	1
		50	0	22.56	22.62	22.59	1
	16QAM	1	0	22.76	22.82	22.79	1
		1	24	22.72	22.78	22.75	1
		1	49	22.68	22.74	22.71	1
		25	0	21.60	21.66	21.63	2
		25	12	21.56	21.62	21.59	2
		25	25	21.52	21.58	21.55	2
		50	0	21.57	21.63	21.60	2
	64QAM	1	0	21.63	21.69	21.66	2
		1	24	21.59	21.65	21.62	2
		1	49	21.55	21.61	21.58	2
		25	0	20.61	20.67	20.64	3
		25	12	20.58	20.64	20.61	3
		25	25	20.55	20.61	20.58	3
		50	0	20.59	20.65	20.62	3

LTE Band 25							
BW	Modulation	RB Size	RB Offset	Low CH 26115	Mid CH 26365	High CH 26615	3GPP MPR (dB)
				Frequency 1857.5 MHz	Frequency 1882.5 MHz	Frequency 1907.5 MHz	
15MHz	QPSK	1	0	23.50	23.56	23.53	0
		1	37	23.45	23.51	23.48	0
		1	74	23.42	23.48	23.45	0
		36	0	22.57	22.63	22.60	1
		36	19	22.53	22.59	22.56	1
		36	39	22.48	22.54	22.51	1
		75	0	22.58	22.64	22.61	1
	16QAM	1	0	22.78	22.84	22.81	1
		1	37	22.74	22.80	22.77	1
		1	74	22.70	22.76	22.73	1
		36	0	21.62	21.68	21.65	2
		36	19	21.58	21.64	21.61	2
		36	39	21.54	21.60	21.57	2
		75	0	21.59	21.65	21.62	2
	64QAM	1	0	21.68	21.74	21.71	2
		1	37	21.64	21.70	21.67	2
		1	74	21.60	21.66	21.63	2
		36	0	20.66	20.72	20.69	3
		36	19	20.63	20.69	20.66	3
		36	39	20.60	20.66	20.63	3
		75	0	20.64	20.70	20.67	3

LTE Band 25							
BW	Modulation	RB Size	RB Offset	Low CH 26140	Mid CH 26365	High CH 26590	3GPP MPR (dB)
				Frequency 1860 MHz	Frequency 1882.5 MHz	Frequency 1905 MHz	
20MHz	QPSK	1	0	23.53	23.59	23.56	0
		1	50	23.48	23.54	23.51	0
		1	99	23.45	23.51	23.48	0
		50	0	22.60	22.66	22.63	1
		50	25	22.56	22.62	22.59	1
		50	50	22.51	22.57	22.54	1
		100	0	22.61	22.67	22.64	1
	16QAM	1	0	22.81	22.87	22.84	1
		1	50	22.77	22.83	22.80	1
		1	99	22.73	22.79	22.76	1
		50	0	21.65	21.71	21.68	2
		50	25	21.61	21.67	21.64	2
		50	50	21.57	21.63	21.60	2
		100	0	21.62	21.68	21.65	2
	64QAM	1	0	21.73	21.79	21.76	2
		1	50	21.69	21.75	21.72	2
		1	99	21.65	21.71	21.68	2
		50	0	20.71	20.77	20.74	3
		50	25	20.68	20.74	20.71	3
		50	50	20.65	20.71	20.68	3
		100	0	20.69	20.75	20.72	3



EIRP POWER (dBm)

GSM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
512	1850.2	-18.97	43.83	24.86	306.20	H
661	1880.0	-18.45	43.57	25.12	325.09	H
810	1909.8	-18.42	44.57	26.15	412.10	H
512	1850.2	-20.24	46.39	26.15	412.10	V
661	1880.0	-20.41	47.10	26.69	466.44	V
810	1909.8	-19.07	45.98	26.91	490.46	V

REMARKS: 1. EIRP Output Power (dBm) = SPA LVL (dBm) + Correction Factor (dB).
2. Correction factor (dB) = Free Space Loss + Antenna Factor + Cable Loss

EDGE

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
512	1850.2	-20.33	43.83	23.50	223.87	H
661	1880.0	-19.48	43.57	24.09	256.45	H
810	1909.8	-19.75	44.57	24.82	303.39	H
512	1850.2	-20.56	46.39	25.83	382.82	V
661	1880.0	-20.16	47.10	26.94	494.08	V
810	1909.8	-20.63	45.98	25.35	342.45	V

REMARKS: 1. EIRP Output Power (dBm) = SPA LVL (dBm) + Correction Factor (dB).
2. Correction factor (dB) = Free Space Loss + Antenna Factor + Cable Loss

WCDMA

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)
9262	1852.4	-21.68	43.83	22.15	164.06	H
9400	1880.0	-21.05	43.57	22.52	178.65	H
9538	1907.6	-20.92	44.57	23.65	231.74	H
9262	1852.4	-23.98	46.39	22.41	174.18	V
9400	1880.0	-23.34	47.10	23.76	237.57	V
9538	1907.6	-23.02	45.98	22.96	197.51	V

REMARKS: 1. EIRP Output Power (dBm) = SPA LVL (dBm) + Correction Factor (dB).
2. Correction factor (dB) = Free Space Loss + Antenna Factor + Cable Loss



CDMA BC 1

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	ERP(dBm)	ERP(mW)	Polarization (H/V)
25	1851.3	-17.56	43.83	26.27	423.64	H
600	1880.0	-17.69	43.57	25.88	387.26	H
1175	1908.8	-17.96	44.57	26.61	458.14	H
25	1851.3	-19.12	46.39	27.27	533.33	V
600	1880.0	-19.74	47.10	27.36	544.25	V
1175	1908.8	-20.05	45.98	25.93	391.38	V

REMARKS: 1. ERP Output Power (dBm) = SPA LVL (dBm) + Correction Factor (dB) -2.15(dB).
2. Correction factor (dB) = Free Space Loss + Antenna Factor + Cable Loss

LTE BAND 2

CHANNEL BANDWIDTH: 1.4MHz QPSK

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
18607	1850.7	-20.34	43.83	23.50	223.82	H	2
18900	1880.0	-20.36	43.57	23.21	209.51	H	2
19193	1909.3	-20.79	44.32	23.53	225.37	H	2
18607	1850.7	-22.48	46.41	23.93	247.00	V	2
18900	1880.0	-23.41	47.07	23.66	232.49	V	2
19193	1909.3	-22.79	45.88	23.09	203.80	V	2

CHANNEL BANDWIDTH: 1.4MHz 16QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
18607	1850.7	-21.21	43.83	22.63	183.19	H	2
18900	1880.0	-21.29	43.57	22.28	169.12	H	2
19193	1909.3	-21.75	44.32	22.57	180.68	H	2
18607	1850.7	-23.35	46.41	23.06	202.16	V	2
18900	1880.0	-24.34	47.07	22.73	187.67	V	2
19193	1909.3	-23.75	45.88	22.13	163.38	V	2

CHANNEL BANDWIDTH: 1.4MHZ 64QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
18607	1850.7	-22.21	43.83	21.62	145.34	H	2
18900	1880.0	-22.28	43.57	21.29	134.59	H	2
19193	1908.3	-22.53	44.32	21.79	150.97	H	2
18607	1850.7	-23.95	46.41	22.46	176.28	V	2
18900	1880.0	-25.06	47.07	22.01	158.85	V	2
19193	1908.3	-24.82	45.88	21.06	127.76	V	2

CHANNEL BANDWIDTH: 3MHz QPSK

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
18615	1851.5	-20.32	43.82	23.51	224.23	H	2
18900	1880.0	-20.42	43.57	23.15	206.63	H	2
19185	1908.5	-20.74	44.38	23.64	230.99	H	2
18615	1851.5	-22.46	46.45	23.99	250.44	V	2
18900	1880.0	-23.47	47.07	23.60	229.30	V	2
19185	1908.5	-22.74	45.88	23.14	205.97	V	2

CHANNEL BANDWIDTH: 3MHz 16QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
18615	1851.5	-21.39	43.82	22.44	175.27	H	2
18900	1880.0	-21.31	43.57	22.26	168.34	H	2
19185	1908.5	-21.73	44.38	22.65	183.91	H	2
18615	1851.5	-23.53	46.45	22.92	195.75	V	2
18900	1880.0	-24.36	47.07	22.71	186.81	V	2
19185	1908.5	-23.73	45.88	22.15	163.98	V	2

CHANNEL BANDWIDTH: 3MHZ 64QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
18615	1851.5	-22.19	43.82	21.63	145.61	H	2
18900	1880.0	-22.34	43.57	21.23	132.74	H	2
19185	1908.5	-22.48	44.38	21.90	154.74	H	2
18615	1851.5	-23.93	46.45	22.52	178.73	V	2
18900	1880.0	-25.12	47.07	21.95	156.68	V	2
19185	1908.5	-24.77	45.88	21.11	129.12	V	2

CHANNEL BANDWIDTH: 5MHz QPSK

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
18625	1852.5	-20.38	43.83	23.45	221.46	H	2
18900	1880.0	-20.37	43.57	23.20	209.03	H	2
19175	1907.5	-20.69	44.19	23.50	223.77	H	2
18625	1852.5	-22.52	46.46	23.94	247.69	V	2
18900	1880.0	-23.42	47.07	23.65	231.95	V	2
19175	1907.5	-22.69	45.89	23.20	208.88	V	2

CHANNEL BANDWIDTH: 5MHz 16QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
18625	1852.5	-21.21	43.83	22.62	182.94	H	2
18900	1880.0	-21.39	43.57	22.18	165.27	H	2
19175	1907.5	-21.79	44.19	22.40	173.70	H	2
18625	1852.5	-23.35	46.46	23.11	204.60	V	2
18900	1880.0	-24.44	47.07	22.63	183.40	V	2
19175	1907.5	-23.79	45.89	22.10	162.14	V	2

CHANNEL BANDWIDTH: 5MHZ 64QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
18625	1852.5	-22.25	43.83	21.58	143.81	H	2
18900	1880.0	-22.29	43.57	21.28	134.28	H	2
19175	1907.5	-22.43	44.19	21.76	149.90	H	2
18625	1852.5	-23.99	46.46	22.47	176.77	V	2
18900	1880.0	-25.07	47.07	22.00	158.49	V	2
19175	1907.5	-24.72	45.89	21.17	130.95	V	2

CHANNEL BANDWIDTH: 10MHz QPSK

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
18650	1855.0	-20.19	43.86	23.68	233.13	H	2
18900	1880.0	-20.31	43.57	23.26	211.93	H	2
19150	1905.0	-20.56	43.99	23.43	220.50	H	2
18650	1855.0	-22.33	46.28	23.94	247.97	V	2
18900	1880.0	-23.36	47.07	23.71	235.18	V	2
19150	1905.0	-22.56	45.92	23.36	216.77	V	2

CHANNEL BANDWIDTH: 10MHz 16QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
18650	1855.0	-21.34	43.86	22.53	178.90	H	2
18900	1880.0	-21.41	43.57	22.16	164.51	H	2
19150	1905.0	-21.72	43.99	22.27	168.81	H	2
18650	1855.0	-23.48	46.28	22.79	190.28	V	2
18900	1880.0	-24.46	47.07	22.61	182.56	V	2
19150	1905.0	-23.72	45.92	22.20	165.96	V	2

CHANNEL BANDWIDTH: 10MHz 64QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
18650	1855.0	-22.06	43.86	21.80	151.39	H	2
18900	1880.0	-22.23	43.57	21.34	136.14	H	2
19150	1905.0	-22.30	43.99	21.69	147.71	H	2
18650	1855.0	-23.80	46.28	22.48	176.97	V	2
18900	1880.0	-25.01	47.07	22.06	160.69	V	2
19150	1905.0	-24.59	45.92	21.33	135.89	V	2

CHANNEL BANDWIDTH: 15MHz QPSK

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
18675	1857.5	-20.20	43.99	23.80	239.72	H	2
18900	1880.0	-20.38	43.57	23.19	208.55	H	2
19125	1902.5	-20.63	43.66	23.03	200.68	H	2
18675	1857.5	-22.34	45.93	23.58	228.19	V	2
18900	1880.0	-23.43	47.07	23.64	231.42	V	2
19125	1902.5	-22.63	46.20	23.57	227.51	V	2

CHANNEL BANDWIDTH: 15MHz 16QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
18675	1857.5	-21.06	43.99	22.94	196.65	H	2
18900	1880.0	-21.25	43.57	22.32	170.69	H	2
19125	1902.5	-21.48	43.66	22.18	165.01	H	2
18675	1857.5	-23.20	45.93	22.72	187.20	V	2
18900	1880.0	-24.30	47.07	22.77	189.41	V	2
19125	1902.5	-23.48	46.20	22.72	187.07	V	2

CHANNEL BANDWIDTH: 15MHZ 64QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
18675	1857.5	-22.07	43.99	21.92	155.67	H	2
18900	1880.0	-22.30	43.57	21.27	133.97	H	2
19125	1902.5	-22.37	43.66	21.29	134.43	H	2
18675	1857.5	-23.81	45.93	22.12	162.85	V	2
18900	1880.0	-25.08	47.07	21.99	158.12	V	2
19125	1902.5	-24.66	46.20	21.54	142.63	V	2

CHANNEL BANDWIDTH: 20MHz QPSK

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
18700	1860.0	-20.78	43.50	22.72	187.24	H	2
18900	1880.0	-20.83	43.57	22.74	188.02	H	2
19100	1900.0	-21.21	43.62	22.41	174.02	H	2
18700	1860.0	-22.92	45.57	22.65	183.91	V	2
18900	1880.0	-23.88	47.07	23.19	208.64	V	2
19100	1900.0	-23.21	46.26	23.05	201.79	V	2

CHANNEL BANDWIDTH: 20MHz 16QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
18700	1860.0	-21.71	43.50	21.79	151.15	H	2
18900	1880.0	-21.90	43.57	21.67	146.96	H	2
19100	1900.0	-22.04	43.62	21.58	143.75	H	2
18700	1860.0	-23.85	45.57	21.72	148.46	V	2
18900	1880.0	-24.95	47.07	22.12	163.08	V	2
19100	1900.0	-24.04	46.26	22.22	166.69	V	2

CHANNEL BANDWIDTH: 20MHZ 64QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
18700	1860.0	-22.65	43.50	20.85	121.59	H	2
18900	1880.0	-22.75	43.57	20.82	120.78	H	2
19100	1900.0	-22.95	43.62	20.67	116.57	H	2
18700	1860.0	-24.39	45.57	21.18	131.25	V	2
18900	1880.0	-25.53	47.07	21.54	142.56	V	2
19100	1900.0	-25.24	46.26	21.02	126.50	V	2

REMARKS: 1. EIRP Output Power (dBm) = SPA LVL (dBm) + Correction Factor (dB).

2. Correction factor (dB) = Free Space Loss + Antenna Factor + Cable Loss

LTE BAND 25

CHANNEL BANDWIDTH: 1.4MHz QPSK

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
26047	1850.7	-20.41	43.83	23.42	219.79	H	2
26340	1880.0	-19.90	43.57	23.68	233.08	H	2
26683	1914.3	-19.72	44.40	24.68	293.63	H	2
26047	1850.7	-23.33	46.41	23.09	203.52	V	2
26340	1880.0	-22.64	47.07	24.43	277.33	V	2
26683	1914.3	-23.12	45.99	22.87	193.82	V	2

CHANNEL BANDWIDTH: 1.4MHz 16QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
26047	1850.7	-21.28	43.83	22.55	179.89	H	2
26340	1880.0	-20.83	43.57	22.75	188.15	H	2
26683	1914.3	-20.68	44.40	23.72	235.40	H	2
26047	1850.7	-24.20	46.41	22.22	166.57	V	2
26340	1880.0	-23.57	47.07	23.50	223.87	V	2
26683	1914.3	-24.08	45.99	21.91	155.38	V	2

CHANNEL BANDWIDTH: 1.4MHZ 64QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
26047	1850.7	-21.84	43.83	22.00	158.45	H	2
26340	1880.0	-21.70	43.57	21.87	153.67	H	2
26683	1914.3	-21.77	44.40	22.63	183.32	H	2
26047	1850.7	-23.90	46.41	22.52	178.48	V	2
26340	1880.0	-23.76	47.07	23.32	214.54	V	2
26683	1914.3	-24.26	45.99	21.73	149.07	V	2

CHANNEL BANDWIDTH: 3MHz QPSK

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
26055	1851.5	-20.39	43.82	23.43	220.19	H	2
26340	1880.0	-19.96	43.57	23.62	229.88	H	2
26675	1913.5	-19.67	44.38	24.70	295.39	H	2
26055	1851.5	-23.31	46.45	23.15	206.35	V	2
26340	1880.0	-22.70	47.07	24.37	273.53	V	2
26675	1913.5	-23.07	45.95	22.88	194.27	V	2

CHANNEL BANDWIDTH: 3MHz 16QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
26055	1851.5	-21.46	43.82	22.36	172.11	H	2
26340	1880.0	-20.85	43.57	22.73	187.28	H	2
26675	1913.5	-20.66	44.38	23.71	235.18	H	2
26055	1851.5	-24.38	46.45	22.08	161.29	V	2
26340	1880.0	-23.59	47.07	23.48	222.84	V	2
26675	1913.5	-24.06	45.95	21.89	154.67	V	2

CHANNEL BANDWIDTH: 3MHZ 64QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
26055	1851.5	-21.82	43.82	22.01	158.74	H	2
26340	1880.0	-21.76	43.57	21.81	151.57	H	2
26675	1913.5	-21.72	44.38	22.66	184.42	H	2
26055	1851.5	-23.88	46.45	22.58	180.97	V	2
26340	1880.0	-23.82	47.07	23.26	211.59	V	2
26675	1913.5	-24.21	45.95	21.74	149.42	V	2

CHANNEL BANDWIDTH: 5MHz QPSK

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
26065	1852.5	-20.45	43.83	23.37	217.47	H	2
26340	1880.0	-19.91	43.57	23.67	232.54	H	2
26665	1912.5	-19.62	44.37	24.75	298.40	H	2
26065	1852.5	-23.37	46.46	23.10	204.08	V	2
26340	1880.0	-22.65	47.07	24.42	276.69	V	2
26665	1912.5	-23.02	45.90	22.88	194.27	V	2

CHANNEL BANDWIDTH: 5MHz 16QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
26065	1852.5	-21.28	43.83	22.54	179.64	H	2
26340	1880.0	-20.93	43.57	22.65	183.87	H	2
26665	1912.5	-20.72	44.37	23.65	231.63	H	2
26065	1852.5	-24.20	46.46	22.27	168.58	V	2
26340	1880.0	-23.67	47.07	23.40	218.78	V	2
26665	1912.5	-24.12	45.90	21.78	150.80	V	2

CHANNEL BANDWIDTH: 5MHZ 64QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
26065	1852.5	-21.88	43.83	21.95	156.78	H	2
26340	1880.0	-21.71	43.57	21.86	153.32	H	2
26665	1912.5	-21.67	44.37	22.70	186.29	H	2
26065	1852.5	-23.94	46.46	22.53	178.98	V	2
26340	1880.0	-23.77	47.07	23.31	214.04	V	2
26665	1912.5	-24.16	45.90	21.74	149.42	V	2

CHANNEL BANDWIDTH: 10MHz QPSK

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
26090	1855.0	-20.26	43.86	23.60	228.93	H	2
26340	1880.0	-19.85	43.57	23.73	235.78	H	2
26640	1910.0	-19.49	44.32	24.83	303.88	H	2
26090	1855.0	-23.18	46.28	23.10	204.31	V	2
26340	1880.0	-22.59	47.07	24.48	280.54	V	2
26640	1910.0	-22.89	45.88	23.00	199.43	V	2

CHANNEL BANDWIDTH: 10MHz 16QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
26090	1855.0	-21.41	43.86	22.45	175.67	H	2
26340	1880.0	-20.95	43.57	22.63	183.02	H	2
26640	1910.0	-20.65	44.32	23.67	232.65	H	2
26090	1855.0	-24.33	46.28	21.95	156.78	V	2
26340	1880.0	-23.69	47.07	23.38	217.77	V	2
26640	1910.0	-24.05	45.88	21.84	152.69	V	2

CHANNEL BANDWIDTH: 10MHZ 64QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
26090	1855.0	-21.69	43.86	22.18	165.04	H	2
26340	1880.0	-21.65	43.57	21.92	155.45	H	2
26640	1910.0	-21.54	44.32	22.78	189.71	H	2
26090	1855.0	-23.75	46.28	22.53	179.18	V	2
26340	1880.0	-23.71	47.07	23.37	217.02	V	2
26640	1910.0	-24.03	45.88	21.86	153.39	V	2

CHANNEL BANDWIDTH: 15MHz QPSK

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
26115	1857.5	-20.27	43.99	23.72	235.40	H	2
26340	1880.0	-19.92	43.57	23.66	232.01	H	2
26615	1907.5	-19.56	44.19	24.63	290.13	H	2
26115	1857.5	-23.19	45.93	22.74	188.02	V	2
26340	1880.0	-22.66	47.07	24.41	276.06	V	2
26615	1907.5	-22.96	45.89	22.94	196.56	V	2

CHANNEL BANDWIDTH: 15MHz 16QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
26115	1857.5	-21.13	43.99	22.86	193.11	H	2
26340	1880.0	-20.79	43.57	22.79	189.89	H	2
26615	1907.5	-20.41	44.19	23.78	238.56	H	2
26115	1857.5	-24.05	45.93	21.88	154.24	V	2
26340	1880.0	-23.53	47.07	23.54	225.94	V	2
26615	1907.5	-23.81	45.89	22.09	161.62	V	2

CHANNEL BANDWIDTH: 15MHZ 64QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
26115	1857.5	-21.70	43.99	22.30	169.71	H	2
26340	1880.0	-21.72	43.57	21.85	152.97	H	2
26615	1907.5	-21.61	44.19	22.58	181.13	H	2
26115	1857.5	-23.76	45.93	22.17	164.89	V	2
26340	1880.0	-23.78	47.07	23.30	213.55	V	2
26615	1907.5	-24.10	45.89	21.80	151.18	V	2

CHANNEL BANDWIDTH: 20MHz QPSK

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
26140	1860.0	-20.85	43.50	22.65	183.87	H	2
26340	1880.0	-20.37	43.57	23.21	209.17	H	2
26590	1905.0	-20.14	43.99	23.85	242.77	H	2
26140	1860.0	-23.77	45.57	21.81	151.53	V	2
26340	1880.0	-23.11	47.07	23.96	248.89	V	2
26590	1905.0	-23.54	45.92	22.39	173.22	V	2

CHANNEL BANDWIDTH: 20MHz 16QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
26140	1860.0	-21.78	43.50	21.72	148.42	H	2
26340	1880.0	-21.44	43.57	22.14	163.49	H	2
26590	1905.0	-20.97	43.99	23.02	200.54	H	2
26140	1860.0	-24.70	45.57	20.88	122.32	V	2
26340	1880.0	-24.18	47.07	22.89	194.54	V	2
26590	1905.0	-24.37	45.92	21.56	143.09	V	2

CHANNEL BANDWIDTH: 20MHZ 64QAM

Channel	Frequency (MHz)	SPA LVL (dBm)	Correction Factor(dB)	EIRP(dBm)	EIRP(mW)	Polarization (H/V)	LIMIT (W)
26140	1860.0	-22.28	43.50	21.22	132.56	H	2
26340	1880.0	-22.17	43.57	21.40	137.91	H	2
26590	1905.0	-22.19	43.99	21.81	151.57	H	2
26140	1860.0	-24.34	45.57	21.24	132.89	V	2
26340	1880.0	-24.23	47.07	22.85	192.53	V	2
26590	1905.0	-24.68	45.92	21.25	133.23	V	2

REMARKS: 1. EIRP Output Power (dBm) = SPA LVL (dBm) + Correction Factor (dB).

2. Correction factor (dB) = Free Space Loss + Antenna Factor + Cable Loss

3.2 FREQUENCY STABILITY MEASUREMENT

3.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT


The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

3.2.2 TEST PROCEDURE

- Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the $\pm 0.5^{\circ}\text{C}$ during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

3.2.3 TEST SETUP



3.2.4 TEST RESULTS

GSM1900

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	FREQUENCY ERROR (ppm)		LIMIT (ppm)
	Low Channel	High Channel	
3.85	0.0009	0.0012	2.5
3.5	-0.0012	-0.0012	2.5
4.2	0.0009	0.0011	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.5Vdc to 4.2Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (°C)	FREQUENCY ERROR (ppm)		LIMIT (ppm)
	Low Channel	High Channel	
-30	-0.0055	-0.0053	2.5
-20	-0.0051	-0.0048	2.5
-10	-0.0046	-0.0043	2.5
0	-0.0037	-0.0035	2.5
10	-0.0030	-0.0028	2.5
20	-0.0023	-0.0021	2.5
30	-0.0017	-0.0015	2.5
40	-0.0014	-0.0012	2.5
50	-0.0005	-0.0003	2.5

EDGE 1900

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	FREQUENCY ERROR (ppm)		LIMIT (ppm)
	Low Channel	High Channel	
3.85	0.0012	0.0011	2.5
3.5	-0.0013	-0.0012	2.5
4.2	0.0010	0.0009	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.5Vdc to 4.2Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (°C)	FREQUENCY ERROR (ppm)		LIMIT (ppm)
	Low Channel	High Channel	
-30	-0.0057	-0.0053	2.5
-20	-0.0050	-0.0047	2.5
-10	-0.0045	-0.0043	2.5
0	-0.0038	-0.0036	2.5
10	-0.0029	-0.0027	2.5
20	-0.0024	-0.0022	2.5
30	-0.0017	-0.0016	2.5
40	-0.0012	-0.0011	2.5
50	-0.0005	-0.0004	2.5

**WCDMA BAND II****FREQUENCY ERROR VS. VOLTAGE**

VOLTAGE (Volts)	FREQUENCY ERROR (ppm)		LIMIT (ppm)
	Low Channel	High Channel	
3.85	0.0009	0.0009	2.5
3.5	-0.0010	-0.0011	2.5
4.2	0.0009	0.0010	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.5Vdc to 4.2Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (°C)	FREQUENCY ERROR (ppm)		LIMIT (ppm)
	Low Channel	High Channel	
-30	-0.0055	-0.0052	2.5
-20	-0.0052	-0.0048	2.5
-10	-0.0044	-0.0042	2.5
0	-0.0039	-0.0036	2.5
10	-0.0029	-0.0028	2.5
20	-0.0023	-0.0022	2.5
30	-0.0017	-0.0016	2.5
40	-0.0012	-0.0012	2.5
50	-0.0005	-0.0005	2.5

CDMA BC1

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	FREQUENCY ERROR (ppm)		LIMIT (ppm)
	Low Channel	High Channel	
3.85	0.0015	0.0017	2.5
3.5	-0.0021	-0.0021	2.5
4.2	0.0018	0.0017	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.5Vdc to 4.2Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (°C)	FREQUENCY ERROR (ppm)		LIMIT (ppm)
	Low Channel	High Channel	
-30	-0.0123	-0.0118	2.5
-20	-0.0113	-0.0108	2.5
-10	-0.0100	-0.0095	2.5
0	-0.0087	-0.0083	2.5
10	-0.0066	-0.0063	2.5
20	-0.0051	-0.0049	2.5
30	-0.0047	-0.0045	2.5
40	-0.0028	-0.0027	2.5
50	-0.0015	-0.0014	2.5

LTE BAND 2

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	1.4MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
3.85	0.0008	0.0009	2.5
3.5	-0.0009	-0.0010	2.5
4.2	0.0007	0.0009	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.5Vdc to 4.2Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (°C)	1.4MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
-30	-0.0055	-0.0055	2.5
-20	-0.0050	-0.0051	2.5
-10	-0.0044	-0.0045	2.5
0	-0.0039	-0.0039	2.5
10	-0.0030	-0.0030	2.5
20	-0.0024	-0.0023	2.5
30	-0.0018	-0.0018	2.5
40	-0.0006	-0.0006	2.5
50	-0.0003	-0.0004	2.5

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	3MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
3.85	0.0008	0.0010	2.5
3.5	-0.0010	-0.0010	2.5
4.2	0.0010	0.0009	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.5Vdc to 4.2Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (°C)	3MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
-30	-0.0055	-0.0057	2.5
-20	-0.0050	-0.0048	2.5
-10	-0.0044	-0.0041	2.5
0	-0.0035	-0.0033	2.5
10	-0.0030	-0.0029	2.5
20	-0.0018	-0.0025	2.5
30	-0.0015	-0.0014	2.5
40	-0.0009	-0.0008	2.5
50	-0.0003	-0.0002	2.5

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	5MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
3.85	0.0009	0.0011	2.5
3.5	-0.0011	-0.0012	2.5
4.2	0.0010	0.0010	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.5Vdc to 4.2Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (°C)	5MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
-30	-0.0053	-0.0053	2.5
-20	-0.0046	-0.0048	2.5
-10	-0.0041	-0.0039	2.5
0	-0.0036	-0.0034	2.5
10	-0.0030	-0.0028	2.5
20	-0.0023	-0.0020	2.5
30	-0.0014	-0.0013	2.5
40	-0.0008	-0.0007	2.5
50	-0.0002	0.0002	2.5

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	10MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
3.85	0.0010	0.0008	2.5
3.5	-0.0012	-0.0009	2.5
4.2	0.0009	0.0008	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.5Vdc to 4.2Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (°C)	10MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
-30	-0.0051	-0.0052	2.5
-20	-0.0044	-0.0046	2.5
-10	-0.0039	-0.0040	2.5
0	-0.0034	-0.0034	2.5
10	-0.0028	-0.0025	2.5
20	-0.0021	-0.0019	2.5
30	-0.0015	-0.0013	2.5
40	-0.0010	-0.0008	2.5
50	0.0003	0.0002	2.5

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	15MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
3.85	0.0012	0.0011	2.5
3.5	-0.0011	-0.0012	2.5
4.2	0.0009	0.0010	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.5Vdc to 4.2Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (°C)	15MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
-30	-0.0051	-0.0049	2.5
-20	-0.0047	-0.0043	2.5
-10	-0.0039	-0.0036	2.5
0	-0.0030	-0.0028	2.5
10	-0.0024	-0.0025	2.5
20	-0.0019	-0.0013	2.5
30	-0.0011	-0.0010	2.5
40	-0.0007	-0.0003	2.5
50	0.0002	0.0002	2.5

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	20MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
3.85	0.0011	0.0011	2.5
3.5	-0.0012	-0.0011	2.5
4.2	0.0010	0.0012	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.5Vdc to 4.2Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (°C)	20MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
-30	-0.0048	-0.0051	2.5
-20	-0.0041	-0.0042	2.5
-10	-0.0037	-0.0036	2.5
0	-0.0028	-0.0029	2.5
10	-0.0022	-0.0023	2.5
20	-0.0018	-0.0013	2.5
30	-0.0008	-0.0009	2.5
40	-0.0005	-0.0001	2.5
50	0.0002	0.0002	2.5

LTE BAND 25

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	1.4MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
3.85	0.0008	0.0009	2.5
3.5	-0.0009	-0.0010	2.5
4.2	0.0007	0.0008	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.5Vdc to 4.2Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (°C)	1.4MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
-30	-0.0055	-0.0057	2.5
-20	-0.0050	-0.0052	2.5
-10	-0.0044	-0.0046	2.5
0	-0.0040	-0.0042	2.5
10	-0.0028	-0.0029	2.5
20	-0.0023	-0.0023	2.5
30	-0.0018	-0.0019	2.5
40	-0.0009	-0.0009	2.5
50	-0.0004	-0.0003	2.5

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	3MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
3.85	0.0008	0.0010	2.5
3.5	-0.0010	-0.0010	2.5
4.2	0.0010	0.0010	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.5Vdc to 4.2Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (°C)	3MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
-30	-0.0056	-0.0055	2.5
-20	-0.0052	-0.0051	2.5
-10	-0.0045	-0.0040	2.5
0	-0.0037	-0.0034	2.5
10	-0.0030	-0.0029	2.5
20	-0.0023	-0.0024	2.5
30	-0.0018	-0.0012	2.5
40	-0.0010	-0.0009	2.5
50	-0.0003	-0.0002	2.5

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	5MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
3.85	0.0009	0.0011	2.5
3.5	-0.0012	-0.0011	2.5
4.2	0.0010	0.0010	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.5Vdc to 4.2Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (°C)	5MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
-30	-0.0053	-0.0054	2.5
-20	-0.0046	-0.0049	2.5
-10	-0.0041	-0.0039	2.5
0	-0.0034	-0.0035	2.5
10	-0.0030	-0.0027	2.5
20	-0.0023	-0.0019	2.5
30	-0.0015	-0.0012	2.5
40	-0.0007	-0.0007	2.5
50	-0.0002	0.0002	2.5

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	10MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
3.85	0.0010	0.0007	2.5
3.5	-0.0011	-0.0010	2.5
4.2	0.0010	0.0008	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.5Vdc to 4.2Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (°C)	10MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
-30	-0.0050	-0.0051	2.5
-20	-0.0045	-0.0048	2.5
-10	-0.0039	-0.0039	2.5
0	-0.0034	-0.0033	2.5
10	-0.0029	-0.0022	2.5
20	-0.0021	-0.0019	2.5
30	-0.0015	-0.0015	2.5
40	-0.0010	-0.0008	2.5
50	0.0003	0.0002	2.5

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	15MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
3.85	0.0012	0.0011	2.5
3.5	-0.0011	-0.0012	2.5
4.2	0.0010	0.0010	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.5Vdc to 4.2Vdc.

FREQUENCY ERROR vs. TEMPERATURE.

TEMP. (°C)	15MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
-30	-0.0051	-0.0048	2.5
-20	-0.0045	-0.0041	2.5
-10	-0.0040	-0.0036	2.5
0	-0.0030	-0.0029	2.5
10	-0.0025	-0.0024	2.5
20	-0.0018	-0.0022	2.5
30	-0.0011	-0.0010	2.5
40	-0.0007	-0.0003	2.5
50	0.0002	0.0003	2.5

FREQUENCY ERROR VS. VOLTAGE

VOLTAGE (Volts)	20MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
3.85	0.0011	0.0011	2.5
3.5	-0.0012	-0.0012	2.5
4.2	0.0010	0.0011	2.5

NOTE: The applicant defined the normal working voltage of the battery is from 3.5Vdc to 4.2Vdc.

FREQUENCY ERROR vs. TEMPERATURE.


TEMP. (°C)	20MHz		LIMIT (ppm)
	FREQUENCY ERROR (ppm)		
	Low Channel	High Channel	
-30	-0.0048	-0.0052	2.5
-20	-0.0041	-0.0041	2.5
-10	-0.0035	-0.0036	2.5
0	-0.0028	-0.0030	2.5
10	-0.0022	-0.0022	2.5
20	-0.0019	-0.0015	2.5
30	-0.0010	-0.0010	2.5
40	-0.0005	-0.0002	2.5
50	0.0003	0.0003	2.5

3.3 OCCUPIED BANDWIDTH MEASUREMENT

3.3.1 TEST PROCEDURES


The EUT makes a call to the communication simulator. All measurements were done at low, middle and high operational frequency range. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency. Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

3.3.2 TEST SETUP




3.3.3 TEST RESULTS

Channel	Frequency (MHz)	99% Occupied bandwidth (kHz)		Channel	Frequency (MHz)	99% Occupied bandwidth (MHz)
		GSM	EDGE			WCDMA
512	1850.2	246.00	242.00	9262	1852.4	4.14
661	1880.0	246.00	243.00	9400	1880.0	4.14
810	1909.8	243.00	244.00	9538	1907.6	4.15




Channel	Frequency (MHz)	26dB bandwidth (kHz)		CHANNEL	FREQUENCY (MHz)	26dB bandwidth (MHz)
		GSM	EDGE			WCDMA
512	1850.2	318.14	316.45	9262	1852.4	4.73
661	1880.0	320.43	308.73	9400	1880.0	4.74
810	1909.8	328.67	321.17	9538	1907.6	4.74



CDMA BC 1

CHANNEL	Frequency (MHz)	99% OCCUPIED Bandwidth (MHz)	CHANNEL	Frequency (MHz)	26dB Bandwidth (MHz)
25	1851.25	1.27	25	1851.25	1.43
600	1880.00	1.27	600	1880.00	1.43
1175	1908.75	1.27	1175	1908.75	1.43



LTE band 2				
Channel Bandwidth : 1.4MHz				
Channel	Frequency (MHz)	99% Occupied bandwidth (MHz)		
		QPSK	16QAM	64QAM
18607	1850.7	1.09	1.08	1.08
18900	1880	1.09	1.08	1.08
19193	1909.3	1.08	1.08	1.08



LTE band 2				
Channel Bandwidth : 3MHz				
Channel	Frequency (MHz)	99% Occupied bandwidth (MHz)		
		QPSK	16QAM	64QAM
18615	1851.5	2.69	2.68	2.68
18900	1880	2.69	2.68	2.68
19185	1908.5	2.69	2.68	2.68



LTE band 2				
Channel Bandwidth : 5MHz				
Channel	Frequency (MHz)	99% Occupied bandwidth (MHz)		
		QPSK	16QAM	64QAM
18625	1852.5	4.48	4.47	4.49
18900	1880	4.48	4.47	4.48
19175	1907.5	4.48	4.47	4.48



LTE band 2				
Channel Bandwidth : 10MHz				
Channel	Frequency (MHz)	99% Occupied bandwidth (MHz)		
		QPSK	16QAM	64QAM
18650	1855	8.94	8.95	8.94
18900	1880	8.95	8.94	8.95
19150	1905	8.94	8.94	8.94



LTE band 2				
Channel Bandwidth : 15MHz				
Channel	Frequency (MHz)	99% Occupied bandwidth (MHz)		
		QPSK	16QAM	64QAM
18675	1857.5	13.39	13.37	13.38
18900	1880	13.39	13.39	13.39
19125	1902.5	13.39	13.38	13.41



LTE band 2				
Channel Bandwidth : 20MHz				
Channel	Frequency (MHz)	99% Occupied bandwidth (MHz)		
		QPSK	16QAM	64QAM
18700	1860	17.86	17.82	17.84
18900	1880	17.89	17.82	17.85
19100	1900	17.89	17.84	17.86



LTE band 2							
Channel Bandwidth : 1.4MHz				Channel Bandwidth : 3MHz			
Channel	Frequency (MHz)	26dB bandwidth (MHz)		Channel	Frequency (MHz)	26dB bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
18607	1850.7	1.22	1.23	18615	1851.5	2.94	2.94
18900	1880	1.22	1.22	18900	1880	2.95	2.94
19193	1909.3	1.22	1.23	19185	1908.5	2.94	2.94




LTE band 2							
Channel Bandwidth : 5MHz				Channel Bandwidth : 10MHz			
Channel	Frequency (MHz)	26dB bandwidth (MHz)		Channel	Frequency (MHz)	26dB bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
18625	1852.5	4.87	4.87	18650	1855	9.68	9.67
18900	1880	4.89	4.86	18900	1880	9.66	9.63
19175	1907.5	4.89	4.85	19150	1905	9.69	9.70



LTE band 2							
Channel Bandwidth : 15MHz				Channel Bandwidth : 20MHz			
Channel	Frequency (MHz)	26dB bandwidth (MHz)		Channel	Frequency (MHz)	26dB bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
18675	1857.5	14.35	14.42	18700	1860	19.13	18.99
18900	1880	14.39	14.40	18900	1880	19.14	19.05
19125	1902.5	14.44	14.41	19100	1900	19.19	18.98



LTE band 25				
Channel Bandwidth : 1.4MHz				
Channel	Frequency (MHz)	99% Occupied bandwidth (MHz)		
		QPSK	16QAM	64QAM
26047	1850.7	1.08	1.08	1.08
26365	1880	1.09	1.09	1.08
26683	1914.3	1.09	1.08	1.09



LTE band 25				
Channel Bandwidth : 3MHz				
Channel	Frequency (MHz)	99% Occupied bandwidth (MHz)		
		QPSK	16QAM	64QAM
26055	1851.5	2.69	2.69	2.68
26365	1880	2.69	2.69	2.68
26675	1913.5	2.69	2.68	2.69



LTE band 25				
Channel Bandwidth : 5MHz				
Channel	Frequency (MHz)	99% Occupied bandwidth (MHz)		
		QPSK	16QAM	64QAM
26065	1852.5	4.49	4.47	4.47
26365	1880	4.49	4.47	4.49
26665	1912.5	4.48	4.47	4.49



LTE band 25				
Channel Bandwidth : 10MHz				
Channel	Frequency (MHz)	99% Occupied bandwidth (MHz)		
		QPSK	16QAM	64QAM
26090	1855	8.94	8.92	8.94
26365	1880	8.94	8.94	8.94
26640	1910	8.95	8.95	8.94



LTE band 25				
Channel Bandwidth : 15MHz				
Channel	Frequency (MHz)	99% Occupied bandwidth (MHz)		
		QPSK	16QAM	64QAM
26115	1857.5	13.39	13.40	13.37
26365	1880	13.41	13.39	13.38
26615	1907.5	13.41	13.39	13.39



LTE band 25				
Channel Bandwidth : 20MHz				
Channel	Frequency (MHz)	99% Occupied bandwidth (MHz)		
		QPSK	16QAM	64QAM
26140	1860	17.83	17.82	17.88
26365	1880	17.88	17.85	17.84
26590	1905	17.87	17.82	17.87



LTE band 25							
Channel Bandwidth : 1.4MHz				Channel Bandwidth : 3MHz			
Channel	Frequency (MHz)	26dB bandwidth (MHz)		Channel	Frequency (MHz)	26dB bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
26047	1850.7	1.22	1.22	26055	1851.5	2.96	2.95
26365	1880	1.22	1.23	26340	1880	2.95	2.94
26683	1914.3	1.23	1.22	26675	1913.5	2.97	2.92



LTE band 25							
Channel Bandwidth : 5MHz				Channel Bandwidth : 10MHz			
Channel	Frequency (MHz)	26dB bandwidth (MHz)		Channel	Frequency (MHz)	26dB bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
26065	1852.5	4.89	4.88	26090	1855	9.67	9.63
26365	1880	4.88	4.86	26365	1880	9.66	9.61
26665	1912.5	4.89	4.91	26640	1910	9.65	9.72



LTE band 25							
Channel Bandwidth : 15MHz				Channel Bandwidth : 20MHz			
Channel	Frequency (MHz)	26dB bandwidth (MHz)		Channel	Frequency (MHz)	26dB bandwidth (MHz)	
		QPSK	16QAM			QPSK	16QAM
26115	1857.5	14.42	14.43	26140	1860	19.12	18.95
26365	1880	14.32	14.36	26365	1880	19.12	19.23
26615	1907.5	14.31	14.45	26590	1905	19.02	19.05




3.4 BAND EDGE MEASUREMENT

3.4.1 LIMITS OF BAND EDGE MEASUREMENT

Power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.


3.4.2 TEST SETUP



3.4.3 TEST PROCEDURES

- a. All measurements were done at low and high operational frequency range.
- b. The center frequency of spectrum is the band edge frequency and span is 1.5 MHz. RBW of the spectrum is 10kHz and VBW of the spectrum is 30kHz (GSM/GPRS/ EDGE).
- c. The center frequency of spectrum is the band edge frequency and span is 10MHz. RBW of the spectrum is 100kHz and VBW of the spectrum is 300kHz (WCDMA).
- d. The center frequency of spectrum is the band edge frequency and span is 3MHz. RBW of the spectrum is 15kHz and VBW of the spectrum is 15kHz (CDMA BC 1)
- e. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RBW of the spectrum is 20kHz and VBW of the spectrum is 100 kHz. (LTE bandwidth 1.4MHz)
- f. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RBW of the spectrum is 30kHz and VBW of the spectrum is 100kHz. (LTE bandwidth 3MHz)
- g. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RBW of the spectrum is 50kHz and VBW of the spectrum is 200kHz. (LTE bandwidth 5MHz)
- h. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RBW of the spectrum is 100kHz and VBW of the spectrum is 300kHz. (LTE bandwidth 10MHz)
- i. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RBW of the spectrum is 200kHz and VBW of the spectrum is 1MHz. (LTE bandwidth 15MHz)
- j. The center frequency of spectrum is the band edge frequency and span is 1~5 MHz. RBW of the spectrum is 200kHz and VBW of the spectrum is 1MHz. (LTE bandwidth 20MHz)
- k. Record the max trace plot into the test report.


3.4.4. TEST RESULTS





**BUREAU
VERITAS**

Test Report No.: RF170730W002-5






BUREAU
VERITAS

Test Report No.: RF170730W002-5

LTE BAND 2

Channel Bandwidth: 1.4MHz






BUREAU
VERITAS

Test Report No.: RF170730W002-5

LTE BAND 2

Channel Bandwidth: 3MHz






BUREAU
VERITAS

Test Report No.: RF170730W002-5

LTE BAND 2

Channel Bandwidth: 5MHz






BUREAU
VERITAS

Test Report No.: RF170730W002-5

LTE BAND 2

Channel Bandwidth: 10MHz






BUREAU
VERITAS

Test Report No.: RF170730W002-5

LTE BAND 2

Channel Bandwidth: 15MHz






BUREAU
VERITAS

Test Report No.: RF170730W002-5

LTE BAND 2

Channel Bandwidth: 20MHz






BUREAU
VERITAS

Test Report No.: RF170730W002-5

LTE BAND 25

Channel Bandwidth: 1.4MHz






BUREAU
VERITAS

Test Report No.: RF170730W002-5

LTE BAND 25

Channel Bandwidth: 3MHz






BUREAU
VERITAS

Test Report No.: RF170730W002-5

LTE BAND 25

Channel Bandwidth: 5MHz






BUREAU
VERITAS

Test Report No.: RF170730W002-5

LTE BAND 25

Channel Bandwidth: 10MHz






BUREAU
VERITAS

Test Report No.: RF170730W002-5

LTE BAND 25

Channel Bandwidth: 15MHz





BUREAU
VERITAS

Test Report No.: RF170730W002-5

LTE BAND 25

Channel Bandwidth: 20MHz



3.5 CONDUCTED SPURIOUS EMISSIONS


3.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13dBm .

3.5.2 TEST PROCEDURE

- a. The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- b. Measuring frequency range is from 9 kHz to 19.0GHz for CDMA BC1/ GSM, 9 kHz to 19.1GHz for EDGE/WCDMA/LTE Band 2 and 9 kHz to 19.15GHz for LTE Band 25. 10dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz is used for conducted emission measurement.

3.5.3 TEST SETUP








BUREAU
VERITAS


Test Report No.: RF170730W002-5

3.5.4 TEST RESULTS











BUREAU
VERITAS


Test Report No.: RF170730W002-5

LTE BAND 2

1.4MHz / QPSK


CHANNEL 18607

FREQUENCY RANGE : 30MHz~19.1GHz




CHANNEL 18900

FREQUENCY RANGE : 30MHz~19.1GHz



CHANNEL 19193


FREQUENCY RANGE : 30MHz~19.1GHz





BUREAU
VERITAS


Test Report No.: RF170730W002-5





BUREAU
VERITAS

Test Report No.: RF170730W002-5



BV 7Layers Communications Technology
(Shenzhen) Co. Ltd


No.B102, Dazu Chuangxin Mansion, North of Beihuan
Avenue, North Area, Hi-Tech Industrial Park, Nanshan
District, Shenzhen, Guangdong, China

Tel: +86 755 8869 6566
Fax: +86 755 8869 6577
Email: customerservice.dq@cn.bureauveritas.com

10MHz / QPSK


CHANNEL 18650

FREQUENCY RANGE : 30MHz~19.1GHz




CHANNEL 18900

FREQUENCY RANGE : 30MHz~19.1GHz



CHANNEL 19150


FREQUENCY RANGE : 30MHz~19.1GHz





BUREAU
VERITAS


Test Report No.: RF170730W002-5





BUREAU
VERITAS

Test Report No.: RF170730W002-5





BUREAU
VERITAS


Test Report No.: RF170730W002-5

LTE BAND 25

1.4MHz / QPSK


CHANNEL 26047

FREQUENCY RANGE : 30MHz~19.15GHz




CHANNEL 26365

FREQUENCY RANGE : 30MHz~19.15GHz



CHANNEL 26683


FREQUENCY RANGE : 30MHz~19.15GHz





BUREAU
VERITAS


Test Report No.: RF170730W002-5





BUREAU
VERITAS


Test Report No.: RF170730W002-5





BUREAU
VERITAS


Test Report No.: RF170730W002-5





BUREAU
VERITAS

Test Report No.: RF170730W002-5





BUREAU
VERITAS

Test Report No.: RF170730W002-5

