



Test Report No.: RF200702W001-1



# FCC TEST REPORT

## (Part 15, Subpart C)

Applicant:	Sonim Technologies, Inc.
Address:	6836 Bee Cave Road, Building 1, Suite 279, Austin, Texas 78746, USA

Manufacturer or Supplier:	Sonim Technologies (Shenzhen) Limited
Address:	2nd Floor, No. 2 Building Phase B, Daqian Industrial park, Longchang Road, 67 District, Baoan, Shenzhen, P. R. China
Product:	Mobile Phone
Brand Name:	Sonim
Model Name:	XP8800
FCC ID:	WYPPG4032
Date of tests:	Jul. 01, 2020 ~ Jul. 08, 2020

The tests have been carried out according to the requirements of the following standard:

- FCC Part 15, Subpart C, Section 15.247**
- ANSI C63.10-2013**

**CONCLUSION: The submitted sample was found to COMPLY with the test requirement**

Prepared by Alex Chen Engineer / Mobile Department	Approved by Luke Lu Manager / Mobile Department

Date: Jul. 23, 2020

Date: Jul. 23, 2020

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute you unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



## TABLE OF CONTENTS

<b>RELEASE CONTROL RECORD.....</b>	<b>3</b>
<b>1 SUMMARY OF TEST RESULTS.....</b>	<b>4</b>
<b>1.1 MEASUREMENT UNCERTAINTY.....</b>	<b>5</b>
<b>2 GENERAL INFORMATION.....</b>	<b>5</b>
<b>2.1 GENERAL DESCRIPTION OF EUT.....</b>	<b>5</b>
<b>2.2 DESCRIPTION OF TEST MODES.....</b>	<b>8</b>
<b>2.2.1 CONFIGURATION OF SYSTEM UNDER TEST.....</b>	<b>9</b>
<b>2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....</b>	<b>9</b>
<b>2.3 GENERAL DESCRIPTION OF APPLIED STANDARDS.....</b>	<b>11</b>
<b>2.4 DESCRIPTION OF SUPPORT UNITS.....</b>	<b>11</b>
<b>3 TEST TYPES AND RESULTS.....</b>	<b>12</b>
<b>3.1 CONDUCTED EMISSION MEASUREMENT.....</b>	<b>12</b>
<b>3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT.....</b>	<b>12</b>
<b>3.1.2 TEST INSTRUMENTS.....</b>	<b>12</b>
<b>3.1.3 TEST PROCEDURES.....</b>	<b>12</b>
<b>3.1.4 DEVIATION FROM TEST STANDARD.....</b>	<b>13</b>
<b>3.1.5 TEST SETUP.....</b>	<b>13</b>
<b>3.1.6 EUT OPERATING CONDITIONS.....</b>	<b>13</b>
<b>3.1.7 TEST RESULTS.....</b>	<b>14</b>
<b>3.2 RADIATED EMISSION AND BANDEdge MEASUREMENT.....</b>	<b>16</b>
<b>3.2.1 LIMITS OF RADIATED EMISSION AND BANDEdge MEASUREMENT.....</b>	<b>16</b>
<b>3.2.2 TEST INSTRUMENTS.....</b>	<b>17</b>
<b>3.2.3 TEST PROCEDURES.....</b>	<b>18</b>
<b>3.2.4 DEVIATION FROM TEST STANDARD.....</b>	<b>18</b>
<b>3.2.5 TEST SETUP.....</b>	<b>18</b>
<b>3.2.6 EUT OPERATING CONDITIONS.....</b>	<b>20</b>
<b>3.2.7 TEST RESULTS.....</b>	<b>21</b>
<b>4 PHOTOGRAPHS OF THE TEST CONFIGURATION.....</b>	<b>24</b>
<b>5 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB.....</b>	<b>25</b>



Test Report No.: RF200702W001-1

## RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF170730W002-1	Original release	Nov. 23, 2017
RF171201W001-1	Based on the original report RF170730W002-1 disable CDMA function.	Dec. 11, 2017
RF200702W001-1	Based on the original report RF171201W001-1 add a new charger, update SW version, change the address and add two type numbers	Jul. 23, 2020



Test Report No.: RF200702W001-1

## 1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
STANDARD	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Conducted Emission	Compliance	Meet the requirement of limit.
15.247(a)(1)(iii)	Number of Hopping Frequency Used	N.A	See note 1
15.247(a)(1)(iii)	Dwell Time on Each Channel	N.A	See note 1
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	N.A	See note 1
15.247(b)	Maximum Peak Output Power	N.A	See note 1
15.247(d)& 15.209	Transmitter Radiated Emissions	Compliance	Meet the requirement of limit.
15.247(d)	Out of band Measurement	N.A	See note 1
15.203	Antenna Requirement	N.A	See note 1

\* Refer to KDB 971168 D01 Power Meas License Digital Systems v03r01.

Note:

1. Per the change notice provide by manufactory, the difference is add a new charger and two type numbers, and change the address and SW version, all the change no effect any RF parameter, Therefore only verify the radiated emission and the AC Power Conducted emission, and show the verify test data on this report.



Test Report No.: RF200702W001-1

## 1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
AC Power Conducted emissions	±2.70dB
Radiated emissions (30MHz~1GHz)	±4.98dB
Radiated emissions (1GHz ~6GHz)	±4.70dB
Radiated emissions (6GHz ~18GHz)	±4.60dB
Radiated emissions (18GHz ~40GHz)	±4.12dB
Conducted emissions	±4.01dB
Occupied Channel Bandwidth	±43.58KHz
Conducted Output power	±2.06dB
Power Spectral Density	±0.85 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

## 2 GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Mobile Phone
MODEL NAME	XP8800
TYPE NUMBER	PG4032/PG4033/PG4034/PG4035/PG4012/PG4041/P G4022/PG4011/PG4061
POWER SUPPLY	5/9Vdc (adapter or host equipment) 3.85Vdc (Li-ion, battery)
MODULATION TECHNOLOGY	FHSS
MODULATION TYPE	GFSK, 8DPSK, $\pi/4$ DQPSK
OPERATING FREQUENCY	2402MHz~2480MHz
NUMBER OF CHANNEL	79
MAX. OUTPUT POWER	8.128mW (Max. Measured)
ANTENNA TYPE	PIFA Antenna with -1dBi gain
HW VERSION	A



Test Report No.: RF200702W001-1

<b>SW VERSION</b>	8A.0.0-00-10.0.0-00.34.01
<b>I/O PORTS</b>	Refer to user's manual
<b>CABLE SUPPLIED</b>	USB cable 1: With shield, detachable, 1.5meter USB cable 2: non-shielded, detachable, 1.0meter

**NOTE:**

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. The EUT was powered by the following adapter:

<b>ADAPTER 1</b>	
<b>BRAND:</b>	Sonim
<b>MODEL:</b>	S42A02
<b>INPUT:</b>	AC 100-240V, 500mA
<b>OUTPUT:</b>	DC 5V, 1500mA DC 9V, 1500mA DC 12V, 1100mA



Test Report No.: RF200702W001-1

BUREAU  
VERITAS

**ADAPTER 2**

<b>BRAND:</b>	Sonim
<b>MODEL:</b>	S84A02
<b>INPUT:</b>	AC 100-240V, 750mA
<b>OUTPUT:</b>	DC 5V, 3000mA DC 9V, 2220mA DC 12V, 1670mA

3. The EUT matched the following USB cables:

**USB CABLE 1**

<b>BRAND:</b>	N/A
<b>MODEL:</b>	N/A
<b>SIGNAL LINE:</b>	1.5 METER

**USB CABLE 2**

<b>BRAND:</b>	N/A
<b>MODEL:</b>	N/A
<b>SIGNAL LINE:</b>	1.0 METER

4. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.



Test Report No.: RF200702W001-1

## 2.2 DESCRIPTION OF TEST MODES

79 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		



Test Report No.: RF200702W001-1

## 2.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photograph of the test configuration for reference.

## 2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case was found when positioned on X axis for radiated emission. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE<1G	RE≥1G	PLC	APCM	
-	√	-	√	-	-

Where    **RE<1G:** Radiated Emission below 1GHz  
**PLC:** Power Line Conducted Emission

**RE≥1G:** Radiated Emission above 1GHz  
**APCM:** Antenna Port Conducted Measurement

### RADIATED EMISSION TEST (BELOW 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
-	0 to 78	78	FHSS	GFSK	DH5



Test Report No.: RF200702W001-1

BUREAU  
VERITAS

**POWER LINE CONDUCTED EMISSION TEST:**

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture) and packet type.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
-	0 to 78	78	FHSS	GFSK	DH5

**TEST CONDITION:**

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE (SYSTEM)	TESTED BY
RE<1G	23deg. C, 70%RH	DC 5V/9V12V By Adapter	Star Le
PLC	25deg. C, 52%RH	DC 5V/9V12V By Adapter	Jocan Guo



Test Report No.: RF200702W001-1

BUREAU  
VERITAS

## 2.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

### FCC Part 15, Subpart C. Section 15.247

### ANSI C63.10-2013

**NOTE:**

1. All test items have been performed and recorded as per the above standards.
2. The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (Certification). The test report has been issued separately.

## 2.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Desktop	Lenovo	M73 SFF	PC04GRQV	N/A
2	Desktop	Lenovo	M73 SFF	PC06CS27	N/A
3	Laptop	Lenovo	Thnikpad L440	R90FTFKN	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	AC Line: Unshielded, Detachable 1.5m
2	AC Line: Unshielded, Detachable 1.5m
3	AC Line: Unshielded, Detachable 1.5m



Test Report No.: RF200702W001-1

## 3 TEST TYPES AND RESULTS

### 3.1 CONDUCTED EMISSION MEASUREMENT

#### 3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB $\mu$ V)	
0.15 ~ 0.5 0.5 ~ 5 5 ~ 30	Quasi-peak	Average
	66 to 56	56 to 46
	56	46
	60	50

**NOTE:** 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

#### 3.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR3	101900	Feb. 26,20	Feb. 25,21
EMC32 test software	Rohde&Schwarz	EMC32	NA	NA	NA
LISN network	Rohde&Schwarz	ENV216	101922	Feb. 26,20	Feb. 25,21

**NOTE:** 1. The test was performed in CE shielded room.  
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

#### 3.1.3 TEST PROCEDURES


- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

**NOTE:** All modes of operation were investigated and the worst-case emissions are reported.

### 3.1.4 DEVIATION FROM TEST STANDARD

No deviation.

### 3.1.5 TEST SETUP



**Note:**

1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

### 3.1.6 EUT OPERATING CONDITIONS

- Turned on the power and connected of all equipment.
- EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.



Test Report No.: RF200702W001-1

BUREAU  
VERITAS

### 3.1.7 TEST RESULTS

#### CONDUCTED WORST-CASE DATA:

Frequency Range	150KHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120Vac, 60Hz	Environmental Conditions	24deg. C, 55RH
Tested By	Chase Zhou	Test Date	2020/07/06

Frequency (MHz)	QuasiPeak (dB <sub>1</sub> IV)	CAverage (dB <sub>1</sub> IV)	Limit (dB <sub>1</sub> IV)	Margin (dB)	Line	Filter	Corr. (dB)
0.150000	---	38.43	56.00	-17.57	L	ON	9.7
0.150000	52.22	---	66.00	-13.78	L	ON	9.7
0.216000	---	29.16	52.97	-23.81	L	ON	9.7
0.216000	44.57	---	62.97	-18.40	L	ON	9.7
0.512000	---	28.92	46.00	-17.08	L	ON	9.7
0.512000	38.94	---	56.00	-17.06	L	ON	9.7
1.152000	---	18.67	46.00	-27.33	L	ON	9.7
1.152000	28.23	---	56.00	-27.77	L	ON	9.7
17.136000	---	26.42	50.00	-23.58	L	ON	10.0
17.136000	34.28	---	60.00	-25.72	L	ON	10.0
18.024000	---	28.16	50.00	-21.84	L	ON	10.0
18.024000	35.48	---	60.00	-24.52	L	ON	10.0

**REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.


2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.

3. The emission levels of other frequencies were very low against the limit.

4. Margin value = Emission level - Limit value

5. Correction factor = Insertion loss + Cable loss

6. Emission Level = Correction Factor + Reading Value.





Test Report No.: RF200702W001-1


BUREAU  
VERITAS

Frequency Range	150KHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120Vac, 60Hz	Environmental Conditions	24deg. C, 55RH
Tested By	Chase Zhou	Test Date	2020/07/06

Frequency (MHz)	QuasiPeak (dB <sub>1</sub> IV)	CAverage (dB <sub>1</sub> IV)	Limit (dB <sub>1</sub> IV)	Margin (dB)	Line	Filter	Corr. (dB)
0.150000	---	33.07	56.00	-22.93	N	ON	9.8
0.150000	46.86	---	66.00	-19.14	N	ON	9.8
0.208000	---	23.18	53.28	-30.11	N	ON	9.8
0.208000	37.75	---	63.28	-25.53	N	ON	9.8
0.500000	---	28.48	46.00	-17.52	N	ON	9.8
0.500000	35.55	---	56.00	-20.45	N	ON	9.8
8.722000	---	19.11	50.00	-30.89	N	ON	10.0
8.722000	29.02	---	60.00	-30.98	N	ON	10.0
17.380000	---	27.76	50.00	-22.24	N	ON	10.1
17.380000	36.26	---	60.00	-23.74	N	ON	10.1
19.256000	---	29.76	50.00	-20.24	N	ON	10.1
19.256000	37.65	---	60.00	-22.35	N	ON	10.1

**REMARKS:** 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.





Test Report No.: RF200702W001-1

BUREAU  
VERITAS

### 3.2 RADIATED EMISSION AND BANDEDGE MEASUREMENT

#### 3.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a). Other emissions shall be at least 20dB below the highest level of the desired power.

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB<sub>u</sub>V/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



Test Report No.: RF200702W001-1

### 3.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	Euroshieldpn-CT0001143-1216	Feb. 26,20	Feb. 25,21
Bilog Antenna	ETS-LINDGREN	3143B	00161965	Feb. 26,20	Feb. 25,21
Horn Antenna	ETS-LINDGREN	3117	00168728	Feb. 26,20	Feb. 25,21
Horn Antenna (18GHz-40GHz)	N/A	QWH-SL-18-40-K-SG/QMS-003 61	15433	Nov. 21, 19	Nov. 20, 20
Test Software	E3	V 9.160323	N/A	N/A	N/A
Test Software	ADT	ADT_Radiated_V7.6.15.9.2	N/A	N/A	N/A
10dB Attenuator	JFW/USA	50HF-010-SMA	1505	Jun. 03,20	Jun. 03,21
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Feb. 26,20	Feb. 25,21
Signal Pre-Amplifier	EMSI	EMC 9135	980249	Jun. 21,20	Jun. 20,21
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	Jun. 21,20	Jun. 20,21
Signal Pre-Amplifier	EMSI	EMC 184045B	980259	Jun. 21,20	Jun. 20,21

**NOTE:**

1. The calibration interval of the above test instruments is 12 months or 36 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in 3m Chamber.
3. The FCC Site Registration No. is 525120; The Designation No. is CN1171.



### 3.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

#### NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz for Average detection (AV) at frequency above 1GHz.
4. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a "duty cycle correction factor", derived from  $20\log(\text{dwell time}/100 \text{ ms})$ , in an effort to demonstrate compliance with the 15.209 limit.
5. All modes of operation were investigated and the worst-case emissions are reported.

### 3.2.4 DEVIATION FROM TEST STANDARD

No deviation.


### 3.2.5 TEST SETUP




Test Report No.: RF200702W001-1

BUREAU  
VERITAS

< Frequency Range 30MHz~1GHz >



<Frequency Range above 1GHz>



**Note:** Above 1G is a directional antenna

Depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).



Test Report No.: RF200702W001-1

BUREAU  
VERITAS

### 3.2.6 EUT OPERATING CONDITIONS

- a. Set the EUT under full load condition and placed them on a testing table.
- b. Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- c. The necessary accessories enable the EUT in full functions.



Test Report No.: RF200702W001-1

BUREAU  
VERITAS

### 3.2.7 TEST RESULTS

#### BELOW 1GHz WORST-CASE DATA:

30 MHz – 1GHz data:


GFSK DH5

CHANNEL	Channel 78	DETECTOR FUNCTION		Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz			

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M										
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK
33.85	21.69	39.44	40	-18.31	18.98	0.84	37.57	200	360	QP
307.65	42.61	63.16	46	-3.39	13.84	2.24	36.63	200	360	QP
370.26	38.71	57.11	46	-7.29	15.85	2.5	36.75	200	360	QP
437.22	38.68	55.12	46	-7.32	17.69	2.76	36.89	200	360	QP
633.52	39.8	52.97	46	-6.2	20.87	3.28	37.32	200	360	QP
694.11	39.35	50.63	46	-6.65	22.63	3.51	37.42	200	360	QP

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value





Test Report No.: RF200702W001-1


BUREAU  
VERITAS

CHANNEL	Channel 78	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M											
FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	READ LEVEL (dBuV)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA FACTOR (dB /m)	CABLE LOSS (dB)	PREAMP FACTOR (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	REMARK	
34.22	32.29	50.22	40	-7.71	18.79	0.85	37.57	100	0	QP	
117.69	32.82	60.53	43.5	-10.68	7.77	1.43	36.91	100	0	QP	
173.96	29.78	54.66	43.5	-13.72	10.14	1.69	36.71	100	0	QP	
208.16	29.77	53.99	43.5	-13.73	10.57	1.83	36.62	100	0	QP	
436.69	38.4	54.85	46	-7.6	17.68	2.76	36.89	100	0	QP	
631.11	39.65	52.88	46	-6.35	20.8	3.28	37.31	100	0	QP	

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value





Test Report No.: RF200702W001-1

**ABOVE 1GHz WORST-CASE DATA:**

**Note:** For higher frequency, the emission is too low to be detected.

N/A



Test Report No.: RF200702W001-1

## 4 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



Test Report No.: RF200702W001-1

## 5 APPENDIX A – MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---