



# FCC RF Test Report

**APPLICANT** : Sonim Technologies, Inc.  
**EQUIPMENT** : Smartphone  
**BRAND NAME** : Sonim  
**MODEL NAME** : X802  
**FCC ID** : WYPS3111  
**STANDARD** : 47 CFR Part 90(R)  
**CLASSIFICATION** : PCS Licensed Transmitter Held to Ear (PCE)  
**TEST DATE(S)** : Nov. 26, 2024 ~ May 08, 2025

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

This report contains data that were produced under subcontract by Sporton International Inc. (ShenZhen)

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia



Approved by: Jason Jia

**Sportun International Inc. (Kunshan)**  
No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300  
People's Republic of China



## TABLE OF CONTENTS

|   |           |
|---|-----------|
| <b>REVISION HISTORY.....</b>                                    | <b>3</b>  |
| <b>SUMMARY OF TEST RESULT .....</b>                             | <b>4</b>  |
| <b>1 GENERAL DESCRIPTION .....</b>                              | <b>5</b>  |
| 1.1    Applicant .....  | 5         |
| 1.2    Manufacturer.....  | 5         |
| 1.3    Feature of Equipment Under Test .....                    | 5         |
| 1.4    Maximum ERP Power, and Emission Designator .....         | 5         |
| 1.5    Testing Site.....  | 6         |
| 1.6    Test Software.....                                       | 6         |
| 1.7    Applied Standards .....                                  | 7         |
| <b>2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST .....</b>       | <b>8</b>  |
| 2.1    Test Mode.....   | 8         |
| 2.2    Connection Diagram of Test System.....                   | 9         |
| 2.3    Support Unit used in test configuration and system ..... | 9         |
| 2.4    Measurement Results Explanation Example.....             | 9         |
| 2.5    Frequency List of Low/Middle/High Channels .....         | 10        |
| <b>3 CONDUCTED TEST ITEMS .....</b>                             | <b>11</b> |
| 3.1    Measuring Instruments .....                              | 11        |
| 3.2    Conducted Output Power and ERP .....                     | 12        |
| 3.3    Peak-to-Average Ratio .....                              | 13        |
| 3.4    Occupied Bandwidth.....                                  | 14        |
| 3.5    Conducted Band Edge Measurement .....                    | 15        |
| 3.6    Emission Mask.....                                       | 16        |
| 3.7    Conducted Spurious Emission Measurement .....            | 17        |
| 3.8    Frequency Stability Measurement.....                     | 18        |
| <b>4 RADIATED TEST ITEMS .....</b>                              | <b>19</b> |
| 4.1    Measuring Instruments .....                              | 19        |
| 4.2    Test Setup .....   | 19        |
| 4.3    Test Result of Radiated Test .....                       | 20        |
| 4.4    Radiated Spurious Emission Measurement .....             | 21        |
| <b>5 LIST OF MEASURING EQUIPMENT.....</b>                       | <b>22</b> |
| <b>6 MEASUREMENT UNCERTAINTY .....</b>                          | <b>23</b> |
| <b>APPENDIX A. TEST RESULTS OF CONDUCTED TEST</b>               |           |
| <b>APPENDIX B. TEST RESULTS OF RADIATED TEST</b>                |           |
| <b>APPENDIX C. TEST SETUP PHOTOGRAPHS</b>                       |           |



## REVISION HISTORY



## SUMMARY OF TEST RESULT

| Report Section | FCC Rule                                 | Description                                  | Limit                               | Result         | Remark                                       |
|----------------|--|--|-------------------------------------|----------------|--|
| 3.2            | §2.1046                                  | Conducted Output Power                       | —                                   | Reporting only | -  |
|                | §90.542 (a)(7)                           | Effective Radiated Power                     | ERP < 3Watt                         | PASS           | -  |
| 3.3            | -  | Peak-to-Average Ratio                        | —                                   | Reporting only | -  |
| 3.4            | §2.1049                                  | Occupied Bandwidth                           | —                                   | Reporting only | -  |
| 3.5            | §2.1053<br>§90.543 (e)(2)(3)             | Conducted Band Edge Measurement              | Refer standard                      | PASS           | -  |
| 3.6            | §2.1051<br>§90.210(n)                    | Emission Mask                                | Mask B                              | PASS           | -  |
| 3.7            | §2.1053<br>§90.543 (e)(3)                | Conducted Spurious Emission                  | < 43+10log <sub>10</sub> (P[Watts]) | PASS           | -  |
| 3.8            | §2.1055<br>§90.539 (e)                   | Frequency Stability<br>Temperature & Voltage | < ±1.25 ppm                         | PASS           | -  |
| 4.4            | §2.1053<br>§90.543 (e)(3)<br>§90.543 (f) | Radiated Spurious Emission                   | < 43+10log <sub>10</sub> (P[Watts]) | PASS           | Under limit<br>15.28 dB at<br>1581.50<br>MHz |

### Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

### Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



## 1 General Description

### 1.1 Applicant

**Sonim Technologies, Inc.**

4445 Eastgate Mall, Suite 200, San Diego, CA 92121, USA

### 1.2 Manufacturer

**Sonim Technologies, Inc.**

4445 Eastgate Mall, Suite 200, San Diego, CA 92121, USA

### 1.3 Feature of Equipment Under Test

| Product Feature                 |                                |
|---------------------------------|--------------------------------|
| Equipment                       | Smartphone                     |
| Brand Name                      | Sonim                          |
| Model Name                      | X802                           |
| FCC ID                          | WYPS3111                       |
| Tx Frequency                    | LTE Band 14: 788 MHz ~ 798 MHz |
| Rx Frequency                    | LTE Band 14: 758 MHz ~ 768 MHz |
| Bandwidth                       | 5MHz / 10MHz                   |
| Maximum Output Power to Antenna | <Ant1>: 23.82 dBm              |
| Antenna Gain                    | <Ant1>: -4.41dBi               |
| Type of Modulation              | QPSK / 16QAM / 64QAM / 256QAM  |
| HW Version                      | V1.0                           |
| SW Version                      | X80.0-01-14.0-42.18.00         |
| EUT Stage                       | Identical Prototype            |

### 1.4 Maximum ERP Power, and Emission Designator

| LTE Band 14 |                       | QPSK           |                              | 16QAM/64QAM/256QAM |                              |
|-------------|-----------------------|----------------|------------------------------|--------------------|------------------------------|
| BW (MHz)    | Frequency Range (MHz) | Maximum ERP(W) | Emission Designator (99%OBW) | Maximum ERP(W)     | Emission Designator (99%OBW) |
| 5           | 790.5~795.5           | 0.0520         | 4M50G7D                      | 0.0414             | 4M49W7D                      |
| 10          | 793                   | 0.0532         | 8M97G7D                      | 0.0415             | 8M95W7D                      |



## 1.5 Testing Site

Sportun International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

|                           |  |                            |                                       |
|---------------------------|--|----------------------------|---------------------------------------|
| <b>Test Firm</b>          | Sportun International Inc. (Kunshan)   |                            |                                       |
| <b>Test Site Location</b> | No. 1098, Pengxi North Road, Kunshan Economic Development Zone<br>Jiangsu Province 215300 People's Republic of China<br>TEL : +86-512-57900158 |                            |                                       |
| <b>Test Site No.</b>      | <b>Sportun Site No.</b>  | <b>FCC Designation No.</b> | <b>FCC Test Firm Registration No.</b> |
|                           | TH01-KS  | CN1257                     | 314309                                |

Sportun International Inc. (ShenZhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

|                           |   |                            |                                       |
|---------------------------|---|----------------------------|---------------------------------------|
| <b>Test Firm</b>          | Sportun International Inc. (ShenZhen)   |                            |                                       |
| <b>Test Site Location</b> | 101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang<br>Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong<br>Province 518103 People's Republic of China<br>TEL: +86-755-86066985 |                            |                                       |
| <b>Test Site No.</b>      | <b>Sportun Site No.</b>   | <b>FCC Designation No.</b> | <b>FCC Test Firm Registration No.</b> |
|                           | 03CH01-SZ   | CN1256                     | 421272                                |

Test data subcontracted: Radiated Spurious Emission test case in section 4 of this report

## 1.6 Test Software

| Item | Site      | Manufacture | Name | Version     |
|------|-----------|-------------|------|-------------|
| 1.   | 03CH01-SZ | AUDIX       | E3   | 6.2009-8-24 |



## **1.7 Applied Standards**

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 90(R)
- ANSI C63.26
- KDB 971168 D01 Power Meas License Digital Systems v03r01
- KDB 412172 D01 Determining ERP and EIRP v01r01

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test


### 2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas License Digital Systems v03r01 with maximum output power. Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission. (Z Plane)

| Conducted<br>Test Cases           | Band   | Bandwidth (MHz) |   |   |    |    |    | Modulation |       |       |        | RB # |      |      | Test Channel |   |   |
|-----------------------------------|--|-----------------|---|---|----|----|----|------------|-------|-------|--------|------|------|------|--------------|---|---|
|                                   |  | 1.4             | 3 | 5 | 10 | 15 | 20 | QPSK       | 16QAM | 64QAM | 256QAM | 1    | Half | Full | L            | M | H |
| Max. Output<br>Power              | 14   | -               | - | V |    | -  | -  | V          | V     | V     | V      | V    | V    | V    | V            | V | V |
|                                   | 14   | -               | - |   | V  | -  | -  | V          | V     | V     | V      | V    | V    | V    |              | V |   |
| Peak-to-Average<br>Ratio          | 14   | -               | - | V | V  | -  | -  | V          | V     | V     | V      | V    |      | V    |              | V |   |
| 26dB and 99%<br>Bandwidth         | 14   | -               | - | V |    | -  | -  | V          | V     |       |        |      |      | V    | V            | V | V |
|                                   | 14   | -               | - |   | V  | -  | -  | V          | V     |       |        |      |      | V    |              | V |   |
| Conducted<br>Band Edge            | 14   | -               | - | V |    | -  | -  | V          | V     | V     | V      | V    |      | V    | V            |   | V |
|                                   | 14   | -               | - |   | V  | -  | -  | V          | V     | V     | V      | V    |      | V    |              | V |   |
| Emission Mask                     | 14   | -               | - | V |    | -  | -  | V          | V     | V     |        | V    |      | V    | V            | V | V |
|                                   | 14   | -               | - |   | V  | -  | -  | V          | V     | V     |        | V    |      | V    |              | V |   |
| Conducted<br>Spurious<br>Emission | 14   | -               | - | V |    | -  | -  | V          |       |       |        | V    |      |      | V            | V | V |
|                                   | 14   | -               | - |   | V  | -  | -  | V          |       |       |        | V    |      |      |              | V |   |
| Frequency<br>Stability            | 14   | -               | - | V | V  | -  | -  | V          |       |       |        |      |      | V    |              | V |   |
| E.R.P                             | 14   | -               | - | V |    | -  | -  | V          | V     | V     | V      | V    | V    | V    | V            | V | V |
|                                   | 14   | -               | - |   | V  | -  | -  | V          | V     | V     | V      | V    | V    | V    |              | V |   |
| Radiated<br>Spurious<br>Emission  | 14   | -               | - | V | V  | -  | -  | V          |       |       |        | V    |      |      | V            | V | V |
| Note                              | <ol style="list-style-type: none"> <li>The mark "V" means that this configuration is chosen for testing</li> <li>The mark "--" means that this bandwidth is not supported.</li> <li>The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.</li> </ol> |                 |   |   |    |    |    |            |       |       |        |      |      |      |              |   |   |



## 2.2 Connection Diagram of Test System



## 2.3 Support Unit used in test configuration and system

| Item | Equipment        | Trade Name | Model No. | FCC ID | Data Cable | Power Cord        |
|------|------------------|------------|-----------|--------|------------|-------------------|
| 1.   | LTE Base Station | Anritsu    | MT8820C   | N/A    | N/A        | Unshielded, 1.8 m |
| 2.   | DC Power Supply  | GW INSTEK  | GPS-3030D | N/A    | N/A        | Unshielded, 1.8 m |

## 2.4 Measurement Results Explanation Example

### For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss.

*Offset = RF cable loss.*

Following shows an offset computation example with cable loss 4.6 dB.

Example :

*Offset(dB) = RF cable loss(dB).*

= 4.6 (dB)



## 2.5 Frequency List of Low/Middle/High Channels

| LTE Band 14 Channel and Frequency List |                        |        |        |         |
|--|------------------------|--------|--------|---------|
| BW [MHz]                               | Channel/Frequency(MHz) | Lowest | Middle | Highest |
| 10                                     | Channel                | -      | 23330  | -       |
|  | Frequency              | -      | 793    | -       |
| 5                                      | Channel                | 23305  | 23330  | 23355   |
|  | Frequency              | 790.5  | 793    | 795.5   |

### 3 Conducted Test Items

#### 3.1 Measuring Instruments


See list of measuring instruments of this test report.

##### 3.1.1 Test Setup


##### 3.1.2 Conducted Output Power



##### 3.1.3 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge, Emission Mask, and Conducted Spurious Emission



##### 3.1.4 Frequency Stability



##### 3.1.5 Test Result of Conducted Test

Please refer to Appendix A.



## 3.2 Conducted Output Power and ERP

### 3.2.1 Description of the Conducted Output Power Measurement and ERP

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 3 Watts for LTE Band 14.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_c$ ,  $ERP = EIRP - 2.15$ , where

$P_T$  = transmitter output power in dBm

$G_T$  = gain of the transmitting antenna in dBi

$L_c$  = signal attenuation in the connecting cable between the transmitter and antenna in dB

### 3.2.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.



### 3.3 Peak-to-Average Ratio

#### 3.3.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

#### 3.3.2 Test Procedures

1. The EUT was connected to spectrum and system simulator via a power divider.
2. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
3. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
4. Record the deviation as Peak to Average Ratio.



## 3.4 Occupied Bandwidth

### 3.4.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

### 3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace. (this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



## 3.5 Conducted Band Edge Measurement

### 3.5.1 Description of Conducted Band Edge Measurement

For operations in the 758-768 MHz and the 788-798 MHz bands

- (1) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than  $76 + 10 \log (P)$  dB in a 6.25 kHz band segment, for base and fixed stations.
- (2) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than  $65 + 10 \log (P)$  dB in a 6.25 kHz band segment, for mobile and portable stations.
- (3) On any frequency between 775-788 MHz, above 805 MHz, and below 758 MHz, by at least  $43 + 10 \log (P)$  dB.

### 3.5.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set spectrum analyzer with RMS detector.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. Checked that all the results comply with the emission limit line.

Example:

$$\begin{aligned} \text{The limit line is derived from } & 43 + 10\log(P) \text{ dB below the transmitter power } P(\text{Watts}) \\ = & P(\text{W}) - [43 + 10\log(P)] \text{ (dB)} \\ = & [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)} = -13 \text{ dBm.} \end{aligned}$$



## 3.6 Emission Mask

### 3.6.1 Description of Emission Mask

<Emission Mask B>.

For transmitters that are equipped with an audio low-pass filter, the power of any emission must be attenuated below the unmodulated carrier power (P) as follows:

- (1) On any frequency removed from the assigned frequency by more than 50 percent, but not more than 100 percent of the authorized bandwidth: At least 25 dB.
- (2) On any frequency removed from the assigned frequency by more than 100 percent, but not more than 250 percent of the authorized bandwidth: At least 35 dB.
- (3) On any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth: At least  $43 + 10 \log(P)$  dB.

### 3.6.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
5. Set spectrum analyzer with RMS detector.
6. Taking the record of maximum spurious emission.
7. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
8. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)  
 $= P(W) - [43 + 10\log(P)]$  (dB)  
 $= [30 + 10\log(P)]$  (dBm) -  $[43 + 10\log(P)]$  (dB)  
 $= -13$  dBm.



## 3.7 Conducted Spurious Emission Measurement

### 3.7.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30MHz up to a frequency including its 10<sup>th</sup> harmonic.

### 3.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and base station via power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and power divider. The path loss was compensated to the results for each measurement.  
Path Loss Factor = Cable + Power Divider, Where the cable and power divider are the total path loss for the system calibration.
4. The low/middle/high channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's, for under 1GHz RBW = 100kHz, VBW = 300kHz and for above 1GHz RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
7. Set spectrum analyzer with RMS detector.
8. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
9. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)  
 $= P(W) - [43 + 10\log(P)]$  (dB)  
 $= [30 + 10\log(P)]$  (dBm) -  $[43 + 10\log(P)]$  (dB)  
 $= -13$  dBm.



## 3.8 Frequency Stability Measurement

### 3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block.

### 3.8.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
1. The EUT was set up in the thermal chamber and connected with the system simulator.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

### 3.8.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5.
2. The EUT was placed in a temperature chamber at  $20\pm5^{\circ}\text{C}$  and connected with the system simulator.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
3. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
4. The variation in frequency was measured for the worst case.


## 4 Radiated Test Items

### 4.1 Measuring Instruments


See list of measuring instruments of this test report.

### 4.2 Test Setup


#### 4.2.1 For radiated test below 30MHz



#### 4.2.2 For radiated test from 30MHz to 1GHz



#### 4.2.3 For radiated test above 1GHz



### 4.3 Test Result of Radiated Test

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.



## 4.4 Radiated Spurious Emission Measurement

### 4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI C63.26.

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

For operations in the 758-775 MHz and 788-805 MHz bands, all emissions including harmonics in the band 1559–1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

### 4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
3. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
5. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9.  $EIRP (dBm) = S.G. Power - Tx Cable Loss + Tx Antenna Gain$
10.  $ERP (dBm) = EIRP - 2.15$
11. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)  
 $= P(W) - [43 + 10\log(P)]$  (dB)  
 $= [30 + 10\log(P)]$  (dBm) -  $[43 + 10\log(P)]$  (dB)  
 $= -13$  dBm.



## 5 List of Measuring Equipment

| Instrument                     | Manufacturer   | Model No.                        | Serial No.   | Characteristics         | Calibration Date | Test Date                  | Due Date      | Remark                |
|--------------------------------|----------------|----------------------------------|--------------|-------------------------|------------------|----------------------------|---------------|-----------------------|
| Spectrum Analyzer              | R&S            | FSV40                            | 101040       | 10Hz~40GHz              | Oct. 10, 2024    | Nov. 26, 2024~May 08, 2025 | Oct. 09, 2025 | Conducted (TH01-KS)   |
| Power divider                  | STI            | STI08-0055                       | -            | 0.5~40GHz               | NCR              | Nov. 26, 2024~May 08, 2025 | NCR           | Conducted (TH01-KS)   |
| Temperature & humidity chamber | Hongzhan       | LP-150U                          | H2014011440  | -40~+150°C<br>20%~95%RH | Jul. 04, 2024    | Nov. 26, 2024~May 08, 2025 | Jul. 03, 2025 | Conducted (TH01-KS)   |
| EXA Spectrum Analyzer          | KEYSIGHT       | N9010A                           | MY55150213   | 10Hz~44GHz              | Jul. 03, 2024    | Jan. 24, 2025              | Jul. 02, 2025 | Radiation (03CH01-SZ) |
| Loop Antenna                   | R&S            | HFH2-Z2E                         | 101141       | 9kHz~30MHz              | Dec. 28, 2024    | Jan. 24, 2025              | Dec. 27, 2025 | Radiation (03CH01-SZ) |
| HF Amplifier                   | KEYSIGHT       | 83017A                           | MY53270105   | 0.5GHz~26.5Ghz          | Oct. 14, 2024    | Jan. 24, 2025              | Oct. 13, 2025 | Radiation (03CH01-SZ) |
| Bilog Antenna                  | TeseQ          | CBL6112D                         | 35407        | 30MHz-2GHz              | Oct. 24, 2023    | Jan. 24, 2025              | Oct. 23, 2025 | Radiation (03CH01-SZ) |
| Double Ridge Horn Antenna      | ETS-Lindgren   | 3117                             | 00119436     | 1GHz~18GHz              | Jul. 04, 2024    | Jan. 24, 2025              | Jul. 03, 2025 | Radiation (03CH01-SZ) |
| SHF-EHF Horn                   | com-power      | AH-840                           | 101071       | 18Ghz-40GHz             | Apr. 09, 2024    | Jan. 24, 2025              | Apr. 08, 2025 | Radiation (03CH01-SZ) |
| LF Amplifier                   | EM Electronics | EM330                            | 060788       | 20MHz-3GHz              | Dec. 25, 2024    | Jan. 24, 2025              | Dec. 24, 2025 | Radiation (03CH01-SZ) |
| HF Amplifier                   | MITEQ          | AMF-7D-00<br>101800-30-1<br>0P-R | 1943528      | 1GHz~18GHz              | Oct. 14, 2024    | Jan. 24, 2025              | Oct. 13, 2025 | Radiation (03CH01-SZ) |
| HF Amplifier                   | MITEQ          | TTA1840-35<br>-HG                | 1871923      | 18GHz~40GHz             | Jul. 03, 2024    | Jan. 24, 2025              | Jul. 02, 2025 | Radiation (03CH01-SZ) |
| AC Power Source                | Chroma         | 61601                            | 616010001985 | N/A                     | Oct. 14, 2024    | Jan. 24, 2025              | Oct. 13, 2025 | Radiation (03CH01-SZ) |
| Turn Table                     | EM             | EM1000                           | N/A          | 0~360 degree            | NCR              | Jan. 24, 2025              | NCR           | Radiation (03CH01-SZ) |
| Antenna Mast                   | EM             | EM1000                           | N/A          | 1 m~4 m                 | NCR              | Jan. 24, 2025              | NCR           | Radiation (03CH01-SZ) |

NCR: No Calibration Required



## 6 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

### Uncertainty of Conducted Measurement

| Test Item                              | Uncertainty |
|--|-------------|
| Conducted Spurious Emission & Bandedge | ±2.22 dB    |
| Occupied Channel Bandwidth             | ±0.1%       |
| Conducted Power                        | ±0.50 dB    |
| Peak to Average Ratio                  | ±0.90 dB    |
| Frequency Stability                    | ±0.04ppm    |

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

|  |         |
|--|---------|
| Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_{c(y)}$ ) | 2.48 dB |
|--|---------|

### Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

|  |         |
|--|---------|
| Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_{c(y)}$ ) | 3.53 dB |
|--|---------|

### Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

|  |         |
|--|---------|
| Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2U_{c(y)}$ ) | 4.02 dB |
|--|---------|

----- THE END -----



## Appendix A. Test Results of Conducted Test

|                        |            |                            |         |
|------------------------|------------|----------------------------|---------|
| <b>Test Engineer :</b> | Smile Wang | <b>Temperature :</b>       | 22~23°C |
|                        |            | <b>Relative Humidity :</b> | 40~42%  |

### Conducted Output Power(Average power) and ERP

#### LTE Band 14\_Ant1:

| BW [MHz]        | Modulation | RB Size | RB Offset | Power Low Ch. / Freq. | Power Middle Ch. / Freq. | Power High Ch. / Freq. | ERP(W) |   |   |
|-----------------|------------|---------|-----------|-----------------------|--------------------------|------------------------|--------|---|---|
| Channel         |            |         |           | 23330                 |                          |                        |        |   |   |
| Frequency (MHz) |            |         |           | 793                   |                          |                        |        | M |   |
| 10              | QPSK       | 1       | 0         | 23.82                 |                          |                        | 0.0532 |   |   |
| 10              | QPSK       | 1       | 25        | 23.55                 |                          |                        | 0.0500 |   |   |
| 10              | QPSK       | 1       | 49        | 23.68                 |                          |                        | 0.0515 |   |   |
| 10              | QPSK       | 25      | 0         | 22.86                 |                          |                        | 0.0427 |   |   |
| 10              | QPSK       | 25      | 12        | 22.68                 |                          |                        | 0.0409 |   |   |
| 10              | QPSK       | 25      | 25        | 22.68                 |                          |                        | 0.0409 |   |   |
| 10              | QPSK       | 50      | 0         | 22.82                 |                          |                        | 0.0423 |   |   |
| 10              | 16QAM      | 1       | 0         | 22.53                 |                          |                        | 0.0395 |   |   |
| 10              | 16QAM      | 1       | 25        | 22.61                 |                          |                        | 0.0403 |   |   |
| 10              | 16QAM      | 1       | 49        | 22.74                 |                          |                        | 0.0415 |   |   |
| 10              | 16QAM      | 25      | 0         | 21.50                 |                          |                        | 0.0312 |   |   |
| 10              | 16QAM      | 25      | 12        | 21.51                 |                          |                        | 0.0313 |   |   |
| 10              | 16QAM      | 25      | 25        | 21.61                 |                          |                        | 0.0320 |   |   |
| 10              | 16QAM      | 50      | 0         | 21.67                 |                          |                        | 0.0324 |   |   |
| 10              | 64QAM      | 1       | 0         | 21.63                 |                          |                        | 0.0321 |   |   |
| 10              | 64QAM      | 1       | 25        | 21.72                 |                          |                        | 0.0328 |   |   |
| 10              | 64QAM      | 1       | 49        | 21.65                 |                          |                        | 0.0323 |   |   |
| 10              | 64QAM      | 25      | 0         | 20.62                 |                          |                        | 0.0255 |   |   |
| 10              | 64QAM      | 25      | 12        | 20.72                 |                          |                        | 0.0261 |   |   |
| 10              | 64QAM      | 25      | 25        | 20.42                 |                          |                        | 0.0243 |   |   |
| 10              | 64QAM      | 50      | 0         | 20.48                 |                          |                        | 0.0247 |   |   |
| 10              | 256QAM     | 1       | 0         | 18.49                 |                          |                        | 0.0156 |   |   |
| 10              | 256QAM     | 1       | 25        | 18.50                 |                          |                        | 0.0156 |   |   |
| 10              | 256QAM     | 1       | 49        | 18.62                 |                          |                        | 0.0161 |   |   |
| 10              | 256QAM     | 25      | 0         | 18.48                 |                          |                        | 0.0156 |   |   |
| 10              | 256QAM     | 25      | 12        | 18.68                 |                          |                        | 0.0163 |   |   |
| 10              | 256QAM     | 25      | 25        | 18.43                 |                          |                        | 0.0154 |   |   |
| 10              | 256QAM     | 50      | 0         | 18.50                 |                          |                        | 0.0156 |   |   |
| Channel         |            |         |           | 23305                 | 23330                    | 23355                  | ERP(W) |   |   |
| Frequency (MHz) |            |         |           | 790.5                 | 793                      | 795.5                  | L      | M | H |




|   |        |    |    |       |       |       |        |        |        |
|---|--------|----|----|-------|-------|-------|--------|--------|--------|
| 5 | QPSK   | 1  | 0  | 23.66 | 23.72 | 23.71 | 0.0513 | 0.0520 | 0.0519 |
| 5 | QPSK   | 1  | 12 | 23.56 | 23.62 | 23.54 | 0.0501 | 0.0508 | 0.0499 |
| 5 | QPSK   | 1  | 24 | 23.51 | 23.64 | 23.66 | 0.0495 | 0.0511 | 0.0513 |
| 5 | QPSK   | 12 | 0  | 22.51 | 22.70 | 22.48 | 0.0394 | 0.0411 | 0.0391 |
| 5 | QPSK   | 12 | 7  | 22.64 | 22.63 | 22.77 | 0.0406 | 0.0405 | 0.0418 |
| 5 | QPSK   | 12 | 13 | 22.54 | 22.76 | 22.61 | 0.0396 | 0.0417 | 0.0403 |
| 5 | QPSK   | 25 | 0  | 22.67 | 22.64 | 22.45 | 0.0408 | 0.0406 | 0.0388 |
| 5 | 16QAM  | 1  | 0  | 22.64 | 22.56 | 22.67 | 0.0406 | 0.0398 | 0.0408 |
| 5 | 16QAM  | 1  | 12 | 22.66 | 22.56 | 22.60 | 0.0407 | 0.0398 | 0.0402 |
| 5 | 16QAM  | 1  | 24 | 22.73 | 22.69 | 22.45 | 0.0414 | 0.0410 | 0.0388 |
| 5 | 16QAM  | 12 | 0  | 21.59 | 21.52 | 21.73 | 0.0318 | 0.0313 | 0.0329 |
| 5 | 16QAM  | 12 | 7  | 21.75 | 21.51 | 21.66 | 0.0330 | 0.0313 | 0.0324 |
| 5 | 16QAM  | 12 | 13 | 21.68 | 21.58 | 21.64 | 0.0325 | 0.0318 | 0.0322 |
| 5 | 16QAM  | 25 | 0  | 21.67 | 21.68 | 21.57 | 0.0324 | 0.0325 | 0.0317 |
| 5 | 64QAM  | 1  | 0  | 21.55 | 21.66 | 21.57 | 0.0316 | 0.0324 | 0.0317 |
| 5 | 64QAM  | 1  | 12 | 21.59 | 21.55 | 21.45 | 0.0318 | 0.0316 | 0.0308 |
| 5 | 64QAM  | 1  | 24 | 21.52 | 21.61 | 21.73 | 0.0313 | 0.0320 | 0.0329 |
| 5 | 64QAM  | 12 | 0  | 20.41 | 20.51 | 20.73 | 0.0243 | 0.0248 | 0.0261 |
| 5 | 64QAM  | 12 | 7  | 20.72 | 20.68 | 20.71 | 0.0261 | 0.0258 | 0.0260 |
| 5 | 64QAM  | 12 | 13 | 20.65 | 20.51 | 20.58 | 0.0256 | 0.0248 | 0.0252 |
| 5 | 64QAM  | 25 | 0  | 20.49 | 20.65 | 20.57 | 0.0247 | 0.0256 | 0.0252 |
| 5 | 256QAM | 1  | 0  | 18.31 | 18.56 | 18.31 | 0.0150 | 0.0158 | 0.0150 |
| 5 | 256QAM | 1  | 12 | 18.35 | 18.38 | 18.42 | 0.0151 | 0.0152 | 0.0153 |
| 5 | 256QAM | 1  | 24 | 18.44 | 18.49 | 18.26 | 0.0154 | 0.0156 | 0.0148 |
| 5 | 256QAM | 12 | 0  | 18.39 | 18.40 | 18.57 | 0.0152 | 0.0153 | 0.0159 |
| 5 | 256QAM | 12 | 7  | 18.51 | 18.62 | 18.55 | 0.0157 | 0.0161 | 0.0158 |
| 5 | 256QAM | 12 | 13 | 18.49 | 18.40 | 18.32 | 0.0156 | 0.0153 | 0.0150 |
| 5 | 256QAM | 25 | 0  | 18.41 | 18.67 | 18.32 | 0.0153 | 0.0163 | 0.0150 |



## LTE Band 14


## Peak-to-Average Ratio

| Mode      | LTE Band 14 / 5MHz |         |         |         |             |
|-----------|--------------------|---------|---------|---------|-------------|
| Mod.      | QPSK               | 16QAM   | 64QAM   | 256QAM  | Limit: 13dB |
| RB Size   | Full RB            | Full RB | Full RB | Full RB | Result      |
| Middle CH | 5.22               | 6.26    | 6.70    | 6.75    | PASS        |






## Middle Channel / Full RB/ 64QAM



Date: 8.MAY.2025 11:22:15


## Middle Channel / Full RB/ 256QAM



Date: 8.MAY.2025 11:22:43



| Mode      | LTE Band 14 / 10MHz |         |         |         |             |
|-----------|---------------------|---------|---------|---------|-------------|
| Mod.      | QPSK                | 16QAM   | 64QAM   | 256QAM  | Limit: 13dB |
| RB Size   | Full RB             | Full RB | Full RB | Full RB | Result      |
| Middle CH | 5.19                | 6.17    | 6.61    | 6.93    | PASS        |





## Middle Channel / Full RB/ 64QAM



Date: 26.NOV.2024 23:04:58

## Middle Channel / Full RB/ 256QAM




Date: 26.NOV.2024 23:05:20



## 26dB Bandwidth


| Mode      | LTE Band 14 : 26dB BW(MHz) |       |
|-----------|----------------------------|-------|
| BW        | 10MHz                      |       |
| Mod.      | QPSK                       | 16QAM |
| Middle CH | 9.81                       | 9.81  |
| BW        | 5MHz                       |       |
| Mod.      | QPSK                       | 16QAM |
| Middle CH | 4.90                       | 5.02  |






## Occupied Bandwidth

| Mode      | LTE Band 14 : 99%OBW(MHz) |       |
|-----------|---------------------------|-------|
| BW        | 10MHz                     |       |
| Mod.      | QPSK                      | 16QAM |
| Middle CH | 8.97                      | 8.95  |
| BW        | 5MHz                      |       |
| Mod.      | QPSK                      | 16QAM |
| Middle CH | 4.50                      | 4.49  |





## Conducted Band Edge







## LTE Band 14 / 5MHz / 16QAM

## Lowest Band Edge / 1 RB

## Highest Band Edge / 1 RB




Date: 26.NOV.2024 22:15:51

Date: 26.NOV.2024 22:32:23


## Lowest Band Edge / Full RB


## Highest Band Edge / Full RB



Date: 26.NOV.2024 22:22:34

Date: 26.NOV.2024 22:38:11









## LTE Band 14 / 5MHz / 256QAM

## Lowest Band Edge / 1 RB

## Highest Band Edge / 1 RB





Date: 26.NOV.2024 22:18:44

Date: 26.NOV.2024 22:35:16


## Lowest Band Edge / Full RB

## Highest Band Edge / Full RB



Date: 26.NOV.2024 22:25:26

Date: 26.NOV.2024 22:41:04








## LTE Band 14 / 10MHz / 16QAM

## Lowest Band Edge / 1 RB


## Highest Band Edge / 1 RB



## Band Edge / Full RB



Date: 26.NOV.2024 22:58:04








## LTE Band 14 / 10MHz / 256QAM

## Lowest Band Edge / 1 RB

## Highest Band Edge / 1 RB



## Band Edge / Full RB



Date: 26.NOV.2024 23:00:56





## Conducted Spurious Emission


### LTE Band 14 / 5MHz

#### Lowest Channel / QPSK

#### Middle Channel / QPSK



### Highest Channel / QPSK



Note: DCC = Duty Cycle Correction / APS = Antenna Port Summation  
Ver 1.1(20241209)

2025-05-06 14:02:00

Count: 100/100 Sweep Point: 35005 Dector: RMS Trace: AVERAGE

Pass

| Item | Range Low   | Range Up    | RBW   | VBW   | Frequency     | Power Abs   | Limit      | Path Loss Factor | DCC      | APS |
|------|-------------|-------------|-------|-------|---------------|-------------|------------|------------------|----------|-----|
| 1    | 30.000 MHz  | 763.000 MHz | 1 MHz | 3 MHz | 762.77050 MHz | -57.699 dBm | -44.699 dB | -13.000 dBm      | 4.973 dB | --- |
| 2    | 763.000 MHz | 806.000 MHz | 1 MHz | 3 MHz | 793.36750 MHz | -24.850 dBm | -5.150 dB  | 30.000 dBm       | 4.984 dB | --- |
| 3    | 806.000 MHz | 1.000 GHz   | 1 MHz | 3 MHz | 967.77625 MHz | -66.333 dBm | -53.333 dB | -13.000 dBm      | 5.055 dB | --- |
| 4    | 1.000 GHz   | 3.000 GHz   | 1 MHz | 3 MHz | 2.38050 GHz   | -29.941 dBm | -16.941 dB | -13.000 dBm      | 6.486 dB | --- |
| 5    | 3.000 GHz   | 8.000 GHz   | 1 MHz | 3 MHz | 6.048400 GHz  | -50.221 dBm | -37.221 dB | -13.000 dBm      | 8.294 dB | --- |

Note: DCC = Duty Cycle Correction / APS = Antenna Port Summation  
Ver 1.1(20241209)


2025-05-06 14:03:07



## LTE Band 14 / 10MHz

## Middle Channel / QPSK

Count: 100/100 Sweep Point: 35005 Dector: RMS Trace: AVERAGE



| Item | Range Low   | Range Up    | RBW   | VBW   | Frequency     | Power Abs   | Limit      | Limit       | Path Loss Factor | DCC | APS |
|------|-------------|-------------|-------|-------|---------------|-------------|------------|-------------|------------------|-----|-----|
| 1    | 30.000 MHz  | 763.000 MHz | 1 MHz | 3 MHz | 760.58500 MHz | -53.140 dBm | -40.140 dB | -13.000 dBm | 4.973 dB         | --- | --- |
| 2    | 763.000 MHz | 806.000 MHz | 1 MHz | 3 MHz | 788.59700 MHz | 25.034 dBm  | -4.966 dB  | 30.000 dBm  | 4.984 dB         | --- | --- |
| 3    | 806.000 MHz | 1.000 GHz   | 1 MHz | 3 MHz | 995.66125 MHz | -61.541 dBm | -48.541 dB | -13.000 dBm | 5.055 dB         | --- | --- |
| 4    | 1.000 GHz   | 3.000 GHz   | 1 MHz | 3 MHz | 2.36600 GHz   | -29.529 dBm | -16.529 dB | -13.000 dBm | 6.486 dB         | --- | --- |
| 5    | 3.000 GHz   | 8.000 GHz   | 1 MHz | 3 MHz | 6.49650 GHz   | -45.966 dBm | -32.966 dB | -13.000 dBm | 8.294 dB         | --- | --- |

Note: DCC = Duty Cycle Correction / APS = Antenna Port Summation  
Ver 1.1(20241209)

2025-05-06 14:03:14

**Mask**