



FCC RF Test Report

APPLICANT : Sonim Technologies, Inc.
EQUIPMENT : Smartphone
BRAND NAME : Sonim
MODEL NAME : X802
FCC ID : WYPS3111
STANDARD : 47 CFR Part 27 Subpart O (3700-3980MHz)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)
TEST DATE(S) : Nov. 17, 2024 ~ Apr. 23, 2025

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

This report contains data that were produced under subcontract by Sporton International Inc. (ShenZhen)

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (Kunshan)

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China**



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test	5
1.4 Product Specification of Equipment Under Test	5
1.5 Modification of EUT	6
1.6 Maximum EIRP and Emission Designator	6
1.7 Testing Location	8
1.8 Test Software	9
1.9 Applicable Standards	9
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	10
2.1 Test Mode	10
2.2 Connection Diagram of Test System	11
2.3 Support Unit used in test configuration and system	11
2.4 Measurement Results Explanation Example	11
2.5 Frequency List of Low/Middle/High Channels	12
3 CONDUCTED TEST ITEMS	13
3.1 Measuring Instruments	13
3.2 Test Setup	13
3.3 Test Result of Conducted Test	13
3.4 Conducted Output Power and EIRP	14
3.5 Peak-to-Average Ratio	15
3.6 Occupied Bandwidth	16
3.7 Conducted Band Edge	17
3.8 Conducted Spurious Emission	18
3.9 Frequency Stability	19
4 RADIATED TEST ITEMS	20
4.1 Measuring Instruments	20
4.2 Test Setup	20
4.3 Test Result of Radiated Test	21
4.4 Radiated Spurious Emission	22
5 LIST OF MEASURING EQUIPMENT	23
6 MEASUREMENT UNCERTAINTY	24
APPENDIX A. TEST RESULTS OF CONDUCTED TEST	
APPENDIX B. TEST RESULTS OF RADIATED TEST	
APPENDIX C. TEST SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG4O2403T	Rev. 01	Initial issue of report	May 22, 2025
FG4O2403T	Rev. 02	Updated Conducted power for 5G NR n77/78 main PA This report is an updated version, replacing the report issued on May 22, 2025	Jun. 26, 2025



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	-	PASS	-
	§27.50(j)(3)	Equivalent Isotropic Radiated Power	EIRP < 1Watt		
3.5	§27.50(j)(4)	Peak-to-Average Ratio	<13 dB	PASS	-
3.6	§2.1049	Occupied Bandwidth	-	PASS	-
3.7	§2.1051 §27.53(l)(2)	Conducted Band Edge Measurement	< 43+10log ₁₀ (P[Watts])	PASS	-
3.8	§2.1051 §27.53(l)(2)	Conducted Spurious Emission	< 43+10log ₁₀ (P[Watts])	PASS	-
3.9	§27.54	Frequency Stability Temperature & Voltage	Within Authorized Band	PASS	-
4.4	§2.1053 §27.53(l)(2)	Radiated Spurious Emission	< 43+10log ₁₀ (P[Watts])	PASS	Under limit 26.69 dB at 11643.600 MHz

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

Sonim Technologies, Inc.

4445 Eastgate Mall,Suite200, San Diego,CA92121,USA

1.2 Manufacturer

Sonim Technologies, Inc.

4445 Eastgate Mall,Suite200, San Diego,CA92121,USA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Smartphone
Brand Name	Sonim
Model Name	X802
FCC ID	WYPS3111
HW Version	V1.0
SW Version	X80.0-01-14.0-42.18.00
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency	5G NR n77: 3700 MHz ~ 3980 MHz 5G NR n78: 3700 MHz ~ 3800 MHz
SCS	30kHz
Bandwidth	n77: 20 / 30 / 40 / 60 / 80 / 100MHz n78: 20 / 30 / 40 / 50 / 60 / 70 / 80 / 90 / 100MHz
Antenna Gain	<Ant. 3> 5G NR n77: -2.97 dBi 5G NR n78: -2.97 dBi <Ant. 4> 5G NR n77: -1.20 dBi 5G NR n78: -1.20 dBi <Ant. 6> 5G NR n77: -5.30 dBi 5G NR n78: -5.30 dBi <Ant. 7> 5G NR n77: -2.97 dBi 5G NR n78: -2.97 dBi
Type of Modulation	CP-OFDM: QPSK / 16QAM / 64QAM / 256QAM DFT-s-OFDM: PI/2 BPSK / QPSK / 16QAM / 64QAM / 256QAM

Remark:

1. The maximum EIRP is calculated from max output power and max antenna gain, only the maximum EIRP is shown in the report, 5G NR n77/n78 for Antenna 4.
2. The device supports two PAs for 5G NR n77 (main PA, and other PA for NSA mode only), both the PAs are full tested.
3. 5G NR n77/n78 main PA support SA and NSA mode, according to the maximum power between SA and NSA mode, SA covers NSA mode for main PA.
4. 5G NR n77/n78 Single Carrier supports PC2 and UL MIMO mode supports PC2.
5. 5G NR n77/n78 supports UL MIMO mode for Ant.(3+7).
6. 5G NR n77/n78 UL_MIMO mode only supports CP-OFDM Modulation, the MIMO mode is completely uncorrelated, so the directional gain is selected the maximum gain among all antennas.
7. For UL MIMO mode, the conducted BE/Spurious are tested at single antenna port and add $10 \cdot \log(N_{\text{ANT}})$ according to KDB 662911 D01.
8. All the supported EN-DC combinations are verified conducted power, only the EN-DC combination with highest power are shown in the report.
9. The EN-DC mode combination could be referred to the product spec.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum EIRP and Emission Designator

5G NR n77 SA		PI/2 BPSK / QPSK		16QAM / 64QAM / 256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
20	3710.01 ~ 3969.99	0.4436	18M2G7D	0.2818	18M2W7D
30	3715.02 ~ 3964.98	0.4467	27M8G7D	0.2773	27M9W7D
40	3720.00 ~ 3960.00	0.4285	37M8G7D	0.2655	37M9W7D
60	3730.02 ~ 3949.98	0.4266	57M7G7D	0.2673	57M8W7D
80	3740.01 ~ 3939.99	0.4178	77M4G7D	0.2606	77M5W7D
100	3750.00 ~ 3930.00	0.4753	97M4G7D	0.3083	97M4W7D



EN-DC_5A_n77A other PA		PI/2 BPSK / QPSK		16QAM / 64QAM / 256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
20	3710.01 ~ 3969.99	0.1486	18M2G7D	0.1042	18M3W7D
30	3715.02 ~ 3964.98	0.1510	27M8G7D	0.1069	27M9W7D
40	3720.00 ~ 3960.00	0.1542	37M8G7D	0.1026	37M9W7D
60	3730.02 ~ 3949.98	0.1592	57M8G7D	0.1021	57M8W7D
80	3740.01 ~ 3939.99	0.1644	77M5G7D	0.1030	77M6W7D
100	3750.00 ~ 3930.00	0.1910	97M4G7D	0.1262	97M5W7D

5G NR n78 SA		PI/2 BPSK / QPSK		16QAM / 64QAM / 256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
20	3710.01 ~ 3789.99	0.3648	18M2G7D	0.2275	18M2W7D
30	3715.02 ~ 3784.98	0.3972	27M8G7D	0.2512	27M9W7D
40	3720.00 ~ 3780.00	0.4055	37M8G7D	0.2636	37M9W7D
50	3725.01 ~ 3774.99	0.3999	47M6G7D	0.2489	47M5W7D
60	3730.02 ~ 3769.98	0.3846	57M7G7D	0.2404	57M8W7D
70	3735.00 ~ 3765.00	0.4036	67M7G7D	0.2523	67M7W7D
80	3740.01 ~ 3759.99	0.3954	77M4G7D	0.2466	77M5W7D
90	3745.02 ~ 3754.98	0.3963	87M6G7D	0.2466	87M5W7D
100	3750.00 ~ 3750.00	0.4295	97M4G7D	0.2716	97M4W7D

5G NR n77 UL MIMO		QPSK		16QAM / 64QAM / 256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
20	3710.01 ~ 3969.99	0.1366	18M2G7D	0.1194	18M3W7D
30	3715.02 ~ 3964.98	0.1389	27M8G7D	0.1220	27M9W7D
40	3720.00 ~ 3960.00	0.1465	37M9G7D	0.1282	37M9W7D
60	3730.02 ~ 3949.98	0.1536	57M8G7D	0.1333	57M9W7D
80	3740.01 ~ 3939.99	0.1591	77M6G7D	0.1370	77M6W7D
100	3750.00 ~ 3930.00	0.1663	97M6G7D	0.1461	97M5W7D



5G NR n78 UL MIMO		QPSK		16QAM / 64QAM / 256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
20	3710.01 ~ 3789.99	0.1507	18M2G7D	0.1315	18M3W7D
30	3715.02 ~ 3784.98	0.1476	27M8G7D	0.1282	27M9W7D
40	3720.00 ~ 3780.00	0.1505	37M9G7D	0.1237	37M9W7D
50	3725.01 ~ 3774.99	0.1376	47M4G7D	0.1159	47M5W7D
60	3730.02 ~ 3769.98	0.1381	57M8G7D	0.1246	57M9W7D
70	3735.00 ~ 3765.00	0.1432	67M5G7D	0.1247	67M6W7D
80	3740.01 ~ 3759.99	0.1385	77M6G7D	0.1216	77M6W7D
90	3745.02 ~ 3754.98	0.1647	87M6G7D	0.1403	87M7W7D
100	3750.00 ~ 3750.00	0.1419	97M6G7D	0.1516	97M5W7D

Note:

- 5G NR Band n77 overlaps the entire frequency range of Band n78, therefore the conducted test results of n77 provided in this report cover n78 except for Bandwidth of 50/70/90MHz.
- All modulations have been tested, and only the worst test results of PSK & QAM are shown in the report.

1.7 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	TH01-KS	CN1257	314309



Sporton International Inc. (ShenZhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China TEL: +86-755-86066985		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH01-SZ	CN1256	421272

Test data subcontracted: Radiated Spurious Emission test case in section 4 of this report

1.8 Test Software

Item	Site	Manufacture	Name	Version
1.	03CH01-SZ	AUDIX	E3	6.2009-8-24

1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 27
- ♦ ANSI C63.26-2015
- ♦ FCC KDB 971168 D01 Power Meas License Digital Systems v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

All test items were verified and recorded according to the standards and without any deviation during the test.



2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items are performed according to KDB 971168 D01 Power Meas License Digital Systems v03r01 with maximum output power.


For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.

The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.

Orthogonal Planes of EUT	X Plane	Y Plane	Z Plane

Test Items	5G NR	Bandwidth (MHz)										Modulation					RB #		Test Channel		
		10	20	30	40	50	60	70	80	90	100	PI/2 BPSK	QPSK	16QAM	64QAM	256 QAM	1	Full	L	M	H
Max. Output Power	n77	-	v	v	v	-	v	-	v	-	v	v	v	v	v	v	v	v	v	v	v
	n78	-	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v
Peak-to-Average Ratio	n77	-	v			-		-		-		v	v				v	v		v	
	n78	-	v									v	v				v	v		v	
26dB and 99% Bandwidth	n77	-	v	v	v	-	v	-	v	-	v		v	v	v	v		v		v	
	n78	-				v		v		v			v	v	v	v		v		v	
Conducted Band Edge	n77	-	v			-	v	-		-	v	v	v				v	v	v		v
	n78	-				v		v		v		v	v				v	v	v		v
Conducted Spurious Emission	n77	-	v			-	v	-		-	v	v	v				v		v	v	v
	n78	-				v		v		v		v	v				v		v	v	v
Frequency Stability	n77	-	v			-		-		-			v					v		v	
	n78	-	v										v					v		v	
E.I.R.P	n77	-	v	v	v	-	v	-	v	-	v	v	v	v	v	v	v	v	v	v	v
	n78	-	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v
Radiated Spurious Emission	n77	Worst Case																	v	v	v
Note	1. The mark “v” means that this configuration is chosen for testing 2. The mark “-” means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported. 4. Frequency Stability : Normal Voltage = 3.87V ; Low Voltage =3.65V. ; High Voltage =4.45V																				

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	DC Power Supply	GW	GPS-3030D	N/A	N/A	Unshielded, 1.8 m
2.	LTE Base Station	Anritsu	MT8821C	N/A	N/A	Unshielded, 1.8 m
3.	NR Base Station	Anritsu	MT8000A	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 6.5 dB and 20dB attenuator.

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 6.5 + 20 = 26.5 \text{ (dB)} \end{aligned}$$



2.5 Frequency List of Low/Middle/High Channels

5G n77 (30kHz) Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
100	Channel	650000	656000	662000
	Frequency	3750	3840	3930
80	Channel	649334	656000	662666
	Frequency	3740.01	3840	3939.99
60	Channel	648668	656000	663332
	Frequency	3730.02	3840	3949.98
40	Channel	648000	656000	664000
	Frequency	3720	3840	3960
30	Channel	647668	656000	664332
	Frequency	3715.02	3840	3964.98
20	Channel	647334	656000	664666
	Frequency	3710.01	3840	3969.99

5G n78(30kHz) Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
100	Channel	650000		
	Frequency	3750		
90	Channel	649668	650000	650332
	Frequency	3745.02	3750	3754.98
80	Channel	649334	650000	650666
	Frequency	3740.01	3750	3759.99
70	Channel	649000	650000	651000
	Frequency	3735	3750	3765
60	Channel	648668	650000	651332
	Frequency	3730.02	3750	3769.98
50	Channel	648334	650000	651666
	Frequency	3725.01	3750	3774.99
40	Channel	648000	650000	652000
	Frequency	3720	3750	3780
30	Channel	647668	650000	652332
	Frequency	3715.02	3750	3784.98
20	Channel	647334	650000	652666
	Frequency	3710.01	3750	3789.99


3 Conducted Test Items

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.

3.4 Conducted Output Power and EIRP

3.4.1 Description of the Conducted Output Power Measurement and EIRP Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The EIRP of mobile transmitters must not exceed 1 Watts for 5G NR n77, n78.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.

3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

3.6 Occupied Bandwidth

3.6.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

27.53(l)(2)

For mobile operations in the 3700-3980 MHz band, the conducted power of any emission outside the licensee's authorized bandwidth shall not exceed -13 dBm/MHz. Compliance with this paragraph is based on the use of measurement instrumentation employing a resolution bandwidth of 1 megahertz or greater. However, in the 1 megahertz bands immediately outside and adjacent to the licensee's frequency block, the minimum resolution bandwidth for the measurement shall be either one percent of the emission bandwidth of the fundamental emission of the transmitter or 350 kHz. In the bands between 1 and 5 MHz removed from the licensee's frequency block, the minimum resolution bandwidth for the measurement shall be 500 kHz.

3.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set RBW $\geq$ 1% EBW in the 1MHz band immediately outside and adjacent to the band edge.
5. Beyond the 1 MHz band from the band edge, RBW=1MHz was used or a narrower RBW was used (generally limited to no less than 1% of the OBW) and the measured power was integrated over the full required measurement bandwidth.
6. Set spectrum analyzer with RMS detector.
7. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
8. Checked that all the results comply with the emission limit line.

Example:

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$

$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)} = -13\text{dBm}.$$

9. When using the integration method, the starting frequency of the integration shall be centered at one-half of the RBW away from the band edge.

3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
7. Set spectrum analyzer with RMS detector.
8. Taking the record of maximum spurious emission.
9. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
10. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)]$ (dB)
 $= [30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
 $= -13\text{dBm}$.

3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5
2. The EUT was placed in a temperature chamber at $20\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup


4.2.1 For radiated test below 30MHz



4.2.2 For radiated test from 30MHz to 1GHz



4.2.3 For radiated test above 1GHz



4.3 Test Result of Radiated Test

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.

4.4 Radiated Spurious Emission

4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI C63.26. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
6. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
7. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
8. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
9. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
10. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
11. $ERP \text{ (dBm)} = EIRP - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

$= P(W) - [43 + 10\log(P)] \text{ (dB)}$

$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$

$= -13\text{dBm}.$



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 10, 2024	Nov. 17, 2024~ Apr. 23, 2025	Oct. 09, 2025	Conducted (TH01-KS)
Power divider	STI	STI08-0055	-	0.5~40GHz	NCR	Nov. 17, 2024~ Apr. 23, 2025	NCR	Conducted (TH01-KS)
Temperature & humidity chamber	Hongzhan	LP-150U	H201401144 0	-40~+150°C 20%~95%RH	Jul. 04, 2024	Nov. 17, 2024~ Apr. 23, 2025	Jul. 03, 2025	Conducted (TH01-KS)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY5515021 3	10Hz~44GHz	Jul. 03, 2024	Feb. 10, 2025	Jul. 02, 2025	Radiation (03CH01-SZ)
Loop Antenna	R&S	HFH2-Z2E	101141	9kHz~30MHz	Dec. 28, 2024	Feb. 10, 2025	Dec. 27, 2025	Radiation (03CH01-SZ)
HF Amplifier	KEYSIGHT	83017A	MY5327010 5	0.5GHz~26.5GHz	Oct. 14, 2024	Feb. 10, 2025	Oct. 13, 2025	Radiation (03CH01-SZ)
Bilog Antenna	TeseQ	CBL6112D	35407	30MHz~2GHz	Oct. 24, 2023	Feb. 10, 2025	Oct. 23, 2025	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00119436	1GHz~18GHz	Jul. 04, 2024	Feb. 10, 2025	Jul. 03, 2025	Radiation (03CH01-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18GHz~40GHz	Apr. 09, 2024	Feb. 10, 2025	Apr. 08, 2025	Radiation (03CH01-SZ)
LF Amplifier	EM Electronics	EM330	060788	20MHz~3GHz	Dec. 25, 2024	Feb. 10, 2025	Dec. 24, 2025	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	AMF-7D-00 101800-30- 10P-R	1943528	1GHz~18GHz	Oct. 14, 2024	Feb. 10, 2025	Oct. 13, 2025	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	TTA1840-35 -HG	1871923	18GHz~40GHz	Jul. 03, 2024	Feb. 10, 2025	Jul. 02, 2025	Radiation (03CH01-SZ)
AC Power Source	Chroma	61601	6160100019 85	N/A	Oct. 14, 2024	Feb. 10, 2025	Oct. 13, 2025	Radiation (03CH01-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Feb. 10, 2025	NCR	Radiation (03CH01-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Feb. 10, 2025	NCR	Radiation (03CH01-SZ)

NCR: No Calibration Required

6 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Spurious Emission & Bandedge	± 2.22 dB
Occupied Channel Bandwidth	$\pm 0.1\%$
Conducted Power	± 0.50 dB
Peak to Average Ratio	± 0.90 dB
Frequency Stability	± 0.04 ppm

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.48 dB
---	---------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.53 dB
---	---------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.02 dB
---	---------

----- THE END -----



Appendix A. Test Results of Conducted Test

Test Engineer :	Simle Wang	Temperature :	22~23°C
		Relative Humidity :	40~42%



Software Version: 23.06.1602

FR1 N77 Ant.4

Transmitter Conducted Output Power and EIRP, $(G_T - L_c) = -1.2\text{dBi}$

NR Band	SCS	BandWidth	Arfcn	Freq (MHz)	Modulation	RB	Conducted Power(dBm)	EIRP (dBm)	EIRP (W)
77	30	100	650000	3750	DFT-s-OFDM PI/2 BPSK	135@67	27.72	26.52	0.4487
77	30	100	650000	3750	DFT-s-OFDM PI/2 BPSK	1@1	27.15	25.95	0.3936
77	30	100	650000	3750	DFT-s-OFDM PI/2 BPSK	1@271	27.97	26.77	0.4753
77	30	100	650000	3750	DFT-s-OFDM QPSK	135@67	26.63	25.43	0.3491
77	30	100	650000	3750	DFT-s-OFDM QPSK	1@1	26.06	24.86	0.3062
77	30	100	650000	3750	DFT-s-OFDM QPSK	1@271	26.99	25.79	0.3793
77	30	100	650000	3750	DFT-s-OFDM 16 QAM	135@67	25.64	24.44	0.2780
77	30	100	650000	3750	DFT-s-OFDM 16 QAM	1@1	25.03	23.83	0.2415
77	30	100	650000	3750	DFT-s-OFDM 16 QAM	1@271	26.09	24.89	0.3083
77	30	100	650000	3750	DFT-s-OFDM 64 QAM	135@67	24.2	23	0.1995
77	30	100	650000	3750	DFT-s-OFDM 64 QAM	1@1	23.38	22.18	0.1652
77	30	100	650000	3750	DFT-s-OFDM 64 QAM	1@271	24.51	23.31	0.2143
77	30	100	650000	3750	DFT-s-OFDM 256 QAM	135@67	22.68	21.48	0.1406
77	30	100	650000	3750	DFT-s-OFDM 256 QAM	1@1	21.92	20.72	0.1180
77	30	100	650000	3750	DFT-s-OFDM 256 QAM	1@271	23.06	21.86	0.1535
77	30	100	650000	3750	CP-OFDM QPSK	137@68	24.93	23.73	0.2360
77	30	100	650000	3750	CP-OFDM QPSK	1@1	24.45	23.25	0.2113
77	30	100	650000	3750	CP-OFDM QPSK	1@271	25.42	24.22	0.2642
77	30	100	656000	3840	DFT-s-OFDM PI/2 BPSK	135@67	27.18	25.98	0.3963
77	30	100	656000	3840	DFT-s-OFDM PI/2 BPSK	1@1	26.76	25.56	0.3597
77	30	100	656000	3840	DFT-s-OFDM PI/2 BPSK	1@271	26.87	25.67	0.3690
77	30	100	656000	3840	DFT-s-OFDM QPSK	135@67	26.14	24.94	0.3119
77	30	100	656000	3840	DFT-s-OFDM QPSK	1@1	25.69	24.49	0.2812
77	30	100	656000	3840	DFT-s-OFDM QPSK	1@271	25.83	24.63	0.2904
77	30	100	656000	3840	DFT-s-OFDM 16 QAM	135@67	25.14	23.94	0.2477
77	30	100	656000	3840	DFT-s-OFDM 16 QAM	1@1	24.7	23.5	0.2239
77	30	100	656000	3840	DFT-s-OFDM 16 QAM	1@271	24.8	23.6	0.2291
77	30	100	656000	3840	DFT-s-OFDM 64 QAM	135@67	23.67	22.47	0.1766
77	30	100	656000	3840	DFT-s-OFDM 64 QAM	1@1	22.98	21.78	0.1507
77	30	100	656000	3840	DFT-s-OFDM 64 QAM	1@271	23.11	21.91	0.1552
77	30	100	656000	3840	DFT-s-OFDM 256 QAM	135@67	22.15	20.95	0.1245
77	30	100	656000	3840	DFT-s-OFDM 256 QAM	1@1	21.53	20.33	0.1079
77	30	100	656000	3840	DFT-s-OFDM 256 QAM	1@271	21.74	20.54	0.1132
77	30	100	656000	3840	CP-OFDM QPSK	137@68	24.43	23.23	0.2104



NR Band	SCS	BandWidth	Arfcn	Freq (MHz)	Modulation	RB	Conducted Power(dBm)	EIRP (dBm)	EIRP (W)
77	30	100	656000	3840	CP-OFDM QPSK	1@1	24.13	22.93	0.1963
77	30	100	656000	3840	CP-OFDM QPSK	1@271	24.23	23.03	0.2009
77	30	100	662000	3930	DFT-s-OFDM PI/2 BPSK	135@67	26.82	25.62	0.3648
77	30	100	662000	3930	DFT-s-OFDM PI/2 BPSK	1@1	26.82	25.62	0.3648
77	30	100	662000	3930	DFT-s-OFDM PI/2 BPSK	1@271	26.45	25.25	0.3350
77	30	100	662000	3930	DFT-s-OFDM QPSK	135@67	25.77	24.57	0.2864
77	30	100	662000	3930	DFT-s-OFDM QPSK	1@1	25.75	24.55	0.2851
77	30	100	662000	3930	DFT-s-OFDM QPSK	1@271	25.39	24.19	0.2624
77	30	100	662000	3930	DFT-s-OFDM 16 QAM	135@67	24.78	23.58	0.2280
77	30	100	662000	3930	DFT-s-OFDM 16 QAM	1@1	24.77	23.57	0.2275
77	30	100	662000	3930	DFT-s-OFDM 16 QAM	1@271	24.41	23.21	0.2094
77	30	100	662000	3930	DFT-s-OFDM 64 QAM	135@67	23.3	22.1	0.1622
77	30	100	662000	3930	DFT-s-OFDM 64 QAM	1@1	23.14	21.94	0.1563
77	30	100	662000	3930	DFT-s-OFDM 64 QAM	1@271	22.84	21.64	0.1459
77	30	100	662000	3930	DFT-s-OFDM 256 QAM	135@67	21.76	20.56	0.1138
77	30	100	662000	3930	DFT-s-OFDM 256 QAM	1@1	21.62	20.42	0.1102
77	30	100	662000	3930	DFT-s-OFDM 256 QAM	1@271	21.29	20.09	0.1021
77	30	100	662000	3930	CP-OFDM QPSK	137@68	24.06	22.86	0.1932
77	30	100	662000	3930	CP-OFDM QPSK	1@1	24.16	22.96	0.1977
77	30	100	662000	3930	CP-OFDM QPSK	1@271	23.86	22.66	0.1845
77	30	20	647334	3710.01	DFT-s-OFDM PI/2 BPSK	1@1	27.67	26.47	0.4436
77	30	20	647334	3710.01	DFT-s-OFDM QPSK	1@1	26.62	25.42	0.3483
77	30	20	647334	3710.01	DFT-s-OFDM 16 QAM	1@1	25.7	24.5	0.2818
77	30	20	656000	3840	DFT-s-OFDM PI/2 BPSK	1@1	27.26	26.06	0.4036
77	30	20	656000	3840	DFT-s-OFDM QPSK	1@1	26.21	25.01	0.3170
77	30	20	656000	3840	DFT-s-OFDM 16 QAM	1@1	25.23	24.03	0.2529
77	30	20	664666	3969.99	DFT-s-OFDM PI/2 BPSK	1@1	24.57	23.37	0.2173
77	30	20	664666	3969.99	DFT-s-OFDM QPSK	1@1	23.41	22.21	0.1663
77	30	20	664666	3969.99	DFT-s-OFDM 16 QAM	1@1	22.39	21.19	0.1315
77	30	30	647668	3715.02	DFT-s-OFDM PI/2 BPSK	1@1	27.7	26.5	0.4467
77	30	30	647668	3715.02	DFT-s-OFDM QPSK	1@1	26.64	25.44	0.3499
77	30	30	647668	3715.02	DFT-s-OFDM 16 QAM	1@1	25.63	24.43	0.2773
77	30	30	656000	3840	DFT-s-OFDM PI/2 BPSK	1@1	27.23	26.03	0.4009
77	30	30	656000	3840	DFT-s-OFDM QPSK	1@1	26.19	24.99	0.3155
77	30	30	656000	3840	DFT-s-OFDM 16 QAM	1@1	25.2	24	0.2512
77	30	30	664332	3964.98	DFT-s-OFDM PI/2 BPSK	1@1	25.02	23.82	0.2410
77	30	30	664332	3964.98	DFT-s-OFDM QPSK	1@1	23.87	22.67	0.1849
77	30	30	664332	3964.98	DFT-s-OFDM 16 QAM	1@1	22.86	21.66	0.1466
77	30	40	648000	3720	DFT-s-OFDM PI/2 BPSK	1@1	27.52	26.32	0.4285
77	30	40	648000	3720	DFT-s-OFDM QPSK	1@1	26.46	25.26	0.3357



NR Band	SCS	BandWidth	Arfcn	Freq (MHz)	Modulation	RB	Conducted Power(dBm)	EIRP (dBm)	EIRP (W)
77	30	40	648000	3720	DFT-s-OFDM 16 QAM	1@1	25.44	24.24	0.2655
77	30	40	656000	3840	DFT-s-OFDM PI/2 BPSK	1@1	27.19	25.99	0.3972
77	30	40	656000	3840	DFT-s-OFDM QPSK	1@1	26.13	24.93	0.3112
77	30	40	656000	3840	DFT-s-OFDM 16 QAM	1@1	25.09	23.89	0.2449
77	30	40	664000	3960	DFT-s-OFDM PI/2 BPSK	1@1	25.12	23.92	0.2466
77	30	40	664000	3960	DFT-s-OFDM QPSK	1@1	23.98	22.78	0.1897
77	30	40	664000	3960	DFT-s-OFDM 16 QAM	1@1	23.04	21.84	0.1528
77	30	60	648668	3730.02	DFT-s-OFDM PI/2 BPSK	1@1	27.5	26.3	0.4266
77	30	60	648668	3730.02	DFT-s-OFDM QPSK	1@1	26.45	25.25	0.3350
77	30	60	648668	3730.02	DFT-s-OFDM 16 QAM	1@1	25.47	24.27	0.2673
77	30	60	656000	3840	DFT-s-OFDM PI/2 BPSK	1@1	27.09	25.89	0.3882
77	30	60	656000	3840	DFT-s-OFDM QPSK	1@1	26.03	24.83	0.3041
77	30	60	656000	3840	DFT-s-OFDM 16 QAM	1@1	25.05	23.85	0.2427
77	30	60	663332	3949.98	DFT-s-OFDM PI/2 BPSK	1@1	26.51	25.31	0.3396
77	30	60	663332	3949.98	DFT-s-OFDM QPSK	1@1	25.4	24.2	0.2630
77	30	60	663332	3949.98	DFT-s-OFDM 16 QAM	1@1	24.47	23.27	0.2123
77	30	80	649334	3740.01	DFT-s-OFDM PI/2 BPSK	1@1	27.41	26.21	0.4178
77	30	80	649334	3740.01	DFT-s-OFDM QPSK	1@1	26.35	25.15	0.3273
77	30	80	649334	3740.01	DFT-s-OFDM 16 QAM	1@1	25.36	24.16	0.2606
77	30	80	656000	3500.01	DFT-s-OFDM PI/2 BPSK	1@1	27.01	25.81	0.3811
77	30	80	656000	3840	DFT-s-OFDM QPSK	1@1	26.17	24.97	0.3141
77	30	80	656000	3840	DFT-s-OFDM 16 QAM	1@1	25.22	24.02	0.2523
77	30	80	662666	3939.99	DFT-s-OFDM PI/2 BPSK	1@1	26.9	25.7	0.3715
77	30	80	662666	3939.99	DFT-s-OFDM QPSK	1@1	25.93	24.73	0.2972
77	30	80	662666	3939.99	DFT-s-OFDM 16 QAM	1@1	24.94	23.74	0.2366

**Frequency Stability**

NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Deviation (ppm)	Verdict	Environment
77	30	20	656000	3840.0	DFT-s-OFDM PI/2 BPSK	50@0	0.0016	PASS	NV
77	30	20	656000	3840.0	DFT-s-OFDM PI/2 BPSK	50@0	0.0012	PASS	LV
77	30	20	656000	3840.0	DFT-s-OFDM PI/2 BPSK	50@0	0.0027	PASS	HV
77	30	20	656000	3840.0	DFT-s-OFDM PI/2 BPSK	50@0	0.0021	PASS	-30°C
77	30	20	656000	3840.0	DFT-s-OFDM PI/2 BPSK	50@0	-0.0015	PASS	-20°C
77	30	20	656000	3840.0	DFT-s-OFDM PI/2 BPSK	50@0	0.0037	PASS	-10°C
77	30	20	656000	3840.0	DFT-s-OFDM PI/2 BPSK	50@0	-0.0042	PASS	0°C
77	30	20	656000	3840.0	DFT-s-OFDM PI/2 BPSK	50@0	0.0012	PASS	10°C
77	30	20	656000	3840.0	DFT-s-OFDM PI/2 BPSK	50@0	0.0025	PASS	20°C
77	30	20	656000	3840.0	DFT-s-OFDM PI/2 BPSK	50@0	0.0029	PASS	30°C
77	30	20	656000	3840.0	DFT-s-OFDM PI/2 BPSK	50@0	-0.0019	PASS	40°C
77	30	20	656000	3840.0	DFT-s-OFDM PI/2 BPSK	50@0	0.0011	PASS	50°C

**Peak to Average Ratio**

NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Result (dB)	Limit (dB)	Verdict
77	30	20	656000	3840.0	DFT-s-OFDM PI/2 BPSK	50@0	4.09	13	PASS
77	30	20	656000	3840.0	DFT-s-OFDM PI/2 BPSK	1@0	4.39	13	PASS
77	30	20	656000	3840.0	DFT-s-OFDM QPSK	50@0	5.16	13	PASS
77	30	20	656000	3840.0	DFT-s-OFDM QPSK	1@0	5.46	13	PASS

N77(20M)_DFT-s-OFDM_PI_2-
BPSK_Outer_Full_Mid_CH




N77(20M)_DFT-s-OFDM_PI_2-
BPSK_Edge_1RB_Left_Mid_CH



N77(20M)_DFT-s-
OFDM_QPSK_Outer_Full_Mid_CH



N77(20M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Mid_CH




**Occupied Bandwidth**


NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	OBW (MHz)	26dB BW (MHz)
77	30	20	656000	3840.0	CP-OFDM QPSK	51@0	18.212	19.69
77	30	20	656000	3840.0	CP-OFDM 16 QAM	51@0	18.118	19.04
77	30	20	656000	3840.0	CP-OFDM 64 QAM	51@0	18.163	19.39
77	30	20	656000	3840.0	CP-OFDM 256 QAM	51@0	18.181	18.96
77	30	30	656000	3840.0	CP-OFDM QPSK	78@0	27.794	29.77
77	30	30	656000	3840.0	CP-OFDM 16 QAM	78@0	27.822	29.58
77	30	30	656000	3840.0	CP-OFDM 64 QAM	78@0	27.813	29.13
77	30	30	656000	3840.0	CP-OFDM 256 QAM	78@0	27.869	29.25
77	30	40	656000	3840.0	CP-OFDM QPSK	106@0	37.802	39.61
77	30	40	656000	3840.0	CP-OFDM 16 QAM	106@0	37.832	39.76
77	30	40	656000	3840.0	CP-OFDM 64 QAM	106@0	37.907	39.4
77	30	40	656000	3840.0	CP-OFDM 256 QAM	106@0	37.87	39.41
77	30	60	656000	3840.0	CP-OFDM QPSK	162@0	57.699	59.67
77	30	60	656000	3840.0	CP-OFDM 16 QAM	162@0	57.775	59.67
77	30	60	656000	3840.0	CP-OFDM 64 QAM	162@0	57.784	59.67
77	30	60	656000	3840.0	CP-OFDM 256 QAM	162@0	57.668	59.82
77	30	80	656000	3840.0	CP-OFDM QPSK	217@0	77.434	80.04
77	30	80	656000	3840.0	CP-OFDM 16 QAM	217@0	77.439	80.01
77	30	80	656000	3840.0	CP-OFDM 64 QAM	217@0	77.536	79.96
77	30	80	656000	3840.0	CP-OFDM 256 QAM	217@0	77.331	79.87
77	30	100	656000	3840.0	CP-OFDM QPSK	273@0	97.421	100.8
77	30	100	656000	3840.0	CP-OFDM 16 QAM	273@0	97.342	100.6
77	30	100	656000	3840.0	CP-OFDM 64 QAM	273@0	97.375	100.4
77	30	100	656000	3840.0	CP-OFDM 256 QAM	273@0	97.398	100.7




N77(20M)_CP-
OFDM_QPSK_Outer_Full_Mid_CH




N77(20M)_CP-OFDM_16
QAM_Outer_Full_Mid_CH



N77(20M)_CP-OFDM_64
QAM_Outer_Full_Mid_CH




N77(20M)_CP-OFDM_256
QAM_Outer_Full_Mid_CH





N77(30M)_CP-
OFDM_QPSK_Outer_Full_Mid_CH




N77(30M)_CP-OFDM_16
QAM_Outer_Full_Mid_CH



N77(30M)_CP-OFDM_64
QAM_Outer_Full_Mid_CH




N77(30M)_CP-OFDM_256
QAM_Outer_Full_Mid_CH







N77(40M)_CP-
OFDM_QPSK_Outer_Full_Mid_CH




N77(40M)_CP-OFDM_16
QAM_Outer_Full_Mid_CH



N77(40M)_CP-OFDM_64
QAM_Outer_Full_Mid_CH




N77(40M)_CP-OFDM_256
QAM_Outer_Full_Mid_CH







N77(60M)_CP-
OFDM_QPSK_Outer_Full_Mid_CH




N77(60M)_CP-OFDM_16
QAM_Outer_Full_Mid_CH



N77(60M)_CP-OFDM_64
QAM_Outer_Full_Mid_CH




N77(60M)_CP-OFDM_256
QAM_Outer_Full_Mid_CH







N77(80M)_CP-
OFDM_QPSK_Outer_Full_Mid_CH




N77(80M)_CP-OFDM_16
QAM_Outer_Full_Mid_CH



N77(80M)_CP-OFDM_64
QAM_Outer_Full_Mid_CH




N77(80M)_CP-OFDM_256
QAM_Outer_Full_Mid_CH







N77(100M)_CP-
OFDM_QPSK_Outer_Full_Mid_CH




N77(100M)_CP-OFDM_16
QAM_Outer_Full_Mid_CH



N77(100M)_CP-OFDM_64
QAM_Outer_Full_Mid_CH



N77(100M)_CP-OFDM_256
QAM_Outer_Full_Mid_CH



Conducted Spurious Emissions

NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Result	Verdict
77	30	20	647334	3710.01	DFT-s-OFDM BPSK	1@0	see graph	---
77	30	20	647334	3710.01	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	20	647334	3710.01	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	20	647334	3710.01	DFT-s-OFDM QPSK	1@0	see graph	---
77	30	20	647334	3710.01	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	20	647334	3710.01	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	20	656000	3840.0	DFT-s-OFDM BPSK	1@0	see graph	---
77	30	20	656000	3840.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	20	656000	3840.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	20	656000	3840.0	DFT-s-OFDM QPSK	1@0	see graph	---
77	30	20	656000	3840.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	20	656000	3840.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	20	664666	3969.99	DFT-s-OFDM BPSK	1@0	see graph	---
77	30	20	664666	3969.99	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	20	664666	3969.99	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	20	664666	3969.99	DFT-s-OFDM QPSK	1@0	see graph	---
77	30	20	664666	3969.99	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	20	664666	3969.99	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	60	648668	3730.02	DFT-s-OFDM BPSK	1@0	see graph	---
77	30	60	648668	3730.02	DFT-s-OFDM BPSK	1@0	see graph	PASS




77	30	60	648668	3730.02	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	60	648668	3730.02	DFT-s-OFDM QPSK	1@0	see graph	---
77	30	60	648668	3730.02	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	60	648668	3730.02	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	60	656000	3840.0	DFT-s-OFDM BPSK	1@0	see graph	---
77	30	60	656000	3840.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	60	656000	3840.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	60	656000	3840.0	DFT-s-OFDM QPSK	1@0	see graph	---
77	30	60	656000	3840.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	60	656000	3840.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	60	656000	3840.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	60	663332	3949.98	DFT-s-OFDM BPSK	1@0	see graph	---
77	30	60	663332	3949.98	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	60	663332	3949.98	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	60	663332	3949.98	DFT-s-OFDM QPSK	1@0	see graph	---
77	30	60	663332	3949.98	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	60	663332	3949.98	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	100	650000	3750.0	DFT-s-OFDM BPSK	1@0	see graph	---
77	30	100	650000	3750.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	100	650000	3750.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	100	650000	3750.0	DFT-s-OFDM QPSK	1@0	see graph	---
77	30	100	650000	3750.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	100	650000	3750.0	DFT-s-OFDM QPSK	1@0	see graph	PASS




77	30	100	656000	3840.0	DFT-s-OFDM BPSK	1@0	see graph	---
77	30	100	656000	3840.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	100	656000	3840.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	100	656000	3840.0	DFT-s-OFDM QPSK	1@0	see graph	---
77	30	100	656000	3840.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	100	656000	3840.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	100	662000	3930.0	DFT-s-OFDM BPSK	1@0	see graph	---
77	30	100	662000	3930.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	100	662000	3930.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	100	662000	3930.0	DFT-s-OFDM QPSK	1@0	see graph	---
77	30	100	662000	3930.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	100	662000	3930.0	DFT-s-OFDM QPSK	1@0	see graph	PASS




N77(20M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Low_CH




N77(20M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Low_CH



N77(20M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Low_CH




N77(20M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Low_CH







N77(20M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Mid_CH




N77(20M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Mid_CH



N77(20M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Mid_CH




N77(20M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Mid_CH







N77(20M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_High_CH




N77(20M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_High_CH



N77(20M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_High_CH




N77(20M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_High_CH







N77(60M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Low_CH




N77(60M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Low_CH



N77(60M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Low_CH




N77(60M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Low_CH







N77(60M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Mid_CH




N77(60M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Mid_CH



N77(60M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Mid_CH




N77(60M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Mid_CH







N77(60M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_High_CH




N77(60M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_High_CH



N77(60M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_High_CH




N77(60M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_High_CH







N77(100M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Low_CH




N77(100M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Low_CH



N77(100M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Low_CH




N77(100M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Low_CH







N77(100M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Mid_CH




N77(100M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Mid_CH



N77(100M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Mid_CH




N77(100M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Mid_CH







N77(100M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_High_CH




N77(100M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_High_CH



N77(100M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_High_CH



N77(100M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_High_CH



**Conducted Band Edge**


NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Result	Verdict
77	30	20	647334	3710.01	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	20	647334	3710.01	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	20	647334	3710.01	DFT-s-OFDM BPSK	50@0	see graph	PASS
77	30	20	647334	3710.01	DFT-s-OFDM QPSK	50@0	see graph	PASS
77	30	20	664666	3969.99	DFT-s-OFDM BPSK	1@50	see graph	PASS
77	30	20	664666	3969.99	DFT-s-OFDM QPSK	1@50	see graph	PASS
77	30	20	664666	3969.99	DFT-s-OFDM BPSK	50@0	see graph	PASS
77	30	20	664666	3969.99	DFT-s-OFDM QPSK	50@0	see graph	PASS
77	30	60	648668	3730.02	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	60	648668	3730.02	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	60	648668	3730.02	DFT-s-OFDM BPSK	162@0	see graph	PASS
77	30	60	648668	3730.02	DFT-s-OFDM QPSK	162@0	see graph	PASS
77	30	60	663332	3949.98	DFT-s-OFDM BPSK	1@161	see graph	PASS
77	30	60	663332	3949.98	DFT-s-OFDM QPSK	1@161	see graph	PASS
77	30	60	663332	3949.98	DFT-s-OFDM BPSK	162@0	see graph	PASS
77	30	60	663332	3949.98	DFT-s-OFDM QPSK	162@0	see graph	PASS
77	30	100	650000	3750.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
77	30	100	650000	3750.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
77	30	100	650000	3750.0	DFT-s-OFDM BPSK	270@0	see graph	PASS
77	30	100	650000	3750.0	DFT-s-OFDM QPSK	270@0	see graph	PASS
77	30	100	662000	3930.0	DFT-s-OFDM	1@272	see graph	PASS




BPSK								
77	30	100	662000	3930.0	DFT-s-OFDM QPSK	1@272	see graph	PASS
77	30	100	662000	3930.0	DFT-s-OFDM BPSK	270@0	see graph	PASS
77	30	100	662000	3930.0	DFT-s-OFDM QPSK	270@0	see graph	PASS




N77(20M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Low_CH




N77(20M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Low_CH



N77(20M)_DFT-s-
OFDM_BPSK_Outer_Full_Low_CH




N77(20M)_DFT-s-
OFDM_QPSK_Outer_Full_Low_CH







N77(20M)_DFT-s-
OFDM_BPSK_Edge_1RB_Right_High_CH




N77(20M)_DFT-s-
OFDM_QPSK_Edge_1RB_Right_High_CH



N77(20M)_DFT-s-
OFDM_BPSK_Outer_Full_High_CH




N77(20M)_DFT-s-
OFDM_QPSK_Outer_Full_High_CH







N77(60M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Low_CH




N77(60M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Low_CH



N77(60M)_DFT-s-
OFDM_BPSK_Outer_Full_Low_CH




N77(60M)_DFT-s-
OFDM_QPSK_Outer_Full_Low_CH







N77(60M)_DFT-s-
OFDM_BPSK_Edge_1RB_Right_High_CH




N77(60M)_DFT-s-
OFDM_QPSK_Edge_1RB_Right_High_CH



N77(60M)_DFT-s-
OFDM_BPSK_Outer_Full_High_CH




N77(60M)_DFT-s-
OFDM_QPSK_Outer_Full_High_CH







N77(100M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Low_CH




N77(100M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Low_CH



N77(100M)_DFT-s-
OFDM_BPSK_Outer_Full_Low_CH




N77(100M)_DFT-s-
OFDM_QPSK_Outer_Full_Low_CH







N77(100M)_DFT-s-
OFDM_BPSK_Edge_1RB_Right_High_CH



N77(100M)_DFT-s-
OFDM_QPSK_Edge_1RB_Right_High_CH



N77(100M)_DFT-s-
OFDM_BPSK_Outer_Full_High_CH



N77(100M)_DFT-s-
OFDM_QPSK_Outer_Full_High_CH

