

SGS-CSTC Standards Technical Services Co., Ltd.

No. 1 Workshop, M-10, Middle Section, Science & Technology Park,

District Shenzhen, China 518057

Telephone: +86 (0) 755 2601 2053 Fax: +86 (0) 755 2671 0594

Email: sgs_internet_operations@sgs.com

Page: 1 of 1

FCC ID: WYQ-BT-860509

RF Exposure Statement

1. Standard Applicable

According to 1.1307 (b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

This is a portable device.

2. Measurement Result:

This is a portable device and the max peak output power is 47mW, the power is less than limit whose held to face more than 2.5cm. The device's antenna is away from head more than 2.5cm.

Table 1 - SAR Evaluation Power Thresholds for PTT devices, $f \le 0.5$ GHz

Exposure Conditions	\mathbf{mW}
Held to face ≥ 2.5 cm	250
Body-worn ≥ 1.5 cm	200
Body-worn ≥ 1.0 cm	150
Notes:	

The SAR/MPE measurement is not necessary.

"This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at www.sgs.com/terms and conditions.htm and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at www.sgs.com/terms e-document.htm. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.'

^{1.} The time-averaged output power, corresponding to the required PTT duty factor, is compared with these thresholds.

^{2.} The closest distance between the user and the device or its antenna is used to determine the power thresholds.