



■ Report No.: DDT-R22041207-3E04

■ Issued Date: Sep. 15, 2022

RF EXPOSURE REPORT

FOR

Applicant	:	Specialthing International Co, Ltd
Address	:	Unit 7, 7/F, Block A, Veristrong Ind. Centre, 34-36 Au Pui Wan Street, Fotan, Shatin, Hong Kong
Equipment under Test	:	Bluetooth Dongle
Model No.	:	DGL-A501
Trade Mark	:	NSPG, Dr. Owl, Sports, Ear
FCC ID	:	WYQDGL01
Manufacturer	:	Specialthing International Co, Ltd
Address	:	Unit 7, 7/F, Block A, Veristrong Ind. Centre, 34-36 Au Pui Wan Street, Fotan, Shatin, Hong Kong

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park,
Dongguan City, Guangdong Province, China, 523808

Tel.: +86-0769-38826678, **E-mail:** ddt@dgddt.com, <http://www.dgddt.com>

REPORT

Table of Contents

Test report declares.....	3
1. General Information	5
1.1. Description of equipment	5
1.2. Assess laboratory.....	5
2. RF Exposure evaluation for FCC	5

Test Report Declare

Applicant	:	Specialthing International Co, Ltd
Address	:	Unit 7, 7/F, Block A, Veristrong Ind. Centre, 34-36 Au Pui Wan Street, Fotan, Shatin, Hong Kong
Equipment under Test	:	Bluetooth Dongle
Model No.	:	DGL-A501
Trade mark	:	SPG, Dr. Owl, Sports, Ear
Manufacturer	:	Specialthing International Co, Ltd
Address	:	Unit 7, 7/F, Block A, Veristrong Ind. Centre, 34-36 Au Pui Wan Street, Fotan, Shatin, Hong Kong

Standard Used: KDB447498 D01 General RF Exposure Guidance v06

We Declare:

The equipment described above is assessed by Dongguan Dongdian Testing Service Co., Ltd. and in the configuration assessed the equipment complied with the standards specified above. The assessed results are contained in this report and Dongguan Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these assess.

After evaluation, our opinion is that the equipment In Accordance with above standard.

Report No:	DDT-R22041207-3E04		
Date of Receipt:	Aug. 18, 2022	Date of Test:	Aug. 18, 2022 ~ Sep. 15, 2022

Prepared By:

Johnny Wang

Johnny Wang/Engineer

Approved By:



Damon Hu/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

Revision History

Rev.	Revisions	Issue Date	Revised By
---	Initial issue	Sep. 15, 2022	

1. General Information

1.1. Description of equipment

EUT* Name	:	Bluetooth Dongle
Model Number	:	DGL-A501
EUT Function Description	:	Please reference user manual of this device
Power Supply	:	DC 3.7V from battery or external adapter
Radio Specification	:	Bluetooth V5.0
Operation Frequency	:	2402 MHz - 2480 MHz
Modulation	:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Data Rate	:	1 Mbps, 2 Mbps, 3 Mbps
Antenna Gain	:	Maximum PK gain: 1.32 dBi
Sample Type	:	Series production
Sample Number	:	S22041207-05 for conductive S22041207-06 for radiation

1.2. Assess laboratory

Dongguan Dongdian Testing Service Co., Ltd.

Add.: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, G-20118

2. RF Exposure evaluation for FCC

According to 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where:}$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

Manufacturing Tolerance**BT**

GFSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	6	6	6
Tolerance \pm (dB)	1.5	1.5	1.5
$\pi/4$ DQPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	8	8	8
Tolerance \pm (dB)	1.5	1.5	1.5
8DPSK (Peak)			
Channel	Channel 0	Channel 39	Channel 78
Target (dBm)	8	8	8
Tolerance \pm (dB)	1.5	1.5	1.5

Estimation Result

Worse case is as below: [2480 MHz, 9.5 dBm, (8.9125 mW) output power]

$$(8.9125 / 5) \cdot [\sqrt{2.480(\text{GHz})}] = 2.81 < 3.0 \text{ for 1-g SAR}$$

Then SAR evaluation is not required.

END OF REPORT